INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 51, NO. 12 **DECEMBER 21, 1968**

AUTHOR INDEX TO THE JOURNAL

The number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Adelsberg, L. M., and Cadoff, L. H. Chemical diffusion and phase equilibria in the vanadium-carbon system above 1900°C, (4) 213–20.
Allen, A. W. See Forlano, R. J.
Allen, W. C. The series $MgCr_2O_4$-$MgFe_2O_4$, (9) 485–90.
Ampian, S. G. X-ray and optical crystallographic data for $NaZrO_3$, (10) 607–608.
Ampian, S. G., and Myklebust, R. L. Solid state synthesis of Na_2ZrSiO_5, (10) 605–607.
Anderson, R. C. See Dickson, R. W.
Angell, C. A. Oxide glasses in light of the "ideal glass" concept: I, Ideal and nonideal transitions, and departures from ideality, (3) 117–24; II, Interpretations by reference to simple ionic glass behavior, (3) 125–34.
Archer, J. R., Moody, W. E., and Stanford, A. L., Jr. Third-order elastic constant c_{111} in lithium fluoride, (10) 603–604.
Arlett, R. H. Growth of $ZnRh_2O_4$ single crystals, (5) 292–93.
Armstrong, A. M. See Chaklader, A. C. D.
Aronson, S. See Salzano, F. J.
Aykan, Kamran. A novel lead titanate, $PbTi_3O_7$, (10) 577–82.

Babcock, C. L. Substructures in silicate glasses, (3) 163–69.
Bacmann, J. J., and Cizeron, G. Dorn method in the study of initial phase of uranium dioxide sintering, (4) 209–12; a reply, (12) 724.
Baird, D. H. See Natansohn, S.
Bannister, M. J. Equivalence of X-ray and electron microscopy crystallite sizes in thoria gel, (4) 228–29; Shape sensitivity of initial sintering equations, (10) 548–53.
Barber, D. J., and Tighe, N. J. Neutron damage in single crystal aluminum oxide, (11) 611–17.
Barsom, J. M. Fracture of tempered glass, (2) 75–78.
Bartlett, R. W. Elastic modulus of β-silicon carbide whiskers, (2) 114–15.
Beals, R. J. See Forlano, R. J.; White, D. E.
Benecki, W. T., and Hummel, F. A. High-temperature mechanical properties of ceramic materials: V, $(Zr_{0.6}Mg_{0.4})_2SiO_4$, (4) 220–23.
Berard, M. F., Wirkus, C. D., and Wilder, D. R. Diffusion of oxygen in selected monocrystalline rare earth oxides, (11) 643–47.
Bergeron, C. G. See Laird, J. A.; Ricker, J. M.
Bhide, V. G., Hegde, M. S., and Deshmukh, K. G. Ferroelectric properties of lead titanate, (10) 565–68.
Blickensderfer, Robert. See Henry, J. L.
Bopp, H. F. See Duke, D. A.
Borom, M. P., and Pask, J. A. Kinetics of dissolution and diffusion of the oxides of iron in sodium disilicate glass, (9) 490–98.
Bradley, F. N. Diffraction line shifts observed in fine-grained barium titanate, (5) 293–94; Effect of grain size on discoloration of barium titanate powder, (9) 537.
Bransky, I., and Hed, A. Z. Thermogravimetric determination of the composition-oxygen partial pressure diagram of wustite ($Fe_{1-y}O$), (4) 231–32.
Bratton, R. J., and Ho, S. M. $MgAl_2O_4$ fibers and platelets, (1) 56–57.
Bredig, M. A. Further comment on the phase diagram of Ca_2SiO_4 (and of $CaCl_2$), (6) 354.
Brennan, J. J., and Pask, J. A. Effect of nature of surfaces on wetting of sapphire by liquid aluminum, (10) 569–73.
Brower, W. S., Jr. See Wachtman, J. B., Jr.
Bruki, C. E. See Rudy, Erwin.
Buchanan, R. C., and Zuegel, M. A. Electrical properties of glasses in the system PbO-Al_2O_3-B_2O_3-SiO_2, (1) 28–32.
Budke, Jürgen. Thermal etching of NaCl cleavage faces in vacuum, (4) 238.
Budworth, D. W. Comments on "Observations on pressure sintering of NaCl and other ionic materials," (12) 722.

Cadoff, L. H. See Adelsberg, L. M.
Carnahan, R. D. Elastic properties of silicon carbide, (4) 223–24.
Chaklader, A. C. D., Armstrong, A. M., and Misra, S. K. Interface reactions between metals and ceramics: IV, Wetting of sapphire by liquid copper-oxygen alloys, (11) 630–33.
Chang, L. L. Y. Melting relation in the system TiO_2-WO_3, (5) 295; see also Hill, V. G.
Charles, R. J., and Wagstaff, F. E. Metastable immiscibility in the B_2O_3-SiO_2 system, (1) 16–20.
Chase, A. B. Habit changes and growth mechanisms of In_2O_3 grown from PbO-B_2O_3 melts, (9) 507–10.
Chay, D. M., Palmour, Hayne III, and Kriegel, W. W. Microstructure and room-temperature mechanical properties of hot-pressed magnesium aluminate as described by quadratic multivariable analysis, (1) 10–16.
Christman, R. P. See Elleman, T. S.
Cizeron, G. See Bacmann, J. J.
Coble, R. L. See Francis, T. L.; Gupta, T. K.; Mistler, R. E.; Roy, S. K.
Cole, W. F., and Crook, D. N. High-temperature reactions of clay mineral mixtures and their ceramic properties: IV, Dimensional and weight changes on refiring and the pore-size distribution of fired kaolinite-muscovite-quartz mixtures with 25 wt% quartz, (2) 79–84.
Conway, J. B. See Hein, R. A.
Cook, R. L. See Harris, N. H.
Cook, W. R., Jr. Structure of δ-Fe_2O_3 (hydrate) as proposed by Okamoto, (7) 408; the CdS-MnS and CdSe-MnSe phase diagrams, (9) 518–20.
Cooper, A. R., and Varshneya, A. K. Diffusion in the system K_2O-SrO-SiO_2: I, Effective binary diffusion coefficients, (2) 103–106.
Copley, G. J. Electrical polarization during internal friction measurements in alkali silicate glass, (11) 667–68.
Cronan, C. J. See diBenedetto, B.
Crook, D. N. See Cole, W. F.
Cucka, Paul, and Oliva, R. F. X-ray measurement of strain in quartz particles of whiteware bodies, (8) 458–64.
Cullen, G. V. See Hensler, J. H.
Cutler, I. B. See Keski, J. R.; Petersen, R. O.
Cutler, I. B., and Henrichsen, R. E. Effect of particle shape on the kinetics of sintering of glass, (10) 604.

Datta, R. K., and Roy, Rustum. Reinvestigation of order-disorder in gallate spinels, (5) 297–98.
Deshmukh, K. G. See Bhide, V. G.
Desjardins, Michel, and Williams, J. P. Comparison of surface and bulk glass composition with the spark source mass spectrometer, (5) 296–97.
DeVries, R. C. and Jugle, D. B. Structure-property relation in flexible sandstone, (7) 387–90.
DeVries, R. C., and Roth, W. L. High-pressure synthesis of $PbCrO_3$, (2) 72–75; correction, (5) 298.
diBenedetto, B., and Cronan, C. J. Single crystals of (Pb_xSr_{1-x}) TiO_3 grown by traveling heater method, (7) 364–68.
Dickson, R. W., and Anderson, R. C. Temperature dependence of the elastic moduli of 91 Y_2O_3 + 9 ThO_2 from 25° to 1100°C, (4) 233–34.
Doi, K. See Livage, J.
Domagala, R. F. See Ruh, Robert.
Duffy, J. A., and Ingram, M. D. Environment of cobalt(II) in nitrate glass, (9) 544.
Duke, D. A., Megles, J. E., Jr., MacDowell, J. F., and Bopp, H. F. Strengthening glass-ceramics by application of compressive glazes, (2) 98–102.
Dungan, R. H. Thermodynamic relations between composition and ferroelectric-to-antiferroelectric phase transitions, (10) 609–10.

Eagan, R. J. See Ricker, J. M.
Elleman, T. S., Mears, L. D., and Christman, R. P. Rare gas diffusion in cesium iodide: use of fission recoil doping techniques, (10) 560–64.
Ernsberger, F. M. Role of densification in deformation of glasses under point loading, (10) 545–47.

Farabaugh, E. N. See Wachtman, J. B., Jr.
Farkas, M. S. See Stellrecht, D. E.
Feigelson, Robert. Flux growth of type RVO_4 rare-earth vanadate crystals, (9) 538–39.
Ficalora, P. J., Uy, O. M., Muenow, D. W., and Margrave, J. L. Mass spectrometric studies at high temperatures: XXIX, Thermal decomposition and sublimation of alkali metal sulfates, (10) 574–77.
Field, M. B., and Redwine, R. H. Empirical determination of background in internal friction studies, (2) 112–13.
Fine, M. E. See Wirtz, G. P.
Fischer, G. R. See Ostertag, W.
Fiagella, P. N. See Hein, R. A.
Flood, H., and Knapp, W. J. Structural characteristics of liquid mixtures of feldspar and silica, (5) 259–63.
Forlano, R. J., Allen, A. W., and Beals, R. J. Elasticity and anelasticity of uranium oxides at room temperature: II, Hyperstoichiometric oxides, (4) 192–95.
Foster, P. A., Jr. Melting point of cryolite, (2) 107–109.
Foster, W. R. Comment on the Ca_2SiO_4 phase diagram, (6) 353–54.
Francis, T. L., and Coble, R. L. Creep of polycrystalline silicon carbide, (2) 115–16.
Freiman, S. W., and Hench, L. L. Kinetics of crystallization in Li_2O-SiO_2 glasses, (7) 382–87.
Frischat, G. H. Sodium diffusion in SiO_2 glass, (9) 528–30.
Fukunaga, Osamu, and Saito, Shinroku. Phase equilibrium in the system CrO_2-Cr_2O_3, (7) 362–63.
Fulrath, R. M. See Stett, M. A.
Fuschillo, N. See Gimpl, M. L.

Gagne, R. See Sieger, J. S.
Garrett, H. J. See Ruh, Robert.
Garvie, R. C. The cubic field in the system CaO-ZrO_2, (10) 553–56.
Gdula, R. A. High-field losses of adulterated lead zirconate-titanate piezoelectric ceramics, (12) 683–87.
Gejyo, Tetsuo. See Minagawa, Shigekazu.
Geschwind, Gary. Low-temperature electrical conductivity in calcium-doped lithium fluoride, (9) 539–40.
Gibbon, C. F. Technique for measuring grain boundary mobility and its application to potassium chloride, (5) 273–76; Grain boundary energies in NaCl in the rigid lattice approximation, (5) 276–77.
Gifkins, R. C. Diffusional creep mechanisms, (2) 69–72.
Gimpl, M. L., McMaster, A. D., and Fuschillo, N. Influence of orientation on properties of grain boundaries in NaCl, (11) 655–70.
Glasser, F. L. See Roeder, P. L.
Glasser, L. S. D., and Mileson, J. S. Crystal data for $NaCa_2Si_2O_6$, (1) 55.
Gordon, R. S. See Kent, R. C.
Goswami, A. K. Contribution of grain boundary to optical dielectric constant of barium titanate, (10) 609; Absolute reflective spectra of ceramic barium titanate, (11) 666.
Grabmaier, J. G., and Watson, B. Chr. Czochralski growth of magnesium-aluminum spinel, (6) 355–56.
Greskovich, C., and Stubican, V. S. Coherent precipitation in the system MgO-Al_2O_3-Cr_2O_3, (1) 42–46.
Gross, G. E. See Gutshall, P. L.

Grossman, L. N., and Kaznoff, A. I. Determination of enthalpy of fusion of uranium dioxide, (1) 59–60.
Groves, G. W. See Shockey, D. A.
Gruver, R. M., and Kirchner, H. P. Residual stress and flexural strength of thermally conditioned 96% alumina rods, (4) 232–33; see also Kirchner, H. P.
Guggenheim, H. J. See MacChesney, J. B.
Gulden, T. D. Deposition and microstructure of vapor-deposited silicon carbide, (8) 424–27.
Gupta, T. K., and Coble, R. L. Sintering of ZnO: I, Densification and grain growth, (9) 521–25; II, Density decrease and pore growth during the final stage of the process, (9) 525–28.
Gutshall, P. L., and Gross, G. E. Fracture energy of polycrystalline beryllium oxide, (10) 602.

Hahn, S. J. See Kent, R. C.
Hang, K. W. See Tennery, V. J.
Harker, R. I. See Hill, V. G.
Harris, J. R., and Rossington, D. R. Comparison of surface states of quartz, cristobalite, and silicic acid, (9) 511–18.
Harris, N. H., and Cook, R. L. Formation mechanism of $PbTiO_3$, (4) 230.
Heckel, R. W., and Youngblood, J. L. X-ray line broadening study of explosively shocked MgO and α-Al_2O_3 powders, (7) 398–401.
Hed, A. Z. See Bransky, I.
Hegde, M. S. See Bhide, V. G.
Hein, R. A., Flagella, P. N., and Conway, J. B. High-temperature enthalpy and heat of fusion of UO_2, (5) 291–92.
Hench, L. L. See Freiman, S. W.; Kinser, D. L.
Henrichsen, R. E. See Cutler, I. B.
Henry, J. L., Blickensderfer, Robert, and Thompson, G. G. Quaternary system U-C-O-N at 1700°C: phase relations in the low-nitrogen region, (11) 617–21.
Hensler, J. H., and Cullen, G. V. Shape of the compression creep curve for magnesium oxide, (3) 178–79; Stress, temperature, and strain rate in creep of magnesium oxide, (10) 557–59.
Hickman, B. S., Rotsey, W. B., Hilditch, R. J., and Veevers, K. Effects of irradiation on beryllia-based fuels, (2) 63–69.
Hilditch, W. B. See Hickman, B. S.
Hill, V. G., Chang, L. L. Y., and Harker, R. I. Subsolidus stability relations in the system $KTaO_3$-$KNbO_3$, (12) 723–24.
Ho, S. M. See Bratton, R. J.
Hornstra, J. See Roeder, E.
Hummel, F. A. See Benecki, W. T.; Johnson, D. W.; Martinek, Charles; Nath, D. K.; and Tressler, R. E.
Hunter, Orville, Jr. See Manning, W. R.

Ingraham, A. See Salzano, F. J.
Ingram, M. D. See Duffy, J. A.
Inouye, H., and Leitnaker, J. M. Equilibrium nitrogen pressures and thermodynamic properties of UN, (1) 6–9.
Ip, J. See Murthy, M. K.
Iyengar, Leela. See Rao, K. V. K.

Jaeger, R. E. Influence of OH^- concentration and irradiation on low-temperature dielectric loss in silica glass, (1) 57–58.
Janowski, K. R., and Rossi, R. C. Mechanical degradation of MgO by water vapor, (8) 453–55.
Jech, R. E. See Readey, D. W.
Johnson, D. W., and Hummel, F. A. Phase equilibria and liquid immiscibility in the system PbO-B_2O_3-SiO_2, (4) 196–201.
Johnson, R. E., and Muan, Arnulf. Phase diagrams for the systems Si-O and Cr-O, (8) 430–33.
Jones, D. W., Matthews, R. S., Ruddlesden, K., and Williams, D. J. Proton magnetic resonance in borate glasses, (11) 664–65.
Jugle, D. B. See DeVries, R. C.

Kakar, A. K. Sintering kinetics based on geometric models, (4) 236.
Karpenko, Igor. Replication of particulate Al_2O_3 for examination by the electron microscope, (7) 408–409.
Kaznoff, A. I. See Grossman, L. N.
Kent, R. C. Gordon, R. S., and Hahn, S. J. Model for rheology of halloysite suspensions, (5) 269–73.
Keski, J. R., and Cutler, I. B. Initial sintering of Mn_2O-Al_2O_3, (8) 440–44.
Kevane, C. J. See Warmkessel, B. M.
Kilgore, R. V., and Williamson, W. O. Effect of graphite on microstructure and drying shrinkage of clay, (5) 256–58; Anomalous differential drying shrinkage of clay-quartz mixtures, (3) 181.
King, A. G., and Yavorsky, P. J. Stress relief mechanisms in magnesia- and yttria-stabilized zirconia, (1) 38–42.
Kinser, D. L., and Hench, L. L. Effect of a metastable precipitate on the electrical properties of an Li_2O-SiO_2 glass, (8) 445–48.
Kirby, R. K., and Rothrock, B. D. Thermal expansion of vitreous selenium from −190° to +30°C, (9) 535.
Kirchner, H. P., Gruver, R. M., and Walker, R. E. Chemical strengthening of polycrystalline alumina, (5) 251–55; see also Gruver, R. M.
Knapp, W. J. See Flood, H.
Koizumi, M. See Shimada, M.
Koyama, K. See White, J. L.
Krause, J. T., and Kurkjian, C. R. Vibrational anomalies in inorganic glass formers, (4) 226–27.
Kriegel, W. W. See Chay, D. M.
Kröger, F. A. See Yanagida, Hiroaki.
Kruger, O. L. See Moser, J. B.
Kulcinski, G. L. High-pressure induced phase transition in ZrO_2, (10) 582–84.
Kume, S. See Shimada, M.
Kurkjian, C. R. See Krause, J. T.

Lacy, E. D. Structure transition in alkali silicate glasses, (3) 150–57.
Laird, J. A., and Bergeron, C. G. Interface temperature of a crystallizing melt, (1) 60–61.
Latta, R. E. See Szwarc, R.
Lawless, W. N. Observations on "Pressure sintering of NaCl and other ionic materials," (4) 234–35.
Lay, K. W. Grain growth in UO_2-Al_2O_3 in the presence of a liquid phase, (7) 373–76.
Leipold, M. H., and Nielsen, T. H. Fabrication and characterization of isostatically hot-pressed MgO, (2) 94–97.
Leitnaker, J. M. See Inouye, H.; Spear, K. E.
Li, Pei-Ching, and Pappis, James. Preparation of boron-pyrographalloy foam and foil, (4) 225.
Librant, Zdzislaw, and Pampuch, Roman. X-ray strain analysis of MgO crystallites derived from thermal decomposition of various magnesium compounds, (2) 109–10.
Litovitz, T. A. See Tauke, J.
Livage, J., Doi, K., and Mazières, C. Nature and thermal evolution of amorphous hydrated zirconium oxide, (6) 349–53.
Loiacono, G. M., and Michelman, B. Growth and properties of $K_4Nb_6O_{17}$, (9) 542–43.
Long, L. See Murthy, M. K.

MacChesney, J. B., Potter, J. F., and Guggenheim, H. J. Vanadium dioxide coatings applied to alumina substrates, (3) 176–77.
MacDowell, J. F. See Duke, D. A.
Macedo, P. B. See Tauke, J.
McMahon, W. R., and Wilder, D. R. Hemispherical spectral emittance of selected rare earth oxides, (4) 187–92.
McMaster, A. D. See Gimpl, M. L.
Manning, C. R., Jr., and Stoops, R. F. High-temperature cermets: I, Compatibility, (8) 411–15; II, Wetting and fabrication, (8) 415–19.
Manning, W. R., and Hunter, Orville, Jr. Porosity dependence of Young's and shear moduli of polycrystalline yttrium oxide, (9) 537–38.
Marek, R. W. See Pearce, M. L.
Margrave, J. L. See Ficalora, P. J.
Martinek, Charles, and Hummel, F. A. Linear thermal expansion of three tungstates, (4) 227–28.
Masson, C. R. Ionic equilibria in liquid silicates, (3) 134–43.
Matthews, R. S. See Jones, D. W.
Mazières, C. See Livage, J.
Mears, L. D. See Elleman, T. S.
Megles, J. E., Jr. See Duke, D. A.
Messier, D. R. Evaporation of hypostoichiometric plutonium dioxide from 2070° to 2380°K, (12) 710–13.
Michelman, B. See Loiacono, G. M.
Milberg, M. E. See Otto, Klaus.
Mileson, J. S. See Glasser, L. S. D.
Minagawa, Shigekazu, Saito, Tadashi, and Gejyo, Tetsuo. Growth patterns on the surface of alumina grown by chemical vapor deposition, (9) 532–33.
Misra, S. K. See Chaklader, A. C. D.
Mistler, R. E., and Coble, R. L. Microstructural variation due to fabrication, (4) 237; Comments on the use of log-log plots in analyzing grain growth data, (8) 472.
Moak, D. P. See Steilrecht, D. E.
Moody, W. E. See Archer, J. R.
Moore, J. W., and Van Vlack, L. H. Preferred orientation in microstructures of eutectics between compounds, (8) 428–30.
Morgan, C. S. Comment on "Dorn method in the study of initial phase of uranium dioxide sintering," (12) 724.
Moser, J. B., and Kruger, O. L. Thermal conductivity and heat capacity of the monophosphide and monosulfide of plutonium, (7) 369–72.
Muan, Arnulf. See Johnson, R. E.
Muchow, G. M. See Ray, Satyabrata.
Muenow, D. W. See Ficalora, P. J.
Muller, Olaf, Roy, Rustum, and White, W. B. Phase equilibria in the systems NiO-Cr_2O_3-O_2, MgO-Cr_2O_3-O_2, and CdO-Cr_2O_3-O_2 at high oxygen pressures, (12) 693–99.
Murthy, M. K., Long, L., and Ip, J. Studies in germanium oxide systems: IV, Phase equilibria in the system K_2O-GeO_2, (11) 661–63.
Myklebust, R. L. See Ampian, S. G.

Naidu, S. V. N. See Rao, K. V. K.
Natansohn, S., and Baird, D. H. Effect of Cd-for-Zn substitution on magnetic properties of managanese zinc ferrites, (9) 533–34.
Natarajan, M. See Rao, G. V. S.
Nath, D. K., and Hummel, F. A. Crystal field studies of Co^{++} in α-$Zn_3(VO_4)_2$, (12) 720–22.
Negas, Taki. The system PbO-chromium oxide in air, (12) 716–19.
Negas, Taki, and Sorrell, C. A. Silica transformations in the system PbO-SiO_2, (11) 622–25.
Neumann, H., and Wijn, H. P. J. Polycrystalline hexagonal Fe_2W with varying ferrous contents, (9) 536.
Nichols, F. A. Further comments on the theory of grain growth in porous compacts, (8) 468–69.
Nicholson, G. C. See Olsen, K. H.
Nielsen, T. H. See Leipold, M. H.
Nitta, Tsuneharu. Properties of sodium-lithium niobate solid solution ceramics with small lithium concentrations, (11) 626–29.
Northrop, D. A. Vaporization of lead zirconate-lead titanate materials: II, Hot-pressed compositions at near theoretical density, (7) 357–61.
Norton, F. H. See Turnbaugh, J. E.
Novak, R. E. See Tennery, V. J.

Okamoto, Shoichi. Structure of the new δ-Fe_2O_3 (hydrate), (1) 54; Structure and magnetic properties of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (2) 113–14; Structure of δ-FeOOH, (10) 594–99.
Oliva, R. F. See Cucka, Paul.
Olsen, K. H., and Nicholson, G. C. Anomalous sintering behavior as revealed by in situ electron microscopy, (11) 669–70.
Osborn, E. F. See Roeder, P. L.
Ostertag, W., Fischer, G. R., and Williams, J. P. Thermal expansion of synthetic β-spodumene and β-spodumene–silica solid solutions, (11) 651–54.
Otto, Klaus, and Milberg, M. E. Ionic conduction in alkali and thallium silicate glasses, (6) 326–29.
Ouchi, Hiromu. Piezoelectric properties and phase relations of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics with barium or strontium substitutions, (3) 169–76.

Palmour, Hayne III. See Chay, D. M.; Rummler, D. R.
Pampuch, Roman. See Librant, Zdzislaw.
Pappis, James. See Li, Pei-Ching.
Pask, J. A. See Borom, M. P.; Brennan, J. J.
Pearce, M. L., and Marek, R. W. Formation of silicon and titanium carbides by chemical vapor deposition, (2) 84–87; Discussion of "Formation of silicon and titanium carbides by chemical vapor deposition," (6) 355.
Petersen, R. O., and Cutler, I. B. Effects of water vapor on the initial sintering of calcia, (1) 21–22.
Piumat, E. R. New sulfide and selenide glasses: Preparation, structure, and properties, (9) 499–507.
Potter, J. F. See MacChesney, J. B.
Pranatis, A. L. Phase fields and thermal expansion of oxides of copper, (3) 182.
Price, G. H., Stuart, W. I., and Walker, D. G. Crystallite growth of beryllium oxide powders and its inhibition by adsorbed phosphate, (9) 481–84.

Rao, C. N. R. See Rao, G. V. S.
Rao, G. V. S., Natarajan, M., and Rao, C. N. R. Effect of impurities on the phase transformations and decomposition of $CaCO_3$, (3) 179–80.
Rao, K. V. K., Naidu, S. V. N., and Iyengar, Leela. Thermal expansion of rutile-type GeO_2 by the X-ray method, (8) 467–68.
Rao, M. R. Liquidus relations in the quaternary subsystem $CaAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, (1) 50–54.
Ray, Satyabrata, and Muchow, G. M. High-quartz solid solution phases from thermally crystallized glasses of compositions (Li_2O, MgO)-Al_2O_3-$nSiO_2$, (12) 678–82.
Readey, D. W., and Jech, R. E. Energies and grooving kinetics of [001] tilt boundaries in nickel oxide, (4) 201–208.
Redwine, R. H. See Field, M. B.
Ricker, J. M., Bergeron, C. G., and Eagan, R. J. Enthalpy of fusion of $PbO \cdot 2B_2O_3$, (7) 410.
Riebling, E. F. Structural similarities between a glass and its melt, (3) 143–49; Nonideal mixing in binary GeO_2-SiO_2 glasses, (7) 406–407.
Rindone, G. E. See Taylor, T. D.
Roeder, E., and Hornstra, J. Grain growth during hot-pressing of tantalum carbide, (4) 224–25.
Roeder, P. L., Glasser, F. P., and Osborn, E. F. The system Al_2O_3-Cr_2O_3-SiO_2, (10) 585–94.
Rossi, R. C. Prediction of the elastic moduli of composites, (8) 433–39; see also Janowski, K. R.
Rossington, D. R. See Harris, J. R.
Rossington, D. R., and Runk, E. J. Adsorption of admixtures on portland cement hydration products, (1) 46–50.
Roth, W. L. See DeVries, R. C.
Rothrock, B. D. See Kirby, R. K.
Rotsey, W. B. See Hickman, B. S.
Roy, Rustum. See Datta, R. K.; Muller, Olaf.
Roy, S. K., and Coble, R. L. Solubilities of magnesia, titania, and magnesium titanate in aluminum oxide, (1) 1–6.
Ruddlesden, K. See Jones, D. W.
Rudy, Erwin, Brukl, C. E., and Windisch, Stephan. Constitution of ternary Ta-Mo-C alloys, (5) 239–50.
Ruh, Robert, Garrett, H. J., Domagala, R. F., and Tallan, N. M. The system zirconia-hafnia, (1) 23–27.
Rummler, D. R., and Palmour, Hayne III. Vacuum hot-pressing of magnesium aluminate spinel, (6) 320–26.
Runk, E. J. See Rossington, D. R.

Saito, Shinroku. See Fukunaga, Osamu.
Saito, Tadashi. See Minagawa, Shigekazu.
Sakaino, Teruo. See Yamane, Masayuki.
Salzano, F. J., Aronson, S., and Ingraham, A. Comment on compound formation in the lithium-carbon system, (8) 465.
Schatz, E. A. Spectral reflectance of sintered oxides, (5) 287–89.
Schreiber, Edward. Comment on the elastic modulus-porosity relation, (9) 541–42; see also Soga, Naohiro.
Schultz, A. H. See Stubican, V. S.
Scott, W. D. See Shackelford, J. F.
Scruggs, D. M., Van Vlack, L. H., and Spurgeon, W. M. Reaction between nitrogen and spinel in chromium, (9) 473–81.
Sereda, P. J. See Soroka, I.
Seward, T. P. III, Uhlmann, D. R., and Turnbull, David. Phase separation in the system BaO-SiO_2, (5) 278–85; Development of two-phase structure in glasses, with special reference to the system BaO-SiO_2, (11) 634–43.
Shackelford, J. F., and Scott, W. D. Relative energies of [1100] tilt boundaries in aluminum oxide, (12) 688–92.
Shaw, R. R., and Uhlmann, D. R. Subliquidus immiscibility in binary alkali borates, (7) 377–82.
Shimada, M., Kume, S., and Koizumi, M. Possible existence of dense ferrimagnetic perovskite allotropic form of yttrium iron garnet, (12) 713–15.
Shockey, D. A., and Groves, G. W. Effect of water on toughness of MgO crystals, (6) 299–303.
Sieger, J. S., and Gagne, R. Densification of glass under a cutting wheel, (5) 294–95.
Smith, D. K., Jr., and Weissmann, Sigmund. Residual stress and grain deformation in extruded polycrystalline BeO ceramics, (6) 330–36.
Smith, W. A. See Williams, D. T.
Smothers, W. J. See Ulmer, G. C.
Soga, Naohiro, and Schreiber, Edward. Porosity dependence of sound velocity and Poisson's ratio for polycrystalline MgO determined by resonant sphere method, (8) 465–66.
Soroka, I., and Sereda, P. J. Interrelation of hardness, modulus of elasticity, and porosity in various gypsum systems, (6) 337–40.
Sorrell, C. A. Synthesis of rhenium ditelluride, (5) 285–86; Fusion and vaporization characteristics of $ZrTe_5O_8$, (12) 674–77; see also Negas, Taki.
Spear, K. E., and Leitnaker, J. M. A consistent set of thermodynamic values for plutonium mononitride, (12) 706–709.
Spurgeon, W. M. See Scruggs, D. M.
Stanford, A. L., Jr. See Archer, J. R.
Stellrecht, D. E., Farkas, M. S., and Moak, D. P. Compressive creep of uranium carbide, (8) 455–58.
Stett, M. A., and Fulrath, R. M. Strengthening by chemical bonding in brittle matrix composite, (10) 599–600.
Stoch, L. Effect of cationic field strengths on the liquidus of oxide systems, (8) 419–23.
Stoops, R. F. See Manning, C. R., Jr.
Stuart, W. I. See Price, G. H.
Stubican, V. S. See Greskovich, C.; Tressler, R. E.
Stubican, V. S., and Schultz, A. H. Spinodal decomposition in the system TiO_2-SnO_2, (5) 290–91.
Subba Rao, G. V. See Rao, G. V. S.
Szwarc, R., and Latta, R. E. Vapor pressure of hypostoichiometric urania as a function of composition, (5) 264–68.

Tagai, Hideo, and Zisner, Tuvia. High-temperature creep of polycrystalline magnesia: I, Effect of simultaneous grain growth, (6) 303–10; see also Zisner, Tuvia.
Tallan, N. M. See Ruh, Robert.
Tauke, J., Litovitz, T. A., and Macedo, P. B. Viscous relaxation and non-Arrhenius behavior in B_2O_3, (3) 158–63.
Taylor, T. D., and Rindone, G. E. Internal friction of ion-exchanged glasses, (5) 289–90.
Tennery, V. J. Dielectric properties and phase transitions of sodium-strontium-cadmium niobates, (4) 183–86.
Tennery, V. J., and Hang, K. W. Heats of transition in $NaNbO_3$, (8) 469; Role of certain impurities in heats of transition of $PbZrO_3$, (11) 688–89.
Tennery, V. J., Hang, K. W., and Novak, R. E. Ferroelectric and structural properties of the $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ system, (12) 671–74.
Thompson, G. G. See Henry, J. L.
Tighe, N. J. See Barber, D. J.
Tokar, Michael. Increase in preferred orientation in lead ferrite by firing, (10) 601–602.
Tressler, R. E., Hummel, F. A., and Stubican, V. S. Pressure-temperature study of sulfospinels, (11) 648–51.
Tressler, R. E., and Stubican, V. S. Magnetic properties of $A^{2+}Cr_2S_4$ compounds with the NiAs structure, (7) 391–93.
Turkalo, A. M. Technique for obtaining thin glass sections for transmission electron microscopy, (8) 470–71.
Turnbaugh, J. E., and Norton, F. H. Low-frequency grain-boundary relaxation in alumina, (6) 344–48.
Turnbull, David. See Seward, T. P. III.

Uhlmann, D. R. See Seward, T. P. III; Shaw, R. R.
Ulmer, G. C., and Smothers, W. J. The system MgO-Cr_2O_3-Fe_2O_3 at 1300°C in air, (6) 315–19.
Uy, O. M. See Ficalora, P. J.

Vagnard, Gerard, and Washburn, J. Plastic deformation of cuprous oxide, (2) 88–94.
Van Vlack, L. H. See Moore, J. W.; Scruggs, D. M.
Varshneya, A. K. See Cooper, A. R.
Veevers, K. See Hickman, B. S.

Wachtman, J. B., Jr., Brower, W. S., Jr., and Parabaugh, E. N. Elastic constants of single crystal calcium molybdate ($CaMoO_4$), (6) 341–44.
Wagstaff, F. E. Crystallization kinetics of internally nucleated vitreous silica, (8) 449–52; see also Charles, R. J.
Waldbaum, D. R. Enthalpies of fusion of $KAlSi_2O_6$ and $NaAlSi_2O_6$, (1) 61–62.
Walker, D. G. See Price, G. H.
Walker, R. E. See Kirchner, H. P.
Warmkessel, B. M., and Kevane, C. J. Platinum contamination and reduction of cerium oxide, (11) 663–64.
Washburn, J. See Vagnard, Gerard.
Watson, B. Chr. See Grabmaier, J. G.
Weissmann, Sigmund. See Smith, D. K., Jr.
White, D. E., and Beals, R. J. Dry-pressing of a urania pycnometer, (11) 666–67.
White, J. L., and Koyama, K. Graphitic materials hot-worked with a dispersed liquid carbide: Thermal and electrical conductivity, (7) 394–98.
White, W. B. See Muller, Olaf.
Wijn, H. P. J. See Neumann, H.
Wilder, D. R. See Berard, M. F.; McMahon, W. R.
Williams, D. J. See Jones, D. W.
Williams, D. T., and Smith, W. A. Plasma heat transfer in verneuil crystal growth, (1) 32–37.
Williams, J. P. See Desjardins, Michel; Ostertag, W.
Williams, P. P. Crystal structure of a fluoride derivative of $12CaO \cdot 7Al_2O_3$, (9) 531.
Williamson, W. O. See Kilgore, R. V.
Wilshaw, T. R. Measurement of tensile strength of ceramics, (2) 111.
Windisch, Stephan. See Rudy, Erwin.
Wirkus, C. D. See Berard, M. F.
Wirtz, G. P., and Fine, M. E. Precipitation and coarsening of magnesioferrite in dilute solutions of iron in MgO, (7) 402–406.

Yamane, Masayuki, and Sakaino, Teruo. Chemical composition of phase-separated droplets in soda-lime-silica glass, (3) 178.
Yanagida, Hiroaki, and Kröger, F. A. The system Al-O, (12) 700–706.
Yavorsky, P. J. See King, A. G.
Youngblood, J. L. See Heckel, R. W.

Zisner, Tuvia, and Tagai, Hideo. High-temperature creep of polycrystalline magnesia: II, Effects of additives, (6) 310–14, see also Tagai, Hideo.
Zuegel, M. A. See Buchanan, R. C.

SUBJECT INDEX TO THE JOURNAL

Volume 51, 1968

The number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number.

Absorption, acoustic, of simple glasses, (4) 227.
Acids, silicic, surface state compared with quartz and cristobalite, (9) 511.
Additives, effect on high-temperature creep of polycrystalline MgO, (6) 310.
Adsorption, of admixtures on portland cement hydration products, (1) 46.
Adulteration, A-site and B-site, of Pb zirconate-titanate ceramics, (12) 683.
Aging, effect on saturation magnetization of precipitated magnesioferrite, (7) 405.
Alloys, Cu-O, wetting of sapphire by, (11) 630.
Aluminum, liquid, effect of nature of surfaces on wetting of sapphire by, (10) 569.
oxide, α-powders, explosively shocked, X-ray line broadening study of, (7) 398.
effect of Mn_2O of initial sintering kinetics, (8) 440.
effect on electrical properties of glasses in system PbO-Al_2O_3-P_2O_5-SiO_2, (1) 31.
γ-, effect of fabrication process on microstructure, (4) 237.
grown by chemical vapor deposition, growth patterns on surface, (9) 532.
Aluminum, oxide (*continued*)
low-frequency grain boundary relaxation in, (6) 344.
[1100] tilt boundaries in, relative energies of, (12) 688.
particulate, replication for electron microscopy, (7) 408
polycrystalline, chemical strengthening of, (5) 251.
polycrystalline, tensile strength measurement in, (2) 111.
rods, thermally conditioned, residual stress and flexural strength of, (4) 232.
single-crystal, neutron damage in, (11) 611.
sintered, spectral reflectance of, (5) 287.
solubility of MgO, TiO_2, and $MgTiO_3$ in, (1) 1.
substrates, application of VO_2 coatings, (3) 176.
suboxides, X-ray diffraction patterns of, (12) 700.
tungstate, linear thermal expansion, (4) 228.
Analysis. See also *X rays.*
of glass, by methods of stored elastic energy and linear-elastic fracture mechanics, (2) 77.
of grain growth data, use of log-log plots, (8) 472.
Analysis (*continued*)
mass spectrographic, of isostatically pressed MgO, (2) 96.
metallographic, X-ray diffraction, and DTA, of system ZrO_2-HfO_2, (1) 24.
quadratic multivariable, of microstructure and mechanical properties of hot-pressed $MgAl_2O_4$, (1) 10.
spectrochemical, for silica glasses, (1) 58.
Anelasticity, of U oxides, at room temperature, II, (4) 192.
Annealing, effect on color of unstrained MgO, (6) 308.
Atmosphere, laboratory, effect on fracture stress and Young's modulus of polycrystalline MgO, (8) 453.

Barium, silicate, films, vapor deposited, electron diffraction pattern of, (11) 635.
substitutions, in $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, effect on properties, (3) 169.
titanate, absolute reflective spectra of, (11) 666.

Barium, titanate (*continued*)
fine-grained, diffraction line shifts in, (5) 293.
optical dielectric constant, contribution of grain boundary to, (10) 609.
powder, effect of grain size on discoloration, (9) 537.
Beryllia, fuels, effect of irradiation on, (2) 63.
polycrystalline, extruded, residual stress and grain deformation in, (6) 330.
polycrystalline, fracture energy of, (10) 602.
powders, crystallite growth and inhibition by adsorbed phosphate, (9) 481.
Bonding, chemical, in strengthening brittle matrix composite, (10) 599; quartz-mica, in flexible sandstone, (7) 387.
Borates, alkali, subliquidus immiscibility in, (7) 377.
Borides, Nb and Ta, stability in combination with refractory metals, (8) 411.
Boron, oxide, effect on electrical properties of glasses in system PbO-Al_2O_3-B_2O_3-SiO_2, (1) 31; viscous relaxation and non-Arrhenius behavior in, (3) 158; -Pyrographalloy foam, formation and deposition, (4) 225.

Cadmium, stoichiometry, effect on dielectric constant of Na-Sr-Cd niobate, (4) 185; substitution for Zn, effect on magnetic properties of Mn Zn ferrites, (9) 533.
Calcium, $CaZr_4O_9$, inference from X-ray data, (10) 553.
fluoride, in packing material for Al_2O_3 bodies, effect on strength, (5) 255.
lignosulfonate, adsorption on cement hydration products, (1) 46.
molybdate, single crystal, elastic constants of, (6) 341.
oxide, effects of water vapor on initial sintering of, (1) 21.
silicate, polymorphism of, (6) 354.
Carbides, Hf, Nb, Ta, Zr, stability in combination with refractory metals, (8) 411; liquid, dispersed, graphitic materials produced by hot-working with, (7) 394; Si and Ti, formation by chemical vapor deposition, (2) 84.
Carbon, sintering behavior of gold spheres on, (11) 670; see also *Graphite*.
Carburization, time, relation to thickness of V carbide layers, (4) 215.
Celsian, nepheline-, glass-ceramic, strengthening with compressive glazes, (2) 102.
Cement, portland, adsorption of admixtures on hydration products, (1) 46.
Ceramics, interface reactions with metals, IV, (11) 630.
Cerium, oxide, Pt contamination and reduction of, (11) 663; oxide, sintered, spectral reflectance of, (5) 287.
Cermets, high-temperature, I, (8) 411; II, (8) 415.
Chalcogenides, phase separation behavior, analogy to oxides, (9) 499.
Chromates, characterization by X-ray and infrared, (12) 693.
Chromium, CrO_2 and Cr_2O_3, phase equilibrium curve, (7) 363.
Cr_2O_3, in solid solution layer for strengthening Al_2O_3, (5) 251.
oxidation-reduction behavior during reaction with other oxides in air, (12) 716.
oxidation state, determination in chromates, (12) 693.
reaction between N and spinel in, (9) 473.
tungstate, linear thermal expansion, (4) 228.
Clays, kaolinite-illite, effect of graphite on microstructure and drying shrinkage, (5) 256; -quartz mixtures, anomalous differential drying shrinkage of, (3) 181.
Cleavage faces, of NaCl, evaporation topography of, (4) 238.
Coatings, low-expansion solid solution, for chemically strengthening Al_2O_3 bodies, (5) 251; for spherical fuel particles, SiC as, (8) 424; vanadium dioxide, application to Al_2O_3 substrates, (3) 176.
Cobalt, Co^{3+}, in α-$Zn_3(VO_4)_2$, crystal field studies in, (12) 720; $CoCr_2S_4$, magnetic properties of, (7) 391; (II), environment in nitrate glass, (9) 544.
Colloids, gel, thoria, crystallite sizes measured by X-ray and electron microscopy, (4) 228.
Compatibility, of refractory metals and oxides, (8) 413.
Composites, brittle matrix, strengthening by chemical bonding, (10) 599; elastic moduli of, prediction of, (8) 433.
Conductivity, electrical, in alkali and thallium silicate glasses, (6) 326; of graphitic materials hot-worked with dispersed liquid carbide, (7) 394; low-temperature, in Ca-doped LiF, (9) 539.
Conductivity, thermal, of graphitic materials hot-worked with dispersed liquid carbide, (7) 394; of PuP and PuS, (7) 369.
Copper, liquid, additions of cupric oxide, (11) 630; oxide, cuprous, plastic deformation of, (2) 88; oxides, phase fields and thermal expansion, (3) 182.
Creep, compression, shape of curve for MgO, (3) 178.
compressive, of uranium carbide, (8) 455.
diffusional, mechanisms in polycrystalline aggregates, (2) 69.
high-temperature, of polycrystalline MgO, I, (6) 303; II, (6) 310.
of MgO, stress, temperature, and strain rate in, (10) 557.
of polycrystalline SiC, (2) 115.
Cristobalite, calculation of ΔH_f and ΔS_f for, (5) 263.
Cristobalite (*continued*)
exsolution of PbO from, in system PbO-SiO_2, (11) 622.
in internal nucleation in vitreous silica, (8) 449.
surface state, compared with quartz and silicic acid, (9) 511.
Cryolite, melting point of, (2) 197.
Crystal chemistry, for join $MgCr_2O_4$-$MgFe_2O_4$, (6) 318.
Crystal growth, mechanism, in In_2O_3 grown from PbO-B_2O_3 melts, (9) 507.
Crystallites, growth, of BeO powders, inhibition by adsorbed phosphate, (9) 481.
Crystallization, kinetics, of amorphous ZrO_2, (6) 350.
kinetics, in Li_2O-SiO_2 glasses, (7) 382.
primary phase fields in silicate glasses, relation to composition areas, (3) 163.
of vitreous silica, effect of internal nucleation by cristobalite, (8) 449.
Crystals, apparatus for growing, (1) 56.
CrO_2, from decomposition of CrO_3, (7) 363.
Czochralski growth, of Mg-Al spinel, (6) 355.
data, for $Na_2Ca_2Si_2O_7$, (1) 55.
field studies, of Co^{2+} in α-$Zn_3(VO_4)_2$, (12) 720.
growth, effect of temperature at crystal-melt interface, (1) 60.
traveling heater method, for $(Pb_xSr_{1-x})TiO_3$, (7) 364.
in verneuil plasma torch, heat transfer processes in, (1) 32.
in gypsum, effect of intergrowth and interlocking on mechanical behavior, (6) 337.
rare-earth vanadate, flux growth of, (9) 538.
structure, of Cu_2O, (2) 88.
structure, of fluoride derivative of $12CaO \cdot 7Al_2O_3$, (9) 531.
Cutting tools. See *Tools*.

Decomposition, of $CaCO_3$, effect of impurities on, (3) 179.
of $PbTi_2O_7$, first-order kinetic and Arrhenius plots, (10) 581.
spinodal, in system TiO_2-SnO_2, (5) 290.
thermal, of alkali metal sulfates, relation to sublimation, (10) 574.
thermal, of Mg compounds, MgO crystallites formed from, (2) 109.
Deformation, in flexible sandstone, (7) 387.
of glasses under point loading, role of densification, (10) 545.
grain, in extruded polycrystalline BeO ceramics, (6) 330.
plastic, of Cu_2O, (2) 88.
plastic, as stress relief mechanism in MgO- and Y_2O_3-stabilized ZrO_2, (1) 38.
Degradation, mechanical, of MgO by water vapor, (8) 453.
Densification, behavior, of Mg aluminate during vacuum hot-pressing, (6) 325.
of glass, under cutting wheel, (5) 294.
role in deformation of glasses under point loading, (10) 545.
in sintering of ZnO, (9) 521.
Density, decrease, in final stage sintering of ZnO, (9) 525; near theoretical, for hot-pressed Pb zirconate-Pb titanate materials, (7) 357.
Deposition, of SiC, by vapor, (8) 424; vapor, chemical, in formation of Si and Ti carbides, discussion of, (6) 355.
Dielectrics, constant, of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, effect of Ba or Sr substitutions, (3) 175.
constant, optical, of $BaTiO_3$, contribution of grain boundary to, (10) 609.
loss, in silica glass, effect of OH^- concentration and irradiation, (1) 57.
properties, of Na-Li niobate ceramics, (11) 626.
properties, of Na-Sr-Cd niobates, (4) 183.
Diffraction. See *X rays*.
Diffractometry, double-crystal, in study of grain and subgrain structure of BeO, (6) 331.
Diffusion, chemical, in V-C system above 1900°C, (4) 213.
as creep mechanism in polycrystalline aggregates, (2) 69.
gas, along boundaries in pore growth during sintering of ZnO, (9) 525.
of iron oxides in Na disilicate glass, kinetics of, (9) 490.
lattice, model for sintering of pressed ZnO pellets, (9) 521.
of oxygen, in monocrystalline rare earth oxides, (11) 643.
oxygen-ion, as rate-limiting step in densification of Mn_2O-Al_2O_3 compacts, (8) 440.
rare gas, in CsI, (10) 560.
Na, in SiO_2 glass, (9) 528.
surface, in Al_2O_3, (12) 688.
in system K_2O-SrO-SiO_2, I, (2) 103.
Diffusivity, thermal, of hot-worked graphites containing Mo and Zr, (7) 396.
Dilatometry, isothermal, in study of sintering kinetics, (4) 212.
Discoloration, of barium titanate powder, effect of grain size, (9) 537.
Doping, fission recoil techniques, in rare gas diffusion in CsI, (10) 560.
Dorn method, in study of initial phase of UO_2 sintering, (4) 209; comment on note, (12) 724; reply, (12) 724.
Dysprosium, oxide, single crystal, O diffusion in, (11) 643.

Elasticity, constant, c_{111}, in LiF, (10) 603.
constants, of single crystal $CaMoO_4$, (6) 341.
modulus, of β-SiC whiskers, (2) 114.
Elasticity, modulus (*continued*)
of composites, prediction of, (8) 433.
of gypsum systems, relation to hardness and porosity, (6) 337.
of polycrystalline Y_2O_3, porosity dependence, (9) 537.
relation to porosity in small spinel specimens, (9) 541.
of $91Y_2O_3$-$9ThO_2$, temperature dependence of, (4) 233.
of $(0.65Zn, 0.35Mg)_2SiO_4$, effect of temperature, (4) 222.
properties, of SiC, (4) 223.
of U oxides at room temperature, II, (4) 192.
Electrical conductivity. See *Conductivity, electrical*.
Electrical properties, of glasses in system PbO-Al_2O_3-B_2O_3-SiO_2, (1) 28; of Li_2O-SiO_2 glass, effect of metastable precipitate on, (8) 445.
Electronic properties, of PuS, (7) 372.
Electron microscopy, in measurement of crystallite sizes in thoria gel, (4) 228.
Electrooptic behavior, demonstration by extinction technique, (7) 368.
Emittance, hemispherical spectral, of rare earth oxides, (4) 187.
Energy, activation, for binary silicate glasses with additives, frequency dependence of, (6) 326.
of creep in polycrystalline MgO, (6) 312.
for diffusion, sintering, creep, and electrical conductivity of Al_2O_3, (1) 5.
fracture, of polycrystalline BeO, (10) 602.
free, -composition diagrams for B_2O_3-SiO_2, (1) 18.
free, vs. temperature, for Ca_2SiO_4, (6) 353.
grain boundary, in NaCl in rigid lattice approximation, (5) 276.
relative, of [1100] tilt boundaries in Al_2O_3, (12) 688.
of [001] tilt boundaries in Ni oxide, (4) 201.
Enthalpy, of fusion, of $PbO \cdot 2B_2O_3$, (7) 410.
of $KAlSi_2O_6$ and $NaAlSi_2O_6$, (1) 61.
of UO_3, (1) 59.
high-temperature, of UO_2, (5) 291.
Equilibrium studies, Cu-Cu_2O and Cu_2O-CuO phase fields, (3) 182; ionic, in liquid silicates, (3) 134; of joins in subsystem $CaAl_2O_4$-$CaAl_2O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, (1) 51.
Erbium, oxide, single crystal, O diffusion in, (11) 643; sesquioxide, hemispherical spectral emittance, (4) 187.
Etching, thermal, of NaCl cleavage faces in vacuum, (4) 238.
Eutectics, preferred orientation in microstructures of, (8) 428.
Evaporation, of PuO_2, hypostoichiometric, from 2070° to 2380°K, (12) 710.
Expansion, linear, of $PbTiO_3$ crystals, (10) 567.
Expansion, thermal, of crystalline compounds in Ge oxide systems, (11) 661.
of crystalline and noncrystalline silicates, (3) 151.
linear, of tungstates, (4) 227.
of oxides of copper, (3) 182.
of rutile-type GeO_2 by X-ray method, (8) 467.
of synthetic β-spodumene and β-spodumene–silica solid solutions, (11) 651.
of vitreous Se from −190° to +30°C, (9) 535.
Explosive shock, effect on structure of MgO and α-Al_2O_3 powders, (7) 398.

Fabrication, of cermets, (8) 415; microstructural variation due to, (4) 237.
Feldspars, alkali, enthalpies of fusion of, (1) 61; -SiO_2, liquid mixtures, structure of, (5) 259.
Ferrites, Fe_3W, polycrystalline hexagonal, effect of varying ferrous contents, (9) 536; Mn Zn, effect of Cd-for-Zn substitution on magnetic properties of, (9) 533.
Ferroelectric properties, of $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ system, (12) 671; of $PbTiO_3$, (10) 565.
Ferrous. See *Iron, ferrous*.
Films, glass, of BaO-SiO_2 composition, two-phase structure in, (11) 634; see also *Coatings*.
Firing, effect on preferred orientation in lead ferrite, (10) 601.
Flint, effect on drying shrinkage of clay, (5) 258.
Flow, processes, in alkali silicate glasses, high-temperature model, (3) 150; in silicate glasses, relation to primary phase fields, (3) 168.
Fluoride, derivative, of $12CaO \cdot 7Al_2O_3$, (9) 531.
Fluxes, PbO, in growth of $ZnRh_2O_4$ single crystals, (5) 292; KF, growth of $PbTiO_3$ crystals from, (10) 565.
Flux growth, of type RVO_4 rare-earth vanadate crystals, (9) 538.
Foam, boron-Pyrographalloy, preparation and deposition, (4) 225.
Formation, mechanism, of $PbTiO_3$, (4) 230.
Fractionation, curves, for system Al_2O_3-Cr_2O_3-SiO_2, (10) 588.
Fracture, energy of, in polycrystalline BeO, (10) 602; of MgO crystals, effect of water on, (6) 301; of tempered glass, (2) 75.
Friction, internal, determination of background in, (2) 112.
of ion-exchanged glasses, (5) 289.
measurement in alkali silicate glass, electrical polarization during, (11) 667.
spectrum, of polycrystalline sintered Al_2O_3, (6) 344.
of U oxides, effect of O/U ratios, (4) 192.
Fuels, BeO, effects of irradiation on, (2) 63.
Furnaces, high-temperature, for uranium oxide studies, (5) 265.
plasma-verneuil, in growth of single crystals, (1) 32.
sessile drop, diagram, (10) 569.
sessile drop, with optical system, (8) 415.
Fusion, enthalpy of, for $PbO \cdot 2B_2O_3$, (7) 410.
enthalpy of, of $KAlSi_2O_6$ and $NaAlSi_2O_6$, (1) 61.

Fusion (*continued*)
of UO_2, enthalpy determination, (1) 59.
of $ZrTe_2O_8$, (12) 674.

Gadolinium, sesquioxide, hemispherical spectral emittance, (4) 187.
Garnets, yttrium iron, dense ferrimagnetic perovskite allotropic form, possible existence, (12) 713.
Gases, rare, diffusion in CsI, (10) 560.
Gels. See *Colloids.*
Germanium, dioxide, determination of thermal expansion by X-ray method, (8) 467.
Glass, alkali silicate, electrical polarization during internal friction measurements in, (11) 667.
ionic conduction in, (6) 326.
structure transition in, (3) 150.
BaO-SiO_2, development of two-phase structure in, (11) 634.
borate, proton magnetic resonance in, (11) 663.
B_2O_3-K_2O melts, viscosity isotherms for, (3) 129.
B_2O_3-SiO_2, separation of silica-rich droplets, (1) 19.
bulk, composition compared to surface, with mass spectrometer, (5) 296.
deformation under point loading, role densification in, (10) 545.
densification, under cutting wheel, (5) 294.
droplets, Na_2O-CaO-SiO_2, phase-separated, (3) 178.
formers, inorganic, vibrational anomalies in, (4) 226.
GeO_2-SiO_2, binary, nonideal mixing in, (7) 406.
"ideal" concept, in oxide glasses, I, (3) 117; II, (3) 125.
inorganic, departure from ideality, (3) 121.
ion-exchanged, internal friction of, (5) 289.
PbO-Al_2O_3-B_2O_3-SiO_2, electrical properties of, (1) 28.
PbO-B_2O_3-SiO_2, electron micrographs of, (4) 198.
$(Li_2O,MgO)\cdot Al_2O_3\cdot nSiO_2$, thermally crystallized, high-quartz solid solution phases from, (12) 678.
Li_2O-SiO_2, effect of metastable precipitate on electrical properties of, (8) 445.
$Li_2O\cdot 2.5SiO_2$, ion-exchanged in $NaNO_3$, internal friction of, (5) 289.
Li_2O-SiO_2, kinetics of crystallization in, (7) 382.
nitrate, environment of Co(II) in, (9) 544.
oxide, "ideal glass" concept, I, (3) 117; II, (3) 125.
porous, effect of stress concentration on strength, (10) 599.
$KAlSi_2O_8$ and $NaAlSi_2O_8$, molar enthalpies and free energies, (1) 62.
potassium germanate, structure of, (11) 661.
selenide, new, preparation, structure, and properties, (9) 499.
silica, effect of OH^- concentration and irradiation on low-temperature dielectric loss in, (1) 57.
SiO_2, sodium diffusion in, (9) 528.
silicate, substructures in, (3) 163.
sintering, effect of particle shape on kinetics, (10) 604.
Na disilicate, dissolution and diffusion of iron oxides in, (9) 490.
sodium silicate, internal friction vs. temperature in, (2) 112.
Na_2O-SiO_2, compactibility as function of SiO_2, GeO_2, or P_2O_5, (3) 128.
soda-lime-silica, chemical composition of phase-separated droplets in, (3) 178.
sphericity, effect on sintering kinetics, (10) 604.
structure, correlation with melt structure, (3) 143.
sulfide, new, preparation, structure, and properties, (9) 499.
surface, composition compared to bulk glass by mass spectrometer, (5) 296.
tempered, fracture of, (2) 75.
thallium silicate, ionic conduction in, (6) 326.
thin sections, obtaining for transmission electron microscopy, (8) 470.
Glass-ceramics, strengthening by compressive glazes, (2) 98.
Glazes, compressive, in strengthening glass-ceramics, (2) 98.
Gold, spheres, sintering behavior on C layers, (11) 670.
Grain boundaries, in $BaTiO_3$, contribution to optical dielectric constant, (10) 609.
energies, in NaCl in rigid lattice approximation, (5) 276.
low-frequency relaxation in Al_2O_3, (6) 344.
mobility, in KCl, technique for measuring, (5) 273.
in NaCl, effect of orientation on properties, (11) 655.
Grain growth, data, use of log-log plots in analyzing, (8) 472.
during hot-pressing of Ta carbide, (4) 224.
excessive, in BeO, (6) 330.
in porous compacts, theory of, (8) 468.
simultaneous, effect on high-temperature creep of polycrystalline MgO, (6) 303.
in sintering of ZnO, (9) 521.
in UO_2-Al_2O_3, in presence of liquid phase, (7) 373.
Grain size, effect on discoloration of $BaTiO_3$ powder, (9) 537.
Graphite, effect on microstructure and drying shrinkage of clay, (5) 256; materials, hot-worked with dispersed liquid carbide, thermal and electrical conductivity, (7) 394; pyrolytic, low density foam, formation mechanism and deposition of, (4) 225.
Growth, patterns, on surface of Al_2O_3 grown by chemical vapor deposition, (9) 532.
Gypsum, systems, interrelation of hardness, modulus of elasticity, and porosity in, (6) 337.

Halloysite, suspensions, model for rheology of, (5) 269.
Hardness, of Al_2O_3, single crystal, effect of irradiation, (11) 611; of glasses, microplastic effects in point loading determination of, (10) 545; in gypsum systems, relation to modulus of elasticity and porosity, (6) 337.
Heat, capacity, of PuP and PuS, thermal conductivity and heat capacity, (7) 369.
of formation, of PuN, (12) 706.
of fusion, of UO_2, (5) 291.
specific, of $PbTiO_3$, (10) 568.
transfer, in single crystal growth in verneuil plasma torch, (1) 32.
of transition, of $PbZrO_3$, role of impurities in, (11) 668.
of transition, in $NaNbO_3$, (8) 469.
Holmium, oxide, single crystal, O diffusion in, (11) 643.
Hydration, products, of cement, adsorption of admixtures on, (1) 48.
Hydrogen, effect on deposition of Ti carbide, (2) 85.
Hydrogen ion concentration, effect on rheology of halloysite suspensions, (5) 269.
Hydroxyls, concentration, effect on low-temperature dielectric loss in silica glass, (1) 57.

Immiscibility, liquid, in system PbO-B_2O_3-SiO_2, (4) 196.
liquid-liquid, in system BaO-SiO_2, rapid-quenching device for determining, (5) 278.
metastable, in system B_2O_3-SiO_2, (1) 16.
subliquidus, in binary alkali borates, (7) 377.
Impurities, effect on phase transformations and decomposition of $CaCO_3$, (3) 179; role in heats of transition of $PbZrO_3$, (11) 668.
Indium, In_2O_3, grown from PbO-B_2O_3 melts, habit changes and growth mechanisms, (9) 507.
Interferometer, high-temperature, (3) 158.
Ions, exchange, in glass, effect on internal friction, (5) 289.
Iron, $FeCr_2S_4$, magnetic properties of, (7) 391.
δ-Fe_2O_3, structure, (1) 54.
δ-Fe_2O_3 (hydrate), structure proposed by Okamoto, (7) 408.
δ-FeOOH, structure of, (10) 594.
Fe_2W, polycrystalline hexagonal, effect of varying ferrous contents, (9) 536.
ferrous, relation of concentration to composition and phase assemblage for MgO-Fe_2O_3 system, (6) 316.
oxides, dissolution and diffusion in Na disilicate glass, (9) 490.
Irradiation, effect on BeO-based fuels, (2) 63; effect on low-temperature dielectric loss in silica glass, (1) 57.
Itacolumite, flexible quartz-mica composite, (7) 387.

Kaolinite, -muscovite-quartz mixtures, dimensional and weight changes on refiring, (2) 79.
Kinetics, crystallization, of internally nucleated vitreous silica, (8) 449.
densification, of Mg aluminate spinel, (6) 320.
of dissolution and diffusion of iron oxides in Na disilicate glass, (9) 490.
grain growth, in UO_2-Al_2O_3 compacts, (7) 373.
grooving, of [001] tilt boundaries in Ni oxide, (4) 201.
of sintering of glass, effect of particle shape, (10) 604.

Lead, ferrite, increase in preferred orientation by firing, (10) 601.
$PbCrO_3$, high-pressure synthesis, (2) 72; (5) 298.
$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, with Ba or Sr substitutions, (3) 169.
PbO-$2B_2O_3$, enthalpy of fusion of, (7) 410.
monoxide, in nucleation and growth of cristobalite and tridymite, (11) 622.
oxide, effect on electric properties of glasses in system PbO-Al_2O_3-B_2O_3-SiO_2, (1) 31.
pyrophosphate and pyroarsenate, in growth of rare-earth vanadate crystals, (9) 538.
titanate, ferroelectric properties of, (10) 565.
formation mechanism, (4) 230.
$PbTi_3O_7$, new compound, (10) 577.
zirconate, heats of transition, role of impurities in, (11) 668.
zirconate-titanate, vaporization of, II, (7) 357.
zirconate-titanate piezoelectric ceramics, adulterated, high-field losses of, (12) 683.
Linear expansion. See *Expansion.*
Liquid phase, effect on grain growth in UO_2-Al_2O_3, (7) 373.
Liquids, feldspar-SiO_2, structure of, (5) 259.
Liquidus, of oxide systems, effect of cationic field strengths, (8) 419.
Lithium, fluoride, Ca-doped, low-temperature electrical conductivity in, (9) 539.
fluoride, third-order elastic constant c_{111} in, (10) 603.
graphite, lamellar compounds, formation of, (8) 465.
$LiGa_5O_8$, X-ray powder pattern, (5) 297.
$Li_2Si_2O_5$, crystallization from glasses, kinetics of, (7) 382.
in Na-Li niobate solid solution ceramics, effect on properties, (11) 626.
Lutetium, oxide, single crystal, O diffusion in, (11) 643.

Magnesia. See *Magnesium, oxide.*
Magnesioferrite, precipitation and coarsening in dilute solutions of Fe in MgO, (7) 402.
Magnesium, aluminate, compacts, fabrication parameters and properties, (6) 321.
aluminate, fibers and platelets, (1) 56.
chromate, α- and β-, preparation at lower oxygen pressures, (12) 693.
$MgCr_2O_4$ and $MgFe_2O_4$, variation of cell size and normality, (9) 486.
oxide, compression creep curve for, (3) 178.
crystallites, X-ray strain analysis of, (2) 109.
crystals, effect of water on toughness, (6) 299.
with 1% Fe, precipitation and coarsening of magnesioferrite in, (7) 402.
isostatically hot-pressed, fabrication and characterization, (2) 94.
$MgAl_2O_4$, and $MgCr_2O_4$, effect of exposure to N on weight, (9) 475.
mechanical degradation by water vapor, (8) 453.
polycrystalline, determination of porosity dependence of sound velocity and Poisson's ratio, (8) 465.
polycrystalline, high-temperature creep of, I, (6) 303; II, (6) 310.
powder, explosively shocked, X-ray line broadening study of, (7) 398.
as stabilizer in ZrO_2, (1) 38.
stress, temperature, and strain rate in creep of, (10) 557.
and titanate, solubility in Al_2O_3, (1) 1.
Magnetic properties, of $A^{2+}Cr_2S_4$ compounds with NiAs structure, (7) 391.
of δ-FeOOH, (10) 594.
of Mn Zn ferrites, effect of Cd-for-Zn substitution, (9) 533.
of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (2) 113.
Magnetization, of δ-FeOOH, temperature dependence of, (10) 596; superpara-, of magnesioferrite particles precipitated from MgO + 1% Fe, (7) 404.
Manganese, $MnCr_2S_4$, magnetic properties of, (7) 391; oxide, effect on initial sintering kinetics of Al_2O_3, (8) 440; substitution for Cd in CdS and CdSe, effect on pressure of transformation from wurtzite to rock salt structure, (9) 520.
Mechanical properties, high-temperature, of ceramic materials, V, (4) 220; room-temperature, of hot-pressed $MgAl_2O_4$, quadratic mutivariable analysis, (1) 10.
Melting, diagram, for system Al_2O_3-Al, (12) 700; relation, in system TiO_2-WO_3, (5) 295.
Melting point, of cryolite, (2) 107.
Melts, PbO-B_2O_3, habit changes and growth mechanisms of In_2O_3 grown from, (9) 507.
Metals, interface reactions with ceramics, IV, (11) 630.
Mica, muscovite, in flexible sandstone, (7) 387.
Microplastic phenomena, in glasses under point loading, (10) 545.
Microscopy, electron, replication of particulate Al_2O_3 for, (7) 408.
in situ, in study of anomalous sintering behavior, (11) 669.
in study of phase separation in alkali borates, (7) 380.
transmission, obtaining thin glass sections for, (8) 470.
hot-stage, in equilibrium studies for subsystem $CaAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, (1) 50.
Minerals, $12CaO\cdot 7Al_2O_3$, crystal structure of fluoride derivative, (9) 531.
Mixing, nonideal, in binary GeO_2-SiO_2 glasses, (7) 406.
Models, geometric, sintering kinetics based on, (4) 236; for rheology of halloysite suspensions, (5) 269.
Modulus of rupture, of $(0.65Zn,0.35Mg)_2SiO_4$, effect of temperature, (4) 222.
Molybdenum, carbide, in hot-worked materials, thermal and electrical conductivity, (7) 394; carbide, structure and lattice parameters, (5) 239.
Mullite, cell dimensions of, (10) 594.
Muscovite, -kaolinite-quartz mixtures, dimensional and weight changes on refiring, (2) 79.

Nepheline, TiO_2-nucleated, and nepheline-celsian glass-ceramics, strengthening with compressive glazes, (2) 102.
Neutrons, damage from, in single-crystal Al_2O_3, (11) 611.
Nickel, $Ni_{1/3}Fe_{2/3}$ coprecipitate, structure and magnetic properties, (2) 113; oxide, energies and grooving kinetics of [001] tilt boundaries in, (4) 201; spheres, effect on strength of D glass composites, (10) 600.
Niobates, Na-Li, solid solution ceramics with small Li concentrations, properties of, (11) 626; Na-Sr-Cd, dielectric properties and phase transitions of, (4) 183.
Nitrides, Hf, stability in combination with refractory metals, (8) 411.
Nitrogen, reaction with spinel in Cr, (9) 473.
Nomenclature, of high-quartz solid solution phases, (12) 678.
Nucleation, in growth of In_2O_3 crystals from PbO-B_2O_3 melts, (9) 507; in Li_2O-SiO_2 glasses, mechanism of, (7) 382.

Orientation, effect on properties of grain boundaries in NaCl, (11) 655; preferred, increase in lead ferrite by firing, (10) 601; preferred, in microstructures of eutectics between compounds, (8) 428.
Oxides, liquidus, effect of cationic field strengths on, (8) 419.
sintered, spectral reflectance of, (5) 287.
Th, Hf, Zr, liquid metals on, effect of temperature on contact angles, (8) 416.

Oxides (*continued*)
Y_2O_3-stabilized HfO_2, ZrO_2, ThO_2, CeO_2, stability in combination with refractory metals, (8) 411.
Oxygen, bridging and nonbridging, in silica glass, modes of coordination, (3) 151; diffusion, in monocrystalline rare earth oxides, (11) 643.

Particles, shape, effect on initial sintering equations, (10) 548; shape, effect on kinetics of sintering of glass, (10) 604; size, effect on strength of irradiated BeO-based fuels, (2) 68.
Permittivity. See *Dielectrics, constant.*
Perovskite, deformed type, (12) 713; ferroelectric and structural properties of, (12) 671.
Phase diagrams. See also *Systems.*
of alkali borates, showing subliquidus miscibility gap, (7) 379.
Al_2O_3-Cr_2O_3-SiO_2, (10) 587.
B_2O_3-SiO_2, (1) 18.
CdS-MnS and CdSe-MnSe, (9) 518.
Ca_2SiO_4, comments on, (6) 354.
isothermal section, of system MgO-Al_2O_3-Cr_2O_3, (1) 43.
PbO-B_2O_3-SiO_2, (4) 197.
Li_2O-SiO_2, (8) 447.
MgO-Cr_2O_3-FeO_3, 1300°C in air, (6) 316.
NiO-Cr_2O_3-O_2, MgO-Cr_2O_3-O_2, and CdO-Cr_2O_3-O_2 at high oxygen pressures, (12) 693.
partial, of $PbTiO_3$-KF system, (10) 566.
proposed, for ZrO_2, (10) 584.
Si-O and Cr-O, (8) 430.
for system Ta-Mo-C, (5) 244.
for system U-C-O-N, low-nitrogen region, (11) 617.
V-C, above 1900°C, (4) 216.
ZrO_2-HfO_2, (1) 27.
Phase separation, in soda-lime-silica glass, chemical composition of droplets, (3) 178; in system BaO-SiO_2, (5) 278.
Phosphates, adsorbed, effect on crystallite growth of BeO powders, (9) 481.
Physical properties, of Al_2O_3, single crystal, effect of neutron damage, (11) 611; of glasses in system K_2O-GeO_2, (11) 662.
Piezoelectricity, high-field losses, in adulterated Pb zirconate-titanate, (12) 683; properties, and phase relations of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics with Ba or Sr substitutions, (3) 169; properties, of Na-Li niobate ceramics, (11) 626.
Plasma, verneuil torch, heat transfer in single crystal growth in, (1) 32.
Platinum, contamination of ceria by, (11) 663.
Plutonium, dioxide, hypostoichiometric, evaporation from 2070° to 2380°K, (12) 710; mononitride, consistent thermodynamic values, (12) 706; PuP and PuS, thermal properties of, (7) 369.
Poisson's ratio, in polycrystalline MgO, porosity dependence of, determination by resonant sphere method, (8) 465.
Polarization, electrical, during internal friction measurements in alkali silicate glass, (11) 667; spontaneous, of ferroelectric perovskite, (12) 671.
Polishing, chemical, apparatus for, (2) 89.
Pores, growth, during final stage sintering of ZnO, (9) 525; size distribution, of fired kaolinite-muscovite-quartz mixtures, (2) 79.
Porosity, dependence, of sound velocity in MgO, determination by resonant sphere method, (8) 465.
dependence, of Young's and shear moduli of polycrystalline Y_2O_3, (9) 537.
effect on high-temperature creep of polycrystalline MgO, (6) 310.
in gypsum systems, relation to hardness and modulus of elasticity, (6) 337.
relation to elastic modulus in small spinel specimens, (9) 541.
Porous materials, compacts, theory of grain growth in, (8) 468.
Potassium, aluminosilicate, enthalpy of fusion of, (1) 61.
chloride, measurement of grain boundary mobility in, (5) 273.
concentration distribution in system K_2O-SrO-SiO_2, (2) 103.
niobate, growth and properties, (9) 542.
tantalate niobate, single crystals, growth of, (12) 723.
Precipitates, metastable, effect on electrical properties of Li_2O-SiO_2 glass, (8) 445.
Precipitation, co-, of ZrO_2 and MgO, (6) 350; coherent, in system MgO-Al_2O_3-Cr_2O_3, (1) 42; of magnesioferrite in dilute solutions of Fe in MgO, (7) 402.
Pressing, dry-, of urania pycnometer, (11) 666.
hot-, effect on properties of $MgAl_2O_4$, (1) 10.
isostatic, effect on MgO, (2) 95.
of TaC, grain growth during, (4) 224.
vacuum, of Mg aluminate spinel, (6) 320.
Pressure, nitrogen, measurement in UN, (1) 6.
-temperature study, of sulfospinels, (11) 648.
transformation of YIG to dense form by, (12) 713.
vapor, of hypostoichiometric urania as function of composition, (5) 264.
vapor, of $PuO_{1.98}$, temperature dependence, (12) 710.
Protons, magnetic resonance, in borate glasses, (11) 664.
Pycnometer, urania, dry-pressing of, (11) 666.

Quartz, -clay mixtures, anomalous differential drying shrinkage of, (3) 181.
-kaolinite-muscovite, dimensional and weight changes on refiring, (2) 79.
Quartz (*continued*)
particles, in whiteware body, X-ray measurement of strain in, (8) 458.
surface state compared with cristobalite and silicic acid, (9) 511.
Quenching, data, for system Al_2O_3-Cr_2O_3-SiO_2, (10) 586; rate, effect on phase separation morphologies in BaO-SiO_2, (5) 281.

Rare earths, oxides, hemispherical spectral emittance of, (4) 187; oxides, monocrystalline, diffusion of oxygen in, (11) 643.
Reflectance. See *Reflection.*
Reflection, spectral, of sintered oxides, (5) 287.
Refractive index, in silicate glasses, relation to composition, (3) 166.
Refractories, oxides, carbides, borides, and HfN, stability in combination with metals, (8) 411.
Relaxation, viscous, in B_2O_3, (3) 158.
Replication, of particulate Al_2O_3 for electron microscopy, (7) 408.
Resonance, proton magnetic, in borate glasses, (11) 664.
Rhenium, ditelluride, synthesis of, (5) 285.
Rheology, of halloysite specimens, model for, (5) 269.
Rutile. See *Titanium, dioxide.*

Salicylic acid, adsorption on cement hydration products, (1) 46.
Samarium, sesquioxide, hemispherical spectral emittance of, (4) 187.
Sand, effect on drying shrinkage of clay, (5) 258.
Sandstone, flexible, structure-property relation in, (7) 387.
Sapphire, wetting of by liquid Al, effect of nature of surfaces, (10) 569; wetting of, by liquid Cu-O alloys, (11) 630.
Scandium, oxide, single crystal, O diffusion in, (11) 643.
Selenium, vitreous, thermal expansion from −190° to +30°C, (9) 535.
Sessile drop technique, in study of wetting of sapphire by liquid Cu-O alloys, (11) 630.
Shear, modulus, of polycrystalline Y_2O_3, porosity dependence of, (9) 537; modulus, relation to elastic compliances and orientation in $CaMoO_4$, (6) 342.
Shrinkage, drying, anomalous differential, of clay-quartz mixtures, (3) 181.
drying, of kaolinite-illite clay, effect of graphite, (5) 256.
isothermal, of CaO powder compacts as function of P_{H_2O}, (1) 21.
-time relations, for mass transport processes, effect of particle shape on, (10) 552.
Silicates, liquid, ionic equilibria in, (3) 134; $(0.65Zn,0.35Mg)SiO_4$, high-temperature mechanical properties, (4) 220.
Silicon, β-SiC whiskers, elastic modulus of, (2) 114.
carbide, elastic properties of, (4) 223.
formation by chemical vapor deposition, (2) 84; discussion of, (6) 355.
polycrystalline, creep of, (2) 115.
vapor-deposited, deposition and microstructure, (8) 424.
dioxide, activity coefficients in B_2O_3-SiO_2 melts, (1) 17.
effect on anisotropy and expansion of β-spodumene–silica solid solutions, (11) 651.
-feldspar, liquid mixtures, structure of, (5) 259.
as quartz, cristobalite, and silicic acid, comparison of surface states, (9) 511.
transformations, in system PbO-SiO_2, (11) 622.
vitreous, internally nucleated, crystallization kinetics of, (8) 449.
epitaxially grown, Mg-Al spinel as insulating substrate for, (6) 355.
Sintering, anomalous behavior, revealed by in situ electron microscopy, (11) 669.
effect on spectral reflectance of oxides, (5) 287.
equations, shape sensitivity of, (10) 548.
of glass, effect of particle shape on sintering of, (10) 604.
initial, of calcia, effects of water vapor, (1) 21.
initial, of Mn_2O-Al_2O_3, (8) 440.
kinetics, based on geometric models, (4) 236.
low-temperature, of BeO powders, effect of adsorbed phosphate, (9) 481.
pressure, of NaCl and other ionic materials, (4) 234.
pressure, of NaCl and other ionic materials, (12) 722.
UO_2, Dorn method in study of initial phase, (4) 209; comment on note, (12) 724.
of ZnO, I, (9) 521; II, (9) 525.
Sodium, aluminosilicate, enthalpy of fusion of, (1) 61.
chloride, cleavage faces in vacuum, thermal etching of, (4) 238.
effect of orientation on properties of grain boundaries in, (11) 655.
pressure sintering of, (4) 234; comments on, (12) 722.
in rigid lattice approximation, grain boundary energies in, (5) 276.
diffusion, in SiO_2 glass, (9) 528.
niobate, heats of transition in, (8) 469.
silicoborate, specific conductance, (3) 144.
$Na_2Ca_2Si_3O_9$, crystal data for, (1) 55.
Na_2ZrO_3, X-ray and optical crystallographic data for, (10) 608.
Na_2ZrSiO_5, solid state synthesis of, (10) 605.
Solid solutions. See *Solutions, solid.*
Solubility, of MgO, TiO_2, and $MgTiO_3$ in Al_2O_3, (1) 1; of N in Cr, (9) 473.
Solution, dis-, of iron oxides in Na disilicate glass, kinetics of, (9) 490.
Solutions, solid, in amorphous coprecipitates of Zr and Mg oxide, (6) 349.
spinel, sesquioxide, and periclase, in system MgO-Cr_2O_3-Fe_2O_3, in air at 1300°C, (6) 319.
β-spodumene–silica, thermal expansion of, (11) 651.
high-quartz phases, from thermally crystallized (Li_2O,MgO)-Al_2O_3-πSiO_2 glasses, (12) 678.
in system U-C-O-N at 1700°C, (11) 617.
Sound, velocity, porosity dependence of, in MgO, determination by resonant sphere method, (8) 465.
Spectra, absolute reflective, of ceramic $BaTiO_3$, (11) 666; infrared absorption, of δ-FeOOH, (10) 595.
Spectrometer, mass, spark source, in comparing surface and bulk glass composition, (5) 296.
Spectrometry, mass, at high temperatures, XXIX, (10) 574.
Spheres, resonant, in determination of porosity dependence of sound velocity and Poisson's ratio in polycrystalline MgO, (8) 465.
Spinels, elastic modulus-porosity relation in, (9) 541.
gallate, order-disorder in, (5) 297.
Mg-Al, Czochralski growth of, (6) 355.
$MgAl_2O_4$, hot-pressed, microstructure and mechanical properties, (1) 10.
$MgAl_2O_4$, platelet growth in, (1) 56.
$MgAl_2O_4$, vacuum hot-pressing of, (6) 320.
reaction with N in Cr, (9) 473.
rhodite, growth of single crystals from PbO flux, (5) 292.
sulfo-, pressure-temperature study, (11) 648.
Spodumene, β-synthetic, and β-spodumene–silica solid solutions, thermal expansion of, (11) 651.
Stability, of refractory oxides, carbides, borides, and HfN, (8) 411; subsolidus relations, in system $KTaO_3$-$KNbO_3$, (12) 723; thermal, of chromates and spinels, (12) 693.
Stoichiometry, of wustite, deviation as function of composition-P_{O_2}, (4) 231.
Strain, measurement, apparatus for spinning specimens, (6) 331; in quartz particles of whiteware bodies, X-ray measurement of, (8) 458; rate, in creep of MgO, (10) 557.
Strength, cationic field, effect on liquidus of oxide systems, (8) 419; flexural, of thermally conditioned 96% Al_2O_3 rods, (4) 232; tensile, of ceramics, measurement of, (2) 111.
Strengthening, chemical, of polycrystalline Al_2O_3, (5) 251; by chemical bonding in brittle matrix composite, (10) 599; of glass-ceramics by compressive glazes, (2) 98.
Stress, concentration, about a random spheroidal cavity, effect on Young's modulus, (8) 438.
in creep of MgO, (10) 557.
fracture, of polycrystalline Al_2O_3, (2) 111.
relief, mechanisms in MgO- and Y_2O_3-stabilized ZrO_2, (1) 38.
residual, in extruded polycrystalline BeO ceramics, (6) 330.
residual, of thermally conditioned 96% Al_2O_3 rods, (4) 232.
Strontium, concentration distribution in system K_2O-SrO-SiO_2, (2) 103; substitutions, in $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics, piezoelectric properties and phase relations in, (3) 169.
Structure, of AB_2S_4-type compounds, (11) 649.
of amorphous ZrO_2, (6) 352.
of crystals. See *Crystals.*
of flexible sandstone, relation to properties, (7) 387.
of δ-Fe_2O_3, (1) 54.
of δ-Fe_2O_3 (hydrate) as proposed by Okamoto, (7) 408.
of δ-FeOOH, (10) 594.
of $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ system, (12) 671.
of liquid mixtures of feldspar and SiO_2, (5) 259.
of MgO and α-Al_2O_3 powders, effect of explosive shock, (7) 398.
micro-, of carbide and oxide wetting test specimens, (8) 417.
of clay, effect of graphite on, (5) 256.
of eutectics between compounds, preferred orientation in, (8) 428.
of flexible sandstone, (7) 390.
of hot-pressed $MgAl_2O_4$, quadratic multivariable analysis, (1) 10.
of hot-pressed TaC containing 1 wt% Mn, (4) 224.
of SiC, vapor-deposited, (8) 424.
of uranium carbide, effect of creep testing, (8) 458.
of U oxides, (4) 193.
variation due to fabrication, (4) 237.
NiAs, magnetic properties of sulfochromite compounds with, (7) 391.
of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (2) 113.
similarities, in glass and melt, (3) 143.
of solid solution of Na-Li niobate ceramics, (11) 626.
sub-, in silicate glasses, (3) 163.
transition, in alkali silicate glasses, (3) 150.
two-phase, development in glasses in system BaO-SiO_2, (11) 634.
Sublimation, of alkali metal sulfates, relation to thermal decomposition, (10) 574.
Sulfates, alkali metal, thermal decomposition and sublimation in, (10) 574.
Sulfur, sulfochromite compounds, cation-defective NiAs-type polymorphs, (7) 391.
Surfaces, effect on wetting of sapphire by liquid Al, (10) 569; states, of quartz, cristobalite, and silicic acid, (9) 511.
Synthesis, high-pressure, of $PbCrO_3$, (2) 72.
high-pressure, of $PbCrO_3$, correction, (5) 298.
of $ReTe_2$, (5) 285.
solid state, of Na_2ZrSiO_5, (10) 605.

Systems. See also *Phase diagrams.*
Al-O, *P-T-x* diagram of, (12) 700.
Al-O, stable interfaces in, (10) 573.
Al_2O_3-Cr_2O_3-SiO_2, equilibrium data for, (10) 585.
BaO-SiO_2 development of two-phase structure of glasses in, (11) 634.
BaO-SiO_2, phase separation in, (5) 278.
B_2O_3-SiO_2, metastable immiscibility in, (1) 16.
CaO-ZrO_2, cubic field in, (10) 553.
Cr-O, phase diagrams for, (8) 432.
CrO_2-Cr_2O_3, equilibrium curve for, (7) 362.
Cr-spinel-N, reactions in, (9) 474.
$Co_3(VO_4)_2$-α-$Zn_3(VO_4)_2$, *d* values as function of composition in, (12) 720.
"FeO"-SiO_2, ionic distributions in, (3) 137.
Pb-Cr-O, $PbCrO_3$ as stable phase in, (2) 72.
PbO-Al_2O_3-B_2O_3-SiO_2, electrical properties of glasses in, (1) 28.
PbO-B_2O_3, growth of In_2O_3 crystals from, (9) 507.
PbO-B_2O_3-SiO_2, phase equilibria and liquid immiscibility, (4) 196.
PbO-chromium oxide, in air, (12) 716.
$Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$, ferroelectrc and structural properties, (12) 671.
PbO-SiO_2, silica transformations in, (11) 622.
PbO-TiO_2, new compound $PbTi_3O_7$ in, (10) 577.
$PbTiO_3$-KF, eutectic and solidus temperatures, (10) 565.
$PbZrO_3$-$PbTiO_3$, $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$, Pb-HfO_3-$PbTiO_3$, and $Pb_{0.99}Nb_{0.02}[(Zr_{0.6}Sn_{0.4})_{1-y}Ti_y]O_3$, phase boundaries for, (10) 610.
Li-C, compound formation in, (8) 465.
Li, Na, K, Rb, and Cs borates, phase boundaries of subliquidus immiscibility in, (7) 377.
Li_2O-SiO_2, crystallization in, (7) 382.
MgO-Al_2O_3-Cr_2O_3, coherent precipitation in, (1) 42.
MgO-Cr_2O_3-Fe_2O_3, at 1300°C in air, (6) 315.
MgO-oxide, effect of cationic field strengths on liquidus, (8) 421.
MnO-MnS, NaCl-NaF, NaBr-NaF, LiF-NaF, and FeO-FeS, microstructures of eutectics between compounds in, (8) 428.
MnO-SiO_2, CoO-SiO_2, and NiO-SiO_2, ionic equilibria in, (3) 142.
NiO-Cr_2O_3-O_2, MgO-Cr_2O_3-O_2, and CdO-Cr_2O_3-O_2, phase equilibria in, (12) 693.
oxide, effect of cationic field strengths on liquidus, (8) 419.
K_2O-GeO_2, phase equilibria in, (11) 661.
K_2O-SrO-SiO_2, diffusion in, I, (2) 103.
$KTaO_3$-$KNbO_3$, subsolidus stability relations in, (12) 723.
Re-Pb-Te, compatibility relations in, (5) 286.
series $MgCr_2O_4$-$MgFe_2O_4$, spinels in, (9) 485.
Si-O, phase diagram, (8) 431.
SiO_2-Na_2O-(CaO,Al_2O_3), effect of cationic field strengths on liquidus, (8) 422.
SiO_2-R_2O and SiO_2-RO, effect of cationic field strengths on liquidus, (8) 421.
$Na_2O \cdot SiO_2$-B_2O_3, molar volumes of B_2O_3 glasses and melts in, (3) 148.
Na_2O-ZrO_2-SiO_2, the join Na_2O-$ZrSiO_4$, (10) 605.
sub-, $CaAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, liquidus relations in, (1) 50.
Ta-Mo-C, X-ray, mp, DTA, and metallographic studies, (5) 239.
TiO_2-SnO_2, spinodal decomposition in, (5) 290.
TiO_2-WO_2, melting relation in, (5) 295.
U-C-O-N, phase relations in low-nitrogen region at 1700°C, (11) 617.
V-C, chemical diffusion and phase equilibria above 1900°C, (4) 213.
ZrO_2-HfO_2, metallographic, X-ray diffraction, and microprobe analysis, (1) 23.
ZrO_2-TeO_2, intermediate phase stable in air, (12) 674.

Tantalum, carbide, grain growth during hot-pressing, (4) 224; carbide, structure and lattice parameters, (5) 239.
Tellurium, dioxide, loss from $ZrTe_3O_8$ at high temperatures, (12) 674.
Temperature, in creep of MgO, (10) 557.
eutectic and solidus, of $PbTiO_3$-KF system, (10) 565.
Temperature (*continued*)
interface, of crystallizing melt, (1) 60.
-pressure, study, of sulfospinels, (11) 648.
Thermal conductivity. See *Conductivity, thermal.*
Thermal decomposition. See *Decomposition, thermal.*
Thermal expansion. See *Expansion.*
Thermodynamics, of ferroelectric-to-antiferroelectric phase transitions, relation to composition, (10) 609; in melts MO-SiO_2, (3) 141; properties, of UN, (1) 6; values, for PuN, consistent set, (12) 706.
Thermogravimetry, in determination of composition-P_{O_2} diagram of wustite, (4) 231.
Thorium, oxide, gel, X-ray and electron microscopy crystallite sizes in, (4) 228.
Thulium, oxide, single crystal, O diffusion in, (11) 643; sesquioxide, hemispherical spectral emittance, (4) 187.
Titanates, $(Pb_xSr_{1-x})TiO_3$, single crystals, growth by traveling heater method, (7) 364.
Titania. See *Titanium, oxide.*
Titanium, carbide, formation by chemical vapor deposition, (2) 84; discussion of, (6) 355.
dioxide, crystals, in PbO vapor, formation of $PbTiO_3$ from, (4) 230.
TiO_2, sintered, spectral reflectance of, (5) 287.
oxide, solubility in Al_2O_3, (1) 1.
Tools, cutting wheel, effect on glass density, (5) 294.
Toughness, of MgO crystals, effect of water on, (6) 299.
Transformation, phase, in $CaCO_3$, effect of impurities, (3) 179; silica, in system PbO-SiO_2, (11) 622; of YIG to dense form at high pressure, (12) 713.
Transition, ideal and nonideal, in oxide glasses, (3) 117.
phase, ferroelectric-to-antiferroelectric, thermodynamic relation to composition, (10) 609.
phase, high-pressure induced, in ZrO_2, (10) 582.
phase, in Na-Sr-Cd niobates, (4) 183.
Tridymite, calculation of ΔH_f and ΔS_f, (5) 263.
Tungstates, linear thermal expansion of, (4) 227.

Urania. See *Uranium, dioxide.*
Uranium, carbide, compressive creep of, (8) 455.
dioxide, -Al_2O_3, grain growth in presence of liquid phase, (7) 373.
enthalpy of fusion of, (1) 59.
high-temperature enthalpy and heat of fusion, (5) 291.
hypostoichiometric, vapor pressure of as function of composition, (5) 264.
pycnometer, dry-pressing of, (11) 667.
sintering, Dorn method in study of initial phase, (4) 209; comment on note, (12) 724.
nitride, equilibrium N pressures and thermodynamic properties, (1) 6.
oxide, hyperstoichiometric, elasticity and anelasticity at room temperature, (4) 192.
sesquicarbide, at 1700°C, (11) 620.

Vanadates, rare-earth, flux growth of type RVO_4 crystals, (9) 538.
Vanadium, dioxide, coatings, application to Al_2O_3 substrates, (3) 176.
Vapor deposition, chemical, in formation of Si and Ti carbides, (2) 84; chemical, growth patterns on surface of Al_2O_3 grown by, (9) 532.
Vaporization, characteristics, of $ZrTe_3O_8$, (12) 674; of Pb zirconate-Pb titanate materials, II, (7) 357.
Velocity, fractional, vs. temperature of simple glasses, (4) 226.
Vibration, anomalies, in inorganic glass formers, (4) 226.
Viscosity, shear, in B_2O_3, origin of non-Arrhenius behavior, (3) 162.

Water, effect on toughness of MgO crystals, (6) 299.
vapor, atmospheric, effect on mechanical properties of MgO, (8) 453.
vapor, effects on initial sintering of calcia, (1) 21.
Water (*continued*)
vapor pressure, effect on sintering of S-BeO, (9) 483.
Wettability, of sapphire by liquid Al, effect of nature of surfaces, (10) 569; of sapphire by liquid Cu-O alloys, (11) 630.
Wetting, of cermets, by refractory metals, (8) 415.
Whiskers, β-SiC, elastic modulus of, (2) 114.
Whiteware, bodies, X-ray measurement of strain in quartz particles of, (8) 458.
Wurtzite, phase, in CdSe-MnSe system, transformation to rock salt phase with pressure, (9) 520.
Wustite, composition-P_{O_2} diagram, thermogravimetric determination of, (4) 231.

Xenon, radioactive, diffusion in single crystals of CsI, (10) 560.
X rays, analysis, strain, of MgO crystallites formed by thermal decomposition, (2) 109.
cell, for obtaining crystal structure information under high pressures, (10) 583.
crystallographic data, for Na_2ZrO_3, (10) 607.
data, for compounds in system K_2O-GeO_2, (11) 662.
in determining thermal expansion of rutile-type GeO_2, (8) 467.
diffraction data, for crystallite sizes in thoria gel, (4) 228.
diffraction data, for ZrW_2O_8, (4) 228.
diffraction patterns, of Al suboxides, (12) 700.
diffraction profiles, of $BaTiO_3$, (5) 293.
intensities, in δ-FeOOH, variation as function of annealing temperature, (10) 597.
line broadening, in study of explosively shocked MgO and α-Al_2O_3 powders, (7) 398.
in measurement of strain in quartz particles of whiteware bodies, (8) 458.
microtopography, in study of grain and subgrain structure of BeO, (6) 331.
powder data, for $ReTe_3$, (5) 286.
powder diffraction, of thermally crystallized glasses (Li_2O,MgO)-Al_2O_3-$nSiO_2$, (12) 678.
powder diffraction data, for $PbTi_3O_7$, (10) 580.
powder diffraction data, for $Na_2Ca_2SiO_2O_8$, (1) 55.
powder diffraction patterns, of high pressure phases In_2S_3 and $NiRh_2S_4$, (11) 649.
of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (2) 113.
of $LiGa_5O_8$, (5) 297.

Young's modulus. See *Elasticity.*
Ytterbium, sesquioxide, hemispherical spectral emittance, (4) 187.
Yttrium, oxide, polycrystalline, porosity dependence of Young's and shear moduli of, (9) 537.
single crystal, O diffusion in, (11) 643.
sintered, spectral reflectance of, (5) 287.
as stablizer in ZrO_2, (1) 38.
+9ThO_2, temperature dependence of elastic moduli, (4) 233.
sesquioxide, hemispherical spectral emittance, (4) 187.

Zinc, substitution of Cd for, effect on magnetic properties of Mn Zn ferrites, (9) 533.
oxide, sintered, spectral reflectance of, (5) 287.
oxide, sintering of, I, (9) 521; II, (9) 525.
$ZnRh_2O_4$, single crystals, growth of, (5) 292.
α-$Zn_3(VO_4)_2$, crystal field studies of Co^{2+} in, (12) 720.
Zirconia. See *Zirconium, dioxide.*
Zirconium, carbide, in hot-worked materials, thermal and electrical conductivity, (7) 394.
oxide, amorphous hydrated, nature and thermal evolution, (6) 349.
commercial grade, recovery from zircon, (10) 605.
high-pressure induced phase transition in, (10) 582.
MgO- and Y_2O_3-stabilized, stress relief mechanisms in, (1) 38.
tungstate, linear thermal expansion, (4) 228.
$ZrTe_3O_8$, fusion and vaporization characteristics, (12) 674.

JOURNAL
of the
American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO CERAMICS

VOLUME 51, 1968

F. P. Reid, *Publisher and General Secretary*
Herbert Insley, *Editor*
Margie K. Reser, *Technical Editor*
M. Geraldine Smith, *Associate Editor*
Olive Scott, *Editorial Assistant*
Nancy L. Reed, *Editorial Assistant*

Committee on Publications: W. J. Smothers, *Chairman;*
Clarence L. Babcock, Seymour L. Blum, E. F. Osborn;
ex officio members: F. P. Reid, Herbert Insley, Edward E. Mueller

Executive, Editorial, and Advertising Offices: **4055 North High Street, Columbus, Ohio 43214**
Publication Office: **Easton, Pennsylvania**

Officers of the American Ceramic Society, 1968–69

Society Officers

President: LORAN S. O'BANNON
Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
President-Elect: ARTHUR J. BLUME
American Olean Tile Co., Lewisport, Ky. 42351
Vice Presidents:
CLARENCE L. BABCOCK, 5643 E. Holmes St., Tucson, Ariz. 85711 (Owens-Illinois, Inc.)
LANE MITCHELL, Georgia Institute of Technology School of Ceramic Engineering, Atlanta, Ga. 30332
THEODORE J. M. PLANJE
University of Missouri at Rolla
School of Mines and Metallurgy, Rolla, Mo. 65401
Treasurer: J. EARL FRAZIER
Frazier-Simplex, Inc., Box 492, Washington, Pa. 15301

Division Officers

Basic Science Division

Trustee: FLOYD A. HUMMEL (1969)
Pennsylvania State University, Materials Science Dept. College of Earth & Mineral Sciences, University Park, Pa. 16802
Chairman: ALBERT E. PALADINO, JR., Raytheon Co. Research Div., 28 Seyon St., Waltham, Mass. 02154
Chairman-Elect: ORSON L. ANDERSON, Lamont Geological Observatory, Columbia University, Palisades, N. Y. 10964
Vice Chairman: RALPH E. CARTER
General Electric Research & Development Center
Box 1088, Schenectady, N. Y. 12301
Secretary: ROBERT L. COBLE, University of Florida
Dept. of Metallurgical & Materials Engineering
Gainesville, Fla. 32601

Ceramic-Metal Systems Division

Trustee: EUGENE E. BRYANT (1970) Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
Chairman: CLIFTON G. BERGERON, University of Illinois
203 Ceramics Bldg., Urbana, Ill. 61801
Vice Chairman: LYNN E. FUSSELL, 435 Crestover Circle
Richardson, Texas 75080 (Texas Instruments, Inc.)
Secretary: ROBERT J. McWILLIAMS, Pfaudler Co.
Div. of Ritter Pfaudler Corp., 1000 West Ave.
Rochester, N. Y. 14603
Counselor: HAROLD C. WILSON, Vitreous Steel Products Co.
Box 150, Nappanee, Ind. 46550
Counselor: JACK E. BURROUGHS, SR., General Dynamics Corp.
Grant Lane, Fort Worth, Texas 76101

Design Division

Trustee: MARVIN G. YUTZEY, (1971), Fostoria Glass Co.
1200 First St., Moundsville, W. Va. 26041
Chairman: CHARLES R. DIBBLE, 848 Livingston Ave.
Syracuse, N. Y. 13210 (Syracuse University)
First Vice Chairman: GEORGE F. R. MILLER
Syracuse China Corp., Syracuse, N. Y. 13201
Second Vice Chairman: GERALD D. GULOTTA
420 E. 72nd St., New York, N. Y. 10021
Secretary: JOHN A. DODSON
Matthey Bishop, Inc., Malvern, Pa. 19355

Electronics Division

Trustee: ALEXIS G. PINCUS (1969) IIT Research Institute
10 W. 35th St., Chicago, Ill. 60616
Chairman: GILBERT GOODMAN, Globe-Union Inc.
5757 N. Green Bay Ave., Milwaukee, Wisc. 53201
Chairman-Elect: MERLE D. RIGTERINK
Bell Telephone Labs., Inc., Murray Hill, N. J. 07974
Vice Chairman: BERNARD SCHWARTZ, IBM Corp.
R.R. 52, Hopewell Junction, N. Y. 12533
Secretary: VICTOR J. TENNERY, Oak Ridge National Lab.
Metals & Ceramics Div., Box X, Oak Ridge, Tenn. 37830

Glass Division

Trustee: WILLIAM R. PRINDLE (1971) Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
Chairman: ALFRED R. COOPER, Case Western Reserve University
Dept. of Metallurgy, 10900 Euclid Ave., Cleveland, Ohio 44106
First Vice Chairman: JOHN R. HUTCHINS III
Corning Glass Works, Sullivan Park, Corning, N. Y. 14830
Second Vice Chairman: RICHARD E. MOULD
American Glass Research, Inc., Box 149, Butler, Pa. 16001
Secretary: J. RAYMOND HENSLER, Bausch & Lomb, Inc.
635 St. Paul St., Rochester, N. Y 14602

Materials & Equipment Division

Trustee: JOHN McLAREN (1969) Box 75
East Liverpool, Ohio 43920 (Sales representative)
Chairman: WILLIAM K. BURRISS, Lavino Div. of International Minerals & Chemical Corp. 3 Penn Center Plaza, Philadelphia, Pa. 19102
Chairman-Elect: RICHARD O. HOMMEL, 5 Grandview Ave. Apt. 803, Pittsburgh, Pa. 15211 (The O. Hommel Co.)
Vice Chairman: WILLIAM C. MOHR, Electro Refractories & Abrasives Div. of Ferro Corp., Box 151, Crooksville, Ohio 43731
Secretary: CARL W. GARTNER
General Color & Chemical Co., Inc.
Box 7, Minerva, Ohio 44657

Nuclear Division

Trustee: STEPHEN D. STODDARD (1970) 203 Chamisa
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
Chairman: JOSEPH H. HANDWERK, 1112 Black Rd.
Joliet, Ill. 60435 (Argonne National Lab.)
Vice Chairman: STEPHEN C. CARNIGLIA
Rocketdyne Div., North American Rockwell Corp.
6633 Canoga Ave., Canoga Park, Calif. 91304
Secretary: J. LAMBERT BATES, Battelle/Northwest
Box 999, Richland, Wash. 99352

Refractories Division

Trustee: KENNETH A. BAAB (1970) Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016
Chairman: RALPH C. PADFIELD, 2990 Avon Rd.
Bethlehem, Pa. 18017 (Bethlehem Steel Corp.)
Vice Chairman: WILLIAM D. FITZPATRICK, 412 E. Promenade
Mexico, Mo. 65265 (A. P. Green Refractories Co.)
Secretary: CHARLES A. McFADDEN, Bickley Furnaces, Inc.
550 State Rd., Philadelphia, Pa. 19114

Structural Clay Products Division

Trustee: GILBERT C. ROBINSON (1969)
Box 91, Clemson, S. C. 29631 (Clemson University)
Chairman: ROBERT B. HOCKADAY, Acme Brick Co.
Research Dept., Box 1189, Denton, Texas 76201
Chairman-Elect: ROBERT W. RICHARDS, Richards Brick Co.
234 Springer, Edwardsville, Ill. 62025
Vice Chairman: SHERWOOD E. PATEK
Midland Brick & Tile Co., Chillicothe, Mo. 64601
Secretary: ROGER C. STOEN, Can-Tex Industries
Div. of Harsco Corp., Fourth and Washington Sts.
Cannelton, Ind. 47520

White Wares Division

Trustee: WALTER W. PERKINS (1971) 871 Jacoby Rd.
Copley, Ohio 44321 (U. S. Stoneware, Inc.)
Chairman: MILAN VUKOVICH, JR.,
Edward Orton Jr. Ceramic Foundation, 1445 Summit St.
Box 8007, Sta. A, Columbus, Ohio 43201
Chairman-Elect: WILLIAM B. CAMPBELL, 1892 Inchcliff Rd.
Columbus, Ohio 43221 (Ohio State University)
Vice Chairman: DONALD L. HEATH, Coors Porcelain Co.
600 Ninth St., Golden, Colo. 80401
Secretary: E. L. KASTENBEIN, Rutgers, the State University
School of Ceramics, New Brunswick, N. J. 08903

Ceramic Educational Council

Trustee: DAVID R. WILDER (1971) Iowa State University
Dept. of Ceramic Engineering, Ames, Iowa 50010
President: ALFRED W. ALLEN, University of Illinois
Ceramic Engineering Dept., Urbana, Ill. 61801
President-Elect: WILLIS G. LAWRENCE
State University of New York, College of Ceramics
at Alfred University, Alfred, N. Y. 14802
Vice President: ROBERT E. MOORE
University of Missouri at Rolla, School of Mines
& Metallurgy, Rolla, Mo. 65401
Secretary-Treasurer: MALCOLM G. McLAREN
Rutgers, the State University, School of Ceramics
New Brunswick, N. J. 08903

National Institute of Ceramic Engineers

Trustee: WINSTON DUCKWORTH (1971)
Battelle Memorial Institute
505 King Ave., Columbus, Ohio 43201
President: ROBERT J. BEALS, Argonne National Laboratory
Bldg. 212, 9700 S. Cass Ave., Argonne, Ill. 60439
President-Elect: MURRAY C. GAUTSCH, 540 Golfview Dr.
Vero Beach, Fla. 32960
Vice President: HAROLD D. PRIOR, Chas. Taylor Sons Co.
Box 14058, Cincinnati, Ohio 45214
Secretary-Treasurer: J. R. TINKLEPAUGH
State University of New York, College of Ceramics
at Alfred University, Alfred, N. Y. 14802

TABLE OF CONTENTS

VOLUME 51, 1968

January [No. 1], pp. 1–62

1. Salil K. Roy and Robert L. Coble: Solubilities of Magnesia, Titania, and Magnesium Titanate in Aluminum Oxide 1
2. H. Inouye and J. M. Leitnaker: Equilibrium Nitrogen Pressures and Thermodynamic Properties of UN 6
3. Dong M. Chay, Hayne Palmour III, and W. W. Kriegel: Microstructure and Room-Temperature Mechanical Properties of Hot-Pressed Magnesium Aluminate as Described by Quadratic Multivariable Analysis 10
4. R. J. Charles and F. E. Wagstaff: Metastable Immiscibility in the B_2O_3–SiO_2 System 16
5. Ronald O. Petersen and Ivan B. Cutler: Effects of Water Vapor on the Initial Sintering of Calcia 21
6. Robert Ruh, H. J. Garrett, R. F. Domagala, and N. M. Tallan: The System Zirconia-Hafnia 23
7. R. C. Buchanan and M. A. Zuegel: Electrical Properties of Glasses in the System PbO-Al_2O_3-B_2O_3-SiO_2 28
8. D. T. Williams and W. A. Smith: Plasma Heat Transfer in Verneuil Crystal Growth 32
9. Alan G. King and Paul J. Yavorsky: Stress Relief Mechanisms in Magnesia- and Yttria-Stabilized Zirconia 38
10. C. Greskovich and V. S. Stubican: Coherent Precipitation in the System MgO-Al_2O_3-Cr_2O_3 42
11. D. R. Rossington and Ellen J. Runk: Adsorption of Admixtures on Portland Cement Hydration Products 46
12. M. Ramakrishna Rao: Liquidus Relations in the Quaternary Subsystem $CaAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$ 50

Discussions and Notes

Shoichi Okamoto: Structure of the New δ-Fe_2O_3 (Hydrate) 54
L. S. Dent Glasser and J. S. Mileson: Crystal Data for $Na_2Ca_2Si_2O_7$ 55
R. J. Bratton and S. M. Ho: $MgAl_2O_4$ Fibers and Platelets 56
R. E. Jaeger: Influence of OH^- Concentration and Irradiation on Low-Temperature Dielectric Loss in Silica Glass 57
L. N. Grossman and A. I. Kaznoff: Determination of Enthalpy of Fusion of Uranium Dioxide 59
J. A. Laird and C. G. Bergeron: Interface Temperature of a Crystallizing Melt 60
D. R. Waldbaum: Enthalpies of Fusion of $KAlSi_2O_6$ and $NaAlSi_2O_6$ 61

February [No. 2], pp. 63–116

13. B. S. Hickman, W. B. Rotsey, R. J. Hilditch, and K. Veevers: Effects of Irradiation on Beryllia-Based Fuels 63
14. R. C. Gifkins: Diffusional Creep Mechanisms 69
15. R. C. DeVries and W. L. Roth: High-Pressure Synthesis of $PbCrO_3$ 72
16. John M. Barsom: Fracture of Tempered Glass 75
17. W. F. Cole and D. N. Crook: High-Temperature Reactions of Clay Mineral Mixtures and Their Ceramic Properties: IV, Dimensional and Weight Changes on Refiring and the Pore-Size Distribution of Fired Kaolinite-Muscovite-Quartz Mixtures with 25 Wt% Quartz 79
18. M. L. Pearce and R. W. Marek: Formation of Silicon and Titanium Carbides by Chemical Vapor Deposition 84
19. Gerard Vagnard and J. Washburn: Plastic Deformation of Cuprous Oxide 88
20. M. H. Leipold and T. H. Nielsen: Fabrication and Characterization of Isostatically Hot-Pressed MgO 94
21. D. A. Duke, J. E. Megles, Jr., J. F. MacDowell, and H. F. Bopp: Strengthening Glass-Ceramics by Application of Compressive Glazes 98
22. A. R. Cooper and A. K. Varshneya: Diffusion in the System K_2O-SrO-SiO_2: I, Effective Binary Diffusion Coefficients 103
23. Perry A. Foster, Jr.: Melting Point of Cryolite 107

Discussions and Notes

Zdzislaw Librant and Roman Pampuch: X-Ray Strain Analysis of MgO Crystallites Derived from Thermal Decomposition of Various Magnesium Compounds 109
T. R. Wilshaw: Measurement of Tensile Strength of Ceramics 111
M. B. Field and R. H. Redwine: Empirical Determination of Background in Internal Friction Studies 112
Shoichi Okamoto: Structure and Magnetic Properties of $Ni_{1/3}Fe_{2/3}$ Coprecipitate 113
R. W. Bartlett: Elastic Modulus of β-Silicon Carbide Whiskers 114
T. L. Francis and R. L. Coble: Creep of Polycrystalline Silicon Carbide 115

March [No. 3], pp. 117–82

24. C. A. Angell: Oxide Glasses in Light of the "Ideal Glass" Concept: I, Ideal and Nonideal Transitions, and Departures from Ideality 117
25. C. A. Angell: Oxide Glasses in Light of the "Ideal Glass" Concept: II, Interpretations by Reference to Simple Ionic Glass Behavior 125
26. C. R. Masson: Ionic Equilibria in Liquid Silicates 134
27. E. F. Riebling: Structural Similarities Between a Glass and Its Melt 143
28. E. D. Lacy: Structure Transition in Alkali Silicate Glasses 150
29. J. Tauke, T. A. Litovitz, and P. B. Macedo: Viscous Relaxation and Non-Arrhenius Behavior in B_2O_3 158
30. C. L. Babcock: Substructures in Silicate Glasses 163
31. Hiromu Ouchi: Piezoelectric Properties and Phase Relations of $Pb(Mg^{1}/_{3}Nb^{2}/_{3})O_3$-$PbTiO_3$-$PbZrO_3$ Ceramics with Barium or Strontium Substitutions 169

Discussions and Notes

J. B. MacChesney, J. F. Potter, and H. J. Guggenheim: Vanadium Dioxide Coatings Applied to Alumina Substrates 176
Masayuki Yamane and Teruo Sakaino: Chemical Composition of Phase-Separated Droplets in Soda-Lime-Silica Glass 178
J. H. Hensler and G. V. Cullen: Shape of the Compression Creep Curve for Magnesium Oxide 178
G. V. Subba Rao, M. Natarajan, and C. N. R. Rao: Effect of Impurities on the Phase Transformations and Decomposition of $CaCO_3$ 179
R. V. Kilgore and W. O. Williamson: Anomalous Differential Drying Shrinkage of Clay-Quartz Mixtures 181
A. L. Pranatis: Phase Fields and Thermal Expansion of Oxides of Copper 182

April [No. 4], pp. 183–238

32. Victor J. Tennery: Dielectric Properties and Phase Transitions of Sodium-Strontium-Cadmium Niobates 183
33. W. R. McMahon and D. R. Wilder: Hemispherical Spectral Emittance of Selected Rare Earth Oxides 187

34. Roberto J. Forlano, A. W. Allen, and R. J. Beals: Elasticity and Anelasticity of Uranium Oxides at Room Temperature: II, Hyperstoichiometric Oxides 192
35. David W. Johnson and F. A. Hummel: Phase Equilibria and Liquid Immiscibility in the System PbO-B_2O_3-SiO_2 196
36. D. W. Readey and R. E. Jech: Energies and Grooving Kinetics of [001] Tilt Boundaries in Nickel Oxide 201
37. J. J. Bacmann and G. Cizeron: Dorn Method in the Study of Inital Phase of Uranium Dioxide Sintering 209
38. L. M. Adelsberg and L. H. Cadoff: Chemical Diffusion and Phase Equilibria in the Vanadium-Carbon System Above 1900°C 213
39. W. T. Benecki and F. A. Hummel: High-Temperature Mechanical Properties of Ceramic Materials: V, $(Zn_{0.65}Mg_{0.35})_2SiO_4$. 220

Discussions and Notes

R. D. Carnahan: Elastic Properties of Silicon Carbide 223
E. Roeder and J. Hornstra: Grain Growth During Hot-Pressing of Tantalum Carbide 224
Pei-Ching Li and James Pappis: Preparation of Boron-Pyrographalloy Foam and Foil 225
J. T. Krause and C. R. Kurkjian: Vibrational Anomalies in Inorganic Glass Formers 226
Charles Martinek and F. A. Hummel: Linear Thermal Expansion of Three Tungstates 227
M. J. Bannister: Equivalence of X-Ray and Electron Microscopy Crystallite Sizes in Thoria Gel 228
Norman H. Harris and R. L. Cook: Formation Mechanisms of $PbTiO_3$ 230
I. Bransky and A. Z. Hed: Thermogravimetric Determination of the Composition-Oxygen Partial Pressure Diagram of Wustite ($Fe_{1-y}O$) 231
R. M. Gruver and H. P. Kirchner: Residual Stress and Flexural Strength of Thermally Conditioned 96% Alumina Rods. 232
R. W. Dickson and R. C. Anderson: Temperature Dependence of the Elastic Moduli of $91Y_2O_3 + 9ThO_2$ from 25° to 1100°C 233
W. N. Lawless: Observations on "Pressure Sintering of NaCl and Other Ionic Materials" 234
Ashok K. Kakar: Sintering Kinetics Based on Geometric Models 236
R. E. Mistler and R. L. Coble: Microstructural Variation Due to Fabrication 237
Jürgen Budke: Thermal Etching of NaCl Cleavage Faces in Vacuum 238

May [No. 5], pp. 239–98

40. Erwin Rudy, C. E. Brukl, and Stephan Windisch: Constitution of Ternary Ta-Mo-C Alloys 239
41. Henry P. Kirchner, Robert M. Gruver, and Ralph E. Walker: Chemical Strengthening of Polycrystalline Alumina 251
42. R. V. Kilgore and W. O. Williamson: Effect of Graphite on Microstructure and Drying Shrinkage of Clay 256
43. H. Flood and W. J. Knapp: Structural Characteristics of Liquid Mixtures of Feldspar and Silica 259
44. R. Szwarc and R. E. Latta: Vapor Pressure of Hypostoichiometric Urania as a Function of Composition 264
45. Raymond C. Kent, Ronald S. Gordon, and Sang J. Hahn: Model for Rheology of Halloysite Suspensions 269
46. C. F. Gibbon: Technique for Measuring Grain Boundary Mobility and Its Application to Potassium Chloride 273
47. C. F. Gibbon: Grain Boundary Energies in NaCl in the Rigid Lattice Approximation 276
48. T. P. Seward III, D. R. Uhlmann, and David Turnbull: Phase Separation in the System BaO-SiO_2 278
49. Charles A. Sorrell: Synthesis of Rhenium Ditelluride 285
50. Elihu A. Schatz: Spectral Reflectance of Sintered Oxides 287

Discussions and Notes

T. D. Taylor and G. E. Rindone: Internal Friction of Ion-Exchanged Glasses 289
V. S. Stubican and A. H. Schultz: Spinodal Decomposition in the System TiO_2-SnO_2 290
R. A. Hein, P. N. Flagella, and J. B. Conway: High-Temperature Enthalpy and Heat of Fusion of UO_2 291
Robert H. Arlett: Growth of $ZnRh_2O_4$ Single Crystals 292
F. N. Bradley: Diffraction Line Shifts Observed in Fine-Grained Barium Titanate 293
J. S. Sieger and R. Gagne: Densification of Glass Under a Cutting Wheel 294
Luke L. Y. Chang: Melting Relation in the System TiO_2-WO_2 295
Michel Desjardins and J. P. Williams: Comparison of Surface and Bulk Glass Composition with the Spark Source Mass Spectrometer 296
R. K. Datta and Rustum Roy: Reinvestigation of Order-Disorder in Gallate Spinels 297
R. C. DeVries and W. L. Roth: Correction: High-Pressure Synthesis of $PbCrO_3$ (February issue, 1968) 298

June [No. 6], pp. 299–356

51. D. A. Shockey and G. W. Groves: Effect of Water on Toughness of MgO Crystals 299
52. Hideo Tagai and Tuvia Zisner: High-Temperature Creep of Polycrystalline Magnesia: I, Effect of Simultaneous Grain Growth 303
53. Tuvia Zisner and Hideo Tagai: High-Temperature Creep of Polycrystalline Magnesia: II, Effects of Additives 310
54. G. C. Ulmer and W. J. Smothers: The System MgO-Cr_2O_3-Fe_2O_3 at 1300°C in Air 315
55. Donald R. Rummler and Hayne Palmour III: Vacuum Hot-Pressing of Magnesium Aluminate Spinel 320
56. Klaus Otto and M. E. Milberg: Ionic Conduction in Alkali and Thallium Silicate Glasses 326
57. Deane K. Smith, Jr., and Sigmund Weissmann: Residual Stress and Grain Deformation in Extruded Polycrystalline BeO Ceramics 330
58. I. Soroka and P. J. Sereda: Interrelation of Hardness, Modulus of Elasticity, and Porosity in Various Gypsum Systems ... 337
59. J. B. Wachtman, Jr., W. S. Brower, Jr., and E. N. Farabaugh: Elastic Constants of Single Crystal Calcium Molybdate ($CaMoO_4$) 341
60. Jerry E. Turnbaugh and F. H. Norton: Low-Frequency Grain-Boundary Relaxation in Alumina 344
61. J. Livage, K. Doi, and C. Maziéres: Nature and Thermal Evolution of Amorphous Hydrated Zirconium Oxide 349

Discussions and Notes

W. R. Foster: Comment on the Ca_2SiO_4 Phase Diagram 353
M. A. Bredig: Further Comment on the Phase Diagram of Ca_2SiO_4 (and of CaC_2) 354
M. L. Pearce and R. W. Marek: Discussion of "Formation of Silicon and Titanium Carbides by Chemical Vapor Deposition" 355
J. G. Grabmaier and B. Chr. Watson: Czochralski Growth of Magnesium-Aluminum Spinael 355

July [No. 7], pp. 357–410

62. David A. Northrop: Vaporization of Lead Zirconate-Lead Titanate Materials: II, Hot-Pressed Compositions at Near Theoretical Density 357
63. Osamu Fukunaga and Shinroku Saito: Phase Equilibrium in the System CrO_3-Cr_2O_3 362
64. B. diBenedetto and C. J. Cronan: Single Crystals of $(Pb_xSr_{1-x})TiO_3$ Grown by Traveling Heater Method 364
65. J. B. Moser and O. L. Kruger: Thermal Conductivity and Heat Capacity of the Monophosphide and Monosulfide of Plutonium 369
66. K. W. Lay: Grain Growth in UO_2-Al_2O_3 in the Presence of a Liquid Phase 373
67. R. R. Shaw and D. R. Uhlmann: Subliquidus Immiscibility in Binary Alkali Borates 377
68. S. W. Freiman and L. L. Hench: Kinetics of Crystallization in Li_2O-SiO_2 Glasses 382
69. R. C. DeVries and D. B. Jugle: Structure-Property Relation in Flexible Sandstone 387

70. R. E. Tressler and V. S. Stubican: Magnetic Properties of $A^{3+}Cr_2S_4$ Compounds with the NiAs Structure 391
71. J. L. White and K. Koyama: Graphitic Materials Hot-Worked with a Dispersed Liquid Carbide: Thermal and Electrical Conductivity 394
72. R. W. Heckel and J. L. Youngblood: X-Ray Line Broadening Study of Explosively Shocked MgO and α-Al_2O_3 Powders 398
73. G. P. Wirtz and M. E. Fine: Precipitation and Coarsening of Magnesioferrite in Dilute Solutions of Iron in MgO 402

Discussions and Notes

E. F. Riebling: Nonideal Mixing in Binary GeO_2-SiO_2 Glasses 406
William R. Cook, Jr.: Structure of δ-Fe_2O_3 (Hydrate) as Proposed by Okamoto 408
Igor Karpenko: Replication of Particulate Al_2O_3 for Examination by the Electron Microscope 408
J. M. Ricker, C. G. Bergeron, and R. J. Eagan: Enthalpy of Fusion of $PbO \cdot 2B_2O_3$ 410

August [No. 8], pp. 411–72

74. Charles R. Manning, Jr., and Robert F. Stoops: High-Temperature Cermets: I, Compatibility 411
75. Charles R. Manning, Jr., and Robert F. Stoops: High-Temperature Cermets: II, Wetting and Fabrication 415
76. L. Stoch: Effect of Cationic Field Strengths on the Liquidus of Oxide Systems 419
77. T. D. Gulden: Deposition and Microstructure of Vapor-Deposited Silicon Carbide 424
78. John W. Moore and Lawrence H. Van Vlack: Preferred Orientation in Microstructures of Eutectics Between Compounds 428
79. R. E. Johnson and Arnulf Muan: Phase Diagrams for the Systems Si-O and Cr-O 430
80. R. C. Rossi: Prediction of the Elastic Moduli of Composites 433
81. J. R. Keski and I. B. Cutler: Initial Sintering of Mn_xO-Al_2O_3 440
82. D. L. Kinser and L. L. Hench: Effect of a Metastable Precipitate on the Electrical Properties of an Li_2O-SiO_2 Glass 445
83. F. E. Wagstaff: Crystallization Kinetics of Internally Nucleated Vitreous Silica 449
84. K. R. Janowski and R. C. Rossi: Mechanical Degradation of MgO by Water Vapor 453
85. D. E. Stellrecht, M. S. Farkas, and D. P. Moak: Compressive Creep of Uranium Carbide 455
86. Paul Cucka and R. F. Oliva: X-Ray Measurement of Strain in Quartz Particles of Whiteware Bodies 458

Discussions and Notes

F. J. Salzano, S. Aronson, and A. Ingraham: Comment on Compound Formation in the Lithium-Carbon System 465
Naohiro Soga and Edward Schreiber: Porosity Dependence of Sound Velocity and Poisson's Ratio for Polycrystalline MgO Determined by Resonant Sphere Method 465
K. V. Krishna Rao, S. V. Nagender Naidu, and Leela Iyengar: Thermal Expansion of Rutile-Type GeO_2 by the X-Ray Method 467
F. A. Nichols: Further Comments on the Theory of Grain Growth in Porous Compacts 468
Victor J. Tennery and Kenneth W. Hang: Heats of Transition in $NaNbO_3$ 469
A. M. Turkalo: Technique for Obtaining Thin Glass Sections for Transmission Electron Microscopy 470
R. E. Mistler and R. L. Coble: Comments on the Use of Log-Log Plots in Analyzing Grain Growth Data 472

September [No. 9], pp. 473–544

87. D. M. Scruggs, L. H. Van Vlack, and W. M. Spurgeon: Reaction Between Nitrogen and Spinel in Chromium 473
88. G. H. Price, W. I. Stuart, and D. G. Walker: Crystallite Growth of Beryllium Oxide Powders and Its Inhibition by Adsorbed Phosphate 481
89. Walter C. Allen: The Series $MgCr_2O_4$-$MgFe_2O_4$ 485
90. Marcus P. Borom and Joseph A. Pask: Kinetics of Dissolution and Diffusion of the Oxides of Iron in Sodium Disilicate Glass 490
91. E. R. Plumat: New Sulfide and Selenide Glasses: Preparation, Structure, and Properties 499
92. A. B. Chase: Habit Changes and Growth Mechanisms of In_2O_3 Grown from PbO-B_2O_3 Melts 507
93. J. R. Harris and D. R. Rossington: Comparison of Surface States of Quartz, Cristobalite, and Silicic Acid 511
94. William R. Cook, Jr.: The CdS-MnS and CdSe-MnSe Phase Diagrams 518
95. T. K. Gupta and R. L. Coble: Sintering of ZnO: I, Densification and Grain Growth 521
96. T. K. Gupta and R. L. Coble: Sintering of ZnO: II, Density Decrease and Pore Growth During the Final Stage of the Process 525
97. Günther H. Frischat: Sodium Diffusion in SiO_2 Glass 528

Discussions and Notes

P. P. Williams: Crystal Structure of a Fluoride Derivative of $12CaO \cdot 7Al_2O_3$ 531
Shigekazu Minagawa, Tadashi Saito, and Tetsuo Gejyo: Growth Patterns on the Surface of Alumina Grown by Chemical Vapor Deposition 532
S. Natansohn and D. H. Baird: Effect of Cd-for-Zn Substitution on Magnetic Properties of Manganese Zinc Ferrites 533
R. K. Kirby and B. D. Rothrock: Thermal Expansion of Vitreous Selenium from $-190°$ to $+30°C$ 535
H. Neumann and H. P. J. Wijn: Polycrystalline Hexagonal Fe_2W with Varying Ferrous Contents 536
Fennimore N. Bradley: Effect of Grain Size on Discoloration of Barium Titanate Powder 537
William R. Manning and Orville Hunter, Jr.: Porosity Dependence of Young's and Shear Moduli of Polycrystalline Yttrium Oxide 537
Robert Feigelson: Flux Growth of Type RVO_4 Rare-Earth Vanadate Crystals 538
Gary Geschwind: Low-Temperature Electrical Conductivity in Calcium-Doped Lithium Fluoride 539
Edward Schreiber: Comment on the Elastic Modulus-Porosity Relation 541
G. M. Loiacono and B. Michelman: Growth and Properties of $K_4Nb_6O_{17}$ 542
J. A. Duffy and M. D. Ingram: Environment of Cobalt(II) in Nitrate Glass 544

October [No. 10], pp. 545–610

98. F. M. Ernsberger: Role of Densification in Deformation of Glasses Under Point Loading 545
99. M. J. Bannister: Shape Sensitivity of Initial Sintering Equations 548
100. Ronald C. Garvie: The Cubic Field in the System CaO-ZrO_2 553
101. John H. Hensler and G. V. Cullen: Stress, Temperature, and Strain Rate in Creep of Magnesium Oxide 557
102. T. S. Elleman, L. D. Mears, and R. P. Christman: Rare Gas Diffusion in Cesium Iodide: Use of Fission Recoil Doping Techniques 560
103. V. G. Bhide, M. S. Hegde, and K. G. Deshmukh: Ferroelectric Properties of Lead Titanate 565
104. John J. Brennan and Joseph A. Pask: Effect of Nature of Surfaces on Wetting of Sapphire by Liquid Aluminum 569
105. P. J. Ficalora, O. M. Uy, D. W. Muenow, and J. L. Margrave: Mass Spectrometric Studies at High Temperatures: XXIX, Thermal Decomposition and Sublimation of Alkali Metal Sulfates 574
106. Kamran Aykan: A Novel Lead Titanate, $PbTi_3O_7$ 577
107. G. L. Kulcinski: High-Pressure Induced Phase Transition in ZrO_2 582
108. P. L. Roeder, F. P. Glasser, and E. F. Osborn: The System Al_2O_3-Cr_2O_3-SiO_2 585
109. Shoichi Okamoto: Structure of δ-FeOOH 594

Discussions and Notes

Mark A. Stett and R. M. Fulrath: Strengthening by Chemical Bonding in Brittle Matrix Composite 599
Michael Tokar: Increase in Preferred Orientation in Lead Ferrite by Firing 601
Paul L. Gutshall and Gordon E. Gross: Fracture Energy of Polycrystalline Beryllium Oxide 602
J. R. Archer, W. E. Moody, and A. L. Stanford, Jr.: Third-Order Elastic Constant c_{111} in Lithium Fluoride 603
Ivan B. Cutler and Roy E. Henrichsen: Effect of Particle Shape on the Kinetics of Sintering of Glass 604
Sarkis G. Ampian and Robert L. Myklebust: Solid State Synthesis of Na_2ZrSiO_5 605
Sarkis G. Ampian: X-Ray and Optical Crystallographic Data for Na_2ZrO_3 607
Amiya K. Goswami: Contribution of Grain Boundary to Optical Dielectric Constant of Barium Titanate 609
R. H. Dungan: Thermodynamic Relations Between Composition and Ferroelectric-to-Antiferroelectric Phase Transitions 609

November [No. 11], pp. 611–70

110. D. J. Barber and N. J. Tighe: Neutron Damage in Single Crystal Aluminum Oxide 611
111. Jack L. Henry, Robert Blickensderfer, and Gerald D. Thompson: Quaternary System U-C-O-N at 1700°C: Phase Relations in the Low-Nitrogen Region 617
112. Taki Negas and Charles A. Sorrell: Silica Transformations in the System PbO-SiO_2 622
113. Tsuneharu Nitta: Properties of Sodium-Lithium Niobate Solid Solution Ceramics with Small Lithium Concentrations 626
114. A. C. D. Chaklader, A. M. Armstrong, and S. K. Misra: Interface Reactions Between Metals and Ceramics: IV, Wetting of Sapphire by Liquid Copper-Oxygen Alloys 630
115. T. P. Seward III, D. R. Uhlmann, and David Turnbull: Development of Two-Phase Structure in Glasses, with Special Reference to the System BaO-SiO_2 634
116. M. F. Berard, C. D. Wirkus, and D. R. Wilder: Diffusion of Oxygen in Selected Monocrystalline Rare Earth Oxides 643
117. R. E. Tressler, F. A. Hummel, and V. S. Stubican: Pressure-Temperature Study of Sulfospinels 648
118. W. Ostertag, G. R. Fischer, and J. P. Williams: Thermal Expansion of Synthetic β-Spodumene and β-Spodumene–Silica Solid Solutions 651
119. M. L. Gimpl, A. D. McMaster, and N. Fuschillo: Influence of Orientation on Properties of Grain Boundaries in NaCl 655
120. M. K. Murthy, L. Long, and J. Ip: Studies in Germanium Oxide Systems: IV, Phase Equilibria in the System K_2O-GeO_2. 661

Discussions and Notes

B. M. Warmkessel and C. J. Kevane: Platinum Contamination and Reduction of Cerium Oxide 663
D. W. Jones, R. S. Matthews, K. Ruddlesden, and D. J. Williams: Proton Magnetic Resonance in Borate Glasses 664
Amiya K. Goswami: Absolute Reflective Spectra of Ceramic Barium Titanate 666
David E. White and Robert J. Beals: Dry-Pressing of a Urania Pycnometer 666
G. J. Copley: Electrical Polarization During Internal Friction Measurements in Alkali Silicate Glass 667
Victor J. Tennery and Kenneth W. Hang: Role of Certain Impurities in Heats of Transition of $PbZrO_3$ 668
K. H. Olsen and G. C. Nicholson: Anomalous Sintering Behavior as Revealed by In Situ Electron Microscopy 669

December [No. 12], pp. 671–731

121. Victor J. Tennery, Kenneth W. Hang, and Richard E. Novak: Ferroelectric and Structural Properties of the $Pb(Sc_{1/2}Nb_{1/2})_{1-x}Ti_xO_3$ System 671
122. Charles A. Sorrell: Fusion and Vaporization Characteristics of $ZrTe_3O_8$ 674
123. Satyabrata Ray and G. M. Muchow: High-Quartz Solid Solution Phases from Thermally Crystallized Glasses of Compositions $(Li_2O,MgO)\cdot Al_2O_3\cdot nSiO_2$ 678
124. R. A. Gdula: High-Field Losses of Adulterated Lead Zirconate-Titanate Piezoelectric Ceramics 683
125. James F. Shackelford and William D. Scott: Relative Energies of [$\bar{1}$100] Tilt Boundaries in Aluminum Oxide 688
126. Olaf Muller, Rustum Roy, and William B. White: Phase Equilibria in the Systems NiO-Cr_2O_3-O_2, MgO-Cr_2O_3-O_2, and CdO-Cr_2O_3-O_2 at High Oxygen Pressures 693
127. Hiroaki Yanagida and F. A. Kröger: The System Al-O 700
128. Karl E. Spear and James M. Leitnaker: A Consistent Set of Thermodynamic Values for Plutonium Mononitride 706
129. Donald R. Messier: Evaporation of Hypostoichiometric Plutonium Dioxide from 2070° to 2380°K 710
130. M. Shimada, S. Kume, and M. Koizumi: Possible Existence of Dense Ferrimagnetic Perovskite Allotropic Form of Yttrium Iron Garnet 713
131. Taki Negas: The System PbO-Chromium Oxide in Air 716
132. D. K. Nath and F. A. Hummel: Crystal Field Studies of Co^{2+} in α-$Zn_3(VO_4)_2$ 720

Discussions and Notes

D. W. Budworth: Comments on "Observations on 'Pressure Sintering of NaCl and Other Ionic Materials' " 722
V. G. Hill, L. L. Y. Chang, and R. I. Harker: Subsolidus Stability Relations in the System $KTaO_3$-$KNbO_3$ 723
C. S. Morgan: Comment on "Dorn Method in the Study of Initial Phase of Uranium Dioxide Sintering" 724
J. J. Bacmann: A Reply 724
Author Index to *The Journal* 725
Subject Index to *The Journal* 727

Instructions for Preparation of Papers and Notes ..... **Back Cover, November Journal**

CERAMIC ABSTRACTS

1968

F. P. Reid, *Publisher and General Secretary*
Herbert Insley, *Editor*
Mary J. Gibb, *Associate Editor*
Gertrude M. Busick, *Assistant Editor*
Virginia Benedict, *Editorial Assistant*
Donna Pinto, *Editorial Assistant*
Jeanne C. Bonham, *Indexer*

Committee on Publications: W. J. Smothers, *Chairman;*
Seymour L. Blum, Clarence L. Babcock, E. F. Osborn, and, ex officio,
Herbert Insley, E. E. Mueller, and F. P. Reid

Technical Adviser: R. S. Sheldon

Compiled by

The American Ceramic Society
4055 North High Street
Columbus, Ohio 43214

ABSTRACTERS FOR 1968

I. A. Aksay—U. S.
Abraham Aladjem—Israel
Eugene Aleshin—U. S.
Wilfred Ashworth—England
D. J. Barbour—U. S.
M. P. Bauleke—U. S.
M. D. Beals—U. S.
K. E. Bell—Canada
Adli Bishay—Egypt
J. J. Borbas—U. S.
J. G. Brady—Canada
N. F. Cerulli—U. S.
John Chown—England
G. W. Cleek—U. S.
J. J. Diamond—U. S.
F. V. DiMarcello—U. S.
E. J. Duff—England
R. H. Edwards—U. S.
Marie Farnsworth—U. S.
Kanekoto Fujii—Japan
J. E. Gillott—Canada
F. W. Glaze—U. S.
H. T. Harrison—U. S.
H. S. Hartmann—U. S.
M. P. Haydon—U. S.
R. O. Heckroodt—South Africa
C. I. Helgesson—Sweden
Stanislav Hnilicka—Denmark
Herbert Insley—U. S.
R. H. Insley—U. S.
B. Z. Kamich—U. S.
Keramos, Ohio State University—U. S.
Herbert Kornguth—U. S.
A. M. Lacy—U. S.
M. P. Lepie—U. S.
S. A. Lindroth—Sweden
J. R. Little—U. S.
Luigi Luciani—Italy
V. V. Mirkovich—Canada
Sylva Modry—Czechoslovakia
M. K. Murthy—Canada
A. W. Norris—England
J. J. Nunes—U. S.
L. S. O'Bannon—U. S.
V. R. Palmeri—U. S.
G. A. L. Peersman—Netherlands
L. N. Perkins—U. S.
W. W. Perkins—U. S.
V. S. Ramachandran—Canada
M. Safdar—West Pakistan
Don Satas—U. S.
J. O. Semmelman—U. S.
Harold Severin—U. S.
J. F. Shackelford—U. S.
Kenneth Shaw—England
R. R. Shaw—U. S.
Shigeyuki Somiya—Japan
K. F. Sporek—U. S.
M. A. Stett—U. S.
Helmut Stoll—Germany
J. A. Sugden—England
V. D. Svikis—Canada
Kazutaka Takizawa—U. S.
Ferenc Tamas—Hungary
J. W. Taylor—Scotland
R. L. Thakur—India
Minoru Tomozawa—U. S.
W. A. Weiss—U. S.
T. B. Weston—Canada
J. H. Weymouth—Australia
J. B. Whitney—U. S.
D. T. Williams—U. S.
W. O. Williamson—U. S.
Kazuo Yamasaki—Japan

CERAMIC ABSTRACTS

December 1968 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1968

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates the position of the abstract on the page.

Abbakumov, V. G. Computing the heating and cooling of refractories in a high temperature tunnel kiln, (9) 267*a*.
Abbas, Y. See Amin, R.
Abbey, S. See Forman, S. A.
Abbott, T. S. Rotary heat exchanger with a chain drive, P (9) 278*c*.
Abdeeva, M. I., and Rafikov, T. K. Compounds of copper and iron with antimony, (4) 106*f*.
Abdella, H. H. Spark plug seal having a lower coefficient of expansion than the ceramic insulator core, P (1) 19*d*.
Abe, H. See Muramori, K.
Abe, R. See Koide, N.; Sawada, A.
Abe, S. See Kaneko, T.
Abeck, W. See Hund, F.
Abel, W. R., Anderson, A. C., Black, W. C., and Wheatley, J. C. Thermal equilibrium between liquid ^3He and powdered cerium magnesium nitrate at very low temperatures, (10) 326*j*.
Abernathy, J. H., Jr. See Wisman, E. C.
Abex Corp. Hammer tip and clamp, P (7) 214*d*.
Abkowitz, M., and Lowe, I. J. Pulsed-NMR study of protonic relaxation in paramagnetic and antiferromagnetic $CoCl_2 \cdot 6H_2O$, (8) 256*i*.
Abraham, M. M. See Weeks, R. A.
Abraham, M. M., Boatner, L. A., Finch, C. B., Lee, E. J., and Weeks, R. A. Paramagnetic resonance of Gd^{3+} in CeO_2 single crystals, (8) 255*f*.
Abraham, R. P. Dust sampling and air testing in industry, (4) 101*i*.
Abrahams, S. C. Crystal structure of the transition-metal molybdates and tungstates (I) paramagnetic α-$MnMoO_4$; (II) diamagnetic $Sc_2(WO_4)_3$; (III) diamagnetic α-$ZnMoO_4$, (11) 351*e*.
Abrahams, S. C., and Bernstein, J. L. Crystal structure of paramagnetic $DyMn_2O_5$ at 298°K, (11) 351*e*.
Abrahams, S. C., Reddy, J. M., and Bernstein, J. L. Crystal structure of piezoelectric ferromagnetic gallium iron oxide, (5) 137*g*.
Abrahamson, E. P., II. Electron concentration and metallic properties, B (4) 121*g*.
Abraitis, R. Gaseous erosion of zirconium oxide refractories (III) effect of potassium additive on erosion resistance in the stream of products of combustion, (5) 132*c*.
Abraitis, R., Griniute, G., and Majauskas, J. Gaseous erosion of zirconium oxide refractories (II) changes at the surface of refractories, (5) 132*c*.
Abramovici, R., and Enache, M. Aluminothermic production and study of mixed ceramic bodies in the system Al_2O_3-$MoSi_2$, (6) 172*e*.
Abramowitz, A. Advances in potentiometry, (11) 346*b*.
Abramowitz, S. See Levin, I. W.
Abrams, M. S., and Gustaferro, A. H. Fire endurance of concrete slabs as influenced by thickness, aggregate type, and moisture, (10) 294*g*.
Abrikosov, N. Kh. See Shelimova, L. E.
Abrosimov, V. A. See Boguslavskii, I. A.
Accary, A. See Cappelaere, M.; Magnier, P.; Trouve, J.; Val, C.
Accary, A., Treillou, A., and Trouve, J. Furnace for manufacturing ingots or bars of metal or alloys, particularly bars of uranium carbide [under vacuum], P (9) 278*c*.
ACF Industries, Inc. Method of forming a permeable structure for aerating bulk materials, P (4) 102*a*. Pneumatic outlet for unloading particulate materials, P (2) 53*f*.
Achar, B. N. N. See Brindley, G. W.
Achard, J. C. Reduction and volatilization of rare earth oxides, (1) 31*f*.
Achenbach, E. Measurement of local heat transfer coefficients in turbulent boundary layers with forced convection, (6) 167*h*.
Achenbach, G. D. See Smith, R. T.
Achenbach, P. R. Performance criteria for building components and systems, (9) 263*a*.
Achjan, A. M. Structure of porcelain during the stages of production, (2) 48*j*.
Achkio, A. A. Preliminary pressing of bent glass laminated assemblies, P (2) 42*c*.
Ackerman, S. C. Incandescent lamp with a tungsten filament with tantalum imbedded in the surface to act as a gettering agent, P (1) 18*f*.
Ackermann, R. J. See Gebert, E.
Ackermann, R. J., Faircloth, R. L., Rauh, E. G., and Thorn, R. J. Evaporation behavior of neptunium dioxide, (4) 110*h*.
Ackermann, R. J., Rauh, E. G., and Thorn, R. J. Comments on pressure of uranium over U-UO_2 system, (3) 79*j*.
Acloque, P., and Morain, M. Secondary processes in the fracture of tempered glass, (7) 197*g*.
Adachi, K. See Tsuchihashi, S.
Adachi, S. See Tanemura, P.
Adam, G., and Gibbs, J. H. Temperature dependence of cooperative relaxation properties in glass-forming liquids, (5) 129*c*.
Adams, D. R. Improved abrasives, P (7) 193*f*.
Adams, N., Mukerjee, T., and Smith, J. M. Semiconductor tunnel diode device, P (7) 210*g*.
Adams, R. B., and Stuart, W. I. Effect of adsorbed sulfate and fluoride on the density of hot-pressed beryllium oxide, (1) 28*g*.
Adams, R. G. Ion exchange of glass fibers, P (8) 235*c*. Treatment of fibrous glass, P (7) 199*b*.
Adams, R. H. Method and apparatus for forming an end profile on asbestos-cement pipe, P (8) 240*i*. See Quint, S. M.
Adamson, D. L., Stephens, J. D., and Tuddenham, W. M. Application of mineralogical principles and infrared spectra in development of spectrographic techniques, (1) 20*i*.
Adamson, L. G., Gingley, D. W., Ainsworth, H. R., and Chilingar, G. V. Electrochemical strengthening of clayey sandy soils, (1) 24*i*.
Addamiano, A. Preparation and photoluminescence of silicon carbide phosphors doped with group IIIA elements and/or nitrogen, (7) 207*h*. Silicon carbide luminescent material, P (4) 101*a*. Single crystal phosphide production, P (7) 210*h*.
Addison, W. E., and Sharp, J. H. Redox behavior of iron in hydroxylated silicates, B (5) 160*c*.
Adelmeier, E. Rhineland stoneware—a notable exhibition, (10) 293*j*.
Adelsberg, L. M., and Cadoff, L. H. Chemical diffusion and phase equilibria in the vanadium-carbon system above 1900°C, (5) 150*a*.
Adelsberg, L. M., St. Pierre, G. R., and Speiser, R. Kinetics of the oxidation of tantalum by water vapor, (6) 186*g*.
Ado, K. See Nobuoka, S.
Adwick, A. G., and Reilly, W. S. C. Role of oxygen/metal ratio during the sintering and oxidation of some uranium-plutonium oxides, B (7) 226*e*.
Aerojet-General Corp. Glass fiber composition, P (4) 94*a*. Impregnation and partial polymerization of resin coated wound glass fiber package, P (8) 235*b*.
Aerovox Corp. Process for manufacturing multilayer ceramic capacitors, P (10) 311*g*.
Afflerbach, H. W. Correlation between warpage and chippage observed in porcelain enamel systems, (9) 262*i*.
Affri, R. Penetration-body hardness testing, P (5) 147*b*.
Agapova, L. K., and Pankova, N. A. Speed of bubbles and diagram of the fining process, (11) 335*e*.
Agarkov, A. S. See Matveev, M. A.
Agarwal, M. K. See Patel, A. R.
Agarwal, V. S., and Sinha, K. P. Specific surface area and water absorption capacity of foundry sands, (6) 174*e*.
Agathonikou-Rokofyllou, E., Costikas, A., and Manos, C. Formation of aggregate centers in additively colored KCl, (8) 253*i*.
Agency of Industrial Science & Technology. Radiation process of deforming glass fiber materials, P (5) 130*d*.
Aggarwal, K. R. See Rawal, N. C.
Aggarwal, P. S., Bishui, B. M., and Sen, S. K. Absorption of atmospheric CO_2 in tricalcium aluminate hexahydrate, (2) 36*b*.
Agrawal, V. K. See Chandra, S.
Agrawal, V. K., Chandra, K., and Parshad, R. Broadband microwave ferrite devices—isolators and circulators, (6) 176*b*.
Agrostroj Prostejov, Narodni Podnik. Apparatus for continuous recovery and separation and cleaning of grit, P (9) 263*e*.
Agule, B. J. See Sedgwick, T. O.
Ahlert, R. H. See Milch, A.
Ahmad, S. See Elahi, Kh. M.
Ahmed, S. M. Measurement of the surface areas of powders by krypton gas adsorption method—construction and operation of the apparatus, (1) 21*g*.
Ahrland, S., Albertsson, J., Ainas, A., Hemmingsson, S., and Kullberg, L. Inorganic ion exchangers (V) effect of water content on the sorption of zirconium phosphate gels of different crystallinity, (7) 218*d*.
Ahuja, D. P. Refractory brick and furnace lining, P (2) 48*d*.
Aiken, H. H., Birrell, R. W., Kerkeslager, D. A., and Sites, L. K., Jr. Automatic X-ray apparatus for crystal Z-axis orientation determination and sorting, P (5) 146*j*.
Aiken Industries, Inc. Automatic X-ray apparatus for crystal Z-axis orientation determination and sorting, P (5) 146*j*.
Ainscough, J. B. Effect of electrical conduction in UO_2 on the measurement of its high temperature thermal conductivity as determined by radial flow techniques, (4) 108*i*.
Ainslie, N. G. Preparation of high-purity materials, P (3) 74*a*.
Ainsworth, H. R. See Adamson, L. G.
Air Preheater Co., Inc. Heat and corrosion resistant coating composition, P (9) 263*b*.
Air Products & Chemicals, Inc. Alumina particles and method of preparation, P (3) 77*i*. Clay-supported cracking catalyst, P (8) 250*b*. Copper chromite-alkali metal oxide high surface area hydrogenation catalyst, P (6) 183*e*. Cracking catalyst preparation, P (8) 251*a*. Packaging system, P (5) 148*g*. Preparation of synthetic faujasite containing exchangeable magnesium cations, P (5) 148*j*.
Air Reduction Co., Inc. Method of making an electrical resistor, P (8) 245*j*. Multiple section graphite electrode, P (4) 97*d*. Resistor substrate having integral metal terminations, P (4) 101*c*. Thallium oxide glaze containing an additive of ruthenium oxide, P (2) 52*g*. See Baker, J. E., Co.
Air Sifters, Inc. Classifying system, P (8) 247*a*.
Airey, A. C. See Ruddlesden, S. N.
Aitken, E. A. Oxidation kinetics of solid solutions of urania-yttria, (4) 113*e*.
Aitkenhead, W. C. See Grunig, J. K.

Aiyama, Y. Magnetic structures in spinel B-site lattices—a proposal of linear antiferromagnetism in $ZnMn_2O_4$, (10) 323*a*. See Tanaka, M.

Aizu, K. Possible species of ferroelectrics, (11) 355*d*. Statistical theory of ferroelectricity based on the concept of ferroelectric modes of lattice vibration, (10) 325*d*.

Akashi, T., Takahashi, M., Yamauchi, F., Tsubouchi, N., and Ohno, T. Iridium and chromium doped lead zirconate titanate piezoelectric ceramic composition, P (6) 177*f*. Lead zirconate-titanate-stannate piezoelectric ceramic containing thorium and iridium, P (1) 18*f*. Piezoelectric PZT ceramic with chromium and thorium additives, P (7) 209*i*. Piezoelectric PZT containing rhodium, P (7) 209*j*.

Akashi, T., and Takamizawa, H. Tantalum doped nickel-zinc ferrite, P (1) 19*a*.

Akbar, M. See Safdar, M.

Aken, J. E. van, Prins, J. A., Reijnhart, R., and Tuinstra, F. Screw and ring molecules in amorphous and crystalline chalcogens S, Se, Te, (7) 221*h*.

Akeret, R. See Solomir, J. G.

Akimoto, S. See Sawaoka, A.; Sugawara, F.; Syono, Y.

Akiyama, K. See Ichinohe, E.; Takemoto, T.

Akopov, F. A. See Poluboyarinov, D. N.

Aktiebolaget Bahco. Method and apparatus for fractionating particulate materials, P (10) 316*a*.

Aktiebolaget Kanthal. Binding means useful in the manufacture of shaped bodies, P (11) 339*j*. Electric heating resistors, P (1) 12*c*. Heat resistant and oxidation-proof bodies containing silicon carbide and molybdenum silicide, P (5) 135*c*. Heat-resistant and oxidation-proof materials containing molybdenum disilicide, P (1) 12*h*.

Aktiebolaget Svenska Flaktfabriken. Wet separator with venturi-shaped gas channels, P (1) 20*f*.

Aktiebolaget Tabougnar. Walking beam furnace for effecting different feed speeds of the charge, P (6) 182*c*.

Aktiebolaget Tudor. Electrostatic precipitator control circuit, P (7) 211*b*.

Akutagawa, W. See Zanio, K.

Aladjem, A. Preparation of labeled refractory oxide films, (10) 315*i*.

Albertson, W. C., and Cahlik, J. C. Method and apparatus for supporting and gaging an article, P (5) 130*f*.

Albertsson, J. See Ahrland, S.

Albinak, M. J., and Turner, W. H. Method for controlling the reduction of metallic ions in glass compositions, P (1) 9*j*. Multicolor photoluminescent glass systems, P (6) 178*b*.

Al'bota, N. K. See Rudi, V. P.

Albrecht, W. L., and Mindick, M. Nonaqueous silica sols and method for preparing, P (2) 56*j*.

Albright, G. P. See Nessim, D. J.

Albright, M. W. See Sullivan, S. J.

Alcock, C. B. Vaporization under vacuum of ceramic oxides at high temperatures, (6) 190*e*.

Alcock, C. B., and Peleg, M. Vaporization kinetics of ceramic oxides near 2000°C, (1) 33*g*.

Aldcroft, D., and Bye, G. C. Crystallization processes in aluminum hydroxide gels—formation and thermal decomposition of nordstrandite, B (7) 226*c*.

Aldred, F. H. Why test refractories? (10) 304*a*.

Aldridge, H. E. Simple gas-fired furnace, (9) 278*b*.

Alegre, R., and Debray, L. Determination of phases by X-ray diffraction—application to the cement industry, (6) 164*g*.

Aleinikov, F. K. See Toropov, N. A.

Aleinikov, F. K., and Parfenov, V. A. Strengthening of glasses by etching, (5) 128*j*.

Aleixandre Ferrandis, V., and Gonzalez Pena, J. M. Forsterite from Spanish serpentines (III) action of mineralizers on serpentines of Barranco de San Juan (Granada), (10) 317*g*.

Aleksandrova, T. A., and Prokhorova, I. Ya. Effect of tar viscosity on properties of tarred dolomite-magnesite refractories, (9) 267*i*.

Alekseeva, E. A. See Dombrovskaya, N. S.

Aleshin, S. M. Problem of false correlation, (9) 277*b*.

Alessi, V. J. Method and apparatus for making a circuit component [diode] with a circuit element and wire leads sealed in a glass sleeve, P (5) 141*f*.

Alexander, G. B., and Lambert, J. B. Process for producing alloys containing chromium and dispersed refractory metal oxide particles, P (10) 305*b*.

Alexander, J. H. See Joyce, R. J.

Alexander, R. B. Method and apparatus for handling and placing tile bodies in precise locations, P (2) 49*a*.

Alexander, W. O. Competition of materials, B (11) 358*i*.

Alexanian, C., Morel, P., and Le Bouffant, L. Infrared absorption spectra of minerals, (6) 180*f*.

Alexiades, C. A., and Jackson, M. L. Quantitative clay mineralogical analysis of soils and sediments, B (8) 259*h*.

Alfa-Laval AB. Moisture content measuring device including capacitor electrodes differing in size, P (10) 316*c*.

Alferieff, M. E. See Duke, C. B.

Alfredson, P. G. See Anastasia, L. J.

Alfredson, P. G., and Cairns, R. C. Development of coated fuel particles for BeO-based fuels, (4) 96*b*.

Ali, A. S. See Qureshi, A. A.

Alkemade, C. T. J. See Kalff, P. J.

Allam, D. S., and Pitt, K. E. G. Structure of evaporated silicon oxide films and its effect on the electrical and optical properties, (10) 308*d*.

Allan, B. W. Process of treating pigmentary TiO_2, P (8) 251*g*.

Allbutt, M., and Dell, R. M. Chemical aspects of nitride, phosphide, and sulfide fuels, (7) 200*c*.

Allegrini, A. P., Puskar, V., and Greene, E. W. Calcination of clay, P (8) 250*f*.

Allen, A. W. See Forlano, R. J.

Allen, E. M., Dye, C. G., and Smrdel, J. A. Process for packaging siliceous pigments, P (9) 279*c*.

Allen, F. M. Bowl adjustment for crushers, P (11) 349*f*.

Allen, L. R., and Steeves, R. W. Vacuum coated product, P (11) 336*h*.

Allen, R. D. Thermal conductivity of brazed expanded pyrolytic graphite to 700°C, (9) 269*f*.

Allen, S. G. See Setchfield, J. B.

Allen, S. J., Jr., Loudon, R., and Richards, P. L. Two-magnon absorption in antiferromagnetic MnF_2, (10) 327*a*.

Allen, W. C. Series $MgCr_2O_4$-$MgFe_2O_4$, (10) 325*f*.

Allendorf, H. D. See Rosner, D. E.

Allersma, T., Hakim, R., Kennedy, T. N., and Mackenzie, J. D. Structure and physical properties of solid and liquid vanadium pentoxide, (11) 357*e*.

Allersma, T., and Mackenzie, J. D. Seebeck coefficient of semiconducting oxide glasses, (5) 139*h*.

Alley, J. K., and Johnson, R. C. Synthesis of aluminum borate whiskers, P (2) 48*c*.

Allgemeine Elektrizitaets-Ges. See Deutsche Edelstahlwerk Akt.-Ges.

Allied Chemical Corp. Consolidation by chemical sintering, P (4) 97*d*. Process for decomposition of aluminum nitrate nonahydrate, P (5) 135*h*. Process of producing ultrafine metal oxides, P (5) 136*d*. Process for the selective recovery of alumina from ores, P (9) 279*e*. Process of separating nondiamond carbonaceous material from synthetic diamantiferous products, P (9) 261*h*. Production of rigid shapes of refractory metals by decomposition of the metal hexafluoride in the interstices of a green compact, P (6) 175*c*.

Allinson, I. M., and Hollaway, L. C. Stresses in fiber-reinforced materials, (3) 87*c*.

Allis-Chalmers Mfg. Co. Apparatus for controlling coating depth in a balling drum, P (2) 53*h*. Cermet and ceramic fuel element, P (7) 204*h*. Fluid pressure operated adjustment and release for gyratory crushers and the like, P (11) 349*h*. Method [solder] of forming ohmic contacts in semiconductor devices, P (11) 344*f*. Rotary heat exchanger with a chain drive, P (9) 278*c*. Rotary kiln thermocouple collector ring and brush assembly, P (11) 348*h*. Spiderless gyratory crusher having frictionless bearings, P (8) 251*i*. Spiderless gyratory crusher with relief valve system, P (6) 183*e*. Superconductor having variable transition temperature, P (4) 101*d*.

Allmanna Svenska Elektriska Aktiebolaget. Semiconductor devices, P (10) 311*c*.

Allnatt, A. R., and Chadwick, A. V. Thermodynamics of the Soret effect in ionic crystals, (3) 88*a*.

Allpress, J. G., and Sanders, J. V. Structure and orientation of crystals in deposits of metals on mica, (10) 308*h*.

Al-Mahdi, A. A. K. See Al-Obaidi, M. S.

Almenningen, A., Bastiansen, O., Haaland, A., and Seip, H. M. Structure determination of free molecules by electron diffraction, (5) 158*b*.

Alnas, A. See Ahrland, S.

Alnor Instruments Div., Illinois Testing Laboratories. Ultrasonic pyrometer, P (2) 55*h*.

Al-Obaidi, M. S., and Al-Mahdi, A. A. K. Semiquantitative estimation and separation of cobalt(II) and copper on the ultramicroscale, (3) 76*e*.

Alper, A. M. Interrelation of phase equilibria, microstructure, and properties in fusion-cast ceramics, 3 (7) 226*f*.

Alper, A. M., and Doman, R. C. Refractory with periclase-based stabilized solid solution, P (1) 14*a*.

Alper, A. M., and McNally, R. N. Basic fused refractory material, P (10) 304*b*.

Alpha, S. Classifying system, P (8) 247*a*.

Alpha Microelectronics Co., Inc. Integrated circuit sealing method and structure, P (2) 51*e*.

Al'takh, O. L. See Kitaigorodskii, I. I.; Pavlushkin, N. M.

Altenschoepfer, T. Behavior of decorated porcelain under conditions of machine washing, (1) 15*a*.

Alter, H. W., and Anderson, C. R. Irradiated nuclear fuel recovery, P (4) 97*f*.

Altman, D. E. See Geller, M.

Altschuler, Z. S., Dwornik, E. J., and Kramer, H. Genesis of kaolinite from montmorillonite by weathering—structural and morphological evidence of transformation (abstract), B (6) 191*e*.

Aluminum Co. of America. Dry grinding of alumina, P (4) 105*a*. Production of fused alumina, P (11) 340*j*.

Alvarez, J. M. G. See Garcia Alvarez, J. M.

Alviset, L. Drying of clays and bodies—water diffusion phenomena, (6) 172*a*. Ease of drying of heavy clays, B (9) 291*e*.

Alyamovskii, S. I. See Volkova, N. M.

Alyamovskii, S. I., Shveikin, G. P., and Gel'd, P. V. Higher oxides of niobium, (3) 81*g*.

Alyanakyan, S. A. See Reisman, A.

Amano, C. K., and Taylor, M. L. Process for the selective recovery of alumina from ores, P (9) 279*e*.

Amato, I. Compatibility studies on UO_2–Nb–H and UO_2–Ta–H systems, (6) 172*j*. See Giuliani, S.

Amato, I., and Ardizzone, L. Preparation of UO_2–Nb and UO_2–Ta cermet fuel by vapor deposition of the metal in a fluidized bed, (6) 173*a*.

Amato, I., Ardizzone, L., and Ravizza, M. Effect of organic additions on columnar grain growth of sintered uranium dioxide, (9) 281*i*.

Amato, I., Colombo, R. L., and Balzari, A. M. P. Causes of high temperature substoichiometry in sintered uranium dioxide, (5) 131*i*. Hot-pressing of uranium dioxide, (2) 44*d*. Reaction between tantalum metal and uranium dioxide, (4) 114*h*.

Amato, I., Colombo, R. L., and Grappiolo, G. C. Grain boundary grooving in uranium dioxide, (11) 353*g*.

Amato, I., Colombo, R. L., and Ravizza, M. Hot-pressing of beryllia and zirconia, (2) 44*c*.

Amato, I., Ravizza, M., and Colombo, R. L. Effect of vanadium oxide additions on sintering and grain growth of uranium dioxide, (7) 201*c*.

Ambler, J. F. R. Metallographic evidence for a martensitic transformation in U_3Si, (10) 323*h*.

Ambrogi, R. R. Forced stream feeding through orifice, P (2) 40*g*.

Ambrogi, R. R., and Carmi, A. Method and apparatus for pressing thermoplastic materials, P (3) 65*c*.

Amelinckx, S. See Ruedl, E.; Spyridelis, J.

American Air Filter Co., Inc. Dust collector apparatus, P (1) 20*a*. Plate electrode assembly for electrostatic precipitator, P (6) 179*f*.

American Can Co. Glass container having metal oxide and resin coatings, P (7) 198*f*.

American Concrete Institute, Committee 116. Cement and Concrete Terminology, B (7) 223*h*.

American Cyanamid Co. Digestion of titanium-bearing ores, P (11) 349*g*. Fuel cell with platinum-rhodium containing catalyst, P (4) 105*c*. Preparation of extruded catalysts and catalyst supports containing polyacrylamide, P (1) 25*h*. Process for the oxidation of $TiCl_4$ to produce TiO_2, P (2) 57*a*. Process for TiO_2 pigment production in controlled calcination of basic titanium sulfate, P (4) 105*g*. Production of finely divided oxides by plasma process, P (4) 105*g*. Purification of titanium dioxide pigment with organic sequestering agents, P (10) 318*e*. Semiconductors and devices employing them, P (2) 52*e*, P (3) 74*b*. Single phase ternary semiconducting compounds of silver or copper, thallium, and sulfur or selenium, P (11) 345*g*. Synergized lanthanide chelate photoluminescent composition, P (7) 210*b*. Titanium dioxide pigment and preparation, P (1) 26*b*.

American Felt Co. Glass polishing head having a detachable felt pad, P (1) 9*c*.

American Instrument Co., Inc. Electrical porosimeter, P (6) 181*e*. Porosimeter, P (6) 181*f*.

American Lava Corp. Ceramic dielectrics, P (4) 99*f*. Ceramic-to-metal seal, P (8) 244*d*. Multilayered electrical capacitor, P (7) 209*h*.

American Machine & Foundry Co. Proton-excited soft X-ray [chemical] analyzer having a rotatable target for selectively directing the X-rays to different detectors, P (5) 147*b*.

American Olean Tile Co., Inc. Tile feeding apparatus for depositing tiles on tile boards, P (7) 206*j*.

American Optical Co. Apparatus for making fiber energy-conducting devices, P (11) 335*e*. Apparatus for making fiber optical image transfer devices, P (6) 170*d*. End pumped laser structures employing immersion optics, P (8) 244*b*. Fiber optical image-encoding-decoding device, P (4) 94*h*. Fiber type energy-conducting structures, P (5) 129*g*. High resolution filter for laser-emissive energy, P (6) 177*d*. Laser amplifier device, P (11) 343*j*. Method for forming image-transfer devices embodying light-conducting fibers and light-absorbing filaments, P (9) 265*b*. Method of making energy-conducting components formed of fiber elements, P (2) 41*e*. Method of making fiberscopes, P (8) 235*h*. Method of making fine adjustment in numerical aperture of fiber optical devices, P (11) 336*g*. Method of making optical elements using ultrasonic vibration, P (11) 336*h*. Optical frequency harmonic generating structure, P (11) 336*d*. Quantum counters, P (7) 199*f*. Sealing porosity of fiber faceplates by yttrium resinate, P (7) 199*a*. Variable density light transmitting device, P (10) 301*b*.

American Potash & Chemical Corp. Process of treating pigmentary TiO_2, P (8) 251*g*. Process for treating rare earth-fluorine materials, P (3) 74*d*. Pyrohydrolytic attack of rare earth fluocarbonate ores, P (7) 215*b*.

American Radiator & Standard Sanitary Corp. Apparatus for testing strain, P (5) 146*i*.

American Saint Gobain Corp. Packaged plate glass, P (2) 42*a*.

American Standard, Inc. Method for casting articles, P (11) 341*e*. Perineal bath, P (7) 206*i*. Plumbing fixture installation, P (5) 137*c*. Settling system, P (5) 144*f*.

Amerongen, H. van. Clay as a raw material for the heavy clay industry, (2) 42*i*. Measurement of the specific surface of clays and its applications, B (7) 226*c*.

Ames, L. L., Jr. Exchange of alkali metal cations on a natural stilbite, (1) 29*b*.

Amin, R., Abbas, Y., Fayek, M., Murasik, A., and Hamouda, I. Neutron diffraction study on magnetoplumbite $PbFe_{12}O_{19}$, B (10) 329*d*.

Amirthalingam, V. δ-U_3O_8, a high temperature modification (II) single crystal studies, (4) 107*d*. See Raj, P.

Ammar, A. A., and Budworth, D. W. Pressure sintering of NaCl and other ionic materials, (1) 31*b*.

AMP, Inc. Connector and insulating sleeve for spark plug or distributor, P (4) 99*g*.

Ampex Corp. Preparation of ferromagnetic $NiMnO_3$, P (8) 245*j*.

Amphenol Corp. Hermetically sealed connector, P (6) 177*d*. Process of making a fired ceramic article and article obtained, P (4) 97*d*. Resistive element and variable resistor, P (2) 52*c*.

Ampian, S. G. X-ray and optical crystallographic data for Na_2ZrO_3, (11) 358*b*.

Ampian, S. G., and Myklebust, R. L. Solid state synthesis of Na_2ZrSiO_5, (11) 356*c*.

Amrein, E., and Gloor, H. R. Model tests on brick, (10) 301*g*. Test-site "Melchtal" of the Testing and Research Station of the Swiss brick industry, (10) 302*b*.

Amsterdam, M. F., Shaikh, M. S., and Tarneja, K. S. Photovoltaic series array comprising *pn* and *np* cells, P (6) 178*c*.

Anaconda Co. Precipitation of beryllium from ores, P (11) 349*d*.

Anaconda Wire & Cable Co. Crystallized glass ceramic coatings, P (9) 263*a*. Electrical apparatus, insulating composition therefor, and method of making, P (1) 4*g*. Electromagnetic structures for high-temperature service, P (5) 141*f*. Glass composition, conductors and coils insulated therewith, and method of making said composition, P (11) 332*h*. Pyrolyzable enamel coated wire comprising manganese and cobalt chelates, P (5) 126*d*.

Ananich, N. I., Mironova, M. L., and Botvinkin, O. K. Relation between the structures of ordinary and porous sodium borosilicate glass, (11) 334*i*.

Anastasia, L. J., Alfredson, P. G., and Steindler, M. J. Selective decladding of nuclear fuel elements, P (1) 14*c*.

Anchor Hocking Glass Corp. Coating process, P (6) 170*g*. Coder for marking randomly spaced containers, P (11) 335*i*. Color ornamentation of glass articles, P (1) 8*g*. Dead plate conveyor for glass machines, P (7) 198*h*. Drive for glass-forming machines, P (9) 265*a*. Liquid-cooled holder for furnace electrode, P (8) 249*h*. Purging mechanism, P (3) 66*b*.

Andersen, T., and Sorensen, G. Solid state reactions with accelerated ions, B (10) 329*c*.

Anderson, A. C. See Abel, W. R.

Anderson, C. H., Weakliem, H. A., and Sabisky, E. S. Selective absorption of circularly polarized light in broad bands by the Zeeman components of divalent thulium in calcium fluoride, (9) 286*j*.

Anderson, C. R. Single cycle irradiated fuel reprocessing, P (3) 69*f*. See Alter, H. W.

Anderson, D. B., August, R. R., Aukland, J. C., and Palmquist, R. L. High frequency diode with small spreading resistance, P (9) 273*d*.

Anderson, D. H. Chemical shifts of ^{207}Pb in perovskite ferroelectrics, (5) 137*i*.

Anderson, E. See Greenberg, S. A.

Anderson, G. S. Method for orienting single crystal films on polycrystalline substrates, P (6) 178*i*.

Anderson, G. W., and Luehrs, F. U., Jr. Structural characterization of and phase separation in vanadate glasses, (9) 264*c*.

Anderson, J. S. See Swanson, A. B.

Anderson, J. W., and Heny, S. L. Method of treating polycrystalline ceramics for polarizing them, P (5) 142*h*.

Anderson, J. W., Heny, S. L., and Joyner, B. L. Transducer assembly for producing ultrasonic vibrations, P (11) 345*c*.

Anderson, J. W., and Joyner, B. L. Method of preparing electroded ceramics for bonding, P (6) 178*a*.

Anderson, O. B., and Mundell, J. M. Stockline lining for a blast furnace, P (4) 97*i*.

Anderson, O. L. Approximate method for computing the isotropic sound velocities using refractive index data, (2) 57*f*.

Anderson, P. J. See Horlock, R. F.

Anderson, R. See Economy, J.

Anderson, R. C. See Dickson, R. W.; Jorgensen, P. J.

Anderson, R. C., and Bartoo, V. S. Apparatus for the manufacture of fibrous material, P (1) 8*j*.

Anderson, R. H. Methods of making seals for pipe joints, P (3) 66*h*.

Anderson, R. H., and Rann, C. H. Gas burners, P (4) 104*c*.

Anderson, W. J. Silicon-containing diffusion coating for ferrous metals, P (11) 333*b*.

Anderson, W. W. See Razi, S.

Andersson, E. Light protective glass, (5) 127*j*.

Andersson, S. See Marklund, I.

Anderton, H. Point-projection X-ray microscopy, (1) 22*g*.

Ando, J., Matsuno, S., and Nishiyama, S. Reactivity of phosphate ores with acids, (2) 56*j*.

Ando, J., Yamakawa, O., and Kaneko, H. Production of calcium chromates from chromium ore, (9) 278*h*.

Ando, T. See Nobuoka, S.

Andre, E., and Le Duc, J. M. Gallium arsenide of high mobility obtained by liquid phase epitaxy, (5) 152*j*.

Andre, J. M. See White, J. L.

Andreas, F., and Gie, O. T. Spray drying as a granulating method, (5) 143*j*.

Andreev, A. Ya. See Klimov, V. V.

Andreeva, A. B. See Leonov, A. I.

Andreeva, I. Yu. Analysis of aluminum nitride, (10) 313*a*.

Andreeva, L. N. See Bil'tyukova, E. P.

Andreeva, L. P. See Krentsis, R. P.

Andreeva, L. P., Sidorenko, F. A., and Gel'd, P. V. Valency states of atoms in the monosilicides of certain 3*d* transition metals at low temperatures, (9) 288*b*.

Andreeva, N. G., and Rastrigina, E. F. Mechanism of metallic contact formation in SAP type alloys, (8) 238*g*.

Andres, F. H. See Gentile, A. L.

Andresen, A. F., Haig, W., Fischer, P., and Stoll, E. Magnetic and crystallographic properties of MnBi studied by neutron diffraction, (5) 138*h*.

Andrews, D. E., Schmidt, P. W., and Olphen, H. van. X-ray study of interactions between montmorillonite platelets, B (9) 289*g*.

Andrews, N. H. Method and apparatus for comminuting materials, P (2) 56*i*.

Andrews, R. See Murray, R. S.

Andrews, R. L. See Cramer, S. D.

Andrews, R. L., Kenahan, C. B., and Schlain, D. Electrodeposition of iridium from fused sodium cyanide and aqueous electrolytes—preliminary study, (2) 44*f*.

Andrusieczko, A. Electrical resistivity of molten glass between the electrodes, (10) 297*i*.

Anfilogov, V. N., Belov, B. I., and Troshin, Yu. P. Behavior of isomorphic impurities in the process of cocrystallization in open systems, (1) 26*i*.

Angel, B. R. See Smith, M. J. A.

Angell, C. A. Diffusion-conductance relations and free volume in molten salts, (11) 351*d*. Electrical conductance of concentrated aqueous solutions and molten salts—correlation through free volume transport model, (11) 352*g*. Electrical conductivity of fused potassium nitrate, (3) 80*b*. New class of molten salt mixtures—hydrated dipositive ion as an independent cation species, (4) 113*h*. Oxide glasses in light of the "ideal glass" concept (I) ideal and nonideal transitions and departures from ideality; (II) interpretations by reference to simple ionic glass behavior, (4) 93*i*.

Angell, C. A., Pollard, L. J., and Strauss, W. Effect of pressure on the electrical conductance and glass-transition temperature of molten nitrates, (5) 127*h*.

Angino, E. E. Far infrared (500 to 30 cm^{-1}) spectra of some carbonate minerals, (5) 152*e*.

Angstadt, R. L., and Hurley, F. R. Hardening accelerated portland cement, P (6) 165*j*.

Angstrohm Precision, Inc. Metal film resistor for low range and linear temperature coefficient, P (3) 73*c*.

Anikeeva, T. V., Butt, Yu. M., and Timashev, V. V. Influence of crystalline structure of clinker on its grindability, the fraction distribution of minerals, and the properties of cement, (6) 165*a*.

Anikeeva, T. V., Timashev, V. V., and Saverchenko, D. A. Effect of temperature in rotary kilns on the crystalline structure of the clinker, (5) 124*h*.

Anikina, G. P. See Drobot, D. V.

Aniskova, L. S. See Belopol'skii, M. S.

Ankel, C. Documentation and evaluation of prehistoric ceramics, (1) 2*b*.

Ankerst, H. Assessment of the chemical resistance of enamels, (1) 3*h*.

Anritsu Keiki Kabushiki Kaisha. Surface contacting thermocouple, P (11) 348*a*.

Ansell, G. S. See Bradt, R. C.

Ansimova, T. A. See Pitak, N. V.

Antell, G. R. Method of forming a gallium arsenide transistor by diffusion, P (2) 51*h*.

Anthony, A. M. Fundamental research in the study of electrical properties of refractory oxides at high temperatures, (3) 71*a*. See Makram, H.

Anthony, A. M., Loup, J. P., and Mihailovic, Z. Measurement of electrical resistivity in ceramics at high temperatures (1000° to 1700°C), (10) 314*g*.

Antic-Jovanovic, A. M. See Marinkovic, M. D.

Antill, J. E. Ceramic fuel element for a gas-cooled nuclear reactor including a metallic fuel container provided with an oxidation resistant coating, P (4) 97*c*.

Antipol Corp. Air cleaner, P (6) 179*f*.

Antonevich, J. N. Ultrasonic transducers, P (5) 143*c*.

Antonova, N. P. See Kostyukov, N. S.

Antsiferov, V. N. See Elyutin, V. P.

Antunes, M. J. Process for making a spark plug, P (2) 52*e*.

Anufriev, Yu. N. See Shur, A. S.

Anwyl, R. H. Hot processing brick and tile, (2) 42*i*.

Aoki, H. See Yamaguchi, G.

Aoki, M., and Kitagawa, N. High frequency semiconductor diode, P (8) 244*e*.

Aoki, S., Hata, T., Kakita, I., Mizukusa, S., and Sakai, S. Stress analysis of high pressure anvil by photoelasticity, (9) 277*h*.

Apel, J. R. See Poehler, T. O.

Aponyi, T. J., and Mecum, W. D. Strength properties of glass fiber reinforced polybenzothiazole composites, (10) 298*h*.

Appel, J. Remark on the hopping transition probability of polaron holes in NiO, (8) 256*g*.

Appendino, P. See Brisi, C.

Applied Research Laboratories, Inc. Apparatus for preparing samples for X-ray analysis, P (9) 277*d*.

Arafa, S. See Bishay, A.

Arai, T. See Miyoshi, S.

Arai, Y. See Ida, I.

Arakelyan, O. I., and Chistyakova, A. A. Determination of the α-Al_2O_3 content of alumina, (10) 313*f*.

Araujo, R. J. Entropy interpretation of viscosity of B_2O_3, (4) 93*e*.

Araujo, R. J., and Stookey, S. D. Photochromic glasses—properties and applications, (11) 334*b*.

Aravamudhan, V. Review of the procedures for the utilization of lithium silicate minerals, (1) 25*c*.

Arbel, A. Stability of edge dislocation arrays, (5) 158*h*.

Arbuthnot, W. R. Production of glass-lined water storage tanks, (9) 263*c*.

Archambault, M., and Olivier, C. A. Water-soluble lithium compounds, P (1) 26*c*.

Archer, F. C. Hydraulic release for gyratory crushers, P (11) 349*i*.

Archer, J. L. See Mee, J. E.

Archer, J. R., Moody, W. E., and Stanford, A. L., Jr. Third-order elastic constant c_{111} in lithium fluoride, (11) 357*h*.

Archer, M. Delftware made at the Glasgow pottery of Delftfield—a starting point for research, (5) 124*b*.

Ardizzone, L. See Amato, I.

Arey, W. F., Jr. See Kimberlin, C. N., Jr.

Argall, F. Some dielectric properties of evaporated indium sulfide films, (10) 308*a*.

Argyle, B. E. See Shafer, M. W.

Ariff, M. R. See Elahi, Kh. M.; Hakim, J.; Iqbal, Q.; Yousuf, M.

Arima, R. See Watanabe, Hideo.

Arimura, S. See Nagata, T.

Arlett, R. H. Growth of $ZnRh_2O_4$ single crystals, (6) 186*b*.

Arlett, R. H., White, J. G., and Robbins, M. Single crystals of $BaAl_2O_4$, (6) 185*c*.

Armco Steel Corp. Process for forming a refractory coating on silicon-iron stock, P (9) 263*b*.

Armington, A. F., and O'Connor, J. J. Gel growth of clear cuprous chloride crystals, (2) 58*j*.

Armorlite Lens Co., Inc. Method of supporting lens blanks for grinding and polishing, P (3) 66*e*.

Armour & Co. Reacting calcium carbonate and wet process phosphoric acid, P (11) 350*a*.

Armsted Industries, Inc. Mold wash composition, P (8) 241*d*.

Armstrong, G. C. Instrument for measuring planes and vectors in space, (5) 145*c*.

Armstrong, G. T. See Domalski, E. S.

Armstrong, J. A. Measurement of picosecond laser pulse widths, (3) 83*j*. See Gutfeld, R. J. von.

Armstrong, M. C. See Shannon, R. F.

Armstrong, P. E. See Brown, H. L.

Armstrong, W. F. Glass polishing head having a detachable felt pad, P (1) 9*c*.

Armstrong Cork Co. Method of making ceramic acoustical product, P (6) 174*g*. Method of measuring the coating thickness on [glass] articles, P (11) 336*h*. Temperature sensing probe, P (3) 76*h*.

Arnesen, A. G., and Basen, T. Apparatus for feeding solid materials into a rotary kiln, P (3) 70*j*.

Arnett, G. M. See Lal, R. B.

Arni, H. T. See Blaine, R. L.

Arnold, A. J., Van Dyke, B., Van Dyke, D., and Porter, D. D. Method for casting articles, P (11) 341*e*.

Arnold, R. See MacLachlan, D. F. A.

Arnold, R. T., and Stanford, A. L., Jr. Effect of FeS_2 on the 120° phase transition in $BaTiO_3$ single crystals, (5) 137*i*.

Aronson, S. Free energies of formation of thorium sulfides from solid-state emf measurements, (5) 152*f*. See Salzano, F. J.

Aronsson, B., Lundstrom, T., and Rundqvist, S. Borides, Silicides, and Phosphides—A Critical Review of Their Preparation, Properties, and Crystal Chemistry, B (4) 119*i*.

Arora, K. L., and Gokhale, Y. C. Substitution of imported asbestos in asbestos cement products, (9) 262*d*.

Arrance, F. C. See Berger, C.

Arrison, F. C. See Lowdermilk, M. J.

Arrott, A. See Kendrick, H.

Arslambekov, V. A., and Smirnov, G. V. Oxide films on silicon, (1) 16*b*.

Arst, M. C. Method of growing a crystal, P (4) 100*j*.

Artamonov, A. Ya. Influence of Machining Conditions on the Physicomechanical Condition of Powdered-Metal Materials, B (1) 34*g*.

Artamonova, M. V. See Kitaigorodskii, I. I.

Arthanari, S., and Yu, C. W. Analysis of the creep and shrinkage effects on prestressed concrete members under temperature gradient and its application, (8) 228*b*. Creep of concrete under uniaxial and biaxial stresses at elevated temperatures, (8) 228*d*.

Arthur D. Little, Inc. Method of anodizing by applying a positive potential to a body immersed in a plasma, P (10) 310*c*. Silicide-coated composites and method of making them, P (8) 230*a*. Treatment of surfaces, P (8) 236*b*.

Arthur, E. P. Glass standard for fluorescence, (3) 63*i*. Isolated glass transducer and method of making, P (8) 244*g*.

Arthur, G. See Rich, J.

Artman, J. O. Electric field gradient calculations in transition-metal sesquioxides, (9) 281*j*.

Artman, J. O., and Murphy, J. C. Symmetry considerations in the spectrum of ruby, (5) 158*j*.

Arzt, R. M., Salzmann, E., and Dransfeld, K. Elastic surface waves in quartz at 316 Mhz, (4) 109*a*.

Asada, C., Sugiyama, T., and Onishi, M. Temperature distribution and cooling rate of electric furnace for crucible method corrosion tests and experiments on the quantity of slag charged, (10) 304*g*.

Asada, M., Omori, Y., and Sanbongi, K. Study of the properties of calcium ferrites in the CaO–FeO–Fe_2O_3 ternary system, (9) 287*g*.

Asahara, Y. See Namikawa, H.

Asahi Glass Co., Ltd. Spacers for multiple glass sheet glazing unit, P (2) 42*e*.

Asai, K. See Yuri, Y.

Asai, S., Muira, N., and Tanaka, S. Conductivity change in CdS by microwave phonons, (11) 350*h*.

Asamoto, R. R., and Novak, P. E. Tungsten-rhenium thermocouples for use at high temperatures, (1) 23*i*.

Asano, K. See Kawamura, S.

Ashbee, K. H. G. See Baeta, R. D.

Ashbee, K. H. G., Lyall, R., and White, D. Plastic deformation of a glass-ceramic, (8) 233*c*.

Ashida, T., and Toyoda, H. Effects of additives and of ambient atmosphere during heating on the electrical resistivity of semiconducting $BaTiO_3$, (8) 253*i*.

Ashkin, A. See Boyd, G. D.

Ashland Oil & Refining Co. Method of making rapid curing foundry cores, P (8) 241*b*. Process of preparing inorganic foams from alkali metal silicates and aluminum, P (11) 340*g*.

Ashworth, J. L. See Rand, M. J.

Aslanova, M. S. Properties of glass fibers of different composition, (6) 168*i*.

Aso, K., and Miyahara, S. Magnetic susceptibility of $SrLaFeO_4$ with K_2NiF_4 structure, (10) 323*b*.

Asquith, G. B. Marine dolomitization of the Mifflin member Platteville limestone in southwest Wisconsin, (1) 30*b*.

Associated Electrical Industries, Ltd. Ceramic dielectrics, P (1) 17*b*. Electric incandescent lamps, P (1) 8*i*. Manufacture of ferrite plate, P (7) 209*d*. Mass spectrometer sample insertion devices, P (8) 249*c*. Method for producing *pin* semiconductors, P (7) 209*e*. Method of terminating thin [Ta] film components, P (7) 209*g*. Preparation of zinc and cadmium sulfides, P (1) 25*h*. Production of cadmium sulfide crystals, P (1) 26*b*.

Associated Lead Manufacturers, Ltd., and Booth, F. T. Ceramic stains, P (2) 56*f*.

Astakhov, E. A. See Epik, A. P.

Astbury, N. F. Ceramic research in England, (10) 327*i*. Changing pattern in available fuels, (3) 76*i*. Relation between chemical composition and physical properties of ceramic bodies, B (7) 224*h*.

Astbury, N. F., and Owen, V. J. Electrical method for studying connected porosity, B (9) 291*f*.

Atkins, J. T., and Billmeyer, F. W., Jr. Edge-loss errors in reflectance and transmittance measurement of translucent materials, (1) 21*f*.

Atlantic Research Corp. High silica matrix radioactive source and method of preparation, P (4) 100*c*. Vertical mixer, P (2) 53*g*.

Ato, Y. See Huzimura, R.; Ozawa, L.

Atomic Energy of Canada, Ltd. Clad ceramic nuclear reactor fuel element having axial void, P (7), 204*i*. Doped hypostoichiometric dioxide nuclear fuel composition and method of preparation, P (6) 174*b*. Method of making lithium-drift diodes by diffusion, P (6) 178*d*. Nuclear reactor fuel, P (3) 69*e*.

Atwood, J. G. See Dueker, G. W.

Au, P. K. L., and Calvo, C. Crystal structure of $Cd_3V_2O_7$, (5) 150*f*.

AuCoin, T. R. See Gualtieri, J. G.

AuCoin, T. R., Savage, R. O., Jr., and Tauber, A. Method of growing single crystals of $Ba_2Zn_2Fe_{12}O_{22}$, P (8) 245*b*.

Auda, D. See Keister, F. Z.

Auda, D., and Schneider, M. Ceramic glazes for thick film microelectronics, (7) 207*a*.

Auer, M. F. Method and means for orienting crystals by alternate application of angularly spaced magnetic fields, P (7) 213*a*.

Augsburger, C. Method for filling structural clay tile, P (1) 10*h*.

August, R. R. See Anderson, D. B.

Augustin, E. H. See Greenler, R. J.

Augustine, F. Method of making photosensitive elements, P (6) 178*e*.

Aukland, J. C. See Anderson, D. B.

Auld, B. A., Collins, J. H., and Zapp, H. R. Adiabatic time domain conversion of hybrid magnetoelastic waves in YIG, (4) 105*j*.

Auld, J. R., Brown, R. B., and Gniewek, T. T., Jr. Process for joining glass-lined metal conduits, P (4) 95*b*.

Ault, R. G. See Beaver, E. R., Jr.

Aumento, F. Stability, lattice parameters, and thermal expansion of β-cristobalite, (3) 87*a*; reply to discussion, (6) 185*f*.

Auskern, A. Rare-gas diffusion in nonstoichiometric zirconium carbide, (10) 324*d*.

Austerman, S. B. Growth and properties of BeO single crystals, (3) 67*g*. Self-diffusion in BeO, (3) 68*a*. See Smith, D. K., Jr.

Austin, G. See Parham, W.

Austin, L. K. See Radford, C.

Australian Atomic Energy Commission. Graphite heating element for electric resistance furnace, P (11) 348*f*.

Authier, A. See Sauvage, M.

Auty, D. B. See Elliot, M. N.

Auzins, P. V. See Wertz, J. E.

Auzins, P. V., and Wertz, J. E. Spin states of trivalent chromium with tetragonal symmetry in MgO, (6) 189*b*.

Avco Corp. Flame spray metallizing, P (1) 20*b*. Method of improving the performance of electrodes in magnetohydrodynamic devices, P (2) 51*a*. Superconductive material of NbN and ZrN, P (10) 311*e*.

Avdeev, Yu. G. See Sulimenko, L. M.

Aveline-Jauffret, M. Study of stresses in set earthenware wall tiles, B (9) 291*f*.

Avella, F. J. Rare earth activated indium borate cathodoluminescent phosphors, P (10) 311*a*.

Avella, F. J., and Palilla, F. C. Method of preparing yttrium oxide phosphors, P (5) 142*d*.

Aven, M. Method of purifying zinc and cadmium chalcogenides, P (8) 245*f*.

Aven, M., and Garwacki, W. Selenotelluride *pn* junction device utilizing deep trapping states, P (9) 274*h*.

Averbach, B. L. See Blech, I. A.

Avery, W. H. Method of producing pyrolytic graphite, P (6) 175*c*.

Avriel, M. See Hasson, D.; Resnick, W.

Awasthi, S. K., Chackraburtty, D. M., and Tondon, V. K. Tetravalent, pentavalent, and hexavalent uranium compounds of the type A_2B-$B'O_5$, (5) 159*j*.

Aykan, K. Novel lead titanate, $PbTi_3O_7$, (11) 355*c*. $PbTi_3O_7$ and process for its manufacture, P (4) 105*b*. Process for improving the catalytic properties of lead titanate, P (4) 105*c*.

Aylwin, J. J. See McCrary, J. W., Jr.

Ayres, G. H. See Embry, W. A.

Ayres, W. A. Thermometer manufacture, P (7) 199*b*.

Azelitskaya, R. D. See Lokot, A. A.

Azim, Y. Y. A. See Joy, A. S.

Baab, K. A. See Osterholtz, C. E.

Baak, N. T. E. A. Process for bonding devitrified surfaces, P (1) 10*a*.

Baak, T., Rapp, C. F., Hartley, H. T., and Wiens, B. E. Chemical durability of a soda-lime glass with TiO_2, GeO_2, ZrO_2, and $AlPO_4$ partially substituted for SiO_2, (9) 263*f*.

Babachev, G. Separation and determination of Fe, Al, Cr, Ca, and Mg by ion exchangers and Komplexon III (EDTA), (2) 55*b*.

Babaeva, E. P. See Bukhalova, G. A.

Babb, S. E., Jr., and Chaney, P. E. Melting properties of KNO_3 under pressure, (5) 154*g*.

Babcock, C. L. Substructures in silicate glasses, (4) 93*i*.

Babcock, E. W., and Vascik, R. A. Glass sheet support frame, P (1) 9*d*.

Babcock, K. L. See Sposito, G.

Babcock, K. R. See Chamberland, B. L.

Babcock & Wilcox Co. Pulverizer, P (1) 26*c*. See Bailey Meter Co.

Babel, H. W., and Sines, G. Improved method for uniaxial and biaxial testing of brittle materials, (9) 276*h*.

Babichev, N. I. See Galdina, N. M.

Bacher, J. F. See Nelson, F. W.

Bachman, G. S., Fitzgerald, J. V., and Matusik, F. J. Wide range portable viscometer, (11) 347*d*.

Bacmann, J. J., and Cizeron, G. Dorn method in the study of initial phase of uranium dioxide sintering, (5) 151*e*.

Bacmann, M., Bertaut, E. F., and Bassi, G. Atomic parameters and magnetic structure of $UCrO_4$, (5) 149*g*.

Baden, H. G. H. Apparatus for assembling glass sheets during manufacture of double glazed windows, P (10) 299*i*.

Bader, H. Particle studying apparatus with self-clearing scanner element, P (11) 348*c*.

Badger, A. E. See Lehr, G. J.

Badger, A. E., and Lehr, G. J. Calculated efficiency of a glass-melting furnace in relation to melting load, (11) 333*e*.

Badische Anilin- & Soda-Fabrik Akt.-Ges. Multiple-chamber rotary kiln, P (4) 104*d*.

Badzian, A. R. Radial distribution function of noncrystalline boron, (4) 114*e*.

Baeckmann, A. von. See Glemser, O.

Baer, C. A., Clough, P. J., and Steeves, R. W. Process of joining bodies with boron nitride, P (5) 135*i*.

Baer, R., Wessel, G., and Rubins, R. S. Paramagnetic resonance study at millimeter wavelengths of an axial Fe^{3+} spectrum in strontium titanate, (9) 285*f*.

Baer, W. S. Faraday rotation in $KTaO_3$, (11) 352*i*. Free-carrier absorption in reduced $SrTiO_3$, (9) 282*e*. Interband Faraday rotation in some perovskite oxides and rutile, (6) 186*c*.

Baes, C. F., Jr. See Romberger, K. A.

Baeta, R. D., and Ashbee, K. H. G. Plastic deformation and fracture of quartz at atmospheric pressure, (4) 114*g*.

Baev, A. K., and Novikov, G. I. Thermodynamic investigation of the oxychlorides of the rare-earth elements, (10) 326*b*.

Bagdonas, V. Effect of densification on the deformation of keramzit concrete, (1) 2*c*.

Baggaley, B. J., and McCartney, E. R. Sintering of alumina containing small concentrations of magnesium oxide, (5) 133*i*.

Bagley, B. G., Chen, H. S., and Turnbull, D. Characterization of amorphous alloy films, (7) 216*b*.

Bahezre, C. See Fleurence, A.

Bahl, O. P. See Patel, A. R.

Bahramian, B. See Hughes, B. P.

Baier, E., Deeg, E., and Constabel, H. G. Radiochemical study of the adsorption of orthophosphate on two ternary borate glasses (II, III), (8) 233*j*.

Bailey, A. I., and Kay, S. M. Direct measurement of the influence of vapor, liquid, and oriented monolayers on the interfacial energy of mica, (9) 280*j*.

Bailey, A. R. Structure and Strength of Metals, B (5) 161*e*.

Bailey, D. J. Method and apparatus for separating heavy minerals, P (9) 279*e*.

Bailey, E. G. Method for heating solid inorganic material, P (1) 3*e*. Vertical kiln operation using shrouded fuel, P (1) 3*d*.

Bailey, L. See Tully, G. R., Jr.

Bailey, L. G., and Mehal, E. W. Method for depositing a single crystal on an amorphous film and for manufacturing a metal base transistor and a thin-film metal base transistor, P (6) 177*j*.

Bailey, R. J. Pottery—industry of opportunity for school leavers, (2) 60*f*.

Bailey, R. T. See Brociner, R. E.

Bailey, S. W. (editor). Clays and Clay Minerals—Proceedings of the Fourteenth National Conference, Berkeley, Calif., August 1965, B (8) 259*g*; Proceedings of Fifteenth Conference, Pittsburgh, Pa., October 1966, B (9) 289*b*. Status of clay mineral structures, B (8) 259*g*. See Bradley, W. F.; Eggleton, R. A.; Mossman, M. H.

Bailey, T. W. Glass-molding apparatus, P (3) 235*a*.

Bailey Inventions, Inc. Method for heating solid inorganic material, P (1) 3*e*. Vertical kiln operation using shrouded fuel, P (1) 3*d*.

Bailey Meter Co. and Babcock & Wilcox Co. Measurement and control of burner excess air, P (5) 147*f*.

Baily, W. E. See Lyon, W. L.

Bain, A. S. Clad ceramic nuclear reactor fuel element having axial void, P (7) 204*i*.

Bain, E. C. See Fisher, R. M.

Baird, D. H. See Natansohn, S.

Baird, S. S., and Cunningham, J. A. Application of glass to semiconductor devices, P (3) 72*j*.

Baker, A. A., and Jackson, P. W. Silica fiber reinforcement of aluminum, (8) 229*j*.

Baker, B. H., and Schroth, P. High hot strength in basic brick, (8) 237*e*.

Baker, C. A. Gamma-activation analysis—a review, (2) 54*e*.

Baker, C. L., and Holloway, P. W. Sodium metasilicate pentahydrate product and preparation P (7) 215*e*.

Baker, D., and Bryan, I. E. Thermocompression bonding of metals to semiconductor, metallic, or nonmetallic surfaces, P (8) 246*e*.

Baker, D. H., Jr. See Gomes, J. M.

Baker, D. W. See Wenk, H. R.

Baker, E. H., and Richardson, F. D. Activities in the oxide-carbonate melts of the alkaline earth metals, (4) 105*j*.

Baker, H. W. Methods of and apparatus for toughening sheets of glass with reserve zone, P (11) 336*b*. Toughened sheets of glass, P (4) 95*f*.

Baker, J. E., Co. Process for making dead-burned dolomite, P (11) 340*f*.

Baker, J. E., Co. and Air Reduction Co., Inc. Combustion process and apparatus to increase a flame temperature, P (11) 348*h*.

Baker, J. M. Evaluation of film and filmless radiographic systems for the nondestructive testing of thin materials and electronic assemblies, (7) 212*d*.

Baker, L. A. See DiMarcello, F. V.

Baker, L. A., Warner, N. A., and Jenkins, A. E. Decarburization of a levitated iron droplet in oxygen, (6) 184*i*.

Baker, M. McD., Less, L. N., and Orman S. Uranium + water reaction (I) kinetics, products, and mechanism; (II) effect of oxygen and other gases, (3) 88*i*.

Baker, T. C. Method and apparatus for inspecting transparent articles for defects by fluorescent radiation, P (10) 300*f*.

Baker, T. C., Mathias, B. B., and Sager, J. R. Bottle inspection method and apparatus, P (11) 335*h*.

Baker, T. W. See Baldock, P. J.

Baker, T. W., and Baldock, P. J. X-ray diffraction intensities of the high temperature (β) phase of beryllium oxide, (4) 119*c*.

Baker, T. W., Baldock, P. J., and Clarke, F. J. P. Residual strain and the fracture-stress temperature relation in BeO, (3) 67*f*.
Bakker, R. Connector and insulating sleeve for spark plug or distributor, P (4) 99*g*.
Bakker, W. T., and Lindsay, J. G. Reactive magnesia spinel, preparation and properties, (1) 15*f*.
Bakunov, V. S. See Poluboyarinov, D. N.
Balakshina, A. V. See Negina, V. R.
Balascio, J. F., White, W. B., and Roy, R. Growth of single crystal hexagonal selenium from supercritical ammonia, (2) 58*f*.
Balasubramanian, N. See McNally, R. N.
Balasundaram, L. J. See Sinha, A. N.
Balderen, R. F. van. See Wijn, H. W. de.
Baldino, P., and Connor, T. Hot filament vs. cold cathode gages, (1) 21*b*.
Baldock, P. J. See Baker, T. W.
Baldock, P. J., Spindler, W. E., and Baker, T. W. X-ray diffraction study of the variation of the lattice parameters and their ratio for beryllium oxide up to 2000°C, (4) 119*d*.
Baldwin, N. L. See Langer, S.
Baldwin, R. E. Furnace and burner for testing temperature probes, P (11) 347*i*.
Balgord, W. See Roy, R.
Balint, G. Study of Hungarian silicate minerals by infrared spectrophotometry, (7) 222*i*.
Balk, P. See Eldridge, J. M.
Ball, F. E., and Martin, J. W. Presses for compacting electrically conductive compositions, P (8) 247*g*.
Ball, M. C., Brown, D. S., Page, D., and Thurman, R. R. T. Action of alkali on transition-metal carbides, (5) 149*f*.
Ball, W. L. Foam engineering in Canada, (5) 132*f*.
Ball Brothers Co., Inc. Glass having dual protective coatings thereon and method for forming such coatings, P (2) 40*j*. Iron alloy, P (6) 170*k*. Lubricious coating for glass, P (9) 265*i*. Lubricious coating for glass containing polyvinyl alcohol, emulsified polyethylene, and an inorganic acid, P (3) 65*a*.
Ball Brothers Research Corp. High speed ultraviolet thin spot detector, P (1) 9*e*.
Ballantyne, J. See Hunsperger, H.
Ballestraci, R. Crystal structure of oxysulfides of the rare earths, $Ln_2O_2S_2$, (1) 27*e*. Structural study of the basic sulfates of the rare earths and yttrium, (4) 116*b*.
Ballman, A. A. See Holmes, C. H.; Lenzo, P. V.
Ballman, A. A., King, J. C., and Laudise, R. A. Synthetic quartz growth using lithium ions in the nutrient solution, P (10) 318*i*.
Ballman, A. A., Laudise, R. A., and Rudd, D. W. Synthetic quartz growth, P (3) 74*b*.
Ballman, A. A., Levinstein, H. J., Capio, C. D., and Brown, H. Curie temperature and birefringence variation in ferroelectric lithium metatantalate as a function of melt stoichiometry, (1) 16*d*.
Bally, A. O. Filter and its production, P (1) 8*j*.
Balyuk, S. T., Lavrovskaya, G. M., and Taukchi, V. N. Nondestructive determination of porosity of refractories, (9) 267*j*.
Balzar, H., and Heimann, E. Possibilities of rationalization in salt glazing, (9) 266*f*.
Balzari, A. M. P. See Amato, I.
Balzers Patent- und Lizenz-Anstalt. Combined electron microscope and diffraction apparatus for the electron-optical inspection of the surfaces of objects, P (4) 103*f*.
Ban, T. E., and Nelson, C. J. Lightweight aggregate from fly ash pellets, P (6) 172*b*.
Banaev, A. M., and Chekhovskoi, V. Ya. Experimental determination of the coefficient of thermal conductivity of solid materials at 200° to 1000°C, (5) 145*a*.
Bando, Y. See Hamamura, A.
Bando, Y., Kiyama, M., Yamamoto, N., Takada, T., Shinjo, T., and Takaki, H. Magnetic properties of α-Fe_2O_3 fine particles, (3) 83*i*.
Banerjee, B. K. See Roy, A. K.
Banerjee, J. C. Some observations on problems relating to the refractories industry of India, (5) 134*c*.
Banerjee, J. C., Banerjee, S. P., and Sircar, N. R. Chemical and magnetic properties of magnesites, (5) 147*j*.
Banerjee, S. K. Lightweight aerated cellular concrete—a structural ceramic unit, (5) 125*d*. Science, technology, and engineering of clay based mechanized brickmaking in India (I, II), (9) 266*d*. See Dutta, R.
Banerjee, S. K., O'Reilly, W., Gibb, T. C., and Greenwood, N. N. Behavior of ferrous ions in iron-titanium spinels, (3) 70*j*.
Banerjee, S. P. See Banerjee, J. C.
Banerji, S. K. See Srivastava, M. C.
Bange, G. R., and Young, H. F. Method for making joined glass lined pipes, P (9) 265*f*.
Banin, A., and Ravikovitch, S. Kinetics of reactions in the conversion of Na- or Ca-saturated clay to H-Al clay, B (8) 259*c*.
Banks, E., Kostiner, E., and Wertheim, G. K. Moessbauer effect in $MnFeO_3$, (10) 323*b*.
Banner, J. G. See Loukes, D. G.
Banning, L. H. See Holmes, W. T., II.
Bannister, M. J. Crystallite size measurements on thoria gel, (1) 27*h*. Equivalence of X-ray and electron microscopy crystallite sizes in thoria gel, (5) 152*g*. Kinetics of sintering and grain growth in BeO, (3) 67*h*. Shape sensitivity of initial sintering equations, (11) 356*b*. Sinterability studies on various BeO powders, (3) 68*b*.
Banno, H. Piezoelectric and electrostrictive ceramic articles of lead zirconate titanate containing manganese and tungsten oxides, P (6) 178*c*.
Banus, M. D. See Jena, A. K.
Barakat, D. See Stark, R. A.
Barakat, N., and Zakhm, F. G. A. Phase change in transmission through silver layers and its variation with thickness for variable radiation, B (10) 329*g*.
Baraskiewicz, P. See Widaj, J.
Barbanyagre, V. D. See Luginina, I. G.
Barbashov, G. K. See Sulimenko, L. M.
Barbe, J. P. See Chol, G.
Barben, T. R. Industrial pH measurements, (11) 346*c*.
Barber, C. M. See Westrum, E. F., Jr.
Barber, D. J. Recrystallization of anodic alumina films, (4) 115*d*.
Barber, S. W. Cathode ray tube display screen comprising woven mat of luminescent glass fibers, P (6) 177*b*. Ytterbium ion as a microprobe in oxide glasses, B (10) 329*f*.
Barber, W. A. Fuel cell with platinum-rhodium containing catalyst, P (4) 105*c*.
Barber-Greene Co. Bowl adjustment for crushers, P (11) 349*f*.
Barbezat, S. See Trillat, J. J.
Barbi, G. B. Thermodynamic functions by emf measurements on solid galvanic cells in nonstationary conditions—system Al + Al_2O_3, (3) 87*f*.
Barch, F. N. Inspection packing costs cut 70%, (3) 64*a*.
Barch, H. W., and Posney, R. V. Method of controlling heat application to glass to repair scored regions, P (2) 41*a*.
Bardash, I. See Siekanowicz, W. W.
Bardin, C., and Millier, A. Detailed analysis of the bloating fault in vitreous sanitary ware, B (9) 291*f*.
Bardin, P. C. Color coating clear glass permanently, (3) 63*f*. How fiber glass products are made, (5) 127*d*.
Bardyukov, M. E. See Zuikov, N. V.
Barham, D., and Barrett, L. R. Dissolution of magnesium aluminate spinel in sodium silicate melts, (10) 302*e*.
Barieau, R. E. Thermodynamic properties of a van der Waals fluid in the two-phase region, (3) 87*j*. See Dalton, B. J.
Barker, A. J. See Bott, T. R.
Barker, A. S., Jr. Temperature dependence of the transverse and longitudinal optic mode frequencies and charges in $SrTiO_3$ and $BaTiO_3$, (10) 326*f*.
Barker, R. S. Gamma radiation induced optical absorption in lead borate glasses, B (10) 329*a*.
Barker, W. A. See Bevelo, A. J.
Barker, W. W., and Williams, L. S. Some limitations of cubic stabilization in zirconia, (11) 356*g*.
Barkhau, M. L. Lubricant coating for glassware molds and equipment, P (1) 9*f*.
Barkley, D. J., Hitchen, A., Zechanowitsch, G., Zimmerman, J. B., and Ingles, J. C. Chemical determination of Pb, Ti, and Zr in precipitates used for production of homogeneous lead zirconate-lead titanate solid solutions, (9) 271*i*.
Barlett, H. B. Corrosion-resistant coating for magnesium die castings, P (7) 195*a*.
Barna, G. L. Plasticity of clay minerals, (1) 22*g*.
Barna, J. Characterization and evaluation of aqueous suspensions of clay minerals, (10) 305*h*.
Barner, J. O. See Mills, R. G.
Barnes, J. C., and Thomson, A. J. Design and construction of a microspectrophotometer, (4) 102*g*.
Barnes, R. S., and Nelson, R. S. Behavior of inert gases in ceramic fuels, (11) 337*g*.
Barnes Engineering Co. Black pigment for the blackening of infrared radiation detectors, P (4) 93*a*.
Barnett, D. M., and Tetelman, A. S. Stress distribution produced by screw dislocation pileups at rigid circular cylindrical inclusions, (4) 116*f*.
Barogenics, Inc. Apparatus for pressurizing a liquid, P (5) 144*d*.
Baron, J. See Halm, L.
Baronin, E. E. Methods for Determining Boron and Its Inorganic Compounds, B (7) 225*h*.
Barr, F. A., Montgomery, T. S., and Long, R. A. Liquid phase sintering, (3) 67*h*.
Barr, L. W. Isotope effect in thermal diffusion in solids, (4) 112*g*.
Barr, P. J. Apparatus for drying finely divided particles, P (3) 75*c*.
Barrachin, A. M., Jouquet, G., Micaud, G., and Pattou, F. Effect of porosity and crystalline orientation on Young's modulus of artificial graphite, (4) 108*d*.
Barradell-Smith, R., and McLaggan, J. R. Apparatus for forming glass ribbon on molten metal with gas seal means, P (2) 40*i*. Manufacture of flat glass, P (7) 198*j*.
Barrett, H. I. Glass cutting device, P (6) 170*b*.
Barrett, J. R., and Jensen, H. A. High efficiency semiconductor light emitter, P (2) 51*c*.
Barrett, L. R. See Barham, D.
Barrett, M. W., Cramer, D. G., and Oltman, R. B. Apparatus for forming ribbon with lateral force means, P (2) 40*j*.
Barrington, J., and Bergmann, O. R. Preparation of brittle inorganic polycrystalline powders by shock-wave techniques, P (5) 148*b*.
Barrington, R. R. Method of calcining aluminum hydroxide by cross-flowing the heating gas, P (8) 251*f*.
Barrios, H. R. See Nordberg, R. C.
Barros, S. de S., and Friedberg, S. A. Low-temperature magnetic susceptibility of ferrous oxalate dihydrate, (8) 254*i*.
Barry, B. E. See Bolger, D. E.
Barry, T. I., McNamara, P., and Moore, W. J. Paramagnetic resonance and optical properties of amethyst, (3) 84*c*.
Barry, T. L., and Roy, R. Densification of ionic solids by cold-pressing at ultrahigh pressures, (11) 351*h*. New rare earth-alkaline earth oxide compounds, predicted compound formation, and new families, (5) 155*f*.
Barsby, N. Roller hearth kiln, (5) 147*f*.
Barshad, I. Factors affecting the frequency distribution of clay minerals in soils (abstract), B (8) 259*d*.
Barshchevskaya, L. F. See Radomysel'skii, I. D.
Barsom, J. M. Fracture of tempered glass, (3) 63*i*.
Barson, F. See Miller, W. H.
Barsotti, L. R. See Kelly, A. C.
Barta, C., and Zemlicka, J. Electrochemical crystallization of calcite, (2) 58*d*.
Barta, J., and Gorni, J. Direct conversion of $Mg(OH)_2$ to high-density periclase, (10) 302*d*.
Bartell, L. S. See Hansen, K. W.
Bartenev, G. M. Structure and Mechanical Properties of Inorganic Glasses, B (4) 121*i*.
Bartha, P. See Kupzog, E.
Bartholomew, R. F. Diffusion-controlled attack of glass surfaces by molten hydroxides, (1) 5*b*.
Bartkus, E. A., Brownlow, J. M., and Grebe, K. R. Method of fabricating magnetic storage devices, P (10) 310*c*.
Bartlett, A. F. See Eyre, B. L.
Bartlett, E. S. See Gibeaut, W. A.
Bartlett, H. J. Refractory compound and method of production, P (2) 48*c*.
Bartlett, R. W. Elastic modulus of β-silicon carbide whiskers, (3) 80*a*.
Bartlett, R. W., Halden, F. A., and Fowler, J. W. High temperature verneuil crystal growth by arc melting, (3) 81*d*.
Barton, J. L. Dielectric relaxation in some alkali-alkaline earth-silica glasses, (7) 196*c*.
Bartoo, V. S. See Anderson, R. C.
Bartram, R. H. See La, S. Y.
Bartram, S. F. Crystal structure of the rhombohedral MO_3-$3R_2O_3$ compounds (M = U, W, or Mo) and their relation to ordered R_7O_{12} phases, (5) 150*c*.
Bas, G. Possibility of increasing the use of glass in buildings, (6) 168*c*.
Basak, N. Quantitative estimation of free silica content of some Indian rocks and minerals, (1) 34*d*.
Basen, T. See Arnesen, A. G.
Bashnina, G. L. See Boganov, A. G.
Basic, Inc. Controlled reagent introduction in a magnesite ore concentration process, P (8) 250*i*.
Basic Products Corp. Bonding machine sighting means, P (8) 243*i*. Diffusion furnace with transport means, P (11) 348*i*. Jet conveying system, P (8) 244*h*.
Basinska-Pampuchowa, S. Dilatometric properties of kaolinitic clays as a measure of their mineralogical composition, (6) 180*j*.
Baskin, Y. Melting point determination of uranium monophosphide, (3) 83*b*. Preparation and properties of uranium metaphosphate, $U(PO_3)_4$, (5) 157*d*.
Basov, N. Note on the magic ray, (5) 139*d*.
Bassett, A. T., Jr., and Siegia, D. C. Stacked dish infrared surface heating unit, P (3) 77*b*.
Bassett, W. A., Takahashi, T., and Stook, P. W. X-ray diffraction and optical observations on crystalline solids up to 300 kbars, (3) 88*a*.
Basseville, P. See Dubuisson, J.
Bassi, G. See Bacmann, M.; Grenier, J. C.
Bassi, G., and Lajzerowicz, J. Structure of the potassium lead pyrogermanate, $K_2Pb_2Ge_2O_7$, (5) 158*c*.
Bastable, P. W. See St. John, D. A.
Bastian, S., and Gruener, M. Cement composition and process for preparing it, P (7) 194*c*.
Bastiansen, O. See Almenningen, A.
Batchelor, C. S., and Jensen, W. R. Flame spray metallizing, P (1) 20*b*.
Bates, C. H., White, W. B., and Roy, R. Solubility of transition metal oxides in zinc oxide and the reflectance spectra of Mn^{3+} and Fe^{3+} in tetrahedral fields, (4) 116*b*.
Bates, E. B. Mandrel supporting apparatus, P (4) 94*d*.
Bates, F. See Hsu, Pa Ho.
Bates, J. L., Hinman, C. A., and Kawada, T. Electrical conductivity of uranium dioxide, (1) 11*h*.
Bates, K. F. Enamelist, B (3) 89*c*.
Bates, T. F. Geology and mineralogy of the sedimentary kaolins of the southeastern United States—a review, B (6) 191*d*.
Bateson, S. See Fickert, K. W. J.
Batha, H. D. See Webb, W. W.
Bats, R. See Broman, A.
Batsanov, S. S. See Rigin, V. I.
Battelle Development Corp. Radial grate for shaft kilns, P (6) 182*a*.
Battelle-Institut E. V. Manufacture of pottery, P (2) 49*c*.
Battino, R., and Wood, S. E. Thermodynamics—An Introduction, B (5) 161*f*.

Baudran, A. Ceramic building equipment, (9) 270*b*. Practical problems in the industrial color measurement of glazes, (10) 306*c*.

Bauer, A., and Buchwieser, G. High pressure electric discharge lamp having a fill including uranium halide, P (5) 141*j*.

Bauer, D. J., Lindstrom, R. E., and Higbie, K. B. Extraction behavior of cerium-group lanthanides in a primary amine-chelating agent system, (6) 182*g*.

Bauer, W. C. See Manring, W. H.

Bauer, W. R. See Rex, R. W.

Bauer Bros. Co. Eccentric head hydrocyclone, P (8) 247*c*.

Bauerle, J. E. Electrical conduction in thoria and thoria-yttria as a function of oxygen pressure, (5) 138*b*.

Bauerle, L. C. See Chindgren, C. J.

Baum, W. Semiconducting metal oxide layers on eucryptite glass-ceramics, (8) 234*b*.

Baumann, E. W. Trace fluoride determination with specific ion electrode, (10) 316*a*.

Baumberger, C., and Micheron, F. Nonlinear ferroelectric ceramics, (6) 176*f*.

Baumgart, W. Behavior of forsterite brick made from various raw materials, (8) 236*i*.

Baumgartel, F. A., and Hage, W. T. Measurement and control of burner excess air, P (5) 147*f*.

Baur, A., and Lecoco, A. Process for the preparation of beryllium oxide, P (7) 215*c*.

Bausch, W. M. Clay mineral forming processes (I, II), (2) 57*e*.

Bausch & Lomb, Inc. Apparatus for absorption spectrochemical analysis, P (9) 275*h*. Measuring laser output energy comprising a lead fluosilicate glass dosimeter element, P (7) 199*a*. Method of changing the conductivity of ceramic materials, P (10) 300*f*. Method for selective etching of alkali glass, P (6) 171*a*.

Bautista, R. G., and Margrave, J. L. Langmuir studies of the sublimation of strontium fluoride and barium fluoride single crystals, (11) 354*d*.

Baxter, N. D. Means [mechanical] for preventing blowouts of porcelain valves, P (8) 242*e*.

Bay, T., and Ross, C. W. Method and apparatus for control of rotary kiln exit gas conditions, P (5) 125*e*.

Bayer, G. Oxide spinels containing hexavalent tellurium, (8) 255*d*. Preparation and X-ray study of new tellurium-containing metal oxides of the type B_3TeO_6 (B = Mg, Mn, Ni, Cu), (8) 256*d*.

Bayer, G., Floerke, O. W., Hoffmann, W., and Scheel, H. J. Phase separation and crystallization of glasses in the system Na_2O–TiO_2–SiO_2, (6) 168*h*.

Bayer, P. D. See Calow, C. A.

Bazin, H. See Koran, J.

B & B Industries, Inc. Glass cutting device, P (6) 170*b*.

Beale, J. R. A. Unipolar transistor with narrow channel between source and drain, P (1) 19*d*.

Beale, J. R. A., and Beer, A. F. Low capacity and resistance transistor structure employing a two-conductivity collector region, P (7) 209*c*.

Beale, J. R. A., Beer, A. F., and Moulding, K. W. Variable gain transistor structure employing base zones of various thicknesses and resistivities, P (7) 210*g*.

Beall, A. O., and Ojakangas, R. W. Mineralogy of an Upper Cambrian K bentonite from Missouri, (4) 113*c*.

Beals, R. J. See Forlano, R. J.; Kern, R. S.

Bean, K. E., and Runyan, W. R. Semiconductor wafer with at least one epitaxial layer and methods of making, P (7) 210*g*.

Beardslee, H. J., Jr. Spark plug and process of manufacturing, P (6) 175*h*.

Beasley, E. S. G., and Slinn, G. G. Vibration grinding, (5) 144*b*.

Beattie, J. R. Applying radiation pyrometry to glass manufacture, (3) 63*f*. See Benson, H.

Beatty, R. L. See Beutler, H.

Beaumont, A. J. Finnish flotation feldspar, (4) 104*h*.

Beaumont, D. H. See Friedman, A. I.

Beaumont, J. H., and Jacobs, P. W. M. Polarization in potassium chloride crystals, (6) 187*h*.

Beauzee, C., and Desvignes, F. Method of manufacturing semiconductor plate using molten zone on powder support, P (8) 245*b*.

Beaver, E. R., Jr. Method of producing thermoelectric bodies, P (4) 100*g*. See Henderson, C. M.

Beaver, E. R., Jr., and Ault, R. G. Graphite containing segmented thermoelement and method of molding, P (10) 304*d*.

Beaver, W. W., Theodore, J. G., and Bielawski, C. A. Effects of powder characteristics, additives, and atmosphere on the sintering of sulfate-derived BeO, (4) 96*c*.

Beavitt, A. R. Wide-band particle eliminator, (11) 343*b*.

Beck, A. Method of making ρn junctions by hydrothermally growing, P (7) 209*h*.

Beck, C. W. See Brunton, G.; DeRudder, R. D.

Beck, J. H. High temperature electrical heating unit, P (7) 213*i*.

Beck, J. H., and Bogosh, R. B. High temperature electrical furnace, P (8) 249*f*.

Beck, P. A. Survey of possible layer stacking structures, (8) 257*c*.

Beck, P. W. See Brockman, F. G.

Beck, T. A., Bhandary, V. S., and Gupta, P. K. Particle size determination of indigenous clays and their properties, (6) 182*f*.

Beck, W. R., and O'Brien, D. L. Glass bubbles prepared by reheating solid glass particles, P (5) 129*i*.

Becker, C. E. Method of forming a permeable structure for aerating bulk materials, P (4) 102*a*.

Becker, G. See Schulze, E.

Becker, H. Diffusion of aluminous cords in sheet glass, (8) 231*i*.

Becker, W. See Lehmann, H.

Becker, W. M. See Stirn, R. J.; Yep, T.O.

Beckett, L. T. A. See Fishman, D.

Beckman, P. Grid type thermocouple, P (4) 103*g*.

Beckman Instruments, Inc. Capillary passage and method of making, P (7) 198*c*. Cermet electrical resistance material and method of using, P (1) 12*j*. Fragmentation inlet for gas chromatography and method of loading a sample thereinto, P (1) 23*h*. Isolated glass transducer and the method of making, P (8) 244*g*. Method of making cermet resistance element and terminal connections therefor, P (9) 273*h*. Scattered light spectrophotometer, P (1) 24*a*. Spectrophotometer, P (4) 103*i*.

Becton Dickinson & Co. Thermometer manufacture, P (7) 199*b*.

Becvar, J. See Jakes, D.

Bedell, J. R. See Engdahl, R. E.

Bedenbaugh, J. H. See McDonald, C. W.

Bedjai, J. G. See Orbach, H. K.

Beech, D. G. Some factors affecting the efficiency of dry pan grinding, B (9) 291*e*. See West, H. W. H.

Beechan, C. R. See Herron, R. H.

Beek, W. J. See Bonne, H.

Beekenkamp, P. Structure of glasses in the system K_2O-B_2O_3-Al_2O_3, (7) 197*a*. Structure of vitreous borates and borophosphates, (5) 128*i*.

Beekenkamp, P., and Hardeman, G. E. G. Nuclear magnetic resonance studies of the structure of glasses in the system Na_2O-B_2O_3-P_2O_5, (7) 196*h*.

Beekenkamp, P., and Stevels, J. M. Suggestion for a new nomenclature to describe the structure of vitreous systems and their related crystalline compounds, (8) 234*j*.

Beeler, J. R., Jr. Primary damage state in finite neutron irradiated BeO specimens, (8) 256*h*.

Beer, A. F. See Beale, J. R. A.

Beerntsen, D. J. See Spiering, G. A.

Beggs, D. See Thome, W. L.

Beggs, J. E. Electron discharge device having a barium dispensing anode structure, P (1) 17*g*.

Beghi, G., and Cazzaniga, E. Examination of the alumina phases in SAP after irradiation, (6) 185*g*.

Begley, E. R. See Wehrenberg, T. M.

Behl, W. K., and Egan, J. J. Standard molar free energy of formation of uranium dicarbide and uranium sesquicarbide by electromotive force measurements, (11) 357*c*.

Behrens, H. See Cremer, G.

Behrndt, K. H. Film-thickness and deposition-rate monitoring devices and techniques for producing films of uniform thickness, B (8) 260*d*.

Beigelman, M. See Salvadori, A.

Beighton, J. Air pollution—the special industrial processes, (6) 179*b*.

Beisswenger, H., Bober, M., and Schumacher, G. Thermal diffusion in the system UO_2-CeO_2, (9) 287*j*.

Beketov, A. R., Vlasov, V. G., and Strekalovskii, V. M. Phase transformations on dissociation of the β and γ forms of uranium trioxide, (7) 220*a*.

Belanger, L. G. See Vorce, L. H.

Belasco, M. Gallium arsenide transistor and methods of making it, P (1) 17*j*. Semiconductor devices and methods for making, P (3) 74*a*.

Belasco, M., Howeth, B. W., Martin, D. D., and Wende, P. T. Gallium arsenide semiconductor device and contact alloy therefor, P (6) 177*a*.

Belasco, M., and Martin, D. D. Alloy contact containing aluminum and tin, P (3) 72*i*.

Belcher, C. B. See Kinson, K.

Belen'kii, B. S. See Zarubitskii, O. G.

Belitskii, M. E. Investigation of the chemical stability of solid lubricants at high temperatures (I), (11) 338*f*.

Beljaev, A. N., and Shilov, I. S. Apparatus for drying and hardening welding electrode coatings, P (3) 65*c*.

Belknap, J. L. Gas burner unit, P (5) 147*e*.

Bell, D. Manufacture of vulcanized liquid resin bonded abrasive articles, P (8) 227*f*.

Bell, H. B. See Perron, P. O.

Bell, K. E. Influence of lime on the thermal expansion of clay, (9) 266*f*. See Brady, J. B.

Bell, L. W. See Hetherington, G.

Bell, M. C., and Flengas, S. N. Electrical conductivities and the structural properties of molten $PbCl_2$-PbS mixtures (I); structural properties; (II) electrical conductivities of the systems PbS-$PbCl_2$ and Pb-PbS-$PbCl_2$, (10) 320*h*.

Bell, R. J., Bird, N. F., and Dean, P. Vibrational spectra of vitreous silica, germania, and beryllium fluoride, (11) 358*a*.

Bell, R. L. See Uebbing, J. J.

Bell, T. M. See Pugh, N. R.

Bell, W. E. Vacuum sealing of gas laser windows, P (9) 266*a*.

Bell Telephone Laboratories, Inc. Divalent metal doped fluorides as optical maser material, P (8) 244*j*. Electroluminescent gallium phosphide crystal with three dopants, P (5) 141*e*. Fabrication of beam lead semiconductor devices, P (9) 272*i*. Fabrication of semiconductor integrated devices with a ρn junction running through the wafer, P (6) 177*h*. Faraday rotator utilizing terbium aluminum garnet and dysprosium aluminum garnet, P (5) 141*g*. Ferrite phase shifter having longitudinal and circular magnetic fields applied to the ferrite, P (8) 244*c*. Growth of divalent metal aluminates, P (6) 190*g*. Growth of lithium niobate crystals, P (1) 18*a*. Growth of yttrium iron garnet, P (9) 273*c*. Hydrothermal growth of zinc oxide crystals with ammonium ion additives, P (3) 72*i*. Interferometric strain analysis, P (3) 76*f*. Junction diode maser, P (4) 100*e*. Laser device using Nd:$PrCl_3$, P (3) 73*b*. Luminescent semiconductor devices including a compensated zone with a balanced concentration of donors and acceptors, P (9) 273*f*. Method for coating semiconductor devices with silicon oxide, P (11) 344*e*. Method of depositing films of controlled specific resistivity and temperature coefficient of resistance using cathode sputtering, P (11) 344*f*. Method of forming an oxide coating on semiconductor bodies, P (8) 245*g*. Method of forming a piezoelectric ultrasonic transducer, P (9) 273*b*. Method of making low resistance ohmic contact to p-type lead telluride, P (4) 100*d*. Method of preparing a film resistor by sputtering a ternary alloy of tin, antimony, and indium in the presence of oxygen, P (9) 274*e*. Method of sputtering highly pure refractory metals in an anodically biased chamber, P (10) 310*i*. Microwave devices utilizing Eu-Fe garnet containing Ga, P (3) 73*h*. Positive temperature coefficient [La-Ba-Sr] titanate thermistor, P (7) 210*a*. Preparation of metal oxides by reactive sputtering of carbides, P (11) 345*b*. Rotated Y-cut rectangular piezoelectric quartz crystal plates, P (7) 210*e*. Small area semiconductor device, P (4) 101*b*. Synthetic quartz growth using lithium ions in the nutrient solution, P (10) 318*i*. Temperature gradient zone melting and growing of semiconductor material, P (4) 101*e*. Thin film capacitor, P (7) 210*f*. Vapor-liquid-solid crystal growth technique, P (1) 19*d*.

Bell Telephone Laboratories, Inc., and Western Electric Co., Inc. Method of testing the internal friction of synthetic quartz crystal by the use of two different frequencies of infrared, P (2) 51*h*. Synthetic quartz growth, P (3) 74*b*.

Bellemann, H. Method for soldering graphite to metals, (1) 22*b*.

Bellis, W. H., and Mankin, C. J. Analcime deposits in the Wichita Mountains, southwestern Oklahoma (abstract), B (9) 289*b*.

Belopol'skii, M. S., Belostotskaya, N. S., Aniskova, L. S., and Kublanovskaya, M. A. Features of wall tile production with spray-dried powders, (8) 242*c*.

Belostotskaya, N. S. See Belopol'skii, M. S.

Belotskii, D. P., and Galichanskii, V. G. CdSb-Cu section of the ternary system Cd-Sb-Cu, (4) 106*h*.

Belov, B. I. See Anfilogov, V. N.

Belt, C. B., Jr. Partial analysis of silicate rocks by atomic absorption, (1) 22*i*.

Belt, R. F. X-ray topography of Czochralski ruby, (1) 34*a*. X-ray topography of lithium ferrite, (3) 88*e*.

Belue, J. C. See Klink, J. P.

Belyaev, I. N., and Belyaeva, A. G. System Na_2TiO_3-NaCl-TiO_2, (3) 87*i*.

Belyaev, I. N., and Golovanova, T. G. K_2TiO_3-Na_2TiO_3 system, (9) 283*f*.

Belyaeva, A. G. See Belyaev, I. N.

Belyakov, I. M. See Tananaev, I. V.

Benard, E. J. J. Paste mold with evaporation grooves, P (11) 336*c*.

Benczek, K. See Obst, K. H.

Benda, L. See Maurer, K.

Bendix Corp. Furnace for treatment of wax-bonded sinterable preforms, P (4) 104*b*. Method of forming a semiconductor device by diffusing and alloying, P (9) 273*f*. Method of forming a semiconductor by masking and diffusion, P (1) 18*a*. Method of making a vitreous off-axis light filter, P (8) 235*i*.

Benecki, W. T., and Hummel, F. A. High-temperature mechanical properties of ceramic material (V) $(Zn_{0.6}Mg_{0.4})_2SiO_4$, (5) 153*a*.

Benedetto, B. di, and Cronan, C. J. Single crystals of $(Pb_xSr_{1-x})TiO_3$ grown by traveling heater method, (8) 243*c*.

Benjamini, E., and Duffek, E. F. Use of anodizing to reduce channelling on semiconductor material, P (3) 74*f*.

Benner, S. G. See Maddox, R. E.

Bennetch, L. M. Process for the preparation of iron oxide, P (11) 349*g*.

Bennett, F. R. See Langrod, K.

Bennett, G. E., and Olson, F. A. Magnetoelastic two-port configuration in YIG, (3) 71*j*.

Bennett, G. F. See Palermo, J. A.

Bennett, H. Developments in methods of analysis of ceramic materials, B (7) 224*f*. Results on the accuracy of industrial ceramic analysis, B (7) 224*h*. Sceptical chemist, B (7) 224*g*.

Bennett, H., Bishop, J. L., Jr., and Wulfinghoff, M. F. Practical Emulsions (Vol. I) Materials and Equipment; (Vol. II) Applications, B (9) 290*b*.

Bennett, H., and Reed, R. A. Analysis of chrome-bearing materials (III) determination of alumina, (6) 179*i*.
Bennett, J. D., Chaney, P. E., Jones, J. W., and McCaleb, S. B. Automatic control system for an X-ray diffraction apparatus, P (2) 55*c*.
Bennett, R. B. See Rice, H. H.
Bennett, R. W. Positioning apparatus, P (5) 130*b*.
Bennett, R. W., and Blanding, W. S. Cathode ray tube envelopes and methods of preparing parts therefor and fabricating such envelopes, P (5) 129*c*.
Bennett, R. W., and Golladay, C. F. Coating apparatus with tracking means, P (1) 8*f*.
Benson, G. E. Apparatus and process for making bulky [glass fiber] yarn, P (9) 264*h*.
Benson, H., Rickaby, A., and Beattie, J. R. Apparatus for detecting faults in or on the surface of flat glass, P (4) 94*a*.
Benthien, E. Reversible temperature dependence of metal film resistors, (10) 308*f*.
Bentle, G. G. See Carniglia, S. C.
Benton Clay Co. Clay products and the like, P (7) 214*j*.
Benz, R. Ranges of composition of the Th_3N_2O and ThO_2 phases equilibrated with different nitrogen (plus oxygen) atmospheres, (3) 85*f*.
Benz, R., Hoffman, C. G., and Rupert, G. N. Some phase equilibria in the thorium-nitrogen system, (3) 86*d*.
Beranger, G., Duffaut, F., Gelas, B. de, and Lacombe, P. Electron microscopic observations of thin zirconia films obtained by Zr oxidation, (4) 109*i*.
Beranger, G., Gelas, B. de, Ovo, K., and Lacombe, P. Study of the micrographic structure and oxidation behavior of a black zirconia obtained by fusion in an electron beam furnace, (7) 203*g*.
Beranger, G., and Lacombe, P. Modifications in the structure of pure zirconia or its compounds by the passage of dc at high temperatures, (1) 30*i*.
Berden, W. J. H. See Dal, P. H.
Berdonosov, S. S., and Lapitskii, A. V. X-ray study of Nb_2Br_8 and $NbBr_{3.04}$, (10) 327*g*.
Berendsen, A., Keezer, M. B., Schoubye, S., Santos Simoes, J. M. dos, and Tichelaar, J. Tiles—A General History, 5 (6) 192*f*.
Berens, L. W. See Schwiete, H. E.
Beretski, E. See Maier, Ya.
Berg, L. G., and Pribylov, K. P. Determination of thermal effects in the dehydration of $MgSO_4 \cdot 7H_2O$, (4) 107*i*.
Berg, P. W. See Nishimura, Y.
Berg, R. A. See Wharton, L.
Berger, C. Inorganic permselective membranes, P (10) 309*j*.
Berger, C., and Arrance, F. C. Battery containing a sintered aluminosilicate separator, P (7) 204*g*.
Berger, D. F. See Knupp, R. C.
Berger, H. Refinement of the crystal structure of orthorhombic tellurite, TeO_2, (8) 256*c*. See Jacobs, J. E.
Bergeron, C. G. See Laird, J. A.; Ricker, J. M.
Bergeron, J. A., and Gaines, G. L. Precise differential measurement of monolayer surface potentials, (1) 31*i*.
Berglund, C. N. Electroluminescence using GaAs MIS structures, (2) 49*g*.
Bergman, A. G. See Finkel'shtein, N. A.; Goryacheva, V. P.; Il'yasov, I. I.
Bergman, A. G., and Misler, Zh. V. System zinc and lithium chloride with lead chromate, (1) 33*g*.
Bergman, A. G., and Zimina, T. D. System Cs,Sr||Cl,SO_4, (10) 325*j*.
Bergmann, O. R. See Barrington, J.
Bergna, H. E., and Iler, R. K. Microcrystalline corundum powder, sols thereof, and processes for preparing both, P (5) 135*d*.
Bergner, K. Recent results of basic research on technical materials for ceramic prefabrication, B (9) 291*d*. See Ruehle, H.
Bergseth, H. Electrophoretic indication of thixotropic properties of a clay mineral suspension, (7) 217*i*.
Bergstresser, T. K. See Cohen, M. L.
Bergstrom, J. W., Sutherland, G., and Taeler, D. H. Ferriroll process, (3) 71*i*.
Berk, Ltd. High temperature flame spraying pistols, P (10) 296*f*.
Berkenblit, M. See Reisman, A.
Berkenblit, M., and Reisman, A. Vapor polishing of a semiconductor wafer, P (5) 143*c*.
Berkin, L. V. I., and Holdridge, D. A. Physicochemical properties for the characterization and control of Dorset ball clays, (1) 31*c*.
Berkowitz, J. See Stafford, F. E.
Berlincourt, D. A. See Jaffe, H.
Berman, R. Heat conduction in nonmetallic crystals, (2) 58*a*.
Bernard, G., Hocine, R., and Lupis, C. H. P. Thermodynamic conditions for spinodal decomposition in a multicomponent system, (6) 190*f*.
Bernett, F. E. Strain investigations of ceramic tile installations, (1) 10*c*.
Bernstein, J. L. See Abrahams, S. C.
Bernuth, G. von. Method of producing monocrystalline semiconductor bodies, P (7) 209*d*. See Herlet, A.
Berry, E. E. Structure and composition of some calcium-deficient apatites (I), (5) 158*a*; (II), (6) 189*g*.
Berry, J. M. See Mullin, J.
Bersch, C. F. See Smoke, E. J.
Bertaut, E. F. See Bacmann, M.; Dinh, C. D.; Guillen, M.; Montmory, M. C.
Bertaut, E. F., Mareschal, J., Pauthenet, R., and Rebouillat, J. P. Magnetic structures in $TCrO_3$ and $TMnO_3$ compounds (T = rare earths and Y), (6) 176*c*.
Bertaut, E. F., and Patrat, G. Structure of $LiGaTiO_4$, a new ordering type in spinels, (7) 222*a*.
Bertelsen, B. I. Process of depositing thin films by cathode sputtering using a controlled grid, P (4) 100*j*.
Bertolacini, R. J., and Brennan, H. M. Hydrocarbon conversion process and catalyst, P (7) 214*d*. Hydroforming process with mordenite, alumina, and platinum catalyst, P (7) 214*e*.
Bertolacini, R. J., and Strong, E. R., Jr. Hydrofining catalyst and process using same, P (10) 318*a*.
Bertolotti, R. L., and Fulrath, R. M. Effect of micromechanical stress concentrations on strength of porous glass, (1) 28*i*.
Berul, S. I. See Tananaev, I. V.
Berul, S. I., and Kryukova, A. I. Fusibility in the system calcium tungstate and the chlorides of Li, Na, and K, (10) 321*b*.
Beryllium Corp. Beryllium product comprised of beryllium particles coated with a metal beryllide, P (8) 240*b*.
Besenbruch, G. See Kent, R. A.
Bespalov, I. G. See Dombrovskaya, N. S.
Bessent, R. G., Hayes, W., and Hodby, J. W. Paramagnetic resonance and electron nuclear double resonance of substitutional hydrogen atoms in CaF_2, (1) 30*j*.
Bessing, R. See Dresia, H.
Bessonov, A. A. See Yastrebova, L. S.
Bessonov, A. F., Shalaginov, V. N., and Taksis, G. A. Investigation of phase conversions in mixtures of alumina and copper oxides, (9) 283*h*.
Bessonova, E. S. See Vorob'eva, O. V.
Best, H. S., and Borchert, A. E. Chip bonding machine, P (11) 343*g*.
Best, H. S., and Bowser, R. E. Article handling and cleaning apparatus, P (7) 208*g*.
Best, H. S., and Buergel, G. K. Machine for automatically testing and orienting miniature semiconductor chips, P (8) 244*i*.
Bestul, A. B. See Chang, S. S.
Bestul, A. B., and Chang, S. S. Excess entropy at glass transformation, (5) 127*a*.
Beth, W. F. See Seymour, J. A.
Bethlehem Steel Corp. Division wall for soaking pits, P (7) 204*b*. Magnesia chrome ore refractory, P (4) 97*g*.
Bettens, B. See Cypres, R.
Bettinali, C. Thermoluminescence and color centers in some irradiated vitreous and crystalline silicates, borates, and phosphates, B (10) 329*a*.
Bettinali, C., and Ferraresso, G. Thermoluminescence of unirradiated MgO and $Mg(OH)_2$, (7) 222*j*. Thermoluminescence in vitreous sodium silicate, (4) 93*i*.
Bettinali, C., Ferraresso, G., and Bonetti, G. Thermoluminescence and color centers in glasses of the M_2O-Al_2O_3-SiO_2 system, (1) 8*c*.
Bettinali, C., Gottardi, V., and Ferraresso, G. Thermoluminescence of vitreous sodium aluminosilicates and germanates, B (10) 329*b*.
Betz, C. R. Passivating silicon semiconductor devices with sputtered tungsten oxide at low temperatures, P (2) 52*b*.
Beucherie, P., and Wurm, J. G. Process for the preparation of mixed carbides, P (7) 205*h*.
Beudin, L. L. J. B. Rotating grinders, P (8) 251*k*.
Beus, M. D. See Kitaigorodskii, I. I.
Beutler, H., Beatty, R. L., and Coobs, J. H. Low-density pyrolytic-carbon coatings for nuclear fuel particles, (2) 44*i*.
Bevan, A. W., Jr. See Veigele, W. J.
Bevan, S. C. See Brown, R. A.
Bevelo, A. J., and Barker, W. A. Laser emission lines and materials, (5) 138*g*.
Bever, M. B. See Jena, A. K.
Beyer, G. J. See Paxton, R. R.
Beyerlein, F. W. Method for mass producing semiconductor devices, P (11) 344*e*. Method of treating the surface of semiconductor devices to improve the noise characteristics, P (10) 310*j*.
Beyersdorfer, P. Microindentation hardness and elasticity and Poisson's ratio of glasses, (7) 196*f*; reply to discussion, (7) 196*h*. See Koranyi, G.
Beynon, J., and Head, K. Phenomenon associated with the abrasion of Cr-SiO cermet resistors, (10) 307*h*.
Bhan, S. See Jain, K. C.
Bhandary, V. S. See Beck, T. A.
Bhandary, V. S., Gupta, P. K., and Nijhawan, B. R. Expansion characteristics of indigenous sands, (6) 173*a*.
Bhappu, R. B. See Deju, R. A.
Bhasker, K. Rehandling porcelain enamel parts causes damage, (3) 63*d*.
Bhat, R. See Moorthy, V. K.
Bhatt, K. V., and Subramanyam, C. G. Evaluation of torroidal magnetic materials, (5) 138*h*.
Bhatt, V. S. Ceramics—past and present trends, (10) 327*j*.
Bhattacharya, J. See Ramaswamy, P. S.
Bhattacharya, T. K. Current saturation in n-GaAs, (8) 243*a*.
Bhide, V. G., Hegde, M. S., and Deshmukh, K. G. Ferroelectric properties of lead titanate, (11) 352*i*.
Bhide, V. G., and Shenoy, G. K. ^{57}Fe Moessbauer effect in nickel oxide, (9) 282*j*.
Bhushan, B. Talc and its use in the manufacture of steatite, forsterite, and cordierite bodies, (6) 176*i*.
Bialek, F., Machalica, A., and Szymborski, W. Mineralogical and chemical study of raw Brazilian magnesites, (3) 67*c*.
Biberman, L. M. Radiative transfer in spectral lines, (10) 324*c*.
Bicking, C. A. Designing valid experiments, (1) 20*j*. Sampling of bulk materials, (6) 181*c*.
Bicking, C. A., Bingham, R. S., Jr., and Weiss, R. L. Automatic data logging for experimentation and quality control, (2) 53*i*.
Bickley, F. See Mackenzie, F. T.
Biegler, H., and Kallrath, G. Process for producing silica in the form of hollow spheres, P (8) 251*f*.
Biehler, W. Manufacture of lightweight firebrick and its use in industrial furnaces, (7) 202*g*.
Bielawski, C. A. See Beaver, W. W.
Bieler, B. H. Photometric counting of seeds and stones in glass, (10) 298*g*.
Bieler, B. H., and Madison, R. P. Simple continuous solid particle shape classifier, (6) 179*e*.
Bienstock, D., Field, J. H., and Myers, J. G. Process development in removing sulfur dioxide from hot flue gases (III) pilot plant study of the alkalized alumina system for SO_2 removal, (1) 24*f*.
Biet, J. P., and Dufour, C. Delay line having a thermoelectric generator responsive to rate of heat transfer, P (11) 343*b*.
Bigare, M., Guinier, A., Mazieres, C., Regourd, M., Yannaquis, N., Eysel, W., Hahn, T., and Woermann, E. Polymorphism of tricalcium silicate and its solid solutions, (1) 31*g*.
Bigelow-Liptak Corp. Furnace wall structure, P (5) 135*c*.
Bihis, M. L. M., and Cubacub, C. V. Volumetric analysis of titanium, (2) 55*a*.
Bilaney, S. M. See Brown, R. K., Jr.
Billiau, R. See Schechter, M.
Billings, D. D. See Manring, W. H.
Billmeyer, F. W., Jr. Significance of recent CIE recommendations for color measurement, (6) 188*b*. See Atkins, J. T.
Billmeyer, F. W., Jr., and Smith, R. Optimized equations for MacAdam color differences, (6) 18*7a*.
Billue, R. F. Fractured clay, P (1) 25*b*.
Bil'tyukova, E. P., Andreeva, L. N., and Gerasimova, G. I. Flame-photometric method for determination of alkali oxides in glasses and silicate raw materials, (10) 314*d*.
Bingham, J. T. See Gross, P.
Bingham, R. S., Jr. See Bicking, C. A.
Binkley, M. E. Insulating riser sleeve composition, P (11) 340*e*.
Binnis, K. Corrosion-inhibiting titanium dioxide pigments, P (1) 25*j*.
Binns, D. B. Results and discussion of testing program, B (4) 122*c*.
Binns, R. A. Barroisite-bearing eclogite from Naustdal, Sogn og Fjordane, Norway, (4) 106*f*.
Bird, G. S., Jr. Thermoelectric junction assembly with insulating irregular grains bonding insulating layer to metallic thermojunction member, P (7) 210*d*.
Bird, N. F. See Bell, R. J.
Bird Machine Co. Calcium sulfate centrifuging, P (7) 194*j*.
Bird & Son, Inc. Intumescent coated roofing granules and asphalt composition felt-base roofing containing them, P (5) 131*b*.
Birgeneau, R. J., Hutchings, M. T., and Rogers, R. N. Electric quadrupole-quadrupole interaction between cerium pairs in lanthanum chloride, (11) 352*f*.
Birk, R. Sputtered silicon dioxide for multilayer interconnects, (10) 308*b*.
Birk, R. K. See Moore, M. D.
Birman, J. L., Lax, M., and Loudon, R. Intervalley-scattering selection rules in III-V semiconductors, (10) 322*i*.
Birnbaum, M., Fincher, C. L., and Stocker, T. L. Thermal effects in semiconductor reflectivity enhancement, (1) 17*d*.
Birrell, R. W. See Aiken, H. H.
Biryukova, I. M. See Botvinkin, O. K.
Bishay, A. (editor). Interaction of Radiation with Solids—Proceedings of the Cairo Solid State Conference Held at the American University, Cairo, September 1966, B (10) 328*c*.
Bishay, A., and Arafa, S. Manganese arsenic borate glass dosimeter, (1) 6*i*.
Bishay, A., and Hassan, F. Radiation damage studies of Libyan Desert silica glass, B (10) 328*i*.
Bishay, A., Maklad, M., Gomaa, I., and Arafa, S. Gamma induced coloration in relation to structural changes in glass, B (10) 328*j*.
Bishop, F. L. Cathode-ray tube having an improved fiber optic faceplate, P (1) 8*e*. Glass semiconductor housing having its interior surfaces covered with an alkali-free solder glass, P (5) 141*j*. Radiation indicating glass, P (4) 95*d*.
Bishop, J. & Co., Platinum Works. Process of producing oxides of platinum and palladium, P (3) 78*c*.
Bishop, J. L., Jr. See Bennett, H.
Bishop, W. M., and DiCristina, V. Prediction technique for ablative material performance under high-shear reentry conditions, (9) 268*g*.
Bishui, B. M. See Aggarwal, P. S.
Bishui, B. M., and Ghosh, D. K. Mineralogical nature of Bansi clays by the intercalation technique, (6) 182*e*.

Bishui, B. M., Ghosh, D. K., and Prasad, J. Mineralogy of Bansi clays, (4) 113*d*.

Biswas, A. B. See Kshirsagar, S. T.; Rao, V. V. S.

Biswas, S. R. See Mukerji, J.

Bither, T. A., Gillson, J. L., and Young, H. S. Synthesis of molybdenum and tungsten bronzes at high pressure, (6) 189*h*.

Bither, T. A., Jr. Ternary copper, zinc, cadmium, and manganese dichalcogenides having the pyrite-type crystal structure, P (6) 178*h*.

Bitko, S. Glass-metal seal, P (3) 65*i*.

Bittmann, C. A., and Sah, Chih-Tang. Method of forming a metal rectifying contact to semiconductor material by displacement plating, P (11) 344*i*.

Bizon, P. See Odler, I.

Bizzarri, V. Binding means useful in the manufacture of shaped bodies, P (11) 339*j*.

Bjerkelund, E., and Kjekshus, A. Structural properties of the $Ta_{1+x}Se_2$ phase, (5) 158*j*.

Bjorling, G., and Kolta, G. A. Wet oxidation of iron sulfide concentrates catalyzed by nitric acid, (3) 77*g*.

Bjornson, G. Titania-chromium oxide catalyst and polymerization process, P (5) 149*c*.

Black, J. F., and Ku, S. M. Preparation and properties of AlAs-GaAs mixed crystals, (7) 207*i*.

Black, J. R. Cleaning of semiconductor devices, P (8) 244*c*.

Black, W. C. See Abel, W. R.

Blackburn, A. R., and Kendall, V. D. Crystalline bonded ceramic ware pressing mold and method of making, P (8) 242*d*. Glass bonded ceramic ware pressing mold and method of making, P (9) 271*g*.

Blackburn, L. D., Burte, H. M., and Bonanno, F. R. Filament-matrix interactions in metal matrix composites, B (4) 121*h*.

Blackburn, P. E., and Mattuck, J. B. Silicide-coated composites and method of making them, P (8) 230*a*.

Blacknall, D. M. See Williams, E. W.

Blackstone Corp. Ultrasonic transducers, P (5) 143*c*.

Blaha, E. Process for making a filter, P (3) 69*g*.

Blaha, M. See Pacl, J.

Blahnik, C. E. Differentially pumped ultrahigh-vacuum system baked to 900°C, (5) 145*e*.

Blaine, R. L., Arni, H. T., and DeFore, M. R. Interrelations between cement and concrete properties (III) compressive strengths of portland cement test mortars and steam-cured mortars, (10) 295*a*.

Blair, F. E. See Miller, F. W.

Blair, G. E., Hamblen, D. P., and Weidel, R. A. Method of changing the conductivity of ceramic materials, P (10) 300*j*.

Blair, J. See Shaver, P. J.

Blair, R. E. See Buell, H. W.

Blais, M. See Verneker, V. R. P.

Blake, H. E., Jr. See Fursman, O. C.

Blakeslee, A. E. See Kontrimas, R.

Blanc, M. See Petit, G.

Blanchard, F. N. Thermoluminescence of synthetic fluorite, (5) 140*d*.

Blanchard, M. B. Method for determining the density of microsize spherical particles, (4) 103*b*.

Blanding, W. S. See Bennett, R. W.

Blanding, W. S., Foster, L. H., and Spremulli, P. F. Metal inserts for use in the wall of glass envelopes for the support of electrodes, P (4) 100*i*.

Blank, H., and Ronchi, C. Stacking faults and antiphase boundaries in U_4O_9, (9) 286*f*.

Blank, K. Electrical conductivity of alkali silicate glasses, (8) 231*b*.

Blanken, G. See Rosenstock, H. B.

Blaschek, H. Ceramic artists and their work—Hans Heckmann and Renate Heckmann, (10) 293*h*.

Blase, E. F. See Rutland, D. F.

Blasse, G. Crystal structure and fluorescence of compositions $ATiNbO_6$, $ATiTaO_6$, and $ATiSbO_6$, (1) 27*c*. Eu^{3+} fluorescence in mixed metal oxides (IV) photoluminescent efficiency of Eu^{3+}-activated oxides, (10) 321*c*.

Blasse, G., and Bril, A. Crystal structure and fluorescence of some lanthanide gallium borates, (5) 150*b*. Eu^{3+} fluorescence in mixed metal oxides (III) energy transfer in Eu^{3+}-activated tungstates and molybdates of the type Ln_2WO_6 and Ln_2MoO_6, (10) 321*b*. Luminescent properties of $NaGdO_2$:Eu, (11) 354*f*. New phosphor for flying-spot cathode-ray tubes for color television—yellow-emitting $Y_3Al_5O_{12}$-Ce^{3+}, (2) 49*j*.

Blasse, G., and Vries, J. de. New family of lanthanide compounds—lithium lanthanide silicates and germanates, (5) 155*c*.

Blaszyk, P. E. See Riebling, E. F.

Blau, T. N., and Davis, E. J. High temperature thermal insulation, P (1) 12*i*.

Blauer, J. A., Greenbaum, M. A., and Farber, M. Thermodynamic and physical properties of beryllium compounds (VII) enthalpy and entropy of sublimation of beryllium fluoride, (11) 357*c*.

Blaw-Knox Co. Composite carbonaceous members for furnace rolls and other high temperature members, P (2) 46*h*.

Blech, I. A., and Averbach, B. L. Long-range magnetic order in MnO, (8) 254*f*.

Blickensderfer, R. See Henry, J. L.

Blin, C. Tests on the high frequency and very high frequency drying of ceramic products, (6) 175*e*. Vital importance of the control of raw materials in the modern ceramic industry, B (9) 291*d*.

Blinov, V. A. See Kitaigorodskii, I. I.

Bliznakov, G., Peshev, P., and Niemyski, T. Preparation of crystalline aluminum borides by a vapor deposition process, (2) 45*i*.

Bloch, H. S., and Nixon, W. G. Catalyst manufacture, P (8) 250*h*.

Blocher, J. M., Jr. See Oxley, J. H.

Block, F. E. See Skirvin, F. A.

Block, S. See Evans, H. T., Jr.

Blokh, K. I. Thermal expansion and structure of glass fibers, (8) 234*e*.

Blokh, S. A., Guz, D. B., et al. Conveyor kiln with walking hearth for fast firing of porcelain without saggers, (4) 104*b*.

Blood, C. M. See Bruin, H. J. de.

Blood, W. R. Method of toughening glass article and article produced, P (4) 95*e*. See Pilkington Brothers, Ltd.

Bloom Engineering Co., Inc. Burner for tempered flame operation, P (5) 147*g*.

Bloor, D., Ellis, E., Martin, D. H., and Wadham, A. Low-lying crystal-field spectra of rare earth compounds, (11) 354*e*.

Bloss, F. D. Suggested terminology for interstratified clay minerals, (2) 59*j*.

Blotekjaer, K. Mobility and temperature of electrons in polar semiconductors, (5) 139*a*.

Bluemel, F. House stoves in the modern style, (10) 293*i*.

Blum, J. E., and Ezell, J. W. Spark plug with a conductive glass seal electrode of glass, copper, and zinc, P (2) 52*f*.

Blum, P., Moreau, C., and Bochirol, L. Process for the fabrication of fuel elements for nuclear reactors, P (7) 205*f*.

Blum, P. L. See Guinet, P.

Blum, S., Mountvala, A., and McKinley, R. Method of making piezoelectric layers by flame spraying, P (9) 274*b*.

Bluman, D. E., Galli, A. F., Coates, N. H., Spencer, J. D., and Rosenecker, C. N. Heat transfer coefficients for continuously recirculated gas-solid suspensions, (5) 148*a*.

Blume, A. J. Operation of the pug mill-extruder, (10) 301*h*.

Blume, M. Theory of the first-order magnetic phase change in UO_2, (8) 258*a*.

Blumenfeld, J. F. Air stream device for cooling glass furnace electrodes, P (11) 335*c*. Electrode holder for glass melting furnace, P (8) 249*f*, P (10) 300*g*. Engineering and economic considerations in evaluation of glass melting furnaces, (1) 6*b*.

Blumenthal, J. Method of forming a miniature nozzle from a glass tube, P (10) 301*a*.

Blust, H. L. See Shaffer, G. A., Jr.

Bluvshtein, M. N., Zykova, Z. K., et al. Statistical method for checking silica density, (9) 277*f*.

Boart & Hard Metal Products S. A., Ltd. Abrasive cutting tools such as saws, P (3) 61*h*.

Boatman, J. C. See McCarley, R. E.

Boatner, L. A. See Abraham, M. M.

Bober, M. See Beisswenger, H.

Bobo, P. O. Polyphase arc furnace with control system to raise one electrode prior to all electrodes striking an arc, P (7) 214*a*.

Bochirol, L. See Blum, P.

Bockris, J. O'M., Richards, S. R., and Nanis, L. Self-diffusion and structure in molten group II chlorides, (11) 356*a*.

Boddy, P. J. See Frova, A.

Bode, D. E. Lead salt detectors, B (8) 260*f*.

Boderke, H. See Taubmann, H.

Bodiford, W. E. See Bryant, B. E.

Bodnar, R. See Wang, R.

Bodnar, Z., and Ratajczyk, F. Autocollimation method of optical glass heterogeneity measurement, (5) 126*h*; Some remarks concerning optical glass homogeneity measurement with the help of the autocollimation method, (5) 128*i*.

Boeer, K. W. See Esbitt, A. S.

Boehm, H. P. Functional groups on the surface of solids, (10) 321*a*.

Boehm, P., and Maaz, K. Hall generator magnetic structure, P (6) 177*b*.

Boehme, H. J. See Schwiete, H. E.

Boehme, W. Study of the porosity of long shaft insulator bodies by measuring the velocity of ultrasonic waves with a direct reading device, (2) 49*a*.

Boeing Co. Electrode for glass melting furnaces, P (7) 198*d*. Porous ceramic oxides and method, P (10) 304*h*. X-ray cryostat, P (9) 266*b*.

Boemmel, H. See Kuendig, W.

Boenisch, D. Apparatus for measurement of physical characteristics of solid bodies [molding sands], P (1) 12*h*.

Boettcher, A. Fuel element for nuclear reactors, P (3) 68*d*.

Bogachek, L. M., and Demchishin, A. V. Electron-beam apparatus for the vacuum vaporization of metallic and nonmetallic samples, (10) 314*h*.

Boganov, A. G., Pirogov, Yu. A., and Makarov, L. P. Investigation of the effective thermal conductivity and total emissivity of heat-resistant ceramic coatings of refractory oxides produced by gas-flame spraying, (5) 132*g*.

Boganov, A. G., Rudenko, V. S., and Bashnina, G. L. Correlations in the crystallization and nature of quartz glass, (1) 5*g*.

Bogar, I. See Toeroek, L.

Bogdanova, G. S., and Orlova, E. M. Structural changes in glasses of the SiO_2-Al_2O_3-BaO-TiO_2 system during the initial crystallization stage, (2) 40*c*.

Bogdanova, G. S., Orlova, E. M., and Zevin, L. S. Dependence of the amount of crystalline phase on the heat-treating conditions of sitalls in the SiO_2-Al_2O_3-BaO-TiO_2 system, (6) 185*b*.

Boggs, A. C. Sheathed electric heating elements, P (8) 230*a*.

Boggs, S., Jr. Measurement of roundness and sphericity parameters using an electronic particle size analyzer, (2) 54*c*. Numerical method for sandstone classification, (1) 30*f*.

Boggum, P. See Glaser, W.

Bogh, E. String effect and its use in solid state investigations, B (10) 329*b*.

Bogomolov, B. N., Gal'perina, T. Ya., and Pavlov, Yu. S. Porphyroids as siliceous component in cement raw mix, (3) 62*d*.

Bogosh, R. B. See Beck, J. H.

Bogoslovskaya, L. N. See Danchuk, I. M.

Boguslavskii, I. A., Abrosimov, V. A., and Markelova, M. Ya. Strengthening of sodium calcium silicate glass by low temperature ion exchange, (8) 234*f*.

Bohling, W. C. See Folk, H. F.

Bohn, J. R. See Felgar, R. P.

Bohor, B. F. High-temperature phase development in illitic clays, B (6) 191*h*. See Ehrlinger, H. P.

Boicey, C. R. Method of producing multiple glass sheet glazing units, P (9) 265*h*.

Boicey, J. H. See Walters, E. L.

Boichun, V. Yu. See Grosheva, V. M.; Tresvyatskii, S. G.

Boija, S. See Huldt, L.

Boinot, J. D., Naudin, F., and Zarzycki, J. Development of ultraviolet absorption bands of vitreous sodium silicates during melting, (9) 280*e*.

Bokhyn'ska, A. See Vol'ski, V.

Bokin, P. Ya., Korelova, A. I., and Piskunova, A. D. Kinetics of phase transformations and change in microstructure and mechanical properties during the sitallization of lithium aluminosilicate glass, (8) 232*g*.

Bokros, J. C. See Price, R. J.; Sanderfur, N. L.

Bokros, J. C., Price, R. J., and Tully, G. R., Jr. Anisotropy of extruded graphite tubes, (5) 131*e*.

Bokros, J. C., and Schwartz, A. S. Pyrolytic graphite and nuclear fuel particles coated therewith, P (4) 97*f*.

Boksay, Z., Bouquet, G., and Dobos, S. Diffusion processes in the surface layer of glass, (1) 5*e*. Kinetics of the formation of leached layers on glass surfaces, (8) 232*e*.

Bokuchava, G. V. See Loladze, T. N.

Bolboceanu, V. See Veiser, I.

Boles, S. J. See Forchheimer, O. L.

Bolgar, A. S. See Fesenko, V. V.

Bolger, D. E. See Whitaker, J.

Bolger, D. E., and Barry, B. E. Formation of aluminum, gallium, arsenic, and phosphorus binary coatings, P (10) 309*f*.

Boliden Aktiebolag. Rod screen, P (10) 312*i*.

Boller, E. Heating rods for electric furnaces, (7) 213*i*.

Bollmann, W. Geometry of grain and phase boundaries (I) general theory; (II) applications of general theory, (8) 253*j*.

Bolton, H. C., and Shall, C. A. Field gradient in BeO, (3) 67*f*.

Boltz, D. F., and Mellon, M. G. Light absorption spectrometry, (10) 314*f*.

Bolutenko, A. I. See Matveev, M. A.

Bonanno, F. R. See Blackburn, L. D.; Burte, H. M.

Bondar, I. A. See Toropov, N. A.

Bondarenko, V. G. See Yamshchikov, V. S.

Bondarev, D. E. Causes of transformation of the magnetic properties of scandium-containing ferrites, (1) 16*b*.

Bondy, C., Vidal, J. P., and Robin, G. Activable tracer method and recent applications in glassmaking, (11) 333*d*.

Bonetti, G. See Bettinali, C.

Bongers, P. F., and Enz, U. Metamagnetism of $NaNiO_2$, (11) 354*d*.

Bonin, G. E. Cutter for glass pipe, P (11) 335*j*. Grinding and polishing pad, P (3) 65*i*.

Bonitz, E. Reactions of elementary silicon, (5) 157*e*.

Bonjour, E., and Pierre, J. Device for the thermal study of a sample, P (10) 316*a*.

Bonnan, D. See Heyndryckx, P.

Bonne, H., and Beek, W. J. Influence of drawing-off force on the flow rate and diameter of spun glass fibers, (5) 127*e*.

Bonner, H. See Schenck, H.

Bonner, M. K. Technique for improving information quality in electron micrograph prints, (5) 146*d*.

Bonner, W. A. See Van Uitert, L. G.

Bonner, W. A., Dearborn, E. F., Geusic, J. E., Marcos, H. M., and Van Uitert, L. G. Dielectric and electrooptic properties of lead magnesium niobate, (4) 107*f*.

Bonner, W. A., and Van Uitert, L. G. Growth of divalent metal aluminates, P (6) 190*g*.

Bonnet, R. E., and Hill, J. S. Method of making a mandrel for precision-shaping internal surfaces on glass vessels, P (6) 171*d*.

Bonney, L. G., Jr. See Shaffer, R. A.

Bonnin, F. See Bouillard, Y.

Bonning, N. G. Cup topping machine, P (3) 70*f*.

Bonvallet, G. G. Reflex marker, P (1) 10*a*.

Boone, D. H. See Ellison, E. G.

Boone, F. H. See Quentin, R. J.

Boose, E. D. See Johnson, M. R.

Booth, A. P. Water closet installations, P (10) 306*f*.

Booth, F. T. See Associated Lead Manufacturers, Ltd.

Bopp, H. F. See Duke, D. A.

Bopp, H. F., Megles, J. E., and Morrissey, J. W. Method of glazing semicrystalline glass-ceramic articles and resuitant intermediate layer containing composite, P (8) 235*h*.

Borchardt, H. J. Efficiency of Eu^{3+} fluorescence in oxygen-dominated host lattices, (3) 80*j*.

Borchert, A. E. See Best, H. S.

Borchert, W., Petzenhauser, I., and Gugel, E. Indialite and barium osumilite in fired bodies, B (7) 226*b*.

Borg, I. Y., and Smith, D. K., Jr. X-ray diffraction studies on CdTe at high pressure, (8) 258*c*.

Borg-Warner Corp. Self-rimming lavatory, P (4) 98*g*.

Borgkvist, T. A. Walking beam furnace for effecting different feed speeds of the charge, P (6) 182*c*.

Borisov, B. I. Water glass—binder in different compositions, (5) 125*a*.

Borisov, V. G., and Yudin, B. F. Thermodynamics of reactions in the SiO_2-SiC system, (9) 288*d*.

Borie, W. N., and Sharma, B. L. Method of casting sound ingots of thermoelectric materials, (7) 207*e*.

Borom, M. P. Magnetic studies of iron diffused into sodium disilicate glass, (3) 64*d*.

Borom, M. P., and Pask, J. A. Kinetics of dissolution and diffusion of the oxides of iron in sodium disilicate glass, (10) 297*j*. Kinetics of the interfacial reaction and diffusion processes in the system iron-sodium disilicate glass, (3) 64*b*.

Borovicka, R. See Croft, W. J.

Borovskii, I. B. See Rydnik, V. I.

Borrelli, N. F. Faraday rotation in glasses, (5) 127*a*.

Borrelli, N. F., and Su, G. J. Infrared spectra of glass network formers and their interpretations, (6) 167*a*.

Borresen, H. C. Fluorescence spectrophotometer recording corrected excitation spectra between 100°K and room temperature, (6) 180*c*.

Bosch, Robert, G.m.b.H. See Robert Bosch G.m.b.H.

Bose, U. P., Lokras, S. G., and Chakravarti, B. N. Study of the rate of erosion of the silica roof of a 250-ton open-hearth furnace by tracer techniques, (1) 12*f*.

Bosler, K. Self-rimming lavatory, P (4) 98*g*.

Bosman, A. J., and Crevecoeur, C. Mechanism of the electrical conduction in Li-doped NiO, (9) 284*b*.

Boss, B. D., and Stejskal, E. O. Antisotropic diffusion in hydrated vermiculite, (6) 183*g*.

Bostick, R. E. See Fisher, P. M.

Botden, T. P. J. See Haans, P. F. A.; Klomp, J. T.

Botka, A. T. Semiconducting device, P (5) 142*h*

Botsco, R. J. Nondestructive testing of composite structures with the Sonic Resonator, (7) 212*g*.

Bott, T. R., and Barker, A. J. Examination of glass fiber surfaces using a scanning electron microscope, (8) 231*j*.

Botvinkin, O. K. See Ananich, N. I.

Botvinkin, O. K., and Denisenko, O. N. Ion exchange and increased strength of glass, (10) 297*i*.

Botvinkin, O. K., Kulikova, E. N., Ryabov, V. A., and Fedoseev, D. V. Statistical evaluation of the strength of window glass, (11) 335*g*.

Botvinkin, O. K., Zaporozhskii, A. I., Zaporozhskaya, Z. P., and Biryukova, I. M. Electron-microscope study of quartz glass, (10) 297*j*.

Bouchard, J. G. F. Chopper amplifier having high breakdown voltage, P (5) 140*h*.

Bouchard, R. J., Robinson, W. T., and Wold, A. Structure and properties of NiV_2Se_4, (5) 158*d*.

Bouchaud, J. P. See Fruchart, R.

Bouillard, Y., and Bonnin, F. Stoichiometry of sodium metaniobate, (7) 221*i*.

Boulton, William, Ltd. See William Boulton, Ltd.

Bouquet, G. See Boksay, Z.

Bourat, G. Extraction of the sulfuric acid complexes of beryllium using primary amines, P (4) 105*b*.

Bourdeau, R. G., and Papalegis, F. E. Process for producing coatings on carbon and graphite filaments, P (5) 136*c*. Process for producing pyrolytic graphite whiskers, P (7) 205*j*.

Bourrasse, A., Carteret, Y., Elston, J., and Lucas, R. Moderator-fuel element, P (1) 13*b*.

Bowdish, F. W. Process for refining sands, P (6) 183*b*.

Bowen, D. H. See Clarke, F. J. P.; Morgan, C. S.

Bowers, D. J. See Hedden, W. A.

Bowers, G. M. See Hammond, M. L.

Bowles, A. G. Apparatus for the manufacture of brick and tile, P (2) 43*a*.

Bowman, E. ~7. Rapid cooling system for glass annealing lehrs, P (6) 171*f*.

Bowman, H. A., Schoonover, R. M., with Jones, M. W. Procedure for high precision density determinations by hydrostatic weighing, (2) 54*g*.

Bowman, H. R., Hyde, E. K., Thompson, S. G., and Jared, R. C. Application of high-resolution semiconductor detectors in X-ray emission spectrography, (5) 144*i*.

Bowman, J. Furnace and refractory, P (3) 68*e*. Refractory bonding composition, P (3) 69*d*.

Bowman, W. S. See Webster, A. H.

Bowser, R. E. See Best, H. S.

Boyd, G. D., and Ashkin, A. Theory of parametric oscillator threshold with single-mode optical masers and observation of amplification in $LiNbO_3$, (11) 357*d*.

Boyd, J. R., Mones, A. H., and Schottmiller, J. C. Electrical device, method, and material, P (6) 177*d*.

Boyden, J. H. See Grayson, L. P.

Boyer, A. J. G., Fray, D. J., and Meadowcroft, T. R. Application of the rigid sphere model to the pure molten phosphates of Ca, Li, Na, and Zn, (2) 57*d*.

Boyer, J. L., and Hartman, R. A. Large area wafer semiconductor device, P (8) 244*h*.

Boykin, O. F. Method of making a thin film capacitor, P (2) 51*b*. Thin film capacitor, P (10) 311*f*.

Boyle, J. E. See Rabo, J. A.

Bozsin, M. Chemistry of water used in the porcelain enamel industry, (9) 262*h*.

Bracco, D. J. See Wacher, P.

Bracht, L. J., Devall, K. L., and Krause, H. J. Molded resistor and method of fabricating, P (3) 73*h*.

Bracken, A. L., Jr. See Hanks, G. F.

Brackpool, J. L., and Phelps, L. A. Vibratory compacting of metal powders, B (3) 80*j*.

Brads, Y. See Mitra, S. S.

Bradbury, B. T., Demant, J. T., and Martin, Mrs. P. M. Solid fission products in irradiated uranium dioxide, (11) 339*f*.

Bradford, J. L. See Woyski, M. M.

Bradhurst, D. H., and Bruin, H. J. de. Electrical conductivity of BeO and BeO binaries, (7) 201*f*.

Bradhurst, D. H., Draley, J. E., and Van Drunen, C. J. Electrochemical model for the oxidation of zirconium, (4) 109*g*.

Bradley, C. D. See Tate, M. C.

Bradley, C. H., Jr. Abrasive separator, P (5) 123*h*.

Bradley, D. J., Magyar, G., and Richardson, M. C. Optical sum generation of the two-frequency output of a giant pulse ruby laser, (2) 49*j*.

Bradley, F. N. Diffraction line shifts observed in fine-grained barium titanate, (6) 185*e*. Effect of grain size on discoloration of barium titanate powder, (10) 319*g*.

Bradley, J. N., and Greene, P. D. Potassium iodide + silver iodide phase diagram—high ionic conductivity of $KAgI_3$, (3) 85*b*. Solids with high ionic conductivity in group I halide systems, (7) 221*c*.

Bradley, R. S., Munro, D. C., and Whitfield, M. Reactivity and polymorphism of selected nitrides at high temperatures and high pressures, (4) 115*c*.

Bradley, W. F. (editor). Clays and Clay Minerals—Proceedings of the Eleventh National Conference, Ottawa, Ontario, Canada, August 1962, B (5) 160*i*; Proceedings of the Twelfth National Conference, Atlanta, Ga., September-October 1963, B (6) 191*c*. See Cox, W. L.; Kunze, G. W.; Wang, R.

Bradley, W. F., and Bailey, S. W. (editors). Clays and Clay Minerals—Proceedings of the Thirteenth National Conference, Madison, Wis., October 1964, B (7) 224*j*.

Bradt, E. C., and Ansell, G. S. Growth of barium titanate single crystals by a modified Remeika technique, (1) 29*f*.

Bradt, R. C. Ferroelectric ceramics in the electron microscope, (11) 342*e*.

Brady, E. L., and Wallenstein, M. B. National Standard Reference Data System, (2) 54*e*.

Brady, J. G. Processing problems associated with some typical ceramic clays and shales of Ontario, (11) 349*b*.

Brady, J. G., Bell, K. E., and Zengals, L. K. Some methods of investigating firing problems, (9) 277*c*.

Braecher, L. Efflurescence—causes and cures, (4) 95*h*.

Brafman, O., and Steinberger, I. T. Optical band gap and birefringence of ZnS polytypes, (9) 285*a*.

Bragg, H. A. See Roberts, G. L., Jr.

Brailsford, A. D. Effective mass of a dislocation, (8) 253*i*. Stress field of a dislocation, (8) 257*f*.

Brambilla, G., and Neri, D. Method of forming spheroids of particulate agglomeration-resistant refractory metal oxides, P (11) 349*a*.

Bramman, J. I., and Yates, G. Crystal orientation dependence of X-ray production in bulk specimens, (8) 248*a*.

Brand, H. Brick manufacturing apparatus, P (2) 43*b*.

Brandhorst, H. See Kasper, J. S.

Brandon, C. S. See Mayland, B. J.

Brandt, B. J. See Illis, A.

Brandt, W. W., and Hattori, M. Composite diffusion mechanisms and diffusional anisotropy of helium in beryl, aquamarine, quartz, and related glasses, (3) 79*j*.

Brandt, W. W., Hattori, M., and Sreenivasan, V. R. Desorption of He and $^{14}CO_2$ from micas, (3) 79*i*.

Brandwine, M. D. Burner system upgrades test furnaces, (2) 55*j*.

Braniski, A. Properties of barium silicate cements as function of their clinker minerals, (8) 228*h*.

Branska, K. Applications of the electron microscope for studies of electrotechnical porcelain, (2) 48*h*.

Bransky, I., and Hed, A. Z. Thermogravimetric determination of the composition-oxygen partial pressure diagram of wustite ($Fe_{1-\delta}O$), (5) 159*e*.

Bransky, I., and Tannhauser, D. S. High-temperature defect structure of ferrous oxide, (4) 111*h*.

Bratschun, W. R. Process for optionizing electrical and physical characteristics of ferroelectric materials, P (1) 18*j*.

Bratton, R. J., and Brindley, G. W. Kinetics of vapor phase hydration of magnesium oxide (II) dependence on temperature and water vapor pressure; (III) effect of iron oxides in solid solution, (3) 82*j*.

Bratton, R. J., and Ho, S. M. $MgAl_2O_4$ fibers and platelets, (2) 59*b*.

Brau, M. J. Ge-S-Te glass compositions and infrared detection system, P (6) 170*j*. See Hilton, A. R., Jr.

Brau, M. J., and Jarman, H. E. Inorganic glass composition, P (6) 170*g*.

Brau, M. J., Johnson, R. E., and Patterson, R. J. Ge-Sb-Se glass compositions, P (4) 94*h*. Ge-Se-Te glass and infrared detection system, P (1) 9*b*.

Brauer, G., and Leibrandt, F. Zirconium-molybdenum nitride, (8) 258*f*.

Braunstein, M. See Grossman, J. J.

Bray, P. J. Magnetic resonance studies of bonding, structure, and diffusion in crystalline and vitreous solids, B (10) 328*i*. See Greenblatt, S.; Lee, S.

Bray, P. J., Kline, D., and Poch, W. ^{11}B NMR measurements on high pressure modifications of B_2O_3 and potassium borate glasses, (6) 166*f*.

Brayman, J. See Zeitlin, A.

Breck, D. W. See Flanigen, E. M.

Bredig, M. A. Electrical conductance and density of alkali metal nitrate melts, (11) 352*g*. Electrical conductivity of molten and solid lithium hydride, (5) 138*b*. Further comment on the phase diagram of Ca_2SiO_4 (and of CaC_2), (7) 216*e*.

Bredt, J. H. See Kendall, L. F., Jr.

Breedlove, J. G. Multilayered electrical capacitor, P (7) 209*h*.

Brehat, F. See Piendl, J. N.

Breitenburger Portland-Cement-Fabrik. Treatment of sludge in the manufacture of cements and limes, P (2) 37*f*.

Bremser, S. M. See White, W. A.

Brennan, H. M. See Bertolacini, R. J.

Brennan, J. J., and Pask, J. A. Effect of nature of surfaces on wetting of sapphire by liquid aluminum, (11) 352*b*.

Brennemann, A. E., Seraphim, D. P., and Tansal, S. Method for fabricating insulated-gate field effect transistor, P (9) 273*i*.

Brett, G. Pedestal bowl—its probable origin and purpose, (5) 124*b*.

Brett, N. H. See Russell, ? . E.

Bretz, G. Economic development of wall materials, (1) 10*h*.

Breuch, R. A. Studies on the effects of interplanetary space environment on thermal-control coatings, (9) 263*c*.

Breuer, R. G. See Titus, L.

Brewer, L. Future developments in the spectroscopy of high-temperature molecules, B (7) 225*d*.

Brewin, J. D., and Wynne, H. C. Methods of heat treating and gas pressure supporting glass in sheet form, P (4) 95*f*.

Brewster, G. F., Hensler, J. R., Rood, J. L., and Weidel, R. A. Partial dispersion ratios of some new borate and phosphate glasses, (9) 264*b*.

Brichard, E., Dupont, A., and De Keersmaecker, J. Process for casting [refractory] articles, P (8) 241*g*.

Brichard, E., and Malicheff, A. Glass batch melting process, P (11) 336*b*.

Brichard, E., Piumat, E., and Duperroy, M. Process and apparatus for the homogenization of molten glass in the chamber connecting the refining furnace to the working compartment, P (2) 42*c*.

Bricker, O. P. See Mackenzie, F. T.

Bridenbaugh, P. M. See Peterson, G. E.

Bridge, H., and Kelly, B. T. Graphite structures in nuclear reactors, P (7) 204*d*.

Bridge, H., and Mottershead, D. Relation between irradiation temperature, flux intensity, and start temperature for stored energy release in irradiated graphite, (4) 115*f*.

Bridgwater, J. Note on the equation for compressible cake filtration, (1) 19*h*.

Briggs, G. G. Preparation of dense thoria and sulfate containing thoria from an aqueous thorium nitrate solution, P (5) 135*g*.

Briggs, W. S. See Magee, J. S.

Brigham, R. V. Alumina in whitewares, B (3) 89*d*.

Bril, A. See Blasse, G.; Wanmaker, W. L.

Bril, A., and Wanmaker, W. L. Energy transfer in $CaNaBO_3$ activated with Tb and Gd, (6) 185*b*.

Bril, A., Wanmaker, W. L., and Broos, J. Photoluminescent properties of some Eu-activated Gd and Y compounds, (5) 139*g*.

Bril, J., and Dinet, A. Coulter Counter, (6) 180*f*.

Brill, K. Electrolytic capacitor comprising film-forming metal sheet carrying a dielectric oxide film and a metal dioxide electrolyte layer, P (7) 208*e*.

Brilling, P. E. See Fokin, K. F.

Brimhall, J. L., Klein, M. J., and Huggins, R. A. Influence of a finely dispersed second phase on recrystallization, (10) 322*c*.

Brindley, G. W. Clay mineral nomenclature, B (9) 289*j*. Discussions and recommendations concerning the nomenclature of clay minerals and related phyllosilicates, B (8) 259*h*. Report on the work of the Nomenclature and Liaison Committee of the Clay Minerals Society, 1963–1964, B (7) 225*e*. See Bratton, R. J.; Copp, A. N.; Ficalora, P. J.; Harward, M. E.; Mering, J.; Souza Santos, P. de.

Brindley, G. W., and Hayami, R. Kinetics and mechanisms of dehydration and recrystallization of serpentine (I); (II) spectrum of activation energies for recrystallization, B (6) 191*g*.

Brindley, G. W., Sharp, J. H., Patterson, J. H., and Achar, B. N. N. Kinetics and mechanism of dehydroxylation processes (I) temperature and vapor pressure dependence of dehydroxylation of kaolinite, (5) 154*f*.

Brinen, J. S. See Stonehart, P.

Brinkman, R. J. See Hann, D. G.

Briody, T. F., Santangini, J., and Kipp, K. F. Slicing semiconductor materials, (3) 72*d*.

Brisi, C., and Appendino, P. Solid-state equilibria in the system calcium oxide-barium oxide-silica, B (7) 226*d*.

Brite, D. W. See Hague, J. R.

British Cast Iron Research Assn. Measurement of moisture content in [molding] sand, P (1) 23*j*. Porous plug assembly for metallurgical receptacle, P (1) 13*f*.

British Ceramic Research Assn. Glazes for ceramic articles, P (2) 49*c*.

British Hydrocarbon Chemicals, Ltd. Catalyst, preparation thereof, and polymerization process using the catalyst, P (1) 25*i*.

British Titan Products Co., Ltd. Corrosion-inhibiting titanium dioxide pigments, P (1) 25*j*. Finely divided metal oxides, P (2) 56*f*. Process for producing pigmentary metal oxides substantially free from falling accretion material, P (3) 78*d*. Production of titanium dioxide, P (1) 26*c*, P(5) 149*d*. Production of zirconium and silicon tetrahalides, P (2) 57*b*. Reduction in scale buildup in the vapor phase production of pigmentary metal oxides, P (10) 318*g*. Vapor phase oxidation, P (2) 57*a*. Vapor phase oxidation of metal halides to form metal oxides of pigmentary size and apparatus for use therewith, P (8) 251*j*.

Brittan, K. W. Laminated transparent panels incorporating heating wires, P (7) 198*i*.

Brixey, J. C., Jr., and Statham, K. E. Method for diffusing an impurity from a doped oxide of pyrolytic origin, P (3) 73*f*.

Brixner, L. H. Alkali compensated rare earth doped zinc or cadmium borate phosphors, P (7) 208*c*. Luminescent properties of some rare earth ions in zinc borate as a host, (4) 112*f*. Preparation and properties of the $SrTi_{1-x}Fe_xO_{3-x/2+x/2}$ system, (11) 342*c*. Single-phase solid solution luminescent compositions, preparation thereof, and lasers containing same, P (7) 210*i*. Vacancy compensated calcium neodymium vanadate phosphors, P (6) 178*j*. See Flournoy, P. A.

Brochet, M. See Prod'homme, M.

Brociner, R. E., and Bailey, R. T. Mechanical treatment of ceramic bodies, B (9) 291*e*.

Brock, M. R. See Heyl, A. V.

Brockie, W. Drying and handling in clayworks, (5) 143*j*.

Brocklehurst, B., Russell, R. D., and Savadatti, M. I. Thermoluminescence of γ-irradiated solutions of aromatic compounds in rigid organic glasses, (2) 40*c*.

Brocklehurst, J. E., and Martin, W. H. Comparison of the bromination and irradiation growth of graphite, (5) 131*g*.

Brockman, F. G. Magnetic ceramics—a review and status report, (3) 71*i*.

Brockman, F. G., Beck, P. W., and Steneck, W. G. Electromechanical transducer employing piezomagnetic manganese ferrous ferrite, P (7) 208*f*.

Brockway Glass Co., Inc. Automatic inspection means for containers, P (7) 198*b*. Finish inspection apparatus for glass containers, P (10) 300*h*. Means for automatically weighing glass containers, P (10) 300*f*. Mold holder actuating mechanism, P (3) 66*a*. Treatment of melting glass with SO_2, P (7) 199*c*.

Brodkina, E. R. See Fedorov, N. F.; Yurganov, N. N.

Brodskii, Yu. A., Lapshits, B. L., and Khodorov, F. S. Cutting structural glass with diamond wheels, (8) 230*g*.

Broek, J. van den. Physical interpretation of a PbO photodetector, (11) 355*a*.

Broers, G. H. J. See Schenke, M.

Broja, G., and Gradinger, H. Aluminum fluoride manufacture with a moving AlF_3 bed, P (8) 250*d*.

Brokhin, I. S., and Fridman, A. A. Preparation and investigation of some titanium nitride-molybdenum cermets, (2) 45*j*.

Brokhin, I. S., and Platov, A. B. Preparation and microstructure of Al_2O_3-Mo and ZrO_2-Mo cermets, (2) 45*b*.

Broli, M. See Hagemark, K.

Brom, M. L. See Rex, C. H.

Broman, A., and Bats, R. Processes and apparatus for the manufacture of sheets of glass by drawing, P (2) 42*f*.

Bron, W. E., and Dreyfus, R. W. Electric resonance of rotating dipoles in ionic crystals, (10) 320*h*.

Bron, W. E., Heller, W. R., and Roland, P. A. Cathode ray device with screen having integrity against stress, P (5) 140*e*.

Bronnes, R. L. Transistor base and method of making, P (9) 275*b*.

Bronnes, R. L., Sweet, R. C., and Hughes, R. C. Hermetic electrical lead-in assembly, P (6) 177*c*.

Brooks, R. Production of sodium carbonate, P (7) 215*b*.

Brooks, R., and Kaufman, M. Rotational magnetic moment of BaO, (5) 139*h*.

Brooks, R. A. See Mehran, F.

Broos, J. See Bril, A.

Brosset, C., and Helgesson, C. I. (editors). Transactions of the Xth International Ceramic Congress, Stockholm, 1966, B (9) 290*e*.

Brower, E. O. See Brower, K. L.

Brower, K. L., Stapleton, H. J., and Brower, E. O. Electron spin resonance of Nd^{3+} pairs in $LaCl_3$ and $LaBr_3$, (11) 352*b*.

Brower, W. S. See Khanna, R. K.; Wachtman, J. B., Jr.

Brown, A. W., and Leary, D. E. Method of making dielectric panels, P (10) 310*h*.

Brown, B. B. See Nottle, R. A.

Brown, D. C. See Lyons, S. C.

Brown, D. S. See Ball, M. C.

Brown, D. W. Selection and use of pyrometer sheaths, (2) 46*a*.

Brown, F. C., Cavenett, B. C., and Hayes, W. Magneto-optical properties of defect centers in alkali halide crystals, (9) 284*j*.

Brown, G. See Newman, A. C. D.; Rayner, J. H.

Brown, G. A., Fuller, C. R., and Carlson, H. G. Method of treating planar junctions, P (9) 274*j*.

Brown, G. E. Method of control of particle size utilizing viscosity, P (4) 103*g*.

Brown, H. See Ballman, A. A.

Brown, H. L., Armstrong, P. E., and Kempter, C. P. Elastic properties of some polycrystalline transition-metal monocarbides, (10) 320*d*.

Brown, J. D. See Campbell, W. J.

Brown, K. L. See Carroll, J. E.

Brown, L. L. See Holmes, W. T., II.

Brown, M. K. Method of separating frit sealed parts of an electron tube, P (9) 274*j*.

Brown, M. R., Nash, W. B., Phillips, G., and Shand, W. A. Optical frequency-changing devices and materials for use therein, P (11) 344*h*.

Brown, R. A., and Bevan, S. C. Thermal decomposition of ferrous oxalate dihydrate, (4) 117*j*.

Brown, R. B. See Auld, J. R.

Brown, R. F. See Neuman, C. H.

Brown, R. J. Homogeneity of microscopic particles, (3) 75*c*.

Brown, R. K., Jr., and Bilaney, S. M. Temperature stresses in an aggregate cement paste model, (3) 63*a*.

Brown, R. N. See Pidgeon, C. R.

Brown, R. W., and Sandmeyer, K. H. Shortening the gap between refractory development and furnace practice (I, II), (11) 339*e*.

Brown, R. W., and Tatnall, R. F. Fused cast refractories move into refractory tunnel kilns, (4) 96*d*.

Brown, T. E. See Kennedy, V. C.

Browning, J. S. See Eddy, W. H.; Hollenbeck, R. P.; Rampacek, C.

Browning, M. F., and Wilson, W. J. Process of vapor coating nuclear fuel with beryllium oxide and carbon, P (11) 340*i*.

Browning, R. R., Jr. Bulk material handling, (2) 52*j*.

Brownlow, J. M. See Bartkus, E. A.

Brubaker, B. D. Ductile magnesium oxide whiskers, (1) 28*c*.

Brubaker, B. D., and Russell, R., Jr. Residual stress development in laminar ceramics, (1) 15*g*.

Bruch, C. A. Problems in die-pressing submicron size alumina powder, (3) 74*j*.

Bruck, Schloesser & Co. G.m.b.H. Methods and devices for the production of bricks, P (7) 199*h*.

Brucklacher, D. See Steeb, S.

Brueckner, E. Method and machine for the manufacture of pottery, P (9) 271*h*. Shaping of high voltage insulators, (10) 306*f*.

Brueckner, R. Formation and causes of inhomogeneities in slip casting and in ceramic bodies, (10) 305*f*.

Brueckner, R., and Dietzel, A. Orientation phenomena as causes of inhomogeneities in casting slips and cast bodies, (7) 206*b*.

Brueckner, R., and Fernandez Navarro, J. Physicochemical investigations in the system B_2O_3-SiO_2, (6) 168*a*.

Brugger, R. M., Strong, K. A., and Carpenter, J. M. Lattice vibrations of BeO, (8) 254*f*.

Bruhl, D. A., Jr., and Counts, W. E. Method of making cermet resistance element and terminal connections therefor, P (9) 273*h*.

Bruin, H. J. de. See Bradhurst, D. H.

Bruin, H. J. de, and Watson, G. M. Self-diffusion of beryllium in unirradiated BeO, (3) 67*j*.

Bruin, H. J. de, Watson, G. M., Blood, C. M., and Roman, D. Cation self-diffusion in fast neutron-irradiated beryllium oxide, (8) 252*e*.

Bruki, C. E. See Rudy, E.

Brull, E. See Steinmetz, H.

Brumage, W. H., Segraves, E. C., and Lin, C. C. High-temperature magnetic susceptibilities and trigonal-field splitting of vanadium-doped corundum crystals, (5) 138*e*.

Brunfelt, A. O., and Steinnes, E. Determination of phosphorus in rocks by neutron activation, (8) 248*c*.

Brungs, M. P., and McCartney, E. R. Use of a resistivity technique to determine the initial reaction temperature in the PbO-Fe_2O_3 system, (11) 358*a*.

Brunner, M. Dolomite sinter and its production, P (1) 12*b*.

Bruns, J. H., Jr., Ihrig, A. C., and Knapp, L. W. Method of making a refractory delivery apparatus and apparatus produced, P (3) 69*c*.

Bruns, R. F. Crusher jaws, P (8) 251*a*.

Brunton, G., Tettenhorst, R., and Beck, C. W. Montmorillonite-polyalcohol complexes (II), B (5) 160*c*.

Brutskus, T. K. See Tulovskaya, Z. D.

Brutskus, T. K., Tulovskaya, Z. D., Pogarskaya, T. I., and Segalova, E. E. Effect of surfactants on the coagulative structure formation in aqueous suspensions of asbestos, (8) 237*g*.

Bryan, I. E. See Baker, D.

Bryan, L. E. Artificial logs for fireplaces, P (7) 204*f*.

Bryan, W. S., and Worchel, G. S. Method of forming a semiconductor by masking and diffusion, P (1) 18*a*.

Bryant, B. E., and Bodiford, W. E. Resin bonded magnesium oxychloride cement composition, P (1) 3*c*.

Bryant, E. E. Enamel characteristics for air atomized electrostatic spray, (9) 262*g*.

Bryant, J. P., and Dixon, J. B. Clay mineralogy and weathering of a red-yellow podzolic soil from quartz mica schist in the Alabama Piedmont, B (6) 192*f*.

Bryant, P. J., and Gosselin, C. M. Method of treating glass to reduce helium permeation, P (11) 336*a*.

Bryden, J. G. See Cromarty, R. E.

Brydon, J. E. See Kodama, H.

Brydon, J. E., and Kodama, H. Nature of aluminum hydroxide-montmorillonite complexes, (2) 59*h*.

Bryer, R. G. Radioactive radiation dosimeter of the silver phosphate glass type, P (8) 246*d*.

Brzozowski, J. Use of mazout for heating tank furnaces, (2) 56*a*.

BTU Engineering Corp. High temperature electrical furnace, P (8) 249*f*. High temperature electrical heating unit, P (7) 213*i*.

Bubb, J. N., and Perry, D. Porosity in some synthetic dolomites, (9) 285*e*.

Buchanan, D. N. E. See Gallagher, P. K.

Buchanan, R. C. Substrate surfaces for microelectronics, (7) 208*d*.

Buchanan, R. C., and Zuegel, M. A. Electrical properties of glasses in the system PbO-Al_2O_3-B_2O_3-SiO_2, (2) 39*f*.

Buchel, G. L. See Butherus, A. D.

Buchkremer, R. Electric furnace for ceramics, P (3) 77*a*.

Buchkremer, R., and Petzi, F. Kilns for sintering soft ferrites, (3) 76*i*; further development, (5) 138*b*.

Buchmann, F. J. See Kimberlin, C. N., Jr.

Buchmayer, P. See Thormann, P.

Buchner, S. Structure of grinding wheels, (10) 293*g*.

Buchter, H. H. See Harris, D. M.

Buchwieser, G. See Bauer, A.

Buckley, F. T., Mason, G. R., and Riek, R. F. Laminated safety glass, P (9) 265*h*.

Buddecke, C. L., Meyer, W. E., and Stites, R. S. Image projection device, P (11) 343*h*.

Budin, C., and Lucasson, P. Method for studying point defects, especially interstitial atoms in metals, B (10) 329*e*.

Budke, J. Thermal etching of NaCl cleavage faces in vacuum, (5) 159*b*.

Budnikov, P. P., and Duderov, Yu. G. Porous heat-insulating materials from polyethers and diisocyanates, (7) 202*f*. Porous refractory shapes from fused quartz, (1) 11*j*.

Budnikov, P. P., and Kharitonov, F. Ya. Determination of the bulk density and porosity of ceramic materials, (10) 313*g*. Increasing the strength of high melting point compounds, (8) 237*i*.

Budnikov, P. P., Kroichuk, L. A., and Vinogradov, B. N. Specific features in the crystallization of calcium hydrosilicates in the presence of gypsum and aluminum oxide, (2) 36*j*.

Budnikov, P. P., and Kulikova, N. V. Preparation and properties of barium silicates and aluminates, (9) 278*j*.

Budnikov, P. P., and Maslennikova, G. N. Effect of vitreous phase on the properties of high-tension electrical porcelain, B (9) 291*f*.

Budnikov, P. P., Matveev, M. A., Petrovykh, I. M., and Voronin, A. V. Hydrothermal synthesis of cesium aluminosilicates and their properties, (6) 182*h*.

Budnikov, P. P., Pashchenko, A. A., and Serbin, V. P. Study of hardened cement reinforced with mineral fiber, (2) 37*b*.

Budnikov, P. P., Savel'ev, V. G., and Petrovykh, I. M. Physicochemical properties of trans-Carpathian perlite, (6) 165*i*.

Budnikov, P. P., and Sturman, V. K. Refractories based on magnesite with increased lime content, (5) 133*g*.

Budworth, D. W. See Ammar, A. A.; Warman, M. O.

Budzinowski, F. See Widaj, J.

Buechel, E. H. See Buehler, H. E.

Buehl, W. M., and Cowan, J. H., Jr. Method of reducing reboil in molten glass, P (9) 265*i*.

Buehler, H. E., Buechel, E. H., and Leontaritis, L. Investigations at the metal-enamel interface of direct-on enameled sheet steel, (5) 126*b*.

Buehler, W. J. See Wang, F. E.

Buell, H. W., and Blair, R. E. Abrasive coated [flexible] products, P (9) 261*k*.

Buergel, G. K. See Best, H. S.

Buerger, M. J., and Taxer, K. Rhodizite—structure and composition, (5) 158*b*.

Buessem, W. R. Microstructure, B (3) 89*d*. See Chung, D. H.; Lange, F. F.

Buffalo China, Inc. Cup topping machine, P (3) 70*f*.

Bufferd, A. S. Preparation of metal-oxide dispersion composites, B (4) 121*i*.

Buie, B. F. Possibility of volcanic origin of the Cretaceous sedimentary kaolin of South Carolina and Georgia (abstract), B (6) 191*d*.

Buisson, G., and Michel, C. Isomorphous orthosilicates and orthogermanates of the rare earths, (7) 219*a*.
Buker, D. O., and Merrill, T. W. Process for making vanadium carbide briquets, P (1) 14*b*.
Buketov, E. A., and Ugorets, M. Z. Method for extracting selenious oxide from gas mixtures, P (10) 318*c*.
Bukhalova, G. A. See Yagub'yan, E. S.
Bukhalova, G. A., and Babaeva, E. P. System of the fluorides of lithium, cesium, and lanthanum, (9) 287*a*.
Bukhalova, G. A., and Mal'tsev, V. T. Complex formation between sodium cryolite and hexafluoroaluminates of K, Rb, and Cs, (9) 280*e*.
Bukhalova, G. A., and Sementsova, D. V. System of the fluorides and chlorides of lithium and cesium, (9) 287*j*. System of the fluorides of Li, Na, and Cs, (9) 287*b*.
Bukhtiyarov, V. V. See Korshunov, B. G.
Bulakh, V. L. See Tsigler, V. D.
Bullock, K. C. Minerals of Utah, (7) 214*f*.
Bulovic, V. See Cvjeticanin, D.
Bultman, H. J. Dynamic friction measured fast, accurately, (3) 75*i*.
Bundy, A. J. See Jones, J. C.
Bundy, F. P. Phase diagrams of silicon and germanium to 200 kbars, 1000°C, (6) 187*d*.
Bundy, F. P., and Kasper, J. S. Hexagonal diamond—a new form of carbon, (11) 353*j*.
Bundy, F. P., and Wentorf, R. H., Jr. Direct transformation of hexagonal boron nitride to denser forms, (5) 151*c*.
Bundy, W. M., Johns, W. D., and Murray, H. H. Interrelations of physical and chemical properties of kaolinites, B (8) 259*i*.
Bureau de Recherches Geologiques et Minieres. Rotating grinders, P (8) 251*h*.
Buresch, F. E. Numerical determination of phase compounds in polycomponent systems with an example in the uranium-carbon-chromium system, (10) 324*a*.
Burge, R. W. See Thomas, P. M.
Burggraaf, A. J., and Stelt, E. O. W. van der. Sodium-vapor discharge lamp having an envelope with a porous inner wall, P (7) 199*a*.
Burham, F. P., and Hamilton, R. W. Apparatus for vapor coating tumbling substrates, P (11) 343*f*.
Burhans, R. O., and Criss, G. H. Refractory bonding mortar, P (7) 205*b*.
Burke, J. J., Reed, N. L., and Weiss, V. (editors). Strengthening Mechanisms; Metals and Ceramics—Proceedings of the Twelfth Sagamore Army Materials Research Conference Held at Sagamore Conference Center, Raquette Lake, N. Y., August 1965, B (4) 121*j*.
Burke, O. W., Jr. Mechanical modification of wet silica pigment for reduction of free water retentivity thereof, P (9) 279*d*. Silica pigments and process for producing, P (6) 183*d*.
Burke, O. W., Jr., and Jackson, C. B. Apparatus for the production of silica pigments, P (9) 279*b*.
Burke, T. J. In-plant printing, drying, and direct filling of nonreturnables, (10) 297*g*.
Burkett, W. E. High-strength lightweight aggregate and its manufacture, P (7) 199*g*.
Burkley, R. L. Preblended tile bodies, (3) 70*b*.
Burks, D. P. Ceramics in hybrid integrated circuits, (3) 71*a*.
Burlet, P. See Villers, G.
Burmeister, R. A., Jr., and Green, P. E. Synthesis and crystal growth of B_6P, (4) 117*j*.
Burnett, P. See Heuer, A. H.
Burnham, C. W., and Radoslovich, E. W. Refinement of the crystal structures of coexisting muscovite and paragonite (extended abstract), B (7) 224*a*.
Burnie, G. See Wood, W. A.
Burns, G. See Giess, E. A.; Nathan, M. I.
Burns, J. H., and Busing, W. R. Crystal structures of $RbLiF_2$ and $CsLiF_2$, (4) 107*i*.
Burns, L. Electroluminescent lamp having a high resistivity electrode, P (2) 50*j*.
Burns, R. G., Clark, M. G., and Stone, A. J. Vibronic polarization in the electronic spectra of gillespite ($BaFeSi_4O_{10}$), a mineral containing iron(II) in square-planar coordination, (6) 190*f*.
Burns, R. P. Discontinuity in the rate of evaporation of aluminum oxide, (5) 151*c*. Systematics of the evaporation coefficient of Al_2O_3, Ga_2O_3, In_2O_3, (7) 222*b*.
Burroughs Corp. Apparatus and method for introducing vaporizable materials into an electron tube envelope, P (5) 140*b*. Method for fabricating an electrical memory module, P (1) 18*j*.
Burrows, F. A. Recent developments in oil firing equipment for the ceramic industry, (5) 147*f*.
Burrows, R. C. Process of preparing inorganic foams from alkali metal silicates and aluminum, P (11) 340*g*.
Burte, H. M. See Blackburn, L. D.
Burte, H. M., Bonanno, F. R., and Herzog, J. A. Metal matrix composite materials, B (4) 121*b*.
Burton, C. D. S., and Reid, A. M. Glass, P (5) 129*g*.
Burton, E. Wedgwood Etruria 1766–1966, (4) 91*i*.
Burykina, A. L., Dubovik, T. V., Evtushok, T. M., and Krasnov, A. N. Coating of aluminum nitride on graphite, (5) 131*f*.
Burykina, A. L., and Evtushok, T. M. Study of contact reaction between metallic borides and graphite at high temperature in a vacuum, (2) 46*e*.
Burykina, A. L., Krasnov, A. N., and Evtushok, T. M. Plasma and diffusion coatings on graphite, (5) 133*a*.
Busby, T. S. Tank Blocks for Glass Furnaces, B (1) 34*e*.
Busche, M. G. High modulus carbon fiber—new entry in fiber-reinforced plastics race, (8) 237*e*. New dielectrics solve 10 insulation problems, (3) 72*a*.
Bush, D. C., Jenkins, R. E., and McCaleb, S. B. Separation of swelling clay minerals by a centrifugal method, B (8) 260*b*.
Bush, D. R. Color control in glass enamels, (2) 38*j*.
Bush, E. A. Method of molding comminuted nonplastic inorganic material, P (1) 20*c*.
Bush, E. A., and Rostoker, D. Method of forming a synthetic marble, P (10) 318*d*.
Bush, H. J. See Gordy, I.
Bush & Wilson, Ltd., and Dawes, R. J. Apparatus for controlling the rate of flow of granular and powdered material, P (5) 144*d*.
Bushkovich, S. N., Ganichev, A. A., Petrov, G. N., and Rutgaizer, Yu. S. Evaporator for studying the thermodynamic properties of refractory materials, (11) 346*j*.
Busing, W. R. See Burns, J. H.
Bustany, S. H. See Faith, L. E.
Busteed, D. Airless spraying, (3) 74*b*.
Butherus, A. D., Leonard, R. B., Buchel, G. L., and Eick, H. A. Preparation and some properties of $Nd_2O_2C_2$, (6) 188*a*.
Butler, B. C. M. Chemical study of minerals from the Moine schists of the Ardnamurchan area, Argyllshire, Scotland, (3) 79*d*.
Butler, C. P. See Jenkins, R. J.
Butler, C. T. Room-temperature deformation luminescence in alkali halides, (8) 256*g*.
Butler, G. Production of finely divided oxides by plasma process, P (4) 105*g*.
Butler, J. F., and Calawa, A. R. PbS diode laser, (4) 113*i*.
Butler, J. H., Chance, D. A., and Im, S. S. Method of forming tunneling junctions for intermetallic semiconductor devices, P (3) 73*a*.
Butler, K. H., Thomas, M. J. B., and Quirk, R. F. Method of processing halophosphate phosphors, P (2) 51*c*.
Butt, J. B. See Irving, J. P.
Butt, Yu. M. See Anikeeva, T. V.; Dregoi, I.; Imashev, M. K.; Kaushanskii, V. E.; Lagoida, A. V.; Maier, Ya.; Savin, E. S.; Topil'skii, G. V.
Butt, Yu. M., and Danilova, S. G. Cellular structure of gas concrete and granulometric composition of filler, (6) 164*a*.
Butt, Yu. M., Timashev, V. V., and Sulimenko, L. M. Granulometric composition of material fired in a Lepol kiln, (6) 164*b*.
Buttrey, D. V. E. See Curcio, J. A.
Butts, W. R. Cellular material and method for making, P (1) 12*i*.
Buyers, A. G., and Mohr, A. J., Jr. Ceramic-metal seal, P (5) 126*f*.
Byakhova, N. I. See Vidavskii, L. M.
Byczkowski, M. W. Method of forming a semiconductor device with a depletion area, P (7) 209*e*.
Bye, G. C. See Aldcroft, D.
Bykodorova, I. S. See Lesnikov, A. K.
Bykov, I. I., and Khan, B. Kh. Thermophysical processes of the shaping of cast silicate crystalline materials, (2) 46*a*.
Bykov, V. M., Lifanov, I. I., and Mikhailov, N. V. Deformation of cement stone and sand concrete during freezing, (5) 124*h*.
Bysath, K. Sealing compound for high temperature use, P (11) 341*c*.
Bystrikov, A. S., and Cherepanov, B. S. X-ray study of the formation of zircon in the system SiO_2-ZrO_2-V_2O_5, (3) 88*d*.
Bystrom-Asklund, A. M. Sample cups and a technique for sideward packing of X-ray diffractometer specimens, (1) 23*a*.
Byurganovskaya, G. V., Vargin, V. V., Leko, N. A., and Orlov, N. F. Action of Radiation on Inorganic Glasses, B (10) 328*b*.

Cabanillas, H. L. See Lopez Cabanillas, H.
Cable, M., Rasul, C. G., and Savage, J. Laboratory investigation of foaming and reboil in soda-lime-silica melts, (8) 233*a*.
Cabot Corp. Apparatus for producing metal oxides, P (6) 182*c*. Cyclonic apparatus, P (5) 144*g*. Metal and metalloid oxide production, P (5) 148*e*. Mixing control during metal and metalloid oxide production, P (4) 105*a*. Preparation of metallurgical carbon, P (5) 135*h*. Pyrogenic silica production, P (10) 318*f*. Vapor phase process for producing metal oxides, P (2) 57*b*.
Cadle, P. J., and Satterfield, C. N. Anisotropic diffusivities in pressed boehmite pellets, (9) 279*g*.
Cadoff, L. H. See Adelsberg, L. M.
Cadotte, J. E. Acoustical panel having openings and ceramic surfacing material bonded to the panel, P (2) 40*g*.
Cady, W. G. Piezoelectric vibrators and systems embodying them for converting the mechanical vibration into electric energy, P (6) 178*d*.
Caesar, P. D. Electrochemical electrode, P (7) 195*c*.
Caffyn, J. E., Goodfellow, T. L., and Hamdani, A. J. Movement of dislocations in an electric field in sodium chloride, (4) 113*g*.
Cagle, C. V. See Smith, D. F.
Cahen, R. R. See France, H. de.
Cahlik, J. C. See Albertson, W. C.
Cahoon, J. B., Jr., and Gardner, W. J. Exothermically heated molten metal pouring nozzle, P (10) 304*c*.
Cahoy, R. P., and Coyne, D. M. Novel oxidation catalyst compositions and processes, P (1) 13*d*.
Caignan. Tunnel-kiln cars made of refractory concrete, (10) 317*d*.
Caillat, R. See Francois, B.
Caires, E. J. See Weller, B. L.
Cairns, R. C. See Alfredson, P. G.
Calaman, J. J. Mineral working burner apparatus, P (8) 251*a*.
Calawa, A. R. See Butler, J. F.; Meingailis, I.
Calbick, C. J. See Sinclair, W. R.
Calcimatic International, Ltd. Method and means of calcining limestone, P (1) 3*b*.
Calkins, T. H., and Duckwall, F. E. Method and apparatus for manufacturing optical lenses, P (2) 41*h*.
Callaghan, A., Moeller, C. W., and Ward, R. Magnetic interactions in ternary ruthenium oxides, (6) 187*c*.
Callow, A. E., Hughes, W., and Groves, J. D. Vapor phase oxidation, P (2) 57*a*.
Calmon, C., and Grundner, W. T. Preparation and use of silver [aluminosilicate] zeolites of improved exchange capacity, P (8) 251*b*.
Calow, C. A., Bayer, P. D., and McCarthy, G. P. R. Sizing and mechanical testing of whiskers of α-Al_2O_3, (5) 158*d*.
Calvert, J. M. See Szego, L.
Calvert, L. D. See Sato, M.
Calvo, C. See Au, P. K. L.; Chambers, J. G.
Calvo, C., Leung, J. S., and Datars, W. R. ESR study of Mn^{2+} in α- and β-$Mg_2P_2O_7$, (11) 352*g*.
Camahort, J. L. Protective coating by surface nitridation of boron filaments, (10) 303*g*.
Cambridge Thermionic Corp. Thermoelectric junction assembly with insulating irregular grains bonding insulating layer to metallic thermojunction member, P (7) 210*d*.
Cameron, N. M. Effect of environment and temperature on the strength of E-glass fibers (I) high vacuum and low temperature, (7) 196*b*.
Cameron & Jones, Inc. Discharge grate and hopper for shaft kiln, P (4) 104*b*.
Camm, J. See Dinsdale, A.
Cammarata, I. See Vecchio, M.
Camp, L. R. See Ehrlinger, H. P., III.
Campbell, C. Bearings, P (5) 134*d*.
Campbell, C. L. Dry separator, P (6) 179*c*.
Campbell, D. S. See Harrop, P. J.; Lewis, B.
Campbell, G. W., Jr. Process for producing noncaking borax, P (8) 251*c*.
Campbell, J. Making slab pottery, (3) 61*j*.
Campbell, J. G. Graphite thermal assembly jigs, (1) 11*f*.
Campbell, J. K. Process for post-finishing pigmented glass fabric, P (11) 336*g*.
Campbell, L. R. See Shaffer, G. A., Jr.
Campbell, P. S. Klystron having high frequency radiation means comprising a half-wave short-circuited choke, P (10) 310*b*.
Campbell, R. W. Pipe apparatus, P (8) 241*f*.
Campbell, T. T. See Skirvin, F. A.
Campbell, W. J., and Brown, J. D. X-ray absorption and emission, (10) 316*c*.
Campbell, W. W. See Leatham, E.
Campbell, W. W., Pack, A. H., and Davies, B. Burned basic refractory, P (11) 340*b*.
Campbell, W. W., Rossi, C. E., and Good, W. R. Shaft kiln, P (3) 77*c*.
Canadian Industries, Ltd. Hard and flexible stoving enamels, P (2) 38*c*.
Canadian Patents & Development, Ltd. Apparatus for specific gravity separation of solid particles, P (3) 77*j*. Cyclone apparatus, P (5) 144*c*. Hot-pressing of decomposable compounds to form oxide-containing products, P (7) 204*b*. Method of making ceramic capacitors, P (8) 245*j*. Preparation of silicon chlorides, P (7) 215*a*. Process for manufacturing clay products, P (2) 43*b*.
Cannon, P. High density magnesium compounds and their preparation, P (1) 18*c*.
Canrad Precision Industries, Inc. Coated phosphor having radioisotope dispersed therein and method of preparation, P (5) 140*h*.
Cant, N. W., and Little, L. H. Chemisorption sites on porous silica glass and on mixed-oxide catalysts, (11) 333*c*.
Canterford, J. H., and O'Donnell, T. A. Reactivity of transition metal fluorides (III) higher fluorides of vanadium, niobium, and tantalum, (6) 188*g*.
Cantor, S. See Hill, D. G.
Capacho-Delgado, L., and Manning, D. C. Determination by atomic-absorption spectroscopy of elements including Si, Al, and Ti in cement, (2) 36*i*.
Capillon, E. A. Composite material of a ceramic silver-gold alloy and a nickel alloy, P (1) 17*d*.
Capio, C. D. See Ballman, A. A.; Van Uitert, L. G.
Capits, E. R. Centrifugal furnace, P (7) 213*g*. Vapor deposition apparatus including centrifugal force substrate-holding means, P (8) 247*h*.
Caplan, S., Gonda, T., Lamorte, M. F., and Nyul, P. Thermal resistance of GaAs laser diodes, (4) 118*d*.
Caporali, G. See Feriazzo, N.
Cappelaere, M., and Accary, A. Effects of thermal cycling on uranium-carbon alloys, (6) 172*j*.
Cappa, W. See Macedo, P. B.
Cappa, W., Macedo, P. B., O'Meara, B., and Litovitz, T. A. Temperature dependence of the high frequency moduli of vitreous B_2O_3, (5) 129*d*.
Carasso, J. I. See Faktor, M. M.

Carborundum Co. Abrasive coated [flexible] products, P (9) 261*k*. Electrical welding method and apparatus, P (5) 141*c*. Metal carbide and boride production, P (7) 204*j*. Method of joining electrode bodies of dissimilar thermal coefficients of expansion, P (7) 205*c*. Method for making ducted refractory articles, P (1) 13*e*. Microcrystalline sintered bauxite abrasive grain, P (9) 261*g*. Process and apparatus for effecting solid-state reactions, P (7) 205*d*. Silicon carbide igniter, P (6) 175*b*. Thermoelectric device comprising $100SnO_2 \cdot xSb_2O_3$, P (5) 143*a*.
Cardona, M. See Shaklee, K. L.
Cardona, M. P. See Puig Cardona, M.
Carini, G. F. See Davies, B.
Carl, D. G., and Steigelman, H. A. Abrasion-resistant glass article having dual protective coatings thereon, P (5) 129*h*.
Carl, W. L., and Hickle, J. C. Electron discharge device and method, P (3) 72*e*.
Carl Zeiss Stiftung (trading as Jenaer Glaswerk Schott & Gen.). Glass, P (5) 129*g*, P (7) 198*c*. Spectropolarimeter, P (4) 103*i*. See Jenaer Glaswerk Schott & Gen.
Carlson, H. G. See Brown, G. A.
Carlson, K. D. See Gilles, P. W.
Carlson, K. D., and Claydon, C. R. Electronic structure and ground-state properties of titanium mononitride, (11) 352*c*.
Carlson, R. I. See Elwood, A. A.
Carlson, S. Development problems of Swedish industry, B (9) 291*d*.
Carman, J. N. Glass encapsulated electronic devices, P (10) 309*h*.
Carman Laboratories, Inc. Glass encapsulated electronic devices, P (10) 309*h*.
Carmi, A. See Ambrogi, R. R.
Carmi, A., and Rayeski, T. J. Clamping device, P (1) 8*e*.
Carnahan, R. D. Elastic properties of silicon carbide, (5) 151*c*.
Carnall, E., Jr. Densification of MgO in the presence of a liquid phase, (4) 107*f*.
Carnall, E., Jr., Hatch, S. E., Ladd, L. S., and Parsons, W. F. Magnesium fluoride optical element, P (5) 130*e*.
Carnall, W. T., Neufeldt, S. J., and Walker, A. Reactions in molten salt solution (I) uranate and neptunate formation in molten lithium nitrate-sodium nitrate, (4) 115*a*.
Carnall, W. T., Walker, A., and Neufeldt, S. J. Anhydrous sodium polyuranates, (6) 183*j*.
Carniglia, S. C., Johnson, R. E., Hott, A. C., and and Bentle, G. G. Hot-pressing for nuclear applications of BeO—process, product, and properties, (4) 96*e*.
Carniol, B., and Maly, Z. Circuit arrangement for accurate measurement of temperatures or small temperature changes, P (1) 23*h*.
Carozzi, A. V. See Heath, C. P.
Carpay, F. M. A. System vanadium-selenium near the composition VSe, (4) 117*e*.
Carpco Research & Engineering, Inc. Magnetic separator, P (7) 214*e*.
Carpenter, C. L. See Wendell, C. B.
Carpenter, C. L., and Wendell, C. B. Metal and metalloid oxide production, P (5) 148*e*.
Carpenter, J. H. Magnetic separator, P (7) 214*e*. See Trumbo, P. W.
Carpenter, J. M. See Brugger, R. M.
Carpenter, M. R., Davies, D. B., and Matheson, A. J. Measurement of the glass-transition temperature of simple liquids, (5) 128*b*.
Carpenter, R. D. Vanadium carbide process, P (8) 241*g*.
Carpenter, W. W., and Seibert, E. Fluxing pipe, P (7) 195*c*.
Carr, A. P. London clay surface in part of Suffolk, (10) 317*i*.
Carr, B. See Wilson, C. P., Jr.
Carr, R. Birth of a bath, (2) 35*i*.
Carr, R. J. See Peterson, D. L.
Carrara, A. S., and McGarry, F. J. Matrix and interface stresses in a discontinuous fiber composite model, (10) 298*a*.
Carrell, M. A., and Wilder, D. R. Sintering study in the partially vitreous As-S-Se system, (1) 32*d*.
Carrier, G. B. Discussion of "Transmission electron microscopy of thin glass samples," (1) 5*g*.
Carrier Corp. Brazing preform, P (2) 40*f*.
Carrington, A. Electron paramagnetic resonance, (11) 346*i*.
Carroll, J. E., and Brown, K. L. Arc welding flux, P (10) 296*f*.
Carroll, W. E. Brick and wall construction, P (10) 302*b*.
Carson, F. J. See Leflet, H. A., Jr.
Carson, F. J., Ferguson, C. W., Ritter, G. F., Jr., and Hymore, F. J. Method of and apparatus for bending and tempering glass sheets by differential heating, P (11) 336*c*.
Carson, F. J., and Leflet, H. A., Jr. Method for bending glass sheet to a complex curvature, P (2) 41*j*.
Carson, R. W. Foolproof logic guides operator of potentiometer, (3) 75*j*.
Carstea, D. D. See Harward, M. E.
Carter, C. J., and Stewart, R. F. Diode array and process for making, P (8) 244*i*.
Carter, G. See Huges, D. M.; Konjevic, R.
Carter, R. C. Pipe couplings, P (6) 172*c*.
Carter, R. S. See Preston, J. B.
Carter, S. W. See LoPilato, S. A.
Carter, T. J. Thickness measurements in the electron microscope, (4) 103*d*.
Carteret, Y. See Bourrasse, A.
Carvelle, B., Caye, R., Levy, C., and Picot, P. Apparatus for the study by transmitted polarized light (infrared) of minerals opaque in the visible, (4) 102*e*.
Casale, M. E. A. See Iles, G. S.
Casale, R., and Woulbroun, J. M. Composite protective coat for thin film devices, P (5) 140*j*.
Casalot, A. See Pouchard, M.
Casey, K. Purification by differential migration, (6) 181*c*.
Cash, P. Measuring refractory resistance to hot slags, (3) 67*i*.
Cashen, G. H. Thixotropy and dilatancy, (6) 190*h*.
Cashion, J. D., Cooke, A. H., Thorp, T. L., and Wells, M. R. Some thermal properties of three antiferromagnetic rare-earth orthoaluminates, (11) 356*i*.
Cassidy, R. W. See Nale, R. F.
Castagne, R. Electronic properties of semiconductors, (6) 176*f*.
Castle, J. G., Jr. See Feldman, D. W.
Castor, W. S., Jr. See Whately, W. R.
Caswall, R. D., Jr. See Leflet, H. A., Jr.
Catalysts & Chemicals, Inc. Dehydrogenation catalysts, P (4) 104*j*.
Catana, V. See Dumitrescu, T.
Caterina, J. R. Self-leveling self-aligning brick and block, P (11) 337*d*.
Cautius, W. See Engel, W.
Cauwenberg, W. J. See Roberts, G. L., Jr.
Cavanagh, J. C. Fair Packaging and Labeling Act, (10) 327*j*.
Cave, E. F. Composite insulator-semiconductor wafer, P (5) 140*i*. See Mayer, A.
Cavenett, B. C. See Brown, F. C.
Cavitt, J. H. See Turner, N. C.
Caye, R. See Carvelle, B.
Cazzaniga, E. See Beghi, G.
Cella, C. See Gervais, H.
Celotex Corp. Binder distribution method for producing mineral wool board, P (1) 12*i*.
Central Electricity Generating Board. Electrical insulators, P (7) 206*h*.
Central Glass Co., Ltd. Method of preparing sodium tripolyphosphate, P (8) 251*h*.
Centre National de Recherches Metallurgiques. Rotatable sample changer for an electron probe microanalyzer having means for maintaining a vacuum in the analysis chamber, P (3) 76*g*.
Centre National de la Recherche Scientifique. Goniometric supports for supporting crystal during crystal analysis and subsequent cutting, P (8) 249*b*. Process for the epitaxial growth of semiconductor layers on metal supports, P (8) 246*b*.
Centrifix Corp. Dry separator, P (6) 179*c*.
Ceramic Coating Co. Fluxing pipe, P (7) 195*c*.
Cerles, G. Rotatable tubular structure embodying a large reserve section and heat exchanger and furnace embodying same, P (8) 229*c*.
Cerles, G., and Dupuy, E. Cooler for finely divided materials and method, P (3) 77*a*.
Cerny, J. J., and Hosbein, L. H. Refractory lining structure for a rotary kiln, P (4) 97*k*.
Cerrai, E., and Trucco, R. Laser microprobe sampling for qualitative analysis, (9) 276*a*.
Certain-Teed Fiber Glass Corp. Spinning glass filaments, P (1) 10*a*.
Certain-Teed Products Corp. Glass fiber cooling means, P (10) 300*j*.
Chabal, J. See Junge, A. E.
Chaberski, A. Z. Electroluminescent display panel with rodlike electrodes embedded in phosphor, P (8) 244*b*.
Chackraburtty, D. M. See Awasthi, S. K.
Chadha, O. P., and Singh, A. Some aspects of the use and manufacture of calcined shale as a pozzolan at Bhakra, (1) 2*j*.
Chadwick, A. V. See Allnatt, A. R.
Chadwick, G. F. Method of making an electrical resistor, P (8) 245*j*.
Chagnon, P. L., Gartner, S. J., and Jankowski, A. S. Conveying and orienting apparatus, P (7) 208*a*.
Chaki, P. R. Basic fireclay and high aluminous refractory bricks or shapes, P (3) 68*i*.
Chaklader, A. C. D. Hot-pressing of decomposable compounds to form oxide-containing products, P (7) 204*h*. See Hart, J. L.; Sunderland, P. W.
Chaklader, A. C. D., and Cook, R. C. Kinetics of reactive hot-pressing of clays and hydroxides, (9) 270*i*.
Chaklader, A. C. D., and McKenzie, L. G. Process for manufacturing clay products, P (2) 43*b*.
Chakraborty, K. C. Charge balance and cation distribution in some natural biotites, (10) 319*g*.
Chakraborty, P. N. See Choudhury, U. C. R.
Chakravarti, B. N. See Bose, U. P.
Chakravortty, S. K. Phosphate bonding in refractories and other ceramic products, (5) 133*a*.
Chakravorty, D. M. See Moorthy, V. K.
Chamberlain, J. M. W. Vibratory mill, P (2) 57*c*.
Chamberland, B. L. Crystal growth of CrO_2, (1) 27*a*. Ferromagnetic metal oxyfluorides, P (5) 141*h*.
Chamberland, B. L., and Babcock, K. R. Preparation and properties of InOF, (1) 31*a*.
Chamberod, A. See Dautreppe, D.
Chambers, A., and Prutton, M. F centers and the epitaxial growth of nickel, (10) 307*i*. Improved epitaxy of nickel on rock salt substrates due to electron bombardment, (11) 342*i*.
Chambers, J. G., Datars, W. R., and Calvo, C. ESR study of the crystallographic phases in $Zn_3P_2O_7$:Mn and $Zn_3P_2O_7$:Cu, (5) 152*h*.
Chambron, W. See Dautreppe, D.
Champion Spark Plug Co. Drive mechanism for a plurality of rotatable objects, P (5) 137*c*. Insulator body having an electrically conductive surface and method, P (11) 343*i*.
Chan Ngok Mai, Korenev, Yu. M., and Novoselova, A. V. System KF-K_2BeF_4-K_2ZrF_7, (9) 287*e*.
Chance, D. A. See Butler, J. H.
Chance, H. Records and the Nailsea glassworks, (5) 128*h*.
Chandra, A. See Rao, M. G.
Chandra, B. Basic approach to furnace design, (5) 147*d*.
Chandra, K. See Agrawal, V. K.
Chandra, P., Tare, V. B., and Sinha, A. P. B. Optical and electrical properties of zinc oxide single crystals, (3) 84*f*.
Chandra, S., Pandey, G. K., and Agrawal, V. K. Entropy of vacancies in ionic crystals, (9) 282*e*.
Chandrashekhar, G. V., Mehrotra, P. N., Rao, G. V. S., Subbarao, E. C., and Rao, C. N. R. Semiconduction in nonstoichiometric rare earth oxides, (5) 139*h*.
Chaney, P. E. See Babb, S. E., Jr.; Bennett, J. D.
Chang, C. H., and Margrave, J. L. High pressure-high temperature studies (II) direct preparation of β- and γ-$LiBO_2$, (3) 81*a*.
Chang, H. C. See Jennings, V. J.
Chang, L. L. Y. Melting relation in the system TiO_2-WO_2, (6) 87*g*. Solid solutions of scheelite with other $R^{II}WO_4$-type tungstates, (6) 188*g*.
Chang, L. L. Y., Scroger, M. G., and Phillips, B. High-temperature condensed phase equilibria in the system Ti-W-O, (8) 254*h*.
Chang, N. C. Energy levels and crystal-field splittings of Nd^{3+} in yttrium oxide, (7) 217*j*. See Richman, I.
Chang, N. C., and Gruber, J. B. Spectra and energy levels of Eu^{3+} in Y_2O_3, (6) 188*j*.
Chang, R. Relations between the nonlinear elastic constants of monocrystalline and polycrystalline solids of cubic symmetry, (11) 356*c*.
Chang, S. S. See Bestul, A. B.
Chang, S. S., Horman, J. A., and Bestul, A. B. Heat capacities and related thermal data for diethyl phthalate crystal, glass, and liquid to 360°K, (4) 110*j*.
Chang, T. N. See Greenberg, S. A.
Chang, Y. A. Temperature dependence of the bulk modulus and the Anderson-Grueneisen parameter δ of oxide compounds, (6) 189*j*.
Chao, C. C. See Wertz, J. E.
Chao, T. See Sun, Shiou-Chuan.
Chapin, D. S., Kafalas, J. A., and Honig, J. M. Electrical properties of ferromagnetic CrO_x-$(1.89 < x < 2.02)$, (11) 352*i*.
Chapin, R. Why should American women look at china and glass? (4) 91*i*.
Chapman, A. T. See Hamner, R. L.
Chapple, B. S., Jr. Marketing—making things happen, (3) 89*b*.
Charbonnages de France. Grinding device in a fluidized layer, P (8) 251*c*.
Charbonnier, F. M., Martin, E. E., and Swanson, L. W. Field emission cathode having tungsten Miller indices 100 plane coated with zirconium, hafnium, or magnesium on oxygen binder, P (6) 177*j*.
Charig, J. M. Low-energy electron diffraction observations of α-alumina, (4) 112*c*.
Charles F. Kettering Foundation. Direct reading wavelength independent radiometer employing a pyroelectric crystal detector, P (11) 343*b*.
Charles, N. Out of an impasse, (6) 175*i*.
Charles, R. J. Activities in Li_2O-, Na_2O-, and K_2O-SiO_2 solutions, (1) 5*a*. Metastable immiscibility in the BaO-Li_2O-SiO_2 system, (3) 64*f*. Method for producing high critical field superconducting circuits, P (2) 51*c*. Nature of glasses, B (11) 358*h*.
Charles, R. J., and Wagstaff, F. E. Metastable immiscibility in the B_2O_3-SiO_2 system, (2) 59*a*.
Charlesby, A. Problems in the irradiation of polymers, B (10) 329*b*.
Charleston, R. J. James Giles as a decorator of glass (I, II), (4) 91*f*. Porcelain in the collection of Earl Spencer at Althorp, Northamptonshire (I) English porcelain, (4) 91*g*.
Charlier, R. A. See Schechter, M.
Charlton, E., and Childs, E. E., Jr. Dolomite—a basic refractory, (1) 11*c*.
Charlton, T. E., and Long, R. K. Aircraft nose radome with ceramic cover mounted on metallic framework, P (11) 339*g*.
Charm, W. B. Freeze-drying as a rapid method of disaggregating silts and clays for dry particle size analysis, (2) 54*d*.
Charnock, H. Method of attenuating a ribbon of glass on a molten metal bath, P (2) 41*j*.
Charpentier, P., Rabbe, P., and Manenc, J. Plasticity of magnetite measured by hardness as a function of temperature, (7) 220*b*.
Charvat, V. K. Method of manufacturing grinding wheels, etc., P (7) 193*h*.
Charvat, V. K., Jarvi, R. E., and Srail, R. C. Apparatus for making abrasive articles, P (10) 293*g*.
Chas. Pfizer & Co., Inc. Process for the preparation of iron oxide, P (11) 349*g*. Process for slaking high calcium quicklime, P (5) 125*h*.
Chase, A. B. Habit changes and growth mechanisms of In_2O_3 grown from PbO-B_2O_3 melts, (10) 321*f*. See Wolten, G. M.
Chase, A. B., and Osmer, J. A. Growth and preferential doping of zircon and thorite, (10) 321*e*.
Chatfield, E. J. Simple particle size comparator, (4) 103*g*.
Chatterjee, A. K. Nature of china clay deposits around Karanjia, Singhbhum, Bihar, (1) 15*d*.
Chatterjee, M. See Mukhopadhyaya, M.

Chatterjee, M. K., and Lahiri, D. Pozzolanic activity in relation to specific surface of some artificial pozzolans (I) measurement of surface area from water adsorption isotherms; (II) relation between pozzolanic activity and specific surface, (5) 125*f*.
Chatterjee, M. R. See Jagas, P. J.
Chatterji, S. See Majumdar, A. J.
Chatterji, S., and Jeffery, J. W. Discussion of "Expansion characteristics of calcium sulfoaluminate hydrates," (1) 2*g*. Discussion of "Influence of $CaSO_4 \cdot 2H_2O$ on the hydration character of $3CaO \cdot Al_2O_3$," (8) 228*g*. Further evidence relating to the new hypothesis of sulfate expansion, (8) 228*d*. Microstructure of set high-alumina cement pastes, (10) 295*g*.
Chatterji, S., and Majumdar, A. J. Studies of the early stages of paste hydration of high alumina cements (I) hydration of individual aluminates, (1) 3*a*; (III) hydration of commercial high alumina cements, (1) 3*c*.
Chau, J. Y. H. Electronic Raman spectrum of $Ce^{3+}/CaWO_4$ at 77° and 2.2°K, (7) 217*h*.
Chaudhuri, M. K. R. Bauxite in India—an assessment of reserves, (3) 77*d*.
Chaumet, C. Milling of clay, (9) 278*i*.
Chaumont, H. J. Surface treatment of glass and apparatus therefor, P (3) 66*d*.
Chaurskii, N. I. See Il'yasov, I. I.
Chay, D. M., Palmour, H., III, and Kriegel, W. W. Microstructure and room-temperature mechanical properties of hot-pressed magnesium aluminate as described by quadratic multivariable analysis, (2) 59*b*.
Chebotarev, N. T. See Zaytseva, L. L.
Cheema, A. A. See Safdar, M.
Chekhovskoi, V. Ya. See Banaev, A. M.
Chembestos Corp. Means and method for removing iron from asbestos ore, P (6) 183*b*.
Chemokomplex Vegyipari Gep-es Berendezes Export-Import Vallalat. Mechanized heavy duty filter presses, P (10) 312*e*.
Chem-Seek, Inc. Carbon-coated alumina and process for making, P (4) 104*h*.
Chen, H. S. See Bagley, B. G.
Chen, N. Y., and Weisz, P. B. Novel cyclic catalytic process for the conversion of hydrocarbons, P (4) 105*a*.
Chen, Pei-Yuan. Modification of sandstone classification, (9) 284*f*.
Chenavas, J. See Waintal, A.
Chenebault, P., and Francois, B. Uranium dioxide as a fuel in power reactors, (6) 174*h*.
Cheney, G. L. Method for making compound semiconductor materials, P (10) 310*g*.
Chen-Tsai, Ching-Tang. See Sun, Kuan-Han.
Cherepanov, B. S. See Bystrikov, A. S.
Chernets, A. N. See Podgaetskii, V. M.
Chernick, C. L. See Selig, H.
Chernyak, M. G. Problem of the strength of glass fiber, (10) 298*i*.
Chernyakova, R. M. See Pavlushkin, N. M.
Chernysh, N. V. See Kondrat'ev, Yu. N.
Cheroff, G. See Reisman, A.
Cherpin, V. T. Automation in magnetometric and dilatometric measurements, (1) 20*j*.
Chesswas, M. See Cockayne, B.
Chevron Research Co. Method for adjusting the initial activity of chromia-alumina catalysts, P (1) 25*d*. Vanadium oxide catalyzed oxidations, P (11) 350*a*.
Chi, C. W. See Punwani, D.
Chiarotti, G., and Grassano, U. M. Modulated F-center absorption in KCl, (10) 323*a*.
Chiba, S. See Takei, H.
Chicago Aerial Industries, Inc. Method of fusing single layer fiber optic strip, P (1) 9*c*.
Chicago Copper & Chemical Co. Treatment of metallic ferrites, P (9) 275*c*.
Chikawa, Jun-ichi. See Mitsuhashi, H.
Chikisheva, L. S. See Negina, V. R.
Childress, L. K. Apparatus and method for determining specific gravity, P (4) 103*f*.
Childs, E. E., Jr. See Charlton, E.
Childs, G. E. Lamp sealing apparatus with double revolving and orienting sealing heads, P (6) 170*j*.
Chilingar, G. V. See Adamson, L. G.
Chilingarian, G. V. See Serruya, C.
Chindgren, C. J., Bauerle, L. C., and Shibler, B. K. Calcium vanadate precipitation and processing, (5) 147*i*.
Ching, A. See Welsh, W. E., Jr.
Chinner, G. A. Chloritoid and the isochemical character of Barrow's zones, (3) 79*f*.
Chinoy, A. R. See Jha, J. C.
Chiola, V. See Vanderpool, C. D.
Chirana Praha, Narodni Podnik. X-ray diffraction goniometer with specific drive mechanism for the specimen holder and detector, P (4) 103*j*.
Chirnside, R. C. Analytical techniques at their limit—some implications of modern techniques, B (7) 224*i*.
Chisholm, R. S., Sleighter, G. E., and Ernsberger, F. M. Method of increasing stain resistance of a glass body subjected to an ion exchange strengthening setup, P (3) 65*g*.
Chistyakova, A. A. See Arakelyan, O. I.
Chivers, M. A. Infrared moisture measurement, (7) 212*i*. See Seabridge, F. T.
Chmela, J. Determination of stresses in the enamel-cast iron system, (5) 125*j*.
Chmielenski, J. Heat resistance of glass products, (3) 63*j*.
Cho, T. Y. See Messer, C. E.
Chojnicka, G. Technology of obtaining pictures in photosensitive glasses, (3) 64*b*.
Chol, G., and Damay, F. X-ray diffraction study of the formation mechanism of ferrites of the spinel type, (10) 327*c*.
Chol, G., Gros, Y., Pebay-Peyroula, J. C., and Barbe, J. P. Study by Moessbauer effect of intermediate phases in the formation of manganese and zinc ferrites, (1) 32*e*.
Chopoorian, J. A., Dorion, G. H., and Model, F. S. Photochromism of metal oxides (I) light sensitivity of MoO_3 or WO_3 coprecipitated with TiO_2, (4) 114*d*.
Chopra, A. Means for forming planar junctions and devices, P (4) 100*i*.
Chopra, K. L. See Mariano, A. N.
Chopra, S. K. Hydration and hardening of some clinker-based cements—unresolved problems, (1) 2*g*.
Chopra, S. K., and Taneja, C. A. Coordination state of aluminum ions in $CaO-Al_2O_3-SiO_2$ glasses, (1) 27*h*. Test investigation of Rourkela slag, (8) 229*b*.
Chorne, J. See Sutton, W. H.
Chorney, P. See Chow, K. K.
Choudhury, U. C. R., and Chakraborty, P. N. Angularity and mineralogical studies on Indian foundry sands, (6) 172*g*.
Chow, K. K., Maddix, H. S., and Chorney, P. Thermionic emission of alkali ions from impregnated metal matrices, (1) 17*d*.
Chow, Ken-Tang. Charged particle detector with lithium compensated intrinsic silicon as an intermediate region, P (11) 343*g*.
Chow, T. K. See Lipschutz, L. D.
Choyke, W. J. See Patrick, L.
Christ, C. L. See Hostetler, P. B.
Christensen, A. N. Crystal structure of a new polymorph of CrOOH, (6) 184*e*.
Christensen, A. N., Hazell, R. G., and Nilsson, A. Hydrothermal investigation of the systems $Y_2O_3-H_2O-Na_2O$, $Y_2O_3-D_2O-Na_2O$, $Y_2O_3-H_2O$, and $Y_2O_3-H_2O-NH_3$—crystal structure of $Y(OH)_3$, (7) 218*f*.
Christensen, A. N., and Jensen, S. J. Hydrothermal preparation of α-ScOOH and γ-ScOOH—crystal structure of α-ScOOH, (5) 153*a*.
Christensen, D. I. Laminated safety glass, P (11) 336*b*.
Christensen, E. C. P. Rotary kiln installations, P (2) 56*c*.
Christensen, F. L. Apparatus for shaping crystalline carbon bodies, P (6) 163*h*.
Christensen Diamond Products Co. Apparatus for shaping crystalline carbon bodies, P (6) 163*h*. Diamond saw or milling blades, P (6) 163*j*.
Christenson, C. W. See Gloyna, E. F.
Christiansen, E. B. See Denson, C. D.
Christie, G. E., Jackson, J., Lyons, G. A., Cragg, D. G., and Martin, F. S. Fabrication of fueled BeO by extrusion and sintering, (4) 96*d*.
Christman, R. P. See Elleman, T. S.
Christy, R. W., and Dimock, J. D. Color centers in TlCl, (8) 252*h*.
Chromalloy American Corp. Heat-treatable nickel-containing refractory carbide tool steel, P (5) 135*d*. Surface hardened composite metal article, P (5) 136*b*.
Chromy, S. High-temperature microscopic investigation of tricalcium silicate and dicalcium silicate phases in portland cement clinker, (1) 2*g*. Optical relations between modifications of Ca_2SiO_4, (1) 30*g*.
Chrysler Corp. Laminating process and apparatus, P (1) 9*f*.
Chu, G. P. K. See Sanford, E. A.
Chu, G. P. K., and Potter, A. Structure of pottery and whiteware bodies, (9) 271*f*.
Chu, G. P. K., and Soga, N. Apparatus for testing strain, P (5) 146*i*.
Chu, K. C., Kikuchi, C., and Viehmann, W. ESR of niobium in $CaWO_4$, (11) 352*f*.
Chu, T. L. Apparatus for producing vapor growth of silicon crystals, P (6) 177*a*. Method for growing germania films, P (1) 18*a*.
Chu, T. L., Ing, D. W., and Noreika, A. J. Aluminum nitride films by chemical transport, (11) 350*g*.
Chu, T. L., and John, H. F. Use of halogens and hydrogen halides in insulating oxide and nitride deposits, P (6) 178*j*.
Chu, T. L., Szedon, J. R., and Gruber, G. A. Silica films by the oxidation of silane, (10) 303*f*.
Chukhlantsev, V. G. See Galkin, Yu. M.
Chukreev, N. Ya. See Smirnov, M. V.
Chung, D. H., and Buessem, W. R. Elastic anisotropy of crystals, (2) 58*c*.
Churaev, N. V. See Mironov, A. M.
Churms, S. C. Effect of pH on the ion-exchange properties of hydrated alumina (I) capacity and selectivity; (II) kinetics of exchange, (3) 80*f*.
Chute, J. H. Direct observation of fission fragment damage in some ceramic oxides, (9) 281*b*.
Chute, J. H., and Walker, D. G. Direct observations of damage in neutron-irradiated BeO, (2) 43*h*.
Chvatal, T. Aluminum-chromium phosphate, a new refractory binder, B (9) 291*d*.
Ciapetta, F. G. See Wilson, C. P., Jr.
Ciba, Ltd. Heat treatment of high-melting solids in fine particle form, P (2) 47*b*. Process for the manufacture of niobates and tantalates of alkali metals and alkaline earth metals and coating objects therewith, P (5) 142*d*.
Cieala, M. See Widaj, J.
Cilyo, F. F. Determination of vapor coating rate by X rays emitted from the vapor, P (6) 181*d*.
Cincinnati Milling Machine Co. Dressable heat conductive backing for abrasive wheels, P (9) 261*i*.
Cini, L. Equilibrium reactions and dielectric characteristics of compositions near the field of primary crystallization of cordierite, (6) 176*f*.
Ciric, J. Synthetic zeolites—growth of larger single crystals, (4) 117*c*.
Cizeron, G. See Bacmann, J. J.
Claassen, H. H. See Selig, H.
Claps, W. A., and Dorman, E. L. Automatic control structure for particle study apparatus, P (9) 277*e*.
Clar, E., and Paris, R. A. Solid solution of fine grain metallic carbides and method, P (8) 241*e*.
Clare, C. P., & Co. Method of forming projections in reed switch assemblies by selective heat softening, P (5) 141*i*.
Clark, D. P., and Meredith, R. E. High-temperature solid-state battery, (6) 176*a*.
Clark, F. P., and Gladwell, R. T., Jr. Automatic molten glass level control apparatus, P (2) 40*c*.
Clark, H. T. See Creevy, C.
Clark, M. G. See Burns, R. G.
Clark, O. M. High voltage semiconductor rectifier with a sloping surface across barrier edge, P (11) 343*g*.
Clark, R. See Palmer, A. R.
Clark, W. L. See Wang, F. E.
Clarke, E. C. W., and Glew, D. N. Evaluation of thermodynamic functions from equilibrium constants, (3) 81*a*.
Clarke, F. J. P. See Baker, T. W.; Davidge, R. W.
Clarke, F. J. P., Wilks, R. S., and Bowen, D. H. Mechanisms of irradiation-induced growth and cracking in BeO, (2) 45*a*.
Clarke, J. F. Ceramic brazing means, P (8) 244*c*.
Clarke, O. M., Jr. Clay deposits of the Tuscaloosa group in Alabama, B (6) 192*e*.
Clarke, T. E. Studies in the cold-pressing and sintering of BeO, (4) 96*h*.
Clary, J. D. Apparatus for conveying and blending solids, P (8) 247*d*.
Clasen, H., Mueller, J., and Joppen, R. Process for the production of soluble compounds, P (3) 78*d*.
Claspy, P. C. See Smakula, P. H.
Claudel, J. See Hadni, A.
Clausen, E. M. See Rutter, J. W.
Clausier, M. See Rolin, M.
Claydon, C. R. See Carlson, K. D.
Clearfield, A. Production of aqueous suspension of colloidal, crystalline, hydrous oxides of zirconium and hafnium, P (4) 97*f*.
Cleary, J. G. See Johansen, H. A.
Cleek, G. W. Optical constants of some oxide glasses in the strong absorption region, (9) 263*j*.
Clements, J. F. Attempting the impossible—a survey of refractories testing, (10) 302*c*.
Clendenen, R. L., and Drickamer, H. G. Lattice parameters of nine oxides and sulfides as a function of pressure, (7) 219*c*.
Clennett, G. See Marshall, J. G.
Clerc de Bussy, J. M. Y. le. Electric glassmaking furnace, P (7) 198*a*.
Clevite Corp. Method of forming a miniature nozzle from a glass tube, P (10) 301*a*. Method of making photosensitive elements, P (6) 178*e*. Method for producing a multilayer bearing, P (5) 126*a*. Piezoelectric resonator and method, P (4) 100*f*, P (5) 142*a*, P (8) 245*j*. Transducing method and apparatus, P (3) 74*d*.
Clewes, H. W. Enamel preparation, (11) 332*i*.
Clifton, R. A., Jr., and Johnson, R. C. Method of preparing zirconium carbide fibers and the product, P (8) 241*c*.
Cline, C. See Frechette, V. D.
Cline, C. F. See Smith, D. K., Jr.
Cloos, E. Experimental analysis of gulf coast fracture patterns, (9) 282*i*.
Cloos, P., and Mortland, M. M. Expansion and electrical conductivity of montmorillonite in ammonia atmosphere, B (7) 224*h*.
Clough, P. J. See Baer, C. A.
Clougherty, E. V., and Kalish, D. High-pressure, high-temperature ceramic structures, B (4) 121*h*.
Clyne, M. A. A., and Coxon, J. A. Formation and detection of some low-lying excited electronic states of BrCl and other halogens, (9) 282*j*.
C. M. C. Corp. Ceramic coatings, P (2) 38*a*.
C M Mfg. & Machine Co. High temperature furnace conveyor, P (9) 278*c*.
Coates, D. F., and Gyenge, M. Capabilities of photoelastic coatings for the study of strain in rocks, B (3) 90*i*. Plate-load testing on rock for deformation and strength properties, B (3) 90*i*.
Coates, D. G. Kikuchi-like reflection patterns obtained with the scanning electron microscope, (8) 248*j*.
Coates, N. H. See Bluman, D. E.; Rosenecker, C. N.
Coates, R. B. Porous plug assembly for metallurgical receptacle, P (1) 13*f*.
Coats, C. J. A. Serpentine minerals from Manitoba, (9) 278*i*.
Coats & Clark, Inc. Traveler inserts including ceramic wear resistant element, P (5) 126*c*.
Cobb, V. J., and Coleman, J. R. Czochralski growth of iron-59 doped calcium tungstate crystals and the determination of iron retention by radiochemical analysis, (4) 107*j*.

Coble, R. L. See Francis, T. L.; Gupta, T. K.; Mistler, R. E.; Roy, S. K.
Cocca, T. See Nester, H. H.
Cochardt, A. W. Ferrite magnets, P (6) 177*h*. Permanent magnet material and process, P (8) 245*i*.
Cochran, C. N. Calculated model for NaF-AlF$_3$ system, (6) 184*a*.
Cochran, L. F. Manufacture of ceramic bases, P (4) 100*g*.
Cockayne, B., Chesswas, M., and Gasson, D. B. Single-crystal growth of sapphire, (8) 257*a*.
Cockayne, D. J. H., Goodman, P., Mills, J. C., and Moodie, A. F. Design and operation of an electron diffraction camera for the study of small crystalline regions, (1) 20*j*.
Cockrell, W. D. Control means for sequencing a plurality of glass scoring means, P (1) 8*h*.
Cocks, A. C., and Wood, A. A. R. Method for bonding aluminum to borides, P (6) 174*f*.
Codell, M. See Iyengar, R. D.
Coeure, P. Spectroscope for piezoelectric and nuclear reasonance, (3) 76*g*.
Coffman, A. C. Mill-jar support, P (3) 75*b*.
Cohen, A. J. See Schlesinger, M.
Cohen, J. Gas emission in vacuum from MgO surfaces previously exposed to air, (4) 98*j*.
Cohen, M. I. Laser beams and integrated circuits, (3) 71*g*.
Cohen, M. L., and Bergstresser, T. K. Band structures and pseudopotential form factors for fourteen semiconductors of the diamond and zinc blende structures, (8) 252*d*.
Cohen, S. Thermoluminescence, photoconduction, and optical absorption of irradiated doped vitreous silica, (7) 197*e*.
Cohn, E., De Forest, R. A., and Frick, R. G. Process of producing high temperature resistant insulated wire, such wire, and coils made therefrom, P (2) 38*e*.
Cohn, M. I., and Perdue, R. D. Reducing particle size of clay and rheology control of clay-water systems, P (2) 57*c*.
Colapinto, E. Elements of silk-screening (I, II), (8) 246*j*.
Colbow, K. Free-to-bound and bound-to-bound transitions in CdS, (8) 253*j*.
Colchagoff, R. D. Glass forming apparatus, P (3) 65*h*.
Colding, B. Cutting insert for chip cutting machining and means for manufacturing, P (5) 123*i*.
Cole, D. G. Some mechanical aspects of compression testing machines, (8) 248*b*.
Cole, E. L., and Knowles, E. C. Preparation of metal aluminides, P (10) 318*i*.
Cole, H. B. Method for forming image-transfer devices embodying light-conducting fibers and light-absorbing filaments, P (9) 265*b*. See Hopkins, E. C.; Siegmund, W. P.
Cole, K. J. Ceramic finishing investigated, (7) 211*d*.
Cole, M. E. Basic oxygen furnace construction, P (6) 174*j*.
Cole, P. H. Nonlinear coupling between antiferromagnetic resonance modes in RbMnF$_3$, (1) 16*j*.
Cole, S. S., Jr. Thermal conductivity of molybdenum thick films on beryllium oxide, (10) 308*i*.
Cole, T., Donald, D. K., Lambe, J. J., and Vassell, W. C. Electroluminescent process including an ionically conducting electrolyte, P (2) 51*a*.
Cole, W. F. Some relations between mineralogical and chemical composition and moisture expansion of fired clay bodies, (10) 306*b*.
Cole, W. F., and Crook, D. N. High-temperature reactions of clay mineral mixtures and their ceramic properties (IV) dimensional and weight changes on refiring and the pore-size distribution of fired kaolinite-muscovite-quartz mixtures with 25% (wt) quartz, (3) 81*c*.
Coleburn, N. L. Compressibility of pyrolytic graphite, (5) 150*f*.
Coleman, D. S., and Lacy, P. D. A. Phase equilibrium diagram for the KCl-NaCl system, (3) 84*h*.
Coleman, J. R. See Cobb, V. J.
Coleman, M. Block for refractory linings, P (11) 340*a*.
Colgan, J. D., and Witheford, J. M. Preparation of extruded catalysts and catalyst supports containing polyacrylamide, P (1) 25*b*.
Coli, G. F. Noble combustible in the service of a highly specialized technology, (8) 249*g*.
Colles, M. J., and Smith, R. C. Direct measurement of gain in a lithium niobate parametric amplifier, (1) 16*d*.
Collet, J. P. See Leglise, G.
Collier, J. See Radford, C.
Collings, R. K. Industrial Minerals—review—1966, (1) 24*j*; 1967, (11) 348*j*.
Collins, A. C., Masterson, H. G., and Jennings, P. P. Effect of oxidation on the compressive strength of graphite, (8) 253*h*.
Collins, A. L. See Wells, R. L.
Collins, F. C., and Nakayama, T. Transport processes in the thermal growth of metal and semiconductor oxide films, (10) 309*c*.
Collins, G. A., Jr., and Phelps, F. L., Jr. Method for making ceramic bodies, P (2) 47*i*.
Collins, J. H. See Auld, B. A.
Collins, T. C. See Park, Y. S.
Collis, W. J. See Jacobs, J. E.
Collongues, R. See Harari, A.; Queyroux, F.
Collongues, R., Gilles, J. C., Lejus, A. M., Perez y Jorba, M., and Michel, D. Metallic oxynitrides, (1) 30*g*.
Collongues, R., Thery, J., and Lejus, A. M. Alkali ferrites and aluminates, (6) 183*h*.
Colombo, R. L. See Amato, I.; Giuliani, S.
Colonial Sugar Refining Co., Ltd. Method of ore sorting based on differential infrared emission, P (11) 349*c*. Method of rendering asbestos ore particles differentially fluorescent [for economical separation], P (1) 25*f*.
Colthorpe, A. C. Selecting isostatic pressing equipment, (10) 312*i*.
Columbiana, Inc. Hot top and composition thereof, P (6) 174*c*.
Combe, E. C., and Smith, D. C. Effects of some organic acids and salts on the setting of gypsum plaster (II) tartrates, (10) 294*e*.
Comes, R., Lambert, M., and Guinier, A. Mechanism of the transformation of crystalline quartz into amorphous silica by neutron irradiation, B(10) 329*b*.
Cometta, C., and Van Rutten, F. Pendulum for zeta potential determination, (9) 277*a*.
Comitato Nazionale per l'Energia Nucleare. Production of thorium-uranium oxides, P (7) 205*a*.
Comly, J. B. Magnetic susceptibility of ($U_{1-c}Th_c$)-O_2, (11) 354*b*.
Commissariat a l'Energie Atomique. Device for the thermal study of a sample, P (10) 316*a*. Extraction of the sulfuric acid complexes of beryllium using primary amines, P (4) 105*b*. Furnace for manufacturing ingots or bars of metal or alloys, particularly bars of uranium carbide [under vacuum], P (9) 278*c*. Induction melting process of central core portion of cylindrical refractory materials, P (2) 47*c*. Method of inhibiting the corrosion of graphite in a CO_2-cooled nuclear reactor, P (6) 174*g*. Moderator-fuel element, P (1) 13*b*. Porosimeter, P (9) 277*h*. Process for the fabrication of fuel elements for nuclear reactors, P (7) 205*f*. Process for the preparation of beryllium oxide, P (7) 215*c*. Process of separation of uranium and thorium from a solution containing them, P (4) 97*e*.
Commonwealth Scientific & Industrial Research Organization. Method of producing compacts by reacting particulate ingredients, P (3) 69*d*. Silicate layer minerals and [grease] products made therefrom, P (3) 78*c*.
Compagnie Francaise de Raffinage. Fuel cell having solid stabilized zirconium oxide electrolyte, P (2) 51*b*.
Compagnie Francaise de Television. Color tube with triplet phosphor strips making 40° to 70° angle with horizontal, P (4) 99*f*.
Compagnie Francaise Thomson-Houston. Fluorescent screen for brightness amplifier tubes and method of making, P (3) 72*g*.
Compagnie Generale d'Electricite. Delay line having a thermoelectric generator responsive to rate of heat transfer, P (11) 343*b*. Preparation of oriented monocrystals, P (9) 274*e*.
Compagnie Generale d'Electro-Ceramique. Self-washing insulators, P (3) 70*g*.
Compagnie Generale de Telegraphie Sans Fil. Cubic ferrite with a high upper frequency limit, P (10) 309*j*.
Compagnie Industrielle Francaise des Tubes Electroniques. Method and means for manufacturing electron tube sockets, P (3) 65*i*.
Compagnie de Saint-Gobain. Apparatus and method for cutting glass, P (2) 40*b*. Method and apparatus for detecting flaws in transparent [planar] bodies, P (4) 94*h*. Method and apparatus for glassmaking, P (2) 41*f*. Method and apparatus for tempering glass between cold plates, P (5) 130*g*. Surface treatment of glass and apparatus therefor, P (3) 66*d*.
Compagnoni, A. F. Hammer tip and clamp, P (7) 214*d*.
Companion, A. L., and Mackin, M. Diffuse reflectance spectra of some thiometallates and oxides of the chromium family, (3) 80*c*.
Components, Inc. Passivating silicon semiconductor devices with sputtered tungsten oxide at low temperatures, P (2) 52*b*.
Compton, V. B. See McWhan, D. B.
Comstock, R. L., and Raymond, J. J. Magnetostriction of ytterbium and cerium in YIG, (4) 98*j*.
Conard, B. R. See Franzen, H. F.
Cone, C., Pinney, R. E., and Rinker, F. G. Hearth dam, P (7) 204*e*.
Congleton, J., and Petch, N. J. Crack-branching, (5) 126*h*. Dislocation movement in the brittle fracture of alumina, (10) 319*f*.
Congleton, R. S. See Keister, F. Z.
Conley, J. W. See Mahan, G. D.
Conley, R. F. Insulating compositions containing heat tempered montmorillonite-free kaolin, P (5) 137*f*. Statistical distribution patterns of particle size and shape in the Georgia kaolins, B (8) 259*i*.
Conn, J. B. See Taylor, R. C.
Connor, T. See Baldino, P.
Conrad, G. H. See Estill, W. B.
Conrad, R. W., Jones, C. E., and Williams, E. W. Reflectivity studies of epitaxial $Ga_xIn_{1-x}As$, (11) 356*d*.
Conroy, A. R. See Manring, W. H.
Consolidated Vacuum Corp. Cathode sputtering [triode] apparatus with plasma confining means, P (10) 309*h*.
Consortium fuer Elektrochemische Industrie G.m.b.H. Process for manufacturing homogeneous bodies of germanium-silicon, P (5) 142*e*.
Constabaris, G. See Kuendig, W.
Constabel, H. G. See Baier, E.
Constantinescu, F. Effect of composition on the physicotechnical properties of cast calcium silicates, (6) 164*a*. Indirect methods of determining the specific surface of fine-ground quartz sands, (2) 54*j*.
Constantinescu, F., and Sas, I. Methods for determining the specific surface of quartz sands of fine grain size, (3) 75*g*.
Conti, R., Toussaint, C. J., and Vos, G. Application of X-ray diffraction analysis to uranium ceramics (II) quantitative analysis of the uranium carbides, (8) 247*i*.
Continental Carbon Co. Production of finely divided silicon or titanium carbide, P (1) 14*f*.
Continental Oil Co. Process for producing colloidal-size particles of alumina monohydrate, P (3) 78*c*. Water hydrolysis reactor for making alumina, P (8) 252*a*.
Control Systems Corp. Method and apparatus for high frequency treatment of materials, P (9) 278*a*.
Conty, C. Recent improvements in the MS 46 Cameca microprobe, (10) 315*c*. See Rouberol, J. M.
Conway, J. B. See Hein, R. A.
Conway, J. B., Salyards, D. G., Holowach, J., and Stanley, R. A. Techniques for measuring localized corrosion rates of BeO, (2) 46*g*.
Coobs, J. H. See Beutler, H.
Cook, A. M. Apparatus for molding a [resin] bearing surface on a grinding wheel, P (3) 61*f*.
Cook, C. G. Metal vapor lamp coating, P (6) 171*b*.
Cook, C. R., Jr. Resistors for integrated circuits, P (4) 101*d*.
Cook, E. G. See Linden Laboratories, Inc.
Cook, M. D., and Troell, P. T. Method of in situ fabrication of a monolith refractory lining, P (3) 69*c*.
Cook, M. D., and Watson, D. R. Bayer aluminas custom-processed for ceramic applications, (6) 182*e*.
Cook, M. G., and Rich, C. I. Negative charge of dioctahedral micas as related to weathering, B (5) 160*a*.
Cook, P. B. Lightweight aggregate by the sintering process, (10) 301*f*.
Cook, R. C. See Chaklader, A. C. D.
Cook, R. L. See Haertling, G. H.; Harris, N. H.
Cook, T. S. See Dickinson, G. A.
Cook, W. R., Jr. CdS-MnS and CdSe-MnSe phase diagrams, (10) 319*e*. Structure of δ-Fe_2O_3 (hydrate) as proposed by Okamoto, (8) 257*f*.
Cooke, A. H. See Cashion, J. D.
Cooke, C. C. Process control variables in glass melting, (2) 39*j*.
Cooley, C. G. Vibrating grinding mill, P (10) 318*j*.
Cooley, R. H. Profit advancement through handling, (10) 298*c*.
Coombs, D. S. See Roedder, E.
Cooper, A. E. See Worrall, W. E.
Cooper, A. R. See Haggerty, J. S.; Kreider, K. G.
Cooper, A. R., and Varshneya, A. K. Diffusion in the system K_2O-SrO-SiO_2 (I) effective binary diffusion coefficients, (3) 63*f*.
Cooper, D. E. Copper oxide-alumina catalyst composition, P (6) 183*b*.
Cooper, G. A., and Kelly, A. Tensile properties of fiber-reinforced metals—fracture mechanics, (1) 4*d*.
Cooper, G. E. See Raine, F. F.
Cooper, M., and Leake, J. A. Compton profiles of graphite and diamond, (4) 107*a*.
Cooper, S. A. See Miller, B. C.
Coors Porcelain Co. Alumina ceramic, P (7) 206*g*. Ceramic housing for semiconductor components, P (9) 272*a*.
Coovert, R. E. See Delord, J. F.
Cope, G. R. See Koenig, E. W.
Copp, A. N., Nakahira, M., and Brindley, G. W. Detection of thermal reaction in mixed oxide powders by electrical resistance measurements, (11) 351*i*.
Coppel, C. P. See McClaine, L. A.
Coppen, P. J. See Mehta, R. R.
Corbin, V. L., Koury, F., and Levesque, M. High pressure electric discharge device containing a fill of mercury, halogen, and an alkali metal and barrier refractory oxide layers, P (2) 51*d*.
Cordelle, M. See Pruniaux, B.
Cordes, L. F. Evidence of excess silicon in reactively sputtered silicon nitride films, (11) 352*g*.
Cordfunke, E. H. P., and Giessen, A. A. van der. Particle properties and sintering behavior of uranium dioxide, (7) 202*c*.
Cordfunke, E. H. P., and Loopstra, B. O. Preparation and properties of the uranates of calcium and strontium, (5) 157*c*.
Cordone, L., and Palma, M. U. Permanent photoinduced conductivity in silver halide crystals, (10) 324*h*.
Corenzwit, E. See Matthias, B. T.
Corhart Refractories Co. Basic fused refractory material, P (10) 304*b*. Immersion-type thermocouple having a sheath composed of a sintered ceramic refractory, P (7) 204*i*. Refractory, P (8) 241*d*. Refractory with periclase-based stabilized solid solution, P (1) 14*a*.
Coriell, A. S. See Kolb, E. D.
Corley, R. A. See Wilcox, W. R.
Corll, J. A., and Samara, G. A. Search to 25 kbars for a transition in sodium chloride, (11) 356*j*.
Corneanu, A. See Petri, L.; Veiser, I.
Cornelius, E. B. Packaging system, P (5) 148*g*.

Cornelius, E. B., Cosgrove, L. A., and Mills, G. A. Alumina particles and method of preparation, P (3) 77*i*.

Cornelius, E. B., McEvoy, J. E., and Mills, G. A. Cracking catalyst preparation, P (8) 251*a*. Preparation of synthetic faujasite containing exchangeable magnesium cations, P (5) 148*j*.

Corning Glass Works. Alignment structure for a glass mold and plunger, P (10) 299*i*. Apparatus for blending glass, P (2) 40*b*. Apparatus for decorating glassware, P (10) 299*j*. Apparatus for forming articles from overlapping glass sheets, P (1) 8*a*. Apparatus for manufacturing glass, P (1) 8*a*. Apparatus for and method of shaping the open end of glass tubes between cooperating rollers, P (4) 94*d*. Article handling and cleaning apparatus, P (7) 208*g*. Automatic molten glass level control apparatus, P (2) 40*c*. Automatic temperature control for glass molding process, P (6) 170*f*. Cathode ray tube envelopes and methods of preparing parts therefor and fabricating such envelopes, P (5) 129*e*. Chip bonding machine, P (11) 343*g*. Clamping device, P (1) 8*e*. Coating apparatus with tracking means, P (1) 8*f*. Composition and method for making ceramic articles, P (7) 198*g*. Cutter for glass pipe, P (11) 335*j*. Electrically heated article, P (7) 198*c*. Electrode structure including temperature control means, P (3) 65*e*. Filter and method for its production, P (1) 8*j*. Flexible glass-plastic laminate, P (10) 300*b*. Forced stream feeding through orifice, P (2) 40*g*. Glass electrode composition, P (6) 170*c*. Glass electrode composition and method of using same for measuring potassium ion and sodium ion concentration, P (3) 65*f*. Glass electrodes, P (3) 65*g*. Grinding and polishing pad, P (3) 65*i*. Laminated structures and method for preparing, P (8) 235*d*. Laser employing photochromic glass as a *Q*-spoiling medium, P (5) 130*c*. Loading apparatus, P (10) 300*c*. Machine for automatically testing and orienting miniature semiconductor chips, P (8) 244*i*. Mechanical coupling for glass and ceramic articles, P (1) 9*i*. Metal inserts for use in the wall of glass envelopes for the support of electrodes, P (4) 100*d*. Method and apparatus for pressing thermoplastic materials, P (3) 65*c*. Method of forming charges of molten glass, P (2) 41*b*. Method of forming a synthetic marble, P (10) 318*d*. Method of glazing semicrystalline glass-ceramic articles and resultant intermediate layer containing composite, P (8) 235*h*. Method of making cellular phosphate glass, P (1) 9*d*. Method of making macroscopic silicon carbide fibers with a silica sheath, P (6) 174*h*. Method of making magnesium oxide fibers, P (6) 174*i*. Method of making a refractory delivery apparatus and apparatus produced, P (3) 69*c*. Method of molding comminuted nonplastic inorganic material, P (1) 20*c*. Method of preoxidation of stainless steel, P (6) 178*j*. Method for pressure molding powdered material, P (1) 18*g*. Method for producing hermetic glass to metal seals, P (6) 171*g*. Method for producing light-diffusing coatings of titania on glass, P (2) 41*i*. Method for production of glass article having increased mechanical strength, P (11) 336*i*. Method of protecting the surfaces of glass molding equipment, P (7) 199*d*. Method of reducing reboil in molten glass, P (9) 265*i*. Method of removing airlines in a cathode ray tube, P (1) 9*g*. Method for softening glass for punching holes therein by heating with a hf pulse current, P (5) 130*a*. Method of treating glass in a molten salt, P (11) 336*j*. Miniature transistor enclosed in a glass disk-shaped housing, P (7) 209*h*. Positioning apparatus, P (5) 130*b*. Process for making humidity sensing device, P (5) 130*c*. Projection lamp with multiple reflectors, P (8) 236*a*. Protection and lubrication of metals at high temperatures, P (3) 66*a*. Radiation-resistant metal sealing glass, P (5) 130*e*. Radiation window glass, P (3) 66*c*. Reflex marker, P (1) 10*a*. Refractory housing, P (10) 305*c*. Seam finishing, P (2) 42*b*. Variable index mechanism for glass press, P (4) 95*f*. Variable intensity lamp, P (7) 199*e*.

Coronas Ribera, J. M., and Puig Cardona, M. Determination of the specific surface of cement by the adsorption of colorants, (3) 62*d*.

Corral, J. S. Compacting method and means, P (8) 247*b*.

Corrin, M. L. See Glossman, N.

Corum, J. M. Determination of the fracture toughness of EGCR-type graphite, (2) 43*i*.

Coselli, R. See Giuliani, S.

Cosgrove, L. A. See Cornelius, E. B.

Costes, J. Control of quality in the electrocast refractories industry, (3) 67*a*.

Costikas, A. See Agathonikou-Kokofyllou, E.

Coston, C. J., Ingalls, R., and Drickamer, H. G. Moessbauer study of ^{60}Co (^{57}Fe) in cobaltous oxide at high pressure, (10) 323*f*.

Cotton, F. A., and Lippard, S. J. Chemical and structural studies of the rhenium(V) oxyhalide complexes (I) complexes from rhenium(III) bromide, (4) 106*c*.

Cotton, F. A., and Mague, J. T. Crystal and molecular structure of tetragonal ruthenium dioxide, (5) 150*j*.

Cotton, H. L. Hole cutting apparatus for pipe sections, P (5) 131*c*.

Cottrell, A. H. Nature of metals, B (11) 358*h*. See Kelly, A.

Coufova, P., Novak, J., and Hlasivcova, N. Hydroxyl as a defect of the perovskite $BaTiO_3$ lattice, (10) 322*a*.

Coulbert, C. D., and Campbell, J. G. Multislot film cooled pyrolytic graphite rocket nozzle, P (3) 69*e*.

Coulter, W. H. Particle analyzer threshold level control, P (10) 316*d*. See Morgan, C. T.

Coulter, W. H., and Hogg, W. R. Particle analyzing apparatus having means for observing a scanning aperture, P (9) 277*g*.

Coulter Electronics, Inc. Automatic control structure for particle study apparatus, P (9) 277*e*. Electronic particle study apparatus and vessel construction therefor, P (11) 347*g*. Particle analyzing apparatus having means for observing a scanning aperture, P (9) 277*g*. Particle analyzer threshold level control, P (10) 316*d*. Particle studying apparatus with self-clearing scanner element, P (11) 348*c*.

Counsell, J. F., Dell, R. M., Junkison, A. R., and Martin, J. F. Thermodynamic properties of uranium compounds (III) low temperature heat capacity and entropy of UP and U_3P_4, (7) 222*e*.

Counsell, J. F., Dell, R. M., and Martin, J. F. Thermodynamic properties of uranium compounds (II) low-temperature heat capacity and entropy of three uranium nitrides, (3) 87*h*.

Counts, W. E. See Bruhl, D. A., Jr.

Courbon, J. See Michel, M.

Coutures, J. P. See Foex, M.

Covington, A. K. See Robinson, R. A.

Cowan, J. H., Jr. See Buehl, W. M.

Cowan, R. E. Semiautomatic hot-pressing, (2) 53*f*.

Cowlard, F. C. See Garner, G. M.

Cowley, E. R., and Okazaki, A. Lattice dynamics of thallous bromide, (9) 283*g*.

Cowley, J. M. Irradiation effects in beryllia and zinc oxide, (4) 112*d*.

Cox, C. D., and Surek, T. Growth of single crystal calcium orthovanadate, (11) 342*h*.

Cox, D. E. See Sieger, J. S.

Cox, G. A., Cummins, D. O., Kawabe, K., and Tredgold, R. H. Preparation, optical properties, and electrical behavior of aluminum nitride, (2) 50*c*.

Cox, S. M. Method of making film resistors, P (6) 178*c*.

Cox, W. L., Steinfink, H., and Bradley, W. F. Structure refinement of La_2Te_3, a Th_3P_4 type structure, (5) 158*d*.

Coxon, J. A. See Clyne, M. A. A.

Coyne, D. M. See Cahoy, R. P.

Cozine, H. E., and Torok, J. J. Apparatus for drawing glass in cylindrical form, P (4) 94*c*.

Cragg, D. G. See Christie, G. E.

Craig, R. A. Process of making uranium mononitride nuclear fuel, P (1) 14*a*.

Craig, R. D., and Willdig, E. Mass spectrometer sample insertion devices, P (8) 249*c*.

Craig, R. R. See Webster, A. H.

Cramer, D. G. See Barrett, M. W.

Cramer, L. W. See Kovacic, S.

Cramer, R. H., Houser, A. F., and Jagel, K. I., Jr. Method for removing ammonia from an ammonium zeolite, P (1) 13*j*.

Cramer, S. D., Kenahan, C. B., Andrews, R. L., and Schlain, D. Electrodeposition of thick coatings of platinum and palladium on refractory metals from aqueous electrolytes, (2) 37*j*.

Crandall, R. S. Photoconductivity and impact ionization in CdS, (1) 16*c*.

Crandall, W. B. See Smith, C. F., Jr.

Crandon, H. D. Method of making optical elements using ultrasonic vibration, P (11) 336*h*. See Granitsas, G. A.

Crane, P. J., Dickens, P. G., and Thomas, R. E. Recombination of oxygen atoms on oxide surfaces (III) catalytic activities of doped oxides, (7) 221*b*.

Cratchley, D. See Jackson, P. W.

Craven, R. E. Palletizing equipment for the brick industry, (5) 130*j*.

Crawford, C. K. Design of thermal manipulators for ultrahigh vacuum, (8) 243*a*.

Crawford, J. H. Radiation effects in semiconductors, B (10) 328*i*.

Creevy, C., and Clark, H. T. Vented enclosed glass ampoule and method of making it, P (7) 199*c*.

Cremer, G. Ceramic documentation—proposal for an efficient system of "knowledge reference" within AEC, B (9) 291*d*.

Cremer, G., and Behrens, H. Tunnel furnace, P (7) 214*b*.

Cremer, G., Behrens, H., and Dietzsch, H. J. Apparatus for producing ceramic bodies, P (8) 247*h*.

Cremers, A., Loon, J. van, and Laudelout, H. Geometry effects for specific electrical conductance in clays and soils, B (8) 259*b*.

Crepaz, E., Raccanelli, A., and Navazio, G. Activated bentonite for bleaching, (5) 143*e*.

Cressman, H. E. Crossword puzzle approach to solving ceramic problems, (2) 54*c*.

Crevecoeur, C. See Bosman, A. J.

Creyke, W. E. C. See Duncan, J. H.

Cribb, J. L., and Tomkins, B. Nature of the stress at the tip of a perfectly brittle crack, (1) 6*a*.

Crichton, N. T. Basic oxygen furnace construction, P (4) 97*a*, P (5) 134*c*.

Crile, E. E. See Thomas, P. M.

Crisler, R. O. Infrared spectrometry, (10) 314*e*.

Criss, G. H. Castable gunning mix, P (4) 97*b*. High alumina castable, P (11) 340*d*. Mold wash, P (4) 97*c*. See Burhans, R. O.; Wallace, R. W.

Crocheron, V. D. Corrosion-proof [rubber] lining for metallurgical grinding mills, P (7) 214*c*.

Croeni, J. G., and Howe, J. S., Jr. Consolidation and forming by high-energy-rate extrusion of powder material, P (10) 312*b*.

Croft, J. B. Structures of soils stabilized with cementitious agents, (8) 229*a*.

Croft, W. J., Kestigian, M., Borovicka, R., and Garabedian, F. Unit cell dimensions in the system $PbAl_{(12-x)}Fe_xO_{19}$, (1) 33*d*.

Crofts, J. D., and Marshall, W. W. Novel synthesis of aluminosilicates, etc., (1) 30*d*.

Cromarty, R. E., and Bryden, J. G. Apparatus for measuring dimensional changes in fresh cement paste, (8) 228*c*.

Cronan, C. J. See Benedetto, B. di.

Cronan, W. L. See Jagaciak, G. J.

Cronin, G. R. High resistivity chromium doped gallium arsenide and process of making, P (1) 18*c*. See Haisty, R. W.

Cronin, G. R., Larrabee, G. B., and Osborne, J. F. Annular facets and impurity striations in tellurium-doped gallium arsenide, (11) 350*i*.

Cronin, J. See Rodriguez, A. R.

Croninger, G. J. Techniques for ceramic manufacturing, (1) 20*a*.

Crook, D. N. See Cole, W. F.

Crook, E. H. See Schultz, B. J.

Croom, H. C. Plant tips, (4) 103*f*.

Cros, C. See Kasper, J. S.

Crosby, D. P. Nondestructive testing of fireclay nozzles by sonic technique, (8) 239*d*.

Crose, G. J., Fuchs, W., and Wiegand, D. A. Schottky disorder and lattice relaxation in single crystals of NaCl due to X irradiation at room temperature, (11) 356*j*.

Croslay, T. C. Process dynamics of grinding circuits and the use of automatic control, (1) 19*j*.

Cross, F. L., Jr., and Ross, R. W. Field control of a dolomite plant, (6) 190*j*.

Cross, L. E. Ferroelectrics relaxation dielectrics, (9) 272*b*. See Cummins, S. E.; Tien, T. Y.

Crouse, D. J., Jr., and Seeley, F. G. Process for separating beryllium values from aqueous solutions, P (4) 105*f*.

Crouse, J. E. Settle blowhead and baffle attachment for glassware forming machine, P (3) 66*d*.

Crouthamel, C. E. See Johnson, C. E.

Crow, J. See Turner, C. W.

Crowder, B. L., Morehead, F. F., and Wagner, P. R. Light emitting semiconductor device, P (5) 141*c*.

Crowder, B. L., and Sienko, M. J. Some solid-state studies of tungsten trioxide and their significance to tungsten bronze theory, (5) 158*g*.

Crowe, W. G. Solid abrasive article and method of making honing elements therefrom, P (11) 331*g*.

Crowell, C. R. See Rideout, V. L.

Crowley, M. S. Failure mechanism of two-component lining of flue-gas duct, (6) 173*f*.

Crownover, J. W. Composition and method for electroding dielectric ceramics, P (1) 17*d*.

Crowther, P. A., and Dean, P. J. Phonon interactions, piezooptical properties, and the interrelation of the N3 and N9 absorption-emission systems in diamond, (8) 255*j*.

Cruickshank, D. W. J. See McDonald, W. S.

Crummett, W., and Hummel, R. Ultraviolet spectrometry, (10) 316*c*.

Crump, N. E. See Philpott, A. A.

Csabi, M. Semiconductor testing, P (7) 210*f*.

Csendes, E. See Lee, D. E.

CSF. See Compagnie Generale de Telegraphie Sans Fil.

CTS Corp. Integrated circuit, P (8) 244*f*.

Cubacub, C. V. See Bihis, M. L. M.

Cucka, P. See Kalnin, I. L.

Cucka, P., and Oliva, R. F. X-ray measurement of strain in quartz particles of whiteware bodies, (9) 271*d*.

Cuer, P., Long, J., and Teichner, S. J. Production of metallic oxides as homodispersed spherical particles, (6) 173*b*.

Cuff, D. W. Method of making fine adjustment in numerical aperture of fiber optical devices, P (11) 336*g*.

Cullen, G. V. See Hensler, J. H.

Cullen, G. V., Cutter, I. A., and Hensler, J. H. Hot-pressing of magnesium oxide aggregates, (1) 29*c*.

Cummings, H. B. Kiln loader and unloader, P (4) 98*f*. Method for decorating pottery, P (9) 271*h*. Tile setter, P (5) 137*d*.

Cummings, J. L., Sr. Metal clad refractory shapes, P (4) 97*h*. Process for making hydration resistant refractory brick, P (5) 135*f*.

Cummins, D. O. See Cox, G. A.

Cummins, S. E., and Cross, L. E. Crystal symmetry, optical properties, and ferroelectric polarization of $Bi_4Ti_3O_{12}$ single crystals, (3) 79*f*.

Cundill, M. A., and Sherman, W. F. External modes of vibration of small polyatomic ions isolated in alkali halides, (11) 352*h*.

Cuneo, F. L., Jr. Lithium silicate composition, P (10) 318*g*.

Cunningham, J. A. Semiconductor device utilizing glass and oxides as an insulator for hermetically sealing the junctions, P (8) 246*g*. See Baird, S. S.

Cunningham, R. A. See Douillard, P. A.
Cuomo, J. J. See Gambino, R. J.
Curcio, J. A., and Buttrey, D. V. E. Transmission of infrared radiation from flames by CO_2, (9) 278*b*.
Curran, D. R. See Koneval, D. J.; Shockley, W.
Currie, T. E. Measure organic film on surfaces—is it clean? (11) 332*e*.
Currin, C. G., and Hood, J. S. Method of making semiconductor circuits, P (11) 344*a*.
Curry, R. B. Deposition of montmorillonite from suspension during flow through porous media, B (9) 289*g*.
Curtis, A. W. Gas fired infrared ray generator, P (4) 104*c*.
Cuthbert, J. D., MacFarlane, W. T., and Petch, H. E. ^{11}B quadrupole coupling tensors in the hydrated borates (I) the tunnellite polyanion, (5) 137*g*.
Cuthbert, J. D., and Petch, H. E. NMR studies of hydrated sodium tetraborate minerals (I) boron-oxygen polyions in borax and tincalconite; (II) ^{23}Na sites in borax and tincalconite, (5) 155*j*.
Cutler, I. B. See Holt, J. B.; Keski, J. R.; Petersen, R. O.
Cutler, I. B., and Henrichsen, R. E. Effect of particle shape on the kinetics of sintering of glass, (11) 333*i*.
Cutright, R. C. High-temperature reflective and thermally protective coatings, P (4) 93*a*.
Cutter, I. A. See Cullen, G. V.
Cvjeticanin, D., Bulovic, V., and Zmbov, K. F. Isotope analyses of uranium samples by alpha spectrometry, (1) 21*c*.
Cwen, A. Synthetic fiber guides made of sintered corundum, (10) 299*e*.
Cypher, J. H. Apparatus for supporting a glass sheet in an upright position for heat treating, P (3) 65*b*. Method of press bending glass sheets between cold opposed shaping molds, P (6) 171*f*.
Cypres, R., and Bettens, B. Nondestructive analysis by weak radioactivation of sodium in solids in the presence of K, Al, and Si, (6) 180*j*.
Cyprus Mines Corp. Calcined hydrophilic talc pigment, P (5) 148*j*.

Daem, R. C., Gray, N. W., and Young, B. Abrasive cutting tools such as saws, P (3) 61*h*.
Daendliker, G. Process for the manufacture of niobates and tantalates of alkali metals and alkaline earth metals and coating objects therewith, P (5) 142*d*.
Dagley, J. F. See Van Sickler, R. H.
Dahlberg, R. Method for making semiconductor device, P (4) 100*d*.
Dahlke, W. E. Tunneling into interface states of MOS structures, (1) 17*f*.
Dain, R. J. Multiple billet continuous casting mold, P (1) 13*c*.
Dal, P. H., and Berden, W. J. H. Aging of plaster of Paris in relation to its equilibrium water content, B (7) 226*c*. Drying of plaster molds, (4) 98*b*.
Dale, B., and Ingraham, R. C. Method of producing semiconductor devices, P (9) 274*e*.
Dale, J. R. Semiconductor device, P (3) 74*e*.
D'Alessandro, W. J. Abrasive compositions and structures thereof comprising a thermosetting resin and a thermoplastic polyarylene polyether, P (3) 61*g*.
Daley, R. E. Hot top with centering lugs. P (2) 47*c*.
Dally, D. I. See Kozdemba, S. E.
Dalton, B. J., and Barieau, R. E. Equations for calculating various thermodynamic functions of a two-component system from an empirical equation of state, including liquid-vapor equilibria data, (6) 185*c*.
Dalton, R. H., and Grego, P. Protection and lubrication of metals at high temperatures, P (3) 66*a*.
Dalton, R. H., and Martin, F. W. Radiation-resistant metal sealing glass, P (5) 130*e*.
Daly, D. H. Apparatus for molding glass, P (6) 170*d*.
Daly, M. C. See Milberg, M. E.
Damay, F. See Chol, G.
Damen, T. C. See Porto, S. P. S.; Tell, B.
Damen, T. C., Porto, S. P. S., and Tell, B. Raman effect in zinc oxide, (8) 256*j*.
Dammler, I. See Hofmann, U.
Damon, G. F. See Polinsky, M. A.
Danchuk, I. M., and Bogoslovskaya, L. N. Preparing mineralizers and their effect on Dinas quality, (9) 268*i*.
Danfoss A/S. Semiconductor switching element with heat-responsive central current path, P (8) 246*i*. Unitary multiple solid state switch assembly, P (3) 74*f*. Voltage controlled switch, P (11) 345*e*.
Dangschat, R. See Hoppe, G.
Daniel, L. I. Method and apparatus for the manufacture of asbestos-cement articles, P (5) 135*i*.
Daniel, P. Developing tomorrow's techniques with the tools of today, (2) 35*f*. Evaluation of glass-ceramics for guided missile radomes, (3) 63*h*. Precision finishing of ferrite and ceramic magnetic components, (2) 50*b*.
Danielson, B. L. Saturation effects in the sensitized fluorescence of CaF_2 (Ce, Mn), (8) 256*h*.
Danilova, S. G. See Butt, Yu. M.
Dannoehl, W., and Nixdorf, J. Method of making glass or ceramic covered wires, P (4) 95*d*.
Danon, D. Method and apparatus for controlled deposition of a thin conductive layer, P (6) 177*h*.
Dany, W. How to apply special decorative finishes with a spray gun, (8) 247*a*.
Danyushevskii, S. I., and Liogon'kaya, R. I. Expanding plugging cement for gas boreholes, (3) 62*g*.
Darnell, J. R., and Tarver, D. A. Process for adherently depositing a metal carbide on a metal substrate, P (5) 126*b*.
Darrow, K. A. Bonding diamond to molybdenum, P (7) 193*g*.
Darvoid, T. I., Gurevich, M. A., Novichkova, S. M., and Popova, M. A. System TlBr-TlI, (3) 87*j*.
Das, B. N. See Wolff, G. A.
Das, C. R. Determination of corrosion resistance of glass to various solutions, (2) 38*i*. Studies on the opacification of glasses by phosphate, (6) 169*c*.
Das, C. R., and Douglas, R. W. Studies on the reaction between water and glass (III), (3) 64*f*.
Das, S. K., and Thakur, R. L. Sintering of titania with rutile crystals, manganese oxide, and sodium oxide as additives, (6) 173*j*.
Das, T. P. See Sharma, R. R.
D'Asaro, L. A. See Dyment, J. C.
Datars, W. R. See Calvo, C.; Chambers, J. G.
Date, M., and Motokawa, M. Spin-cluster resonance in $CoCl_2 \cdot 2H_2O$, (11) 357*b*.
Datschefski, G. Natural gas firing in a cross-fired glass melting furnace, (5) 128*b*.
Datta, B. K. See Kroener, E.
Datta, R. K. Empirical studies on the absorption and emission of the phosphor YVO_4: Eu, (4) 109*g*. Strontium magnesium orthophosphate phosphors, P (11) 345*g*.
Datta, R. K., and Roy, R. Equilibrium order-disorder in spinels, (1) 29*a*. Reinvestigation of order-disorder in gallate spinels, (6) 188*h*. Synthesis of cubic nickel orthosilicate, (1) 33*b*.
Dau, G. J., and Davis, M. V. Gamma-induced electrical conductivity in alumina, (3) 81*g*.
Daubert, D. B. Press refinements for critical compacting requirements, (3) 74*i*.
Daudans, J. See Sevin, A.
Daughenbaugh, G. A. See Hench, L. L.
Dauknys, V. See Pranckevicius, G.
Daunt, J. G. See Kreitman, M. M.
Dautreppe, D., Chamberod, A., Chambron, W., Hivert, V., Minier-Cassayre, C., Moser, P., Pauleve, J., Peretto, P., Verdone, J., and Vigier, P. Defect studies in irradiated ferromagnetic metals or alloys, B (10) 329*e*.
Dauvergne, J. P. Homogeneous condensation of high melting oxide vapors in a plasma jet close to a cold surface, (7) 218*e*.
Dauvergne, J. P., and Le Goff, P. Simultaneous transfer of heat and material between a plasma and a cooled surface, (7) 221*h*.
Davenport, T. Pottery of Lucie Rie, (2) 35*j*.
Davidge, R. W., and Clarke, F. J. P. Resistance of ceramics to thermal and mechanical shock, (6) 188*j*.
Davidge, R. W., and Tappin, G. Thermal shock and fracture in ceramics, (2) 55*g*.
Davidovich, Ya. G. See Fialkov, A. S.
Davidse, P. D., and Maissel, L. I. Apparatus for cathode sputtering including a shielded rf electrode, P (5) 140*a*.
Davidson, D. F. See Lansche, A. M.
Davidson, J. A. C. Moldable refractories, (2) 45*d*. See Workman, G. M.
Davidson, J. K., and Miller, R. S. Cermet and ceramic fuel element, P (7) 204*h*.
Davidson, J. M., Gates, L. O., and Nightingale, R. E. Radiation-damage effects in borated graphite, (4) 114*f*.
Davidson, S. Wound resistors with terminal means, P (9) 275*d*.
Davies, B. Basic refractories, P (4) 97*b*. See Campbell, W. W.; Weaver, E. P.; Woodruff, R. W.
Davies, B., and Carini, G. F. Magnesite refractories, P (9) 270*e*.
Davies, C. N. Effect of a crosswind when sampling dust particles through an orifice in the base of a horizontal cylinder, (5) 145*f*.
Davies, D. B. See Carpenter, M. R.
Davies, D. B., and Matheson, A. J. Viscosity of liquids containing spherical molecules or ions, (7) 223*b*.
Davies, D. K. Examination of the electrical properties of insulators by surface charge measurement, (2) 49*i*.
Davies, E. N., et al. Discussion of "Blast furnace slag as aggregate for concrete" and "Steel in concrete with blast furnace slag aggregate," (5) 124*j*.
Davies, M. O. Transport phenomena in pure and doped magnesium oxide, (5) 159*f*.
Davies, P. H. See Hulme, K. F.
Davies, P. J., and Till, R. Stained dry cellulose peels of ancient and recent impregnated carbonate sediments, (8) 248*h*.
Davies, R. L. See Davis, C. M.
Davies, T. A., and Johnson, T. Metal-to-glass seal, P (8) 245*b*.
Davies, T. E. Psychrometry of drying ceramic materials, (6) 179*d*.
Davies, W., and Lister, R. R. Maturing of basic brick during use, (4) 96*f*.
Davis, B. C., and Singer, A. Thermocouple assembly having a deformable ferrule housing, P (7) 213*c*.
Davis, C. M., and Davies, R. L. Power bulk breakdown semiconductor devices, P (5) 142*b*.
Davis, E. E. Composite car top tile, P (7) 204*j*.
Davis, E. J. See Blau, T. N.
Davis, E. K. Dielectric glasses and capacitors employing them, P (7) 198*i*.
Davis, G. A. See Worrall, W. E.
Davis, H. M. See Jones, T. S.
Davis, H. T. See White, L. R.
Davis, J. Method of forming a nonuniform metal coating on a ceramic body using an abrasive erosion step, P (10) 310*f*.
Davis, J. L., and Greene, R. F. Interpretation of Hall effect data in PbS polycrystalline films, (6) 176*b*.
Davis, J. L., Riedl, H. R., and Schoolar, R. B. Photoconductivity in *p*-type single-crystal PbS films, (4) 114*f*.
Davis, L. A., and Gordon, R. B. Pressure dependence of dislocation mobility in alkali halide crystals, (4) 114*c*.
Davis, M., and Sowers, M. L. Semiconductive device and method of making, P (6) 178*g*.
Davis, M. V. See Dau, G. J.
Davis, W. B. See Grunig, J. K.
Davis, W. M. Apparatus for densifying powdered solids, P (7) 214*h*.
Davis Fire Brick Co. Composite car top tile, P (7) 204*j*.
Davison, J. L. Study of efflorescence in clay brick, (11) 337*d*.
Davy & United Engineering Co., Ltd. Multiple billet continuous casting mold, P (1) 13*c*.
Davydova, G. E. See Loladze, T. N.
Dawes, R. J. See Bush & Wilson, Ltd.
Dawihl, W., and Klingler, E. Applications of sintered Al_2O_3 products as wear- and corrosion-resistant material and their properties, (6) 172*h*. Sintered alumina as a wear- and heat-resisting material, (8) 239*a*.
Dawson, B. Covalent bond in diamond, (9) 280*f*. General structure factor formalism for interpreting accurate X-ray and neutron diffraction data, (9) 282*f*.
Dawson, B., Hurley, A. C., and Maslen, V. M. Anharmonic vibration in fluorite structures, (9) 279*i*.
Dawson, J. A. Structural ceramics industry in Canada, B (9) 291*g*.
Day, F., and Womeldorph, R. C. Apparatus for producing fibers from high temperature fusible material, P (9) 264*h*.
Day, P. R. See Ripple, C. D.
Day, R. E., and Parfitt, G. D. Characterization of the surface of rutile by nitrogen and water vapor adsorption, (7) 216*b*. Factors involved in adsorption at the solid/liquid interface, (4) 110*i*.
Dayal, R. R., and Glasser, F. P. Phase relations in the system CaO-Al_2O_3-Fe_2O_3, B (7) 226*c*.
Daybell, M., Overton, W. C., Jr., and Laquer, H. L. Faraday effect at low temperatures in terbium alumina silicate glass, (6) 176*g*.
Dayton, D. R., and Gates, P. E. High energy tubular incandescent lamp having heat dissipative sleeves, P (3) 72*i*.
Deal, B. E. See Snow, E. H.
Dean, H. N. Apparatus for producing multiple sheet glazing unit, P (8) 235*d*.
Dean, P. See Bell, R. J.
Dean, P. J. See Crowther, P. A.
Dean, R. M. Fire resistant wallboard, P (7) 194*e*.
Dear, W. N. See De Rycke, D. A. C.
Dearborn, E. F. See Bonner, W. A.; Van Uitert, L. G.
De Bell & Richardson, Inc. Method of applying glass-resin coupling compositions to glass strands, P (5) 130*h*.
DeBenedittis, J., and Katz, L. Complex metal oxides of the type $AM^{II}Mo^{IV}_3O_8$, (4) 106*j*.
Debras-Guedon, J. Organic matter in clay, (10) 315*d*. See Vilnat, J.
Debray, L. See Alegre, R.
Dechery, M. [Glass] pot production, (11) 338*c*.
Decker, E. L. Follow-up survey—direct-to-steel enameling, (9) 262*h*.
Decker, H., and Stoeckmann, H. Suspended-spindle gyratory crusher with means to adjust the spindle, P (1) 26*b*.
Deckker, B. E. L., and Srinivas, R. A. Effect of combustion time on the appearance of vibrating diffusion flames, (8) 249*e*.
DeConinck, R., Devreese, J., and Nagels, P. Influence of neutron irradiation on the thermoelectric power and the electrical conductivity of nearly stoichiometric single crystals of uranium dioxide, B (10) 328*j*.
Deeg, E. Mechanism of spectral absorption in glasses used for passive Q switches, B (10) 329*f*. See Baier, E.
DeFore, M. R. See Blaine, R. L.
De Forest, R. A. See Cohn, E.
Degen, M. G., and Toropov, N. A. Electron-microscope study of the formation of spherulites in silicate glasses, (8) 231*i*. Kinetics of spherulite growth in silicate glasses, (8) 232*i*.
Degtyareva, E. V. Transparent polycrystalline corundum ceramic shapes, (9) 271*b*. See Kainarskii, I. S.; Totsenko, S. B.
Degtyareva, E. V., and Kainarskii, I. S. Kinetics of sintering of corundum under pressure, (6) 180*h*.
De Hollander, W. R. Method of preparing uranium [ammonium] diuranate, P (11) 340*c*.
Deica, N. See Petri, L.
Dejong, V. W. See Franzen, H. F.
Deju, R. A., and Bhappu, R. B. Chemical interpretation of surface phenomena in silicate minerals, (7) 216*c*. Correlation between surface phenomena and flotation in silicates, (7) 214*c*.
De Keersmaecker, J. See Brichard, E.

De Keyser, W. L. Applications of infrared spectrometry to the study of ceramic material, (6) 180*c*. Solid state reactions between SiO_2, Al_2O_3, MgO, CaO, Fe_2O_3, and ZrO_2, (7) 221*b*.
De Keyser, W. L., and Wollast, R. Chemical analog method for calculating rates of reaction, B (7) 226*c*.
Dekking, H. G. G. Preparation and properties of some polymer-clay compounds, B (6) 192*a*.
Deknock, R. See DeMeester, P.
Delamarre, C. System HfO_2-CaO—comparison with the corresponding system based on ZrO_2, (9) 287*c*.
Delaney, R. A., and Puttlitz, K. J. Hygrometer and method of fabrication, P (1) 18*d*.
Delaney, R. A., and Spielberger, R. K. Semiconductor-ferroelectric dielectrics, P (5) 142*i*.
Delapalme, A. Crystallographic study of the composition $Fe_xGa_{2-x}O_3$ with polarized neutrons, (8) 252*g*.
Delaunois, C. See Van Bemst, A.
Delavignette, P. See Ruedl, E.; Spyridelis, J.
Delbecq, C. J., Ghosh, A. K., and Yuster, P. H. Electron and positive hole reactions in KCl-TlCl, B (10) 329*c*.
Delchar, T. A., Thompkins, F. C., and Ham, F. S. Chemisorption and incorporation of oxygen at a nickel surface, (9) 280*a*.
deLhery, G. P. See Gualtieri, J. G.
Delic, D., and Stojadinovic, S. Effect of storage on the hydration rate of β-$CaSO_4 \cdot {}^1/_2H_2O$, (2) 36*j*.
Delic, D., Zivanovic, B., Kostic, E., and Ristic, M. M. Kinetic characteristics of the sintering of oxides, (7) 219*b*.
DeLisle, M. See Gastel, D. G.
Dell, C. C., and Sinha, J. Experimental study of the behavior of flocculated clays in thickening, (5) 143*j*.
Dell, R. M. See Allbutt, M.; Counsell, J. F.
Dell, R. M., and Wheeler, V. J. Ignition of uranium mononitride and uranium monocarbide in oxygen, (2) 44*c*.
Della Porta, P. Gettering system for electron tubes, P (3) 72*h*.
Della Porta, P., Giorgi, T. A., and Rabusin, E. Gettering device including a getter metal and a gas releasing material, P (9) 273*b*. Process for producing within electron tubes, in particular television picture tubes, a thin metallic film capable of sorbing their residual gases, P (9) 274*g*.
Della Rose, F. S. Method of operating a blast furnace to produce pig iron and cement slag, P (7) 194*h*.
Delly, J. G. See McCrone, W. C.
Delmas, R. See Francois, B.
De Long, G. E. Method and apparatus for introducing a flocculating agent to an asbestos-cement slurry to control the thickness of the sheet used in winding to form a pipe, P (5) 135*h*.
Delord, J. F., Johnston, K. H., Coovert, R. E., Pistoulet, B., Roustand, C., and Rouzeyre, M. Correlation between electroluminescence and electron emission of thin metal-oxide-metal sandwiches, (6) 176*c*.
Demaison, R. J. Furnace wall of blocks with embedded fastening elements, P (7) 204*c*. Method for prolonging the life of refractory linings in furnaces of the Kaldo, Linz-Donawitz, De May, or basic or acid converter types, P (2) 47*c*.
Demant, J. T. See Bradbury, B. T.
Demarest, H. M., Jr., and Sieger, J. S. Glass prepolishing method and apparatus, P (2) 41*a*.
Dembinski, G. W. See Sinfelt, J. H.
Dembo, V. Assessment tests for metallized ceramics, B (4) 122*c*.
Dembovskii, S. A., Vinogradova, G. Z., and Pashinkin, A. S. Crystallization of glasses in the system Se-Ge, (3) 63*i*.
Demchishin, A. V. See Bogachek, L. M.
DeMeester, P., Deknock, R., and Verstappen, G. Survey of devices to measure fuel element coolant channels, (9) 277*a*.
Deminet, C. X-ray cryostat, P (9) 266*b*.
Demishev, G. K. Internal friction and structure of glass, (10) 297*h*. See Grinevetskaya, S. N.
Demonis, I. M., and Kalliga, G. P. Influence of the degree of purity of ZrO_2 and the stabilization method on some properties of zirconium ceramics, (7) 202*c*.
Denisenko, O. N. See Botvinkin, O. K.
Denner, W. H. Trace elements in quartz as indicators of provenance, (4) 118*b*.
Dennison, T. Technical trends in the steel industry and their impact on the refractories industry, (2) 46*g*.
Denny, P. J., and Roy, R. Cation exchange between mixtures of clay minerals and between a zeolite and a clay mineral, B (6) 192*g*.
Denson, C. D., Christiansen, E. B., and Salt, D. L. Particle migration in shear fields, (10) 324*h*.
Dentists' Supply Co. of New York. Method of chemically bonding dental porcelain to synthetic resin base materials and resulting prosthetic appliance, P (5) 137*c*.
De Oliveira, L. R. Adjustable keystone assembly of molded refractory material for arches, walls, and the like, P (11) 339*g*.
De Paolis, P. F., and Mauer, P. B. Silicate based laser glass, P (8) 236*b*.
Dereich, J. E. Epoxy resin ink for printing on glass, P (9) 265*b*.
Deren, J., and Ziolkowski, J. Thermoelectric power and electrical conductivity of NiO doped with lithium, (7) 222*i*.
Dermatis, S. N. Apparatus for producing dendrites, P (1) 17*i*.
Derolf, M. R. See Weldes, H. H. W.
Dersin, H. See Sirtl, E.
DeRudder, R. D., and Beck, C. W. Stevensite and talc—hydrothermal alteration products of wollastonite, B (5) 160*f*.
De Rycke, D. A. C., and Dear, W. N. Manufacture of oxides of Ti, Zr, Fe, Al, and Si, P (4) 105*c*.
Desai, C. C. See Patel, A. R.
Deschamps, P. See Rouberol, J. M.
Deschanvres, A., and Desgardin, G. Ternary hydrides in the system Zr-Ag, (8) 257*i*.
Desgardin, G. See Deschanvres, A.
Deshmukh, K. G. See Bhide, V. G.
Deshpande, V. V., and Rao, K. R. Phase studies in the system ZrO_2-TiO_2, (6) 187*g*.
Design, Inc. Interferometric spectrometer utilizing three Fabry-Perot etalons in series, P (6) 181*c*.
Desjardins, M., and Williams, J. P. Comparison of surface and bulk glass compositions with the spark source mass spectrometer, (6) 166*i*.
Desmond, T. J., Greenberg, L. S., and Weisberg, H. Method of decreasing the minority carrier lifetime by diffusion, P (3) 73*c*.
Destura, A. E. Match plate plaster of Paris for machine molding, (8) 238*c*.
Desvignes, F. See Beauzee, C.
DeTemple, T. A. See Geller, M.
Deters, P. C. Drainage tile, P (11) 337*a*.
Detrick, M. H., Co. Panelized furnace roof, P (7) 213*j*. Refractory lining for conical portion of a furnace and brick therefor, P (2) 48*c*. Refractory lining structure for a rotary kiln, P (4) 97*h*.
Dettloff, B. B. See McMaster, R. C.
Detweiler, R. M., and Kulp, B. A. Annealing of radiation damage in ZnSe, (11) 350*i*.
D'Eustachio, D., Ford, W. D., and Johnson, H. E. Cellular glass nodules and method of making them, P (3) 65*d*.
Deutsch, L. See Geld, I.
Deutsche Akademie der Wissenschaften zu Berlin. Process for the purification of materials in single crystal production, P (9) 274*g*.
Deutsche Edelstahlwerk Akt.-Ges. and Allgemeine Elektrizitaets-Ges. Fluid-cooled ferrite core, P (7) 208*h*.
Deutsche Erdoel Akt.-Ges. Process for the hydrolysis of aluminum alkoxides, P (11) 349*f*.
Deutsche Gold- und Silber-Scheideanstalt vorm. Roessler. Process for changing the properties of finely divided silica, P (7) 215*d*. Process for the decomposition of zircon sand, P (9) 279*a*. Process for producing silica in the form of hollow spheres, P (8) 251*f*. Process for the production of hydrides of Ti, Zr, and Th, P (8) 241*a*. Process for the production of a mixture of zirconium oxide and silica, P (1) 25*j*. Production of hydrides of alkaline earth metals and lithium, P (5) 149*b*.
Deutscher, J. S. See Floyd, J. R.
Devall, K. L. See Bracht, L. J.
DeVany, A. S. Instrument for measuring strain and homogeneity in glass; supplement, (5) 127*h*.
DeVoe, J. R., and Spijkerman, J. J. Moessbauer spectrometry, (10) 315*b*.
Devor, D. P. See Robinson, M.
Devreese, J. See DeConinck, R.
DeVries, R. C. Stability of CrO_2 at high pressures and temperatures in the "belt" apparatus, (4) 116*e*. See Rodbell, D. S.; Sears, G. W.
DeVries, R. C., and Jugle, D. B. Structure-property relation in flexible sandstone, (8) 257*g*.
DeVries, R. C., and Roth, W. L. High-pressure synthesis of $PbCrO_3$, (3) 81*b*; correction, (6) 186*b*.
Dewerdt, F. Ion-exchange resins, (6) 180*h*.
Dexco Corp. Method of making a tool for removing material from workpieces and product thereof, P (7) 193*g*.
Dgebuadze, T. P., and Mazurin, O. V. Determination of the nature of the chemical heterogeneity of borosilicate glasses by means of dielectric losses, (8) 231*e*.
Dhaka, V. A., and Wajda, E. S. Method of shaping pn junction profiles, P (3) 73*f*.
Diadur Aktiebolag. Cutting insert for chip cutting machining and means for manufacturing, P (5) 123*i*.
Diamond, J. J. See Dragoo, A. L.
Diamond, J. J., and Dragoo, A. L. Studies of molten alumina in the arc-image furnace, (1) 32*i*.
Diamond, S., White, J. L., and Dolch, W. L. Transformation of clay minerals by calcium hydroxide attack, B (6) 192*b*.
Diamond Alkali Co. Method of preparing calcium carbonate, P (1) 25*d*.
Dichter, J. Machine for reshaping the neck portion of small glass bottles with lubricating means, P (1) 9*g*.
Dick, B. G. Lattice distortions and field gradients in alkali halide solid solutions, (10) 322*c*.
Dickens, B. Bondings in Ag_2PbO_2 and $Ag_4Pb_2O_5$, (4) 106*j*. See Soederquist, R.
Dickens, P. G. See Crane, P. J.
Dickens, P. G., and Halstead, T. K. Oxygen chemisorption on doped nickel oxide and related conductivity changes, (3) 84*c*.
Dickeson, J. E. See Kinson, K.
Dickinson, G. A. See Pilkington, D. F.
Dickinson, G. A., and Cook, T. S. Pressure rollers for glass ribbon polishing machine, P (6) 171*c*.
Dickson, E. J. Kiln designing advances using characteristics of insulating refractories, (1) 24*d*.
Dickson, R. W., and Anderson, R. C. Temperature dependence of the elastic moduli of $91Y_2O_3 + 9ThO_2$ from 25° to 1100°C, (5) 159*c*.
DiCristina, V. See Bishop, W. M.
Didier-Werke Akt.-Ges. Apparatus for operating a burner fired shaft furnace, P (6) 182*b*. Device for installing or replacing the lining of rotary kilns, P (8) 249*c*.
Didkovskaya, O. S. See Klimov, V. V.
Diehl, D. S. Four layer planar semiconductor switch and method of making, P (9) 273*b*.
Diehl, J. M. See Fielder, W. S.
Dienes, G. J. Influence of radiation on metallurgical processes, B (10) 329*d*.
Dienes, G. J., Hatcher, R. D., Smoluchowski, R., and Wilson, W. Minimum-energy configuration of Li^+ in KCl, (10) 323*a*.
Dieterle, H. See Maltner, W.
Dietert, H. W. Granular material conditioning apparatus, P (6) 174*b*.
Dietert, H. W., and Steinmueller, R. E. Granular material testing apparatus, P (3) 76*f*.
Dietert, Harry W., Co. See Harry W. Dietert Co.
Dietz, E. D., and Florence, J. M. Glass and ceramic periodic table, (2) 39*i*.
Dietz, R. E., Guggenheim, H. J., and Johnson, L. F. Divalent metal doped fluorides as optical maser material, P (8) 244*j*.
Dietz, R. E., Misetich, A. A., and Guggenheim, H. J. Effect of uniaxial stress on magnon sidebands in MnF_2, (11) 352*e*.
Dietz, W. See Roeder, M.
Dietzel, A. Measurement of plasticity, (9) 276*c*. See Brueckner, R.; Upadhyaya, V. G.
Dietzsch, H. J. See Cremer, G.
Dijken, R. H., Jager, J., Krikke, M., and Kraus, J. Apparatus for manufacturing rings or cylinders of ferromagnetic material, P (5) 140*b*.
Dijkmeijer, H. E., Kuijpers, M. H., and Veenemans, B. Base construction for evacuated envelope housing a printed circuit and components, P (4) 99*d*.
Dilger, L. Nickel oxide capacitors, P (2) 51*j*.
Dill, F. H., Jr. Crystalline injection laser device manufacture, P (1) 17*c*. Transistor structure with an emitter region epitaxially grown over the base region, P (11) 345*c*.
Dill, H. G. Metal-oxide-semiconductor field effect transistor, P (1) 18*i*.
Dill, H. G., and Pizzarello, F. A. Production of thin films of cadmium sulfide, telluride, or selenide, P (4) 101*c*.
DiMarcello, F. V., Treptow, A. W., and Baker, L. A. Glaze for ceramic substrates for thin films, (6) 176*j*.
Dimelow, J. Firing of sanitary ware, (5) 136*j*.
Dimmock, J. O. See Phelan, R. J., Jr.
Dimock, J. D. See Christy, R. W.
Dinet, A. See Bril, J.
Dingle, H. E. Reactivity of barium carbonate in combating scumming in structural clay products—correction, (1) 10*c*.
Dingus, G. W. Cyclonic apparatus, P (5) 144*g*.
Dingwall, A. G. F. Low resistance bonds to germanium-silicon bodies and method of making, P (1) 18*g*.
Dingwall, A. G. F., and Horsting, C. W. Thermoelectric generator including silicon germanium alloy thermoelements, P (1) 19*b*.
Dinh, C. D., and Bertaut, E. F. Atomic parameters of $BaAl_2O_4$ and studies of the solid solutions $BaFe_xAl_{2-x}O_4$ and $BaGa_xAl_{2-x}O_4$, (7) 215*j*.
Dinnin, J. I. Atomic fluorescence flame spectrometric detection of Pd, Ti, Zr, Cr, and Al using a hot hollow cathode lamp, (5) 144*j*.
Dinsdale, A. Constitution of bone china, B (7) 226*f*.
Dinsdale, A., Camm, J., and Wilkinson, W. T. Mechanical strength of ceramic tableware, (2) 48*g*.
Di Piazza, G. C. Ferrite phase shifter having longitudinal and circular magnetic fields applied to the ferrite, P (8) 244*c*.
Di Pietro, C. Electroluminescent display panel with rodlike electrodes embedded in phosphor, P (8) 244*b*.
Disegna, W. L., and Erickson, H. Catalyst containing silica-alumina and finely divided CaF_2, MgF_2, SrF_2, AlF_3, or InF_3, P (4) 104*i*.
Dismukes, J. P. See White, J. G.
Distillers Co., Ltd. Activation of antimony oxide-tin oxide catalysts using water, acid, or base, P (1) 25*h*.
Ditrick, N. H. Semiconductor devices, P (5) 142*h*.
Dittrich, F. J. Carbide flame spray material, P (11) 340*b*.
Dixon, E. O., and Simpson, G. R. End pumped laser structures employing immersion optics, P (8) 244*b*.
Dixon, J. B. Quantitative analysis of kaolinite and gibbsite in soils by differential thermal and selective dissolution methods, B (8) 259*j*. See Bryant, J. P.
Dixon, K. Basic metal preparation, (9) 262*g*.
Dixon, R. W. Acoustic nonlinear frequency mixing detected using optical Bragg diffraction, (11) 350*c*.
Dixon, R. W., and Matthews, H. Diffraction of light by elastic waves in YIG, (4) 108*a*.
Dixon, W. D. See Kindlesparker, J. H.
Djabarov, N. B. Significance of the cement composition for the CO_2 treatment of cellular concrete, (10) 295*g*.
Dmitruk, M. V. See Voron'ko, Yu. K.

Doane, J. W., and Hultsch, R. A. Nuclear-spin pumping study of relaxation and defects in sodium bromate, (9) 284*j*.

Dobos, S. See Boksay, Z.

Dobrov, W. I. Paramagnetic acoustic resonance and relaxation of rare earths in CaF_2, (11) 355*f*.

Dobrovol'skii, A. G. Slip Casting, B (10) 329*j*.

Dobrovol'skii, A. G., Dobrovol'skii, G. G., Lyudvinskaya, T. A., and Popichenko, E. Ya. Slip casting of zirconium boride, (2) 46*d*.

Dobrovol'skii, A. G., and Popichenko, E. Ya. Slip casting of titanium carbide components, (2) 46*b*.

Dobrovol'skii, G. G. See Dobrovol'skii, A. G.

Docci, E. Observations on Yugoslav ceramics, (8) 228*a*.

Dock, N., and Erlesand, L. Wet separator with venturi-shaped gas channels, P (1) 20*f*.

Dockery, S. M. Refractory housing, P (10) 305*c*.

Dodd, C. V. Applications of a phase sensitive eddy current instrument, (7) 211*i*.

Dodd, D. M. Computer processing of data in production of glass containers, (7) 195*j*.

Dodd, D. M., and Fraser, D. B. Infrared studies of the variation of H-bonded OH in synthetic α-quartz, (5) 153*f*.

Dodds, R. K. Calculation of the average ground-stress components from measurements of the diametral deformation of a drill hole, B (3) 90*i*. Measurement and analysis of rock physical properties on the Dez project, Iran, B (3) 90*i*.

Dode, M. See Heiss, A.

Dodson, V. H., and Farkas, E. Concrete mix with set retarding admixture, P (2) 37*e*.

Doell, W. See Loh, E.

Doerbecker, K., and Oel, H. J. Optical properties of ceramic glazes (I), (10) 306*a*.

Doerr, R. M. See George, L. C.

Doerr, R. M., Neumeier, L. A., and Jensen, J. W. Reaction of tungsten-cobalt alloys with oxygen at 1000° and 1100°K, (2) 45*i*.

Doerre, E. See Klingler, E. A.

Doetzer, R. Method and apparatus for producing a semiconducting compound of two or more components, P (1) 18*i*.

Dohm, K. D. See Schwiete, H. E.

Doi, H. See Mikami, Y.

Doi, K. See Livage, J.

Dolby, P. See Kelly, B. T.

Dolch, W. L. See Diamond, S.

Dolf, H. R. Method of forming glass beads in a molten metal bath, P (3) 65*e*.

Dolmatov, Yu. D. See Salin, A. A.

Dolomanov, L. A., Ponomarev, N. M., Rakhshtadt, Yu. A., and Sinitsyn, B. V. Exposing the dislocations in single crystals of lanthanum fluoride, (10) 321*d*.

Dolton, T. A. See Schneider, P. F.

Domagala, R. F. See Ruh, R.

Domalski, E. S., and Armstrong, G. T. Heat of formation of boron carbide, (9) 282*j*. Heats of formation of aluminum diboride and α-aluminum dodecaboride, (4) 111*c*.

Doman, R. C. See Alper, A. M.

Dombrovskaya, N. S., Khakhlova, N. V., Posypaiko, V. I., Mikhailova, N. D., Alekseeva, E. A., and Bespalov, I. G. Application of electronic computing machines for computing tables of indices of multicomponent systems, (1) 26*g*.

Domicone, J. J., and Ott, P. L. Method of preoxidation of stainless steel, P (6) 178*j*.

Domicone, J. J., and Rittler, H. L. Method of protecting the surfaces of glass molding equipment, P (7) 190*d*.

Domicone, J. J., and Smith, W. C. Method for producing light-diffusing coatings of titania on glass, P (2) 41*i*.

Dominey, D. A., Morley, H., and Young, D. A. Oxidation of uranium dioxide by carbon dioxide in a reactor flux, (3) 84*j*.

Domingo, G., Itoga, R. S., and Kannewurf, C. R. Fundamental optical absorption in SnS_2 and SnSe, (9) 282*e*.

Dominion Engineering Works, Ltd. Automatic high pressure lubrication system for rotary grinding mills, P (7) 211*a*. Structure for large diameter grinding mill, P (11) 346*a*.

Dominion Magnesium, Ltd. Magnesium alloy drill rod assembly with ceramic coated coupling member, P (4) 93*c*.

Domotor, L. Thermionic emissive cathode, P (5) 143*d*.

Donaho, R. M., Jr. Loading apparatus for bulk transport systems, P (4) 105*d*.

Donald, D. K. See Cole, T.

Donald, R. G. Diffused resistor for an integrated circuit, P (9) 272*f*.

Donaldson, A. D. See Gardner, N. R.

Donath, F. A. Triaxial pressure apparatus for testing consolidated or unconsolidated materials subjected to pore pressure, B (3) 90*i*.

Donnelly, T. W. Kinetic considerations in the genesis of growth twinning, (5) 154*d*.

Donohue, P. C., Katz, L., and Ward, R. Modification of structures of ternary oxides by cation substitution (I) substitution of Sr for Ba in barium ruthenium oxide and in barium iridium oxide, (5) 155*d*; (II) substitution of various cations for ruthenium in barium ruthenium oxide, (5) 155*d*.

Donovan, E. P. Structures for semiconductor integrated circuits and methods of forming them, P (1) 19*e*.

Donskoi, A. V., Dresvin, S. V., Voronin, K. K., and Volynets, F. K. Some features of the growth processes of refractory crystals in high frequency plasma torches, (5) 146*a*.

Donzel, A. See Dupont, H.

Doo, V. Y. Process of making planar semiconductor devices isolated by encapsulating oxide filled channels, P (9) 274*f*.

Doorn, C. Z. van, and Koch, G. Abnormal green edge emission in CdS, (11) 350*c*.

Doppioni, F. Firing enameled copper, (8) 229*g*. Transparency in copper enamels, (8) 229*g*.

Dorairaj, G. See Narayanan, V. H.

Doran, D. G. Shock-wave compression of barium titanate and 95/5 lead zirconate titanate, (9) 286*b*.

Dore, B. V., Geppert, D. V., Muller, R. S., and Spicer, W. E. Electron emission from metal-BaO systems, (2) 49*h*.

D'Oria, F. J. See Geld, I.

Dorion, G. H. See Chopoorian, J. A.

Dorm, E., and Marinder, B. O. Thortveitite-type structure of $Mn_2V_2O_7$, (5) 159*f*.

Dorman, E. L. See Claps, W. A.

Dorman, W. H. Variable intensity lamp, P (7) 199*e*.

Dornelas, W., and Lacombe, P. Electric field diffusion of oxygen at 900° to 1000°C in UO_2, (9) 281*i*.

Dornfeld, J. E. Mica capacitor, P (4) 100*h*. Mica disk capacitor, P (11) 344*g*.

Dorr-Oliver, Inc. Agglomerative drying, P (10) 312*a*. Traveling belt type drum filter, P (3) 75*c*.

Dorstener Eisengiesserei und Maschinenfabrik AG. Brick manufacturing apparatus, P (2) 43*b*.

Dosch, W. Interlamellar reactions of tetracalcium aluminate hydrates with water and organic compounds, B (9) 289*e*.

Dosch, W., and Strassen, H. zur. Alkali-containing calcium aluminate sulfate hydrate, (3) 62*a*.

Doss, K. S. See Narayanan, V. H.

Dostrup, M. Silo plant, P (2) 53*g*.

Douady, P. See Solomir, J. G.

Dougill, J. W. Mathematical model for the failure of cement paste and mortars, (8) 228*g*.

Douglas, D. A. See Olsen, A. R.

Douglas, F. C. Reply to "Analysis of high-purity synthetic vitreous silicas," (3) 63*e*. See Galasso, F. S.

Douglas, R. W. Spectroscopy of glasses, B (10) 329*f*. Structure of simple silicate and borate glasses, (6) 169*a*. See Das, C. R.; McCurrie, R. A.; Paul, A.

Douglas, T. B. Calculated heats of dilute solid solution among the alkali halides other than cesium salts, (10) 319*e*.

Douglas Aircraft Co., Inc. Glass filament tape, P (10) 300*a*.

Douglass, D. L., and Landuyt, J. van. Structure and morphology of oxide films during the initial stages of titanium oxidation, (10) 325*d*.

Douillard, P. A., Jones, R. W., Cunningham, R. A., and Lucek, J. R. Centrifugally cast hollow glass body, P (7) 198*d*.

Douillet, P. See Nicolas, J.

Doulton & Co., Ltd. Ceramic compositions, P (2) 56*e*. Ceramic compositions and the formation of cores and molds from them, P (5) 134*g*. Electrical insulator having improved surface electrical stress distribution, P (5) 137*d*.

Douma, G. H. Shortening of fat clays with calcined clay or sand—influence on firing behavior and on properties of the unfired and fired products, (11) 337*c*.

Dow Chemical Co. Electroless plating on nonconducting surfaces, P (5) 141*d*. Electroluminescent cells, P (4) 99*i*. Graphite metal body composite, P (8) 240*f*. Gypsum product and method of making, P (5) 125*d*. Method of preparing composite pigments, P (7) 214*h*. Method of preparing manganese dioxide, P (3) 78*c*. Method of producing hydrogen fluoride and solubilized beryllium, P (7) 214*i*. Preparation of anhydrous sodium metasilicate, P (5) 148*g*. Preparation of sodium metasilicate pentahydrate, P (9) 279*f*. Preparation of sodium trisilicate, P (3) 78*a*. Process of cleaning porcelain surfaces, P (8) 229*j*. Process for preparing low density graphite structures, P (9) 270*c*. Process for producing compressed vermicular graphite structures, P (9) 270*d*. Production of magnesium hydroxide, P (5) 149*c*. Resin bonded magnesium oxychloride cement composition, P (1) 3*c*. Vermicular graphite structures and process of making, P (9) 270*e*.

Dow Corning Corp. Bonding of organic resins or rubbers to inorganic substances, P (11) 335*g*. Bonding of organic resins to siliceous materials, P (11) 335*h*. Compositions and methods for production of colored glass fibers, P (9) 264*j*. Deposition chamber for manufacture of refractory coated filaments, P (5) 134*h*. Method of etching silicon carbide, P (11) 344*h*. Method of making semiconductor circuits, P (11) 344*a*. Process for post-finishing pigmented glass fabric, P (11) 336*g*. Semiconductor integrated circuits and method of making, P (11) 345*f*. Silicon carbide glass fiber [drawing] bushing and method of making, P (2) 42*e*.

Dowdy, R. H., and Mortland, M. M. Alcohol-water interactions on montmorillonite surfaces (I) ethanol, B (9) 289*e*.

Doyle, W. M., and White, M. B. Generation of combination tones by the interaction of orthogonal oscillations in a gas laser, (5) 138*d*.

Draeger, W. See Schwiete, H. E.

Draftz, R. G. See McCrone, W. C.

Dragoman, I. See Petri, L.

Dragoo, A. L. Diffusion rates in inorganic nuclear materials, (9) 280*h*. See Diamond, J. J.

Dragoo, A. L., and Diamond, J. J. Transitions in vapor-deposited alumina from 300° to 1200°C, (1) 33*b*.

Drakenfeld, B. F., & Co., Inc. Mat surface vitreous enamels and articles made therefrom, P (8) 229*i*.

Draker, H. C. Ceramic stains in fast fire glazes, (9) 270*i*.

Draley, J. E. See Bradhurst, D. H.

Dransfeld, K. See Arzt, R. M.

Dregoi, I., Butt, Yu. M., and Vorob'eva, M. A. Conditions for the crystallization of magnesium oxide in fused calcium aluminates, (6) 164*d*.

Drennen, T. J., and Kelley, L. E. Treatment of siliceous fibers with aqueous mixtures of unsaturated polyimidazoline anchoring agents and resulting article, P (7) 199*d*.

Dresia, H., Fischotter, P., and Bessing, R. Moisture content measurement [apparatus] having neutron reflecting material to provide optimum counting range, P (2) 55*f*.

Dresser Industries, Inc. Electric furnace roof construction, P (5) 134*j*. High alumina castable, P (11) 340*d*. Ladle starter shape, P (10) 304*f*. Magnesite refractories, P (9) 270*e*. Method of making a shell mold, P (11) 340*a*.

Dresvin, S. V. See Donskoi, A. V.

Drexel Institute of Technology. Method of producing oriented graphite, P (1) 13*h*.

Dreyfus, B. A. Manufacturing thin monocrystalline layers, P (8) 244*j*.

Dreyfus, R. W. See Bron, W. E.

Drickamer, H. G. See Clendenen, R. L.; Coston, C. J.; Hart, H. V.; Lewis, G. K., Jr.; Lynch, R. W.; Perez-Albuerne, E. A.

Driel, G. A. H. van, Esveldt, C. J., and Joosten, J. E. Lithium nickel ferrite magnetic switching element, P (7) 209*b*.

Driessens, F. C. M., and Rieck, G. D. Phase equilibria in the system Zn-Mn-O in air, (4) 114*a*.

Dringham, M. R. See Stakebake, J. L.

Driscoll, T. J., Jr., and Norman, L. D., Jr. Thermoelectric properties of yttrium-group V and yttrium-group VI binary and ternary compounds, (2) 50*j*.

Drobnic, M., and Kolar, D. Calorimetric determination of the enthalpy of hydration of UO_3, (4) 106*j*.

Drobot, D. V. See Korshunov, B. G.

Drobot, D. V., Anikina, G. P., Durinina, L. V., and Korshunov, B. G. Phase diagram of the system YCl$_3$-CsCl, (3) 84*g*.

Drosdziok, H. See Ziehr, G.

Drost, W. Zeolite A bodies and their preparation, P (11) 350*a*.

Drost, W., and O'Connor, F. M. Wet attrition-resistant molecular sieve bodies and their manufacture, P (8) 252*a*.

Droste, J. B. Clay mineral formation in mud pots, Yellowstone Park, Wyoming, B (9) 289*i*.

Drowart, J. See Verhaegen, G.

Drozdovskii, B. A., Prokhodtseva, L. V., and Friźman, Ya. B. Methods for evaluating the cracking tendency [of solids], (10) 314*h*.

Druilhe, R. See Villers, G.

Drum, E. W. Electrostatic coating methods and apparatus for conductive coating materials, P (8) 247*c*.

Drumm, W. M. Precision camera for microphotography, (5) 146*a*.

Dry, M. E., and Ferreira, L. C. Structural promotion of reduced magnetite, (3) 87*d*.

Dryburgh, P. M. Glove box and drying system for the manipulation of moisture sensitive materials, (4) 102*g*.

DuBois, F. J. Method of preparing slurries of siliceous pigment, P (7) 214*i*.

DuBose, C. K. H., and Stiegler, J. O. Controlled jet polishing of specimens for transmission electron microscopy, (1) 20*h*.

Dubovik, T. V. See Burykina, A. L.

Dubovik, T. V., and Dubovik, V. N. Dielectric properties of some glasses within the range 20° to 600°C, (9) 263*h*.

Dubovik, V. N. See Dubovik, T. V.

Dubrovo, S. K., and Shnypikov, A. D. Certain properties of glasses in the Na_2O-La_2O_3-SiO_2 system, (8) 230*h*.

Dubrovskaya, L. B., and Matveenko, I. I. Magnetic properties of cubic tantalum carbide, (9) 284*e*.

Dubuisson, J., and Basseville, P. Reduction of barium titanate and its effect on electrical properties, (6) 176*h*.

Duckwall, F. E. See Calkins, T. H.

Duckworth, W. H. See Lynch, J. F.; Sheets, H. D.

Ducote, H. J. See Kelly, A. C.

Dudek, J. A. See Mellen, E. J., Jr.

Duderov, I. G. Determination of the relative increase in the number of microcracks in ceramic materials from changes in thermal conductivity, (10) 314*a*.

Duderov, Yu. G. See Budnikov, P. P.

Dudkowski, S. J., Kepka, A. G., and Grossweiner, L. I. Spectral sensitization of ZnO thin films with organic dyes, (3) 72*e*.

Dudley, R. W. Getting the most from your compressed air system, (2) 53*b*.

Dudzik, C. J., and Perkins, G. E. Method and apparatus for processing glass yarn, P (2) 41*h*.

Dueker, G. W., Kellington, C. M., Katzmann, M., and Atwood, J. G. Optical properties and laser thresholds of 39 ruby laser crystals, (5) 139*d*.
Dueker, J. E. Optical fiber electroluminescent-photoconductive image intensifier, P (5) 142*j*.
Duff, G. M. S. See Wilson, H. N.
Duffaut, F. See Beranger, G.
Duffek, E. F. See Benjamini, E.
Duffy, J. A., and Ingram, M. D. Environment of cobalt(II) in nitrate glass, (10) 297*d*.
Dufour, C. See Biet, J. P.
Dugger, C. O. Growth of pink magnesium aluminate ($MgAl_2O_4$) single crystals, (11) 353*i*.
Duhart, P. A. See Jamey, M. A.
Duke, B. W., and Marshall, C. W. Coated abrasives for electrolytic grinding, P (7) 193*h*.
Duke, C. B., and Alferieff, M. E. Solvable model of a hydrogenic system in a strong electric field—application to optical absorption in semiconductors, (10) 325*a*.
Duke, D. A., Megles, J. E., MacDowell, J. F., and Bopp, H. F. Strengthening glass-ceramics by application of compressive glazes, (3) 64*e*.
Duke, J. B. Method for improving the brightness of clay, P (3) 78*b*. See Jacobs, D. A.
Dulat, J. Sodium calcium metaborate, P (10) 318*h*.
Dumez, P., Provost, G., and Lecrivain, L. Measurement of thermal conductivity by the cylinder method, (6) 180*h*.
Dumitrescu, R. See Dumitrescu, T.
Dumitrescu, T., Catana, V., Dumitrescu, R., and Popescu, V. Radiometric and autoradiographic methods for determining the optimal homogenization time for refractory raw material mixture in the Eirich mixer, (9) 268*d*.
Dumont, G. C. See Schechter, M.
Dunbar, R. B. See Williams, S. E.
Duncan, J. F. See Robinson, G. C.
Duncan, J. H. Technical ceramics and the optical microscope, (10) 315*h*.
Duncan, J. H., and Creyke, W. E. C. Factors affecting the distortion of high-alumina ceramics during high-temperature metallizing, B (4) 122*d*.
Duncumb, P. Electron probe microanalysis, (5) 145*h*. Electron probe microanalysis with specific X-ray spectrometer structure, P (5) 147*b*.
Dunegan, H. L. High temperature dynamic modulus measurements by use of ultrasonics, (7) 212*h*.
Dungan, R. H. Thermodynamic relations between composition and ferroelectric-to-antiferroelectric phase transitions, (11) 343*b*.
Dunn, J. P. Seam finishing, P (2) 42*b*.
Dunn, S. A. Viscous behavior of silica with tungsten inclusions, (7) 204*c*.
Dunseth, M. G. Continuous multistep process for preparing granular zinc ammonium phosphate, P (8) 250*i*.
Dunsmore, J. M. See Hofmann, J. J.
Dunsmore, J. M., and Reimschussel, H. C. Locator device, P (6) 170*j*.
Dunster, D. F. T. Nickel-gold contacts for semiconductors, P (4) 100*i*.
Dunton, G. R., III, and Green, L. Q. Process for rendering glass scratch resistant by decomposition of a titanium ester chelate, P (9) 265*j*.
Duperroy, M. See Brichard, E.; Plumat, E.
Dupnock, A. See Schumann, P. A., Jr.
Dupont, A. See Brichard, E.
Dupont, H., Donzel, A., and Ernest, J. Laser-induced breakdown and fracture in glasses, (6) 167*g*.
Du Pont de Nemours, E. I., & Co. Alkali compensated rare earth doped zinc or cadmium borate phosphors, P (7) 208*e*. Alumina-zircon ceramic coatings and bodies, P (8) 240*a*. Capacitor and method of making, P (10) 309*g*. Color stabilized mica, P (6) 182*j*. Composite superconducting structures, P (8) 244*g*. Diamond purification, P (2) 35*h*. Ferromagnetic metal oxyfluorides, P (5) 141*h*. Fibrous niobium carbide and nitride, P (4) 97*e*. Germanium selenides and processes for their production, P (7) 208*i*. Gold-palladium conductor compositions and conductors made therefrom, P (1) 17*j*. Microcrystalline corundum powder, sols thereof, and processes for preparing both, P (5) 135*d*. Multicrystalline diamond abrasive composition and article, P (8) 227*g*. $PbTi_3O_7$ and process for its manufacture, P (4) 105*b*. Preparation of aluminum and chromium sesquioxide fibers, P (10) 304*i*. Preparation of brittle inorganic polycrystalline powders by shock-wave techniques, P (5) 148*h*. Process for improving the catalytic properties of lead titanate, P (4) 105*c*. Process for joining glass-lined metal conduits, P (4) 95*b*. Process for rendering glass scratch resistant by decomposition of a titanium ester chelate, P (9) 265*j*. Safety glass, P (1) 10*d*. Silica-coated lead chromate pigment, P (6) 183*d*. Silver compositions containing vitreous binders and a vehicle, P (2) 42*c*. Single-phase solid solution luminescent compositions, preparation thereof, and lasers containing same, P (7) 210*i*. Ternary copper, zinc, cadmium, and manganese dichalcogenides having the pyrite-type crystal structure, P (6) 178*h*. Thermal gravimetric analyzer, P (6) 181*g*. Thermally stable fibrous alkali metal titanates, P (8) 246*d*. Thermoelectric modules, P (4) 101*e*. Vacancy compensated calcium neodymium vanadate phosphors, P (6) 178*j*.
Dupuis, M. General theoretical ideas on the constitution of the atom and the structure of solids, (3) 81*h*.
Dupuy, C. H. S. Study of the electric charge appearing during plastic deformation of ionic crystals, particularly lithium fluoride, (7) 222*g*.
Dupuy, E. See Cerles, G.
Durinck, R. Tire fastening for a rotary shell, P (8) 249*j*.
Durinina, L. V. See Drobot, D. V.
Durney, L. J. Vacuum metallizing—a quick bright metallic coating, (5) 144*b*.
Dusollier, G., and Robredo, J. Differential thermal analysis in the study of changes in glass composition, (11) 333*e*.
Dutta, R., and Banerjee, S. K. Adsorption behavior of hydrous beryllium oxide in media of varying pH, (7) 215*h*.
Dvorak, V., and Glogar, P. Influence of impurities on the Curie temperature of ferroelectric crystals, (9) 283*b*.
Dvorina, L. A. See Samsonov, G. V.
Dvorina, L. A., and Verkhoglyadova, T. S. Vacuum-thermal production of the silicides of the rare-earth metals, (9) 288*b*.
Dwight, K. See Menyuk, N.
Dwornik, E. J. See Altschuler, Z. S.
Dwyer, F. B. See Thompson, R. L.
Dwyer, F. G., and Stover, W. A. Catalysts having improved thermal stability and method of preparing, P (10) 317*j*.
D'yachkov, P. N. See Khoroshavin, L. B.
Dyban, Yu. P. See Matveeva, F. A.
Dye, C. G. See Allen, E. M.
Dyer, E. T. See Koubek, F. J.
Dyer, H. B. Grind steel with diamonds, (6) 163*i*.
Dyer, H. B., and Preez, L. du. Irradiation damage in type I diamond, (3) 82*e*.
Dykoski, W. S. See Wertz, J. E.
Dyment, J. C. Hermite-Gaussian mode patterns in GaAs junction lasers, (4) 111*d*.
Dyment, J. C., and D'Asaro, L. A. Continuous operation of GaAs junction lasers on diamond heat sinks at 200° K, (11) 350*i*.
Dzhurinskii, B. F. See Tananaev, I. V.
Dziemianowicz, T. Q. Ceramic permanent magnets, (3) 70*j*.
Dzierzanowski, F. J. See Haden, W. L., Jr.

Eades, J. L. See Gaudette, H. E.
Eadie, G. P. Oil firing of glass melting furnaces, (11) 348*f*.
Eagan, R. J. See Ricker, J. M.
Eagleston, A. A. See Lockett, T. A.
Eakins, W. J. Method of applying glass-resin coupling compositions to glass strands, P (5) 130*h*. Silanol groups on silica and their reactions with trimethyl chlorosilane and trimethylsilanol, (9) 264*i*.
Eardley, R. P. Direct-reading spectrometry in ceramic analysis, B (7) 224*h*.
Eargle, D. H., Jr. Electron paramagnetic resonance, (10) 314*a*.
Early, V. H. See Hanst, P. L.
Eash, D. T. Compatibility of tungsten with molten UO_2, (4) 106*h*.
East, P. J. See Gast, R. G.
Eastman Kodak Co. Calcium fluoride optical elements and method for making, P (4) 94*e*. Magnesium fluoride optical element, P (5) 130*e*. Process for manufacturing magnetic oxide, P (2) 52*f*. Silicate based laser glass, P (8) 236*b*.
Eastwood, F. Method for forming hot top liners, P (8) 240*j*.
Eberle, C. D. Clay temperature vs. kiln loss, (2) 42*f*.
Eberle, H. Method of preparing fibers from a viscous melt, P (3) 66*a*.
Ebert, E., Immendorfer, M., and Spielmann, W. Method of epitaxially growing silicon carbide by pyrolytically decomposing SiH_4 and CH_4, P (8) 245*f*.
Ebert, E., and Spielmann, W. Method of epitaxially growing a layer of silicon carbide on a seed by pyrolytic decomposition of hydrocarbons or mixtures of silanes and hydrocarbons, P (9) 273*h*.
Ebina, A. See Nakada, R.; Takahashi, T.
Ebisuzaki, Y., Kass, W. J., and O'Keeffe, M. Quantum mass effects in diffusion, (4) 114*e*.
Eckardt, D., Mentzel, F. A., and Reinke, H. Apparatus for pulling semiconductor crystals, P (1) 17*i*.
Eckert, J. S., and Haught, G. J. Drum roller, P (6) 179*c*.
Eckert, O., and Staerk, K. Piezoelectric ceramics, (9) 272*d*.
Eckstein, B. Concept of temperature and temperature measurement in glasses, (8) 230*e*. Dielectric study of thermal aftereffect in glasses, (10) 297*h*. Vitreous states, (6) 169*h*.
Economy, J., and Anderson, R. New route to boron nitride, (5) 155*i*.
Eddy, W. H., Browning, J. S., and Hardemon, J. E. Continuous flotation of fluorspar from a calcareous Illinois ore, (1) 19*g*.
Edelman, L. I. See Khodakov, G. S.
Edelman, R. E. See Saia, A.
Edick, P. Clay mixer and extruder, P (2) 53*i*.
Edlmayr, F. See Schreiner, H.
Edmundsson, I. See Lindner, G.
Edstroem, J. O. Hot top lining, P (10) 304*e*.
Edwards, J. G. Measurement of the cross section for stimulated emission in neodymium-doped glass from the output of a free-running laser oscillator, (9) 263*g*.
Edwards, L. W. See Fuller, J. E.
Edwards, R. K. See Martin, A. E.
Edwin L. Wiegand Co. Sheathed electric heating elements, P (8) 230*a*.
Effer, D. Epitaxial growth of doped and pure GaAs in an open flow system, (4) 109*i*.
Efimenko, J. Mass spectrometric study of the BeO-BeF_2 system at high temperatures, (6) 187*c*.
Eft, N. W. Pulverizer, P (1) 26*c*.
Egan, J. J. See Behl, W. K.
EG & G, Inc. Thermoluminescent dosimetry system, P (7) 213*e*.
Eggert, H., Schatz, R., and Schillmann, E. Method for producing a selenium rectifier having a high blocking voltage, P (5) 142*f*.
Eggleton, R. A., and Bailey, S. W. Crystal structure of stilpnomelane (I) the subcell, B (7) 224*b*.
Eglit, B. Snow ski with porcelain [enamel] running surface, P (11) 333*c*.
Egorov, B. D. Procedure for determining quality of sheet glass from optical distortions, (11) 334*e*.
Egorova, L. S. See Kitaigorodskii, I. I.
Eguchi, K., Tasaka, K., and Tarumi, S. Production and application of high silica glasses (I) relation between heat treatment and acid leaching of borosilicate glasses, (1) 7*a*.
Ehrenreich, H. Electrical properties of materials, B (11) 358*i*.
Ehrlinger, H. P., III, Bohor, B. F., Camp, L. R., and Khandelwal, S. Lightweight bricks made with clay and expanded plastic, (1) 10*i*.
Ehrlinger, H. P., III, Mirza, M. B., Camp, L. R., and Jackman, H. W. Illinois clays as binders for iron ore pellets—a further study, (1) 10*h*.
Ehrlinger, H. P., III, Schroder, M. L., Camp, L. R., and Jackman, H. W. Silica sand briquets and pellets as a replacement for quartzite, (7) 203*h*.
Eichelberger, W. C. See Lauder, W. B.
Eichhorn, E., and Garrison, L. G. Production of zeolitic adsorbents in nodular form, P (6) 183*c*.
Eick, H. A. See Butherus, A. D.
Eiduk, O. I. See Ivensen, V. A.
Eilers, K. F. Rock crusher, P (4) 105*h*.
Einstein, E. Production of magnesium carbonate and magnesia, P (3) 69*a*.
Einstein, E., Miller, E. D., Jr., and Leatham, E. Mullite production, P (5) 135*e*.
Eipeltauer, E., and Hammer, E. Viscous behavior and constitution of binary bismuth phosphate glasses, (6) 169*g*.
Eisenberg, A., and Saito, S. Possible experimental equivalence of the Gibbs-DiMarzio and free-volume theories of the glass transition, (5) 128*e*.
Eisenberger, P., and Pershan, P. S. Rare-earth-doped CdF_2 as a far infrared photoconductor, (1) 16*d*.
Eisenman, G. See Riseman, J. H.
Eisenman, G., and Ross, J. W. Glass electrode composition and method of using same for measuring sodium and potassium ion concentration, P (3) 65*f*.
Eisner, E. Interferometric strain analysis, P (3) 76*f*.
Eisner, R. L., and Suarez, H. E. High voltage [single crystal] rectifier having controlled current leakage, P (1) 18*d*.
Ekdahl, W. G. Refractory fiber composition, P (2) 42*a*.
Ekstrom, R. A., Jr. Surface temperature thermocouple fixture, P (4) 103*i*.
Elahi, Kh. M., Ahmad, S., Ariff, M. R., and Faruqi, F. A. Majolica glazes for dinnerware, (9) 270*j*.
Elarde, V. D. Resistive element and variable resistor, P (2) 52*c*.
Elarde, V. D., Potocki, E. A., and Gajewski, H. M. Process of making a fired ceramic article and article obtained, P (4) 97*d*.
El Bindari, A. Superconductive material of NbN and ZrN, P (10) 311*e*.
Elcombe, M. M. Crystal dynamics of lead sulfide, (9) 280*i*.
Elder, M., and Penfold, B. R. Crystal structure of technetium(IV) chloride—a new AB_4 structure, (6) 184*e*.
Eldon Industries, Inc. Method of making a heating element, P (3) 73*c*.
Eldridge, J. M., and Balk, P. Formation of phosphosilicate glass films on silicon dioxide, (10) 307*a*.
Electro Materials Corp. Composition and method for electroding dielectric ceramics, P (1) 17*d*.
Electro-Nite Co. Molten material sampling apparatus and method, P (5) 130*a*.
Electro-Nuclear Laboratories, Inc. Charged particle detector with lithium compensated intrinsic silicon as an intermediate region, P (11) 343*g*.
Electro-Optical Systems, Inc. Stacked electrode field effect triode, P (8) 246*c*.
Elektrokemisk A/S. Apparatus for feeding solid materials into a rotary kiln, P (3) 76*j*.
Elemelt, Ltd. Glass feeding furnaces, P (8) 235*j*.
El-Hinnawi, E. E. Methods in Chemical and Mineral Microscopy, B (4) 120*d*.
Eliasova, M. See Proks, I.
El Jack, S. A. See Mitchell, J. K.
El'kin, G. B. See Ginzburg, D. B.
El'kina, N. T. See Shur, A. S.
Elleman, T. S., Mears, L. D., and Christman, R. P. Rare gas diffusion in cesium iodide—use of fission recoil doping techniques, (11) 355*h*.

Elleman, T. S., Price, R. B., and Sunderman, D. N. Fission fragment induced expansion in ceramic materials, (5) 132*e*.

Ellern, G. A. See Kitaigorodskii, I. I.

Ellinger, F. H. See Land, C. C.

Elliot, M. N., and Auty, D. B. Durability of glass for the disposal of highly radioactive waste—discussion of method and effect of leaching conditions, (7) 196*f*.

Elliott, G. E. P., and Riddiford, A. C. Dynamic contact angles (1) the effect of impressed motion, (9) 276*c*.

Elliott, H. H. See Woyski, M. M.

Elliott, J. E., and Morrell, A. P. Production of metallic compacts, P (7) 205*a*.

Elliott, J. F. Temperature compensated semiconductor strain gage, P (5) 143*d*.

Ellis, C. C. Shaker hearth furnaces, P (8) 249*h*.

Ellis, E. See Bloor, D.

Ellis, J. D., and Nicholls, A. M. Preparation of mixed metal oxides by thermal decomposition of metal salts, P (7) 214*j*.

Ellis, J. L. See Tarkan, S. E.

Ellis, J. L., and Tarkan, S. E. Heat-treatable nickel-containing refractory carbide tool steel, P (5) 135*d*. Surface hardened composite metal article of manufacture, P (5) 136*b*.

Ellis, M. P., Murphy, R. T., and Horgan, J. F. Bonded abrasive grade [hardness] checking apparatus, P (1) 1*f*.

Ellis, P. J. See Klein, A. G.

Ellis, R. B., and Freeman, A. C. Surface tension in the reciprocal system K^+,Cd^{++}-Cl^-, Br^-, (11) 357*a*.

Ellis, R. T., and Juel, L. H. Refractory graphite and method of producing, P (6) 175*d*.

Ellis, R. W. Glass furnace electrode, P (9) 278*d*.

Ellis, S. G. Method of changing the conductivity of vapor deposited gallium arsenide by the introduction of water into the vapor deposition atmosphere, P (11) 344*d*. Method of electrolytically binding a layer of semiconductors together, P (11) 344*g*.

Ellis, W. C., Pfann, W. G., and Wagner, R. S. Vapor-liquid-solid crystal growth technique, P (1) 19*d*.

Ellis, W. P. Hydrofluorination kinetics of doped uranium dioxide, (3) 81*h*.

Ellison, E. G., and Boone, D. H. Some mechanical properties of boron-tungsten boride filaments, (4) 96*f*.

Elson, D. B., and Weymouth, J. H. Etching of portland cement clinker, (9) 262*a*.

Elms, W. A. See Rimmer, W. S.

El-Shabat, R. M., Gadalla, A. M. M., and White, J. Recent developments in phase-equilibrium studies, B (7) 226*d*.

El-Shanshoury, I. A. See Krugloff, A. S.

Elsken, J. van der. See Matselaar, R.

Elston, J. Effect of radiation on ceramic materials, (7) 201*a*. See Bourrasse, A.; Morize, P.

Elwood, A. A., and Carlson, R. I. Crystal temperature and pressure transducer, P (3) 76*e*.

Ely, R. E. Strength of magnesium silicate and graphite under biaxial stresses, (6) 189*d*.

Elyard, C. A., and Potter, T. J. Sintered uranium dioxide containing yttrium oxide, P (1) 14*e*. Sintered uranium dioxide-iridium composition and method of preparation, P (1) 14*f*.

Elyutin, V. P., Antsiferov, V. N., Mozzhukhin, E. I., and Natanson, A. K. Effect of small additions of disperse alumina inclusions on some characteristics of sintered nickel, (8) 237*e*.

Embry, W. A., and Ayres, G. H. Spectrophotometric determination of ruthenium with 2,4,6-tri(2′-pyridyl)-*s*-triazine, (11) 347*i*.

Emele, O. Arrangement for automatically displacing plates and frames, especially in filter presses, P (3) 75*c*.

Emerson, W. W. Coherence of clay crystals in water (abstract), B (9) 289*e*.

Emery, A. H., Co. Batch weigher with respective dials for successive loads and total weight, P (3) 75*a*.

Emhart Corp. Air stream device for cooling glass furnace electrodes, P (11) 335*c*. Apparatus for applying coatings to articles of glassware, P (3) 64*i*. Blow molding apparatus for a glassware forming machine, P (11) 335*g*. Body gaging apparatus for glass containers, P (1) 8*d*. Electrode holder for glass melting furnace, P (8) 249*f*; P (10) 300*g*. Glass-melting furnace, P (4) 94*b*. Heating section of decorating lehr, P (9) 265*f*. Method for damping the stack of a glass melting furnace, P (4) 94*j*. Method of melting glass, P (3) 65*i*. Mold cooling control apparatus for a glassware forming machine, P (3) 66*a*. Optical inspection apparatus for surface coatings on articles of glassware, etc., wherein the articles are inspected in a liquid having the same index of refraction as the glass, P (11) 336*d*. Settle blowhead and baffle attachment for glassware forming machine, P (3) 66*d*. Take-out tong mechanism for a glassware forming machine, P (4) 95*c*.

Emley, F. New method for compacting metal or ceramic powders into continuous sections, B (3) 89*i*.

Emrich, H. W. See Stevenson, C. L.

Enache, M. See Abramovici, R.

Endevco Corp. Semiconductor transducers, P (10) 311*d*.

Energy Conversion Devices, Inc. Method of making solid state relay devices from tellurides, P (11) 344*c*.

Engan, H., Ingebrigtsen, K. A., and Tonning, A. Elastic surface waves in α-quartz—observation of leaky surface waves, (5) 151*c*.

Engberg, A., and Soling, H. Crystal structures of $RbCoCl_3$ and Rb_3CoCl_5, (5) 150*e*.

Engdahl, R. E., Bedell, J. R., and Kroha, C. E., Jr. Protecting refractory metal at high temperatures, (1) 4*i*.

Engel, F., and Kiley, W. R. Apparatus with means to measure the characteristic X-ray emission from and the density of a material, P (3) 76*c*.

Engel, W., Cautius, W., and Schoen, K. Fuel elements for nuclear reactors, P (1) 12*f*.

Engelen, J. Capless lamps, P (5) 129*d*.

Engelhard Industries, Inc. Alumina-based catalyst and method of preparing, P (4) 104*h*. Composite material of a ceramic silver-gold alloy and a nickel alloy, P (1) 17*d*. Electric heating element, P (4) 104*b*. Gold decorating compositions and method, P (10) 312*c*. Metal-to-ceramic seal, P (5) 141*d*. Method of making a mandrel for precision-shaping internal surfaces on glass vessels, P (6) 171*d*. Noble metal thermocouple having base metal leads, P (6) 181*f*.

Engelhard Minerals & Chemicals Corp. Bonded molecular sieve catalysts and preparation, P (8) 250*c*. Calcination of clay, P (8) 250*f*. Grinding method, P (11) 349*h*. Method for preventing activation of silica in ore flotation, P (8) 251*i*. Method for producing faujasite-type zeolites, P (10) 318*g*. Solid catalysts, P (5) 149*a*. Spray dried clay product and method for producing, P (6) 183*f*. Synthetic zeolite contact masses and method for making, P (5) 149*b*.

Engelleitner, W. H. Pelletizing disk applications in ceramic processing, (3) 74*h*.

Engelman, J. H., and Witsell, W. A. Method for fabricating an electrical memory module, P (1) 18*j*.

Engelthaler, K. See Engelthaler, Z.

Engelthaler, Z., and Engelthaler, K. New technical information on spray drying in the manufacture of structural ceramics, (4) 95*i*.

Englehart, O. D., and Shuster, J. S. Glass sheet press bending apparatus with indexed cover over the shaping surface, P (9) 265*e*.

Englert, W. J., and Fuhrman, P. K. Identifying causes of back surface ream lines in sheet glass, (7) 196*j*.

English, F. L. Electron-mirror microscope analysis of surface potentials on ferroelectrics, (9) 281*j*. See Parsons, M. K.; Whitehurst, H. B.

English, J. F. Decorative pulsating flame incandescent lamp, P (8) 235*f*.

English, R. H. See Ornitz, M. N.

English Electric Co., Ltd. Bonded metal/glass-ceramic elements, P (5) 140*e*. Ceramic articles, P (7) 206*h*. Devitrified glass-ceramics and their production, P (1) 8*i*. Glass-ceramics, P (1) 9*c*, P (7) 198*ef*. Method of making glass-ceramic and product, P (2) 41*f*. Method of making glass-ceramics by devitrification in a single stage, P (2) 41*h*.

English Electric Valve Co., Ltd. Klystron having high frequency radiation means comprising a half-wave short-circuited choke, P (10) 310*b*.

Engmann, F. Rationalization and automation in the wall- and floor-tile industry, (4) 95*h*.

Enright, C. R. Method of producing tile panels, P (4) 98*g*.

Entin, Z. B., Fridman, I. A., and Khokhlov, V. K. Study of K_2O sublimation by mathematical design of experiment, (3) 62*j*.

Entreprise Generale de Chauffage Industriel Pillard Freres & Cie Soc. Anon. Air distributors of burners for solid, liquid, or gaseous fuel, P (4) 104*e*.

Enz, U. See Bongers, P. F.

Epik, A. P. See Samsonov, G. V.

Epik, A. P., Sharivker, S. Yu., and Astakhov, E. A. Forces binding plasma coatings to the base, (8) 237*a*.

Epperson, C. E., Gremillion, A. F., and Ferguson, J. E. Study of β-ferric oxide monohydrate containing excess water, (4) 116*i*.

Eppler, R. A., and Smiser, L. W. Viscosity of porcelain enamel frits, (9) 263*d*.

Epstein, D. J., and Tocci, L. High temperature resonance losses in silicon-doped yttrium-iron garnet, (3) 71*d*.

Epstein, D. W. See Ramberg, E. G.

Epstein, L. F. Ideal solution behavior and heats of fusion from the UO_2-PuO_2 phase diagram, (10) 322*a*.

Era, K. See Shionoya, S.

Erdenberger, P. Apparatus for distributing melt and forming fibers therefrom, P (9) 264*g*.

Erdey, L., Paulik, F., and Paulik, J. Heater controller for isothermic thermogravimetric analysis, P (1) 23*i*.

Eremenko, V. N., Lukashenko, G. M., and Sidorko, V. P. Thermodynamic properties of manganese silicides (II), (9) 288*b*.

Eremenko, V. N., Nizhenko, V. I., and Skiyarenko, L. I. Effect of zirconium on the surface properties of liquid nickel at the melt-gas and melt-solid aluminum oxide interfaces, (2) 44*c*.

Erginsoy, C. Channeling and related effects in the passage of charged particles through crystal lattices, B (10) 329*b*.

Erickson, H. See Disegna, W. L.

Erie Development Co. Product sizing control in a grinding circuit closed by a separating means, P (11) 346*a*.

Erie Mining Co. Gyratory crusher liner, P (3) 78*b*.

Erie Technological Products, Inc. Module capacitor, P (10) 311*b*. Overvoltage protective device, P (10) 311*c*.

Erinui, H., and Malcheva, N. Surface tensions of synthetic slags rich in manganese, (3) 87*h*.

Erlesand, L. See Dock, N.

Erlin, B., and Greening, N. R. Hydration studies by time-lapse photomicrography, (10) 294*h*.

Ermakov, I. S., Kochkin, G. M., Meshengisser, M. J., and Shakhov, F. N. Automatic chamber pressure filter, P (1) 20*c*.

Ernest, J. See Dupont, H.

Ernsberger, F. M. Method of drawing a glass sheet, a portion of its surface being untouched, P (1) 9*j*. Role of densification in deformation of glasses under point loading, (11) 335*c*. See Chisholm, R. S.

Ernst Leitz G.m.b.H. Controlling mechanism for spectrometer, P (5) 147*b*.

Ervin, G., Jr., and Korst, W. L. Reported high-temperature solubility of uranium in UC, (3) 86*c*.

Ervin, G., Jr., and Miller, K. T. Oriented growth of oxidation products on single crystals of UC, (10) 324*c*.

Esaki, L., and Laff, R. A. High sensitivity diodes, P (5) 141*a*.

Esbitt, A. S., Boeer, K. W., and Kaufman, W. M. Method of improving the photoconducting characteristics of layers of photoconductive material, P (10) 310*f*.

Esch, R. P. See Pliskin, W. A.

Escher Wyss Akt.-Ges. Heat transfer from waste gas of a cement kiln to pulverulent raw material, P (8) 229*a*.

Esdaile, J. D. Lead oxide-lead sulfate system, (10) 322*c*.

Esguerra, F. B. Aluminous lateritic soil of the Lutawon Basin area, Nonoc Island, Surigao Province, Philippines, (2) 56*e*.

Esper, F., and Friese, K. H. Spark plug with a sealing glass mixture with graphite and iron, nickel, or cobalt, P (4) 101*d*.

Essers, W. G. See Tichelaar, G. W.

Esso Research & Engineering Co. Anhydrous magnesium chloride production, P (11) 349*e*. Catalyst compositions and process for preparation thereof, P (1) 25*i*. Catalyst preparation, P (5) 148*j*. Ceramic lined return bend, P (1) 15*j*. Dehydration of magnesium chloride, P (1) 25*j*. Dehydration of magnesium chloride using gaseous ammonia, P (1) 25*a*. High temperature protective coating, P (3) 63*c*. Method of making a porous electrode, P (11) 340*i*. Modified cement mortar containing emulsion polymer of 2 methyl α olefin and mixed dialkyl fumarate, P (6) 166*a*. Moisture content determining device having a pressure-operated capacitor member, P (7) 213*a*. Physically stable aluminosilicate zeolite catalysts, P (10) 318*h*. Preparation of a crystalline aluminosilicate zeolite in a siliceous matrix, P (1) 25*g*. Process for ion exchanging crystalline zeolites, P (5) 148*j*. Process for producing synthetic faujasite having a high silica to alumina ratio, P (1) 25*j*. Promoted catalyst used for town gas production, P (11) 350*a*.

Estill, W. B., Robertson, M. M., and Conrad, G. H. Electron microprobe and electron diffraction analysis of surface replica extractions, (1) 21*j*.

Estour, H. Study of the contact between glass and refractory by the electron microprobe, (10) 298*j*.

Esveldt, C. J. See Driel, G. A. H. van.

Esveldt, C. J., Gorter, E. W., and Peloschek, H. P. Method for manufacturing lithium-nickel-manganese ferrite magnetic memory cores, P (6) 178*g*.

Esveldt, C. J., and Weerden, T. J. van der. Method of manufacturing a magnetic memory core, P (6) 178*h*.

Ethington, R. L., and Hilbrand, H. C. Anisotropy in wood, B (4) 121*c*.

Ethyl Corp. Copper oxide-alumina catalyst composition, P (6) 183*b*.

Ett, A. H., Keiper, F. P., Jr., and Revesz, G. Radiation-sensitive means for detecting flaws in radiation-transmissive materials, P (5) 147*c*.

Ettinghausen, R. Immanent features of Persian art—reflections on recent exhibitions, (4) 91*f*.

Ettre, K. S. Automatic metallizing, (2) 37*g*. Method of applying uniform thickness of frit on semiconductor wafers, P (6) 177*i*.

Eubanks, A. G., and Hunkeler, R. E. Foamed-in-place ceramic refractory insulating material, P (8) 240*d*.

Euler, R. Mineralogical investigation of the erosion of tar-dolomite and tar-magnesite bricks in oxygen process steel converters, (7) 202*i*.

Euratom. See European Atomic Energy Community.

European Atomic Energy Community—Euratom. Magnetic forming apparatus, device, and method for making deep grooves on parts made of conducting materials, particularly tubes made of metal or ceramic-metal materials, P (2) 47*e*. Process for obtaining Al-Al_2O_3 structures for nuclear applications, P (10) 305*a*. Process for the preparation of mixed carbides, P (7) 205*h*.

Eutectic Welding Alloys Corp. Coated carbide particles, P (6) 174*a*. Method of flame spraying and powder, P (6) 166*c*.

Euwema, R. N. See Langer, D. W.

Evans, C. C. Manufacture of silicon nitride, P (11) 340*g*.

Evans, D. J. Health and safety developments, (10) 328*a*.
Evans, E. H. See Swanson, H. E.
Evans, H. T., Jr., and Block, S. Crystal structures of potassium and cesium trivanadates, (6) 184*h*.
Evans, J. C. See Moyer, J. R.
Evans, P. E. Mechanism of the compaction of metal powders by rolling, B (3) 89*i*.
Evans, P. E., Hardiman, B. P., Mathur, B. C., and Rimmer, W. S. Alumina-based cutting tools (6) 163*f*.
Evans, P. E., and Millman, R. S. Vibratory packing of powders, B (3) 90*b*.
Evans, P. E., and Smith, G. S. Compaction of metal powders by rolling (I) properties of strip rolled from copper powders, B (3) 89*i*.
Evans, R. E. See Jones, W. M.
Evans, R. J. See Revesz, A. G.
Evans, R. M. Hydraulic cement compositions and methods, P (4) 92*d*.
Evans, T. See Wild, R. K.
Evans, T., and Wild, R. K. Effect of neutron irradiation on the plastic behavior of type IIA diamond plates, (1) 28*i*.
Evans, W. H. Rapid complexometric determination of aluminum and total iron in silicate and other rock material, (5) 146*c*.
Evans, W. H., and Sergeant, G. A. Determination of small amounts of fluorine in rocks and minerals, (5) 145*a*.
Everest, D. A., and Napier, E. Discussion of the microstructures of silica rich binary silicate melts and glasses, (4) 108*c*.
Everett, L. H. See Gutt, W.
Everett, L. H., and Gutt, W. Steel in concrete with blast furnace slag aggregate, (4) 92*g*.
Everill, J. B. See West, H. W. H.
Everts, J. C. See Wyman, L. L., Sr.
Evode, Ltd. Adhesive composition for fixing ceramic tiles, P (1) 15*j*.
Evstatiev, D. G., Solomchenko, N. Ya., Serb-Serbina, N. N., and Rebinder, P. A. Mechanism of structure formation during clay fixing with quicklime additions, (5) 125*e*.
Evtushok, T. M. See Burykina, A. L.
Ewing, R. D. See Fair, H. D., Jr.
Eyles, T. E., and Torok, J. J. Method and apparatus for cooling glass plungers and molds, P (4) 94*g*.
Eyraud, M. C., Lenoir, J., Siclet, G., and Gery, M. Surface chemical properties of metal oxides—Lewis acid-base and ion-exchange reactions, (10) 325*f*.
Eyre, B. L., and Bartlett, A. F. Structure of high carbon hyperstoichiometric uranium carbide single crystals, (4) 116*c*.
Eyring, H. See Hahn, S. J.
Eyring, L. See Hyde, B. G.
Eysel, W. See Bigare, M.; Woermann, E.
Ezell, J. W. See Blum, J. E.

Fa, C. H. Semiconductor device and process for producing, P (9) 274*j*.
Fabel, D. A., and Hunter, R. M. Multilayer contact system for semiconductor devices including gold and copper layers, P (5) 142*j*.
Fabricacion de Maquinas. Method of manufacture of rolls for glass drawing machinery, P (5) 130*h*.
Fabricius, J. H. See Marty, R. S.
Fabriques de Produits Chimiques de Thann et de Mulhouse. Process and apparatus for continuously producing titanium dioxide by the oxidation of vaporized $TiCl_4$, P (3) 78*a*.
Fabri-Tek, Inc. Component sizing apparatus, P (11) 343*i*.
Fadeeva, V. I. See Portnoi, K. I.; Umanskii, Ya. S.
Faeth, P. A. See Singer, J.
Fagerta Bruks A. B. Methods of producing shaped bodies of sintered cemented carbides, nitrides, borides, and silicides, P (2) 47*d*.
Fahey, R. E. See Reed, T. B.
Fahlstrom, P. A. H. H. Rod screen, P (10) 312*i*.
Fahmy, A. A. Neutron radiography and microradiography studies, B (10) 329*f*.
Faille, M. della. See Fripiat, J. J.
Fain, I. A., Kamenetskii, S. P., et al. Production of perlite-chamotte insulating products, (9) 268*a*.
Fainberg, E. A. Change in electrical conductivity of surface layer of lead silicate glass during heat treatment in hydrogen, (2) 38*i*.
Fair, H. D., Jr., Ewing, R. D., and Williams, F. E. Photo-induced paramagnetic resonance of chromium in zinc sulfide crystals, (9) 285*c*.
Fairbanks, D. F. Process of bonding copper foil to foil containing superconductive layer such as niobium stannide, P (2) 52*c*.
Fairchild Camera & Instrument Corp. Dielectric isolation process, P (10) 309*a*. Method of forming a metal rectifying contact to semiconductor material by displacement plating, P (11) 344*i*. Use of anodizing to reduce channelling on semiconductor material, P (3) 74*f*.
Faircloth, R. L. See Ackermann, R. J.
Faircloth, R. L., Flowers, R. H., and Pummery, F. C. W. Studies of the equilibrium metal vapor pressures over the alkaline earth carbides (II) CaC_2, (6) 189*j*.
Faith, L. E., Bustany, S. H., Hanson, D. N., and Wilke, C. R. Particle precipitation by space charge in tubular flow, (3) 76*c*.
Faktor, M. M., and Carasso, J. I. Tetragonal germanium dioxide and equilibria in the Ge-O-H system, (3) 87*b*.
Faktor, M. M., and Hanks, R. Quantitative application of dynamic differential calorimetry (I) theoretical and experimental evaluation, (5) 146*b*.
Falk, R. A. Induction furnace crucible, P (10) 304*f*.
Fal'kovskii, V. A. See Ivensen, V. A.
Fallon, A. D. Method of forming a semiconductor device by diffusing and alloying, P (9) 273*f*.
Fan, G. J. See Shafer, M. W.
Fanderlik, M. Color and structure of glass, (1) 5*d*.
Fanderlik, M., and Palecek, M. Investigations on sodium phosphate glasses, (6) 167*e*.
Fang, F. F., Yeh, Tsu-Hsing, and Yu, H. N. Optoelectronic semiconductor devices, P (5) 142*j*.
Fann, J. D. Filter press, P (6) 179*d*.
Fanning, D. S., and Jackson, M. L. Clay mineral weathering in southern Wisconsin soils developed in loess and in shale-derived till, B (7) 224*g*.
Fanselow, J. R. Spray dried clay product and method for producing, P (6) 183*f*.
Fansteel Metallurgical Corp. Process for dispersing refractory metal oxides in other metals, P (8) 241*h*. Process for producing alloys containing chromium and dispersed refractory metal oxide particles, P (10) 305*b*.
Farabaugh, E. N. See Wachtman, J. B., Jr.
Farbenfabriken Bayer Akt.-Ges. Aluminum fluoride manufacture with a moving bed, P (8) 250*d*. Process and apparatus for continuously separating mixtures of substances by fractional crystallization, P (2) 53*g*. Process for the [continuous] production of highly pure semiconducting selenium materials, P (3) 74*b*. Process for the preparation of γ-FeOOH, P (8) 251*c*. Process for the production of molecular sieve granules, P (3) 78*d*. Process for the production of titanium tetrachloride, P (4) 105*f*. Production of highly pure hexagonal crystals of cadmium and zinc chalcogenides by sublimation, P (4) 101*b*. Sized glass fiber material, P (5) 130*f*. Two stage process for making ferromagnetic modified chromium dioxide, P (6) 178*i*.
Farber, M. See Blauer, J. A.
Farbwerke Hoechst Akt.-Ges. Process for granulating substances from the melt, P (2) 56*j*. Refractory masses, P (1) 14*i*.
Farinett, P. F. Technical requirements of good sensitive solutions for silk-screening, (8) 247*c*.
Farkas, E. See Dodson, V. H.
Farkas, M. S. See Stellrecht, D. E.
Farmer, V. C., and Russell, J. D. Infrared absorption spectrometry in clay studies, B (9) 289*h*.
Farr, A. E., and Kreidler, E. R. Effect of dissolved materials on pickup behavior of ground coat enamels, (9) 262*j*.
Farrell, E. F., and Newnham, R. E. Electronic and vibrational absorption spectra in cordierite, (6) 185*j*.
Farrington, G. M. Precast taphole assembly, P (11) 340*c*.
Farrow, L. C. Practical experience with electrostatic spraying, (9) 253*b*.
Farrow, L. C., Roth, R. J., and Thompsen, R. S. Effect of production variables on electrostatic spraying efficiency, (7) 195*c*.
Faruqi, F. A. See Elahi, Kh. M.; Qureshi, M. H.
Faruqi, F. A., and Qureshi, M. H. High temperature pyrometric cones, (9) 276*h*. Mineralogy of Ahl kaolinite, (9) 278*j*.
Fasolt, N. Evolution of the facing tile industry and problems of quality, (3) 66*g*.
Fasselle, R. J. de. See Mellen, E. J., Jr.
Fassler, M., and Horner, M. H. Tungsten carbide base cermet, P (6) 175*d*.
Fateeva, N. I., and Koziova, V. K. Determination of content of certain minerals in clinkers by rational chemical analysis, (3) 62*c*.
Fattore, V. See Vecchio, M.
Faunce, C. A. See Straumanis, M. E.
Faust, J. W., Jr. Method of angularly pulling continuous dendritic crystals, P (6) 190*h*.
Faust, J. W., Jr., and John, H. F. Method of varying the thickness of dendrites by adding an impurity which controls growth in the (111) direction, P (11) 344*f*.
Fawcett, J. D. New rotary screen and waste chopper, (5) 143*h*.
Fay, H. Characterization of potassium tantalate-niobate crystals by electrooptic measurements, (1) 26*h*.
Faye, G. H. Optical absorption spectra of iron in six-coordinate sites in chlorite, biotite, phlogopite, and vivianite—some aspects of pleochroism in the sheet silicates, (9) 284*j*.
Fayek, M. See Amin, R.
Fazioli, W. A. See Olton, D. J.
Feder, H. M. See Rudzitis, E.
Federal Republic of Germany, Secretary of Defense. Method of making glass or ceramic covered wires, P (4) 95*d*.
Fedorenko, V. A. See Galdina, N. M.
Fedorov, N. F. ,See Kuznetsova, G. N.; Toropov, N. A.
Fedorov, N. F., and Brodkina, E. R. Solid solutions in the $2CaO \cdot SiO_2$–$K_2O \cdot CaO \cdot SiO_2$ system, (2) 36*i*.
Fedorov, N. F., and Sadikova, N. S. Hardening and sorel cement analogs, (2) 36*j*.
Fedorov, P. I., Liu, Kuo-Yuan, and Nedev, S. K. Reactions of the chlorides of gallium and iron, (10) 325*a*.
Fedorov, T. F., Kuz'ma, Yu. B. Skolozdra, R. V., and Popova, N. M. Phase equilibria in the ternary systems Zr–Co–C and Nb–Fe–C, (9) 285*h*.
Fedorovskii, Ya. A. See Gendler, T. S.
Fedoseev, A. D. See Skorik, Yu. I.
Fedoseev, D. V. See Botvinkin, O. K.; Ryabov, V. A.
Feher, G., Shepherd, I. W., and Shore, H. B. Paraelectric resonance of OH^- dipoles in KCl, (10) 324*f*.
Fehling, W. See Kleber, W.
Fehner, R. H. Soot-resistant roofing granules, P (11) 337*e*.
Feigelson, R. Flux growth of type RVO_4 rare-earth vanadate crystals, (10) 321*h*.
Feingold, E. See Mehan, R. L.
Feinstein, L. See Peters, D. W.
Feldman, C. Amorphous boron films, (6) 176*a*. Rhenium thin film resistors, P (8) 246*f*.
Feldman, D. W., Castle, J. G., Jr., and Wagner, G. R. Spin relaxation of atomic hydrogen in fused silica—temperature dependence, (10) 325*b*.
Fel'dman, M. A. See Sheinkop, I. M.
Feldman, R. F., and Ramachandran, V. S. Reply to discussion of "Influence of $CaSO_4 \cdot 2H_2O$ on the hydration character of $3CaO \cdot Al_2O_3$," (8) 228*g*.
Feldmann, T., and Treinin, A. Dihalide ions trapped in glasses, (5) 127*d*. Inorganic radicals trapped in glasses at room temperature (IV) silver radicals in metaphosphate glass, (5) 127*f*.
Feldmann, T., Treinin, A., and Volterra, V. Inorganic radicals trapped in glasses at room temperature (II) Cd^+ and Ni^+ in metaphosphate glass, (5) 127*f*.
Feldmuhle Akt.-Ges. Method of preparing satin white, P (10) 318*e*.
Felgar, R. P., and Bohn, J. R. Thermal shock resistant rocket nozzle insert, P (8) 241*f*.
Felicetta, V. F., and Markham, A. E. Cement composition and products thereof, P (11) 332*c*.
Felten, E. J. Preparation of $CuNb_2O_6$ and $CuTa_2O_6$, (5) 157*b*.
Felty, E. J. See Myers, M. B.
Fenner, E. See Schofer, R.
Fenwal, Inc. Plasma arc spraying of hafnium oxide and zirconium boride mixtures, P (7) 195*c*.
Feodos'ev, N. N. See L'vova, A. S.; Panfilov, B. I.
Ferguson, C. W. See Carson, F. J.; Rahrig, D. D.
Ferguson, I. F. Lattice contractions associated with the neutron irradiation of self-bonded silicon carbide, (8) 254*e*.
Ferguson, J., and Guggenheim, H. J. Electronic absorption spectrum of Ni(II) in cubic perovskite fluorides (II) concentration and exchange effects, (7) 217*h*.
Ferguson, J., Guggenheim, H. J., and Wood, D. L. Electronic absorption spectrum of Ni(II) in cubic perovskite fluorides (I), (7) 217*h*.
Ferguson, J. E. See Epperson, C. E.
Ferlazzo, N., Caporali, G., Giordano, N., and Marinozzi, P. Catalytic process for the preparation of nitriles, P (5) 148*a*.
Fermor, J. H., and Kjekshus, A. Electrical properties of KNO_3, (5) 138*c*.
Fern, N. D. Tooling for high temperature electronic packaging, (3) 72*h*.
Fernandez Navarro, J. See Brueckner, R.
Ferrandis, V. A. See Aleixandre Ferrandis, V.
Ferranti, Ltd. Parallel light fibers with longitudinal axes making oblique angle with display surface of cathode-ray tubes, P (4) 100*i*.
Ferraresso, G. See Bettinali, C.
Ferrari, S., and Segre, G. J. Experiments on uranium emission from sintered uranium oxide pellets, (7) 201*g*.
Ferreira, L. C. See Dry, M. E.
Ferrell, R. E., Jr., and Grim, R. E. Influence of alkaline solutions on the alteration of the clay minerals, B (9) 289*f*.
Ferris, L. M. See Sears, M. B.
Ferro, A., Montalenti, G., and Soardo, G. P. Magnetic viscosity induced by fast neutron irradiation in high permeability pure iron, B (10) 329*d*.
Ferro Corp. Ceramic refractory flame retention nozzle, P (2) 56*b*. Deburring tumbling media, P (7) 193*i*.
Fertillo, A. See Wisniak, J.
Fesenko, V. V. See Gordienko, S. P.
Fesenko, V. V., Bolgar, A. S., and Gordienko, S. P. Study of the rate of vaporization, vapor pressure, compositional discontinuity, and certain thermodynamic properties of refractory compounds up to 3000°C, (1) 32*g*.
Fessel, P. Cutting and grinding devices, P (1) 1*g*.
Fetner, M. J., and Freedman, R. P. Apparatus and method of measuring molten metal temperature, P (5) 134*c*.
Fetterman, H. R. See Fitchen, D. B.
Fetters, C. R. Process for removing thin films from vitreous surfaces, P (6) 171*d*.
Feuer, I. Coated phosphor having radioisotope dispersed therein and method of preparation, P (5) 140*h*.
Fialkov, A. S., Davidovich, Ya. G., Pshenichkin, P. A., and Galeev, G. S. Diamagnetic susceptibility and linear thermal expansion of graphitized carbons, (2) 43*j*.
Fibreboard Corp. Catalyzed gypsum wallboard and its production, P (6) 165*a*.
Ficalora, P. J., and Brindley, G. W. Oxidation of magnesiowustite single crystals (II) dependence on temperature, oxygen pressure, and crystal composition, (1) 30*h*.

Ficalora, P. J., Uy, O. M., Muenow, D. W., and Margrave, J. L. Mass spectrometric studies at high temperatures (XXIX) thermal decomposition and sublimation of alkali metal sulfates, (11) 354*c*.
Fickert, K. W. J., Kappes, K. A., and Bateson, S. Ferroelectric ceramics in the system PbO–Nb_2O_5, (11) 342*f*.
Fiebiger, E. See Mecky, K.
Field, J. H. See Bienstock, D.
Field, M. B., and Redwine, R. H. Empirical determination of background in internal friction studies, (3) 80*i*.
Field Emission Corp. Field emission cathode having tungsten Miller indices 100 plane coated with zirconium, hafnium, or magnesium on oxygen binder, P (6) 177*j*.
Fielder, W. S., Rautiola, N. A., and Diehl, J. M. Method of making a battery plate, P (2) 41*d*.
Fieschi, R., and Scaramelli, P. Evidence for L bands in NaCl, (10) 321*c*.
Figiel, F. J. Process of separating nondiamond carbonaceous material from synthetic diamantiferous products, P (9) 261*h*.
Figner, A. I., Soloveichik, A. I., and Judinskaja, I. V. Metal porous body having pores filled with barium scandate, P (3) 73*d*.
Figone, D. C. See Reed, L.
Filimonov, Y. P. Calculation of output of heating furnaces, (1) 24*c*.
Filippova, E. A. See Tumanov, S. G.
Finch, C. B. See Abraham, M. M.
Fincher, C. L. See Birnbaum, M.
Fine, M. E. See Wirtz, G. P.
Finkel, V. M., Kutkin, I. A., and Zuev, L. B. Growth and branching of cracks in glass, (5) 127*b*.
Finkel'shtein, N. A., Bergman, A. G., and Nagornyi, G. I. Interactions of the chlorides and sulfates of potassium, calcium, and barium in melts, (9) 283*c*. Interactions of the sulfates of K, Ca, and Ba, (9) 283*e*.
Finlayson, M. B. See Horspool, J. M.
Finlayson, R. W. Canadian sports in ceramics made in Scotland, (5) 124*a*.
Finnie, I. See Oh, H. L.
Fiore, J. P. Color television picture tube and mating support members for mounting the color selection mask within the tube, P (3) 72*c*. Method of coating cathode-ray tubes, P (7) 209*d*.
Fiore, J. P., and Kaplan, S. H. Method of establishing a light absorbing design on a screen structure of an image reproducer, P (5) 141*f*.
Firma Essener Teerschotter G.m.b.H. Method and apparatus for the drying and heating of gravel and crushed stone, P (4) 105*g*.
Firnhaber, M. S. Apparatus for manufacturing mineral fibers, P (10) 300*a*.
Firsov, V. M. See Kitaigorodskii, I. I.; Sil'vestrovich, S. I.
Fischbach, D. B., and Kotlensky, W. V. Mechanisms of high-temperature plastic deformation in pyrolytic carbons, (4) 113*b*.
Fischer, C. F. Basic refractories in glass tank regenerators, (1) 5*b*.
Fischer, H. A. See Funke, G.
Fischer, J. J. Solids-liquids blender, P (4) 102*b*.
Fischer, P. See Andresen, A. F.
Fischer, T. E. Photoelectric emission and work function of InP, (8) 256*a*.
Fischer, W. A. Metallurgical furnace lining, P (7) 205*a*. Methods and apparatus for determining the oxygen activity of molten metals, metal oxides, and slags, P (4) 97*a*.
Fischer & Porter Co. Dry chemical feeder, P (4) 101*j*. Joint construction for glass pipe and the like, P (6) 170*i*.
Fischler, S. See Shapira, Y.
Fischman, J. L. Techniques and binders for investment casting, (2) 46*g*.
Fischotter, P. See Dresia, H.
Fisher, B., and Tannhauser, D. S. Electrical properties of cobalt monoxide, (5) 138*b*.
Fisher, G. E. Support for refractory blocks, P (2) 48*c*.
Fisher, P. M., and Bostick, R. E. Colored signal lights—their history, development, and speculation, (6) 166*h*.
Fisher, R. D., and Haber, H. E. Ferromagnetic storage devices having uniaxial anisotropy, P (10) 309*e*.
Fisher, R. M., Lally, J. S., Bain, E. C., and Greider, M. H. Electron microscopy, (10) 314*j*.
Fishman, D., and Beckett, L. T. A. Strain relieving transition member for contacting semiconductor devices, P (9) 275*a*.
Fishwick, J. H. Treatment of spodumene, P (11) 350*b*. See Richardson, L. S.
Fishwick, J. H., and Talley, R. W. Castable refractories based on spodumene, (4) 96*a*.
Fiske, M. D. Magnetic field responsive superconducting tunneling devices, P (5) 141*d*.
Fisyuk, G. K. See Matveev, M. A.
Fitch, F. T. See Flack, H. P.; Smith, J. G.
Fitch, F. T., and Smith, J. G. Preparation of a thoria sol by heating an aqueous solution of a thorium salt in an autoclave, P (3) 69*f*.
Fitchen, D. B., and Fetterman, H. R. Zero-phonon transition at *M'* and *R'* centers in alkali halides, (11) 358*b*.
Fitts, R. B. See Meservey, A. B.
Fitzgerald, J. V. See Bachman, G. S.
Fitzpatrick, R. L., and Munir, Z. A. Studies on the stabilization of gamma phase cerium sulfide, (2) 59*h*.
Fitzpatrick, T. J. Method of making a stable electrically conductive sheet and product thereof, P (1) 18*e*.
Fitzpatrick, W. D. Composite stopper rod sleeve with insulating inner portion, P (7) 204*a*.
Flack, H. P., Sanchez, M. G., and Lamberth, C. T. Sol-gel microsphere forming process using dissolved ammonia in the dehydrating solvent, P (1) 14*g*.
Flack, H. P., Smith, J. G., and Fitch, F. T. Apparatus for converting hydrosols into solid microspheres, P (8) 250*d*.
Flagella, P. N. See Hein, R. A.
Flanigen, E. M., Breck, D. W., Mumbach, N. R., and Taylor, A. M. Characteristics of synthetic emeralds, (8) 250*a*.
Fleck, D. G. Method and apparatus for removal of condensed deposits from mold covers, P (8) 240*i*.
Fleischer, M. Index of new mineral names, discredited minerals, and changes of mineralogical nomenclature in Volumes 1–50 of the *American Mineralogist*, B (1) 34*f*.
Flemings, M. C. Controlled solidification, B (4) 121*g*.
Flemming, J. C. Evaluation of a high temperature blackbody as a working standard of spectral radiance, (9) 276*e*.
Flengas, S. N. See Bell, M. C.
Flerova, M. I. See Kaibicheva, M. N.
Fletcher, A. T. Glass cutting apparatus, P (6) 170*b*.
Fletcher, W. W. Progress in the development of analytical methods—reports from the working groups (III) lead bisilicate and borax frits, B (7) 224*h*.
Fletcher-Terry Co. Glass cutting apparatus, P (6) 170*b*.
Fleurence, A. Microhardness tests on refractory raw materials and products, (6) 180*i*. Physical methods of analysis applied to raw materials and refractory products of silica and alumina (I, II, III) refractory products, (6) 180*j*.
Fleurence, A., and Bahezre, C. Electron microprobe in the study of diffusion in ceramic products, (10) 314*j*.
Fleurence, A., and Levandowsky, L. Mineralogical applications of electron microprobes, (10) 315*a*.
Fleurence, A., and Loisel, M. Stoneware tile made by the traditional process, (3) 70*d*.
Flinchbaugh, D. E. See Galasso, F. S.
Flockhart, B. D., Scott, J. A. N., and Pink, R. C. Electron transfer at alumina surfaces (I) electron-acceptor properties of aluminas, (3) 80*f*.
Floeck, J. H. Nuclear fluorescence for measuring coatiug weight, (9) 276*f*.
Floehl, R. Ceramic artists and their work—Beate Kuhn, (4) 91*f*.
Floerke, O. W. Structures of $AlPO_4$ and SiO_2, B (7) 226*c*. See Bayer, G.
Flood, H., and Knapp, W. J. Structural characteristics of liquid mixtures of feldspar and silica, (6) 189*d*.
Floreen, S., and Hayden, H. W. Effect of noble metal additions on the toughness of iron-carbon alloys, (6) 185*h*.
Florence, J. M. See Dietz, E. D.
Florence, T. M. See Zittel, H. E.
Flory, P. J. See Semlyen, J. A.
Flournoy, P. A., and Brixner, L. H. Laser characteristics of niobium compensated $CaMoO_4$ and $SrMoO_4$, (3) 83*d*.
Flowers, R. H. See Faircloth, R. L.
Floyd, J. R. Alumina additive makes a difference, (2) 48*f*.
Floyd, J. R., Sterne, J. H., III, and Deutscher, J. S. Test technique makes a difference, (2) 49*a*.
Fluid Energy Processing & Equipment Co. Apparatus for pulverizing and drying solids, P (4) 101*j*.
FMC Corp. Active soda ash compaction, P (7) 214*h*. Method of preparing fibers from by-product slag of a phosphorus furnace, P (4) 97*i*. Method of preparing fibers from solidified phosphorus-furnace slag, P (4) 97*j*. Mixed-cation phosphate glasses, P (4) 95*f*. Process of sequestering metal ions with slowly soluble phosphate glasses, P (6) 171*e*.
Foch, P. Grinding device in a fluidized layer, P (8) 251*c*.
Foex, M. Effect of additions of lime on the C-B transformation in rare earth sesquioxides, (7) 217*a*. Measurement of the solidification points of several refractory oxides with a solar furnace, (5) 154*e*.
Foex, M., and Traverse, J. P. Crystalline transformations of rare earth sesquioxides at high temperatures, (1) 27*g*.
Foex, M., Traverse, J. P., and Coutures, J. P. New crystalline varieties of the sesquioxides of terbium and dysprosium stable at high temperature, (5) 155*d*.
Fogelson, M. Electron vacuum tube getter and method of use, P (9) 272*h*.
Foit, F. F., Jr., and Peacor, D. R. High temperature furnace for a single crystal X-ray diffractometer, (2) 54*i*.
Fokin, K. F., Brilling, P. E., and Khlevchuk, V. R. Thermal characteristics of single-thickness ceramic panels, (10) 302*b*.
Folberth, O. G., and Gremmelmaier, R. Method for the production and remelting of compounds and alloys, P (5) 142*f*.
Folk, H. F., and Bohling, W. C. High temperature strength of high alumina refractories, (7) 202*a*.
Folkmann, E., and Pammer, E. Method and apparatus of epitaxially depositing semiconductor material, P (5) 141*e*.
Folland, D. F. Fluidic density measurement, (8) 248*g*.
Follioni, M. Sampling programs in glassmaking problems, (7) 197*g*.
Folman, M. See Kozirovski, Y.
Folweiler, R. C. Tensile test apparatus, P (7) 213*b*.
Fong, F. K. Method of making divalent rare earth laser crystals in an electric field, P (10) 310*i*.
Fontana, H. Economics of all-electric melting furnaces in Europe, (1) 5*g*.
Foote Mineral Co. Treatment of spodumene, P (11) 350*b*.
Forber, A., and Reid, A. M. Glass, P (7) 198*d*.
Forber, W. E. See Pilkington Brothers, Ltd.
Forbes, D. W. A. Dilatometric analysis as a control tool, (3) 75*h*. Impact of semiconductors on ceramics, (3) 71*f*.
Forchheimer, O. L. See Paul, R. A.
Forchheimer, O. L., Kling, R. P., and Boles, S. J. Hydration susceptibility and hydration of dead-burned dolomite grains, B (9) 291*a*.
Ford, D. L., and Kennard, W. W. Radiation sensitive evaporative analyzer, P (11) 348*a*.
Ford, R. W. See West, H. W. H.
Ford, W. D. See D'Eustachio, D.
Ford, W. F. Institute of Ceramics Textbook Series (4) Effect of Heat on Ceramics, B (1) 34*i*.
Ford Motor Co. Dispersion strengthened aluminum oxide with tungsten or molybdenum, P (5) 123*i*. Electroluminescent process including an ionically conducting electrolyte, P (2) 51*a*. Iron bonded tungsten carbide, P (8) 240*g*. Method and apparatus for preventing bubbles in float glass apparatus, P (10) 300*h*. Molding composition comprising a refractory material and, as a binder, the reaction product of formaldehyde, furfuryl alcohol, and a urea, P (4) 97*c*.
Forest, J. Study of local encrustation in rotary cement kilns and of belite (I, II), (9) 262*c*. Study of rings (I, II), (6) 165*h*.
Forland, T., and Thulin, L. U. Alkali-glass membrane as sodium electrode, (5) 126*g*.
Forlano, R. J., Allen, A. W., and Beals, R. J. Elasticity and anelasticity of uranium oxides at room temperature (II) hyperstoichiometric oxides, (5) 132*c*.
Forman, P. F., and Stoll, R. Metal to glass welding, P (4) 94*f*.
Forman, S. A., Kodama, H., and Abbey, S. Re-examination of xanthophyllite (clintonite) from the type locality, (4) 115*e*.
Formold Corp. Method for producing hollow ceramic articles, P (10) 306*e*.
Foroulis, Z. A. Effect of plastic deformation on the anodic dissolution of iron in acids, (7) 195*b*.
Forrat, F. Preparation of oriented monocrystals, P (9) 274*e*.
Forrest, N. Method of making a flexible mold, P (5) 144*d*.
Forrester, P. A. See McLaughlan, S. D.
Forsheda Gummifabrik Aktiebolag. Bell and spigot pipe joints and method of sealing and locking pipe joints, P (11) 337*f*.
Forshey, W. O., Jr., and Ring, H. F. Fibrous niobium carbide and nitride, P (4) 97*e*.
Forstat, H., Love, N. D., McElearney, J., and Weinstock, H. Magnetic transition in thiourea-coordinated cobalt chloride, (10) 323*e*.
Forster, H., and Seidler, R. Apparatus for continuous manufacture of continuous profiled glass members, P (1) 8*h*.
Fortes, M. A., Smith, D. A., and Ralph, B. Interpretation of field-ion micrographs—contrast from perfect dislocation loops, (8) 248*i*.
Foseco International, Ltd. Additives to sand molds and cores, P (7) 204*c*.
Foseco Trading Akt.-Ges. Method for forming hot top liners, P (8) 240*j*.
Foss, G. J. See Hart, A. W.
Foster, G. B. Noncontacting dynamic distance measurements, (3) 76*a*.
Foster, H. B. Method and composition for forming ceramic structures, P (3) 66*g*. Method of forming and firing a ceramic mass, P (11) 337*b*.
Foster, H. R. Glass polishing composition containing an inorganic barium salt, P (9) 265*d*. Method of making glass polishing composition, P (9) 265*d*.
Foster, L. H. See Blanding, W. S.
Foster, N. F. Method of forming a piezoelectric ultrasonic transducer, P (9) 273*b*.
Foster, P. A., Jr. Melting point of cryolite, (3) 83*a*.
Foster, R. W. Sources for lightweight shale aggregate in New Mexico, (7) 214*g*.
Foster, W. F. See Roberts, J. W.
Foster, W. R. Comment on the Ca_2SiO_4 phase diagram, (7) 216*e*.
Fouke, H. A. Refractor for use in uniformly illuminating a polygonal area, P (1) 10*b*.
Fournier, J. T. See Landry, R. J.
Fouse, F. Z. Dead plate conveyor for glass machines, P (7) 198*h*. Drive for glass-forming machines, P (9) 265*a*.
Fouse, W. H. Liquid-cooled holder for furnace electrode, P (8) 249*h*.
Fowler, J. W. See Bartlett, R. W.
Fowles, G. W. A. Spectroscopic techniques in chemistry, (1) 23*c*.
Foxboro Co. Consistency measuring apparatus, P (5) 147*a*.
Foyt, A. G. See Oliver, M. R.; Wolfe, C. M.
Frass, F. Magnetic separator with a combination field, P (8) 251*e*.
France, H. de, and Cahen, R. R. Color tube with triplet phosphor strips making 40° to 70° angle with horizontal, P (4) 99*f*.

Francel, J., and Pinotti, A. D. Color indicia for glass and method of applying same, P (7) 198*f*.
Franceschi, A. Use of room-temperature-cured silicone rubbers, (8) 242*c*.
Francis, T. L., and Coble, R. L. Creep of polycrystalline silicon carbide, (3) 79*d*.
Francois, B. See Chenebault, P.
Francois, B., Delmas, R., Caillat, R., and Lacombe, P. Qualitative relations between sintering rate of UO_2 in hydrogen and the observed microstructures, (8) 256*j*.
Frank, D. F. See Rapp, R. A.
Frank, R. I., and Moberg, W. L. Optical properties of reactively evaporated chromium oxide films, (3) 84*g*.
Frank-Kamenetskii, V. A., and Sosedko, T. A. Effect of annealing on the structure of alkaline beryls, (4) 108*g*.
Franklin, A. D. Born model calculation of enthalpies of solution in CaF_2, (1) 26*f*. See Hummel, F. A.
Franklin, A. D., Marzullo, S., and Wachtman, J. B., Jr. Surface-layer relaxation in the dielectric spectrum of CaF_2 doped with GdF_3, (4) 117*h*.
Franklin, A. G. See Krizek, R. J.
Franklin, W. Anharmonicity in the statistical dynamical theory of solid state diffusion, (6) 183*i*.
Franzen, H. F. See Gilles, P. W.
Franzen, H. F., Dejong, V. W., and Conard, B. R. New subsulfide in the Nb–S system, (4) 113*a*.
Franzen, H. F., and Gilles, P. W. High-temperature vaporization and thermodynamic properties of titanium monosulfide, (3) 81*d*.
Franzen, H. F., and Graham, J. Lower sulfides of hafnium at high temperature, (4) 112*c*.
Franzen, H. F., Smeggil, J., and Conard, B. R. Group IV ditransition metal sulfides and selenides, (4) 110*h*.
Fraser, D. B. See Dodd, D. M.
Fraser, D. B., Krause, J. T., and Meitzler, A. H. Physical limitations on the performance of vitreous silica in high-frequency ultrasonic and acoustooptical devices, (6) 176*g*.
Fraser, D. B., and Rudd, D. W. Method of testing the internal friction of synthetic quartz crystal by the use of two different frequencies of infrared, P (2) 51*h*.
Fray, A. F. See McLaughlan, S. D.
Fray, D. J. See Boyer, A. J. G.
Freas, D. H. See Mossman, M. H.
Frechette, V. D., and Cline, C. Laser damage in transparent glasses and crystals, B (10) 329*a*. Stimulation of thermoluminescence in LiF by ruby laser light, (4) 116*f*.
Freck, D. V., Rouse, R. L., and Wakefield, J. Method for producing *pin* semiconductors, P (7) 209*e*.
Fredley, J. C., and Sleighter, G. E. Method of heat treating glass sheets on a gaseous support bed, P (1) 9*c*.
Fredrick, R. E. Semiconductive alloy composition having thermoelectric properties, P (4) 101*e*.
Freed, B. A. See Sun, Shiou-Chuan.
Freed, C. See Wisniak, J.
Freed, K. F. See Huo, W. M.
Freedman, R. P. See Fetner, M. J.
Freel, J., and Galwey, A. K. Kinetic study of nickel carbide oxidation, (7) 219*b*.
Freeman, A. C. See Ellis, R. B.
Freeman, A. G. See Whitfield, H. J.
Freeman, I. L. Moisture expansion of structural ceramics (II) influence of composition, B (9) 291*f*.
Freeman Supply Co. Abrasive roll, P (5) 123*h*.
Freestone, R. C. See Pickavance, A.
Freiling, E. C. See Scheidt, R. C.
Freiman, S. W., and Hench, L. L. Kinetics of crystallization in Li_2O–SiO_2 glasses, (8) 232*e*.
French, C. S. Fluorescence spectra of sharp cutoff filters, (5) 145*b*.
French, D. W. Pipe joint, P (5) 131*b*.
French, J. F. See Lawver, J. E.
Frenchtown Porcelain Co. Manufacture of ceramic bases, P (4) 100*g*.
Frescura, B. L. Dielectric isolation process, P (10) 309*a*.
Freshley, M. D. See Halas, D. R. de.
Freund, F. Ceramic firing process (I) formation of water in the lattice of clay minerals; (II) dehydration of the lattice of clay minerals, (7) 215*h*. Dehydration of gibbsite and the formation of boehmite, (2) 57*j*. Infrared spectra of kaolinite, metakaolinite, and aluminum-silicon spinel, (3) 82*b*. Spontaneous formation of diaspore in partially dehydrated single crystals of gibbsite, (3) 86*j*.
Frick, G. See Widrow, B.
Frick, H. Economical dust extraction in the ceramic factory, (4) 101*i*.
Frick, R. G. See Cohn, E.
Fridkin, V. M., Groshik, I. L., Lyakhovitskaya, V. A., Mikhailov, M. P., and Nosov, V. N. Current saturation and photoferroelectric effect in SbSI, (3) 71*b*.
Fridman, A. A. See Brokhin, I. S.
Fridman, I. A. See Entin, Z. B.
Fridman, Ya. B. See Drozdovskii, B. A.
Fridman, Ya. D., Moshkina, V. A., Gorokhov, S. D., and Nitsevich, E. A. Formation and thermal dissociation of the fluoride and carbonate of yttrium, (10) 321*a*.
Friedberg, S. A. See Barros, S. de S.; Uryu, N.
Friedl, E. Factors affecting the rate of lining wear in the LD vessel, (6) 173*d*.
Friedman, A. I., and Beaumont, D. H. Halophosphate phosphor treatment process, P (8) 244*d*.
Friedman, G. M. Dynamic processes and statistical parameters compared for size frequency distribution of beach and river sands, (1) 28*e*.
Friedman, H. A. High temperature centrifuge for phase equilibrium studies in molten salts, (2) 54*h*.
Friedrich, H. See Hofmann, U.
Friend, P. F. Clay fractions and colors of some Devonian red beds in the Catskill Mountains, U.S.A., (1) 27*b*.
Friese, K. H. See Esper, F.
Frieser, R. G. Phase changes in thin reactively sputtered alumina films, (11) 355*f*.
Fripiat, J. J. Recent researches on clay minerals in Belgium and the Netherlands, B (6) 192*e*. Surface properties of aluminosilicates, B (6) 192*b*. See White, J. L.
Fripiat, J. J., and Faille, M. della. Surface properties and texture of chrysotiles, B (9) 289*f*.
Fripiat, J. J., and Helsen, J. Kinetics of decomposition of cobalt coordination complexes on montmorillonite surfaces, B (8) 259*c*.
Frisby, H. See Levavasseur, G.
Frisch, B. Abrasion of oxide ceramics under the influence of surfactants, (7) 210*j*. Grain orientation in columns of powder and sintered bodies under the effect of intermediate layers, (8) 254*c*.
Frisch, H. L. Isothermal diffusion in systems with glasslike transitions, (5) 127*h*.
Frisch, H. L., and Salsburg, Z. W. (editors). Simple Dense Fluids, B (9) 290*g*.
Frischat, G. H. Sodium diffusion in SiO_2 glass, (10) 298*d*. Volume and grain boundary diffusion of ^{22}Na and ^{45}Ca in polycrystalline Na_2O·$2CaO \cdot 3SiO_2$, (2) 60*a*.
Frischat, G. H., and Oel, H. J. Calcium self-diffusion in glassy and crystalline Na_2O·$2CaO \cdot 3SiO_2$, (8) 230*e*.
Frish, G. See Shkol'nikov, E. V.
Fritz, L., and Fritz, R. Magnetic separating apparatus, P (11) 345*j*.
Fritz, R. See Fritz, L.
Froberg, M. L. Method for processing heat-softened mineral material, P (10) 301*b*.
Froemel, J. G. See Sapoff, M.
Froemel, J. G., and Sapoff, M. Method of making a thermistor, P (4) 100*e*.
Froese, E. Strontium magnesium carbonate, (4) 116*j*.
Froese, E., and Winkler, H. G. F. System $CaCO_3$–$SrCO_3$ at high pressures and 500° to 700°C, (1) 33*b*.
Frolovskii, N. M., Genkin, V. Ya., et al. Service of zircon nozzles handling converter steel in a continuous casting plant, (9) 269*i*.
Frosch, C. J., Thurmond, C. D., White, H. G., and May, J. A. Effect of water pressure on the excess donor concentration in GaP grown from the vapor phase in silica tubes, (4) 108*h*.
Frounfelker, R. E. See Wackman, P. H.
Frova, A., and Boddy, P. J. Effect of strong electric fields on the electroreflectance spectrum, (11) 352*e*.
Fruchart, E. See Fruchart, R.
Fruchart, R. See Roger, A.
Fruchart, R., Bouchaud, J. P., Fruchart, E., Lorthioir, G., Madar, R., and Rouault, A. First order magnetic transitions in metallic perovskites of manganese, (4) 98*i*.
Frueh, A. J., and Golightly, J. P. Crystal structure of dawsonite, $NaAl(CO_3)(OH)_2$, (4) 107*e*.
Fryer, G. M. Hot-pressing of alumina—a new treatment of final densification, (1) 29*c*.
Fryer, G. M., and Roberts, J. P. Development of gas permeability in sintered alumina during tensile creep, B (7) 226*f*.
Fuchs, R. Electronic properties of the tungsten bronzes, (5) 138*f*. See Kliewer, K. L.
Fuchs, R. J. Process of sequestering metal ions with slowly soluble phosphate glasses, P (6) 171*c*.
Fuchs, R. J., and Lutz, C. W. Mixed-cation phosphate glasses, P (4) 95*f*.
Fuchs, W. See Crose, G. J.
Fuderer, A. Preparation of alumina with pretreatment of sodium aluminate liquor with alcohol vapors, P (8) 251*b*.
Fuechs, G. See Weingaertner, E.
Fueki, K., and Wagner, J. B., Jr. Oxidation of manganese in CO_2–CO mixtures, (4) 113*f*. Oxidation studies on Ni and on a 0.37% Cr–Ni alloy in CO_2 and in CO_2–CO mixtures, (4) 113*g*.
Fuentes Guerra, R. Ceramics and glass in the Cerralbo Museum (Madrid), (10) 293*i*.
Fuhrman, P. K. See Englert, W. J.
Fujii, Y. See Sakudo, T.
Fujimoto, M., and Sato, Y. P-T-x phase diagram of the lead telluride system, (5) 157*i*.
Fujimura, M. See Matsuo, Y.
Fujimura, Y. See Tagai, H.
Fujisawa, H. See Sawaoka, A.
Fujitsu, Ltd. Method and apparatus for vapor deposition employing an electron beam, P (1) 18*j*. Method of making semiconductor devices by diffusing and forming an oxide, P (11) 344*b*. Method for measuring the specific resistance of a silicon crystal by measuring the breakdown voltage, P (5) 142*c*. Method of producing silicon variable capacitance diodes by diffusion, P (10) 310*k*.
Fujiwara, H. Estimation of perpendicular anisotropy of magnetic thin films originating from nonmagnetic grain boundaries, (3) 80*j*.
Fujiwara, S. Ceramic dielectrics, P (2) 50*h*.
Fujiwara, S., Hayashi, S., and Kawakami, K. Ceramic dielectrics, P (2) 50*i*.
Fujiwara, S., and Shiraiwa, T. Ceramic dielectrics, P (1) 17*b*.
Fukase, M. See Ida, I.
Fukuda, M. See Ida, I.
Fukui, T. See Tanaka, T.
Fukunaga, O., and Saito, S. Phase equilibrium in the system CrO_3–Cr_2O_3, (8) 255*j*.
Fukuoka Tokushugarasu Kabushiki Kaisha. Method and apparatus for manufacturing glass beads, P (4) 94*i*.
Fukushima, E. See Nishijima, T.
Fulk, W. F. See Smock, G. E.
Fuller, C. R. See Brown, G. A.
Fuller, J. E., and Edwards, L. W. Time-temperature programing a furnace system, (4) 103*d*.
Fuller, R. A. Heating section of decorating lehr, P (9) 265*f*.
Fuller, R. G. Diffusion of the chlorine ion in potassium chloride, (8) 253*a*.
Fulrath, R. M. See Bertolotti, R. L.; Rossi, R. C.; Stett, M. A.
Fulrath, R. M., and Hollar, E. L. Manganese glass-molybdenum metallizing ceramics, (6) 166*c*.
Fuls, E. N., Henaler, D. H., and Ross, A. R. Reactively sputtered vanadium dioxide thin films, (4) 115*b*.
Funahashi, Z., Nameishi, N., and Yanagida, K. Proposed design of linings for use in hot-blast stoves, (9) 268*d*.
Funke, G., and Fischer, H. A. Results of dust measurements on cement kilns, (2) 36*h*.
Funke, V. F., Tumanov, V. I., and Panov, V. S. Structure and physical properties of the alloys WC–TaC–Co and WC–NbC–Co, (7) 203*d*.
Funtikov, V. I., Kolbasov, V. M., and Kuznetsova, M. N. Phosphorus slags for the production of hydrothermally hardening binders, (6) 165*h*.
Furer, C. C. Glass gripping tongs with ballast, P (10) 300*b*.
Furlong, R. B. Electron diffraction and microgaphic study of the high-temperature changes in illite and montmorillonite under continuous heating conditions, B (9) 289*f*.
Furnanage, R. A., and Wilson, D. K. Junction diode maser, P (4) 100*e*.
Furnas, T. C., Jr. X-ray diffraction mechanism in which a monochromator diffracts the X-ray beam in planes transverse to an axis of specimen rotation, P (10) 316*h*.
Fursman, O. C., Blake, H. E., Jr., and Mauser, J. E. Recovery of alumina and iron from Pacific Northwest bauxites by the Pedersen process, (6) 182*g*.
Furukawa, Y., and Ishibashi, Y. Transient phenomena in the capacitance of GaAs Schottky barrier diodes, (5) 140*f*.
Furukawa, Y., and Kakuda, N. Silicon single crystal pulled by eccentric seeding method, (5) 139*j*.
Furumi, K. See Koide, Y.
Furumi, K., and Ohishi, M. Use of basic refractory brick in a reverberatory furnace for refining of tin, (10) 304*g*.
Furumoto, S. See Ida, I.
Furuseth, S., Selte, K., and Kjekshus, A. Solid solubility and structural properties of $PdAs_{2-x}Sb_x$, $PtP_{2-x}As_x$, $PtP_{2-x}Sb_x$, $PtP_{2-x}Bi_x$, $PtAs_{2-x}Sb_x$, $PtAs_{2-x}Bi_x$, $PtSb_{2-x}Bi_x$, $Pd_{1-m}Pt_mAs_2$, $Pd_{1-m}Pt_mSb_2$, $Pd_{1-m}Au_mSb_2$, and $Pt_{1-m}Sb_2$, (7) 221*j*.
Furuya, H. See Yajima, S.
Fuschillo, N. See Garner, P. L.
Fushimi, S., and Ikeda, T. Elastic properties of barium titanate single crystal above the Curie point, (5) 151*b*. Optical study of lead zirconate-titanate, (3) 84*g*.
Fussell, L. E., and Lever, R. C. Challenge to porcelain enamel, (2) 37*i*.
Futami, K. See Tanaka, T.
Fuwa, K. See Vallee, B. L.

Gabelnick, S. D. See Riebling, E. F.
Gad, G. See Gharib, N.; Hussein, A. T.
Gad, G., and Gharib, N. Vermiculite insulating refractories, (5) 134*a*.
Gad, G., and Maksoud, M. A. Constitution and suitability of Kharga clays, (3) 79*j*.
Gadalla, A. M. M. Discussion—a note on the system Cu–Pb–O, B (7) 226*d*. See El-Shahat, F. M.
Gaddis, D. H., and Hopkins, V. Inorganic solid film lubricants, P (11) 349*j*.
Gado, E. Method of producing concrete of improved strength, P (9) 262*c*.
Gaffard, J. P. Method and apparatus for detecting flaws in transparent [planar] bodies, P (4) 94*h*.
Gagne, R. See Sieger, J. S.
Gagnon, R. See Woolley, J. C.
Gagnon, R. K., and Lachut, F. J. Coating method for glass fabric and product thereof, P (3) 65*e*.
Galdukova, V. S. See Imashev, M. K.
Gaiger, J. Recent problems with sheet steel enamels and their practical solution, (5) 126*d*.
Gaindhar, J. L. See Kumar, R.
Gaines, G. L. See Bergeron, J. A.
Gajewski, H. M. See Elarde, V. D.
Galabert, P., and Pillon, M. Apparatus and method for cutting glass, P (2) 40*b*.
Galan, A. Estimate of concrete strength by ultrasonic pulse velocity and damping constant, (2) 36*j*.

Galanulis, E., and Scholze, H. Gas analysis study of the mechanism of bubble formation in glazes, (7) 206*c*.

Galasso, F. S., Douglas, F. C., and Kasper, R. J. Relationship between magnetic Curie points and cell sizes of solid solutions with the ordered perovskite structure, (7) 221*d*.

Galasso, F. S., Layden, G. K., and Flinchbaugh, D. E. $Ba(B_{0.5}Ta_{0.5})O_3$ ordered perovskite-type compounds, possible new laser host materials, (5) 137*g*.

Galdina, N. M., Gutman, V. I., Fedorenko, V. A., and Babichev, N. I. Fused cast refractories with high ZrO_2 content, (8) 237*b*.

Galdina, N. M., Verlotskii, A. A., Rogovoi, M. I., Rublevskii, I. P., and Izosenkova, A. V. Calculation analysis of the behavior of sand-marshalite molds during the pouring of bakor-33 melt, (10) 302*e*.

Galeev, G. S. See Fialkov, A. S.

Galer, R. E. Gaseous apparatus for cooling pulverulent material, P (4) 92*c*.

Galey, W. F. Method of controlling the thickness of float glass, P (3) 65*d*. Method of shifting glass on a molten metal bath, P (3) 66*d*. See Sensi, J. E.

Galichanskii, V. G. See Belotskii, D. P.

Galichon, M. Electrical conductivity of solids, (3) 71*f*.

Galigher Co. Corrosion-proof [rubber] lining for metallurgical grinding mills, P (7) 214*c*.

Galkin, Yu. M., and Chukhlantsev, V. G. Subsolidus structure and ternary compounds of the $BaO–ZrO_2–SiO_2$ system, (6) 189*d*.

Galkina, I. P. See Poluboyarinov, D. N.

Gallagher, P. K. Simple technique for the preparation of rare earth FeO_3 and rare earth CoO_3, (6) 181*d*.

Gallagher, P. K., and Kurkjian, C. R. Study of the thermal decomposition of some complex oxalates of iron(III) using the Moessbauer effect, (5) 158*g*.

Gallagher, P. K., MacChesney, J. B., and Buchanan, D. N. E. Moessbauer effect in the system $BaFeO_{2.5-3.0}$, (6) 187*h*. Moessbauer effect in the system $SrFeO_{2.5-3.0}$, (5) 155*h*. Moessbauer effect in the system $Sr_3Fe_2O_{6-7}$, (10) 323*d*.

Gallet, J. P., and Paris, R. A. Thermometric studies of complex formation with iron(III), aluminum, and gallium (I) oxalates and malonates, (2) 55*i*.

Galli, A. F. See Bluman, D. E.

Gal'perina T. Ya. See Bogomolov, B. N.

Galwey, A. K. See Freel, J.

Galy, J. See Vandeven, V.

Gambell, J. W. See Michaels, G. O.

Gambino, R. J. See Lorenz, M. R.

Gambino, R. J., and Cuomo, J. J. Preparation of rare earth nitrides by reactive arc melting, (7) 214*f*.

Gambino, R. J., Holtzberg, F., and Methfessel, S. J. Ferromagnetic compounds and method of preparation, P (1) 17*i*.

Gamble, J. R. Porcelain casing bead construction, P (3) 70*g*.

Gamblin, R. L., and Tunis, C. J. Variable weighted threshold element system, P (11) 345*d*.

Ganapathy, C. V. See Ramanath, T. V.; Ramamurthi, T. V.

Ganguli, D., and Saha, P. Reconnaissance of the system $BeO–Al_2O_3–SiO_2–H_2O$, (5) 157*g*.

Ganichev, A. A. See Bushkovich, S. N.

Gannon, J. J. See Nuese, C. J.

Gannon, R. E. See Laszlo, T. S.

Gantzel, P. K. See Langer, S.

Garabedian, F. See Croft, W. J.

Garashin, V. R. See Larionova, Z. M.

Garbrah, B. W., and Whitley, J. E. Determination of boron in glass by thermal neutron capture gamma ray analysis, (5) 127*a*.

Garcia Alvarez, J. M. See Garcia Verduch, A.

Garcia Verduch, A., Garcia Alvarez, J. M., and Gomis Noguera, F. J. Microstructure of a triaxial porcelain, (10) 306*a*.

Gardille, E. Composition for accelerated grinding, P (1) 1*g*.

Gardiner, J. A. Size analyzer for images and particles, (5) 146*i*.

Gardner, A. R. Flat glass made to order, (5) 127*a*. New bonding agents, (11) 349*a*.

Gardner, N. R., Donaldson, A. D., and Yans, F. M. Extrusion of metal powders, B (3) 89*i*.

Gardner, T. E., and Taylor, A. R., Jr. High-temperature heat contents and entropies of sodium bromide and sodium iodide, (4) 111*j*.

Gardner, W. J. Nozzle for a bottom pour ladle for molten metal, P (11) 340*d*. See Cahoon, J. B., Jr.

Gardner, W. L. Method of making a vitreous off-axis light filter, P (8) 235*i*.

Garey, M. J. See Rice, H. H.

Garg, S. P. See Ramachandran, V. S.

Garnache, R. R., and Vogel, F. L., Jr. S-M-S device with partial semiconducting layers, P (7) 210*a*.

Garner, G. M., and Cowlard, F. C. Process for the preparation of high-purity alumina, B (4) 122*c*.

Garner, L. E. Sand resources of Texas gulf coast, (7) 214*g*.

Garner, P. L., and Fuschillo, N. Method of making tunnel diode, P (7) 209*j*.

Garno, J. P., and Nanney, C. A. Method of making low resistance ohmic contact to *p*-type lead telluride, P (4) 100*d*.

Garrels, R. M. See Mackenzie, F. T.

Garrett, C. G. B. See Merritt, F. R.

Garrett, H. J. See Ruh, R.

Garrett, H. J., and Ruh, R. Fabrication of specimens from pure dense oxidized zirconia, (7) 201*i*.

Garrett, M. B., Lee, P. S., and Kay, J. G. Flash heating and kinetic spectroscopy of $KMnO_4$, (10) 321*e*.

Garrett, W. G. See Walker, G. F.

Garrison, J. W. Apparatus for forming fibers, P (6) 170*c*.

Garrison, L. G. See Eichhorn, E.

Gartner, S. J. See Chagnon, P. L.

Garver, E. E. See Hyde, B. G.

Garvie, R. C. Cubic field in the system $CaO–ZrO_2$, (11) 351*f*.

Garwacki, W. See Aven, M.

Gaskell, D. R., and Ward, R. G. Density of iron oxide-silica melts, (4) 107*g*.

Gaskell, P. H. Thermal properties of silica (I) effect of temperature on infrared reflection spectra of quartz, cristobalite, and vitreous silica; (II) thermal expansion coefficient of vitreous silica, (3) 87*d*. Vibrational spectra of silicates (I), (1) 33*i*.

Gasparac, R. J., and Szaj, A. P. Feeders for crushers, etc., P (8) 251*b*.

Gasparac, R. J., and Zoerb, H. M. Feeder for cone crushers, etc., P (4) 105*b*.

Gasson, D. B. See Cockayne, B.

Gast, R. G., and East, P. J. Potentiometric, electrical conductance, and self-diffusion measurements in clay-water systems, B (6) 192*a*.

Gastel, D. G., DeLisle, M., and Morgan, JR. Some effects of progressive metamorphism on zircons, (4) 116*c*.

Gastner, M. See Quakernaat, J.

Gastuche, M. C. Octahedral layer, B (6) 192*e*.

Gates, L. O. See Davidson, J. M.

Gates, P. E. Single ended quartz type incandescent lamp, P (2) 42*d*. See Dayton, D. R.

Gatos, H. C. See Morizane, K.

Gatti, A. See Mullin, J.

Gatzke, H. Application of rapid firing to suit the operation and the materials, (5) 136*g*.

Gaudette, H. E., Eades, J. L., and Grim, R. E. Nature of illite, B (7) 224*a*.

Gaudlitz, A. Point-contact diode with Au-Pt point, P (3) 74*a*.

Gaur, J. N. See Goswami, N. K.; Jain, D. S.

Gaur, N. K. S., and Verma, G. S. Infrared absorption due to donor electrons in semiconductors, (10) 322*e*.

Gautherie, M. See Goldsztaub, S.

Gay, P. W. Unit labor cost measurement, (3) 70*d*.

Gayet, B., Holder, J., Kurka, G., Reboux, J., and Trouve, J. Induction melting process of central core portion of cylindrical shaped refractory materials, P (2) 47*c*.

Gayner, N. Colors and what may affect them, (4) 91*f*.

G.B.D. Soc. Anon. Holding. Glass tank furnace wall structure, P (1) 9*d*.

Geballe, T. H. See Matthias, B. T.

Gebefuegi, I. Kneading pretreatment for the production of aluminum hydroxide, P (3) 68*h*.

Gebert, E. See Hoekstra, H. R.

Gebert, E., and Ackermann, R. J. Substoichiometry of tungsten trioxide—the crystal systems of $WO_{2.90}$, $WO_{2.92}$, and $WO_{2.94}$, (5) 158*g*.

Gebhardt, E., and Rexer, J. Structure of the system $ZrCr_2–TaCr_2$, (4) 116*f*.

Gebhardt, F., and Sistermanns, A. Determination of sulfate in soda-lime-silica glasses by combustion in oxygen, (8) 231*f*.

Gebrueder Netzsch. Apparatus for shaping pottery in revolving ceramic-mass-containing molds, P (9) 271*c*.

Geguzin, Ya. E. See Lifshitz, I. M.

Geick, R., Perry, C. H., and Rupprecht, G. Normal modes in hexagonal boron nitride, (11) 355*b*.

Geiger, B. Mario Mascarin, (5) 124*b*. Swiss handicraft ceramics, (4) 91*h*.

Geisenheyner, R. M. What's new in bulk shipments of dry flowables, (3) 75*b*.

Gejyo, T. See Minagawa, S.

Gelas, B. de. See Beranger, G.

Geld, I., Deutsch, L., and D'Oria, F. J. Comparison of inhibitive abrasive blasting techniques, (11) 331*g*.

Gel'd, P. V. See Alyamovskii, S. I.; Andreeva, L. P.; Krentsis, R. P.; Volkova, N. M.

Geller, M., Altman, D. E., and DeTemple, T. A. Two-photon absorption in alkali halides with a pulsed N_2 laser, (11) 357*j*.

Geller, S., Romo, P., and Remeika, J. P. Refinement of the structure of scandium sesquioxide, (8) 256*d*.

Gelsing, R. J. H. Vitreous alkali tungstates, (2) 40*f*.

Geltman, G. Explosive compacting of metal powders, B (3) 89*h*. Fabricating yttria stabilized zirconia, (3) 71*h*.

Gem Clay Forming, Inc. Artificial logs for fireplaces, P (7) 204*f*.

Gendler, T. S., Mitrofanov, K. P., Piotnikova, M. V., Tykachinskii, I. D., and Fedorovskii, Ya. A. Study of initial crystallization stages of glass by Moessbauer effect, (8) 234*i*.

General Dynamics Corp. Apparatus and method of measuring molten metal temperature, P (5) 134*c*.

General Electric Co. Apparatus for determining aerosol particle size comprising a combined diffuser-denuder, P (2) 55*c*. Arc discharge lamp having polycrystalline ceramic arc tube, P (4) 99*c*. Blue electroluminescent phosphor and its production, P (9) 272*i*. Bonding diamond to molybdenum, P (7) 193*g*. Brazing lead telluride thermoelectric generator elements, P (8) 243*j*. Cellular material and method for making, P (1) 12*i*. Centrifugally cast hollow glass body, P (7) 198*d*. Composite body and method of making, P (7) 208*h*. Container for molten fused silica, P (2) 46*j*. Control means for sequencing glass scoring means, P (1) 8*h*. Decorative pulsating flame incandescent lamp, P (8) 235*f*. Double heat sink semiconductor diode with glass envelope, P (8) 244*a*. Electric circuit breaker comprising ceramic capacitor elements connected in parallel with its contacts, P (8) 244*a*. Electric discharge lamp envelope having molten inner surface at operating temperature, P (9) 265*a*. Electrical capacitor, P (5) 141*a*. Electron discharge device having a barium dispensing anode structure, P (1) 17*g*. Electron discharge device and method, P (3) 72*e*. Evaporative application of metal coatings to diamond, P (7) 193*j*. Fiber optics scan system, P (9) 265*c*. Filament supports for tubular incandescent lamps, P (9) 265*c*. Glass encapsulated double heat sink diode assembly, P (4) 100*b*. Graphite-catalyst charge element for the preparation of diamond, P (1) 1*h*. Green electroluminescent zinc sulfide phosphor, P (6) 177*b*. Halophosphate phosphor treatment process, P (8) 244*d*. Heat treating pyrolytic graphite and boron nitride bodies with simultaneous application of multiaxial tension, P (2) 47*a*. High density magnesium compounds and their preparation, P (1) 18*c*. High density urania fuel elements, P (1) 12*h*. High efficiency semiconductor light emitter, P (2) 51*c*. High power junction laser structure, P (4) 100*c*. High pressure saturation sodium vapor lamp containing mercury, P (8) 235*b*. Incandescent lamp with a tungsten filament with tantalum imbedded in the surface to act as a gettering agent, P (1) 18*c*. Irradiated nuclear fuel recovery, P (4) 97*f*. Luminaire with optical refracting members, P (11) 336*c*. Magnetic field responsive superconducting tunneling devices, P (5) 141*d*. Mercury metal halide discharge lamp having iodine present in stoichiometric proportions with respect to the reactive metals, P (8) 235*f*. Metal-bonded diamond abrasive body, P (3) 61*g*. Metal vapor lamp coating, P (6) 171*b*. Method for the deposition of an electroconductive transparent indium oxide coating, P (3) 73*c*. Method of making electrical heating elements, P (3) 73*b*. Method of making a polycrystalline dual layered aluminum oxide-magnesium oxide storage electrode, P (7) 209*h*. Method of making superconducting wire, P (10) 310*c*. Method for making thin film glass elements, P (7) 209*i*. Method of preparing uranium [ammonium] diuranate, P (11) 340*c*. Method for producing high critica. field superconducting circuits, P (2) 51*c*. Method of purifying zinc and cadmium chalcogenides, P (8) 245*f*. Monopole mass spectrometer having one ceramic electrode coated with metal to within a short distance of each end, P (2) 55*g*. Multilayer contact system for semiconductor devices including gold and copper layers, P (5) 142*j*. Optically round mechanically ovate reflector with radially stepped sections, P (11) 336*c*. *PnPn* switch with $0 < (N_B/N_E) < 100$ so that conductivity modulation results during turnoff, P (3) 73*j*. Power bulk breakdown semiconductor devices, P (5) 142*b*. Preparation of halophosphate phosphor, P (7) 210*a*. Preparation of thorium pyrophosphate, P (2) 52*b*. Process of coating diamond with an adherent metal coating using cathode sputtering, P (2) 52*d*. Process for the conversion of calcium acid phosphate dihydrate to calcium acid phosphate,P (11) 349*d*. Process for making *n*-type zinc cadmium sulfide electroluminescent material, P (6) 178*e*. Process for preparing highly crystalline alpha strontium acid phosphate, P (8) 251*d*. Process for producing finely divided calcium fluoride having controlled particle size, P (3) 74*b*. Protective ceramic coating, P (11) 332*j*. Reflector discharge lamp having frosted envelope and arc [quartz] tube, P (8) 236*b*. Sandwiched construction for a tunnel diode, P (3) 74*e*. Selenotelluride *pn* junction device utilizing deep trapping states, P (9) 274*h*. Self-contained battery-powered electric incandescent lamp, P (8) 236*b*. Semiconductive junction laser with temperature compensation, P (4) 101*e*. Semiconductor contact diode, P (7) 210*e*. Semiconductor devices, P (3) 74*g*. Semiconductor junction laser device, P (4) 101*a*. Semiconductor testing, P (7) 210*f*. Semiconductor tunnel diode device, P (7) 210*g*. Silicon carbide luminescent material, P (4) 101*a*. Single crystal phosphide production, P (7) 210*h*. Single cycle irradiated fuel reprocessing, P (3) 69*f*. Strontium magnesium orthophosphate phosphors, P (11) 345*g*. Synthesis of calcium chlorspodiosite, P (7) 210*b*. Synthesis of halophosphate phosphors using calcium chlorspodiosite, P (7) 210*c*. Temperature compensated semiconductor strain gage, P (5) 143*d*. Ternary metallic oxide agglomerate and method of preparation, P (6) 175*c*. Variable capacitance force measuring transducer, P (8) 246*h*.

General Electric Co., Ltd. Conveyor arrangements, P (6) 179*g*. Processes involving the melting of semiconductor materials, P (2) 52*h*. Semiconductor junction devices which include wafers having beveled edges, P (4) 101*g*.

General Instrument Corp. Method of improving the photoconducting characteristics of layers of photoconductive material, P (10) 310*f*. Testing apparatus for a sequence of transistors, etc., having a condition responsive marker, P (1) 19*b*.

General Kinematics Corp. Method and apparatus for agglomerating on inclined surfaces including vibrating the material at a greater angle than the inclination of the surface, P (5) 144*c*.

General Magnesite Handels-Anstalt. Tar-bonded refractory bricks, blocks, and masses of burned magnesia, P (2) 48*c*.

General Motors Corp. Corrosion-resistant coating for magnesium die castings, P (7) 195*a*. Creepage spark type plug having low voltage igniter seal, P (1) 17*e*. Furnace and burner for testing temperature probes, P (11) 347*i*. High-temperature alumina-to-niobium article, P (9) 273*e*. Method of calcining aluminum hydroxide by cross-flowing the heating gas, P (8) 251*f*. Method of manufacturing a spark gap semiconductor, P (7) 209*a*. Method of producing a transducer, P (8) 245*d*. Radial flow regenerator matrix formed from ceramic blocks and the method of making, P (5) 136*e*. Spark plug center electrode with a split truncated head, P (1) 16*a*. Spark plug seal having a lower coefficient of expansion than the ceramic insulator core, P (1) 19*d*. Spark plug with a conductive glass seal electrode of glass, copper, and zinc, P (2) 52*f*. Spark plug with the insulator tip coated with a lead oxyhalide, P (1) 19*c*. Stacked dish infrared surface heating unit, P (3) 77*b*. Thermocouple probe with plural junctions, P (10) 316*g*. Visual indicating spark plug with an integral gas lamp, P (1) 19*d*.

General Refractories Co. Precast taphole assembly, P (11) 340*e*. Refractory brick and method of making, P (7) 205*c*.

General Refractories, Ltd. Bonded refractory materials, P (7) 204*h*. Refractory brick and their manufacture, P (5) 136*a*.

General Telephone & Electronics Laboratories, Inc. Electroluminescent translator utilizing thin film transistors, P (7) 208*e*. Method for the formation of thin films, P (5) 141*h*. Method of preparing vanadate phosphors, P (3) 73*e*. Method of preparing yttrium oxide phosphors, P (5) 142*d*. Piezoelectric-electroluminescent display device containing nonlinear resistance layer, P (7) 209*i*. Rare earth activated indium borate cathodoluminescent phosphors, P (10) 311*a*. Solid state triode having gate electrode subtending a portion of the source electrode, P (4) 101*c*.

Genkin, V. Ya. See Frolovskii, N. M.

Gentile, A. L., and Andres, F. H. Constant temperature method for the growth of KTN single crystals, (1) 27*f*.

George, A. M. See Karkhanavala, M. D.

George, C. R. See Johnson, B. J.

George, D. Development of a pilot plant for the manufacture of uranium monocarbide pellets, (11) 337*i*.

George, L. C., Jensen, J. W., and Doerr, R. M. Vapor pressure of metal halides—the $SnCl_2$–$ZnCl_2$ binary system, (4) 118*j*.

George, P. F. Marriage of the porcelain-lined tank and the magnesium anode, (9) 263*a*.

George, T. M. See Radhakrishnan, K.

George, W. Electrical measurements, B (4) 122*f*.

Georgia Kaolin Co. Aluminosilicate pigment, P (10) 317*g*. Insulating compositions containing heat tempered montmorillonite-free kaolin, P (5) 137*f*. Production of low viscosity kaolins by controlled blending of high viscosity kaolins, P (10) 318*d*.

Georgia-Pacific Corp. Cement composition and products thereof, P (11) 332*c*.

Georgia Tech Research Institute. Specimen mounting device for porosity determination apparatus, P (2) 55*g*.

Geppert, D. V. See Dore, B. V.

Gerard-Hirne, J., and Lazennec, Y. Measurement of thermal conductivity of thin refractory coatings, B (9) 291*d*.

Gerasimova, G. I. See Bil'tyukova, E. P.

Gerbaux, X. See Hadni, A.

Gerhard, G. C., and Jensen, H A. $GaAs_{1-x}P_x$ negative-resistance light-emitting diode, (5) 152*i*.

Gerhardt, R. F. Glass container having metal oxide and resin coatings, P (7) 198*f*.

Gerlach, J. K., and Pawlek, F. E. Kinetics of chlorination of metal sulfides, (3) 77*i*.

German, W. L. Training of technologists, (7) 223*f*. See Ratcliffe, S. W.

Gero, T. New method of preparing asbestos cement, (7) 202*c*.

Gerrard, W., Mooney, E. F., and Peterson, W. G. Alkoxyboron difluorides and dichlorides—preparation, structure, and spectroscopic properties, (5) 149*j*.

Gerson, R. See Smith, R. T.

Gerton, M. E. Catalyzed gypsum wallboard and its production, P (6) 165*i*.

Gertz, U. Ceramic artists and their work—Gisela Schmidt-Reuther, (10) 293*h*.

Gervais, H., Cella, C., and Spritzer, C. Low temperature X-ray diffraction chambers, (4) 103*a*.

Gery, M. See Eyraud, M. C.

Geschwind, G. Low-temperature electrical conductivity in calcium-doped lithium fluoride, (10) 322*e*.

Getto, A. Process controls in ferrite core manufacturing, (3) 72*b*. Recent innovations in processing and control of ferrite core manufacturing, (7) 207*j*.

Geusic, J. E. See Bonner, W. A.

Geusic, J. E., Levinstein, H. J., Rubin, J. J., Singh, S., and Van Uitert, L. G. Nonlinear optical properties of $Ba_2NaNb_5O_{15}$, (11) 355*a*.

Geuze, E. C. W. A, and Rebull, P. M. Mechanical force fields in a clay mineral particle system, B (8) 259*a*.

Geyndt, R. de. Method of sampling shaped refractories on receipt (except fused cast products), (11) 338*a*.

Ghanekar, K. M., and Sladek, R. J. Piezoresistance and piezo-Hall effects in *n*- and *p*-type aluminum antimonide, (11) 355*b*.

Gharib, N. See Gad, G.

Gharib, N., and Gad, G. Aluminosilicate insulating refractories, (5) 131*d*.

Gheorghiu, G., Sorocopud, L., Ventel, V., and Sergiu, P. Manufacture of blast-furnace refractories, (9) 267*g*.

Ghosal, J. G. Improved refractory and heat insulating panel for lining furnaces, etc., P (5) 135*f*. Process for the manufacture of alumina cements for refractory purposes, P (5) 135*j*. Process for the manufacture of refractory grade reactive alumina, P (5) 136*b*.

Ghosh, A. Measurement and recording of gas flows with capillary flow elements, (2) 54*c*.

Ghosh, A. K. Color centers in aluminoborate glass, (4) 93*d*. Occurrence of glassmaking sands near Churulia, Burdwan district, West Bengal, (1) 6*d*. Optical spectra of thallium in glasses as related to crystals and solutions, (4) 93*h*. Ultraviolet absorption of glass, (5) 129*f*. See Delbecq, C. J.

Ghosh, D. K. See Bishui, B. M.

Ghosh, R. K. See Jagas, P. J.

Ghosh, S. K. See Roy, A. K.

Ghosh, S. K., Mukherjee, A., and Roy, H. Studies on some Indian limestones (I) mineralogical investigation, (6) 189*b*.

Ghoshtagore, R. N. Method for determining silicon diffusion coefficients in Si and Si compounds, (11) 354*e*.

Giachi, A. Ceramic artists and their work—Hubert Griemert, (1) 1*i*; Sabine Naske, (10) 293*h*.

Giammanco, R. P. Process of growing silicon carbide *pn* junction electroluminescing diodes using a modified traveling solvent method, P (11) 345*d*.

Gibart, P. See Villers, G.

Gibb, T. C. See Banerjee, S. K.

Gibb, T. R. P., Jr. See Messer, C. E.

Gibbon, C. F. Grain boundary energies in NaCl in the rigid lattice approximation, (6) 186*a*. Technique for measuring grain boundary mobility and its application to KCl, (6) 189*j*.

Gibbons, R. C. Three-dimension X ray, (7) 213*a*.

Gibbs, G. B. Activation parameters for dislocation glide, (4) 105*i*.

Gibbs, G. V. Polymorphism of cordierite (I) crystal structure of low cordierite, (2) 59*a*.

Gibbs, J. H. See Adam, G.

Gibbs, R. J. Clay mineral mounting techniques for X-ray diffraction analysis—a discussion, (8) 247*j*.

Gibbs, W. E. K., and Whitcher, R. E. Polarization effects in a rooftop ruby laser, (5) 139*i*.

Gibeaut, W. A., and Bartlett, E. S. Properties of coated refractory metals, B (7) 225*f*.

Gibson, H. B. See Logan, M. C.

Gibson, R. F. See Roberts, J. W.

Gidwani, N. S. Method and apparatus for eliminating arcing in gas-electric sealing of TV bulbs, P (4) 94*h*.

Gie, O. T. See Andreas, F.

Gielisse, P. J. See Marshall, R.

Giesekus, H., and Schnoering, H. Process for the [continuous] production of highly pure semiconducting selenium materials, P (3) 74*b*.

Gieskieng, D. H. See Iten, H. C.

Giess, E. A., Burns, G., O'Kane, D. F., and Smith, A. W. Ferroelectric and optical properties of $KSr_2Nb_5O_{15}$, (6) 176*i*.

Giessen, A. A. van der. Magnetic properties of ultrafine iron(III) oxide-hydrate particles prepared from iron(III) oxide-hydrate gels, (8) 255*d*. See Cordfunke, E. H. P.

Giessen, B. C. Rapidly quenched (splat-cooled) alloys, B (4) 121*g*.

Giffen, J. W. Apparatus for forming articles from overlapping glass sheets, P (1) 8*i*.

Gifford, F. E., and Hill, R. F. Thermionic emitters consisting of BaO–UO_2 dispersed in a tungsten matrix, (4) 118*e*.

Gifford, F. E., and Williams, C. W. Method of producing a transducer, P (8) 245*d*.

Gifkins, R. C. Diffusional creep mechanisms, (3) 80*d*.

Gilard, P. See Mairlot, H.

Gill, L. D. Substantially anhydrous ceramic glazes in propellant-type cans, P (8) 242*f*.

Gilles, J. C. See Collongues, R.

Gilles, P. W. Discrepancies in the thermodynamics of the titanium-oxygen system, (11) 351*e*. See Franzen, H. F.; Smith, P. K.; Wahlbeck, P. G.

Gilles, P. W., Carlson, K. D., Franzen, H. F., and Wahlbeck, P. G. High-temperature vaporization and thermodynamics of the titanium oxides (I) vaporization characteristics of the crystalline phases, (11) 353*b*.

Gillin, L. M. Deformation characteristics of nuclear grade graphite, (7) 201*c*.

Gillis, R. P., and Quint, S. M. Apparatus for forming asbestos cement pipes, P (9) 275*f*.

Gillott, J. E. Clay mineralogy in building research (extended abstract), B (5) 161*a*. See Swenson, E. G.

Gillson, J. L. See Bither, T. A.

Gilman, J. J. Microscopic theory of plastic flow and impact (extended abstract), B (4) 121*g*. Nature of ceramics, B (11) 358*h*.

Gilman, W. S. Piston-type mortar and pestle for pulverizing ceramics, (5) 145*h*. Preparation of CeO_2 hollow microspheres, (9) 275*f*.

Gilmer, T. E., Jr. See Reaves, H. L.

Gilmore, G. B. See Siegmund, W. P.

Gingley, D. W. See Adamson, L. G.

Ginsberg, H., and Wefers, K. Thermochemical study of the system NaF–AlF_3, (3) 87*f*.

Ginsburg, L. High temperature vacuum firing porcelain furnace, P (8) 249*g*.

Ginther, R. J. Thermoluminescent glass and method of preparing, P (11) 336*h*.

Ginzburg, D. B., and Rapoport, A. Ya. New method for calculating the flow of molten glass, (6) 168*c*.

Ginzburg, D. B., Rapoport, A. Ya., El'kin, G. B., Shkiyar, Ya. V., and Pistsov, Yu. N. Heat exchange in the combustion area of a glass melting furnace, (6) 167*i*.

Giordano, N. See Ferlazzo, N.

Giordi, A. L., and Szklarz, E. J. Superconductivity of technetium and TcC, (4) 117*g*.

Giorgi, T. A. See Della Porta, P.

Girard, R. T., Sims, C. T., and Wisely, H. R. Protective ceramic coating, P (11) 332*j*.

Giraudy, M. European porcelain from the Tuck bequest at the Petit Palais, (4) 91*h*.

Girdler Corp. Catalyst for the stream reforming of naphtha and related hydrocarbons, P (10) 317*i*.

Girifalco, L. See Regester, R. F.

Gisondi, A. Characteristics and behavior of saggers and kiln furniture for the ceramic industry, (8) 236*j*.

Gittins, J. See Ingamells, C. O.

Gitzen, W. H. See MacZura, G.

Giuliani, S., Mustacchi, C., Amato, I., Colombo, R. L., and Coselli, R. Dependence on microstructure of the high temperature properties of uranium oxide-molybdenum and uranium oxide-tungsten cermets (II) heat transfer properties, (1) 11*c*.

Giutronich, J. E. Techniques for measuring spectral emittance of solids at high temperatures using a solar furnace, (5) 146*c*.

Given, J. B. Crucible melting furnace, P (3) 68*b*.

Glabau, E. R. Bismuth-free barium titanate ceramic compositions, P (5) 140*d*.

Glaceries Reunies Soc. Anon. Safety glass, P (1) 10*d*.

Gladkikh, M. T. See Palatnik, L. S.

Gladney, H. M. Electronic structure of MgF_2:Co^{3+}, (11) 352*d*. Hyperfine structure of ^{19}F in the electron paramagnetic resonance of $MgF_2:Co^{2+}$, (9) 283*b*.

Gladrow, E. M. See Mattox, W. J.

Gladrow, E. M., and Smith, W. M. Preparation of a crystalline aluminosilicate zeolite in a siliceous matrix, P (1) 25*g*.

Gladushchenko, V. A., and Zakharchenko, M. A. Tetrahedral section of the system Li,Na,Ca‖F,Cl, (7) 195*h*.

Gladwell, R. T., Jr. See Clark, F. P.

Gladyshevskii, E. I. See Verkhogliyadova, T. S.

Glaeser, M. L. Electrode rapping control for an electrostatic precipitator, P (4) 102*a*.

Glang, R., Holmwood, R. A., and Herd, S. R. Resistivity and structure of Cr-SiO cermet films, (5) 139*e*.

Glang, R., Holmwood, R. A., and Maissel, L. I. Sheet resistance control of thin Cr-SiO films, (11) 342*d*.

Glang, R., and Lessor, A. E., Jr. Method of making cermet resistors by etching, P (11) 344*j*.

Glang, R., and Schaible, P. M. Tolerance limitations of etched film resistors, (10) 309*b*.

Glaser, H. I. See Tiede, R. L.

Glaser, W., and Boggum, P. Hot repairs in glass melting furnaces—a practical guide, (4) 93*g*.

Glaser, W., and Simon, G. Rider arches in regenerative chambers of glass-melting tanks, (11) 335*a*.

Glass, A. M. Reactions between vacancies and impurities in magnesium oxide (I) Cr^{3+}-ion impurities, (11) 355*i*.

Glass, A. M., and Searle, T. M. Reactions between vacancies and impurities in magnesium oxide (II) Mn^{4+}-ion and OH-ion impurities, (11) 355*i*.

Glass, W. B. See Langridge, A.

Glasser, F. P. Crystallization of lithium disilicate from Li_2O-SiO_2 glasses, (5) 126*j*. See Dayal, R. R.; Lister, D. H.; Roeder, P. L.

Glasser, L. S. D., and Mileson, J. S. Crystal data for $Na_2Ca_3Si_2O_8$, (2) 57*g*.

Glasson, D. R. Reactivity of lime and related oxides (XIII) sulfating of hydrated lime; (XIV) sulfating of carbonated lime; (XV) crystalline forms of sulfated lime, (10) 295*b*.

Glatz, A. C. Bi_2Te_3-Bi_2S_3 system and synthesis of the mineral tetradymite, (5) 149*h*. Evaluation of the bismuth-tellurium phase system, (4) 110*g*.

Glauser, A. Phase calculation and mix equations for high iron oxide cements on an equivalent basis, (10) 295*j*.

Glaxo Laboratories, Ltd. Vented enclosed glass ampoule and method of making, P (7) 199*e*.

Glazova, V. V. See Kornilov, I. I.

Gleiser, M. Free energy of formation of Cr_3C_2, (11) 353*b*.

Glemser, O., and Baeckmann, A. von. Process for the separation of zirconium from hafnium, P (11) 349*j*.

Glenk, H. Ultrasonic time delay—a new electronic component, (10) 309*d*.

Glenn, R. C., and Nash, V. E. Weathering relations between gibbsite, kaolinite, chlorite, and expansible layer silicates in selected soils from the lower Mississippi Coastal Plain, B (6) 192*f*.

Glew, D. N. See Clarke, E. C. W.

Gliemeroth, G. See Scholze, H.

Glinon, T. G. J. Engineering ceramics and cermets, (1) 11*h*.

Globe-Union, Inc. Method of forming a semiconductor device with a depletion area, P (7) 209*c*. Method of forming a transistor and varistor by reduction and diffusion, P (2) 51*h*. Method of growing a crystal, P (4) 100*j*. Nickel oxide capacitors, P (2) 51*j*. Solar cell and process for making, P (4) 101*b*.

Glogar, P. See Dvorak, V.

Gloor, H. R. See Amrein, E.

Glos, E. A., II. Drum filter element attaching means, P (3) 78*b*. Filter apparatus, P (4) 102*a*.

Glossman, N., and Corrin, M. L. Adsorption of argon on anatase at low relative pressures, (1) 26*e*.

Glover, E. D. See Sippel, R. F.

Glower, D. D., and Heckman, R. C. Conduction, ionic or electronic, in $BaTiO_3$, (5) 137*j*.

Gloyna, E. F., Stoddard, S. D., and Christenson, C. W. Radioactive waste disposal (I, II), (3) 67*g*.

Glushko, V. T. Study of the rheological properties of nonmetallic materials by physical methods, (11) 357*i*.

Glushkova, V. B., and Koehler, E. K. X-ray and spectrographic investigations of phase transitions in ZrO_2 and rare-earth oxides, (1) 34*b*.

Gmundner Portlandzementfabrik Hans Hatschek. Homogenization chamber for granular material, P (10) 312*d*.

Gniewek, T. T., Jr. See Auld, J. R.

Godding, R. G. Measurement of moisture content in [molding] sand, etc., P (1) 23*j*.

Godfrey, R. H. See Morrell, A. M.

Godfrey, T. G. See Leitnaker, J. M.

Godley, C. S. Device for discharging material from a screw conveyor, P (1) 20*f*.

Goeddel, W. V. Method of making carbonaceous products, P (5) 135*a*. See Watson, J. F.

Goemans, A. H. See Whelan, M. V.

Goetz, H. W. False set of cement as influenced by hydroxylated carboxylic acid type admixture, (11) 331*i*.

Goetzberger, A. Improved properties of silicon dioxide layers grown under bias, (7) 207*c*. Method of forming an oxide coating on semiconductor bodies, P (8) 245*g*. See Nicollian, E. H.

Goetzberger, A., and Nicollian, E. H. Transient voltage breakdown due to avalanche in MIS capacitors, (2) 50*b*.

Goff, K. W. Process studies for control system design and evaluation, (2) 54*j*.

Goggin, P. R. Some effects of irradiation at 77°K on the physical properties of graphite, (8) 239*g*.

Goggin, P. R., and Reynolds, W. N. Elastic constants of reactor graphites, (3) 67*d*.

Goikhman, V. Yu., and Knigin, G. Kh. Automatic measurement of the viscosity of glass, (10) 313*j*.

Gokhale, Y. C. See Arora, K. L.

Gold, D. P. Natural and synthetic diamonds and the North American outlook (7) 220*a*.

Gol'dberg, Z. A. See Ivensen, V. A.

Goldheim, D. L. See Westwood, A. R. C.

Goldman, M., and Shen, L. Spin-spin relaxation in LaF_3, (9) 286*e*.

Goldman, R. L., Kritzler, W. R., and Sirvydas, V. C. Fabrication of semiconductor device, P (9) 272*j*.

Goldsmith, H. J., and Smith, J. T. Thermal cells in present use, (8) 243*e*.

Goldsmith, N. Method of forming a *pn* junction by vaporization, P (6) 178*a*.

Goldstein, M. Some thermodynamic aspects of the glass transition—free volume, entropy, and enthalpy theories, (5) 128*i*. See Weber, N.

Goldstein, R. M. Thin-film yttrium oxide capacitors, (10) 308*j*.

Goldsztaub, S., and Gautherie, M. Two methods of determining the temperature field around a crystal growing from a melt, (6) 181*h*.

Golightly, J. P. See Frueh, A. J.

Golightly, J. S. Method for bending glass sheets, P (3) 65*d*.

Golladay, C. F. See Bennett, R. W.

Golmard, M., and Zanni, M. Porosimeter, P (9) 277*h*.

Goloschekov, A. S. See Morozov, E. I.

Golovanova, T. G. See Belyaev, I. N.

Golubev, B. P., Vasil'eva, G. A., Kalitin, P. P., Smirnov, S. N., and Kharitonov, F. Ya. Preparation and properties of corundum microlite insulators for use in corrosive media at high temperatures and pressures, (5) 139*j*.

Golubev, T. M. See Ivashchenko, V. V.

Golynko-Vol'fson, S. L., and Sudakas, L. G. Binding properties of reaction products of titanium dioxide and phosphoric acid, (1) 11*a*.

Gomaa, I. See Bishay, A.

Gomes, J. M., Uchida, K., and Baker, D. H., Jr. High-temperature two-phase extraction technique for tungsten minerals, (9) 278*h*.

Gomes, W. Reaction between hydrogen and potassium chloride crystals doped with nitrite and nitrate, (3) 85*i*.

Gomis Noguera, F. J. See Garcia Verduch, A.

Gonda, T. See Caplan, S.

Gondrand, M. See Waintal, A.

Gonser, U., Grant, R. W., Muir, A. H., Jr., and Wiedersich, H. Precipitation and oxidation studies in the Cu-Fe system using Moessbauer effect, (10) 324*b*.

Gonzalez Pena, J. M. See Aleixandre Ferrandis, V.

Good, W. R. See Campbell, W. W.

Goodenough, J. B. See Van Zandt, L. L.

Goodenough, J. B., Longo, J. M., and Kafalas, J. A. Band antiferromagnetism and the new perovskite, $CaCrO_3$, (11) 341*h*.

Goodenough, R. D. See Harrell, B. R.

Goodfellow, M. Is it possible to avoid unionization? (7) 223*f*. Preventing labor trouble, (2) 60*d*.

Goodfellow, T. L. See Caffyn, J. E.

Goodhue, D. T. See Martin, C. C.

Goodjohn, A. J., and Stewart, H. B. Use of BeO in advanced reactor concepts, (2) 46*b*.

Goodman, A. M. Photoemission of electrons from silicon and gold into SiO_2, (9) 285*b*.

Goodman, P. See Cockayne, D. J. H.

Goodman, P., and Lehmpfuhl, G. Electron diffraction study of MgO *h*00 systematic interactions, (1) 28*g*.

Goodsell, E. L. New materials in engineering, (1) 25*c*.

Goodson, S. O., and Yell, B. R. Sampling apparatus for unground solids, P (8) 249*a*.

Goor, J. M. van. Quality control during the production of electroceramic products, (2) 50*f*.

Goossens, L. M. C. See Whelan, M. V.

Goot, A. S. van der. See Ooigen, D. J. van.

Gopal, E. S. R. See Viswanathan, B.

Gordienko, S. P. See Fesenko, V. V.

Gordienko, S. P., Samsonov, G. V., and Fesenko, V. V. Evaporation of lanthanum hexaboride, (5) 138*i*.

Gordon, E. I. Review of acoustooptical deflection and modulation devices, (9) 277*c*.

Gordon, I., Harvey, R. L., Moss, H. I., Robbi, A. D., Tuska, J. W., Wallmark, J. T., and Wentworth, C. MOS-transistor-driven laminated-ferrite memory, (11) 342*a*.

Gordon, J. L. See Miller, J. E.

Gordon, R. B. See Davis, L. A.

Gordon, R. H. See Widrow, B.

Gordon, R. S. See Kent, R. C.

Gordon, W. A. Arc electrode of graphite with ball tip, P (11) 347*e*.

Gordy, I., and Bush, H. J. Time measurement as indication of temperature, P (1) 24*a*.

Goren, A. See Wiesler, M.

Gorni, J. See Barta, J.

Gornostansky, S. D., and Stager, C. V. Nuclear magnetic resonance study of V_2O_3, (11) 355*c*.

Gorodetskii, S. S. See Kazakov, V. K.

Gorokhov, S. D. See Fridman, Ya. D.

Gorsuch, P. D. See Regester, R. F.

Gorter, E. W. See Esveldt, C. J.

Goryacheva, V. P., and Bergman, A. G. Horizontal cross sections of the system Li, Na, K ||F, P_2O_7, (9) 283*a*.

Gosin, I. Ya. Production of Ceramic Facade and Facing Products, B (10) 329*h*.

Gosmanova, G. Determination of the thickness of a deposited thin layer of nickel by the electron microscope, (11) 346*g*.

Gosnell, R. B. Lamination of amorphous fluorocarbon polymer and glass, P (6) 170*i*.

Gosselin, C. M. See Bryant, P. J.

Gossenberger, H. F. See Nuese, C. J.

Gosudarstvenny Nauchno-Issledovatel'sky Institute Stekla. Method of treating alkali glasses, P (1) 9*h*.

Goswami, A. K. Contribution of grain boundary to optical dielectric constant of barium titanate, (11) 341*j*. Theory of the effect of hydrostatic pressure on the permittivity and Curie point of single crystal barium titanate, (4) 117*g*.

Goswami, J. C. See Okamoto, Y.

Goswami, N. K., and Gaur, J. N. Polarography of zirconium, (5) 145*i*.

Goto, F. Cohesive energy of diamond, (4) 106*h*.

Goto, K. Thickness dependence of the domain width in thin crystals of $BaFe_{12}O_{19}$ and $SrFe_{12}O_{19}$, (3) 88*f*.

Gotoghian, G. J. See Guichet, L. R.

Gotoh, K. See Nakajima. Y.; Shinohara, K.

Goton, R. P. See Recasens, J.; Trillat, J. J.

Goton, R. P., and Recasens, J. Process and apparatus for continuously melting and solidifying refractory materials, P (1) 13*h*.

Gottardi, V. See Bettinali, C.

Gotthardt, R., Hoppe, H. J., and Schiele, E. Sintering behavior of dolomites of different petrographic nature, (1) 23*d*.

Gottschalk, A. See Oel, H. J.

Gottschalk, G. W. See Thiem, D. W.

Gotz, J. Magnetite black and its properties as a polishing agent, (5) 123*j*.

Gouda, V. K. See Mikhail, R. Sh.

Goudswaard, B. Equivalent series resistance of tantalum solid electrolytic capacitors, (10) 307*f*.

Govindaraju, K. Determination of the major elements in silicate rocks by photoelectric spectrometry with the A.R.L. quantometer, (6) 180*h*.

Govindaswamy, G. See Ramamurthi, T. V.

Gowen, H. E. T. Means for controlled deposition and growth of polycrystalline films in a vacuum, P (6) 177*h*.

Graaf, W. P. de. See Westerveld, W.

Grabmaier, J. G., and Watson, B. C. Czochralski growth of magnesium aluminum spinel, (7) 216*d*.

Grabner, L. H. Oscillatory photoconductivity and luminescence in $SrTiO_3$, B (10) 328*j*.

Grace, R. E. See Walters, L. C.

Grace, W. R., & Co. Apparatus for converting hydrosols into solid microspheres, P (8) 250*d*. Apparatus for conveying and blending solids, P (8) 247*d*. Concrete mix with set retarding admixture, P (2) 37*e*. Hardening accelerated portland cement, P(6)165*j*. Metal phosphate gels and methods for producing, P (8) 251*f*. Method of cation exchanging synthetic faujasite, P (7) 214*e*. Preparation of a thoria sol by heating an aqueous solution of a thorium salt in an autoclave, P (3) 69*f*. Process for increasing the thermal stability of synthetic faujasite, P (6) 183*d*. Process for ion exchanging crystalline zeolites [faujasite] with nitrogenous bases, P (6) 183*e*. Process for making high strength molecular sieve nodules and extrudates, P (7) 215*d*. Process for making silica-magnesia-magnesium fluoride cracking catalysts, P (11) 349*g*. Process for preparing a crystalline zeolite, P (6) 183*f*, P (10) 318*b*. Process for preparing uranium dioxide-yttrium oxide-zirconium dioxide microspheres, P (3) 69*h*. Process for producing alumina gel, P (2) 47*j*. Process for producing alumina having a narrow pore size distribution, P (4) 105*d*. Production of zeolitic adsorbents in nodular form, P (6) 183*c*. Sol-gel microsphere forming process using dissolved ammonia in the dehydrating solvent, P (1) 14*g*.

Gradinger, H. See Broja, G.

Graf, D. See Schenck, H.

Graham, A. L. See Nicholls, G. D.

Graham, J. See Franzen, H. F.

Graham, J., Walker, G. F., and West, G. W. Nuclear magnetic resonance study of interlayer water in hydrated layer silicates, (5) 156*a*.

Graham, P. W. L., and Rindone, G. E. Internal friction of glasses in the system Na_2O-BaO-SiO_2, (1) 6*f*.

Granger, D. E. Vacuum impregnation of porous specimens [with resin] prior to microscope examination, (2) 55*a*.

Granitsas, G. A., and Crandon, H. D. Fiber type energy-conducting structures, P (5) 129*g*.

Granitzki, K. E. Behavior of different types of basic brick in an open-hearth furnace with high oxygen enrichment, (7) 200*c*.

Granquist, W. T., and Hollingsworth, C. A. Zero-gradient rotational diffusion constants of some polydisperse clay mineral sols (abstract), B (5) 161*a*.

Granquist, W. T., and Kennedy, J. V. Sorption of water at high temperatures on certain clay mineral surfaces—correlation with lattice fluoride, B (9) 289*g*.

Granquist, W. T., and Pollack, S. S. Clay mineral synthesis (II) a randomly interstratified aluminian montmorillonoid, (5) 150*c*.

Grant, A. E. Processing of metal fluorides including uranium hexafluoride with anhydrous HF, P (8) 241*c*.

Grant, N. J. Dispersion strengthening, B (4) 121*f*.

Grant, R. W. New data on tridymite, (6) 187*i*. See Gonser, U.

Grant, W. A. See Konjevic, R.

Grant, W. H. Chemical weathering of biotite-plagioclase gneiss, B (6) 192*d*. Kaolinite stability in the Central Piedmont of Georgia, B (7) 224*e*. Weathering of Stone Mountain granite, B (5) 160*a*.

Grappiolo, G. C. See Amato, I.

Grassano, U. M. See Chiarotti, G.

Gravereaux, M. Safety glass for automobiles (I, II), (6) 168*j*.

Gray, D. H., and Rex, R. W. Formation damage in sandstones caused by clay dispersion and migration, B (8) 259*j*.

Gray, F., Reed, L. W., and Molthan, H. D. Clay formation and accumulation in selected Oklahoma soils, B (5) 160*g*.

Gray, I. New factory, new glass, (9) 263*i*.

Gray, M. J. B. Trouble shooting in glass decoration, (10) 299*g*.

Gray, N. W. See Daem, R. C.

Gray, R. J. See Sears, M. B.

Grayson, L. P., and Boyden, J. H. Optical laser configuration, P (11) 344*i*.

Great Lakes Carbon Corp. Refractory graphite and method of producing, P (6) 175*d*.

Greaves, E. I., and Lakin, J. R. Behavior of high alumina bricks in arc furnace roofs, B (9) 291*c*.

Grebe, K. R. See Bartkus, E. A.

Grebenyuk, A. A., Karaulov, A. G., et al. Effect of phase composition on spalling resistance of zirconium dioxide, (9) 267*g*.

Grebenyuk, A. A., Karaulov, A. G., Majauskas, J., and Peras, A. Strength characteristics of granular zirconia refractories up to 2500°K, (5) 134*d*.

Grechus, G. K. Methods of severing brittle material along prescribed lines, P (8) 247*f*.

Green, A. P., Refractories Co. Composite stopper rod sleeve with insulating inner portion, P (7) 204*a*.

Green, C. A. See Moore, W. H.

Green, D. Hydrostatic extrusion processes, P (8) 247*d*.

Green, H. W., II. Quartz—extreme preferred orientation produced by annealing, (2) 59*f*.
Green, L. Q. See Dunton, G. R., III.
Green, M. Semiconductor surfaces, (1) 16*i*.
Green, P. See Peterson, G. E.
Green, P. E. See Burmeister, R. A., Jr.
Green, R. L. See Koenig, C. J.
Green, W. V., and Zukas, E. G. Stress dependence of the creep rate of two commercial graphites, (4) 116*h*.
Greenbaum, M. A. See Blauer, J. A.
Greenberg, E. See Porte, H. A.
Greenberg, E., Natke, C. A., and Hubbard, W. N. Fluorine bomb calorimetry (X) enthalpies of formation of niobium and tantalum pentafluorides, (11) 352*j*.
Greenberg, L. S. See Desmond, T. J.
Greenberg, S. A., and Chang, T. N. Colloidal hydrated calcium silicates (II) solubility relations in the calcium oxide-silica-water system at 25°, (11) 350*h*. Hydration of tricalcium silicate, (11) 353*c*.
Greenberg, S. A., Chang, T. N., and Anderson, E. Colloidal hydrated calcium silicates (I) solubility products, (11) 350*h*.
Greenblatt, S., and Bray, P. J. Discussion of the fraction of four-coordinated boron atoms present in borate glasses, (5) 127*g*. Nuclear magnetic resonance investigations of the system BaO-B_2O_3, (3) 64*i*.
Greene, E. W. See Allegrini, A. P.
Greene, M. J. See Wendell, C. B.
Greene, P. D. See Bradley, J. N.
Greene, P. E. See Stearns, R. I.
Greene, R. F. See Davis, J. L.
Greening, N. R. See Erlin, B.
Greenler, R. J., and Augustin, E. H. Method and apparatus for preventing bubbles in float glass apparatus, P (10) 300*h*.
Greenstreet, B. L. See Witt, F. J.
Greenwood, N. N. See Banerjee, S. K.
Greenwood, R. Thermal behavior of SiO_2-X and its relation to the natural silica minerals, (7) 222*c*.
Greet, R. J. Comparison of expressions for cooperative properties in glass-forming liquids, (5) 126*h*.
Greet, R. J., and Turnbull, D. Glass transition in *o*-terphenyl, (5) 127*b*.
GREFCO, Inc. Manufacture of a lightweight insulating product, P (1) 13*a*. Process for beneficiating diatomaceous earth ores, P (7) 215*b*.
Greger, H. H. Apparatus for pressure sintering ceramic material, P (8) 247*f*.
Gregg, D. See White, D.
Grego, P. See Dalton, R. H.
Gregor, L. V. Gas-phase deposition of insulating films, B (8) 260*e*.
Gregory, C. K. Heat treatment refractory furnaces, (10) 303*c*.
Gregory, R. L. See Harrell, B. R.
Greider, M. H. See Fisher, R. M.
Greiser, W. Ceramic sculptures of Gilbert Portaniers, (4) 91*f*. Glass partitions in rolls, (4) 93*f*.
Gremillion, A. F. See Epperson, C. E.
Gremion, R. Method and apparatus for metallic impregnation of carbon and graphite, P (11) 340*h*.
Gremmelmaier, R. See Folberth, O. G.
Gren, V. Solids mixing—a review of present theory, (5) 143*i*.
Grenier, J. C., and Bassi, G. Refinement of the structure of $NbLi_3O_4$, (5) 157*j*.
Greskovich, C., and Stubican, V. S. Coherent precipitation in the system MgO-Al_2O_3-Cr_2O_3, (2) 57*e*.
Greszczuk, L. B. Effect of material orthotropy on the directions of principal stresses and strains, B (4) 120*j*.
Gribkova, L. V., and Mikhailov, N. V. Vibrogranulation of raw materials for cement, (2) 57*b*.
Gridley, P. F. See Hardy, J. F.
Griem, P. D., Jr. Direct digital control of a glass furnace, (3) 63*g*. Furnace control apparatus, P (10) 300*i*.
Griffiths, J. C. Scientific Method in Analysis of Sediments, B (6) 192*b*.
Griggs, D. T. See Wenk, H. R.
Grigor'eva, L. F. See Nadgornyi, E. M.
Grigor'eva, V. V., Savitskii, K. V., Zhdanova, V. N., et al. Deformation resistance and stability of strain distortions of sintered alloys, (3) 67*a*.
Grigorovici, R. Amorphous germanium and silicon, (5) 149*j*.
Grigorovici, R., and Manaila, R. New type of energy band calculation in disordered systems, (5) 155*j*.
Grigsby, D. L., Johnson, D. H., Neuberger, M., and Welles, S. J. (editors). Electronic Properties of Materials—A Guide to the Literature (Vol. 2), B (5) 161*c*.
Grim, R. E. Origin of clay minerals, (3) 84*i*. Properties of clays, (3) 85*e*. Recent developments in research related to clays and soils, (3) 86*a*. See Ferrell, R. E., Jr.; Gaudette, H. E.; Wahl, F. M.
Grimmer, E. J. Method of constructing cast electrical bushings, P (11) 344*e*.
Grimwood, H. W. See Langridge, A.
Grinevetskaya, S. N., and Demishev, G. K. Acoustic-dilatometric studies of the structural parameters of borosilicate glasses, (10) 296*i*.
Gring, J. L., and Mooi, J. Boehmite alumina products, P (7) 214*i*.
Grinlute, G. See Abraitis, R.
Griscom, D. L., and Griscom, R. E. Paramagnetic resonance of Mn^{2+} in glasses and compounds of the lithium borate system, (5) 128*e*.
Griscom, R. E. See Griscom, D. L.
Grislain, B. Determination of flow patterns in a glass tank by tracers, (11) 333*d*.
Grizik, A. A., and Piyushchev, V. E. Polyhafnates of rubidium, (10) 324*a*. Rubidium trizirconate, (10) 325*c*.
Grizik, A. A., Piyushchev, V. E., and Kamenskaya, A. N. Rubidium dizirconate, (4) 115*j*.
Groble, K. K. See Hendron, J. A.
Grodkiewicz, W. H., and Van Uitert, L. G. Growth of yttrium iron garnet, P (9) 273*c*.
Groenou, A. B. van. Low frequency magnetic relaxations in manganese ferrous ferrites at low temperatures, (3) 71*h*.
Groot, K. de. Experimental dedolomitization, (5) 152*h*.
Gros, Y. See Chol, G.
Grosheva, V. M. See Zanemonets, V. F.
Grosheva, V. M., Panasevich, V. M., and Boichun, V. Yu. Stability of mullite at high temperatures, (9) 286*e*.
Groshik, I. I. See Fridkin, V. M.
Gross, G. E. Role of electron configurations in nonmetals, B (4) 121*g*. See Gutshall, P. L.
Gross, P., Hayman, C., and Bingham, J. T. Heats of formation of germanium tetrafluoride and of the germanium dioxides, (3) 81*j*.
Gross, P., Hayman, C., and Stuart, M. C. Heat of formation of phosphorus pentafluoride, (3) 81*i*.
Grossman, J. J., and Braunstein, M. Method and apparatus for preparing single crystal thin films, P (2) 51*g*.
Grossman, L. N., and Kaznoff, A. I. Determination of enthalpy of fusion of UO_2, (2) 58*a*.
Grossman, L. N., Lewis, J. E., and Rooney, D. M. System UO_2-Eu_2O_3 at high temperatures, (10) 326*a*.
Grossweiner, L. I. See Dudkowski, S. J.
Grover, J. R., and Jones, A. D. Glass composition comprising radioactive waste oxide material contained within a steel vessel, P (5) 120*j*.
Groves, G. W. See Shockey, D. A.
Groves, J. D. See Callow, A. E.
Groves, J. D., and Jones, P. A. Reduction in scale buildup in the vapor phase production of pigmentary metal oxides, P (10) 318*g*.
Grubb, P. L. C. Solid solution relations between wolframite and scheelite, (6) 188*d*.
Grubbens & Co. A. B. Screen, P (7) 211*g*.
Gruber, B. A. Article containing silicon carbon fibers, P (9) 270*a*. Process for the production of boron phosphide, P (11) 349*i*.
Gruber, G. A. See Chu, T. L.
Gruber, J. B. See Chang, N. C.; Henderson, J. R.
Gruber, J. B., Krupke, W. F., and Poindexter, J. M. Crystal-field splitting of trivalent thulium and erbium J levels in yttrium oxide, (7) 216*j*.
Gruehn, R. New modification of niobium pentoxide, (3) 83*f*.
Gruener, M. See Bastian, S.
Gruetzmacher, R. W. See Hendron, J. A.
Grunberg, G. See Pruniaux, B.
Grundmann, W. Factors in the formation of "flow marks" in pressed glass, (8) 232*b*.
Grundner, W. T. See Calmon, C.
Grunig, J. K., Aitkenhead, W. C., and Davis, W. B. Precipitation of beryllium from ores, P (11) 349*d*.
Grunzweig & Hartmann Akt.-Ges. Blast nozzle for forming silicate fibers, P (2) 40*e*. Method of preparing fibers from a viscous melt, P (3) 66*a*.
Gruver, R. M. See Kirchner, H. P.
Gruver, R. M., and Kirchner, H. P. Residual stress and flexural strength of thermally conditioned 96% alumina rods, (5) 157*j*.
Grzymek, J., Skalny, J., and Wiesel, K. Polymorphism of dicalcium silicate, (2) 59*d*.
Grzymek, J., Skomorowski, E., and Wieja, C. Studies on portland cement clinker fused at about 3000°C, (6) 165*d*.
Gualandi, D., and Jehenson, P. Process for obtaining Al-Al_2O_3 structures for nuclear applications, P (10) 305*a*.
Gualtieri, J. G., and AuCoin, T. R. Crystal-field term symbols for Nd^{3+} in $CaWO_4$, (10) 319*a*.
Gualtieri, J. G., deLhery, G. P., AuCoin, T. R., and Pastore, J. R. Infrared quantum counter action in Ho-doped crystals, (11) 353*e*.
Gubatenko, A. P. See Tseitlin, L. A.
Gude, A. J., 3d, and Sheppard, R. A. Composition and genesis of analcime in the Barstow formation, San Bernardino County, California (abstract), B (9) 289*b*.
Gudimov, M. M. See Solntsev, S. S.
Guelden, H. See Kamper, E.
Guenthard, H. H. See Mueller, R.
Guenther, R. Flame research and glass melting, (8) 232*c*.
Guerci, C. F., and Shafer, M. W. Method of making crystals of rare earth chalcogenides, P (6) 178*c*. Method of preparing transparent ferromagnetic single crystals, P (7) 209*b*.
Guereca, R. A. See Miller, J. E.
Guereca, R. A., Richardson, H. P., and Walker, L. M. Steady-state laminar flow boundary conditions for a stainless steel coiled-capillary viscosimeter, (1) 23*f*.
Guerra, R. F. See Fuentes Guerra, R.
Gugel, E. Indialite (cordierite) as the basis of thermal shock resistant refractories, (8) 237*j*. See Borchert, W.; Osterried, O.
Guggenheim, H. J. See Dietz, R. E.; Ferguson, J.; MacChesney, J. B.; Merritt, F. R.
Gugger, R. See Montmollin, J. P. de.
Guha, J. P. Formation and stability relations of uranium nitrides, (5) 132*j*.
Guha, P. K. Bauxite deposits of Bagru plateau (Lohardaga) and their origin, (10) 317*g*.
Guha, S., and Kaw, P. K. Photoelectric enhancement of electrical conductivity in dust-laden [BaO] gases, (9) 285*a*.
Guichet, L. R., and Gotoghian, G. J. Method of coating graphite with a refractory coating and products obtained, P (5) 135*j*.
Guilbault, C. G. (editor). Fluorescence, Theory, Instrumentation, and Practice—Proceedings of a Symposium Held by the Analytical Division of the American Chemical Society, Miami Beach, April 1967, B (1) 34*e*.
Guilbert, J. M. See Sloane, R. L.
Guillen, M., and Bertaut, E. F. Structure of La_2TiO_5, (6) 189*i*.
Guillou, M. Effect of porosity on electrolysis in MHD electrodes, (10) 302*h*.
Guilonard, P. J. G. See Swaving, E. C. J.
Guinet, P., Vaugoyeau, H., Laugier, J., and Blum, P. L. Study of a four solid phase equilibrium in the ternary system U–C–Si, (9) 287*e*.
Guinier, A. See Bigare, M.; Comes, R.
Gukov, G. Diamond capsules for temperature measurement, (8) 248*d*.
Gulbransen, E. A., and Hickam, W. M. Nature of the reaction products formed in the graphite-hydrogen reaction at 1300° to 1400°C, (4) 113*h*.
Gulden, M. E. Migration of gas bubbles in irradiated uranium dioxide, (5) 132*i*.
Gulden, T. D. Deposition and microstructure of vapor-deposited silicon carbide, (9) 267*c*. Growth kinetics of interstitial loops in irradiated sapphire, (1) 29*h*.
Gulf General Atomic, Inc. Method of making carbonaceous products, P (5) 135*a*.
Gulf Oil Corp. Novel oxidation catalyst compositions and processes, P (1) 13*d*.
Gulf Research & Development Co. Coprecipitated silica-alumina catalyst process and composition, P (1) 25*i*.
Gul'ko, N. V. See Kainarskii, I. S.
Gulledge, H. C. See Lewis, G. L.
Gullett, W. W. Manganese nitride, P (9) 270*e*.
Gullman, L. O. X-ray diffraction and thermoanalytical investigation of the palladium-phosphorus system, (4) 119*a*.
Gulotta, J. A. Method of removing contaminates from the protective atmosphere of a glass sheet float bath, P (3) 66*c*.
Gumuliauskas, A., and Pavliuk, G. Effect of binder composition on the durability of silicate concrete, (5) 124*f*.
Gupta, C. L. See Wasan, V. P.
Gupta, D. R. D. Thermal decomposition of dolomite and ankerite, (9) 287*j*.
Gupta, J. G. S. Determination of fluorine in silicate and phosphate rocks, micas, and stony meteorites, (10) 313*j*.
Gupta, K. D. X-ray diffraction camera employing two curved crystal transmission type monochromators, P (7) 213*e*.
Gupta, P. K. See Beck, T. A.; Bhandary, V. S.
Gupta, S. C. See Ramamurthi, T. V.
Gupta, S. D. See Kumar, S.
Gupta, S. K., and Prasad, S. N. Production of mirrors and silvering on glass (II) silvering methods, (2) 39*j*.
Gupta, T. K., and Coble, R. L. Sintering of ZnO (I) densification and grain growth; (II) density decrease and pore growth during the final stage, (10) 325*i*.
Gurevich, M. A. See Darvoid, T. I.
Guriuc, V. See Veiser, I.
Gurney, C., and Hunt, J. Quasi-static crack propagation, (9) 285*i*.
Guscott, B. R. See Khanna, R. K.
Guseinov, G. D., Ismailov, M. Z., and Guseinov, G. G. New semiconducting compound, $CdTlS_2$, (1) 30*d*.
Guseinov, G. G. See Guseinov, G. D.
Guseva, V. I. See Lopatnikova, L. Ya.
Guss- und Farbenglaswerke Pirna Copitz VEB. Method and apparatus for the continuous production of a bar of glass of predetermined profile, P (2) 41*e*.
Gustaferro, A. H. See Abrams, M. S.
Gustafson, R. L. See Kunin, R.
Gustard, B. Ferromagnetic domain structure in hematite, (1) 29*d*.
Gustavsson, K. A. G. Method and apparatus for fractionating particulate materials, P (10) 316*a*.
Gutfeld, R. J. von, Nethercot, A. H., Jr., and Armstrong, J. A. Transport of heat from metals to insulators at low temperatures, (8) 258*a*.
Gutman, V. I. See Galdina, N. M.
Gutmann, W. R. Dehydrogenation catalysts, P (4) 104*j*.
Gutshall, P. L., and Gross, G. E. Fracture energy of polycrystalline beryllium oxide, (11) 353*b*. Fracture = strength, (11) 346*c*.
Gutt, W. See Everett, L. H.
Gutt, W., Kinniburgh, W., and Newman, A. J. Blast furnace slag as aggregate for concrete, (4) 92*b*.
Gutt, W., Kinniburgh, W., Newman, A. J., and Everett, L. H. Reply to discussion of "Blast furnace slag as aggregate for concrete" and "Steel in concrete with blast furnace slag aggregate," (5) 124*j*.
Gutt, W., and Smith, M. A. Alpha form of calcium sulfate, (2) 36*d*. Studies of the subsystem CaO–$CaO \cdot SiO_2$–$CaSO_4$, (7) 222*d*.
Gutwirth, K. See Kaspar, J.
Gutzeit, C. L. Carbon fibers and method, P (2) 46*f*. Metal carbide formation on carbon fibers, P (3) 68*j*.
Guy, R. Fiber optics, (6) 167*f*.

Guyot, L. F. Fluorescent screen for brightness amplifier tubes and method of making, P (3) 72*g*.

Guyton, J. L., and Thompson, M. A. Plutonium carbonitride, P (5) 135*g*.

Guz, D. B. See Blokh, S. A.

Guzman, I. Ya., and Tumakova, E. I. Production of silicon nitride shapes, (7) 202*i*.

Gy, P. M. Process for reducing error in the sampling of materials, P (10) 316*c*.

Gyenge, M. See Coates, D. F.

Haaland, A. See Almenningen, A.

Haan, E. F. de, and Haantjes, J. Television camera tube employing a photosensitive target with a transparent member for absorbing reflected light from the target, P (7) 210*d*.

Haans, P. F. A., Botden, T. P. J., and Roelofs, H. Electric conductor suitable for being sealed in the wall of an electric discharge tube, P (7) 208*b*.

Haantjes, J. See Haan, E. F. de.

Haas, A. Chemistry of silicon-sulfur compounds, (5) 150*b*.

Haas, I. Integrated circuit having active and passive components in same semiconductor region, P (4) 100*c*.

Haase, G., and Schopper, E. Investigation of silver chloride crystals for detection of charged particles, B (10) 329*c*.

Haber, H. E. See Fisher, R. D.

Haberecht, R. R. Method of making dielectric bodies having conducting portions, P (9) 273*i*. See Patterson, R. J.

Habgood, H. W. Surface OH groups on zeolite X, (11) 357*a*.

Hach, R. J. See Johnson, R. E.

Hackerman, N. See Venable, R. L.

Hackler, W. C. Process control, B (3) 89*c*.

Hacskaylo, M., and Smith, R. C. Capacitor having dysprosium oxide dielectric, P (9) 272*j*.

Haden, W. L., Jr. See Miller, J. G.

Haden, W. L., Jr., and Dzierzanowski, F. J. Method for producing faujasite-type zeolites, P (10) 318*g*. Solid catalysts, P (5) 149*a*. Synthetic zeolite contact masses and method for making, P (5) 149*b*.

Hadley, D. J. Activation of antimony oxide-tin oxide catalysts using water, acid, or base, P (1) 25*h*.

Hadley, D. W. Field and laboratory studies on the reactivity of sand-gravel aggregates, (6) 164*g*.

Hadley, R. F. See Rolfe, B. N.

Hadni, A. See Plendl, J. N.

Hadni, A., Claudel, J., Gerbaux, X., Morlot, G., and Munier, J. M. Different behavior of crystals and glasses in far infrared (40 to 1500μ) absorption at liquid helium temperature, (5) 127*d*.

Haedicke, U. See Wolf, F.

Haering, J. Auger machines, (10) 311*i*. Recirculation of fuel gas in tunnel kilns, (10) 301*j*.

Haertling, G. H. Semicontinuous hot-press tunnel kiln, (11) 348*f*.

Haertling, G. H., and Cook, R. L. Physical properties vs. crystalline phases in low-loss steatite, (2) 50*b*.

Haese, U. Relation of lattice energy and grinding properties of crystalline materials, (7) 211*f*.

Haessler, A. Status of tunnel and ring kiln firing techniques, (10) 317*d*.

Haessner, F. Ceramic neutron absorbers for control organisms, (10) 319*e*.

Hafford, B. C., and Snow, G. E. Titanium dioxide-silica pigment, P (8) 251*j*.

Hafner, S., and Raymond, M. Nuclear quadrupole coupling tensors of ^{27}Al in kyanite, (7) 220*d*.

Haga, L. J., and Tucker, T. N. Method of etching silicon carbide, P (11) 344*h*.

Hage, W. T. See Baumgartel, F. A.

Hagedorn, E. C., and Hall, D. P. Glass compositions resistant to discoloration, method of making, and articles produced, P (2) 40*h*.

Hagemark, K., and Broli, M. Equilibrium oxygen pressures over nonstoichiometric UO_{2+x} and U_3O_{8-z} at higher temperatures, (4) 109*j*. Equilibrium oxygen pressures over solid solutions of urania-yttria and urania-lanthana at 1100° to 1400°C, (1) 29*b*.

Hagenlocher, A. K. Method for the formation of thin films, P (5) 141*h*.

Hagenmuller, P. See Kasper, J. S.; Pouchard, M.; Vandeven, V.

Hager, H. Evaluation of the shape of coarse abrasive grains, (9) 261*f*.

Hager, N. E., Jr. Temperature sensing probe, P (3) 76*h*.

Hager, N. E., Jr., and Steere, R. C. Radiant heat transfer in fibrous thermal insulation, (5) 133*a*.

Haggerty, J. S., Cooper, A. R., and Heasley, J. H. Heat capacity of three inorganic glasses and supercooled liquids, (8) 232*h*.

Hagiwara, H. See Yamashita, A.

Haglington, J. B., and Lakin, J. R. Behavior of high-fired basic brick in steel furnaces, (7) 200*e*.

Hagni, R. D. Preparation of thin sections of fragmental materials using epoxy resin, (1) 22*i*.

Hagquist, F. M. See Rusk, G. R.

Hague, J. R., and Brite, D. W. Fabrication of materials by high energy-rate impaction, P (1) 12*d*.

Hahn, H. See Yakowitz, H.

Hahn, S. J. See Kent, R. C.

Hahn, S. J., Ree, T., and Eyring, H. Mechanism for the plastic deformation of Yule marble, (4) 113*a*.

Hahn, T. See Bigare, M.; Woermann, E.

Hairion, J. P. See Soulhier, R.

Haisty, R. W. Effect of illumination time on thermally stimulated currents in semi-insulating GaAs, (3) 80*e*. See Hoyt, P. L.; Johnson, R. E.

Haisty, R. W., and Cronin, G. R. Gallium arsenide semiconductor doped with chromium and a shallow acceptor impurity, P (10) 309*g*.

Hakim, J., and Ariff, M. R. Low temperature white coat porcelain enamel for sheet iron, (9) 262*j*.

Hakim, R. See Allersma, T.

Hakim, R. M., and Uhlmann, D. R. Mixed alkali effect in glasses, (3) 64*h*.

Halas, D. R. de, Morgan, W. C., and Freshley, M. D. Reactor materials design, B (4) 120*j*.

Halasyamani, P. See Mallikarjunan, R.

Halasyamani, P., Venkatachalam, S., and Mallikarjunan, R. Influence of pH on the kinetics of comminution of quartz, (4) 101*i*.

Halden, F. A. See Bartlett, R. W.

Haig, W. See Andresen, A. F.

Hall, D. See Ratcliffe, S. W.

Hall, D. H. See Sanford, E. A.

Hall, D. P. See Hagedorn, E. C.

Hall, E. Effect of stress and annealing on Young's modulus of reactor graphite, (8) 253*i*.

Hall, E. S. Zeta potential of aluminum hydroxide in relation to water treatment coagulation, (1) 34*a*.

Hall, H. B. See Wilson, W. D.

Hall, H. L. Method and means of calcining limestone, P (1) 3*b*.

Hall, H. T. Periodic compounds—syntheses at high pressures and temperatures, (4) 113*i*.

Hall, L. C. See Wertz, J. E.

Hall, P. G., and Mureinik, R. J. Adsorption of water vapor on silica-alumina treated with potassium chloride, (3) 78*g*.

Hall, R. C. Strengthening ceramic materials, (4) 119*g*.

Hall, R. N. High power junction laser structure, P (4) 100*c*. Semiconductor junction laser device, P (4) 101*a*. Semiconductive junction laser with temperature compensation, P (4) 101*e*.

Hall, R. T. Heat exchange system for calciner, P (11) 332*a*.

Hall, W. F. See Hildenbrand, D. L.

Halla, F. Note on the thermodynamics of formation of dolomite, (11) 355*b*.

Hallen, R. L., and Valletta, R. M. Cathodic sputtering apparatus including thermionic means for increasing sputtering efficiency, P (5) 140*g*.

Haller, W. Rearrangement kinetics of the liquid-liquid immiscible microphases in alkali borosilicate melts, (5) 128*g*.

Halliburton Co. Cementing compositions for maximum thermal insulation, P (4) 92*b*. Method of disposing of waste materials, P (7) 223*g*.

Hallman, R. W. See Teeg, R. O.

Hallse, R. L. See Mayhall, J. O.

Halm, L., Huguet, F., Lapoujade, P., Lecrivain, L., and Schoendoerffer, M. J. Tests on special refractories in the bosh of blast furnace No. 2 at the Societe Metallurgique de Normandie, B (9) 291*c*.

Halm, L., Schoendoerffer, M. J., and Baron, J. Refractories for oxygen process steel converters, (4) 96*a*.

Halperin, A., and Ralph, J. E. Optical studies of anisotropic color centers in germanium-doped quartz, (5) 156*f*.

Halpern, B. D., and Semmelman, J. O. Method of chemically bonding dental porcelain to synthetic resin base materials and resulting prosthetic appliance, P (5) 137*c*.

Halpern, C. See Olsen, L. O.

Halstead, T. K. See Dickens, P. G.

Halus, D. R. de. Shape of migrating voids, (7) 203*f*.

Halverson, F. Synergized lanthanide chelate photoluminescent composition, P (7) 210*b*.

Ham, C. S. See Lozano, R.

Ham, F. S. See Delchar, T. A.

Hamamura, A., Kiyama, M., Bando, Y., and Takada, T. Cation distribution in chemically precipitated $ZnFe_2O_4$, (11) 350*d*.

Hamano, Y. See Kinoshita, M.

Hamano, Y., Kinoshita, M., and Kose, S. Hot-pressing of titanium diboride with binding metals, (8) 237*f*.

Hamblen, D. P. See Blair, G. E.

Hambleton, F. H., and Hockey, J. A. Infrared spectroscopic investigation of the interaction of BCl_3 with Aerosil silicas, (3) 82*d*.

Hambleton, F. H., Hockey, J. A., and Taylor, J. A. G. Investigation of 1800 to 1400 cm^{-1} region of infrared spectrum of Aerosil silicas, (3) 82*j*. Investigation by infrared spectroscopic methods of deuterium exchange properties of Aerosil silicas, (3) 82*a*.

Hamdani, A. J. See Caffyn, J. E.

Hameau, G., and Legrand, G. Analysis of soils by the flame spectrophotometer, (6) 179*i*.

Hamill, D. W. See Hunter, M. J.

Hamilton, D. R. See Patrick, L.

Hamilton, J. F. Transmission electron microscopy of twinned silver bromide crystals, (4) 118*b*.

Hamilton, R. W. See Burham, F. P.

Hamilton, T. N. See Mee, J. E.

Hamilton, V. E. Apparatus and method for evaporative coating, P (4) 92*j*. Apparatus for producing a laminated glass panel, P (5) 129*c*. Method of making cathode-ray tube with integral light trapping filter, P (4) 95*c*.

Hamilton, V. E., and Johnson, H. F. Method for making cathode-ray tube filters, P (4) 95*b*.

Hamlin, H. P. See Knechtel, M. M.

Hammel, J. J. Direct measurements of homogeneous nucleation rates in a glass-forming system, (5) 127*e*.

Hammer, E. See Eipeltauer, E.

Hammerschmid, P. Relations between the tested properties and the stability of tar-dolomite brick in oxygen process steel converters, (4) 96*d*.

Hammond, M. L., and Bowers, G. M. Preparation and properties of SiO_2 films deposited from SiH_4 and O_2, (10) 308*c*.

Hamner, R. L., Chapman, A. T., and Harms, W. O. Fabrication development and irradiation testing of fueled BeO, (4) 96*c*.

Hamouda, I. See Amin, R.

Hampe, R., and Winter, A. Potters and Roof-Tile Makers in South Italy, Sicily, and Greece, B (4) 121*d*.

Hamrin, C. E., Jr. Tungsten-rhenium coated ceramic reactor fuel particles, P (11) 341*b*.

Hanada, M. See Murakami, K.

Hanak, J. J., and Johnson, D. Epitaxial growth of metal oxides, (9) 271*j*.

Hand, J. W. Grinding mill and fineness control system, P (5) 148*c*.

Handa, K. N. See Ramachandran, V. S.

Handwerk, J. H. See Readey, D. W.

Handy, R. L. See Ho, C.

Hang, K. W. See Tennery, V. J.

Hanks, C. F., Jr. Irreversible thermal expansion, (2) 54*b*.

Hanks, C. F., Jr., and Sanders, L. D. Centrifuge particle size determination, (9) 275*j*.

Hanks, G. F. Method for damping the stack of a glass melting furnace, P (4) 94*j*.

Hanks, G. F., and Bracken, A. L., Jr. Method of melting glass, P (3) 65*i*.

Hanks, R. See Faktor, M. M.

Hanley, W. L. Tunnel kiln preheating section, P (7) 214*a*.

Hann, D. G., and Brinkman, R. J. Glass feeding furnaces, P (8) 235*j*.

Hanna, G. L., Hilditch, R. J., and Hickman, B. S. Effects of fission product damage in BeO dispersion fuels, (4) 96*b*.

Hanna, R. Structure of sodium silicate glasses and their far-infrared absorption spectra, (8) 234*i*.

Hannah, L. A. Ladle starter shape, P (10) 304*f*.

Hannam, H. J. Method of making a polycrystalline dual layered aluminum oxide-magnesium oxide storage electrode, P (7) 209*h*.

Hannavy, A., and West, P. Engineers seek materials for hostile environments, (7) 223*e*.

Hanneman, R. E. See Strong, H. M.

Hanocq, M., and Molle, L. Study of the direct spectrophotometric determination of fluoride ion with the cerium(III)-alizarin fluorine blue complex, (4) 103*b*.

Hansen, K. W. Taphole for a metallurgical vessel, P (1) 14*h*.

Hansen, K. W., and Bartell, L. S. Electron diffraction study of the structure of PF_5, (4) 109*h*.

Hansen, K. W., and Splann, M. T. Dielectric properties of semiconducting iron phosphate glasses, (8) 231*g*.

Hansen, W. C. Potential compound composition of portland cement clinker, (9) 262*e*.

Hansford, R. C. Hydrocarbon conversion process and catalyst comprising a Y type crystalline aluminosilicate promoted with a polyvalent metal, P (4) 105*c*. Pelleted zeolite compositions, P (10) 318*g*. Stabilized zeolites and use thereof for hydrocarbon conversions, P (3) 78*f*.

Hanshaw, B. B. Cation-exchange constants for clays from electrochemical measurements, B (6) 192*c*.

Hansler, R. L. Preferential vaporization of carbon from hafnium carbide, (3) 85*d*.

Hanson, D. N. See Faith, L. E.

Hanson, J. A. See Hedstrom, R. O.

Hanson, L. A. Preparation of an actinide metal monocarbide from an oxide thereof, P (9) 270*a*. Preparation of high quality uranium carbide, P (10) 304*j*. Preparation of pure dense hypostoichiometric uranium carbide, P (11) 340*c*.

Hanson, R. C. Attenuation of high frequency elastic waves in LiF, (8) 252*c*.

Hanson, R. F., and Keller, W. D. Genesis of refractory clay near Guanajuato, Mexico, B (8) 259*f*.

Hanst, P. L., Early, V. H., and Klemperer, W. Infrared spectrum and molecular structure of B_2O_2, (3) 82*f*.

Haq, A. See Qureshi, M. H.

Hara, T., Hirota, N., and Onoshima, Y. Method and compositions for inspecting leakage with gas pressure testing, P (9) 277*f*.

Harada, J., Tanaka, M., and Honjo, G. Thermal diffuse streak in electron diffraction and low frequency transverse optic lattice waves of barium titanate, (4) 117*j*.

Harari, A. See Queyroux, F.

Harari, A., Thery, J., and Collongues, R. Preparation of single crystal oxides MO_2, (7) 220*c*.

Harazono, S., Tajima, M., Tanimoto, S., and Kobayashi, T. Radiating gas burner apparatus, P (10) 317*d*.

Harbison-Walker Refractories Co. Aluminum induction furnace lining construction using zircon and calcium aluminate, P (3) 68*h*. Apparatus for handling and impregnating brick, P (4) 96*j*. Basic oxygen furnace construction, P (4) 97*a*, P (5) 134*c*, P (6) 174*j*. Basic refractories, P (4) 97*b*. Brick press having density control, P (5) 134*f*. Castable gunning mix, P (4) 97*b*. Chemically bonded refractory

shapes, P (2) 46*g*. Continuous casting apparatus with improved nozzle composition, P (3) 68*a*. Crucible melting furnace, P (3) 68*b*. High alumina brick, P (7) 204*f*. Induction furnace [coreless] construction, P (1) 12*j*. Manufacture of kiln furniture, P (1) 13*a*. Method of lining a rotary kiln, P (4) 97*k*. Method of in situ fabrication of monolith refractory lining, P (3) 69*c*. Mold wash, P (4) 97*c*. Mullite production, P (5) 135*e*. Production of magnesium carbonate and magnesia, P (3) 69*a*. Refractory-coated oxygen lance, P (2) 48*d*. Refractory gunning mix, P (3) 69*e*. Refractory shapes and method of producing, P (6) 175*a*. Rotary kiln, P (1) 24*e*. Shaft kiln, P (3) 77*c*. Shaft kiln discharge mechanism, P (2) 56*d*. Shaft kiln and method of operation, P (6) 182*c*. Shapes and method for lining a rotary kiln, P (8) 241*e*. Taphole for a metallurgical vessel, P (1) 14*h*. Zircon refractory, P (1) 14*i*, P (4) 98*a*.

Hardeman, G. E. G. See Beekenkamp, P.

Hardemon, J. E. See Eddy, W. H.

Hardie, L. A. Gypsum-anhydrite equilibrium at one atmosphere pressure, (5) 153*e*.

Hardiman, B. P. See Evans, P. E.

Harding, B. C., and Mortlock, A. J. Diffusion of Be in MgO, (10) 319*e*.

Hards, K. W. Ultrasonic speed diamond machining, (3) 61*f*.

Hardy, C. W. Refractories for the 80-ton FOS furnace at Dorman Long (Steel), Ltd., (9) 268*i*.

Hardy, H. R., Jr. Loading system for the investigation of the inelastic properties of geologic materials, B (3) 90*h*.

Hardy, J. F., Gridley, P. F., and Rivin, D. Preparation of metallurgical carbon, P (5) 135*h*.

Hardy, J. R. See Karo, A. M.

Hardy, J. R., and Lidiard, A. B. Displacements and polarization caused by point defects in ionic crystals, (1) 28*b*.

Hardy, W. A. Optical fiber laser device, P (3) 73*i*.

Hare, R. Meissen porcelain collection of Ernst Schneider, (4) 91*g*.

Hare, W. F. J. See Layer, E. H., Jr.

Harendza-Harinxma, A. J. See Vratny, F.

Harget, P. J., and Sturgill, D. T. Method for making thermistors, P (10) 310*d*.

Hargis, B. M. Ceramic-to-metal seal, P (8) 244*d*.

Harima Refractories Co., Ltd. Low temperature burned refractory brick and method of making, P (5) 135*g*.

Harker, H., and Horsley, J. B. Electron spin resonance in neutron-bombarded graphite, (4) 109*c*.

Harkort, D., and Kling, H. G. Experiments with the quasi-isostatic pressing method, (10) 312*c*.

Harmon, R. W. See Kalb, J. W.

Harms, J. D. Plate electrode assembly for electrostatic precipitator, P (6) 179*f*.

Harms, W. O. See Hamner, R. L.

Harnisch, H. See Heymer, G.

Harnsberger, H. F. See Mulaskey, B. F.

Harp, J. Ceramics engineering of the future (I), (9) 275*c*; (II), (10) 312*a*.

Harper, J. S. See Wilczynski, J. S.

Harper, K. W. Fiber optics scan system, P (9) 265*c*.

Harper, S. A. Method for preparing a europium-activated yttrium vanadate phosphor, P (8) 245*c*.

Harrell, B. R., Goodenough, R. D., and Gregory, R. L. Preparation of sodium metasilicate pentahydrate, P (9) 279*f*.

Harrick, N. J. Vertical double-pass multiple reflection cell for internal reflection spectroscopy, P (10) 316*g*.

Harrington, R. E. See Spaite, P. W.

Harrington, R. V. Radiation window glass, P (3) 66*c*.

Harris, B. See Peacock, J.

Harris, B., and Jones, P. A. Process for producing pigmentary metal oxides substantially free from falling accretion material, P (3) 78*d*.

Harris, D. C., Jambor, J. L., Lachance, G. R., and Thorpe, R. I. Tintinaite, the antimony analog of kobellite, (9) 288*e*.

Harris, D. M., and Buchter, H. H. Electric resistance heaters, P (10) 309*b*.

Harris, H. A. Method and means for controlling flow in a vertical shaft kiln, P (10) 296*c*.

Harris, J. M., and Loughridge, F. A. Electric discharge device having polycrystalline alumina end caps, P (4) 99*h*.

Harris, J. R., and Rossington, D. R. Comparison of surface states of quartz, cristobalite, and silicic acid, (10) 319*j*.

Harris, L. A., and Yakel, H. L. Crystal structure of Y_2BeO_4, (6) 184*f*.

Harris, M. R., and Whitaker, G. Surface properties of hydrolyzed titania (IV) rates of sorption on porous titania, (1) 33*a*.

Harris, N. H., and Cook, R. L. Formation mechanism of $PbTiO_3$, (5) 152*f*.

Harris, R. J., Sr. Chromatographic sample injection apparatus, P (3) 76*d*.

Harris, T. E. Structure for large diameter grinding mill, P (11) 346*a*. See Kozlowski, M. M.

Harris, W. H., Jr. Method of making a tool for removing material from workpieces and product thereof, P (7) 193*g*.

Harris-Maddox, B. Ultrasonic testing of solid-propellant rocket motors, (9) 277*c*.

Harrison, J. D. L. See Russell, L. E.

Harrison, K. T. See Scott, K. T.

Harriss, R. C. Clay minerals and oceanic evolution, B (9) 289*c*.

Harrop, P. J., Oakley, G., and Campbell, D. S. Reactive sputtering of manganese and titanium, (10) 308*e*.

Harrop, P. J., and Wanklyn, J. N. Dielectric constant of zirconia, (2) 58*a*. Embrittlement of oxide films on zirconium by neutron irradiation, (10) 320*i*. Influence of neutron irradiation on ionic mobility in cubic zirconia, (10) 322*d*.

Harrop Precision Furnace Co. Calorimeter apparatus and method of directly determining enthalpy, P (6) 181*d*.

Harry W. Dietert Co. Granular material conditioning apparatus, P (6) 174*b*. Granular material testing apparatus, P (3) 76*f*.

Hart, A. W., and Foss, G. J. Purging mechanism, P (3) 66*b*.

Hart, H. V., and Drickamer, H. G. Effect of high pressure on the lattice parameters of Al_2O_3, (6) 185*g*.

Hart, J. L., and Chaklader, A. C. D. Superplasticity in pure ZrO_2, (1) 32*j*.

Hart, L. D. See Pearson, A.

Hart, P. B. Oxide deposition in silicon epitaxial systems, (4) 99*b*.

Hartlapp, G. See Heymer, G.

Hartley, H. T. See Baak, T.

Hartley, J. M. See Knop, O.

Hartman, J. E. Directory of United States standardization activities, (1) 21*c*.

Hartman, R. A. See Boyer, J. L.

Hartman-Huyck Systems Co., Inc. Gated electroluminescent display device having electroluminescent cells with one cell including a photoconductor element, P (3) 72*h*.

Hartmann, H. J., and Widmann, H. Method of producing semiconductor assemblies, P (10) 310*g*.

Hartmann, S. R. See Kurnit, N. A.

Hartwig, J. Coating carbon substrates with refractory metal carbides, P (10) 304*c*.

Hartzerkleinerungsmaschinen VEB. Method and apparatus for removing textures in ceramic or similar materials, P (7) 211*c*.

Haruta, K. Intensity of X rays diffracted from an elastically vibrating [quartz] single-crystal plate, (2) 54*a*.

Harvey, E. R. See Kreuchen, K. H.

Harvey, P. C. Thermocouple gage control, P (11) 348*b*.

Harvey, P. J., and Hoodless, I. M. Self-diffusion and ionic conductivity in single crystals of cesium chloride, (8) 256*i*.

Harvey, R. D. Thermal expansion of certain Illinois limestones and dolomites, (4) 118*a*.

Harvey, R. L. See Gordon, I.

Harvin, R. L. See Mayland, B. J.

Harward, M. E. See James, D. W.

Harward, M. E., and Brindley, G. W. Swelling properties of synthetic smectites in relation to lattice substitutions, B (7) 224*g*.

Harward, M. E., and Carstea, D. D. Properties of vermiculites and smectites—expansion and collapse (abstract), B (9) 289*f*.

Harwood, D. J. See Maxwell, P. S.

Harwood Engineering Co. High pressure [isostatic] press, P (7) 211*c*.

Hasan, R. See Safdar, M.

Haschka, H., and Poph, W. Coating of feed and breed particles in a fluidized bed under reduced pressure, (7) 200*e*.

Hase, H., and Winkler, H. J. Discharge brick for casting ladles, intermediate containers, etc., P (7) 204*a*.

Hase, N., and Onuki, M. Infrared absorption due to free electrons in CdSe, (5) 153*c*.

Hasegawa, H., Suito, E., and Kondo, M. Process for the manufacture of modified clays, P (2) 57*a*.

Hasegawa, K. See Hayashi, H.; Kozuka, T.; Nakayama, N.

Hasegawa, M. See Kato, E.; Niizeki, N.

Hass, G., and Thun, R. E. (editors). Physics of Thin Films—Advances in Research and Development (Vol. 3), B (8) 260*d*.

Hassan, F. See Bishay, A.

Hassanein, M. Solid-state reactions in the system cadmium-magnesium-tin oxides, (3) 86*b*.

Hasson, D., Avriel, M., Resnick, W., Rozenman, T., and Windreich, S. Mechanism of calcium carbonate scale deposition on heat-transfer surfaces, (5) 147*e*.

Haszko, S. E. See Wolfe, R.

Hata, T. See Aoki, S.; Nakayama, N.

Hatch, S. E. See Carnall, E., Jr.

Hatch, S. E., and Weagley, R. J. Calcium fluoride optical elements and method of making, P (4) 94*e*.

Hatcher, R. D. See Dienes, G. J.

Hatta, T. See Semba, K.

Hattiangadi, R. R. Cement industry and chemical engineering, (5) 124*f*.

Hattori, M. See Brandt, W. W.; Tsubaki, T.

Hattori, T. See Yamamoto, R.

Hauck, J. E. Glass parts—how to select and specify, (4) 93*f*.

Hauel, A. P. Gold decorating compositions and method, P (10) 312*c*.

Hauffe, K., with Seyferth, C. Reactions in and on Solids, B (3) 90*h*.

Haught, G. J. Drum-tumbler holder, P (7) 211*b*. See Eckert, J. S.

Hauser, O., and Schenk, M. Thermodynamic treatment of radiation-induced phase transformations and its application to some perovskites, B (10) 329*c*.

Hausner, H. H. (editor). Coatings of High-Temperature Materials, B (7) 225*e*. Slip casting metal powders, B (3) 80*f*.

Hausner, H. H., Roll, K. H., and Johnson, P. K. (editors). Perspectives in Powder Metallurgy—Fundamentals, Methods, and Applications (Vol. I) New Methods for Consolidation of Metal Powders; (Vol. II) Vibratory Compacting—Principles and Methods, B (3) 89*f*.

Hauth, J. J. Vibrational compaction of nuclear fuels, B (3) 90*b*.

Haveg Industries, Inc. Glass fiber mats, P (3) 65*h*.

Havel, C. J. Beryllium product comprised of Be particles coated with a metal beryllide, P (8) 240*b*.

Havinga, E. E. Shell model of interionic interactions for $BaTiO_3$, (3) 72*c*.

Hawkins, D. B. Zeolite studies (I) synthesis of some alkaline earth zeolites, (3) 88*g*; (II) ion-exchange properties of some synthetic zeolites, (4) 119*c*.

Hayakawa, M., and Yasutake, Y. Method of preparing sodium tripolyphosphate, P (8) 251*h*.

Hayakawa, S. See Ikushima, H.; Matsuo, Y.; Mikoda, M.

Hayami, R. See Brindley, G. W.

Hayashi, H. See Takagi, H.

Hayashi, H., Nakayama, N., Hasegawa, K., Mizukusa, S., Takagi, H., and Torii, Y. Phase transition under high pressure (VI) mineral phases of equimolar mixture of NiO and SiO_2 at high pressure and high temperature, (3) 85*g*.

Hayashi, K. See Suzuki, H.

Hayashi, M. See Ueno, T.

Hayashi, S. See Fujiwara, S.

Hayashi, T. Corrosion tests by standard (crucible) method with reference to slag quantity and effect of heating rate, (10) 302*g*. Results of differential load tests on magnesia clinker and brick of various kinds, (9) 269*a*. Study on characteristics of electric furnaces for crucible erosion tests, (10) 304*d*. See Yasufuku, M.

Hayashi, T., and Nakano, T. Tunnel emission from Al-Al_2O_3-metal structures, (11) 357*h*.

Hayden, H. W. See Floreen, S.

Haydl, W. H. High field domains in *n*-type cadmium sulfide, (4) 111*f*.

Hayes, C. I., Inc. High temperature furnace, P (1) 24*c*.

Hayes, J. B. See Mossler, J. H.

Hayes, J. C. Method of catalyst preparation, P (1) 25*d*. Production of alumina, P (1) 14*e*. See Mitsche, R. T.

Hayes, J. F. Stability and properties of the synthetic pyroxene $CaAl_2SiO_6$, (5) 158*i*.

Hayes, W. See Bessent, R. G.; Brown, F. C.

Hayes, W., and Macdonald, H. F. Effects of uniaxial stress and electric fields on localized vibrational modes of H^- and D^- ions in CaF_2, (1) 28*f*.

Hayman, C. See Gross, P.

Hays, J. F. See Uhlmann, D. R.

Hazell, R. G. See Christensen, A. N.

Head, K. See Beynon, J.

Heald, E. F. See Speidel, D. H.

Healy, R. M., and Royer, L. T. Pyrohydrolytic attack of rare earth fluorocarbonate ores, P (7) 215*b*.

Heasley, J. H. See Haggerty, J. S.

Heath, C. P., Lumsden, D. N., and Carozzi, A. V. Petrography of a carbonate transgressive-regressive sequence—the Bird Spring group (Pennsylvanian), Arrow Canyon Range, Clark County, Nevada, (1) 31*b*.

Heath, D. L. Use of alumina in whiteware bodies, B (3) 89*d*.

Hebert, N. C. See Ross, J. W.

Hecht, H. G. Study of the structure of nickel in soda-boric oxide glasses, (5) 129*b*.

Hecht, H. G., and Johnston, T. S. Study of the structure of vanadium in soda-boric oxide glasses, (5) 129*c*.

Hecht, H. G., and Taylor, E. D. Thermoluminescent study of the color centers in irradiated polycrystalline MgO, (8) 258*c*.

Heckel, R. W., and Youngblood, J. L. X-ray line broadening study of explosively shocked MgO and α-Al_2O_3 powders, (8) 258*e*.

Heckman, R. C. See Glower, D. D.

Heckman, R. W. See Weaver, E. A.

Heckman, R. W., Ringlien, J. A., and Williams, E. L. Sodium diffusion and electrical conductivity in sodium-aluminosilicate and sodium-lime-aluminosilicate glasses, (1) 7*i*.

Heckmann, H. See Kroeger, K.

Hed, A. Z. See Bransky, I.; Kofstad, P.

Hed, A. Z., and Tannhauser, D. S. High temperature electrical properties of manganese monoxide, (5) 138*e*.

Hedberg, B. See Malinowski, R.

Hedden, W. A., Bowers, D. J., and King, B. W., Jr. Radiant heating panels and resistive compositions for them, P (11) 332*j*.

Hedstroem, B. Computation techniques in chemical engineering, (10) 327*j*.

Hedstrom, R. O., Litvin, A., and Hanson, J. A. Influence of mortar and [concrete] block properties on shrinkage cracking of masonry walls, (6) 165*c*.

Hedvall, J. A. Solid State Chemistry—Whence, Where, and Whither, B (4) 121*f*.

Heertjes, P. M., and Kossen, N. W. F. Measuring the contact angles of powder-liquid systems, (1) 21*h*.

Heeschen, J. P. Nuclear magnetic resonance spectrometry, (10) 315*d*.

Heestand, R. L., and Leitten, C. F., Jr. Boron carbide article and method of making, P (5) 134*e*.

Hegarty, B. A. See Langridge, A.

Hegde, M. S. See Bhide, V. G.

Hegner, P. Treatment of phosphogypsum to form building plaster—effect of phosphorus compounds on the quality of plaster, (10) 296*b*.

Heian, G. A. Apparatus for controlling coating depth in a balling drum, P (2) 53*h*.

Heidam, N. Z. See Saermark, K.

Heigl, C. Ceramic artists and their work—Wilhelm and Elly Kuch, (3) 61*i*.

Heiland, G., and Ibach, H. Pyroelectricity of zinc oxide, (11) 355*f*.

Heilig, J. A. See Lawley, K. L.

Heilmann, P. See Hoerl, E. M.

Heim, M. Apparatus for pyrolytic production of semiconductor material, P (1) 17*j*.

Heiman, F. P. Donor surface states and bulk acceptor traps in silicon-on-sapphire films, (5) 151*d*. Method of fabricating semiconductor device, P (9) 273*j*.

Heimann, E. See Balzar, H.

Hein, R. A., Flagella, P. N., and Conway, J. B. High-temperature enthalpy and heat of fusion of UO_2, (6) 186*g*.

Heine, V. Dangling bonds and dislocations in semiconductors, (11) 351*f*.

Heinemann, H. (editor). Catalysis Reviews (Vol. 1), B (8) 258*j*.

Heinicke, W., and Winterling, G. Temperature dependence of stimulated Brillouin scattering in quartz, (11) 357*c*.

Heinrich Maltner, G.m.b.H. Piezoelectric spark igniter, P (11) 345*a*.

Heinze, G. Process for the production of molecular sieve granules, P (3) 78*d*.

Heise, R. See Schnuerch, R.

Heiss, A., and Dode, M. Research on the system uranium-oxygen-carbon, (1) 31*i*.

Heiss, A., Lemonnier, J. M., and Dode, M. Small furnace for studies on chemical equilibria at high temperatures, (6) 181*g*.

Heiter, G. Electrostatic enameling brings an improvement in quality, (1) 4*d*.

Helfferich, F. See Peterson, D. L.

Helgeson, J. See Wertz, J. E.

Helgesson, C. I. Influence of coating variables on the properties of flame and plasma sprayed ceramic coatings, B (9) 291*d*. Investigation of the bonding mechanism between metals and ceramics (I) ceramic-to-metal seals; (II) ceramic-to-metal seals of heavy metals type to beryllia ceramics, (2) 37*j*. See Brosset, C.

Hellbardt, G., and Michelitsch, M. Method of polishing gallium arsenide single crystals by reaction with a gaseous atmosphere incompletely saturated with gallium, P (10) 310*f*.

Heller, P. Nuclear-magnetic-resonance studies of critical phenomena in MnF_2 (I) time-average properties, (11) 355*c*.

Heller, W. R. See Bron, W. E.

Helliwell, D. P. Additives to sand molds and cores, P (7) 204*c*.

Hellstrom, M. J. See Lin, H. C.

Helsen, J. See Fripiat, J. J.

Heltemes, E. C. Far-infrared properties of cuprous oxide, (8) 253*h*.

Helton, D. M., and Wymer, R. G. Electrical potential method for dispersion of metal oxide microspheres, P (2) 53*a*.

Hem, J. D. Graphical methods for studies of aqueous aluminum hydroxide, fluoride, and sulfate complexes, (6) 180*d*.

Hem, J. D., and Roberson, C. E. Form and stability of aluminum hydroxide complexes in dilute solution, (4) 110*c*.

Hemmingsson, S. See Ahrland, S.

Hemphill, R. J. See Hickman, B. S.

Hench, L. L. See Freiman, S. W.; Kinser, D. L.

Hench, L. L., and Daughenbaugh, G. A. Radiation effects in semiconducting glasses, (8) 233*h*.

Henderson, C. M., and Beaver, E. R., Jr. Two-phase thermoelectric body comprising a boron-carbon matrix, P (1) 19*c*.

Henderson, J. See Williams, J. R.

Henderson, J. R., Muramoto, M., and Gruber, J. B. Spectrum of Nd^{3+} in lanthanide oxide crystals, (11) 357*a*.

Henderson, P. Determination of phosphorus in rocks and minerals by activation analysis, (3) 77*f*.

Hendricks, D. M., Whittig, L. D., and Jackson, M. L. Clay mineralogy of andesite saprolite, B (9) 289*i*.

Hendrickson, T. A. See Trumbo, P. W.

Hendrix, W. P. See Orr, C., Jr.

Hendron, J. A., Groble, K. K., Gruetzmacher, R. W., McClurg, G. O., and Retsky, M. M. Corona and microwave methods for the detection of voids in glass-epoxy structures, (7) 212*b*.

Hendron, J. A., Groble, K. K., and Wangard, W., II. Determination of the resin-to-glass ratio of glass-epoxy structures by beta-ray backscattering, (9) 276*a*.

Hendry, A. W. Aspects of design in high rise load bearing brickwork, (9) 266*c*.

Hengstler, R. E. See Maddox, R. E.

Henkel, W. W. Method of plastering wall surfaces and joint sealing compound used, P (8) 229*b*.

Henkel & Cie G.m.b.H. Process for the treatment of metal surfaces prior to enameling, P (5) 126*c*.

Hennicke, H. W. See Leers, K. J.; Schwiete, H. E.

Hennicke, H. W., and Sturhahn, H. H. Basic scientific and technological problems in isotatic pressing, (10) 311*i*.

Hennig, G. R. Optical transmission of graphite compounds, (6) 187*a*.

Hennig, R. K. Apparatus for removing tipped-over bottles from a conveyor, P (5) 129*d*.

Henning, D. C., and Parker, R. Transient response of an intrinsic thermocouple, (11) 347*c*.

Hennings, K. See Schuetze, H. J.

Henrichsen, R. E. See Cutler, I. B.

Henrie, T. A. See Kleespies, E. K.

Henrion, G., and Pungor, E. Simultaneous determination of alkali and alkaline-earth metals by precipitation titration in nonaqueous medium, (4) 103*h*.

Henry, E. C., and Illyn, A. V. Some relations between grain size and properties in high purity barium titanate ceramics, (9) 272*h*.

Henry, G. R. Refractory gunning mix, P (3) 69*e*. Zircon refractory, P (1) 14*i*, P (4) 98*a*.

Henry, J. L., Paulson, D. L., Blickensderfer, R., and Kelly, H. J. Phase relations in the uranium monocarbide region of the system U–C–O at 1700°C, (3) 84*i*.

Henry, P. See Piendl, J. N.

Hensiek, H. H. Faster drying with modern metallic battens, (10) 316*j*.

Hensler, D. H. See Fuls, E. N.

Hensler, J. H. See Cullen, G. V.

Hensler, J. H., and Cullen, G. V. Grain shape change during creep in magnesium oxide, (1) 29*f*. Shape of the compression creep curve for magnesium oxide, (4) 115*b*. Stress, temperature, and strain rate in creep of magnesium oxide, (11) 357*e*.

Henster, J. R. See Brewster, G. F.

Heny, S. L. See Anderson, J. W.

Hepworth Iron Co., Ltd. Clay pipes, P (5) 131*a*, P (7) 199*j*. Pipe couplings, P (6) 172*c*. Vitrified clay piping or conduit, P (7) 199*i*.

Her Majesty's Postmaster General. Thermocompression bonding of metals to semiconductor, metallic, or nonmetallic surfaces, P (8) 246*c*.

Herak, R. M. See Manojlovic, L. J. M.

Herbsleb, F. A. See Lowdermilk, M. J.

Herczog, A. Ferroelectrics and ferrites crystallized from glass, (10) 307*j*.

Herd, S. R. See Glang, R.

Herlet, A., and Bernuth, G. von. Stabilized *pnpn* switch with rough area shorted junction, P (5) 143*c*.

Herlet, A., and Patalong, H. Semiconductor thyristor of *pnpn* type, P (5) 143*a*.

Hermann, F. Firing is the top operation of brickmaking, (10) 301*h*.

Hermans, M. E. A. Particle growth by controlled flocculation, B (7) 226*c*.

Hermes, O. D., and Ragland, P. C. Quantitative chemical analysis of minerals in thin section with the X-ray macroprobe, (5) 146*c*.

Heron, S. D. See Johnson, H. S., Jr.

Herrington, R. A. See O'Connell, T. B.

Herrmann, H. See Roeder, M.

Herrmann, R. Sensitivity of bodies for tableware and electrical porcelain ware to cracking during drying, B (9) 291*c*.

Herron, R. H., Beechan, C. R., and Padfield, R. C. Slag attack on carbon-bearing basic refractories, (1) 12*c*.

Hershinger, L. W. See Kane, W. M.

Herstad, O., and Motzfeldt, K. Vapor pressures in the system Al–Al_2O_3—effusion and pressure compensation methods, (1) 33*c*.

Hertl, W. Fibrous TiC, (1) 24*j*. See Pultz, W. W.

Herzog, E. Ceramic artists and their work—Walter Popp, (7) 193*j*.

Herzog, J. A. See Burte, H. M.

Heslop, R. B., and Pearson, E. F. Liquid extraction of molybdophosphoric and molybdoarsenic acids—application to the determination of phosphorus in the presence of arsenic, (2) 54*b*.

Hess, F. O. Metal heating, P (1) 4*h*. Tube heater, P (4) 104*e*.

Hess, R. L. Program for testing refractory clay prospect samples, (2) 45*g*.

Hesten, F., and Newell, F. W. Apparatus for and methods of toughening glass articles, P (10) 300*b*.

Hester, R. E. Raman spectrometry, (10) 315*b*.

Hetherington, G., and Bell, L. W. Analysis of high-purity synthetic vitreous silicas, (3) 63*e*.

Heuer, A. H., and Burnett, P. Evidence for MgO whisker growth by a vapor-liquid-solid mechanism, (1) 29*b*.

Hevey, R. W. Capacitor and method of making, P (10) 309*g*.

Hewlett-Packard Co. Method of making a reliable low-ohmic nonrectifying connection to a semiconductor substrate, P (10) 310*a*.

Hey, A. W. See Livey, D. T.

Heyer, H. Kinetics of crystal growth, (5) 154*e*.

Heyes, R. See Silverwood, F. W.

Heyl, A. V., Hosterman, J. W., and Brock, M. R. Clay-mineral alteration in the Upper Mississippi Valley zinc-lead district, B (6) 192*d*.

Heyligers, H. J. M. See Lieth, R. M. A.

Heyman, M. D. Mica paper, P (2) 51*j*.

Heymer, G., and Harnisch, H. Process and apparatus for the manufacture of nitride powders of Al, B, Si, or Zr, P (2) 47*e*. Process and apparatus for the manufacture of titanium nitride, P (1) 13*j*.

Heymer, G., Hartlapp, G., and Traulsen, K. Process for the manufacture of sodium tripolyphosphate with a high content of phase I material (high temperature modification), P (9) 279*b*.

Heyndryckx, P., and Bonnan, D. Gas chromatography in analysis of bubbles in glass, (11) 334*a*. Gas chromatography in analysis of glass furnace atmospheres, (11) 334*a*.

Heynes, M. S. R. See Mehta, R. R.

Heystek, H. Hydrothermal rhyolitic alteration in the Castle Mountains, California, B (5) 160*d*.

Heywang, W. Method of producing semiconductor components, P (1) 18*i*.

Heywang, W., and Sirtl, E. Method of producing monocrystalline semiconductor members with layers of different conductance, P (4) 100*g*.

Hibbert, N. S. See Steele, B. R.

Hibino, T., Watanabe, O., and Tanida, M. Effects of V_2O_5 on the formation of zircon, (5) 151*a*.

Hibshman, H. J. Diamond growth process, P (6) 163*i*.

Hicinbothem, W. A., Jr. See Larrabee, R. D.

Hickam, W. M. See Gulbransen, E. A.

Hickerson, W. L. Vibratory conveyor and feeder systems, (10) 312*a*.

Hickle, J. C. See Carl, W. L.

Hickman, B. S. See Hanna, G. L.; Hilditch, R. J.; Walker, D. G.

Hickman, B. S., Rotsey, W. B., Hilditch, R. J., and Veevers, K. Effects of irradiation on beryllia-based fuels, (3) 67*c*.

Hickman, B. S., Rotsey, W. B., and Veevers, K. Removal of anisotropic growth strains in neutron-irradiated beryllium oxide, (3) 86*a*.

Hickman, B. S., Walker, D. G., and Hemphill, R. J. Comparison of microscopic and X-ray growth in irradiated BeO single crystals, (2) 43*h*.

Hickok, R. L. Synthesis of calcium chlorspodiosite, P (7) 210*b*. Synthesis of halophosphate phosphors using calcium chlorspodiosite, P (7) 210*c*.

Hicks, J. C. See Martinet, J. R.

Hicks, J. F. G. Homogeneity and the structure of glass, (10) 297*f*.

Hickson, K. Place of emission spectrography and X-ray fluorescence in chemical analysis (II) X-ray fluorescence, B (7) 224*g*.

Hielscher, J. Investigation of bond tensile strength, bond shear, and the effect of precompression on the shear strength of model brick masonry, (10) 301*e*.

Higatsberger, M. J. Matrix-type nuclear fuel element including fission product retentive materials, P (2) 47*f*.

Higbie, K. B. See Bauer, D. J.

Higgins, R. M. Controlled electrolytic treatment of materials, P (9) 272*e*.

Hilbrand, H. C. See Ethington, R. L.

Hildebrand, R. Discussion of "Face brick—semidry pressed," (10) 301*f*. Equipment for the preparation of raw materials, (11) 348*j*.

Hildebrandt, M., Nicolas, J., and Vassiliev, A. Cubic ferrite with a high upper frequency limit, P (10) 309*j*.

Hildenbrand, D. L., Hall, W. F., and Potter, N. D. Thermodynamics of vaporization of lithium oxide, boric oxide, and lithium metaborate, (5) 159*e*.

Hildenbrand, D. L., and Theard, L. P. Effusion studies, mass spectra, and thermodynamics of beryllium fluoride vapor, (3) 80*j*.

Hildinger, W. M., and Martinet, J. R. Refractory, P (8) 241*c*.

Hilditch, R. J. See Hanna, G. L.; Hickman, B. S.

Hilditch, R. J., Hickman, B. S., Rotsey, W. B., and Veevers, K. Behavior of beryllium oxide-based dispersion fuels, (2) 57*h*.

Hildon, A. M. See Marshall, J. G.

Hill, D. G., Cantor, S., and Ward, W. T. Molar volumes in the LiF–ThF_4 system, (5) 155*a*.

Hill, D. H. Laminating process and apparatus, P (1) 9*f*.

Hill, J. S. See Bonnet, R. E.

Hill, R., and Lauer, R. B. Growth of homogeneous mixed crystals of zinc cadmium sulfide, (1) 29*g*.

Hill, R. F. See Gifford, F. E.

Hill, R. J., and Knopp, C. F. Oxidation resistant high temperature ceramic-to-metal seal compatible with cesium, (1) 4*g*.

Hill, R. M. Single carrier transport in thin dielectric films, (11) 342*f*.

Hill, R. R. Wall structure with a metal shell and lining blocks secured by support bars and retainer pins, P (7) 205*h*.

Hill, T. Catalyst, preparation thereof, and polymerization process using the catalyst, P (1) 25*i*.

Hillard, A. Graphite heat exchangers for high pressures, (10) 316*j*.

Hiller, D. M. Process for dispersing refractory metal oxides in other metals, P (8) 241*h*.

Hillman, T. F., and Rodgers, H. G. Loading apparatus, P (10) 300*e*.

Hills, A. W. D. (editor). Heat and Mass Transfer in Process Metallurgy—Proceedings of a Symposium Held by the John Percy Research Group in Process Metallurgy, Imperial College, London, April 1966, B (1) 34*f*.

Hilton, A. R. Nonoxide chalcogenide glasses as infrared optical materials, (9) 263*j*. Nonoxide chalcogenide infrared transmitting glasses, (2) 39*i*. See Jones, C. E.

Hilton, A. R., Jr., and Jones, C. E., Jr. Glasses and method of making, P (6) 170*e*.

Hilton, A. R., Jr., Jones, C. E., Jr., and Brau, M. J. Ge–Te–As glasses and method of preparation, P (1) 9*b*.

Himmelberg, G. R., and Phinney, W. C. Granulite-facies metamorphism, Granite Falls, Montevideo Area, Minnesota, (4) 110*f*.

Hinchliffe, R. See Warren, R.

Hinckeledey, A. See Kahl, P.

Hinckley, D. N. Variability in "crystallinity" values among the kaolin deposits of the Coastal Plain of Georgia and South Carolina B (5) 160*h*.

Hinder, J. W. Antje Breckwoldt—woman potter of Sylt, (1) 1*j*. Fine stoneware of Heidi Kippenberg, (10) 293*j*.
Hinds, C. E. Intumescent coated roofing granules and asphalt composition felt-base roofing containing them, P (5) 131*b*.
Hindustan Steel, Ltd. Jointing material for use in recuperators in soaking pits, viz., chromesil, P (5) 135*g*.
Hinkle, V. O., Jr. See Zuleeg, R.
Hinkle, V. O., Jr., and Zuleeg, R. Mesa multichannel field-effect triode, P (8) 245*a*.
Hinman, C. A. See Bates, J. L.
Hinson, A. L., and Smith, D. C. Method of treating the surfaces of glass containers, P (2) 41*i*.
Hira, R. J. Basic concepts of instrumentation, (6) 180*f*.
Hirabayashi, M. See Yamaguchi, S.
Hiragushi, K. See Ohba, H.
Hirai, A. See Kubo, T.
Hirai, T. See Watanabe, Kenichi; Yajima, S.
Hiraiwa, O. See Suzuki, K.
Hirohata, H. See Nagata, T.
Hirokawa, S. See Ono, M.
Hirooka, K. See Kawai, N.
Hirose, T., Yoshioka, H., and Horai, K. Conductivity increase of reduced rutile with the saturation of electron spin resonance, (4) 107*b*.
Hirose, Y. See Olsen, A. R.
Hirose, Y., and Takeda, S. Method for the production of ceramic nuclear fuel elements, P (1) 13*j*.
Hirota, E. See Okazaki, C.
Hirota, E., and Mihara, T. Temperature variation of the initial permeability in Ni and Ni-Zn ferrites containing excess iron and small amounts of cobalt, (8) 257*e*.
Hirota, N. See Hara, T.
Hirota, S. See Yamaguchi, M.
Hirsch, H. H. See Van Buren, C. E.
Hirsch, R. F. See Rulfs, C. L.
Hirsh, W. See Sun, Shiou-Chuan.
Hirsl, J. See Maurer, K.
Hirthe, W. M. See Wackman, P. H.
Hitachi, Ltd. Method for introducing calcium oxide into manganese-zinc ferrite magnetic materials, P (7) 209*f*. Method for manufacturing at least one electrically isolated region of a semiconductive material, P (6) 178*f*. Method for the production of ceramic nuclear fuel elements, P (1) 13*j*.
Hitachi Seisakusho Kabushiki Kaisha. Method of production of semiconductor devices, P (7) 209*g*. Production of boron carbide, P (5) 136*e*.
Hitchen, A. See Barkley, D. J.
Hitco. Carbon fibers and method, P (2) 46*f*. Metal carbide formation on carbon fibers, P (3) 68*j*. Method for heat treatment of vitreous fibers, P (2) 41*c*.
Hitzemann, G. See Tillmann, P.
Hivac, Ltd. Cold cathode gas discharge tubes having an optically opaque masking plate, P (5) 140*i*.
Hivert, V. See Dautreppe, D.
Hlasivcova, N. See Coufova, P.
Hloch, A., Kohlhaas, R., Medic, N., and Neises, H. Refractory masses, P (1) 14*i*.
Ho, C., and Handy, R. L. Electrokinetic properties of lime-treated bentonites, B (6) 191*j*. Modification of Ca montmorillonite by low-temperature heat treatment, B (7) 225*b*.
Ho, C. Y., Powell, R. W., and Liley, P. E. Thermal Conductivity of Selected Materials (II), B (9) 290*d*.
Ho, S. M. See Bratton, R. J.
Hoare, H. C., Mostyn, R. A., and Newland, B. T. N. Ultrasonic atomizer applied to atomic absorption spectrophotometry, (5) 146*h*.
Hobbs, R. E. Method of terminating thin [Ta] film components, P (7) 209*g*.
Hobden, M. V. See Hulme, K. F.
Hobo, K. See Isotani, M.
Hochberg, A. K. See Poehler, T. O.
Hochstetter, R. Structure of binder in hydrothermally bonded sand-lime bodies (I), (10) 295*h*.
Hocine, R. See Bernard, G.
Hockey, J. A. See Hambleton, F. H.
Hocking, M. G. See Vasantasree, V.
Hodby, J. W. See Bessent, R. G.
Hodgkiess, T. See Wood, G. C.
Hodgkinson, H. R. Study of the effects of variations in the mode of pressing on the fired properties of building bricks, B (9) 291*e*.
Hodgson, B. P. See McMillan, P. W.
Hodin, J. P. Janet Darnell Leach, (3) 61*j*.
Hodin, J. P., and Leach, B. Bernard Leach—A Potter's Work, B (10) 328*e*.
Hodkin, E. N., Nicholas, M. G., and Poole, D. M. Wetting of uranium carbide, (10) 327*g*.
Hodkinson, J. R. Particle sizing by means of the forward scattering lobe, (9) 276*j*.
Hoekstra, H. R. Phase relations in the rare earth sesquioxides at high pressure, (5) 155*e*.
Hoekstra, H. R., Sigel, S., and Gebert, E. Unit cell of γ-UO_3, (4) 118*g*.
Hoekstra, J. Treatment of combustible waste products and catalyst therefor, P (5) 149*c*.
Hoekstra, P., and Keune, R. Pressure effects on conductance of frozen montmorillonite suspensions, B (9) 289*d*.
Hoelscher, H. E. See Roberts, G. L., Jr.
Hoens, M. F. A. Enameling of cast iron, (11) 332*j*.
Hoepfner, P. Cellulose ethers in ceramics, (10) 305*d*.
Hoepli, M. H. Refractory and process for making, P (10) 305*c*.
Hoerl, E. M., and Heilman, P. Epitaxial growth of UO_2 on graphite, (9) 282*e*.
Hoetink, B. J. Instrumentation for glass melting control, (2) 39*d*.
Hofer, H. See Schmid, A.
Hoffman, C. G. See Benz, R.
Hoffman, D. O. See Hovey, R. J.
Hoffman, J. R. See Rudy, E.
Hoffman, L. C. See Nakayama, T.
Hoffman, R. L. Burner for tempered flame operation, P (5) 147*g*.
Hoffman, R. W. Mechanical properties of thin condensed films, B (8) 260*f*.
Hoffmann, P. R. Ceramic lined return bend, P (1) 15*j*.
Hoffmann, U. Wear resistance of ceramic surface layers, B (9) 291*g*.
Hoffmann, W. See Bayer, G.
Hofmann, H. D. Early ceramic work of Emile Galle (1846–1904), the master of modern style in Nancy, France, (5) 124*c*.
Hofmann, J. J. See Mattimoe, P. T.
Hofmann, J. J., and Dunsmore, J. M. Polishing, P (10) 301*c*.
Hofmann, U., Schembra, F. W., Schatz, M., Scheurlen, D., Friedrich, H., and Dammler, I. Dry bending strength of kaolins and clays, (1) 15*c*.
Hofstadter, R. Europium activated strontium iodide scintillators, P (6) 177*g*.
Hofstein, S. R. Space-charge-limited ionic currents in silicon dioxide films, (1) 17*a*. Tritium-labeled field-induced proton transport in SiO_2 films, (11) 357*h*.
Hogan, J. P. Method of treating supported chromium oxide catalyst and polymerization therewith, P (4) 105*h*.
Hogg, W. R. See Coulter, W. H.
Hohenberger, J. H. Method of forming a coated abrasive wheel, P (8) 227*f*.
Hohenstein, J. Cermet resistors by concurrent rf and dc sputtering, (8) 242*i*.
Holder, J. See Gayet, B.
Holdridge, D. A. See Berkin, L. V. I.; Walker, E. G.
Holdridge, D. A., and Walker, E. G. Changes occurring in potters' plaster and in molds during service, B (9) 291*e*. Dehydration of gypsum and the rehydration of plaster, (6) 164*f*.
Holland, E. J., Jr. Pyrogenic silica production, P (10) 318*f*.
Holland, J. F. Describing temperature emf relation for thermocouples, (4) 102*g*.
Hollander, L. E., Jr. Semiconductor transducers, P (10) 311*d*.
Hollander, T. See Kalff, P. J.
Hollar, E. L. See Fulrath, R. M.
Hollaway, L. C. See Allinson, I. M.
Holle, R. F. Self-contained battery-powered electric incandescent lamp, P (8) 236*b*.
Holleck, H. Alloying behavior of HfB_2 with uranium and transition metal diborides, (9) 279*g*.
Hollenbeck, R. P. Fluorspar in the eastern United States, (3) 77*k*.
Hollenbeck, R. P., Browning, J. S., and McVay, T. L. Industrial sand in Pike County, Kentucky, (7) 214*e*.
Hollenbeck, R. P., and Tyrrell, M. E. Shales for lightweight aggregate in Appalachian region, Kentucky and Tennessee, (10) 301*j*.
Hollingsworth, C. A. See Granquist, W. T.
Holloway, P. W. See Baker, C. L.
Holm, J. L., and Kleppa, O. J. Enthalpy of formation of kyanite (Al_2SiO_5), (5) 152*d*. Thermodynamic properties of the aluminum silicates, (5) 159*c*.
Holmes, C. H., Spencer, E. G., Ballman, A. A., and Lonzo, P. V. Electrooptic effect in calcium pyroniobate, (5) 138*g*.
Holmes, J. T., Koppel, L. B., and Jonke, A. A. Fluidized bed disposal of fluorine, (1) 11*j*.
Holmes, T., and Timmermans, A. Superhigh-pressure mercury vapor discharge lamps, P (8) 236*a*.
Holmes, W. T., II, Banning, L. H., and Brown, L. L. Liquidus temperatures of titaniferous slags (I) TiO_2–Al_2O_3–SiO_2–CaO–MgO, (9) 284*a*.
Holmes, W. T., II, Banning, L. H., Brown, L. L., and Thompson, G. G. Liquidus temperatures of titaniferous slags (II) TiO_2–Al_2O_3–FeO–SiO_2–CaO–MgO, (9) 284*b*.
Holmquist, S. Sodium oxide activities in molten sodium sulfate and sodium silicates, (7) 197*i*.
Holmwood, R. A. See Glang, R.
Holonyak, N., Jr. See Johnson, M. R.
Holophane Co., Inc. Refractor for use in uniformly illuminating a polygonal area, P (1) 10*b*.
Holowach, J. See Conway, J. B.
Holt, J. B., Cutler, I. B., and Wadsworth, M. E. Kinetics of the thermal dehydration of hydrous silicates, B (6) 191*h*.
Holt, T. Central systems approach to grinding (I), (5) 123*g*.
Holtzberg, F. See Gambino, R. J.
Holtzberg, F., McGuire, T. R., and Methfessel, S. J. Process for modifying Curie temperature of ferromagnetic lanthanide chalcogen solid solution compounds, P (6) 178*f*.
Holtzberg, F., and Methfessel, S. J. Preparing large single crystalline bodies of rare earth chalcogenides, P (8) 246*a*.
Holverson, E. L., and Kevane, C. J. Electrical conduction by oxygen ions in cerium oxide, (5) 138*a*.
Holynska, B., and Langer, L. Determination of zirconium in Zr-bearing sand and Zr concentrates by a nondispersive X-ray fluorescence method, (4) 102*i*.
Holzl, R. A. Gaseous deposition method of making a thermocouple probe, P (1) 23*i*.
Honda, T. See Ishihara, T.
Honeywell, Inc. Biaxially anisotropic magnetic thin film structure with magnetic discontinuities, P (11) 343*f*. Process for optionizing electrical and physical characteristics of ferroelectric materials, P (1) 18*j*. Thermocouple with junction bead compressively supported by plug, P (11) 348*c*.
Honig, E. P., and Kotelaar, J. A. A. Electromigration and self-diffusion in ionic melts, (3) 80*b*.
Honig, J. M. See Chapin, D. S.; Reed, T. B.; Van Zandt, L. L.
Honjo, G. See Harada, J.
Honma, A. Nuclear spin-lattice relaxation in ferromagnetic insulators at low temperatures, (8) 255*j*.
Honma, K. Ceramic dielectrics, P (1) 17*b*.
Hood, J. S. See Currin, C. G.
Hoodless, I. M. See Harvey, P. J.
Hooge, F. N. Spectra of praseodymium in yttrium gallium garnet and in yttrium aluminum garnet, (10) 325*a*.
Hoogenboom, L. Variable capacitance force measuring transducer, P (8) 246*h*.
Hope, E. W. See Kittrick, J. A.
Hope, L. L. See Zemon, S.
Hopkins, E. C., and Cole, H. B. Apparatus for making fiber energy-conducting devices, P (11) 335*e*.
Hopkins, V. See Gaddis, D. H.; Kremith, R. D.
Hoppe, G., and Dangschat, R. Method of producing selenium midget rectifiers, P (1) 18*h*.
Hoppe, H. J. See Gotthardt, R.
Hoppe, R. Madelung constants, (10) 322*e*. See Vielhaber, E.
Hoppe, W., Mueller, N., and Schmitten, W. in der. Process for the fusion of metal oxides, P (9) 270*b*.
Horai, K. See Hirose, T.
Horgan, J. F. See Ellis, M. P.
Horiba, T., and Nakajima, Y. Method of producing silicon variable capacitance diodes by diffusion, P (10) 310*h*.
Horigome, S. See Kitagawa, H.
Horiguchi, Y., and Nomura, Y. Formation of tungsten and aluminum carbides by explosive shock, (2) 44*i*.
Horiguchi, Y., Nomura, Y., and Katayama, S. Effects of preshock treatment on synthesis of titanium and tungsten carbides, (7) 201*e*.
Horizons, Inc. Method of spinnerette cleaning during the preparation of inorganic oxide monofilaments, P (8) 247*e*.
Horlock, R. F., and Anderson, P. J. Molecular size pores in beryllium oxide powders, (7) 219*h*.
Horman, J. A. See Chang, S. S.
Horner, M. H. See Fassler, M.
Hornig, M., and Seiter, H. Method of producing semiconductor members by alloying metal into a semiconductor body, P (9) 274*f*.
Hornstra, J. See Roeder, E.
Horsch, E. See Scharbach, H.
Horsley, J. B. See Harker, H.
Horspool, J. M., Rose, N. F., and Finlayson, M. B. Fabrication of uranium-plutonium monocarbide ceramics, (11) 338*a*.
Horsting, C. W. See Dingwall, A. G. F.
Horton, W. H. Crystal structures and method of fabricating them, P (11) 343*j*.
Hosbein, L. H. See Cerny, J. J.
Hoshiko, Y. Causality in system structure, (5) 149*j*.
Hoshino, H. See Shimoji, M.
Hoshino, H., and Shimoji, M. Thermoelectric power of ionic crystals (II) thermoelectric power and ionic conductivity of sodium bromide containing barium bromide, (2) 50*j*.
Hoshino, M. See Ikeda, Y.
Hoskins, R. H. See Maiman, T. H.
Hosokawa, M., Matsuyama, T., and Nakamoto, M. Powder sifting machine, P (10) 312*h*.
Hossfeld, F. See Krauth, A.
Hosterman, J. W. See Heyl, A. V.; Knechtel, M. M.
Hostetler, P. B., Truesdell, A. H., and Christ, C. L. Activity coefficients of aqueous potassium chloride measured with a potassium-sensitive glass electrode, (4) 105*i*.
Hott, A. C. See Carniglia, S. C.
Houbart, I. Rotatable sample changer for an electron probe microanalyzer having means for maintaining a vacuum in the analysis chamber, P (3) 76*g*.
Hough, R. L. Apparatus for depositing material on a filament from ionized coating material, P (9) 275*e*. Method of making refractory metal nitride fibers, flakes, and foil, P (6) 174*j*. Vapor deposition of pyrolytic graphite on tungsten, P (7) 195*f*.
Hough, R. L., and Schwartz, H. S. High temperature dielectric reinforced composite, P (9) 270*c*.
House, H. W. Composite laminated resilient means for a press means, P (10) 312*b*.
Houser, A. F. See Cramer, R. H.
Housh, L. M. Preparation of magnesium hydroxide by treating dolomite with magnesium nitrate solution, P (10) 318*h*.
Houston, J. L. See Selig, H.
Hovey, R. J., and Hoffman, D. O. Variable density light transmitting device, P (10) 301*b*.
Hoviland, M. L. See Whaley, H. P.
Howard, E. E. Microcrystalline sintered bauxite abrasive grain, P (9) 261*g*.
Howard, R. A., and Tolley, G. C. Thermally stable carbon articles, P (10) 305*b*.

Howard, R. E. Random-walk method for calculating correlation factors—tracer diffusion by divacancy and impurity-vacancy pairs in cubic crystals, (9) 286*b*.

Howe, J. P. See McKenzie, D. E.

Howe, J. S., Jr. See Croeni, J. G.

Howell, P. A. Process for preparing crystalline zeolitic molecular sieves, P (10) 318*b*.

Hower, J. Order of mixed-layering in illite/montmorillonites, B (9) 289*e*.

Hower, J., and Mowatt, T. C. Mineralogy of illites and mixed-layer illite/montmorillonites, (2) 59*b*.

Howery, D. G., and Thomas, H. C. Ion exchange on the mineral clinoptilolite, (11) 353*h*.

Howeth, B. W. See Belasco, M.

Howmet Corp. Thermally insulated shell mold and method of making, P (5) 136*c*.

Hoyt, F. G. Tensioning apparatus for vibrator screens, P (1) 20*f*.

Hoyt, P. L., and Haisty, R. W. Preparation of epitaxial semi-insulating gallium arsenide by iron doping, (7) 207*h*.

Hoyt Wire Cloth Co. Tensioning apparatus for vibrator screens, P (1) 20*f*.

Hsu, C. T. Settling system, P (5) 144*f*.

Hsu, L. C. Selected phase relations in the system Al–Mn–Fe–Si–O–H—a model for garnet equilibria, (9) 286*j*.

Hsu, Pa Ho, and Bates, F. Formation of X-ray amorphous and crystalline aluminum hydroxides (extended abstract), B (5) 161*a*.

Huang, C. Y. D. Method of making an electrical resistor, P (10) 310*j*.

Huang, C. Y. D., and Merz, K. M. Glass bonded resistor compositions containing refractory metal nitrides and refractory metal, P (10) 309*g*.

Huang, P. M., and Jackson, M. L. Fluorine determination in minerals and rocks, (8) 248*g*.

Hubbard, W. N. See Greenberg, E.; Porte, H. A.; Rudzitis, E.

Hubble, D. H. Properties of brick for basic oxygen process as related to types of wear, (3) 67*e*.

Huber, J. M., Corp. Method of beneficiating clay by removal of titanium impurities, P (6) 183*b*.

Hubin, L. W., and Mentzer, E. K. Moisture indicating means and method, P (5) 135*e*.

Huchler, K. See Vollmer, H.

Hucke, E. E. Process of making an article having a hard carbide, boride, or silicide outer region, P (2) 47*g*.

Hudson, J. B. See Kressnerr, B. E.; Young, J. R.

Hudson, J. B., and Sandejas, J. S. Observation of adsorption and crystal nucleation by mass-spectrometric techniques, (8) 255*c*.

Huebner, F. New star-shaped steam injector gives complete heat distribution, (10) 317*b*.

Huet, H., Lorrain, C., Mahut, R., Mariette, R., and Vertes, P. Process of separation of uranium and thorium from a solution, P (4) 97*e*.

Huff, W. D. Mineralogy of Ordovician K bentonites in Kentucky, B (5) 160*f*.

Huffadine, J. M. See Rimmer, W. S.

Huffcut, H. W. Heat and corrosion resistant coating composition, P (9) 263*b*.

Huffstutler, M. C., Jr., and Kerns, B. T. Wire-saw cutting technique for optical crystals, (1) 23*g*.

Huggett, G. R., and Teegarden, K. Intrinsic photoconductivity in the alkali halides, (8) 254*d*.

Huggins, R. A. See Brimhall, J. L.

Hughes, A. E. Stability and production of *R'* centers in lithium fluoride, (11) 357*b*.

Hughes, B. P., and Bahramian, B. Accurate laboratory test for determining the absorption of aggregates, (4) 102*d*. Some factors affecting the compressive strength of concrete, (8) 228*j*.

Hughes, D. C., Jr. Automate thick-film production, (6) 176*a*.

Hughes, D. M., and Carter, G. Ultrahigh vacuum system for the preparation and study of surface properties of cadmium sulfide thin films, (5) 140*i*.

Hughes, E. W. Development of an electrodeposition process for porcelain enamel, (8) 229*e*. Electrodeposition for porcelain enamel, (10) 296*d*.

Hughes, F. H. Using diamond abrasive wheels, (2) 35*g*.

Hughes, F. R. Method of making a multialkali cathode, P (6) 178*e*.

Hughes, K., and Isard, J. O. Measurement of ionic transport in glass (I) mixed alkali glasses, (8) 233*f*.

Hughes, K., Isard, J. O., and Milnes, G. C. Measurement of ionic transport in glass (II) soda-lead-silica glass, (8) 233*g*.

Hughes, R. C. See Bronnes, R. L.

Hughes, W. See Callow, A. E.

Hughes Aircraft Co. Cathode ray tube with a perforated aluminum film graticule overlying the illuminescent layer, P (3) 72*b*. Ceramic-metal seal, P (5) 126*f*. Combination of thin-filmed [integrated] electrical devices, P (5) 140*i*. High brightness luminescent evaporated film, P (1) 18*b*. High frequency field-effect triode device, P (8) 244*e*. Laser apparatus having a layer of silver and a layer of silicon monoxide, P (4) 100*g*. Making *p*n junction under glass, P (11) 344*a*. Mesa multichannel field-effect triode, P (8) 245*a*. Metal-oxide-semiconductor field effect transistor, P (1) 18*i*. Method and apparatus for preparing single crystal thin films, P (2) 51*g*. Method of making oxide protected semiconductor devices, P (5) 141*j*. Method of making thin film field sustained conductivity device, P (11) 344*d*. Package for semiconductor devices and method of making, P (3) 73*j*. Planar multichannel field-effect triode, P (8) 245*j*. Production of thin films of cadmium sulfide, telluride, or selenide, P (4) 101*c*. Semiconductor device manufacture, P (4) 101*f*.

Hughes Tool Co. Loading apparatus for bulk transport systems, P (4) 105*d*.

Huguet, F. See Halm, L.

Hukki, R. T. Method and apparatus for continuous classification of solid particles dispersed in a fluid carrier, P (2) 53*c*.

Hulbert, S. F., and Smoak, R. H. Use of atomic absorption to study the kinetics of the reaction between MgO and Cr_2O_3, (4) 96*i*.

Huldt, L., and Boija, S. Optical absorption of photoelectrons in CdS, (11) 355*d*.

Hulinsky, V., and Satava, V. Solubility of gypsum at 100° to 140°C, (11) 331*j*.

Hull, C. O., Jr., and Intrator, A. M. Semiconductor contact diode, P (7) 210*e*.

Hull, E. H., and Vanderslice, T. A. Metal-bonded diamond abrasive body, P (3) 61*g*.

Hull, G. W. See Matthias, B. T.

Hulliger, F. Semiconductors and devices employing them, P (2) 52*e*, P (3) 74*b*.

Hulme, E. W. Cone 11 dry process porcelain, (11) 341*e*.

Hulme, K. F., Jones, O., Davies, P. H., and Hobden, M. V. Synthetic proustite (Ag_3AsS_3)—a new crystal for optical mixing, (4) 117*b*.

Hultsch, R. A. See Doane, J. W.

Humenik, M., Jr. See Whalen, T. J.

Humenik, M., Jr., McHugh, C. O., and Moskowitz, D. Dispersion strengthened aluminum oxide with tungsten or molybdenum, P (5) 123*i*.

Humenik, M., Jr., and Moskowitz, D. Iron bonded tungsten carbide, P (8) 240*g*.

Hummel, F. A. See Benecki, W. T.; Johnson, D. W.; Martinek, C.; Tien, T. Y.

Hummel, F. A., Franklin, A. D., and Klingsberg, C. (editors). Nuclear Science and Technology for Ceramists—Proceedings of a Symposium Held in Washington, D. C., May 1966, B (4) 120*g*.

Hummel, R. See Crummett, W.

Humphreys, F. J., and Martin, J. W. Effect of dispersed silica particles on the recovery and recrystallization of deformed copper crystals, (10) 319*g*. Recrystallization in copper-silica crystals, (10) 325*b*.

Humphreys, G. D. See Meyer, P.

Hund, F. Process for the preparation of γ-FeOOH, P (8) 251*c*.

Hund, F., and Abeck, W. Two stage process for making ferromagnetic modified chromium dioxide, P (6) 178*i*.

Hungerford, W. J., Larmer, J. W., and Levinsohn, M. Conforming polisher for aspheric surfaces of revolution, P (1) 20*f*.

Hunkeler, R. E. See Eubanks, A. G.

Hunn, J. V. Molybdated zinc oxide pigments and method of preparation, P (3) 78*f*.

Hunsperger, H., and Ballantyne, J. Measurement of photon absorption loss in the active and passive regions of a semiconductor laser, (4) 112*i*.

Hunt, J. Salvaged treasure of Florida from a 1715 Spanish plate fleet, (5) 124*c*. See Gurney, C.

Hunt, P. H. Production of dislocation-free silicon single crystals, P (11) 345*d*.

Hunter, M. J., Kern, E. L., and Hamill, D. W. Silicon carbide glass fiber [drawing] bushing and method of making, P (2) 42*c*.

Hunter, O., Jr. See Manning, W. R.

Hunter, R. M. See Fabel, D. A.

Huo, W. M., Freed, K. F., and Klemperer, W. Valence excited states of BeO, (11) 358*c*.

Hurle, D. T. J., and Mullin, J. B. Production of crystalline material, P (7) 215*f*.

Hurley, A. C. See Dawson, B.

Hurley, F. R. See Angstadt, R. L.

Hurley, F. R., Tecotzky, M., and Vanik, M. C. Uranium oxide sols, P (7) 205*h*.

Hurusho, K., and Terunuma, Y. Study on heat treatment of oxygen-doped silicon single crystal, (5) 158*c*.

Husbjerg, J. P. Preheating apparatus for cement raw meal, P (4) 92*f*.

Huschka, H., and Venet, P. Preparation and properties of nuclear fuel particles for high-temperature gas reactors, (6) 173*j*.

Husher, J. D., and Kisinko, P. M. Method of forming a semiconductor integrated circuit that includes a fast switching transistor, P (8) 245*h*.

Hussain, S. Z. See Mehra, O. K.

Hussein, A. T. See Mikhail, R. Sh.

Hussein, A. T., and Gad, G. Chemical determination of glassy phases in aluminosilicate refractories, (5) 131*j*.

Hutcheson, R. L. Process for growing high perfection crystals, P (5) 159*j*.

Hutchings, M. T. See Birgeneau, R. J.

Hutchings, M. T., and Wolf, W. P. Crystal field for Yb^{3+} in garnets, (5) 150*i*.

Hutson, A. R. See Kolb, E. D.

Huzimura, R. See Ozawa, L.

Huzimura, R., and Ato, Y. Radiation quenching of radioluminescence of ZnS phosphors, (3) 85*f*.

Hyakubu, S. See Kinase., W

Hyatt, E. P. Technical ceramics—make or buy? (2) 60*f*.

Hyde, B. G., Garver, E. E., Kuntz, U. E., and Eyring, L. Kinetic studies on reaction of praseodymium oxides in an oxygen atmosphere—$PrO_{1.83} + O_2 \rightleftharpoons PrO_2$, (11) 354*c*.

Hyde, E. K. See Bowman, H. R.

Hydrocarbon Research, Inc. Reduction of metallic oxides, P (8) 251*k*.

Hyland, G. J., and Taylor, A. W. B. Clausius-Clapeyron equation and the V_2O_4, V_2O_3 phase transitions, (4) 106*g*.

Hyland, R. E. See Rom, F. E.

Hymore, F. J. See Carson, F. J.

Hynd, W. C. Floating refractory drawbar, P (11) 336*a*. Homogenization of molten glass with a flow separator, P (4) 94*d*. See Pilkington Brothers, Ltd.

Hysinger, D. M., and Lindahl, F. A. Baghouse construction, P (6) 179*f*.

Iannicelli, J., and Millman, N. Relation of viscosity of kaolin-water suspensions to montmorillonite content of certain Georgia clays, B (8) 259*j*.

Ibach, H. See Heiland, G.

Ichikawa, Y. Dating of ancient ceramics by thermoluminescence, (1) 1*j*.

Ichikawa, Y., and Morii, T. Properties of quartz thermoluminescence dosimeters, (2) 59*d*.

Ichimura, S. See Kajikawa, Y.

Ichinohe, E., Kubo, S., and Akiyama, K. Effects of heat treatment on thermally oxidized silicon, (5) 151*j*.

Ichinose, N. Magnetic and crystallographic studies of ferrimagnetic calcium ferrites containing tri- or tetravalent metal ions, (11) 354*g*. Magnetic and crystallographic studies of ferrimagnetic garnets containing fluorine, (8) 255*a*.

Ichinose, N., and Kurihara, K. Substitution of fluorine in yttrium iron garnet, (3) 87*g*.

Ichinose, N., and Yoshioka, T. Moessbauer study of calcium diferrite, (10) 323*d*.

Ida, I., Arai, Y., Fukuda, M., Suzuki, M., Inamori, K., Sugiura, M., and Tokunaga, H. Relations between firing temperatures and structural properties in ceramics for circuit components, (5) 139*c*.

Ida, I., Arai, Y., Suzuki, M., and Fukuda, M. Lapping characteristics of ceramics with ordinary abrasives, (5) 123*i*.

Ida, I., Fukase, M., and Furumoto, S. Lapping characteristics of lead zirconate-titanate ceramics, (6) 176*c*.

Ida, I., Kajita, M., Arai, Y., and Suzuki, M. Forsterite lapping characteristics using diamond abrasives, (5) 123*g*.

Ideal Cement Co. Method and means for controlling flow in a vertical shaft kiln, P (10) 296*c*.

Idemitsu, Y. See Shinohara, K.

Iga, T. See Ishii, R.; Kato, S.; Sano, S.

Igarashi, Y. See Mizushima, Y.

Ihrig, A. C. Apparatus for manufacturing glass, P (1) 8*a*. See Bruns, J. H., Jr.

Iida, S. Photocurrent and thermal release time studies of uranium dioxide, (9) 285*j*. See Iizuka, T.; Iwahashi, K.; Matsumoto, G.; Miyatani, K.; Mizushima, K.; Ohbayashi, K.; Sugawara, F.

Iida, S., and Miwa, H. Theory of the relaxation of the uniaxial anisotropy induced by ionic migration in iron-cobalt ferrites, (10) 326*b*.

Iida, S., and Mizushima, K. Effective in-plane anisotropy and trigonal magnetostriction in α-Fe_2O_3, (4) 108*j*.

Iijima, K. See Nakayama, N.

IIT Research Institute. Method and apparatus for fractionation of fine particles, P (11) 348*a*. Method of making piezoelectric layers by flame spraying, P (9) 274*b*.

Iiyama, J. T. Influence of the anions on the exchange equilibrium of Na–K ions in alkali feldspars at 600°C under a pressure of 1000 bars, (7) 218*i*.

Iizuka, T., and Iida, S. Exchange coupling between Fe_3O_4 and α-Fe_2O_3, (4) 110*b*. Magnetic anisotropy induced by electron diffusion in $Co_{1+2z}Fe_{2-2z}O_4$ and $Fe_{1-2z}Ni_{2z}Co_2O_4$, (4) 112*g*.

Ikeda, A. See Nishikawa, T.

Ikeda, K., and Minagawa, K. Effect of heat treatment on thermal expansion of lithia ceramics with β-eucryptite composition, (8) 241*j*.

Ikeda, T. See Fushimi, S.; Tanaka, Y.

Ikeda, Y., and Hoshino, M. Electrical properties of barium-titanate ceramics having different grain size, (7) 207*d*.

Ikushima, H. Electron spin resonance of Mn^{2+} in $BaTiO_3$ single crystal, (10) 320*g*.

Ikushima, H., and Hayakawa, S. Forbidden transitions in the electron spin resonance of Mn^{2+} in $BaTiO_3$ single crystal, (3) 81*d*.

Ilani, A. Method and apparatus for the determination of K and Na, P (11) 347*j*.

Iler, R. K. See Bergna, H. E.

Iles, G. S., and Casale, M. E. A. Ruthenium oxide glaze resistors, (2) 50*g*.

Iles, P. A., and Ross, B. Solar cell and process for making, P (4) 101*b*.

Illis, A., Koehler, H. J., and Brandt, B. J. Method for the production of high purity dense nickel oxide and the product, P (1) 25*e*.

Illyn, A. V. See Henry, E. C.

Il'yashenko, V. S. See Zaytseva, L. L.

Il'yasov, I. I. System Na,Cs,K||Br, (10) 326*a*.

Il'yasov, I. I., Bergman, A. G., and Casurskii, N. I. System Cs,Cd,Pb||Cl, (4) 117*c*.

Im, S. S. See Butler, J. H.

Imadate, H. Particle counting device including fluid conducting means breaking up particle clusters, P (9) 277*g*.
Imako, Y. Magnetic aging effect of the Fe_3O_4-γ-Fe_2O_3 solid solution, (3) 83*g*.
Imaoka, M. See Utakoji, M.
Imaoka, M., Kurakata, H., Tai, S., and Nonoyama, H. Glass forming range and cooling rate, (8) 232*c*.
Imashev, M. K., Butt, Yu. M., and Kolbasov, V. M. Effect of preliminary curing on the structure development of steamed specimens from clinker minerals, (6) 164*d*.
Imashev, M. K., Butt, Yu. M., Kolbasov, V. M., and Gaidukova, V. S. Influence of water/cement ratio on physicomechanical properties of hardened cement steamed under accelerated conditions, (6) 165*d*.
Immendorfer, M. See Ebert, E.
Imoto, F. See Yamaguchi, G.
Imperial Chemical Industries of Australia and New Zealand, Ltd. Method of preparing a dry plaster by calcination and compression, P (4) 92*d*.
Imperial Chemical Industries, Ltd. Production of sodium carbonate, P (7) 215*b*.
Improved Machinery, Inc. Rotary drum filter, P (4) 102*b*.
Imre, L. Infrared spectrophotometry—theory and practical applications, (1) 21*c*.
Imris, P. Thermogravimetric study of the oxidation of particles of UO_2 prepared from U_3O_8 calcined under various conditions, (4) 118*j*.
Imris, P., Landspersky, H., and Voboril, M. Distribution of UO_2 particles prepared from variously calcined U_3O_8 investigated by sedimentation analysis, (1) 28*b*.
Inagaki, K. See Sakurai, T.
Inagaki, K., and Torii, T. Reaction between sintered mullite particle containing α-Al_2O_3 and the glass $Na_2O \cdot 2SiO_2$, (11) 334*h*.
Inamori, K. See Ida, I.
Indge, J. Answers about flat lapping, (3) 61*f*.
India, Council of Scientific & Industrial Research. Improvements in mechanical strength and resistance of glass or glass crystal composites to thermal shock and chemical attack of vapors, liquids, and solids, P (5) 130*b*. Process for the manufacture of a novel binding agent for core sand, P (5) 136*a*.
Indian Institute of Technology, Bombay. Process for making improved silica sand molds, P (2) 47*h*.
Indiana University Foundation, Indiana Memorial Union. Prophylactic dental paste compositions comprising zirconium silicate and tin dioxide, P (7) 193*i*.
Industrie-Companie Kleinewefers Konstruktions- und Handlesges. Method for setting up recuperators, P (7) 213*j*.
Infield, J. M. See Rishel, P. A.
Infrared Industries, Inc. Noble metal coated ceramic substrate for glass seals and electronic connector elements, P (10) 311*d*.
Ing, D. W. See Chu, T. L.
Ingalls, R. See Coston, C. J.
Ingamells, C. O., and Gittins, J. Stoichiometry of scapolite, (5) 158*i*.
Ingebrigtsen, K. A. See Engan, H.
Ingham, H. S., Jr. Radio frequency plasma flame spraying, P (1) 4*j*.
Ingles, J. C. See Barkley, D. J.
Ingot Aid Co., Inc. Hot top with centering lugs, P (2) 47*c*.
Ingraham, A. See Salzano, F. J.
Ingraham, R. C. See Dale, B.
Ingram, M. D. See Duffy, J. A.
Inkinen, O., and Meisalo, V. Electron distribution of ions in NiO, MnO, and CoO crystals, (3) 80*d*.
Inland Steel Co. Treatment of ferrous metal, P (8) 230*b*.
Innes, D. D. Place of emission spectrography and X-ray fluorescence in chemical analysis (I) emission spectrography, B (7) 224*f*.
Ino, S. See Suzuki, T.
Inoue, A. See Nameishi, N.
Inoue, E., and Yamaguchi, T. Study of photoconductivity of zinc oxide by electrodeposition, (5) 158*f*.
Inoue, K. Controlled electrical diffusion in an electromagnetic field, P (3) 72*d*. Low-friction materials and bodies incorporating same, P (6) 174*d*.
Inoue, M. See Mizoguchi, T.
Inoue, T. See Kitagawa, H.
Inouye, H., and Leitnaker, J. M. Equilibrium nitrogen pressures and thermodynamic properties of UN, (2) 58*g*.
Insinooritoimisto-Engineering Bureau R. T. Kukki. Method and apparatus for wet and dry screening, P (1) 20*c*.
Intermetall Ges. fuer Metallurgie und Elektronik. Transistor production, P (1) 19*c*.
Intermountain Research & Development Corp. Preparation of soda ash, P (7) 215*a*.
International Business Machines Corp. Activation of glass for electroless metal deposition of uniform thick metal films, P (6) 170*a*. Apparatus for cathode sputtering including a shielded rf electrode, P (5) 140*a*. Cathode ray device with screen having integrity against stress, P (5) 140*e*. Cathode sputtering apparatus including precision temperature control of substrate, P (5) 140*f*. Cathodic sputtering apparatus including thermionic means for increasing sputtering efficiency, P (5) 140*g*. Chemical polishing of a semiconductor substrate, P (1) 17*c*. Conductive element, composition, and method, P (9) 272*c*. Crystalline injection laser device manufacture, P (1) 17*e*. Electrical device, method, and material, P (6) 177*d*. Electrical resistor compositions, elements, and method, P (9) 272*f*. Epitaxial deposition of semiconductor materials, P (1) 17*h*. Fast responding semiconductor device using light as the transporting medium, P (5) 141*g*. Ferromagnetic compounds and method, P (1) 17*i*. Ferromagnetic materials, P (6) 177*i*. Formation of semiconductor devices, P (5) 141*i*. High sensitivity diodes, P (5) 141*a*. Hygrometer and method of fabrication, P (1) 18*d*. Light emitting semiconductor device, P (5) 141*c*. Magnetic materials and preparation, P (6) 177*f*. Method of doping epitaxially grown semiconductor material [Ge], P (4) 100*j*. Method for enhancing efficiency of recovery of semiconductor material in perturbable disproportionation systems, P (3) 73*g*. Method of epitaxially growing silicon carbide by pyrolytically decomposing SiH_4 and CH_4, P (8) 245*f*, P (9) 273*h*. Method for fabricating insulated-gate field effect transistor, P (9) 273*i*. Method for fabricating integrated circuits, P (3) 73*h*. Method of fabricating magnetic storage devices, P (10) 310*e*. Method of forming a semiconductor by diffusion by using a crystal masking technique, P (3) 73*i*. Method of forming a semiconductor by double diffusion, P (3) 73*j*. Method of forming tunneling junctions for intermetallic semiconductor devices, P (3) 73*a*. Method of making cermet resistors by etching, P (11) 344*j*. Method of making crystals of rare earth chalcogenides, P (6) 178*c*. Method of polishing gallium arsenide single crystals by reaction with a gaseous atmosphere incompletely saturated with gallium, P (10) 310*f*. Method of preparing transparent ferromagnetic single crystals, P (7) 209*b*. Method for producing rare earth chalcogenides, P (3) 78*d*. Method for providing electrical connections to semiconductor devices, P (8) 245*e*. Method for providing electrical contacts to a wafer of GaAs, P (9) 274*i*. Method of shaping pn junction profiles, P (3) 73*f*. Method of vapor growing a homogeneous monocrystal, P (10) 310*j*. Methods of making a narrow emitter transistor by masking and diffusion, P (9) 274*a*. Multiple color, multiple beam interferometer, P (4) 103*h*. Optical fiber laser device, P (3) 73*i*. Opto-electronic semiconductor devices, P (5) 142*j*. Preparation of high-purity materials, P (3) 74*a*. Preparing large single crystalline bodies of rare earth chalcogenides, P (8) 246*a*. Process of depositing thin films by cathode sputtering using a controlled grid, P (4) 100*j*. Process of making planar semiconductor devices isolated by encapsulating oxide filled channels, P (9) 274*f*. Process for modifying Curie temperature of ferromagnetic lanthanide chalcogen solid solution compounds, P (6) 178*f*. Semiconductor devices and passivation thereof, P (1) 19*c*. Semiconductor-ferroelectric dielectrics, P (5) 142*i*. Semiconductor-metal-semiconductor structure, P (9) 275*b*. Solder method for providing standoff of device from substrate, P (10) 311*e*. Transistor structure with an emitter region epitaxially grown over the base region, P (11) 345*c*. Two-color multiple beam interferometer for measuring small separations, P (4) 103*i*. Vapor polishing of a semiconductor wafer, P (5) 143*c*. Variable weighted threshold element system, P (11) 345*d*.
International Commission on Glass, Subcommittee A VI. Bibliography of Physical Properties of Glass—Strength, Hardness, Elasticity, B (8) 258*i*.
International Minerals & Chemical Corp. Attachment for a brick press, P (11) 337*f*. Device for discharging material from a screw conveyor, P (1) 20*f*. Electrostatic separation apparatus, P (8) 251*b*. Method of making a refractory brick, P (11) 340*j*.
International Nickel Co., Inc. Metal-to-glass seal, P (8) 245*b*. Method for the production of high purity dense nickel oxide, P (1) 25*c*.
International Pipe & Ceramics Corp. Composite laminated resilient means for a press, P (10) 312*b*.
International Processes, Ltd. Heat exchange system for calciner, P (11) 332*a*.
International Rectifier Corp. Large area wafer semiconductor device, P (8) 244*h*. Process for diffusion of contoured junction, P (11) 345*c*.
International Research & Development Co., Ltd. Coated boron containing material dispersed in a metal matrix, P (3) 68*f*.
International Resistance Co. Apparatus for vapor coating tumbling substrates, P (11) 343*f*. Method of making an electrical resistor, P (4) 100*c*. See IRC, Inc.
International Standard Electric Corp. Ceramic reed relay, P (9) 272*b*. Ceramic reed relay having flux carrying means associated with the armature, P (9) 272*c*. Formation of aluminum, gallium, arsenic, and phosphorus binary coatings, P (10) 309*f*. Method of forming a gallium arsenide transistor by diffusion, P (2) 51*h*. Method of making semiconductor devices, P (7) 209*h*. Nickel-gold contacts for semiconductors, P (4) 100*i*. Production of metallic compacts, P (7) 205*a*. Strain relieving transition member for contacting semiconductor devices, P (9) 275*a*.
International Telephone & Telegraph Corp. High frequency power transistor having electrodes forming transmission lines, P (9) 273*d*. Method of making a sandwich resistor, P (10) 310*b*. Semiconductor device, P (3) 74*f*. Semiconductor device having regions of different conductivity types wherein current is carried by the same type of carrier in all the regions, P (11) 345*c*.
Intrator, A. M. See Hull, C. O., Jr.
Ion Physics Corp. Method of forming a pn junction by an ionic beam, P (9) 273*c*. Solid state translating device comprising irradiation implanted conductivity ions, P (8) 246*b*.
Ionics, Inc. Fluidized bed process for the preparation of colloidal SiC, P (5) 135*a*.
Ionov, S. P., and Porai-Koshits, M. A. Magnetic permeability of sulfur dioxide, (4) 112*h*.
Ippolitova, E. A. See Rachev, V. V.; Vidavskii, L. M.
Iqbal, Q., and Ariff, M. R. Replacement of quartz by barite in the manufacture of white earthenware, (9) 271*e*.
IRC, Inc. Array of transistors having a layer of soft metal film for dividing, P (4) 99*d*. Four layer planar semiconductor switch and method of making, P (9) 273*b*. Glass bonded resistor compositions containing refractory metal nitrides and refractory metal, P (10) 309*g*. Method of making an electrical resistor, P (10) 310*f*. Method of making single crystal films and the product, P (10) 310*c*.
Irgolic, K., Zingaro, R. A., and Kudchadker, M. Synthesis of tetraphosphorus triselenide—preliminary infrared, NMR, and Raman studies, (4) 117*e*.
Irita, Y. See Mukai, H.
Iriyama, K. See Takamori, T.
Iriam, P. S. See Murphy, N. A.
Irland, F. W. Apparatus for producing sheet glass, P (11) 335*f*.
Irvin, C. L. See Neal, J. E.
Irving, J. P., and Butt, J. B. Volume-area distributions for micropores, (1) 33*j*.
Isacks, A. J., and Lugg, R. R. Process for the preparation of sintered metallic oxide catalyst pellets, P (1) 25*i*.
Isard, J. O. See Hughes, K.; Prasad, R. S.
Iseki, T. See Tagai, H.
Isha, J. See Kawahara, H.
Ishibashi, M. See Nagata, T.
Ishibashi, Y. See Furukawa, Y.; Kinase, W.; Nakamura, T.
Ishihara, T. See Takemoto, T.
Ishihara, T., Honda, T., and Ohwada, K. Process for preparing [uranium-resin] nuclear fuel elements of dispersed-in-graphite type, P (1) 14*c*.
Ishihata, A. See Nishijima, T.
Ishii, K. See Kato, S.; Sano, S.
Ishii, E., Kato, S., Sano, S., and Iga, T. Properties of calcined products of basic magnesium carbonate and magnesite containing zinc oxide, (11) 338*g*.
Ishii, T., and Rolfe, J. V centers in potassium bromide crystals, (8) 258*b*.
Ishikawa, R., and Mitsuma, T. Luminescent properties of CdTe diode, (11) 354*f*.
Ishikawa, Y. See Umebayashi, H.
Ishizaki, K. See Suzuki, H.
Ishizuka, H. High temperature and high pressure apparatus, P (2) 55*d*, P (5) 144*b*.
Ishler, W. E., and Smialek, L. J. Mercury metal halide discharge lamp having iodine present in stoichiometric proportions with respect to the reactive metals, P (8) 235*f*.
Ismailov, M. Z. See Guseinov, G. D.
Isotani, M., Kondo, Y., and Hobo, K. Permanent mold coating (V) some properties of the metal mold coating for a cast iron, (9) 268*c*.
Isotronics, Inc. Hermetic metal-to-glass seal and application thereof, P (6) 170*f*.
Israel, Government of. Preparation of mixed metal oxides by thermal decomposition of metal salts, P (7) 214*j*.
Itakura, M., and Toyoda, H. Hall effect and contact properties with metals in conductive CdS single crystals, (5) 153*h*.
Iten, H. C., and Gleskieng, D. H. Rotary kiln thermocouple collector ring and brush assembly, P (11) 348*h*.
Ito, A. See Kawamura, S.
Ito, J. New yttrium magnesium silicate garnet, $Y_3Mg_2Si_3O_{12}$, and its rare earth and nickel analogs, (4) 113*a*. See Wilkins, R. W. T.
Ito, K. See Maeda, S.
Itoga, R. S. See Domingo, G.
Itzel, J. F., Jr. See Poole, C. P., Jr.
Ivaniov, V. See Petri, L.
Ivaniov, W. See Veiser, I.
Ivanov, A. I. See Morozov, E. I.
Ivanov, A. P. See Nadgornyi, E. M.
Ivanova, L. M., Kazaryan, G. A., and Pletyushkin, A. A. Production of silicon carbide by thermal decomposition of methylchlorosilane vapor, (1) 12*a*.
Ivanovic, N. P. Micro creep-testing, P (10) 316*b*.
Ivantsova, S. M. See Sychev, M. M.
Ivashchenko, V. V., Tartakovskii, I. P., and Golubev, T. M. Vibration compaction of two-component systems of spherical powders, (1) 23*e*. Vibration packing of spherical powders, (1) 23*c*.
Ivensen, V. A., Gol'dberg, Z. A., Eiduk, O. I., and Fal'kovskii, V. A. Breaking strength of a hard alloy under impact loads, (5) 131*g*.
Ivey, H. F. Bibliography on electroluminescence and related topics (IV, V), (5) 137*h*.

Ivey, K. H. Fluormicas and fluoramphiboles and methods for making, P (4) 105*b*. See Miller, J. L., Jr.
Iwahashi, K., and Iida, S. Induced parasitic ferromagnetism in $(La_{0.9}Bi_{0.1})CrO_3$, (3) 81*i*.
Iwai, F. See Yamanouchi, T.
Iwamoto, Y. Review of continuous steel casting process and the refractories used, (9) 269*h*.
Iwasa, H. See Teramoto, I.
Iwasaki, H. Dielectric and X-ray studies on the solid solution systems based on $NaNbO_3$, (5) 150*j*. Paramagnetic species in γ-irradiated single crystal ferroelectric lithium trihydrogen selenite, $LiH_3(SeO_3)_2$, (3) 84*f*. See Kawai, S.
Iyengar, L. See Rao, K. V. K.
Iyengar, R. D., Codell, M., Karra, J. S., and Turkevich, J. Electron spin resonance studies of the surface chemistry of rutile, (2) 58*e*.
Izett, G. A. See Wilcox, R. E.
Izosenkova, A. V. See Galdina, N. M.
Izumitani, T. See Yanagida, O.

Jackman, H. W. See Ehrlinger, H. P., III.
Jackson, C. B. See Burke, O. W., Jr.
Jackson, J. See Christie, G. E.
Jackson, J., Jr. See Kleespies, E. K.
Jackson, J. C. Isostatic pressing of powdered materials, B (3) 89*h*.
Jackson, J. G. Coated glass thread, P (7) 198*e*.
Jackson, M. L. Interlayering of expansible layer silicates in soils by chemical weathering, B (5) 160*j*. See Alexiades, C. A.; Fanning, D. S.; Hendricks, D. M.; Huang, P. M.; Raman, K. V.; Volk, V. V.
Jackson, M. R. See Kaye, B. H.
Jackson, P. W. See Baker, A. A.
Jackson, P. W., and Cratchley, D. Effect of fiber orientation on the tensile strength of fiber-reinforced metals, (1) 4*b*.
Jacob, H. Method and apparatus for measuring and adjusting the moisture content and therewith the formability of foundry sand, etc., P (6) 174*e*.
Jacobs, A. See Plumat, E.
Jacobs, D. A., and Duke, J. B. Grinding method, P (11) 349*h*.
Jacobs, D. G. Use of negative sorption in studies of ion fixation by hydrobiotite, B (7) 225*a*.
Jacobs, J. E., Collis, W. J., and Berger, H. Evaluation of an ultrasonic inspection system employing television techniques, (7) 212*f*.
Jacobs, M. B. See Kerr, P. F.
Jacobs, P. W. M. See Beaumont, J. H.
Jacobsen, A., and Rimkus, W. Fiber optics—properties and uses, (10) 297*e*.
Jaeger, R. E. Influence of OH^- concentration and irradiation on low-temperature dielectric loss in silica glass, (2) 58*b*.
Jaffe, H., and Berlincourt, D. A. Transducing method and apparatus, P (3) 74*d*.
Jaffe, P. M. Blue-white europium activated aluminosilicate phosphor, P (4) 99*e*. Green-yellow emitting europium aluminosilicate phosphor, P (4) 100*b*.
Jagaciak, G. J., Poulton, J. W., and Cronan, W. L. Weld arresting composition, P (8) 230*a*.
Jagas, P. J., Ghosh, R. K., and Chatterjee, M. R. Design of cement concrete mixes with different Indian cements based on the compressive strength of concrete, (10) 294*h*.
Jagel, K. I., Jr. See Cramer, R. H.
Jager, J. See Dijken, R. H.
Jahanbagloo, C., and Zoltai, T. Quantitative analysis with the aid of calculated X-ray powder patterns (I), (11) 347*b*.
Jain, D. S., and Gaur, J. N. Polarographic study of the complexes formed by Zn, Mn, Ni, and Co with 1:2 diaminocyclohexanetetraacetic acid, (5) 145*i*.
Jain, K. C., and Bhan, S. System Sn–MnSn$_2$–Ni$_3$Sn$_4$, (7) 222*b*.
Jain, L. C., and Jain, V. K. Brick and tile research in India, (9) 266*d*.
Jain, V. K. See Jain, L. C.
Jakes, D. See Landspersky, H.
Jakes, D., Becvar, J., and Skvor, F. Sintering of ceramics from uranium dioxide (IV) application of some activators of sintering, (3) 68*d*.
Jakes, D., Sedlakova, L., and Wolf, J. Sintering of ceramics from uranium dioxide (I) preparation of uranium dioxide—sintering at low temperature, (3) 68*c*.
Jakesova, L. See Podest, M.
Jakubovics, J. P. See Joy, D. C.
Jalbing, J. I., and Myers, E. H. Spark plug center electrode with a split truncated head, P (1) 16*a*.
Jambor, J. L. New lead sulfantimonides from Madoc, Ontario (I), (4) 113*j*. See Harris, D. C.; Mulligan, R.
James, B. D. Multichip integrated circuit assembly with interconnection structure, P (9) 274*a*.
James, D. W., and Harward, M. E. Mechanism of NH_3 adsorption by montmorillonite and kaolinite, B (5) 161*b*.
James, S. D. Alkali metal doping of semiconductors, (1) 16*b*.
James, W. A. See Roberts, R. F., Jr.
James, W. J. See Smith, R. T.; Straumanis, M. E.
Jamey, M. A., Maurel, P. J. P., and Duhart, P. A. Process for the preparation of crystallized neutral aluminum sulfates having low water content, P (11) 349*h*.
Jamieson, J. C. See McQueen, R. G.
Jammernegg, H. Magnesite brick construction in glass melting furnaces from the port to the regenerator—basic checkerwork in a lead glass tank, (8) 233*d*.
Janah, A. Making opaque glazes with zircon, (5) 136*g*.
Janetos, N. S. See Marzocchi, A.
Jankowski, A. S. See Chagnon, P. L.
Janninck, R. F., and Whitmore, D. H. Thermoelectric power in nonstoichiometric α-Nb_2O_5, (5) 140*c*.
Janowski, K. R., and Rossi, R. C. Elastic behavior of MgO matrix composites, (1) 28*f*. Mechanical degradation of MgO by water vapor, (9) 284*b*.
Janus, T. P. See Varon, J.
Januszkiewicz, K. Measurement of the temperature distribution along the debiteuse during the manufacture of flat glass by the Fourcault method, (3) 64*f*.
Japan Atomic Energy Research Institute. Process for preparing [uranium-resin] nuclear fuel elements of dispersed-in-graphite type, P (1) 14*c*.
Jared, R. C. See Bowman, H. R.
Jarman, H. E. See Brau, M. J.
Jaron, M. G. Method for determining post-depositional alteration in underclays and associated lithologies, (4) 103*c*.
Jarvi, R. E. See Charvat, V. K.
Jasperse, J. R., Kahan, A., Plendl, J. N., and Mitra, S. S. Temperature dependence of infrared dispersion in ionic crystals LiF and MgO, (11) 357*b*.
Jastram, E. P., and Landis, H. M. Electrical temperature sensors with connected heat conductive means, P (11) 347*f*.
Jaswal, S. S. Debye-Waller factor and second-order Doppler shift of ^{129}I in alkali iodides, (9) 280*c*.
Javan, A. Optical properties of materials, B (11) 358*i*.
Javaux, G. Bending chamber for the manufacture of sheet glass by drawing, P (3) 65*b*. Means for the thermal homogenization of glass for drawing it in sheet form, P (3) 65*a*.
Jayaraman, A. See Marezio, M.
Jayne, B. A., and Suddarth, S. K. Matrix-tensor mathematics in orthotropic elasticity, B (4) 121*b*.
Jayne, J. P. See Lunsford, J. H.
Jaywoth Roof Tile Co., Inc. Roofing tile, P (2) 43*c*.
Jeanneau, J. Y. Purification of raw materials, (9) 275*g*.
Jebsen-Marwedel, H. Interpretation of the additional corrosion at the metal line of glass melts and by upward drilling of gas bubbles as a transport process caused by permanent perimetting, (8) 232*j*.
Jech, C., and Kelly, R. Low-temperature diffusion in inert-gas bombarded Al_2O_3, (8) 254*g*.
Jech, R. E. See Readey, D. W.
Jefferies, D. K. Small 180° fast scanning mass spectrometer, (4) 103*j*.
Jeffery, B. M. Microanalysis of inclusions in irradiated UO_2, (2) 45*a*.
Jeffery, J. W. See Chatterji, S.
Jeffery, P. G., and Kerr, G. O. Determination of vanadium in silicate rocks and minerals with *N*-benzoyl-o-tolylhydroxylamine, (5) 145*d*.
Jehenson, P. See Gualandi, D.
Jelacic, C. Compositions based on vitrified cordierite for porcelain, (3) 69*i*.
Jelacic, C., and Kacian, M. Synthesis of cordierite, (10) 304*e*.
Jelesiewicz, A. C. Attachment for a brick press, P (11) 337*f*.
Jelli, A. N. See White, J. L.
Jena, A. K., Bever, M. B., and Banus, M. D. Thermodynamic properties of several solid phases of the compound InSb, (6) 190*g*.
Jena, P. K. See Mehra, O. K.
Jenaer Glaswerk Schott & Gen. Method of producing articles containing predominantly cordierite, anorthite, spinel, and/or forsterite, P (5) 135*c*. Substances for producing crystalline heat-resistant coatings and fused layers, P (8) 236*d*. See Carl-Zeiss-Stiftung.
Jenkins, A. E. See Baker, L. A.
Jenkins, R. E. See Bush, D. C.
Jenkins, R. J., and Butler, C. P. Stability and reproducibility of a carbon arc image furnace, (5) 147*g*.
Jenkins, W. D. See Yakowitz, H.
Jenne, E. A. See Langston, R. B.
Jennings, B. R., and Jerrard, H. G. Light-scattering study of bentonite solutions when subjected to electric fields, (3) 83*d*.
Jennings, P. P. See Collins, A. C.
Jennings, R. E. Ceramic coatings, P (2) 38*a*.
Jennings, V. J., Sommer, A., and Chang, H. C. Epitaxial growth of silicon carbide, (7) 207*j*.
Jenny, D. A. Making *pn* junction under glass, P (11) 344*a*.
Jensen, A. Semiconductor switching element with heat-responsive central current path, P (8) 246*i*. Unitary multiple solid state switch assembly, P (3) 74*f*. Voltage controlled switch, P (11) 345*e*.
Jensen, F. E. Rotary kiln assemblies, P (6) 182*b*. Rotary kiln installations, P (4) 104*e*.
Jensen, H. A. See Barrett, J. R.; Gerhard, G. C.
Jensen, J. W. See Doerr, R. M.; George, L. C.
Jensen, S. J. See Christensen, A. N.
Jensen, W. P. See Niederman, H. H.
Jensen, W. R. See Batchelor, C. S.
Jepsen, T. L. B. Controlled reagent introduction in a magnesite ore concentration process, P (8) 250*i*.
Jepson, S. See Reed, L.
Jernkontoret, Swedish Ironmasters Assn. Dolomite sinter and its production, P (1) 12*b*.
Jerphanion, A. de. Use of natural gas in the glass industry, (7) 197*h*.
Jerrard, H. G. See Jennings, B. R.
Jerrett, S. H. Asian export threats, (6) 190*j*.
Jeschar, R., Poetke, W., and Schroeder, U. Investigation of kilns with the aid of models, (1) 24*c*.
Jessen, F. W. See Mungan, N.
Jester, H. C., and McNeil, R. S. Multistage milling, P (8) 247*f*.
Jewell, R. C. Manufacture of flat glass on improved molten metal bath, P (1) 9*h*. Manufacture of flat glass in ribbon form, P (7) 199*a*.
Jha, J. C., Chinoy, A. R., and Thomas, K. T. Studies on the cesium sorption properties of some Indian vermiculites, (7) 222*b*.
Jitea, B. See Petri, L.
Jitea, B., Szabo, A., and Petri, L. Manufacture of refractory sheaths for immersion thermocouples, (9) 267*g*.
Jochmann, F. From an old glassmaker's recipe book, (7) 194*a*.
Joergensen, P. Infrared absorption of O–H bonds in some micas and other phyllosilicates, B (7) 224*i*.
Jogalekar, P. P., and Sinha, A. P. B. Electrical properties of zinc-lithium manganites, (5) 138*d*.
Johansen, H. A., and Cleary, J. G. Ductile-brittle transition in tantalum carbide, (11) 351*h*.
Johansen, O., and Steinnes, E. Precision analyses of manganese in rocks by neutron activation analysis, (5) 145*j*.
Johanson, W. Experiment on the metasomatic formation of magnesite, (9) 282*h*.
John G. Stein & Co., Ltd. Basic refractory bricks and methods and machines for their production, P (1) 12*h*. Refractory brick, P (7) 205*c*.
John, H. F. See Chu, T. L.; Faust, J. W., Jr.
John Mathews & Co., Ltd. Glass mirrors having resistance to tarnishing, P (7) 198*g*.
John, W. Apparatus for shaping pottery in revolving ceramic-mass-containing molds, P (9) 271*e*.
Johns, W. D. See Bundy, W. M.; Tettenhorst, R.
Johns-Manville Corp. Apparatus for forming asbestos cement pipes, P (9) 275*f*. Apparatus for the manufacture of fibrous material, P (1) 8*j*. Consumable product for ingot hot tops, etc., P (2) 46*i*. High strength-high temperature yarn, P (5) 130*b*. High temperature thermal insulation, P (1) 12*i*. Insulating riser sleeve composition, P (11) 340*e*. Manufacture of calcium silicate insulating products, P (2) 47*e*. Method and apparatus for determining the dewpoint of a gaseous mixture, P (9) 277*e*. Method and apparatus for forming an end profile on asbestos-cement pipe, P (8) 240*i*. Method and apparatus for introducing a flocculating agent to an asbestos-cement slurry to control the thickness of the sheet used in winding to form a pipe, P (5) 135*h*. Method and apparatus for manufacturing asbestos-cement [pipe], P (5) 135*i*. Method and apparatus for processing heat softenable material, P (11) 336*e*. Method and apparatus for producing fibrous material, P (6) 171*c*. Method and apparatus for spreading chopped fibers, P (4) 94*j*. Method and apparatus for use in the manufacture of asbestos-cement articles, P (5) 135*i*. Method of producing asbestos-cement sheets containing cellulosic fiber, P (1) 13*g*. Phosphoric acid bonded asbestos fiber sheets and method of manufacture, P (8) 241*e*. Pipe apparatus, P (8) 241*f*. Pipe joint, P (5) 131*b*. Preparation of a support for use in gas chromatography, P (10) 305*a*. Refractory fiber composition, P (2) 42*a*.
Johnson, A. A., and Kenedi, P. G. Analytical method for determining active fluoride in acid solution, P (10) 316*g*.
Johnson, B. J., and George, C. R. Cementing compositions for maximum thermal insulation, P (4) 92*b*.
Johnson, C. E., Wood, S. E., and Crouthamel, C. E. Studies of lithium hydride systems (II) solid-liquid equilibrium in the sodium chloride-lithium hydride system, (7) 222*c*; (III) solid-liquid equilibrium in the lithium bromide-lithium hydride and lithium iodide-lithium hydride systems, (7) 222*c*.
Johnson, D. See Hanak, J. J.
Johnson, D. E. See Mills, R. G.
Johnson, D. H. See Grigsby, D. L.
Johnson, D. R., and Tabeling, R. W. Thermal gravimetric analyzer, P (6) 181*g*.
Johnson, D. W., and Hummel, F. A. Phase equilibria and liquid immiscibility in the system PbO–B_2O_3–SiO_2, (5) 156*b*.
Johnson, G. E. Evaluating engineering projects, (3) 89*b*.
Johnson, G. F. See Whaley, H. P.
Johnson, G. H. (compiler and editor). Ceramic-Metal Systems and Enamel Bibliography and Abstracts—1967, B (7) 224*i*.
Johnson, H. Insulated-gate field effect triode with an insulator having the same atomic spacing as the channel, P (3) 73*a*.
Johnson, H. E. See D'Eustachio, D.
Johnson, H. F. See Hamilton, V. E.

Johnson, H. & R., Ltd. Method of glazing and decorating ceramic tile, etc., P (5) 137*c*.
Johnson, H. S., Jr., and Heron, S. D. Brick raw materials resources in South Carolina, (3) 77*d*.
Johnson, J. N. Elastic precursor decay in quartzite for cylindrical and spherical flow, (9) 281*h*.
Johnson, J. R. Container decorating means with means for holding and indexing work, P (4) 94*f*. See Sowman, H. G.
Johnson, K. A. See Land, C. C.
Johnson, K. O., and Meyer, W. E. Radial flow regenerator matrix formed from ceramic blocks and method of making, P (5) 136*e*.
Johnson, L. F. See Dietz, R. E.
Johnson, L. R. Calculation of batch formulas using linear programming, (1) 19*g*.
Johnson, M. F. L. See Sanford, R. A.
Johnson, M. F. L., Willis, J. E., and Sanford, R. A. Method [flotation] of separating catalyst particles into fractions of differing surface area, P (4) 105*h*.
Johnson, M. R., Holonyak, N., Jr., Sirkis, M. D., and Boose, E. D. Volume excitation of an ultrathin continuous-wave CdSe laser at 6900 A output, (1) 17*g*.
Johnson, P. D. Arc discharge lamp having polycrystalline ceramic arc tube, P (4) 99*c*.
Johnson, P. K. See Hausner, H. H.
Johnson, P. M., Lincoln, R. L., and McClure, E. R. Development of a high-temperature interferometric dilatometer using a laser light source, (10) 314*f*.
Johnson, P. W., and Peters, F. A. Methods for producing alumina from anorthosite—evaluation of a lime-soda sinter process, (6) 182*i*.
Johnson, Q. See Smith, G. S.
Johnson, R. A. Point-defect calculations for an fcc lattice, (10) 324*f*.
Johnson, R. C. See Alley, J. K.; Clifton, R. A., Jr.
Johnson, R. E. See Brau, M. J.; Carniglia, S. C.
Johnson, R. E., and Mehal, E. W. Process for purifying gallium arsenide, P (4) 101*a*.
Johnson, R. E., Mehal, E. W., Hach, R. J., and Haisty, R. W. Intrinsic-appearing gallium arsenide compound semiconductor material, P (6) 177*e*.
Johnson, R. E., and Muan, A. Phase diagrams for the systems Si–O and Cr–O, (9) 285*g*.
Johnson, R. E., and Parker, S. G. Process of growing cubic zinc sulfide crystals in a molten salt solvent, P (6) 183*c*.
Johnson, R. W. Method of producing tile panels, P (4) 98*g*.
Johnson, S. S., and Tyrrell, M. E. Analyses of clay and related materials—eastern counties (of Virginia), (7) 214*c*.
Johnson, T. See Davies, T. A.
Johnson, V. See Morris, B.
Johnson, Matthey & Co., Ltd. Ceramic transfers, P (2) 49*b*.
Johnston, K. H. See Delord, J. F.
Johnston, T. S. See Hecht, H. G.
Jokelleova, D. Spectrophotometric determination of aluminum and iron in silicates with ferron, (10) 315*f*.
Jonas, E. C. Petrology of the Dry Branch, Georgia, kaolin deposits, B (6) 191*f*.
Jonas, E. C., and Oliver, R. M. Size and shape of montmorillonite crystallites, B (9) 289*c*.
Jonas, E. C., and Roberson, H. E. Structural charge density as indicated by montmorillonite hydration, B (7) 224*h*.
Joncich, M. J. See Spangler, C. W.
Jonckheere, J. Industrial colorimetric measurements, (10) 314*d*.
Jones, A. D. See Grover, J. R.
Jones, C. E. See Conrad, R. W.; Hilton, A. R.
Jones, C. E., and Hilton, A. R. Depth of mechanical damage in gallium arsenide, (3) 79*i*.
Jones, C. M., II. Fluid bed kiln, P (10) 317*a*.
Jones, D. E. See Zimmerman, D. W.
Jones, D. W. Thermal behavior of silica and its application to dental investments (I–III), (11) 341*e*.
Jones, E. D. See Lines, M. E.
Jones, J. B., Jr. Radial grate for shaft kilns, P (6) 182*a*.
Jones, J. C., and Bundy, A. J. Packaged plate glass, P (2) 42*a*.
Jones, J. W. See Bennett, J. D.
Jones, L. H., and Smith, J. M. Vibrational spectra, force constants, and bonding in mixed cyanide-halide complexes of platinum, (4) 119*b*.
Jones, L. W., and Lihou, D. A. Process for the manufacture of a fluosilicate of a metal, P (5) 148*j*.
Jones, M. D., and Mee, C. H. B. Photoluminescence, photoelectric emission, and enhanced thermionic emission from strontium oxide, (11) 355*j*.
Jones, M. H., and Oakes, B. D. Study of the inhibiting effect of ferrous chloride on the corrosion rate of steel in HCl, (11) 332*f*.
Jones, M. W. See Bowman, H. A.
Jones, M. W., and Rigby, L. J. Large rotary vacuum seals for manual operation, (4) 102*j*.
Jones, N. F. See King, H. G. C.
Jones, O. See Hulme, K. F.
Jones, O. E. Piezoelectric and mechanical behavior of *X*-cut quartz shock loaded at 79°K, (3) 85*h*.
Jones, P. A. See Groves, J. D.; Harris, B.
Jones, R. E., Jr. Method for fabricating integrated circuits, P (3) 73*h*.
Jones, R. E., Standley, C. L., and Maissel, L. I. Re-emission coefficients of Si and SiO_2 films deposited through rf and dc sputtering, (5) 139*b*.
Jones, R. V., and Smith, A. B. Microwave modulator using anisotropic effects of ferromagnetic resonance in single crystals, P (11) 344*g*.
Jones, R. W. Furnace wall structure, P (5) 135*c*.
See Douillard, P. A.
Jones, T. S., and Davis, H. M. Reduction of zinc oxide by carbon monoxide in the presence of strontium oxide, (4) 115*e*.
Jones, W. C., and Porter, M. C. Method for measuring contact angles on fibers, (9) 276*f*.
Jones, W. M., and Evans, R. E. Adsorption of carbon dioxide at high pressures (1 to 100 atm) by alumina, determined from measurement of dielectric constant, (3) 78*i*.
Jong, J. de. Function of quartz in whiteware and porcelain bodies, (4) 98*f*.
Jonge, J. de. See Kwestroo, W.; Mulder, B. J.
Jonge, L. S. de. Flue gases of natural gas and their use in dryers, (2) 55*j*.
Jonke, A. A. See Holmes, J. T.
Jonker, G. H. Optimum ceramic structures for various uses of barium titanate, (1) 16*j*.
Jonscher, A. K. Electronic properties of amorphous dielectric films, (11) 342*a*.
Joosten, J. E. See Driel, G. A. H. van.
Joppen, R. See Clasen, H.
Jorba, M. P. y. See Perez y Jorba, M.
Jordan, K. R. Modified carbide fuels, P (1) 13*b*.
Jordan, W. See Weingaertner, E.
Jordan, W. W. What's up front, (2) 53*f*.
Jorgensen, P. Continuous drawing of finished products from a molten or viscous bath (I); (II) equations of the problem; (III) application of equations to the form of the meniscus and production problems, (7) 195*j*; (IV) control of the geometry and stability of the meniscus; (V) secondary thermal effects; (VI) variations in techniques, (11) 333*h*.
Jorgensen, P. J., and Anderson, R. C. Grain-boundary segregation and final-stage sintering of Y_2O_3, (1) 29*e*.
Joseph Lucas (Industries), Ltd. Forming a semiconductor device by diffusing, P (11) 343*f*.
Joshi, M. L. Stacking faults in steam-oxidized silicon, (10) 325*c*.
Joshi, M. S., and Vagh, A. S. Dislocations in cultured quartz, (7) 216*i*. Gradient of growth pyramids and flow of mother liquor on rhombohedral faces of natural quartz, (8) 254*b*.
Jouenne, C. A. Granularity, (3) 67*g*. Mechanism of cast formation, (3) 70*g*.
Jouquet, G. See Barrachin, A. M.
Joy, A. S., Manser, R. M., Lloyd, K., and Watson, D. Flotation of silicates (II) adsorption of ions on feldspar in relation to its flotation response, (5) 143*j*.
Joy, A. S., Watson, D., Azim, Y. Y. A., and Manser, R. M. Flotation of silicates (I) proposals for classification according to their flotation response, (5) 143*f*.
Joy, D. C., and Jakubovics, J. P. Direct observation of magnetic domains by scanning electron microscopy, (8) 248*f*.
Joyce, J. E. See Lozano, R.
Joyce, R. J., Sterling, H. F., and Alexander, J. H. Silicon oxide and nitride films deposited by an rf glow discharge, (10) 308*h*.
Joyner, B. L. See Anderson, J. W.
Judd, D. M. Aluminum porcelain enamels meet new challenges, (1) 3*j*. Enameled aluminum offers color and versatility, (10) 296*e*.
Judinskaja, I. V. See Figner, A. I.
Juel, L. H. See Ellis, R. T.
Jugle, D. B. See DeVries, R. C.
Juhasz, A. Mechanized heavy duty filter presses, P (10) 312*e*.
Juhasz, Z. Modified Blaine method for determining the specific surface of ground minerals, (2) 54*d*.
Juillerat, H. Method for making a diamond-carrying tool, P (1) 1*h*.
Juillet, F. See Vergnon, P.
Julietti, R. J. Progress in the development of analytical methods—reports from the working groups (II) aluminas by spectrographic methods, B (7) 224*g*.
Jung, H. Every other house a ceramic museum—citizens of Xanten (Westphalia, Germany) preserve in their houses the inheritance of a 2000-year-old history, (5) 124*c*.
Junge, A. E., and Chabal, J. Apparatus for single surface etching of glass plates, P (6) 170*e*. Etching process for producing a nonreflective surface on float glass, P (6) 170*i*. Etching solution and process for producing a nonreflective surface on transparent glass, P (6) 170*i*.
Junge, H. See Saalfeld, H.
Junkers & Co. G.m.b.H. Thermocouples and methods of manufacturing them, P (7) 213*d*.
Junkison, A. R. See Counsell, J. F.
Jura, G. See McWhan, D. B.
Jurenas, V. See Pranckevicius, G.
Juza, R., Seidel, H., and Tiedemann, J. Color centers in alkali borate glasses containing cobalt, nickel, or copper, (9) 263*g*.

Kabushiki Kaisha Hitachi Seisakusho. Lithium magnesium ferrite memory core material, P (5) 141*c*. Method of forming a semiconductor device by etching and epitaxial deposition, P (1) 18*a*. Method of making semiconductor devices by double masking, P (1) 18*d*. Recorder for analyzing particle size distributions of powders, P (7) 213*b*.
Kachel, I. Thermionic cathode forming process using electrostatic charge attraction, P (1) 19*b*.
Kachi, S. See Kawano, S.; Shinjo, T.
Kacian, M. See Jelacic, C.
Kacker, K. P. See Ramachandran, V. S.
Kafalas, J. A. See Chapin, D. S.; Goodenough, J. B.
Kaga, F. Filter press, P (4) 102*b*.
Kagan, G. M. See Slysh, R. S.
Kahan, A. See Jasperse, J. R.
Kahan, A., and McCarthy, D. E. Angle-of-incidence dependence of calcium fluoride reflectivity, (8) 252*b*.
Kahl, P., Hinckeldey, A., and Mayerhofer, E. Device for the transmission of short electromagnetic waves, especially for highest frequency tubes, P (8) 244*h*.
Kahng, D., and Ryder, R. M. Small area semiconductor device, P (4) 101*b*.
Kaibicheva, M. N., Yartsev, M. A., and Flerova, M. I. Basic highly refractory mortar with additions of open-hearth agglomerate, (9) 266*h*.
Kaiman, S. Accessories for locating microscopical fields in polished sections, (1) 20*g*.
Kainarskii, I. S. Technology of making dense refractories, (9) 269*d*. See Degtyareva, E. V.; Totsenko, S. B.
Kainarskii, I. S., Gul'ko, N. V., et al. Reaction of sintered spinel and corundum refractories with some compounds, (9) 268*k*.
Kainarskii, I. S., Totsenko, S. B., and Degtyareva, E. V. Influence of heat treatment conditions on the mechanical and dielectric properties of spinel-corundum highly refractory ceramics, (8) 238*b*.
Kaiser Aluminum & Chemical Corp. Chromite refractory, P (4) 97*c*. Furnace and refractory, P (3) 68*c*. High magnesia product and process of making, P (7) 204*g*. Method for preparing an alpha alumina catalyst support, P (10) 318*d*. Preparation of magnesium hydroxide by treating dolomite with magnesium nitrate solution, P (10) 318*h*. Process for the production of refractory hard metal materials, P (2) 48*a*. Process for removing impurities from the precipitation system of the Bayer process, P (6) 183*c*. Refractory, P (4) 97*g*, P (8) 241*c*. Refractory bonding composition, P (3) 69*d*. Refractory construction, P (11) 341*a*. Refractory and method, P (3) 69*e*. Refractory shape, P (10) 305*a*. Refractory structure for a rotary kiln, P (1) 14*b*.
Kaiser Industries Corp. Grinding mill and method of operation, P (2) 55*f*.
Kaita, T. See Miyatake, K.
Kajikawa, Y., Ichimura, S., and Kanome, H. X-ray fluorescent analysis of triple carbonates for electron tubes, (2) 50*d*.
Kajita, M. See Ida, I.
Kakar, A. K. Sintering kinetics based on geometric models, (5) 158*d*.
Kakita, I. See Aoki, S.
Kakuda, N. See Furukawa, Y.
Kalb, J. W., Harmon, R. W., and Winters, D. E. Post insulator with composite fillers, P (8) 242*e*.
Kalff, P. J., Hollander, T., and Alkemade, C. T. J. Flame-photometric determination of the dissociation energies of the alkaline-earth oxides, (6) 185*i*.
Kali-Chemie Akt.-Ges. Electrostatic separation process and conditioning compositions therefore, P (9) 279*c*.
Kalish, D. See Clougherty, E. V.
Kalitin, P. P. See Golubev, B. P.
Kalitina, L. N., and Skrylev, L. D. Preparation of highly dispersed materials for electron microscopy, (11) 347*a*.
Kalliga, G. P. See Demonis, I. M.
Kallrath, G. See Biegler, H.
Kalmar, I., and Tamas, F. Experiments with concretes of retarded setting, (1) 2*d*.
Kalnin, I. L. Strength and elasticity of whiteware (I) relation between flexural strength and elasticity, (1) 15*h*. Uniform silicon coatings on graphite by chemical vapor deposition, (2) 38*c*.
Kalnin, I. L., Cucka, P., Warshaw, S. I., and Seider, R. Strength and elasticity of whiteware (II) effect of porosity and mullite content, (6) 175*j*.
Kalwa, M. Chemical and mineral composition of some carbonaceous clay shales and their properties after firing, (6) 171*h*.
Kamada, O. Theoretical concentration and attainable temperature in solar furnaces, (4) 104*d*. See Sakurai, T.
Kamel, A. M. See Low, M. J. D.
Kamel, N. See Tittel, F.
Kamenetskii, S. P. See Fain, I. A.
Kamenskaya, A. N. See Grizik, A. A.
Kamimura, H. Nuclear magnetic resonance of paramagnetic Co_3O_4 (II) theory of the NMR shift, (4) 113*c*. See Miyatani, K.; Shindo, K.
Kaminskaya, E. I., Lyakhovets, K. A., and Nazarov, K. S. Petrochemical study of periclase-chrome spinel brick after service in an open-hearth roof, (9) 268*f*.
Kaminskaya, O. V. See Kosolapova, T. Ya.
Kaminskii, A. A. High-temperature spectroscopic study of stimulated radiation from Nd^{3+}-activated crystal and glass lasers, (10) 321*h*. See Voron'ko, Yu. K.
Kaminskii, Ya. A. Motion of gases and liquids in porous sintered materials, (1) 22*e*.
Kamiyama, A. See Takahashi, T.

Kamper, E., and Guelden, H. Method and apparatus for the drying and heating of gravel and crushed stone, P (4) 105*g*.
Kana'an, A. S. See Kent, R. A.
Kanazawa, T. Formation of 4-coordination structures of intermediate ions and boron in glass, (8) 232*d*.
Kane, W. M., Spratt, J. P., Hershinger, L. W., and Khan, I. H. Structural and optical properties of thin films of $Zn_xCd_{1-x}S$, (7) 208*c*.
Kaneko, H. See Ando, J.
Kaneko, T., and Abe, S. Entropy change at the Morin point of a hematite crystal, (4) 109*i*.
Kanellakopulos, B. Toward a knowledge of the high temperature modifications of a few compounds of the type $Me^{I}XO_4$ (Me = Cs, Tl; X = Re, Tc, Cl), (4) 118*a*.
Kanellakopulos, B., and Parthey, H. Oxidation of uranium tetrachloride, (4) 113*h*.
Kaneno, M. See Yamaguchi, G.
Kannewurf, C. R. See Domingo, G.
Kanome, H. See Kajikawa, Y.
Kansal, J. N. Productivity and technical change in the glass industry, (5) 128*f*.
Kanter, H. Correlation between electroluminescence and electron emission of thin metal-oxide-metal sandwiches, (10) 306*j*.
Kao, Yu. C., and Wolley, E. D. Guard junctions for p-n junction semiconductor devices, P (10) 309*i*.
Kapauan, P. A. See Pascual, O. S.
Kaplan, S. H. Method for making color phosphor screens, P (1) 18*b*. Subtractive type color cathode ray tube having overlapping color phosphor areas, P (1) 19*a*. See Fiore, J. P.
Kapoor, V. N. Improvement in refractory or heat and/or sound insulating materials, P (5) 135*f*.
Kappes, K. A. See Fickert, K. W. J.
Kapur, P. C. Basic fettling grains, P (2) 46*e*.
Karanth, P. K., and Rao, N. A. M. Diffusion in a sphere with fast irreversible reaction in bounded systems, (7) 216*g*.
Karapet'yants, M. Kh. Comparative predictions of certain properties of hydrides, (9) 280*c*.
Karaulov, A. G. See Grebenyuk, A. A.
Karkhanavala, M. D., and George, A. M. δ-U_3O_8, a high temperature modification (I) preparation and characterization, (4) 107*d*.
Karloskomlos, I. Determination of the tensile strength of concrete, (6) 164*i*.
Karlova, L. G. See Volkov, O. S.
Karlovitz, B. Electromagnetic induction in plasma, (10) 312*c*.
Karlson, E. L., and Kiernan, J. V. Black pigment for the blackening of infrared radiation detectors, P (4) 93*a*.
Karlsson, K. See Marklund, I.
Karmakar, S. K. Standardization in the ceramic industry, (1) 34*d*.
Karo, A. M., and Hardy, J. R. Precise vibrational frequency distributions and the second-order Raman spectrum and specific heat of NaCl, (8) 256*c*.
Karp, J. C. Integrated circuit sealing method and structure, P (2) 51*e*.
Karpenko, I. Replication of particulate Al_2O_3 for examination by the electron microscope, (8) 248*f*.
Karra, J. S. See Iyengar, R. D.
Karsch, K. H. Solubility and crystallization of zirconium silicate in glazes during firing, (3) 70*b*.
Karshenbaum, A. G., Makarov, G. N., and Zhitov, B. N. Problem of DTA, (6) 181*b*.
Karve, V. M. See Madhavan, R. R.
Karyuk, G. G., Linenko, Yu. P., and Suplin, Yu. G. Cutting an optically active material with synthetic diamond disks, (10) 293*f*.
Kasai, P. H. Electron spin resonance of a center in fluorine-doped zinc sulfide, (5) 138*f*. Electron spin resonance studies of γ- and X-irradiated zeolites, (6) 185*j*.
Kasamatsu, T. See Nishiyama, A.
Kasami, A., and Koide, S. Anisotropy of dc and high-frequency resistivity of hexagonal ferrite Zn_2Y, (4) 106*a*.
Kaspar, J., Soudek, J., and Gutwirth, K. Method and apparatus for dynamic filtration of slurries, P (7) 211*c*.
Kasper, J. S. See Bundy, F. P.
Kasper, J. S., and Brandhorst, H. Structure of InSb at high pressures, (6) 189*h*.
Kasper, J. S., Hagenmuller, P., Pouchard, M., and Cros, C. Clathrate structure of silicon Na_xSi_{46} and Na_xSi_{136} ($x < 11$), (4) 106*g*.
Kasper, R. J. See Galasso, F. S.
Kass, W. J. See Ebisuzaki, Y.
Kassierer, F. See Mayer, I.
Kastanek, J. See Sirhal, H.
Kataeva, G. V., Levin, S. L., and Pollyak, V. V. Calculation of the charge composition of multicomponent glasses by the approximate calculation method, (10) 297*b*.
Kataoka, K. See Watanabe, Kenichi.
Katayama, S. See Horiguchi, Y.
Kato, E. Electrical resistivity of sintered composite carbon black-kaolin materials (IV) relation between temperature dependence of resistivity and carbon bulk density; (V) effects of firing temperature on resistivity temperature dependence, (5) 151*d*. See Takashima, H.
Kato, E., and Hasegawa, M. Electrical resistivity of sintered composite carbon black-kaolin materials (VI) pressure dependence of resistivity of carbon black under loose contact; (VII) resistivity-bulk density relations of carbon black under loose contact; (VIII) effects of carbon materials on resistivity, (7) 207*f*.
Kato, K. Porcelain teeth having a new holding structure and method for manufacturing, P (5) 137*d*. Selecting brick for the hearth and bank of an open-hearth furnace, (9) 269*h*. See Saito, S.
Kato, K., Ohba, H., Sugita, K., and Shimada, Y. Results of use tests on stabilized dolomite brick in the uptake of an open-hearth furnace, (9) 269*f*.
Kato, M. See Kosaka, M.; Kubo, T.; Takayanagi, T.; Yamada, M.
Kato, S. See Ishii, E.; Sano, S.
Kato, S., Iga, T., Ishii, E., and Sano, S. Effect of metal oxides on surface grain growth of alumina, (10) 319*h*.
Kato, T. See Nakahira, M.
Kato, T. R. See Kispert, R. C.
Katrus, O. A., Kovacev, S. N., Vinogradov, G. A., and Vernik, E. B. Manufacture of diamond tools by rolling of powders, (6) 163*j*.
Katsuraki, H., and Suzuki, K. Neutron diffraction study of $Fe_{1.76}Ge$ single crystal, (5) 155*c*.
Katura, T. See Murabayashi, M.
Katz, A. Direct and rapid determination of alumina and silica in silicate rocks and minerals by atomic absorption spectroscopy, (9) 276*b*.
Katz, G. Epitaxy of copper on sapphire, (10) 307*e*.
Katz, L. See DeBenedittis, J.; Donohue, P. C.
Katz, S. See Raziunas, V.
Katzmann, M. See Dueker, G. W.
Kauders, H. J. Process for preparing highly crystalline alpha strontium acid phosphate, P (8) 251*d*.
Kauer, E. Electric incandescent lamp with levitating incandescent body, P (8) 235*h*.
Kauffman, A. M. Simple immersion method to determine the refractive index of thin silica films, (11) 347*i*.
Kaufman, E. Instantaneous temperature sensor, (9) 283*c*.
Kaufman, E. R. See Trainor, J. T.
Kaufman, M. See Brooks, R.
Kaufman, M., Wharton, L., and Klemperer, W. Electronic structure of SrO, (5) 138*g*.
Kaufman, M. M. Transformer having windings between two ferrite strips [Mn–ZnO], P (2) 52*h*.
Kaufman, W. M. See Esbitt, A. S.
Kaushanskii, V. E., Butt, Yu. M., and Timashev, V. V. Composition of alite, (6) 164*b*.
Kavage, W. T. Phase-matched four-frequency interactions in calcite, (11) 355*h*.
Kaw, P. K. See Guha, S.
Kawabe, K. See Cox, G. A.
Kawada, T. See Bates, J. L.; Nishijima, T.
Kawahara, H., Isha, J., and Marta, Y. Studies on the clay mineral in bore core samples from the Tsugaru Strait tunnel, (8) 250*i*.
Kawai, N. See Suzuki, T.
Kawai, N., Ono, F., and Hirooka, K. New explanation for the magnetic memory of α-Fe_2O_3 on the basis of a negative pressure effect on the Morin transition point, (11) 354*j*.
Kawai, S., Iwasaki, H., and Kiriyama, R. Electrical properties and hydrothermal reactions of volcanic glasses, (8) 231*h*.
Kawakami, K. See Fujiwara, S.
Kawakatsu, I. See Suzuki, H.
Kawakita, K., Komiyama, T., Sakurai, T., and Nakamichi, H. Study of electroluminescent ceramic cell (II) reflection layer of cell, (1) 4*a*.
Kawamura, N. Crystal anisotropy of density of surface states at Si–SiO_2 interface, (4) 107*e*.
Kawamura, S., Mizuta, H., and Kumazawa, S. Mold marks caused by parting lines of casting molds, (1) 15*c*.
Kawamura, S., Nishimura, T., Maeda, T., Ito, A., Asano, K., Mizuta, H., and Kumazawa, S. Studies on cracking in pottery glazes (I) dolomite earthenware glazes, (9) 271*f*.
Kawamura, T. See Yasufuku, M.
Kawano, S., Kosuge, K., and Kachi, S. Electric and magnetic properties of "VO," (10) 320*e*.
Kawashima, C., and Setaka, N. Fundamental studies on chemical vapor deposition (II) crystal growth of silicon carbide by vapor phase reaction at high temperature, (11) 353*d*.
Kawashima, C., Setaka, N., and Nakagawa, J. Fundamental studies on chemical vapor deposition (I) silicon carbide coatings by vapor phase reaction at high temperature, (11) 353*d*.
Kawashima, S. Blue and green luminescence centers of electroluminescent ZnS:Cu phosphors, (11) 350*j*.
Kawecki, R. E. Method and apparatus for accurately proportioning foundary sand ingredients, P (3) 69*a*.
Kay, E., and Poenisch, A. P. Cathode sputtering apparatus including precision temperature control of substrate, P (5) 140*f*.
Kay, J. G. See Garrett, M. B.
Kay, S. M. See Bailey, A. I.
Kaye, B. H. Method and apparatus for fractionation of fine particles, P (11) 348*a*. Permeability techniques for characterizing fine powders, (1) 22*d*.
Kaye, B. H., and Jackson, M. R. New technique for fractionating powders, (1) 22*g*.
Kaye, W. I. Scattered light spectrophotometer, P (1) 24*a*. Spectrophotometer, P (4) 103*i*.
Kazakov, V. K. Character of reaction of titanium nitride with the iron group metals, molybdenum, and tungsten, (3) 66*i*. Preparation of refractories from silicon carbide with nitride binder and from Si_3N_4–SiC materials, (2) 45*d*.
Kazakov, V. K., and Gorodetskii, S. S. Mechanical properties of materials based on SiC and Si_3N_4, (11) 338*j*.
Kazan, B., and Winslow, J. S. Stacked electrode field effect triode, P (8) 246*c*.
Kazaryan, G. A. See Ivanova, L. M.
Kaznoff, A. I. See Grossman, L. N.
Keane, J. D. Evaluation of coatings in potable water tanks, (7) 195*c*.
Kedzie, R. W. See Lyons, D. H.
Keefer, G. E. Apparatus for glazing glass articles, P (11) 335*d*.
Keefer, G. E., and Pei, Y. K. Molten additions of colorants in a glass furnace forehearth, P (1) 9*j*.
Keene, C. W. See Smith, J. W.
Keer, L. M. Shear and combined loading for a penny-shaped crack, (4) 115*b*.
Keester, K. L. See White, W. B.
Keezer, M. B. See Berendsen, A.
Keffer, F. Magnetic properties of materials, B (11) 358*i*.
Keil, K. See Snetsinger, K. G.
Keilholtz, G. W., Lee, J. E., Jr., and Moore, R. E. Irradiation damage to sintered beryllium oxide as a function of fast-neutron dose and flux at 110°, 650°, and 1100°C, (4) 112*a*.
Keiper, F. P., Jr. See Ett, A. H.
Keister, F. Z., and Auda, D. Thick-film hybrid microcircuits, (6) 176*j*.
Keister, F. Z., and Congleton, R. S. Laser apparatus having a layer of silver and a layer of silicon monoxide, P (4) 100*g*.
Keith, C. D., Kenah, P. M., and Soustruznik, G. Alumina-based catalyst and method of preparing, P (4) 104*h*.
Keler, E. K. See Leonov, A. I.
Kell, T. R. See Sloane, R. L.
Kelleher, C. J. Pressure forming system, P (7) 211*g*.
Keller, J. D. Apparatus for absorption spectrochemical analysis, P (9) 275*h*.
Keller, R. A. (editor). Separation Techniques in Chemistry and Biochemistry, B (2) 60*g*.
Keller, W. Apparatus and method of producing semiconductor rods by pulling from a melt, P (4) 99*b*. Method of producing monocrystalline semiconductor rods, P (2) 51*e*.
Keller, W. D. Diagenesis in clay minerals—a review, B (5) 160*d*. Origin of high-alumina clay minerals—a review, B (6) 191*c*. See Hanson, R. F.; Reesman, A. L.; Tlapek, J. W.
Keller, W. D., McGrain, P., Reesman, A. L., and Saum, N. M. Observations on the origin of endellite in Kentucky and their extension to "indianaite," B (7) 224*d*.
Keller Ofenbau G.m.b.H. Method of kilning ceramic ware in a tunnel kiln and the kiln, P (7) 213*i*.
Kellett, C. M. See King, W. J.
Kelley, H. J. See Russell, J. H.
Kelley, L. E. See Drennen, T. J.
Kelley, L. W., Lewis, A., and Provance, J. D. Glass fiber composition, P (4) 94*a*.
Kellington, C. M. See Dueker, G. W.
Kellner, J. D. See Sundheim, B. R.
Kelly, A. Nature of composite materials, B (11) 358*i*. See Cooper, G. A.
Kelly, A., Tyson, W. R., and Cottrell, A. H. Ductile and brittle crystals, (1) 28*c*.
Kelly, A. C., Ducote, H. J., and Barsotti, L. R. Method for preparing an alpha alumina catalyst support, P (10) 318*d*.
Kelly, B. T. Thermal conductivity of graphite parallel to the basal planes and the velocity of phonons in the "out-of-plane" acoustic mode, (4) 117*h*. See Bridge, H.
Kelly, B. T., Martin, W. H., Price, A. M., Dolby, P., and Smith, K. Annealing of irradiation damage in graphite, (4) 106*a*.
Kelly, D. H., and Yodis, A. W. Process for decomposition of aluminum nitrate nonahydrate, P (5) 135*h*.
Kelly, H. J. See Henry, J. L.
Kelly, J. Dynamic study of glass melting tanks, (6) 167*a*.
Kelly, J. D. See Stilley, G. W.
Kelly, R. See Jech, C.
Kemmler, S. Crystal structure of $LiUO_3$, (5) 150*c*.
Kemnitz, R. H., and Winter, H. W. Fluid pressure operated adjustment and release for gyratory crushers, etc., P (11) 349*h*.
Kemper, R. S., Jr. See Last, G. A.
Kemper, W. D. See Shainberg, I.
Kempter, C. P. See Brown, H. L.; Storms, E. K.
Kempter, C. P., and Merryman, R. G. Thermal expansion of a uranium monocarbide-zirconium monocarbide solid solution, (6) 190*c*.
Kempter, C. P., and Nadler, M. R. Thermal expansion of tantalum monocarbide to 3020°C, (6) 190*c*.
Kempter, C. P., and Storms, E. K. Thermal expansion of some niobium carbides, (5) 134*f*.
Kenah, P. M. See Keith, C. D.
Kenahan, C. B. See Andrews, R. L.; Cramer, S. D.
Kenan, R. P. See Kreitman, M. M.; Mills, R. E.
Kendall, L. F., Jr., and Bredt, J. H. Brazing lead telluride thermoelectric generator elements, P (8) 243*j*.
Kendall, V. D. See Blackburn, A. R.
Kendrick, H., Arrott, A., and Werner, S. A. Neutron diffraction data on Ti_2O_3 and V_2O_3, (11) 354*i*.
Kenedi, P. G. See Johnson, A. A.
Kennametal, Inc. Process for preparing tungsten monocarbide, P (7) 205*i*.
Kennard, W. W. See Ford, D. L.

Kennecott Copper Corp. Mandrel for continuous casting mold, P (1) 12*j*. Process for producing molybdic oxide from molybdate solutions, P (2) 57*b*.
Kennedy, J. V. See Granquist, W. T.
Kennedy, M. C. S. See Posner, E.
Kennedy, S. W. Detection of changes of lattice parameters around the interface in a crystal transformation, (2) 54*c*.
Kennedy, T. N. See Allersma, T.
Kennedy, T. N., and Mackenzie, J. D. Role of the network former in semiconducting oxide glasses, (3) 64*b*; correction, (7) 197*e*.
Kennedy, V. C., and Brown, T. E. Experiments with a sodium-ion electrode as a means of studying cation-exchange rates (extended abstract), B (7) 225*a*.
Kenshol, K. W. Ceramic protective coating for high-temperature metal-working extrusion dies, (2) 37*h*.
Kent, R. A., McDonald, J. D., and Margrave, J. L. Mass-spectrometric studies at high temperatures (IX) sublimation pressure of copper(II) fluoride, (5) 154*c*.
Kent, R. A., Zmbov, K. F., Kana'an, A. S., Besenbruch, G., McDonald, J. D., and Margrave, J. L. Mass spectrometric studies at high temperatures (X) sublimation pressures of scandium(III), yttrium(III), and lanthanum-(III) trifluorides, (7) 219*h*.
Kent, R. C., Gordon, R. S., and Hahn, S. J. Model for rheology of halloysite suspensions, (6) 187*g*.
Kenworthy, R. See Wilde, D.
Kenyon, G. H. Glass Industry of the Weald, B (4) 120*g*.
Kepka, A. G. See Dudkowski, S. J.
Keramatik G.m.b.H. Roofs for a tunnel kiln for ceramic products, P (1) 24*e*.
Keramidas, B. G. Formation of barrier layers in cadmium sulfide solar cells, P (6) 177*a*.
Kerkeslager, D. A. See Aiken, H. H.
Kern, E. L. See Hunter, M. J.
Kern, E. R. Quartz-halogen incandescent lamp having a filament and a support made of rhenium-tungsten alloy, P (10) 311*a*.
Kern, R. S., and Beals, R. J. Thermal properties of compositions in the system UO_2-ZrO_2-CaO, (1) 12*g*.
Kern, S. Magnetic susceptibility of praseodymium oxides, (5) 138*j*.
Kernforschungsanlage des Landes Nordrhein-Westfalen. Fuel element for nuclear reactors, P (3) 68*d*. Process for the recovery of uranium from nuclear fuels, P (3) 69*h*.
Kerns, B. T. See Huffstutler, M. C., Jr.
Kerns, R. L., Jr. Clay-mineral dehydration, (7) 212*a*. Determination of cation-exchange capacity by continuous titration, (7) 212*d*. Particle-size separation of clays, (7) 212*i*.
Kerns, R. L., Jr., and Mankin, C. J. Compositional variation of a vermiculite as related to particle size, B (9) 289*j*.
Kerr, G. O. See Jeffery, P. G.
Kerr, G. T. Chemistry of crystalline aluminosilicates (I) factors affecting the formation of zeolite A; (II) synthesis and properties of zeolite ZK-4; (III) synthesis and properties of zeolite ZK-5, (10) 319*h*.
Kerr, P. F. See Langer, A. M.
Kerr, P. F., and Jacobs, M. B. Argillic alteration and uranium emplacement on the Colorado Plateau, B (6) 191*j*.
Kerstan, H. See Kerstan, W.
Kerstan, W., and Kerstan, H. Study of celadon glazes (II), (4) 98*c*.
Kersting, A., and Wartenberg, K. Method of producing monocrystalline semiconductor material, P (5) 142*e*.
Keshari, H. R. See Swain, A. B.
Keski, J. R., and Cutler, I. B. Initial sintering of Mn_2O-Al_2O_3, (9) 283*c*.
Kessel, D. See Kroener, E.
Kessler, G., and Lehmann, H. A. Infrared spectroscopic investigations on borates (I) sodium (1:1:4) borate hydrate, (5) 153*d*.
Kessler, K. G., Passaglia, E., and Winogradoff, N. N. (editors). Research on laser standards and materials at the National Bureau of Standards, (9) 286*h*.
Kestigian, M. See Croft, W. J.
Ketchpel, R. D. See Lehrer, N. H.
Ketelaar, J. A. A. See Honig, E. P.; Schenke, M.
Kettering, Charles F., Foundation. See Charles F. Kettering Foundation.
Keune, R. See Hoekstra, P.
Kevane, C. J. See Holverson, E. L.; Whitehurst, H. B.
Kevern, J. J. Mechanical microdrilling outperforms even the laser, (5) 143*g*.
Kewanee Oil Co. Europium activated strontium iodide scintillators, P (6) 177*g*. Formation of barrier layers in cadmium sulfide solar cells, P (6) 177*a*.
Khabata, S. J., Miranada, M. D., and Salhana, J. A. Abundance of isotopes of lead in a rock sample of the Deccan traps and estimate of the age of rocks from the lead ratio, (6) 183*g*.
Khadzhi, V. E. See Lushnikov, V. G.
Khakhlova, N. V. See Dombrovskaya, N. S.
Khalafalla, S. E. See Rushton, T. N.
Khalafalla, S. E., and Weston, P. L., Jr. Promoters for carbon monoxide reduction of wustite, (3) 77*j*.
Khan, B. Kh. See Bykov, I. I.
Khan, I. H. See Kane, W. M.
Khan, I. H., and Summergrad, R. N. Growth of single-crystal films of cubic silicon carbide on silicon, (5) 153*c*.
Khan, R. A. See Safdar, M.
Khandelwal, S. See Ehrlinger, H. P., III.
Khanduja, R. S. See Ramanath, T. V.
Khanna, R. K., Brower, W. S., Guscott, B. R., and Lippincott, E. R. Laser induced Raman spectra of some tungstates and molybdates, (6) 186*i*.
Khanna, S. S., and Mehra, K. B. Bonding clays and their use in the foundry industry, (6) 172*k*.
Kharazov, V. G., Lindenburg, G. A., and Kozlov, E. V. Use of high temperature thermocouples in the production of quartz glass, (8) 234*i*.
Kharitonov, F. Ya. Diffusion of water and its vapor into ceramic materials, (8) 241*j*. See Budnikov, P. P.; Golubev, B. P.; Matveev, M. A.; Pevzner, R. L.
Kheifets, V. S. See Vargin, V. V.
Khentov, V. I. See Toropov, N. A.
Khimiko-Metallurgichesky Institute AN Kaz. SSR. Method for extracting selenious oxide from gas mixtures, P (10) 318*c*.
Khlebnikova, I. Yu. See Klyucharov, Ya. V.
Khlevchuk, V. R. See Fokin, K. F.
Khliyan, T. M. See Yagub'yan, E. S.
Khodakov, G. S., and Edelman, L. I. Mechanical and thermal activation of the surface layer of ground quartz, (5) 148*b*.
Khodakovskaya, R. Ya. See Kitaigorodskii, I. I.
Khodorov, F. S. See Brodskii, Yu. A.
Khodskii, L. G. See Matveev, M. A.
Khokhlov, V. K. See Entin, Z. B.
Khoroshavin, L. B., D'yachkov, P. N., et al. Effect of phosphoric acid concentration on some properties of finely milled refractory materials, (9) 267*g*.
Khotkevich, V. I. See Palatnik, L. S.
Khouri, A. S. Method of forming a transistor and varistor by reduction and diffusion, P (2) 51*h*.
Khromov, A. M. See Morozov, E. I.
Khrushchov, M. M. Microhardness determination by scratch tests, (10) 315*a*.
Kibbel, W. H., Jr. See Rau, E.
Kide, L. A. Electrostatic precipitator control circuit, P (7) 211*b*.
Kido, K. See Ueda, M.
Kiehl, J. P., and Montagmir, J. Developments in refractory materials for reheating furnaces, (9) 267*c*.
Kienow, S. Results of pressure and torsion tests at high temperatures on magnesite brick and their importance in practice, B (9) 291*b*.
Kierkegaard, P. See Skancke, A.
Kiernan, J. V. See Karlson, E. L.
Kikuchi, C. See Chu, K. C.
Kikuchi, T. See Nasu, S.
Kilby, J. S. Capacitor for miniature electronic circuits, etc., P (2) 50*g*.
Kiley, W. R. See Engel, F.
Kilgore, R. V., and Williamson, W. O. Anomalous differential drying shrinkage of clay-quartz mixtures, (4) 106*d*. Effect of graphite on microstructure and drying shrinkage of clay, (6) 172*j*. Extrusion and microstructures of clay and clay-graphite mixtures, (9) 267*a*.
Kilian, J., and Szepesi, K. Effect of cement mortar kneading with special regard to steam curing, (1) 2*h*.
Kilpatrick, M., and Lott, S. K. Reaction of flowing steam with refractory metals (I) molybdenum (1100° to 1700°); (II) rhenium (850° to 1700°C); (III) tungsten (1000° to 1700°C), (7) 220*g*.
Kim, G. V. Physicochemical properties of Cu_2Se and Cu_2Te, (4) 114*g*.
Kim, H. See Simonyan, K.
Kim, K. H. Thallium oxide glaze containing an additive of ruthenium oxide, P (2) 52*g*.
Kim, S. C., Schlotzer, G., and Palik, E. S. Method of calculating particle-size distribution from sedimentation balance data, (1) 21*j*.
Kimberlin, C. N., Jr., Arey, W. F., Jr., and Buchmann, F. J. Dehydration of magnesium chloride, P (1) 25*j*.
Kimberling, D. F. Wheel glazing, (6) 163*g*.
Kimura, E. Method of forming a *pn* junction in a polycrystalline material, P (9) 273*c*.
Kimura, H. See Pastor, R. C.
Kimura, Y. See Soeya, T.
Kinase, W., Ishibashi, Y., and Hyakubu, S. Birefringence of $BaTiO_3$ and WO_3 crystals, (3) 79*b*.
Kind, N. E. Density of lithium aluminosilicate glasses and their crystallization products, (8) 230*j*.
Kind, V. V. See Zhukov, Yu. A.
Kindlesparker, J. H., and Dixon, W. D. Method for producing hollow ceramic articles, P (10) 306*e*.
King, A. G. Microscopy tells more about processes and products, (4) 103*d*.
King, A. G., and Wheildon, W. M. Ceramics in Machining Processes, B (5) 160*a*.
King, A. G., and Yavorsky, P. J. Stress relief mechanisms in magnesia- and yttria-stabilized zirconia, (2) 59*g*.
King, A. G. B. Efficiency in brickmaking—utilization of resources, (5) 130*j*.
King, B. W., Jr. See Hedden, W. A.
King, E. G. See Mah, A. D.
King, H. G. C., Pruden, G., and Jones, N. F. Synthesis of the active component of commercial Titan Yellow for use in the determination of magnesium, (5) 146*c*.
King, J. C. See Ballman, A. A.
King, L. K. See Murray, D. W.
King, T. B. History of the Canadian glass industry, (9) 263*g*.
King, W. J. Method of forming a *pn* junction by an ionic beam, P (9) 273*c*.
King, W. J., and Kellett, C. M. Solid state translating device comprising irradiation implanted conductivity ions, P (8) 246*b*.
Kingery, W. D. Deposition of alumina from the vapor phase, (6) 172*g*. Interaction between basic science and technological development in ceramics, B (9) 291*c*.
Kingery, W. D., and Schaffer, P. S. Method of epitaxially growing metal oxide single crystals, P (5) 147*a*.
Kingery, W. D., and Waugh, A. Process of casting refractory materials, P (2) 47*f*.
Kinniburgh, W. See Gutt, W.
Kinnon, W. C. See Lisle, A. L. de.
Kino, G. S. See Ruch, J. G.
Kino, G. S., and Route, R. Sound wave interactions in InSb, (11) 342*j*.
Kino, Y., and Miyahara, S. Cubic-tetragonal transition and X-ray diffuse scattering in $NiCr_2O_4$, (3) 79*g*.
Kinoshita, A., and Nakano, T. Production of cuprous oxide single crystal by melt, (11) 355*d*.
Kinoshita, M. See Hamano, Y.
Kinoshita, M., Kose, S., and Hamano, Y. Hot-pressing of zirconium diboride with binder metals—effects of addition of chromium and nickel, (11) 338*d*.
Kinoshita, N. See Maekawa, S.
Kinser, D. L., and Hench, L. L. Effect of a metastable precipitate on the electrical properties of Li_2O-SiO_2 glass, (9) 263*j*.
Kinson, K., Dickeson, J. E., and Belcher, C. B. Determination of metallic iron, nickel, and cobalt in reduced ores and oxides, (8) 248*b*.
Kipp, K. F. See Briody, T. F.
Kirby, R. A. History and development of the refractories industry, (2) 44*b*.
Kirby, R. K. Thermal expansion of rutile from 100° to 700°K, (4) 118*b*.
Kirby, R. K., and Rothrock, B. D. Thermal expansion of vitreous selenium from −190° to +30°C, (10) 326*j*.
Kirchner, H. P. See Gruver, R. M.; Rishel, P. A.
Kirchner, H. P., Gruver, R. M., and Walker, R. E. Chemical strengthening of polycrystalline alumina, (6) 175*e*. Strengthening alumina by glazing and quenching, (10) 306*d*.
Kiriyama, R. See Kawai, S.
Kirkendale, G. A. (editor). Current Developments in the Whiteware Industry—Continuing Education Symposium, Alfred, June 1966, B (3) 89*c*.
Kirkinskii, V. A., and Makarov, E. S. UO_2-PbO_2 system, (9) 288*f*.
Kirkpatrick, J. W. Thermocouple probe with plural junctions, P (10) 316*g*.
Kirova, S. M. See Veinberg, T. I.
Kirsanov, B. P. See Veduta, A. P.
Kischio, W. Method of manufacturing aluminum nitride, P (11) 340*b*. Method of producing or recrystallizing boron phosphide, P (3) 78*e*.
Kisel, T. P. See Klimov, V. V.
Kiser, K. M., and Shade, R. W. Method for the deposition of an electroconductive transparent indium oxide coating, P (3) 73*e*.
Kiser, R. W., and Sullivan, R. E. Mass spectrometry, (10) 314*g*.
Kishii, T. Polarization of photo- and radiophotoluminescence of a silver-activated borate glass, (1) 6*j*. Stress in glass-indium-glass bimetallic composites, (8) 229*f*. See Ooka, K.
Kishii, T., and Ooka, K. "Sensitized" stress buildup in doped sodium borate glasses by ultraviolet irradiation, (9) 264*g*.
Kisinko, P. M. See Husher, J. D.
Kisliuk, P., and Krupke, W. F. Spectrum of Er^{3+} in single crystals of Y_2O_3, (5) 158*h*.
Kislyi, P. S. See Kuzenkova, M. A.
Kislyi, P. S., and Kuzenkova, M. A. Freezing on of zirconium boride thermocouple sheaths, (2) 44*j*. Protective tubes and high-temperature thermocouples with silicon carbide thermoelectrodes, (3) 67*e*.
Kispert, R. C., and Kato, T. R. Fluoride adsorption by thorium oxide in aqueous thorium nitrate solutions, P (11) 340*c*.
Kiss, E. Chemical determination of some major constituents in rocks and minerals, (2) 53*j*.
Kiss, Z. J. Element and apparatus for generating coherent radiation, P (3) 72*f*.
Kiss, Z. J., and Pressley, R. J. Crystalline solid lasers, (9) 271*j*.
Kistler, W. P. Piezoelectric pressure transducer, P (2) 52*b*.
Kistler Instrument Corp. Piezoelectric pressure transducer, P (2) 52*b*.
Kistler Instrumente AG. Piezoelectric building units, P (9) 274*d*.
Kitada, A. See Yokoi, A.
Kitagawa, H. See Nishijima, T.
Kitagawa, H., Inoue, T., Kurokawa, S., and Horigome, S. Lithium magnesium ferrite memory core material, P (5) 141*c*.
Kitagawa, N. See Aoki, M.
Kitahiro, I., Ohashi, T., and Watanabe, A. Hall effect of vanadium dioxide powder, (10) 321*f*.
Kitahiro, I., and Watanabe, A. Thermoelectric power of vanadium dioxide whisker, (10) 326*h*.
Kitahiro, I., Watanabe, A., and Sasaki, H. Growth of vanadium dioxide whisker, (7) 217*i*.
Kitaigorodskii, I. I., and Al'takh, O. L. Possibility of melting glasses with increased content of rare-earth elements, (6) 168*c*.

Kitaigorodskii, I. I., Artamonova, M. V., and Blinov, V. A. Study of luminescence and absorption of neodymium in germanium glasses, (6) 169*a*.
Kitaigorodskii, I. I., and Egorova, L. S. Dependence of certain properties of glasses on the physical and crystallochemical constants of added elements, (6) 166*j*. Synthesis of borosilicate glasses and study of their physicochemical properties, (6) 169*d*.
Kitaigorodskii, I. I., and Ellern, G. A. Study of glass formation in alkali silicate-zirconium systems, (6) 169*i*.
Kitaigorodskii, I. I., Khodakovskaya, R. Ya., and Beus, M. D. Study of the effect of titanium dioxide on the sitallization (microcrystallization) of glass in the system SiO_2-Al_2O_3-MgO, (6) 169*f*.
Kitaigorodskii, I. I., Pavlushkin, N. M., and Khodakovskaya, R. Ya. Possible use of the method of quantitative X-ray phase analysis for crystallized glass materials, (9) 285*c*.
Kitaigorodskii, I. I., Pavlushkin, N. M., and Petrov, S. V. Influence of phase composition and structure of slag sitalls on some of their physicochemical properties, (1) 11*c*.
Kitaigorodskii, I. I., Petrov, S. V., and Beus, M. D. Preparation of sitalls based on Tyrnauz tailings, (6) 168*c*.
Kitaigorodskii, I. I., Petrov, S. V., and Egorova, L. S. Effect of heat treatment on the phase composition and microstructure of vitreous crystalline materials based on slags, (11) 333*e*.
Kitaigorodskii, I. I., Sil'vestrovich, S. I., and Firsov, V. M. Hardening of glasses in polyethylsiloxane liquids and in melts of heavy metals, (6) 167*g*.
Kitamura, S. See Koide, Y.
Kitani, S., and Ouchi, S. Preparation of monodisperse aerosols of sodium chloride, (1) 31*j*.
Kittrick, J. A. Free energy of formation of kaolinite from solubility measurements, (5) 152*k*.
Kittrick, J. A., and Hope, E. W. Procedure for the identification of small crystals by X-ray diffraction analysis, (1) 23*a*.
Kivel, J., and Manning, B. High silica matrix radioactive source and method of preparation, P (4) 100*c*.
Kiyama, M. See Bando, Y.; Hamamura, A.
Kizer, R. H., Jr. See Robinson, G. C.
Kjekshus, A. See Bjerkelund, E.; Fermor, J. H.; Furuseth, S.
Klasse, F. Refractory and process for making, P (10) 305*c*.
Klassen, V. I., and Zinov'yev, Yu. Z. Effect of magnetic treatment of water on the coagulation of suspensions, (5) 136*h*.
Klebanoff, J. Spring tensioned metal-to-ceramic seal, (1) 4*a*.
Kleber, W., and Fehling, W. Crystallization of corundum from cryolite molten solutions, (5) 150*e*.
Kleespies, E. K., Jackson, J., Jr., and Henrie, T. A. Reaction rates of the titanium-oxygen alloy system and titanium chlorides in molten sodium chloride, (4) 114*j*.
Kleijn, H. R. Determination of the moisture content in porous materials using nuclear measurement techniques, (11) 346*e*.
Klein, A. Ceramic artists and their work—Walter Gebauer, (1) 1*i*; Hans Heiner Koerting and Lisa Koerting, (7) 193*j*. Modern European ceramics—hypotheses and events, (10) 293*j*.
Klein, A. G., Prager, P., Wagenfeld, H., Ellis, P. J., and Sabine, T. M. Diffraction of neutrons and X rays by a vibrating quartz crystal, (5) 150*j*.
Klein, D. L. See Lawley, K. L.
Klein, E. See LeGeros, R. Z.
Klein, E., and Verheyden, L. Bakeable quartz-metal sealed window, (2) 53*j*.
Klein, M. J. See Brimhall, J. L.
Klein, M. V. See Timusk, T.
Klein, M. W. Dipole correlations in a random dilute ferroelectric, (8) 253*a*.
Klein, P. H., Jr. See Smucker, C. A.
Klein, T. Method of making a double diffused semiconductor device by a double masking step, P (4) 100*b*.
Kleinman, L. See Lin, P. J.
Kleinova, H. See Konta, J.
Kleinteich, R. Borosilicate glasses and the construction of modern glass apparatus, (7) 195*i*.
Klement, M. Safeguarding the surface purity of ceramic products, (6) 175*i*.
Klemperer, W. See Hanst, P. L.; Huo, W. M.; Kaufman, M.; Wharton, L.
Klenke, E. F., Jr. See Linton, H. R.
Kleppa, O. J. See Holm, J. L.; Navrotsky, A.; Yokokawa, T.
Klerer, J. Determination of the density and dielectric constant of thin Ta_2O_5 films, (3) 79*j*. Thin film capacitor, P (7) 210*f*.
Kliewer, K. L., and Fuchs, R. Optical modes of vibration in an ionic crystal slab including retardation (I) nonradiative region, (9) 285*f*.
Klimenko, V. S. See Tresvyatskii, S. G.
Klimov, V. V., Kozachenko, V. N., Didkovskaya, O. S., Zvonik, V. A., Kisel, T. P., and Andreev, A. Ya. Production of piezoelectric and Seignette ceramics by spray drying of solutions, (8) 243*j*.
Klimova, K. P. See Skorik, Yu. I.
Kline, D. See Bray, P. J.
Kling, H. G. See Harkort, D.
Kling, R. P. See Forchheimer, O. L.
Klingler, E. See Dawihl, W.
Klingler, E. A., and Doerre, E. New applications of pure alumina in electrical engineering and electronics, (5) 139*b*.
Klingsberg, C. See Hummel, F. A.
Klink, J. P., Belue, J. C., and Sears, J. H. Method and apparatus for packaging strand material, P (4) 94*i*.
Klockner-Humboldt-Deutz Akt.-Ges. Grinding mill plant, P (11) 345*i*. Installation and method for firing materials such as limestone, P (10) 317*b*. Multichamber mill, P (10) 312*e*. Suspended-spindle gyratory crusher with means to adjust the spindle, P (1) 26*b*.
Kloepfer, H., Knorre, H., and Stephan, K. Process for the production of hydrides of Ti, Zr, and Th, P (8) 241*a*. Production of hydrides of alkaline earth metals and lithium, P (5) 149*b*.
Kloepfer, H., Sperr, F., and Meyer-Simon, E. Process for the decomposition of zircon sand, P (9) 279*a*.
Klomp, J. T., and Botden, T. P. J. New sealing method for high-purity alumina, B (4) 122*e*.
Klopman, G. See Schultink, L.
Klugt, L. J. A. R. van der. Loss of quality of extruded clay products, (2) 42*i*. Shortening of fat clays, (11) 337*b*.
Klute, C. H. Stage interferometer for microinterferometry, P (2) 55*h*.
Klyachko, Yu. A. See Mashkovich, L. A.
Klynning, L., and Lindgren, B. Spectra of silicon hydride and silicon deuteride, (7) 221*e*.
Klyucharov, Ya. V., and Khlebnikova, I. Yu. Phase chemical analysis of the MgO-Cr_2O_3-SiO_2 system, (8) 248*b*.
Klyucharov, Ya. V., and Skoblo, L. I. Composition of hardening products of aluminophosphate binder in refractory corundum mixes, (7) 200*i*.
Knacke, O., Laser, M., Merz, E., and Riedel, H. J. Process for the recovery of uranium from nuclear fuels, P (3) 69*h*.
Knapp, L. W. See Bruns, J. H., Jr.
Knapp, O. Manufacture of microscope cover glasses, (7) 196*e*.
Knapp, W. J. See Flood, H.
Knapp, W. R. Method of forming charges of molten glass, P (2) 41*b*.
Knapsack Akt.-Ges. Process and apparatus for controlling the temperature prevailing in a sintering grate of the type used for drying and calcining shapes, P (1) 24*d*. Process and apparatus for the manufacture of nitride powders of Al, B, Si, or Zr, P (2) 47*e*. Process and apparatus for the manufacture of titanium nitride, P (1) 13*j*. Process for the manufacture of sodium tripolyphosphate with a high content of phase I material (high temperature modification), P (9) 279*b*.
Knauf, Saar-Gipswerke G.m.b.H. Geb. Method and apparatus for drying or calcining gypsum, P (2) 37*f*.
Knechtel, M. M., Hamlin, H. P., and Hosterman, J. W. Expandable clay in St. Marys formation of southern Maryland, (7) 214*d*.
Knezevic, G. M. Z. See Manojlovic, L. J. M.
Knibbs, R. H. Fracture in polycrystalline graphite, (7) 201*i*.
Knight, S. See Thim, H. W.
Knigin, G. Kh. See Goikhman, V. Yu.
Knoll, P. See Zuleeg, R.
Knoll, W. See Steeb, S.
Knoop, A. N. Fabrication of semiconductor controlled rectifiers, P (4) 100*a*.
Knop, O., and Hartley, J. M. Refinement of the crystal structure of scandium oxide, (11) 356*b*.
Knopp, C. F. See Hill, R. J.
Knorre, H. See Kloepfer, H.
Knoth, W. H. See Muetterties, E. L.
Knott, R. D., and Wadham, E. Semiconductor junction devices which include wafers having beveled edges, P (4) 101*g*.
Knowles, A. R., and Lovicz, V. Method of making a heating element, P (3) 73*c*.
Knowles, E. C. See Cole, E. L.
Knox, A. B. Properties of WO_3 modified by the substitution of Mo and Cr, (1) 31*d*.
Knudsen, I. E., and Levitz, N. M. Oxidation-reduction procedure for particle-size reduction of UO_2, P (1) 13*d*.
Knudsen, J. M. See Shimony, U.
Knupp, R. C., and Berger, D. F. Color characteristics of ultraviolet absorbing emerald green glass, (4) 93*e*.
Kobayashi, A. See Takahashi, R.
Kobayashi, K. See Oinuma, K.
Kobayashi, M. Vacuum sealed silvered mica capacitor for the capacitance substandard, (5) 140*a*.
Kobayashi, M., and Tsurumiya, K. Method for measuring the specific resistance of a silicon crystal by measuring the breakdown voltage, P (5) 142*c*.
Kobayashi, T. Melting point measuring device, P (5) 147*c*. See Harazono, S.
Kobayashi, Y. See Shionoya, S.
Koch, C., and Ranc, R. Method of inhibiting the corrosion of graphite in a CO_2-cooled nuclear reactor, P (6) 174*g*.
Koch, G. See Doorn, C. Z. van.
Kochkin, G. M. See Ermakov, I. S.
Kocik, J. Reciprocal effect of chromium and manganese ions in glass, (1) 7*d*.
Kocik, J., and Nebrensky, J. Thermoluminescent glass activated by manganese, B (10) 329*b*.
Koda, T. See Shionoya, S.
Kodama, H. See Brydon, J. E.; Forman, S. A.
Kodama, H., and Brydon, J. E. Interstratified montmorillonite-mica clays from subsoils of the prairie provinces, western Canada, B (7) 224*f*.
Kodama, H., and Oinuma, K. Identification of kaolin minerals in the presence of chlorite by X-ray diffraction and infrared absorption spectra, B (5) 160*i*.
Kodama, H., and Schnitzer, M. Interactions between montmorillonite and a soil humic compound (abstract), B (9) 289*e*.
Kodama, K. See Suzuki, T.
Kodera, H. Effect of doping on the electron spin resonance in phosphorus doped silicon (II), (7) 217*b*.
Kodera, H., Shirafuji, J., and Kurata, K. Method of producing heterojunctions between compound semiconductors by alloying and substitution reaction, (8) 255*e*.
Koech, G. Method of forming an abrasive surface including grinding and chemically dressing, P (7) 205*b*.
Koehler, E. K. See Glushkova, V. B.
Koehler, H. J. See Illis, A.
Koenig, C. J., and Green, R. L. Water Vapor in High-Temperature Ceramic Processes, B (7) 226*g*.
Koenig, E. W., and Cope, G. R. Refractory-coated oxygen lance, P (2) 48*d*.
Koenig, G., and Weidemueller, C. Behavior of basic brick in the roof of open-hearth furnaces, (7) 200*b*.
Koenitzer, J., and Zimmermann, K. A. Life of the lining of oxygen converters at the August-Thyssen-Huette works at Beeckerwerth, (1) 11*d*.
Koester, A. See Schnuerch, R.
Kofstad, P., and Hed, A. Z. Defect structure model for nonstoichiometric CeO_2, (1) 28*a*.
Koga, K. Results of using plastic refractories in slag pockets of an open-hearth furnace, (9) 269*g*.
Koga, Y. See Murabayashi, M.
Kohashi, T. Light amplifier including a layer for converting X-rays to visible radiation, P (9) 273*f*.
Kohl, W. H. Handbook of Materials and Techniques for Vacuum Devices, B (4) 120*h*.
Kohler, D. M. Process for forming a refractory coating on silicon-iron stock, P (9) 263*b*.
Kohlhaas, F. Laying of mosaics, (5) 124*d*.
Kohlhaas, R. See Hloch, A.
Kohn, K. See Miyatani, K.; Ohbayashi, K.
Kohn, L. L. Credit as a sales tool, (2) 60*e*. How to overcome liquidity problems, (7) 223*f*.
Koide, N., and Abe, R. Dielectric constant and conductivity of very thin SiO films, (5) 150*i*.
Koide, S. See Kasami, A.; Takei, H.
Koide, Y., Kitamura, S., Furumi, K., and Yagi, T. Results of using fired dolomite brick in a rotary kiln lining for calcining dolomite ore, (10) 304*a*.
Koiwa, M. See Yamaguchi, S.
Koizumi, H. X-ray study of PbO-Nb_2O_5-TiO_2 system, (7) 223*a*.
Kojima, C. See Pernot, F.
Kojima, T. See Mino, M.
Kojima, Y., and Sano, K. Activity of iron oxide in silica-saturated slags, (2) 43*c*.
Kokiso, S. See Nakayama, N.
Kokovin, G. A., and Toropova, N. K. Roentgenometric constants of WO_2Br_2, $WOBr_4$, WBr_6, and WBr_5, (3) 86*d*.
Kokubo, T., Sakka, S., and Tashiro, M. Crystallization of glasses containing BaO and TiO_2, (8) 230*e*.
Kokusai Denki Kabushiki Kaisha. Production of semiconductor crystals, P (5) 142*f*.
Kolar, D. See Drobnic, M.; Komac, M.
Kolb, E. D., Coriell, A. S., Laudise, R. A., and Hutson, A. R. Hydrothermal growth of low carrier concentration ZnO at high water and hydrogen pressures, (4) 111*a*.
Kolb, E. D., and Laudise, R. A. Hydrothermal growth of zinc oxide crystals with ammonium ion additives, P (3) 72*i*.
Kolb, E. D., Wood, D. L., and Laudise, R. A. Hydrothermal growth of rare earth orthoferrites, (11) 353*c*.
Kolb, K. E. Flexible glass-plastic laminate, P (10) 300*h*. See Schreiber, C. L.
Kolbasov, V. M. See Funtikov, V. I.; Imashev, M. K.; Lagoida, A. V.; Savin, E. S.; Topil'skii, G. V.
Kolesnichenko, G. A. See Naidich, Yu. V.
Kolesova, V. A. Comparative study of the infrared absorption spectra of alkali-free and Na_2O-containing calcium and magnesium silicate glasses, (8) 230*j*.
Kolev, M., and Zhechkov, G. Bulgarian brick and tile industry, (2) 42*h*.
Kolsky, H. See Tsai, Y. M.
Kolta, G. A. See Bjorling, G.
Koltermann, M. See Kupzog, E.
Kolthoff, B. (compiler). Glass Terminology—A German-English Glossary, B (9) 290*a*.
Komac, M., Pintar, M., and Kolar, D. Preliminary magnetic resonance and susceptibility study of $UO_2 \cdot xH_2O$, (6) 187*h*.
Komar, C. A., and Pierce, C. I. Effects of ultrasonic energy on fluid flow in porous media, (1) 21*h*.
Komarov, V. E. See Smirnov, M. V.
Komatsu, T. See Tanaka, H.; Tsuchihashi, S.
Komatsubara, K. F., and Yamada, E. Nonlinear galvanomagnetic effect of *n*-type InSb in the quantum limit, (9) 284*i*.

Komissarova, L. N., and Pokrovskii, B. I. Reaction of Sc_2O_3 with oxides of the alkaline earth metals, (10) 324*i*.
Komiya, Y. See Tarui, Y.
Komiyama, T. See Kawakita, K.
Komoda, T. Electron microscopic observation of crystal lattices on the level with atomic dimension, (5) 152*a*.
Komrska, J. Permeability thermal analysis, (10) 315*f*. See Satava, V.
Komrska, J., and Satava, V. Study of the hardening of inorganic cements (I) cements based on zinc phosphates, (2) 37*d*.
Komura, H. Phosphorescence of trivalent terbium ion in barium crown glass, (1) 6*g*.
Konarev, M. I. See Zaytseva, L. L.
Kondner, R. L., and Vendrell, J. R., Jr. Clay mineral effects on the stress-strain response of soils in direct shear, B (5) 160*j*.
Kondo, H., and Miyahara, S. Magnetic properties of several orthosilicates with olivine structure, (10) 322*i*.
Kondo, M. See Hasegawa, H.; Nakajima, T.; Okuto, Y.
Kondo, Y. See Isotani, M.; Umeya, K.; Watanabe, T.
Kondrat'ev, Yu. N., and Chernysh, N. V. Problem of the homogeneity of lithium aluminosilicate glasses, (8) 233*c*.
Kondratiev, V. N., Nikitin, E. E., and Talrose, V. L. Problems connected with the investigation of elementary processes in low-temperature plasma, (10) 312*i*.
Koneval, D. J., and Curran, D. R. Piezoelectric resonator and method of making, P (4) 100*j*, P (5) 142*a*.
Konger, A. P. Method and apparatus for packaging bricks, P (3) 66*g*.
Koningstein, J. A. Absorption spectrum of europium iron garnet between 1900 and 5400 cm^{-1}, (3) 78*g*. Crystal-field studies of excited states of trivalent neodymium in yttrium gallium garnet and yttrium aluminum garnet, (7) 216*a*. Electronic Raman spectra (I) Raman transitions of trivalent ytterbium, europium, and neodymium in yttrium gallium garnet, (11) 352*c*. Energy levels of trivalent europium in yttrium gallium garnet, (3) 80*j*.
Konishi, H. See Shibazaki, K.
Konjevic, R., Grant, W. A., and Carter, G. Thermal desorption of argon ionically pumped into glass, (8) 258*a*.
Konno, H. See Kudaka, K.
Konopicky, K. Experiences in determining the softening characteristics of refractories in regard to temperature and load, and other high temperature properties, (9) 276*g*. Structure of high-fired direct bonded chromite-containing brick, (7) 203*j*. Study of hot load deformation of refractories at maximum temperature of use, B (9) 291*b*. See Routschka, G.; Willems, J.; Wohlleben, K.
Konopicky, K., Lepere, K. E., Routschka, G., and Thoenes, H. W. Investigation of used silica brick from the chamber walls of coke oven batteries, (10) 303*j*.
Konopicky, K., Routschka, G., and Kowalczyk, F. Creep and refractoriness of aluminosilicate brick under load at high temperatures, (10) 302*h*. Properties of brick of the magnesite-chromite series, (4) 96*i*.
Konovalov, L. N. See Zaytseva, L. L.
Konta, J., and Kleinova, H. Magmatic quartz as an indicator of kaolinization of granite, (4) 104*j*.
Kontorovich, S. I., Margolis, L. Ya., Shchukin, E. D., and Rebinder, P. A. Increase in the strength of high-dispersion fine-pored structures of magnesium hydrate and oxide with the addition of SiO_2, (5) 125*c*.
Kontrimas, R., and Blakeslee, A. E. Controlled vapor growth of gallium arsenide on germanium, (8) 242*i*.
Konvalinka, J. A. See Scholten, J. J. F.
Kooi, J. See Schechter, M.
Koonce, S. E. See Sinclair, W. R.
Kopeikin, V. A. See Rashkovan, I. L.
Kopineck, H. J., Muszkiewicz, H., and Schlotter, C. Method of conveying fine granular and pulverous material by gaseous means, P (11) 345*j*.
Koppel, Kh. D. See Luzhnaya, N. P.
Koppel, Kh. D., Luzhnaya, N. P., and Medvedeva, Z. S. System Cd-In-As, (10) 325*j*.
Koppel, L. B. See Holmes, J. T.
Koppers Co., Inc. Apparatus for forming continuous helical coils of resin bonded glass fibers, P (7) 198*a*. Electrode rapping control for an electrostatic precipitator, P (4) 102*a*. Method of making titanium dioxide nacreous pigment, P (11) 349*b*.
Kopylov, N. I., and Novoselov, S. S. System Cu_2S-FeS-Na_2S, (1) 33*e*.
Koran, J., and Bazin, H. Combination swiveling and stationary glass cutting tool, P (10) 300*e*.
Koranyi, G. Discussion of "Microindentation hardness and elasticity and Poisson's ratio of glasses," (7) 196*h*.
Kordes, E. See Petzoldt, J.
Kordis, J. BeO-MgO system, (4) 96*a*.
Kordonskaya, R. K., Prokof'eva, Z. M., Lebedev, B. V., and Rozhkov, A. N. Hydraulic resistance of glazed and unglazed ceramic drainpipe, (8) 236*f*.
Korelova, A. I. See Bokin, P. Ya.
Koren, J. G. See Stonehart, P.
Korenev, Yu. M. See Chan Ngok Mai.
Korin, U. See Soroka, I.
Korinek, G. J. Activation energies of conduction in tantalum anodic films, (8) 242*i*.
Kornilov, I. I., and Glazova, V. V. Thermal stability of the compound Ti_2O in the titanium-oxygen system, (9) 288*b*.
Korolev, V. E. See Malyukov, B. A.
Korpi, G. K. See Wickersheim, K. A.
Korshunov, B. G. See Drobot, D. V.
Korshunov, B. G., and Drobot, D. V. Reaction of the chlorides of europium(III), holmium, and erbium with sodium chloride, (10) 324*f*.
Korshunov, B. G., Drobot, D. V., Petrov, K. I., Bukhtiyarov, V. V., and Rubtsov, M. V. System $SmCl_3$-NaCl-KCl, (9) 287*f*.
Korshunov, B. G., Drobot, D. V., and Shevtsova, Z. N. System YCl_3-NaCl-KCl, (9) 287*g*.
Korst, W. L. See Ervin, G., Jr.
Kortkamp, D. H., and Smith, J. M. Sandwiched construction for a tunnel diode, P (3) 74*e*.
Kosaka, M. See Takayanagi, T.
Kosaka, M., Kato, M., Yamada, M., Takayanagi, T., and Minowa, S. Dissolution of commercially available silicon nitride in liquid iron, (11) 351*f*.
Kose, S. See Hamano, Y.; Kinoshita, M.
Koshkin, I. A., Krat, V. A., and Ostroverkhov, V. I. Production of zirconium diboride thermocouple sheaths, (9) 268*b*.
Kosolapov, V. I. Rapid method for determining the apparent density of solid bodies, (10) 315*d*.
Kosolapova, T. Ya., Kaminskaya, O. V., Kovalenko, N. A., and Pustovoit, L. T. Hydrolysis of the dicarbides of rare earth metals [Y, La, Ce, Pr, and Gd], (10) 321*j*.
Kossen, N. W. F. See Heertjes, P. M.
Kossevich, A. M. See Lifshitz, I. M.
Kostanyan, K. A. See Melik-Akhnazaryan, A. F.
Kostic, E. See Delic, D.
Kostiner, E. See Banks, E.
Kostyukov, N. S., and Antonova, N. P. Operation of ceramic insulating materials at high temperatures, (5) 136*i*.
Kosuge, K. Phase diagram and phase transition of the V_2O_3-V_2O_5 system, (8) 255*h*. See Kawano, S.; Shinjo, T.
Kotera, Y., Sato, K., and Miyayama, A. Photometric particle-size analyzer with moving light flux, (1) 22*e*.
Kothari, N. C. Physical and mechanical properties of blended and ball-milled aluminum-aluminum oxide alloys, (2) 45*c*.
Kotlensky, W. V. See Fischbach, D. B.
Kotov, K. I., Saksaganskii, A. M., et al. Use of Dinas in the upper zone of checkers of blast furnace stoves, (9) 269*i*.
Koubek, F. J., and Dyer, E. T. Method of making a ceramic-plastics composite material, P (4) 93*a*.
Koury, F. See Corbin, V. L.
Koury, F., and Waymouth, J. F. In a high pressure lamp, protective metal oxide layers on the inner wall of the quartz envelope, P (7) 209*b*.
Kovacev, S. N. See Katrus, O. A.
Kovach, S. M. Method of ion exchanging crystalline aluminosilicates, P (8) 251*g*. Olefin polymerization using group VIII metal and zinc fluoride or boria on activated alumina as catalyst, P (4) 105*b*.
Kovacik, S., and Cramer, L. W. Trimming glass sheets, P (1) 10*b*.
Kovalenko, N. A. See Kosolapova, T. Ya.
Kovalenko, V. G., Nikitin, Yu. P., and Kryuk, V. I. Rate of solution of oxides in liquid silicates, (9) 286*b*.
Kovba, L. M. See Rachev, V. V.; Trunov, V. K.
Kovba, L. M., Sirotkina, E. I., and Trunov, V. K. Investigation of some double oxides of uranium, (3) 82*c*.
Kowalchik, M. See Trumbore, F. A.
Kowalczyk, F. See Konopicky, K.
Kowalski, B. See Rosenstock, K. H.
Kowalski, W. See Schmeiser, K.
Koyama, K. See White, J. L.
Koyama, T. See Tsuji, S.
Koyama, Y. See Shimada, N.
Koyano, A. Low loss lead zirconate-titanate ceramics, (2) 49*d*.
Kozachenko, V. N. See Klimov, V. V.
Kozacik, J. J. Cement-asbestos products and improvement in the manufacture thereof, P (3) 68*j*.
Kozdemba, S. E., Soukup, V. G., and Dally, D. I. Dressable heat conductive backing for abrasive wheels, P (9) 261*i*.
Kozirovski, Y., and Folman, M. Infrared spectra of CO_2 adsorbed on evaporated alkali halides, (3) 82*b*. Infrared spectrum and spectral shifts of HCN adsorbed on evaporated alkali halides, (3) 82*g*.
Kozlov, E. V. See Kharazov, V. G.
Kozlova, R. F. See Volodina, D. A.
Kozlova, V. K. See Fateeva, N. I.
Kozlowski, M. M., and Harris, T. E. Automatic high pressure lubrication system for rotary grinding mills, P (7) 211*a*.
Kozuka, T. See Nakayama, N.; Noguchi, T.
Kozuka, T., Yamamoto, T., and Hasegawa, K. Compressive efficiency of a tetrahedral anvil apparatus, (11) 345*h*.
Kozyreva, E. A. See Negina, V. R.
Kraaijveld, T. B. See Kreuter, J. C.
Kraft, W. W., and Schorsch, J. J. Regenerative mass, P (7) 205*d*.
Kragie, H. A. Use of programable robots in glass handling operations, (2) 40*e*.
Krakauer, S., Musikant, S., and Rosenberg, D. J. Spinning glass filaments, P (1) 10*a*.
Krakow, B. Spectroscopic temperature profile measurements in inhomogeneous hot gases, (9) 277*d*.
Kramareva, T. V. See Leonova, T. G.
Kramer, B. E. Method of providing refractory metals with protective coatings and resulting article, P (4) 93*b*.
Kramer, H. See Altschuler, Z. S.
Kramer, I. R., and Strauss, E. L. Thermoplastics exhibiting high viscosity at their decomposition temperatures, P (11) 341*a*.
Kranz, R. Nitrogen compounds in silicate minerals and their importance in the technological behavior of feldspars, (3) 83*g*.
Krasnov, A. N. See Burykina, A. L.
Krasotkina, N. I., Petrova, E. V., et al. Phase composition of silicon carbide products with a silica bond as a function of environment, (9) 268*f*.
Krat, V. A. See Koshkin, I. A.
Kratzer, K. See Stary, J.
Kraus, J. See Dijken, R. H.
Krause, G. See Zagar, L.
Krause, G. O., and Teague, E. C. Misfit dislocations in GaAs-Ge heterojunctions, (1) 16*i*.
Krause, H. B. Mixed rutile crystal formation in the Ti-Ni-Sb-O system (II) mechanism of rutile solid solution, (7) 219*g*.
Krause, H. B., Reamer, H. W., and Martin, J. L. Mixed rutile crystal formation in the Ti-Ni-Sb-O system (I) rutile solid solution and the reaction diagram, (7) 219*e*.
Krause, H. J. See Bracht, L. J.
Krause, J. T. See Fraser, D. B.
Krause, J. T., and Kurkjian, C. R. Vibrational anomalies in inorganic glass formers, (5) 129*g*.
Krauss, L., and Schroeder, W. W. Spectrochemical analysis apparatus supplying substantially the same energy to the gap for all waveforms, P (3) 76*g*.
Krauth, A. Sintering kinetics and the powder properties of MgO and UO_2, (8) 239*c*.
Krauth, A., and Meyer, H. Theoretical and technical viewpoints concerning new glassy plasma-sprayed coatings, (5) 126*d*.
Krauth, A., Oel, H. J., and Hossfeld, F. Determination of crystallite size distribution by X-ray diffraction and electron microscopy, (3) 75*f*.
Kravitz, B. L. Method for producing silicon carbide layers on silicon substrates, P (9) 274*g*.
Kravitz, B. L., and Winsker, H. Integrated circuit modules, P (5) 141*b*.
Krebs, H. Structure of glasses, (4) 93*e*.
Krechmar, V. A. See Matveev, M. A.
Kreglo, J. R., Jr., and Smothers, W. J. Creep characteristics of selected high-alumina brick, (6) 172*e*.
Kreider, K. G., and Cooper, A. R. Dissolution kinetics of quartz spheres in a sodium silicate melt—correction, (7) 196*f*.
Kreidl, J. F. History of the glass laser, (2) 39*j*.
Kreidl, N. J. Tokyo symposium on defects in glass, (2) 40*x*. See Lell, E.
Kreidl, W. H. Method of improving the resistance of refractory products, P (2) 47*g*.
Kreidler, E. R. See Farr, A. E.
Kreim, F. Ceramic artists and their work—Elfriede Balzar-Kopp, (4) 91*f*.
Kreimer, G. S., and Vakhovskaya, M. R. Effect of carbon content on the mechanical properties of tungsten carbide-cobalt hard alloys, (1) 11*f*.
Kreisberg, M., and Minicozzi, A. S. Densifier and waterproofing agents for mortar and concrete and method of making, P (5) 125*c*.
Kreitman, M. M., Milford, F. J., Kenan, R. P., and Daunt, J. G. Magnetic susceptibility of Mn^{3+} in CdS and effects of antiferromagnetic exchange, (9) 284*i*.
Kremith, R. D., Rosenbery, J. W., and Hopkins, V. Solid lubricant coatings applied by plasma spray, (10) 296*e*.
Krentsis, R. P., Radovskii, I. Z., Gel'd, P. V., and Andreeva, L. P. Phase transformation in Mn_5Si_3 (10) 324*i*.
Kressnerr, B. E., and Hudson, J. B. Impurity effects on heterogeneous nucleation from the vapor—selenium on glass, (5) 127*d*.
Kreuchen, K. H., and Harvey, E. R. Ceramic components in modern electronic valves, B (4) 122*c*.
Kreuter, J. C., and Kraaijveld, T. B. Corrosion resistance of enameled articles, (2) 37*i*.
Kreuzer, L. B. Ruby-laser-pumped optical parametric oscillator with electrooptic effect tuning, (1) 16*e*.
Kriegel, W. W. See Chay, D. M.
Krieger, F. See Touchy, W; Toussaint, H. N.
Kriek, H. J. S., and Segal, B. B. Torsional test as an aid in determining the quality of basic refractories, (9) 269*f*.
Krieter, J. E. Fiber optic readout device and method for making it, P (7) 208*g*.
Krikke, M. See Dijken, R. H.
Krikorian, N. H., Wallace, T. C., Krupka, M. C., and Radosevich, C. L. Reaction of some noble and transition metals with refractory carbides, (10) 324*i*.
Krimbill, H. W. See Waldron, G. W., Jr.
Krinov, S. M. Mixing control during metal and metalloid oxide production, P (4) 105*a*.
Krishnamurthy, P. See Vdas, G. R.
Kritchevsky, J. See Orbach, H. K.
Kritzler, W. R. See Goldman, R. L.

Kriukelis, V. Deformation of autoclave hardened lime-sand concrete, (1) 2*c*.

Krivoruchko, V. M. See Nechiporenko, E. P.

Kriz, M., and Pacovsky, V. Melting tank with simultaneous gas and electric heating, (6) 167*j*.

Krizek, R. J., and Franklin, A. G. Viscoelastic shear response of a kaolinite, B (9) 289*d*.

Krochmal, J. J., Shapiro, I., and Lynch, C. T. Preparation of films of boron carbide, P (11) 345*a*.

Krock, R. H. See Zdanuk, E. J.

Kroeger, K., and Heckmann, H. Electrical conductivity of soda-lime-silica melts, (8) 231*d*.

Kroener, E., Datta, B. K., and Kessel, D. Bounds of the shear modulus of macroscopically isotropic aggregates of cubic crystals, (4) 106*j*.

Kroenert, W. See Schwiete, H. E.

Kroha, C. E., Jr. See Engdahl, R. E.

Kroichuk, L. A. See Budnikov, P. P.

Kruchinin, Yu. D. Physicochemical conditions for the production of acid- and wear-resistant cast shapes from blast furnace slags, (8) 239*e*.

Krueger, R., and Salge, H. Transformation behavior of two quartzites, (1) 33*h*.

Kruger, O. L. See Moser, J. B.

Kruger, O. L., and Moser, J. B. Preparation of the sulfides and phosphides of plutonium, (4) 114*a*.

Kruger, O. L., Moser, J. B., Thompson, J. W., and Mailhiot, R. E. Uranium carbide-plutonium phosphide as a reactor fuel, P (4) 97*j*.

Krugloff, A. S., and El-Shanshoury, I. A. Nature of luminescence induced by plastic deformation and light illumination of γ-rayed KCl crystals, B (10) 329*c*.

Krupka, M. C. See Krikorian, N. H.

Krupke, W. F. Optical absorption and fluorescence intensities in several rare earth doped Y_2O_3 and LaF_3 single crystals, (10) 324*b*. See Gruber, J. B.; Kisliuk, P.

Kruse, J. M. Diamond purification, P (2) 35*h*.

Krushinskii, A. N. Conditions of preparation of complex carbide alloys containing scandium carbide, (3) 66*j*. Effect of the temperature at which tungsten carbide is produced on the formation of solid solutions with a nonuniform distribution of the carbide phase, (11) 337*h*. Investigation of the conditions of formation of hard alloys with an uneven distribution of the carbide phase (I), (8) 238*h*.

Krystyniak, C. W. Ternary metallic oxide agglomerate and method of preparation, P (6) 175*c*.

Kryuk, V. I. See Kovalenko, V. G.

Kryukova, A. I. See Berul, S. I.

Kryukova, O. N. See Sterlyadkina, Z. K.

Kshirsagar, S. T., and Biswas, A. B. Crystallographic studies of some mixed manganite spinels, (8) 252*e*.

Ku, S. M. See Black, J. F.

Kubisz, J. Existence of hydronium hydrates $H_5O_4^+$ and $H_3O_7^+$ in minerals, (6) 185*h*.

Kublanovskaya, M. A. See Belopol'skii, M. S.

Kubo, K. Negative electrolytic breakdown in proton bombarded LiF crystal, (10) 323*h*. See Nakayama, N.

Kubo, S. See Ichinohe, E.

Kubo, T., Shirasaki, S., and Kato, M. New method for determination of kinetic parameters in solid state reactions, (7) 220*b*.

Kubo, T., Yasuoka, H., and Hirai, A. ^{55}Mn nuclear magnetic resonance of Mn^{4+} ions located at B sites in ferrites, (4) 113*f*.

Kubodera, H. Apparatus for mixing, milling, washing, extracting, and other processes, P (8) 247*e*.

Kuczynski, G. C. Photomechanical effect in semiconductors, B (10) 328*j*.

Kudaka, K., Konno, H., and Matoba, T. Factors affecting the crystal growth of cubic boron nitride, (7) 217*d*.

Kudchadker, M. See Irgolic, K.

Kudelka, V. High temperature flame spraying pistols, P (10) 296*f*.

Kuehl, G. H. Alkali metal and alkylammonium phosphatoaluminate complexes and the preparation of crystalline aluminosilicates, P (9) 279*b*. Crystalline zeolite ZK-21, P (3) 78*a*.

Kuehn, H. New hopper for materials with poor flow characteristics, (1) 19*g*.

Kuelling, A. See Tillmann, P.

Kuendig, W., Boemmel, H., Constabaris, G., and Lindquist, R. H. Some properties of supported small α-Fe_2O_3 particles determined with the Moessbauer effect, (8) 257*c*.

Kuenzi, E. W. Anisotropic sandwich constructions, B (4) 121*b*.

Kuhlmann-Wilsdorf, D. See Ragavan, K. S.

Kuhn, P. J., and McCarley, R. E. Chemistry of the polynuclear metal halides (I) preparation of the polynuclear tantalum halides Ta_6X_{14}, (4) 106*d*.

Kuijpers, M. H. See Dijkmeijer, H. E.

Kuiper, L. L. Method for providing electrical connections to semiconductor devices, P (8) 245*e*.

Kukharskaya, E. V. See Skorik, Yu. I.

Kukota, Yu. P. See Prshedromirskaya, E. M.; Sleptsov, V. M.

Kukota, Yu. P., Prshedromirskaya, E. M., and Sleptsov, V. M. Gas permeability of porous materials from refractory compounds (III), (5) 132*a*.

Kula, E. B. Strengthening of steel by thermomechanical treatments, B (4) 121*f*.

Kulcinski, G. L. High-pressure induced phase transition in ZrO_2, (11) 353*j*.

Kulig, C. W. Body gaging apparatus for glass containers, P (1) 8*d*. See Lyle, A. K.

Kulikova, E. N. See Botvinkin, O. K.

Kulikova, N. V. See Budnikov, P. P.

Kullberg, L. See Ahrland, S.

Kuloor, N. R. See Kumar, R.

Kulp, B. A. See Detweiler, R. M.

Kulyamina, L. L. See Sidorov, A. B.

Kumar, J. A. See Verghese, P. C.

Kumar, R. See Singh, M.

Kumar, R., and Kuloor, N. R. Small to large flow rates measured by new meter, (2) 55*c*.

Kumar, R., Sharma, R., and Gaindhar, J. L. Expansion scabbing of molded material, (1) 11*h*.

Kumar, S., Gupta, S. D., and Sinha, B. C. New method for rapid estimation of phosphate in ceramics and related materials, (5) 145*c*.

Kumazawa, S. See Kawamura, S.

Kume, K. See Shimada, K.

Kumok, V. N., and Serebrennikov, V. V. Stability of complex compounds of the rare earth elements, (10) 325*b*.

Kundu, S. C. Some aspects of kaolinization of feldspar, (5) 148*g*.

Kunin, R., and Gustafson, R. L. Ion exchange, (10) 314*c*.

Kuno, H., Suzuki, A., Sugimura, Y., and Yamaguchi, T. Reaction between $BaCO_3$ and GeO_2, (9) 286*c*.

Kuno, H., Suzuki, A., and Yokoyama, M. Kinetics of the reaction between $BaCO_3$ and TiO_2, (9) 283*d*.

Kuntsevich, O. V. See Zhukov, Yu. A.

Kuntz, U. E. See Hyde, B. G.

Kunz, A. B., and Van Sciver, W. J. 3*p* energy band in lithium chloride, (8) 258*g*.

Kunze, G. W. See Swoboda, A. R.

Kunze, G. W., and Bradley, W. F. Occurrence of a tabular halloysite in a Texas soil, B (6) 192*f*.

Kunzler, J. E., Maita, J. P., Levinstein, H. J., and Ryder, E. J. Pronounced change in the low-temperature heat capacity of V_3Si with stress, (9) 285*h*.

Kupka, F. Quantitative determination of cristobalite by X-ray diffraction analysis, (10) 315*j*.

Kupzog, E. See Lehmann, H.

Kupzog, E., Koltermann, M., and Bartha, P. Bonding of refractories with a solution of monoaluminum phosphate, (7) 200*g*.

Kurakata, H. See Imaoka, M.

Kurapova, G. I. See Morozov, I. S.

Kurata, K. See Kodera, H.

Kurbiel, Z. See Widaj, J.

Kureha Chemical Industry Co., Ltd. Process for producing a graphite anode, P (1) 14*d*.

Kuriakose, A. K. See Poland, D. E.

Kurihara, K. See Ichinose, N.

Kurilovich, T. I. See Vysotskaya, V. N.

Kurita, Ken-Ichiro. Filter cloth fitting apparatus in a filter press, P (5) 144*g*.

Kurita, Kintaro. Filter plate coupling apparatus in a filter press, P (5) 144*a*.

Kurita, T. Photoelectric properties of microcrystalline zinc oxide powder layers with adsorbed monolayer of a long chain fatty acid, (11) 355*i*.

Kurka, G. See Gayet, B.

Kurkjian, C. R. See Gallagher, P. K.; Krause, J. T.

Kurnit, N. A., and Hartmann, S. R. Recent photon echo experiments, B (10) 329*h*.

Kuroda, T. See Mikoda, M.

Kurokawa, R. See Yamamoto, R.

Kurokawa, S. See Kitagawa, H.

Kuroki, H., and Tokumoto, Y. Dielectric properties of B_2O_3-PbO-SiO_2, (7) 196*a*.

Kuroo, Y. See Nakamura, K.

Kurpiers, P. See Lehmann, H.

Kushida, T. Absorption spectrum of optically pumped ruby (I) experimental studies of spectrum in excited states, (10) 318*j*. See Shinada, M.

Kushida, T., and Parikh, P. Optical double resonance experiments in ruby, (3) 84*c*.

Kutcher, I. D. Automatic glazing and sanding machine, P (8) 242*d*.

Kuteinikov, A. F. See Mashkovich, L. A.

Kutkin, I. A. See Finkel, V. M.

Kuttner, P. Spectropolarimeter, P (4) 103*i*.

Kutyla, J. Method of forming projections in reed switch assemblies by selective heat softening, P (5) 141*i*.

Kuwabara, S. Intensity measurement of electron diffraction ring patterns by "Gegenfeld" filter technique, (4) 111*h*.

Kuwahara, Y. See Ueda, K.

Kuzenkova, M. A. See Kislyi, P. S.

Kuzenkova, M. A., and Kislyi, P. S. Grain growth in zirconium diboride during sintering, (8) 237*c*. Mechanism of shrinkage of zirconium diboride during sintering, (8) 238*h*. Oxidation resistance of alloys of zirconium boride with molybdenum disilicide, (3) 67*c*. Preparation of alloys of ZrB_2 and $MoSi_2$ and determination of some of their properties, (2) 45*g*. Preparation of zirconium diboride, (5) 133*j*.

Kuzenkova, M. A., and Yakimenko, V. D. High temperature dilatometer for measuring shrinkage during sintering, (2) 54*h*.

Kuz'ma, Yu. B. See Fedorov, T. F.

Kuz'minskaya, L. N. See Rashkovan, I. L.

Kuznetsova, G. N., Rzhanitsyn, Yu. P., Fedorov, N. F., and Shevyakov, A. M. Infrared spectra of hardening products of cement clinker mixed with potash solutions, (9) 262*b*.

Kuznetsova, I. G., and Poluboyarinov, D. N. Sintering of boron nitride powders during hot-pressing, (7) 203*i*.

Kuznetsova, M. N. See Puntikov, V. I.

Kwestroo, W., Jonge, J. de, and Vromans, P. H. G. M. Effect of impurities on the formation of red and yellow PbO, (5) 151*g*.

La, S. Y., and Bartram, R. H. Wave functions for F^- centers in alkali halides, (9) 288*e*.

Laar, B. van, Schweizer, J., and Lemaire, R. Neutron-diffraction investigation of CoO single crystals, (8) 255*g*.

Laar, J. van, and Scheer, J. J. Photocathode for electron tubes, P (9) 274*c*.

Labbe, C. See Levavasseur, G.

LaBelle, H. E., Jr. See Wolff, G. A.

Lachance, G. R. See Harris, D. C.

La Chapelle, E. A. Multilayer thin-film coated substrate with metallic parting layer to permit selective sequential etching, P (9) 274*b*.

Lachenmayr, H. See Oel, H. J.

Lacheny, P. Composition of industrial plasters, (10) 294*c*. Effect of preparation methods on the properties of hardened plaster, (9) 261*j*.

Lachut, F. J. See Gagnon, R. K.

Lacombe, P. See Beranger, G.; Dornelas, W.; Francois, B.

Lacy, E. D. Newtonian flow of simple silicate melts at high temperature, (5) 128*d*. Structure transition in alkali silicate glasses, (4) 93*h*.

Lacy, P. D. A. See Coleman, D. S.

Ladd, L. S. See Carnall, E., Jr.

Laferty, J. M., Jr., and Poss, S. M. Process of preparing calcium fluoride, P (5) 149*b*.

Laff, R. A. See Esaki, L.

Laffer, B. G., Posner, A. M., and Quirk, J. P. Hysteresis in the crystalline swelling of montmorillonite, (6) 186*j*.

Lagoida, A. V., Butt, Yu. M., and Kolbasov, V. M. Hydration of tricalcium silicate in the presence of potash at different temperatures, (6) 164*i*.

Laha, S. N. Calcination of magnesite and its importance in refractories, (5) 131*i*.

Lahiri, D. See Chatterjee, M. K.

Laird, J. A., and Bergeron, C. G. Interface temperature of a crystallizing melt, (2) 58*e*.

Lajarrige, A., and Leger, J. Pyrometric probe, P (11) 348*d*.

Lajzerowicz, J. See Bassi, G.

Lakatos, T., and Simmingskold, B. Corrosion effect of glasses containing Na_2O-CaO-MgO-Al_2O_3-SiO_2 on tank blocks of Corhart ZAC and sillimanite, (5) 126*j*.

Lakhovizkaya, V. A. See Lyakhovitskaya, V. A.

Lakin, J. R. See Greaves, E. I.; Haglington, J. B.

Lakomskii, V. I., and Mel'nik, G. A. Spheroidization of aluminum oxide powder in a high-frequency plasma discharge—preliminary investigation, (7) 211*h*.

Lal, R. B., and Arnett, G. M. Electron paramagnetic resonance of photosensitive donors in ZnO, (10) 320*e*.

Lalak, J. J. See Milch, A.

Lall, M. M. Device to prevent overboiling and spilling of liquid paste, P (5) 129*f*.

Lally, J. S. See Fisher, R. M.

Lally, K. P. Gated electroluminescent display device having electroluminescent cells with one cell including a photoconductor element, P (3) 72*h*.

Lamar, R. S. Calcined hydrophilic talc pigment, P (5) 148*j*.

Lamb, D. N. See Redding, G. B.

Lambe, J. J. See Cole, T.

Lambert, J. B. See Alexander, G. B.

Lambert, J. D. B. Irradiation behavior of UO_2 particles in cermets, (11) 338*g*. Microstructural modifications produced in UO_2 particles by irradiation, (6) 173*h*.

Lambert, M. See Comes, R.

Lamberth, C. T. See Flack, H. P.

Laming, J. Manufacture and properties of direct-bonded basic brick, (8) 238*b*.

Lamorte, M. F. See Caplan, S.

Lampani, A., and Margola, G. B. Apparatus for drying ceramic ware, P (8) 240*j*.

Lampe, D. R., and Wagner, P. E. Paramagnetic relaxation and crystal-field theory for the ground manifold of chromium in rutile, (10) 324*f*.

Lampus, J. R. See Ziemendorf, E. F.

Land, C. C. See Ogard, A. E.

Land, C. C., Johnson, K. A., and Ellinger, F. H. Plutonium-silicon system, (8) 256*b*.

Landin, J. T. Inspecting method and apparatus, P (3) 65*j*.

Landis, H. M. See Jastram, E. P.; Waseleski, J. W., Jr.

Landry, R. J., Fournier, J. T., and Young, C. G. Electron spin resonance and optical absorption studies of Cr^{3+} in a phosphate glass, (5) 127*i*.

Landsittel, D. T. See Wildeboer, N.

Landspersky, H. See Imris, P.

Landspersky, H., and Jakes, D. Sintering of ceramics from uranium dioxide (II) determination of specific surface of uranium oxide and initial preparation materials, (3) 68*c*.

Landspersky, H., and Vachuska, J. Relation between surface area of powdered UO_2 and its oxidation temperature, (4) 115*h*.

Landspersky, H., and Voboril, M. Oxidation of UO_2 containing small additions of other oxides, (5) 156*h*.

Landuyt, J. van. See Douglass, D. L.

Lane, M. K., and Sheahan, J. S. Method of producing gypsum articles having improved strength to density ratio, P (4) 92*e*.

Lang, A. R. See Wild, R. K.

Lang, J. E., Wisnyi, L. G., and Ploetz, G. L. Refractory cores for annular pellet nuclear fuel elements, (4) 96*c*.

Lang, W. J. Influence of pressure on the electrical resistivity of clay-water systems, B (9) 289*j*.
Langdon, J. L. Methods of making a narrow emitter transistor by masking and diffusion, P (9) 274*a*.
Langdon, T. G. Thinning of polycrystalline MgO for transmission electron microscopy, (3) 88*h*.
Lange, F. F., and Buessem, W. R. Intrinsic brittle strength of magnesium oxide bicrystals, (2) 58*f*.
Lange, H. Alkali metal vapor lamp, P (8) 243*h*.
Langer, A. M., and Kerr, P. F. Evaluation of kaolinite and quartz differential thermal curves with a new high temperature cell, (5) 145*i*.
Langer, D. W., and Euwema, R. N. Pressure shift of the Cr levels in Al_2O_3, (8) 256*g*.
Langer, D. W., and Richter, H. J. Zero-phonon lines and phonon coupling of ZnSe:Mn and CdS:Mn, (11) 358*b*.
Langer, L. See Holynska, B.
Langer, S., Gantzel, P. K., and Baldwin, N. L. Limited solid solutions of uranium and thorium dicarbides, (6) 187*a*.
Langley, R. C. Coatings from organometallic solutions, (3) 63*b*. Electric heating element, P (4) 104*b*. Metal-to-ceramic seal, P (5) 141*d*.
Langlois, R. E., and Stream, R. M. Strand delivery apparatus, P (10) 301*a*.
Langridge, A., Glass, W. B., Grimwood, H. W., and Hegarty, B. A. Semiconductor junction with a depletion layer, P (3) 74*a*.
Langrod, K. Method and materials for obtaining low-resistance bonds to thermoelectric bodies, P (6) 178*i*.
Langrod, K., and Bennett, F. R. Hot-pressing thermoelectric elements, (1) 16*f*.
Langston, R. B., and Jenne, E. A. NaOH dissolution of some oxide impurities from kaolins, B (6) 192*a*.
Langston, R. B., Jenne, E. A., and Pask, J. A. Effect of impurities on the rheology of two kaolins, B (7) 225*c*.
Lanman, R. K. Method of supporting lens blanks for grinding and polishing, P (3) 66*e*.
Lansche, A. M., with Davidson, D. F. Selenium and tellurium—a materials survey, (3) 77*e*.
Lapitskii, A. V. See Berdonosov, S. S.
Lapluye, G. See Provisor, H.
Laporte Chemicals, Ltd. Process for the production of barium hydroxide, P (5) 149*b*.
Laporte Titanium, Ltd. Manufacture of oxides of Ti, Zr, Fe, Al, and Si, P (4) 105*c*.
Lapoujade, P. See Halm, L.
Lapoujade, P., and Mostetzky, H. Present situation relative to European documentation in ceramics, B (9) 291*d*.
Lapshits, B. L. See Brodskii, Yu. A.
Lapshov, Yu. K. See Mal'tseva, L. F.
Laptev, V. I. Problems of automatic control of molten glass levels, (10) 298*j*.
Laquer, H. L. See Daybell, M.
Larchian, G. A. Composite dual dielectric for isolation in integrated circuits and method of making, P (8) 244*f*.
Larger, G. K. Prefabricated composite masonry panel formed of prelaid individual masonry modules bonded together, P (7) 199*i*.
Larionova, Z. M., Nikitina, L. V., Volkov, O. S., and Garashin, V. R. Complex salts in hardened cement with chemical additives, (2) 36*h*.
Larmer, J. W. See Hungerford, W. J.
Larrabee, G. B. See Cronin, G. R.
Larrabee, R. D., and Hicinbothem, W. A., Jr. Resonance behavior of the dielectric constant of GaAs at microwave frequencies, (1) 16*e*.
Larsen, D. M. Cyclotron resonance of piezoelectric polarons, (8) 252*h*.
Larsen, G. Petrographic method used in a study of the leaching of cement paste in concrete, (1) 2*i*.
Larson, A. H. See Zunkel, A. D.
Larson, K. R. Gypsum composition having dehydration resistant characteristics, P (10) 296*b*.
Laser, M. See Knacke, O.
Laskiewicz, J. F. Method for pressure molding powdered material, P (1) 18*g*.
Last, G. A., and Kemper, R. S., Jr. Formation of submicron uranium carbide particles in metallic uranium, P (1) 12*e*.
Laszlo, T. S., Gannon, R. E., and Sheehan, P. J. Emittance measurements of solids above 2000°C, (4) 109*f*.
Laszlo, T. S., Sheehan, P. J., and Gannon, R. E. Thoria single crystals grown by vapor deposition in a solar furnace, (8) 258*e*.
Latham, B. F., Jr. Production of finely divided silicon or titanium carbide, P (1) 14*f*.
Latif, M. See Yousuf, M.
Latta, R. E. See Szwarc, R.
Latterell, J. J. See Stehl, R. H.
Laudelout, H. See Cremers, A.
Lauder, W. B., and Eichelberger, W. C. Process of producing ultrafine metal oxides, P (5) 136*d*.
Laudise, R. A. See Ballman, A. A.; Kolb, E. D.
Lauer, R. B. See Hill, R.
Laugier, J. See Guinet, P.
Launay, R. Method of etching the contacts on a transistor to improve the power output therefor, P (9) 273*i*.
Laurent, S. M. Catalyst preparation, P (5) 148*j*. Physically stable aluminosilicate zeolite catalysts, P (10) 318*h*.
Lavin, E., and Mont, G. E. Treatment of coverplates for glass laminates, P (9) 266*b*.
Lavrinenko, I. A. See Naidich, Yu. V.
Lavrovskaya, G. M. See Balyuk, S. T.
Lawless, W. N. Discussion of "Pressure sintering of NaCl and other ionic materials," (5) 151*c*.
Lawley, K. L., Heilig, J. A., and Klein, D. L. Preparation of ohmic contacts for *n*-type GaAs, (4) 99*e*. Preparation of restricted-area GaAs tunnel diodes, (4) 99*f*.
Lawrence, J. Composite body and method of making, P (7) 208*h*.
Lawrence, W. G. See Modde, M. F.
Lawrenson, J. Method and apparatus for the manufacture of flat glass on a molten metal bath, P (2) 41*g*.
Lawrenson, J., and Silverwood, F. W. Protecting slipper for an edge roller in a glass sheet support bath, P (6) 171*e*.
Laws, K. L. PbO solid electrolyte voltaic cell, (5) 139*g*.
Lawson, A. W. See Neuman, C. H.
Lawton, D. C. See McMillan, P. W.
Lawver, J. E., Sholine, J. H., and French, J. F. Electrostatic separation apparatus, P (8) 251*b*.
Lax, M. See Birman, J. L.
Lay, K. W. Grain growth in UO_2-Al_2O_3 in the presence of a liquid phase, (8) 254*c*.
Layden, G. K. Dielectric and structural studies of $BaTa_2O_6$, (11) 341*g*. Perovskite fields in portions of the systems BaO-$LuTaO_4$-B_2O_3, BaO-$YTaO_4$-B_2O_3, and BaO-$LaTaO_4$-B_2O_3, (1) 30*j*. Polymorphism of $BaTa_2O_6$, (1) 31*e*. See Galasso, F. S.
Layer, E. H., Jr., and Hare, W. F. J. Integrated circuit, P (8) 244*f*.
Lazarev, M. F. See Strelov, K. K.
Lazarus, A. J. See Womack, E. A.
Lazennec, Y. See Gerard-Hirne, J.; Lecrivain, L.
Leach, B. See Hodin, J. P.
Leach, S. L. Electroluminescent devices with light emission generally perpendicular to the ionic current flow, P (7) 208*e*.
Leadbetter, A. J. Thermal properties of glasses at low temperatures, (7) 197*d*.
Leake, J. A. See Cooper, M.
Lean, E. G. H., Quate, C. F., and Shaw, H. J. Continuous deflection of laser beams, (4) 107*c*.
Leander, K. Refractory materials today and tomorrow, (8) 239*j*.
Leary, D. E. See Brown, A. W.
Leary, J. A. See Ogard, A. E.
Leatham, E. See Einstein, E.
Leatham, E., Campbell, W. W., and Rossi, C. E. Shaft kiln and method of operation, P (6) 182*c*.
Lebech, J. See Saermark, K.
Lebedev, B. V. See Kordonskaya, R. K.
Lebek, A., and Raab, S. Process for the purification of materials in single crystal production, P (9) 274*g*.
Le Bouffant, L. Surface structure of quartz and anomalies in the α-β inversion, (6) 189*g*. See Alexanian, C.
Lechner, F. Forecast of developments in ceramic building products, (9) 266*c*.
Leclercq, R. Method of terminating a heating glass structure, P (8) 235*j*.
Lecoco, A. See Baur, A.
Le Craw, R. C., Matthews, H., and Remeika, J. P. Microwave devices utilizing Eu-Fe garnet containing Ga, P (3) 73*h*.
Lecrivain, L. New earthenware compositions for wall tile, B (9) 291*e*. See Dumez, P.; Halm, L.
Lecrivain, L., Maretheu, A., and Lazennec, Y. Zircon opacified glazes for sanitary porcelain fired at cone 9, (6) 175*f*.
Lecrivain, L., Maretheu, A., and Miny, J. C. Study of new earthenware compositions for ceramic wall tile, (9) 271*h*.
Lecrivain, L., and Martin, R. Interpretation of creep tests on refractories, (10) 303*h*.
Leddy, J. J. Method of preparing composite pigments, P (7) 214*h*.
Leding, F. R. Calcining kettle discharge apparatus, P (7) 194*i*.
Le Dinh, P. H. Industrial cleaning of air, (6) 179*c*.
Ledoux, R. L., and White, J. L. Infrared studies of the hydroxyl groups in intercalated kaolinite complexes, B (7) 224*j*.
Le Duc, J. M. See Andre, E.
Lee, D. E., and Csendes, E. Reacting calcium carbonate and wet process phosphoric acid, P (11) 350*a*.
Lee, E. J. See Abraham, M. M.
Lee, H. A. See Turner, W. H.
Lee, H. N. S., and Wold, A. Vapor phase reaction between anhydrous aluminum fluoride and boron oxide, (6) 190*e*.
Lee, J. E., Jr. See Keilholtz, G. W.
Lee, J. M. Gypsum product and method of making same, P (5) 125*d*.
Lee, K. See Sher, A.
Lee, P. S. See Garrett, M. B.
Lee, S., and Bray, P. J. Electron spin resonance studies of irradiated glasses containing boron, (5) 127*j*. ESR studies of irradiated alkali borate glasses with high alkali oxide content, (5) 127*j*.
Lee, T., and Weber, C. W. Particle size distribution measurement in the 200 to 1200 A range, (1) 22*j*.
Lee Wilson Engineering Co., Inc. Wall structure with a metal shell and lining blocks secured by support bars and retainer pins, P (7) 205*h*.
Leeds, D. H. Coatings on refractory metals, B (7) 225*f*.
Leeds & Northrup Co. Automatic optical pyrometer system with automatic gain control, P (3) 76*d*. Method and apparatus for control of rotary kiln exit gas conditions, P (5) 125*c*. Method and apparatus for the optimization of kiln cooler control, P (8) 229*a*. System for making a series of temperature measurements, P (10) 316*f*.
Leeman, J. N. J. Apparatus for the wet-screening of particles, P (3) 78*a*.
Leers, K. J., and Hennicke, H. W. Testing of ceramic materials by sonic methods, (4) 103*c*.
Leesona Corp. Method and apparatus for processing glass yarn, P (2) 41*h*.
Leeuw, G. de. Glass molding device, P (7) 198*h*.
Lefever, R. A., and Matsko, J. Transparent yttrium oxide ceramics, (1) 33*b*.
Leflet, H. A., Jr. See Carson, F. J.
Leflet, H. A., Jr., and Carson, F. J. Apparatus for bending glass sheets, P (4) 94*a*.
Leflet, H. A., Jr., and Caswall, R. D., Jr. Blast head apparatus for tempering glass sheets with means to attach and seal nozzles to the blast head, P (9) 264*j*.
Legal, C. C., Jr. See Turner, G. J.
Leger, J. See Lajarrige, A.
LeGeros, J. P. See LeGeros, R. Z.
LeGeros, R. Z., Trautz, O. R., LeGeros, J. P., and Klein, E. Apatite crystallites—effects of carbonate on morphology, (4) 106*d*.
Leglise, G., and Collet, J. P. Proper thickness for window glass, (11) 334*f*.
Le Goff, P. See Dauvergne, J. P.
LeGouestre, J., and Tyvaert, P. Enameling of cast iron in nonmuffled furnaces, (5) 125*j*.
Legrand, C. Analysis by electron microprobe, (10) 313*b*. See Trillat, J. J.
Legrand, G. See Hameau, G.
Lehman, H. S. See Pliskin, W. A.
Lehmann, G., and Moore, W. J. Optical and paramagnetic properties of iron centers in quartz, (7) 220*f*.
Lehmann, H., and Becker, W. New method of calibration for the Blaine apparatus—Dyckerhoff system, (4) 92*e*.
Lehmann, H., and Kuptzog, E. Influence of feldspar on the rheological behavior of ceramic slips, B (9) 291*d*.
Lehmann, H., Kurpiers, P., and Mathiak, H. Apparatus for measuring the consistency of plaster slips, (4) 91*j*.
Lehmann, H. A. See Kessler, G.
Lehmann, K. See Schmeiser, K.
Lehmann, W. Emission spectra of impurity activated (Zn,Cd)(S,Se,Te) phosphors (I) copper activated phosphors, (7) 207*j*. Hypermaintenance of electroluminescence, (7) 207*c*. Optical absorption edges of ZnO and CdS, (4) 113*d*.
Lehmpfuhl, G. See Goodman, P.
Lehr, G. J. See Badger, A. E.
Lehr, G. J., and Badger, A. E. Multiple sheet glazing unit, P (11) 336*c*.
Lehrer, N. H., and Ketchpel, R. D. Method of making thin film field sustained conductivity device, P (11) 344*d*.
Leibenzeder, S. See Merkel, H.
Leibowitz, D., and Sommer, A. Segmented ferrite sonar transducer with permanent magnet bias, P (8) 246*e*.
Leibrandt, F. See Brauer, G.
Leipold, M. H. Addenda to "Impurity distribution in MgO," (1) 26*e*. See Wys, E. C. de.
Leipold, M. H., and Nielsen, T. H. Fabrication and characterization of isostatically hot-pressed MgO, (3) 81*d*.
Leisenberg, M. Gas firing of ceramic kilns—why impulse firing? (10) 316*j*.
Leitnaker, J. M. See Inouye, H.
Leitnaker, J. M., and Godfrey, T. G. Thermodynamic properties of uranium carbides, (10) 326*f*.
Leitner, A. Natural gas in three brickworks of the Wienerberger Ziegelfabriks- und Baugesellschaft (Austria), (10) 317*b*.
Leitner, K., Miaker, G. J., Moll, O., and Skalla, N. F. Process for manufacturing basic refractory bricks, P (2) 47*i*.
Leitten, C. F., Jr. See Heestand, R. L.
Leitz, Ernst, G.m.b.H. See Ernst Leitz G.m.b.H.
Lejus, A. M. See Collongues, R.
Lekhnovich, N. M. See Sirota, N. N.
Leko, N. A. See Byurganovskaya, G. V.
L'Electro-Refractaire. Process and apparatus for continuously melting and solidifying refractory materials, P (1) 13*h*.
Lell, E., and Kreidl, N. J. Radiation effects on complex glasses, B (10) 328*j*.
Lellep, O. G. Measurement of rotary kiln temperatures, P (7) 213*f*. Rotary kiln temperature measurement, P (1) 24*f*.
Lemaire, R. See Laar, B. van.
Lemonnier, J. M. See Heiss, A.
Lempel, M. J. Numerical method for determining heat-transfer characteristics for a dilute gas-solids mixture in an externally heated tube, (1) 24*e*.
Lenahan, W. M., and Watts, A. G. Thermally insulated shell mold and method of making, P (5) 136*c*.
Lenev, L. M., and Novokhatskii, I. A. Thermodynamic characteristics of $NiAl_2O_4$, (10) 326*a*.
Lennon, J. W. See Sheets, H. D.
Lenoir, J. See Byraud, M. C.
Lentz, C. W. Analysis of tobermorite by the silicate-derivative technique, (3) 79*a*.

Lenzo P. V., Spencer, E. G., and Ballman, A. A., Electrooptic coefficients of ferroelectric strontium barium niobate, (3) 71*g*.

Leofsky, E. E. See Wright, H. E.

Leonard, L. B. Capillary passage and method of making, P (7) 198*c*.

Leonard, R. A., and Low, P. F. Effect of gelation on the properties of water in clay systems, B (6) 192*a*.

Leonard, R. A., and Weed, S. B. Influence of exchange ions on the *b* dimensions of dioctahedral vermiculite, B (9) 289*i*.

Leonard, R. B. See Butherus, A. D.

Leonov, A. I., Andreeva, A. B., Shvaiko-Shvaikovskii, V. E., and Keler, E. K. High-temperature chemistry of cerium in the systems cerium oxide-Al_2O_3, Cr_2O_3, Ga_2O_3, (6) 186*c*.

Leonov, A. I., Keler, E. K., and Andreeva, A. B. Studies of the La_2O_3-ZrO_2, Ce_2O_3-ZrO_2, and Nd_2O_3-ZrO_2 systems, (9) 287*a*.

Leonova, T. G., Kramareva, T. V., and Shul'man, V. M. Stepwise adsorption of colloidal cadmium sulfide particles on glass, (10) 298*g*.

Leontaritis, L. See Buehler, H. E.

Lepere, K. E. See Konopicky, K.

Lepiane, D. C., and Zimmerman, H. N. Methods of applying doping compositions to base materials, P (3) 73*g*.

Lepinskikh, B. M. See Musikhin, V. I.

Lesk, I. A. Method of making a semiconductor device having improved *pn* junction avalanche characteristics, P (1) 18*c*.

Leslie, W. C. Strength of ferrous martensites, B (4) 121*f*.

Lesnikov, A. K., and Bykodorova, I. S. New method of strengthening quartz glass, (8) 233*i*.

Less, L. N. See Baker, M. McD.

Lessoff, H. Effects of annealing conditions on the magnetic properties of magnesium-manganese ferrite and zinc and cadmium substituted Mn-Mg ferrite, (9) 271*i*. Vanadium-containing lithium ferrites, P (6) 179*a*.

Lessor, A. E., Jr. See Glang, R.

Lester, F. P. How wet is your mold? (1) 15*b*.

Letournier, R. See Patriarche, P.

Letter, E. C. Measuring laser output energy comprising a lead fluosilicate glass dosimeter element, P (7) 199*a*.

Leung, J. S. See Calvo, C.

Leusden, C. O. P. Flow mechanics within the auger, B (9) 291*c*. Flow process in the extruder, (7) 199*h*. Relation between the rheological properties of plastic ceramic materials and technical data of the shaping process, (5) 146*h*.

Levandowsky, L. See Fleurence, A.

Levavasseur, G., Morpain, R., Labbe, C., and Frisby, H. Experiments on sintered beryllium oxide under thermal stress, (6) 173*c*.

Lever, R. C. See Fussell, L. E.

Levesque, M. See Corbin, V. L.

Levett, P. D. Properties and applications of PTC thermistors, (3) 72*c*.

Levey, R. P., Jr., and Smith, A. E. High-temperature isostatic pressing of articles, P (4) 102*c*.

Levin, I. W., and Abramowitz, S. Coriolis ζ constants and force field for osmium tetraoxide, (6) 184*b*. Force field for SiF_4, (10) 321*h*.

Levin, P. A. Factors affecting the quality of liquid gold, (8) 242*a*. New luster colors for glass and porcelain, (5) 136*g*.

Levin, S. I. See Kataeva, G. V.

Levine, A. K. See Palilla, F. C.

Levine, A. K., Palilla, F. C., and Rinkevics, M. Method of preparing vanadate phosphors, P (3) 73*c*.

Levine, C. A. Electroless plating on nonconducting surfaces, P (5) 141*d*.

Levine, I. E. Vanadium oxide catalyzed oxidations, P (11) 350*a*.

Levine, J. D., and Mark, P. Theory and observation of intrinsic surface states on ionic crystals, (9) 287*i*.

Levine, S., and Matijevic, E. Comparison of models for the electric double layer, (1) 27*e*.

Levinskaya, M. Kh. See Levinskii, Yu. V.

Levinskii, Yu. V., and Salibekov, S. E. Reactions of the diborides of Ti, Zr, and Hf with carbon, (3) 85*j*.

Levinskii, Yu. V., Salibekov, S. E., and Levinskaya, M. Kh. Reaction of Cr, Mo, and W borides with carbon, (5) 133*b*. Reaction of V, Nb, and Ta diborides with carbon, (5) 133*c*.

Levinsohn, M. See Hungerford, W. J.

Levinson, L. S. Heat content of uranium dicarbide from 1484° to 2581°K, (5) 153*h*. High-temperature heat content of niobium carbide and tantalum carbide, (5) 153*j*. High-temperature heat content of tungsten carbide and hafnium carbide, (5) 153*j*. High-temperature heat contents of TiC and ZrC, (3) 81*c*.

Levinstein, H. J. See Ballman, A. A.; Geusic, J. E.; Kunzler, J. E.; Van Uitert, L. G.

Levinstein, H. J., and Nassau, K. Growth of lithium niobate crystals, P (1) 18*a*.

Levitz, N. M. See Knudsen, I. E.

Levushkin, L. N. See Yanshchikov, V. S.

Levy, C. See Carvelle, B.

Levy, M. Scottie Wilson—the visionary experience, (2) 36*a*.

Levy, P. W. Physical properties of irradiated ceramic materials, B (4) 120*i*.

Lewek, S. S. Method of treating glass in a molten salt, P (11) 336*j*.

Lewis, A. See Kelley, L. W.

Lewis, A. D. Apparatus for forming the open end portion of small glass containers, P (1) 8*j*.

Lewis, B., and Campbell, D. S. Nucleation and initial-growth behavior of thin-film deposits, (8) 255*j*.

Lewis, G. E., Jr., and Drickamer, H. G. Effect of high pressure on the lattice parameters of Cr_2O_3 and α-Fe_2O_3, (10) 319*g*.

Lewis, G. L., Gulledge, H. C., and Teufer, G. Thermally stable fibrous alkali metal titanates, P (8) 246*d*.

Lewis, J. E. See Grossman, L. N.

Lewis, K. E., and Parfitt, G. D. Infrared study of the surface of rutile, (3) 82*h*.

Lewis, R. R., and Senftle, F. E. Source of ferromagnetism in zircon, (1) 10*j*.

Lewis, T. J., and Wright, A. J. Electrical conductivity of magnesium oxide at low temperatures, (11) 352*h*.

Lexington Laboratories, Inc. Method of epitaxially growing metal oxide single crystals, P (5) 147*a*. Process of casting refractory materials, P (2) 47*f*. Tensile test apparatus, P (7) 213*b*.

Leybold Holding A. G. Semiconductor device for demonstrating the Hall effect, P (5) 142*h*.

Leytsina, V. G. See Rubinchik, Ya. S.

Li, Pei-Ching, and Pappis, J. Preparation of boron-pyrographalloy foam and foil, (5) 133*e*.

Li, Shu-T'ien. Proposed synthesis of gap-graded shrinkage-compensating concrete, (2) 36*f*.

Libbey-Owens-Ford Glass Co. Apparatus for bending glass sheets, P (4) 94*a*. Apparatus for heat-treating and conveying glass sheets vertically oriented, P (1) 8*j*. Apparatus for producing multiple sheet glazing unit, P (8) 235*d*. Apparatus for producing sheet glass, P (11) 335*f*. Blast head apparatus for tempering glass sheets with means to attach and seal nozzles to the blast head, P (9) 264*j*. Conveyor apparatus [for glass sheets], P (1) 8*k*. Electrically heated transparent panel and protective circuit therefor, P (7) 198*c*. Glass breaking apparatus, P (6) 170*j*. Glass sheet support frame, P (1) 9*c*. Internally cooled hot glass contacting roll, P (8) 235*c*. Laminated glass structure, P (2) 41*c*. Locator device, P (6) 170*j*. Method and apparatus for bending horizontally conveyed glass sheets between opposed shaping molds, P (4) 94*f*. Method and apparatus for bending and tempering glass sheets by differential heating, P (11) 336*c*. Method for bending glass sheet to a complex curvature, P (2) 41*j*. Method of producing multiple glass sheet glazing units, P (9) 265*h*. Method for tempering and conveying glass sheets, P (6) 171*b*. Multiple sheet glazing unit, P (11) 336*c*. Polishing, P (10) 301*c*. Process for removing thin films from vitreous surfaces, P (6) 171*d*. Sheet glass apparatus, P (11) 336*g*. Testing apparatus, P (8) 236*a*. Transparent laminates and method of producing, P (9) 266*b*. Trimming glass sheets, P (1) 10*b*.

Liberti, P. A. Centrifugal chromatography and electrophoresis device, P (11) 347*e*.

Librant, Z., and Pampuch, R. X-ray strain analysis of MgO crystallites derived from thermal decomposition of various magnesium compounds, (3) 88*d*.

Licentia Patent-Verwaltungs G.m.b.H. Fuel element for nuclear reactors, P (7) 204*c*. Method of forming a semiconductor by diffusion through the use of a cobalt salt, P (9) 273*f*. Method of making fuel cell electrodes comprised of borides, carbides, nitrides, and/or silicides of transition metals, P (8) 241*b*.

Lidiard, A. B. Fundamentals of radiation damage in ceramics, B (4) 120*i*. See Hardy, J. R.

Liebling, R. S. Effect of low porosity on the elastic properties of boron carbide, (4) 108*c*.

Liebowitz, H. See Vanderveldt, H.

Lieth, R. M. A., and Heyligers, H. J. M. Phase diagram of the pseudobinary system Ge-GaAs, (10) 324*i*.

Lietzke, A. F. See Rom, F. E.

Lifanov, I. I. See Bykov, V. M.

Lifshitz, I. M., Kossevich, A. M., and Geguzin, Ya. E. Surface phenomena and diffusion mechanism of the movement of defects in ionic crystals, (6) 189*c*.

Lightfoot, D. G. See Murphy, N. A.

Lihou, D. A. See Jones, L. W.

Liley, P. E. See Ho, C. Y.

Lillard, J. G., and Zubik, A. R. Moisture content determining device having a pressure-operated capacitor member, P (7) 213*a*.

Limbach, D. von. See Stewart, D. B.

Lin, C. C. See Brumage, W. H.

Lin, H. C. Semiconductor devices with low leakage current across junction, P (4) 101*g*.

Lin, H. C., and Hellstrom, M. J. Constant current gain composite transistor, P (10) 309*i*.

Lin, K. H. See Palermo, J. A.

Lin, P. J., and Kleinman, L. Energy bands of PbTe, PbSe, and PbS, (8) 253*f*.

Lin, Zui-feng. See Rechnitz, G. A.

Linares, R. C. Growth and properties of CeO_2 and ThO_2 single crystals, (8) 254*d*.

Lincoln, J. A. Method of reducing carbon deposits on surfaces in contact with carbonaceous gases and subjected to elevated temperatures, P (2) 56*a*.

Lincoln, R. L. See Johnson, P. M.

Lincoln Brass Works. Burner that creates uniform flame size by using progressively smaller holes, P (4) 104*a*.

Lincoln Electric Co. Arc welding flux, P (10) 296*f*.

Lindahl, F. A. See Hysinger, D. M.

Lindberg, A. Semiconductor device for demonstrating the Hall effect, P (5) 142*h*.

Lindberg, R. See McRae, R. C.

Linden, P. C. van der. See Zalm, P.

Linden Laboratories, Inc. Method of preparing electroded ceramics for bonding, P (6) 178*a*. Method of treating polycrystalline ceramics for polarizing them, P (5) 142*h*.

Linden Laboratories, Inc., and Cook, E. G. Transducer assembly for producing ultrasonic vibrations, P (11) 345*c*.

Lindenburg, G. A. See Kharazov, V. G.

Lindgren, B. See Klynning, L.

Lindley, W. T. See Wolfe, C. M.

Lindmayer, J. Field effect transistor with an induced *p*-type channel by means of high work function metal or oxide, P (8) 244*c*. Induced region semiconductor device, P (4) 100*d*. Small junction area S-M-S transistor, P (10) 311*d*.

Lindner, G., and Edmundsson, I. Analytical determination of inorganic bound phosphorus in the presence of alkylated phosphorus, (5) 149*e*.

Lindquist, R. H. See Kuendig, W.; Mulaskey, B. F.

Lindsay, J. G. See Bakker, W. T.

Lindsley, D. H. Melting relations of $KAlSi_2O_6$—effect of pressures up to 40 kilobars, (5) 154*h*.

Lindson, J. T. Titanium dioxide means white, (11) 332*g*.

Lindstrom, R. E. See Bauer, D. J.

Linenko, Yu. P. See Karyuk, G. G.

Lines, M. E. Antiferromagnetism in the face-centered cubic lattice (I) random-phase Green's function approximation, (8) 252*c*.

Lines, M. E., and Jones, E. D. Antiferromagnetism in the face-centered cubic lattice (II) magnetic properties of MnO; (III) α-MnS, (8) 252*c*.

Linevsky, M. J., White, D., and Mann, D. E. Infrared spectrum and structure of gaseous Al_2O, (5) 153*c*.

Lingl, H., Jr. Longitudinal slot-fired tunnel kiln, (10) 316*j*.

Lingl, J. Method and apparatus for setting bricks, P (9) 266*c*.

Lingren, W. E., Reeck, G. R., and Marson, R. J. Separation of iron(II)-iron(III) mixtures by simultaneous paper chromatography and electrophoresis, (11) 347*g*.

Linhart, O. C., and Thompsen, R. S. Effect of frit composition on set stability, (9) 262*j*.

Link, M. J. High strength inorganic cement compositions, P (5) 125*c*.

Linn, F. C., and Snell, R. G. Glass sag temperature determination, (2) 39*j*.

Linnemann, R. Device for installing or replacing the lining of rotary kilns, P (8) 249*c*.

Lins, S. J. Precision electrical component adjustment method, P (9) 274*d*.

Linstedt, H. Spark plug with the insulator tip coated with spinels of aluminum and cobalt oxides, P (5) 143*b*.

Linton, H. R. Silica-coated lead chromate pigment, P (6) 183*d*.

Linton, H. R., and Klenke, E. F., Jr. Color stabilized mica, P (6) 182*j*.

Liodec, N. See Vilnat, J.

Liogon'kaya, R. I. See Danyushevskii, S. I.

Lipis, L. V. See Zaytseva, L. L.

Lipkins, M. Slicing high cost materials, (2) 60*c*.

Lippard, S. J. See Cotton, F. A.

Lippincott, E. R. See Khanna, R. K.

Lippmann, F. Synthesis of norsethite, $BaMg(CO_3)_2$, at approx 20° and 1 atm—model of dolomitization, (7) 222*j*.

Lipschutz, L. D., and Chow, T. K. Two-color multiple beam interferometer for measuring small separations, P (4) 103*i*.

Lisle, A. L. de, Lisle, F. S. de, and Kinnon, W. C. Means and method for removing iron from asbestos ore, P (6) 183*b*.

Lisle, F. S. de. See Lisle, A. L. de.

Lisov, A. A. See Logginov, G. I.

Lisov, A. A., and Maslennikova, G. N. Elastoplastic-viscous properties of porcelain bodies, (5) 136*i*.

Lisovskaya, G. P. See Pavlushkin, N. M.

List, H. Mixing machine, P (1) 20*d*.

Lister, C. R. B. Design of a deep-ocean pressure case using a ceramic tube, (1) 15*c*.

Lister, D. H., and Glasser, F. P. Phase relations in the system CaO-Al_2O_3-iron oxide, (5) 156*g*.

Lister, R. H. See Roberts, R. F., Jr.

Lister, R. R. See Davies, W.

Litovitz, T. A. See Capps, W.; Macedo, P. B.; Tauke, J.

Little, Arthur D., Inc. See Arthur D. Little, Inc.

Little, J. R., and Sanford, E. A. Semicrystallized ground coats and enameled articles manufactured therefrom, P (11) 333*a*.

Little, L. H. See Cant, N. W.

Littler, E. S. See Oxley, G. H.

Litton, C. W. See Park, Y. S.

Litton Systems, Inc. Method for orienting single crystal films on polycrystalline substrates, P (6) 178*i*.

Litvin, A. Clear coatings for exposed architectural concrete, (10) 294*b*. See Hedstrom, R. O.

Liu, Kuo-Yuan. See Fedorov, P. I.

Liu, S. W. W. See Womack, E. A.

Livage, J., Doi, K., and Mazieres, C. Nature and thermal evolution of amorphous hydrated zirconium oxide, (7) 220*b*.

Livera, P. A. See Rively, C. M.

Livey, D. T., and Hey, A. W. Sintering and densification studies on BeO powders, (3) 85*e*.

Livey, D. T., and O'Neill, J. S. Refractory oxides doped with silicon carbide and silicon nitride, P (1) 14*j*.
Lloyd, K. See Joy, A. S.
Lo, G. Y. S. See Moyer, J. R.
Loc, V. See Makram, H.
Loch, L. D. Thermoelectric device comprising $100SnO_2 \cdot xSb_2O_3$, P (5) 143*a*.
Locher, F. W. Stoichiometry of the hydration of tricalcium silicate, (3) 62*e*.
Lochte-Holtgreven, W. Simple chemical reactions in plasmas, (10) 312*j*.
Lockett, T. A., and Eaglestone, A. A. Royal Rockingham porcelain—a reassessment, (2) 36*a*.
Lockhart, R. J. Method of spinnerette cleaning during the preparation of inorganic oxide monofilaments, P (8) 247*e*.
Lockyer, C. New interferometric method for measuring the thickness of thick films, (4) 103*e*.
Locsei, B. Fireclay products of improved quality, (1) 11*i*. Reaction mechanism of mullite formation in the system kaolinite-AlF_3, (7) 220*i*.
Lodding, W. (editor). Gas Effluent Analysis, B (8) 260*b*.
Loeber, H. *Guttrolf*, forming and manufacture, (8) 227*j*.
Loeffler, C., and Loeffler, J. Determination of alumina in cords by the electron microprobe, (8) 231*d*.
Loeffler, J. See Loeffler, C.
Loftus, P. H. See Meyer, R. A.
Logan, M. C., and Gibson, H. B. Thermocouple junctions, P (7) 213*c*.
Logan, R. A. See Trumbore, F. A.
Logan, R. A., Trumbore, F. A., and White, H. G. Electroluminescent gallium phosphide crystal with three dopants, P (5) 141*e*.
Logan, R. A., White, H. G., and Trumbore, F. A. *P-n* junctions in GaP with external electroluminescence efficiency approx 2% at 25°C, (1) 16*c*.
Logan, T. J. See Peterson, D. J.
Logginov, G. I., and Lisov, A. A. Investigation of the shear of ceramic bodies, (11) 346*d*.
Loh, E. Ultraviolet absorption and excitation spectrum of ruby and sapphire, (7) 222*j*.
Loh, E., and Doell, W. Charging device for machines for working optical lenses, P (3) 65*e*.
Lohmeier, E. B., Jr. Drive mechanism for a plurality of rotatable objects, P (5) 137*c*.
Lohmeyer, S. Measurement of damage to the decoration on porcelain surfaces, (9) 276*b*.
Loiacono, G. M., and Michelman, B. Growth and properties of $K_4Nb_6O_{17}$, (10) 321*e*.
Loisel, M. See Fleurence, A.
Lokot, A. A., Azelitskaya, R. D., and Ponomarev, I. F. Clinker firing as a function of granulometric composition of raw material, (5) 124*g*.
Lokras, S. G. See Bose, U. P.
Lokshina, S. E. See Svet, V. I.
Loladze, T. N., Bokuchava, G. V., and Davydova, G. E. Measurement of the hardness of diamond at high temperatures, (10) 323*e*.
Lombardo, M. C. Densifier and waterproofing agents for mortar and concrete and method of making, P (5) 125*c*.
Lommel, J. M. See Rodbell, D. S.
Long, J. See Cuer, P.
Long, J. V. High-temperature coating technology shows steady advancement, (2) 37*j*.
Long, R. A. High temperature compositions, P (2) 47*b*. See Barr, F. A.
Long, R. K. See Charlton, T. E.
Long, R. K., and Mize, J. P. Method of forming a [zener] diode by using a mask and diffusion, P (3) 73*b*.
Longinotti, L. D. See Matthias, B. T.
Longman, G. W., and Palmer, R. P. Two microscopical methods of determining the contact angles of small drops, (9) 277*b*.
Longo, F. N. High temperature flame spray powder and process, P (7) 195*d*.
Longo, J. M. See Goodenough, J. B.
Longo, J. M., and Raccah, P. M. Magnetic and structural study of the spinel $MnYb_2S_4$, (1) 30*a*.
Longwood Engineering Co., Ltd. Mechanical screens, P (5) 144*c*.
Lonzo, P. V. See Holmes, C. H.
Lood, D. E., Spriggs, R. S., and Rogers, J. L. Method of fabricating thin film resistors, P (8) 245*f*.
Loomis, D. G. Isostatic pressing for ceramics, (1) 19*f*.
Loon, J. van. See Cremers, A.
Loopstra, B. O. See Cordfunke, E. H. P.
Loosjes, R., and Maas, B. J. M. Method of the production of a body from a slip in a porous mold, P (7) 211*d*.
Lopatnikova, L. Ya., and Guseva, V. I. Prevention of false set of cement, (5) 125*g*.
Lopato, L. M. See Tresvyatskii, S. G.
Lopenski, S. A., and Rokosz, F. Electrostatic coating apparatus for uniformly applying phosphor powders, P (4) 99*j*.
Lopez, A. D. Fast etching imperfections in silicon dioxide films, (7) 207*b*.
Lopez Cabanillas, H. Artistic ceramics, (3) 61*i*.
LoPilato, S. A., and Carter, S. W. Unbond detection using ultrasonic phase analysis, (7) 213*d*.
Lopker, E. B. Method of increasing the capacity of horizontal rotary vacuum filters, P (7) 211*d*.
Lorant, M. Electronic ceramics, (1) 16*e*. Fluid-pressure testing device, (7) 212*g*.
Lord, C. W. See Shannon, J. P., Jr.
Lorenc, J. A. See Siegel, I.
Lorenz, M. R., Woods, J. F., and Gambino, R. J. Some electrical properties of the semiconductor β-Ga_2O_3, (3) 72*d*.
Lorrain, C. See Huet, H.
Lorthioir, G. See Fruchart, R.
Lotsch, H. K. V. Filamentary laser mechanism, (6) 185*h*.
Lott, L. A., and Lynch, D. W. Infrared absorption of Mg_2Ge, (8) 254*a*.
Lott, S. K. See Kilpatrick, M.; Spangler, C. W.
Lotto, B. Electrochemical behavior of sodium silicates at high temperature, (1) 6*a*.
Loudon, R. See Allen, S. J., Jr.; Birman, J. L.
Loughridge, F. A. See Harris, J. M.
Louis, J. F. Method of improving the performance of electrodes in magnetohydrodynamic devices, P (2) 51*a*.
Loukes, D. G. Method and apparatus for inhibiting the flow of impurities of a molten bath to the glass sheet thereon, P (11) 336*d*.
Loukes, D. G., and Banner, J. G. Manufacture of flat glass, P (2) 41*d*.
Loukes, D. G., and Robinson, A. S. Method of protecting the surface of the molten bath in a glass sheet float operation, P (3) 66*b*.
Lounsbury, R. W., and Melhorn, W. N. Clay mineralogy of Paleozoic K bentonites of the eastern United States (I) B, (6) 192*g*.
Loup, J. P. See Anthony, A. M.
Loutte, J. Apparatus for the manufacture of sheet glass on a molten bath, P (3) 64*j*.
Love, N. D. See Forstat, H.
Loveiace, B. K. See Waters, W. P.
Loveland, E. F. See Myatt, E. R.
Lovicz, V. See Knowles, A. R.
Lovy, P. See Salvadori, A.
Low, M. J. D., and Kamel, A. M. Thermal decomposition of cadmium hydroxide, (11) 357*e*.
Low, M. J. D., Ramasubramanian, N., and Ramamurthy, P. Contamination of silicas during high-temperature degassing in Vycor tubes, (3) 79*b*.
Low, P. F. See Leonard, R. A.
Lowdermilk, M. J., Herbaleb, F. A., and Arrison, F. C. Molten material sampling apparatus and method, P (5) 130*a*.
Lowe, E. C. Furnace for making silicon carbide crystals, P (1) 24*h*.
Lowe, I. J. See Abkowitz, M.
Lowe, R. S. Ceramic analysis by X-ray fluorescence (II) fully automatic instrument, B (7) 224*h*.
Lowen, J. Method and reagent for surface polishing, P (8) 245*g*.
Lowery, C. J., and Williams, B. B. Method for fabricating electrically isolated semiconductor devices in integrated circuits, P (6) 178*a*.
Loyet, D. L. Method of constructing radome, P (8) 245*d*.
Lozano, R., Ham, C. S., Marshall, C. C., and Joyce, J. E. Treatment of ferrous metal, P (8) 230*b*.
LTV Electrosystems, Inc. Molded resistor and method of fabricating, P (3) 73*h*.
Lublin, P., and Sama, L. Analysis of modified silicide coatings for oxidation protection of columbium and tantalum, (1) 3*g*.
Lucas, D. H. Granular flow stimulating devices, P (5) 144*a*.
Lucas, H. G. See Rosenecker, C. N.
Lucas, Joseph, (Industries), Ltd. See Joseph Lucas (Industries), Ltd.
Lucas, R. See Borrasse, A.
Lucasson, P. See Budin, C.
Luce, R. L. Method of fabricating planar semiconductor devices, P (2) 51*h*.
Lucek, J. R. See Douillard, P. A.
Luck, C. F., Jr., Missio, D. V., and Rupprecht, G. Laser crystal with prismatic end surface, P (8) 244*i*.
Ludwig, H. C. Plasma jet in chemical processing, (8) 249*h*.
Ludwig, U. Influence of various sulfates on setting and hardening of cements, (10) 294*j*.
Ludwig, U., and Schwiete, H. E. Effect of open porosity on the resistance of mortars and concretes to aggressive solutions, (8) 228*i*.
Ludwig Riedhammer G.m.b.H. Electric furnace for ceramics, P (3) 77*a*.
Lueck, A. M. Method for forming a lens on a metal ring, P (1) 9*a*.
Luecke, G. Surface-oriented semiconductor diode, P (6) 178*h*.
Luehrs, F. U., Jr. See Anderson, G. W.
Luescher, J. Transistor-capacitor integrated circuit structure, P (8) 246*g*.
Luessem, H. See Meinecke, G.
Lugg, R. R. See Isacks, A. J.
Luginina, I. G., and Barbanyagre, V. D. Electron microscope study of CaO structure, (1) 28*i*.
Luginina, I. G., and Vydrik, G. A. Use of complex thermography to study the burning process of the raw mix, (2) 37*f*.
Lukacs, J., and Simmler, F. Crystallization of high-alumina fused-cast products (I), (7) 201*a*.
Lukashenko, G. M. See Eremenko, V. N.
Luke, C. L. See Trumbore, F. A.
Lukesh, J. S. Discussion of "Stability, lattice parameters, and thermal expansion of β-cristobalite," (6) 185*f*.
Lummus Co. Regenerative mass, P (7) 205*d*.
Lumsden, D. N. See Heath, C. P.
Lundmark, W. N. Device for recovering feebly magnetic material in wet separators, P (1) 25*b*.
Lundstrom, T. See Aronsson, B.
Lungu, S. N. Study of the liquidus curves and thermodynamic properties of the systems SiO_2-ThO_2 and SiO_2-ThO_2-UO_2, (4) 117*b*.
Lunsford, J. H. Polycrystalline EPR spectrum of Fe^{3+} ions in MgO, (3) 85*b*.
Lunsford, J. H., and Jayne, J. P. Electron paramagnetic resonance of oxygen on ZnO and ultraviolet-irradiated MgO, (7) 217*g*.
Lupis, C. H. P. See Bernard, G.
Lush, J. See Youkers, H. A.
Lushnikov, V. G., and Khadzhi, V. E. Electrolysis of synthetic quartz with a nonstructural impurity, (1) 28*f*.
Luth, W. C. Studies in the system $KAlSiO_4$-Mg_2SiO_4-SiO_2-H_2O (I) inferred phase relations and petrologic applications, (4) 116*h*. See Peters, T.
Luth, W. C., and Tuttle, O. F. Alkali feldspar solvus in the system Na_2O-K_2O-Al_2O_3-SiO_2-H_2O, (5) 149*h*.
Luthi, O. Rotary drum filter, P (4) 102*b*.
Lutz, C. W. See Fuchs, R. J.
Lutze, E. Ceramics of Dorothee Colberg-Tjadens, (1) 1*j*.
Lux, B. See Stecher, P.
Luxmoore, A. R., and Turner, G. I. Determination of discontinuous surface displacements by the moire effect, (8) 248*a*.
Luyckx, A. See Michenaud, J. P.
Luzhnaya, N. P. See Koppel, Kh. D.
Luzhnaya, N. P., Medvedeva, Z. S., and Koppel, Kh. D. Reaction of indium arsenide and cadmium iodide, (10) 324*g*.
L'vova, A. S., and Feodos'ev, N. N. Enthalpy of formation of lithium metahafnate, (10) 321*a*.
Lyakhovets, K. A. See Kaminskaya, E. I.
Lyakhovitskaya, V. A. See Fridkin, V. M.
Lyall, K. D., and Paterson, M. S. Plastic deformation of galena (lead sulfide), (10) 324*j*.
Lyall, R. See Ashbee, K. H. G.
Lyczko, F. J. High temperature generating high intensity burners, P (3) 77*b*.
Lye, R. G. See Westwood, A. R. C.
Lyklema, J. See Van Den Hul, H. J.
Lyle, A. K. Apparatus for applying coatings to articles of glassware, P (3) 64*i*. Design and development of glasses for manufacture of containers—a laboratory procedure, (2) 38*h*. Glass-melting furnace, P (4) 94*b*.
Lyle, A. K., and Kulig, C. W. Optical inspection apparatus for surface coatings on glassware wherein the articles are inspected in a liquid having the same index of refraction as the glass, P (11) 336*d*.
Lynch, C. T. See Krochmal, J. J.; Mazdiyasni, K. S.; Vahldiek, F. W.
Lynch, D. W. Plasma excitations in LiF, (11) 355*c*. See Lott, L. A.
Lynch, J. F., Ruderer, C. G., and Duckworth, W. H. (compilors and editors). Engineering Properties of Selected Ceramic Materials, B (3) 89*j*.
Lynch, R. W., and Drickamer, H. G. Effect of high pressure on the lattice parameters of diamond, graphite, and hexagonal boron nitride, (7) 217*b*.
Lynn, W. C., and Whittig, L. D. Alteration and formation of clay minerals during cat clay [acid sulfate soil] development, B (8) 259*e*.
Lyon, K. C., Pickard, J. E., and Scholes, A. B. Glass having dual protective coatings and method for forming such coatings, P (2) 40*j*.
Lyon, W. L., and Baily, W. E. Solid-liquid phase diagram for the UO_2-PuO_2 system, (10) 325*j*.
Lyons, D. H., and Kedzie, R. W. Paramagnetic-resonance determination of a nuclear quadrupole interaction by means of forbidden hyperfine transitions—$Ca\text{-}WO_4{:}Mn^{2+}$, (10) 324*g*.
Lyons, G. A. See Christie, G. E.
Lyons, S. C., and Brown, D. C. Aluminosilicate pigment, P (10) 317*g*. Production of low viscosity kaolins by controlled blending of high viscosity kaolins, P (10) 318*d*.
Lyons, V. J. See Silvestri, V. J.
Lysak, S. V. See Yutina, A. S.
Lytle, F. W. Determination of metal atom positions in $CrVO_4$ by X-ray absorption spectroscopy, (6) 185*d*.
Lyubina, T. M. See Nosova, Z. A.
Lyudvinskaya, T. A. See Dobrovol'skii, A. G.

Maas, B. J. M. See Loosjes, R.
Maatschappij voor Electrische Bedrijfsautomatisering Electrofact N.V. Glass electrode, P (5) 120*j*.
Maaz, K. See Boehm, P.
Mabey, D. H. Diamond saw or milling blades, P (6) 163*j*.
McAdam, G. D. Effect of carbide and boride additions on the creep strength of niobium alloys, (11) 352*a*.
McAleer, W. J., and Pollak, P. I. Method of making a semiconductor crystal body, P (5) 142*a*.
McAllister, W. A. Luminescence in Mg_2SiO_4:Tb,Li phosphors, (7) 207*d*. See Mercer, E. E.
MacAvoy, T. C. Method of making cellular phosphate glass, P (1) 9*d*.
McBride, J. P., and Pattison, W. L. Urania sol forming method in the presence of formic acid and a palladium-on-thoria catalyst, P (4) 97*j*.
McCaleb, S. B. X-ray diffraction automation and its use in clay mineralogy, B (7) 224*e*. See Bennett, J. D.; Bush, D. C.
McCarley, R. E. See Kuhn, P. J.
McCarley, R. E., and Boatman, J. C. Equilibrium phase diagrams for the tantalum-tantalum bromide and tantalum-tantalum iodide systems, (4) 110*b*.
McCarthy, D. E. See Kahan, A.
McCarthy, D. N. Coating process, P (6) 170*g*. Color ornamentation of glass articles, P (1) 8*g*.

McCarthy, G. J., White, W. B., and Roy, R. Preparation of $Sm_4(SiO_4)_3$, (5) 157*d*.
McCarthy, G. P. R. See Calow, C. A.
McCarthy, J. W., and Stern, S. V. Water hydrolysis reactor for making alumina, P (8) 252*a*.
McCartney, E. R. See Baggaley, B. J.; Brungs, M. P.
MacChesney, J. B. See Gallagher, P. K.
MacChesney, J. B., Potter, J. F., and Guggenheim, H. J. Vanadium dioxide coatings applied to alumina substrates, (4) 99*a*.
MacChesney, J. B., Potter, J. F., Sherwood, R. C., and Williams, H. J. Oxygen stoichiometry in the barium ferrates—its effect on magnetization and resistivity, (5) 139*e*.
MacChesney, J. B., Sherwood, R. C., and Potter, J. F. Electric and magnetic properties of the strontium ferrates, (5) 138*a*.
MacChesney, J. B., Williams, H. J., Sherwood, R. C., and Potter, J. F. Magnetic susceptibility of praseodymium oxides, (6) 187*d*. Preparation and low-temperature magnetic properties of the terbium oxides, (5) 139*i*.
McClaine, L. A., and Coppel, C. P. Electrical conductivity studies of tetragonal zirconia, (10) 320*i*.
McClung, R. W. Factors in radiography at energies below 400 kvp, (7) 212*g*.
McClure, D. S. Comparison of the crystal fields and optical spectra of Cr_2O_3 and ruby, (5) 150*e*. See Russel, P. G.
McClure, E. R. See Johnson, P. M.
McClurg, G. O. See Hendron, J. A.
McCombie, R. L. Laminated safety glass, P (9) 265*h*.
McCombs, F. P. See Smucker, C. A.
McConnell, D. Calculation of the unit-cell volume of a complex mineral structure, (6) 184*c*.
McConnell, J. D. C. See Smith, D. G. W.
McCown, W. E. See Walters, E. L.
McCown, W. E., and Warren, R. E. Internally cooled hot glass contacting roll, P (8) 235*c*.
McCrary, J. W., Jr., Post, R. C., III, and Aylwin, J. J. Silicon carbide coating on graphite bores of heat exchanger, P (10) 305*a*.
McCreight, D. O., Miller, E. D., Jr., and Pavlica, S. R. High alumina brick, P (7) 204*f*.
McCrone, W. C., Draftz, R. G., and Delly, J. G. Particle Atlas, B (4) 121*c*.
McCully, J. B. See Thome, W. L.
McCurdy, W. H., Jr. Volumetric and gravimetric analytical methods for inorganic compounds, (8) 249*a*.
McCurrie, R. A., and Douglas, R. W. Diffusion-controlled growth of second phase particles in a lithium-silicate glass, (1) 5*c*.
McDaniel, C. L. See Schneider, S. J.
McDaniel, C. L., and Schneider, S. J. Phase relations between palladium oxide and the rare earth sesquioxides in air, (6) 187*e*.
McDaniel, C. V. See Maher, P. K.
McDaniel, C. V., and Maher, P. K. Method of cation exchanging synthetic faujasite, P (7) 214*e*. Process for ion exchanging crystalline zeolites [faujasite] with nitrogenous bases, P (6) 183*e*.
McDaniel, C. V., Maher, P. K., and Waxter, W. E. Process for preparing a crystalline zeolite, P (6) 183*f*.
McDermott, P. S., Manley, G. W., Riley, R. J., and Yetter, L. R. Method of vapor growing a homogeneous monocrystal, P (10) 310*j*.
McDivitt, D. T. Method of measuring the coating thickness on [glass] articles, P (11) 336*k*.
Macdonald, A. M. G., and Toth, K. Development of fluoride-sensitive membrane electrodes (I) membranes containing thorium, lanthanum, or calcium fluoride, (8) 243*b*.
Macdonald, A. M. G., and Van der Voort, F. H. Separation of silicon and phosphorus with ammonium molybdate and their successive determination, (9) 286*a*.
McDonald, C. W., and Bedenbaugh, J. H. Spectrophotometric determination of iron using ethyl 4,6-dihydroxy-5-nitrosonicotinate, (5) 146*b*.
Macdonald, H. F. See Hayes, W.
McDonald, J. A. Evolution of part of the lower Critical Zone, Farm Ruighoek, Western Bushveld, (3) 81*b*.
McDonald, J. D. See Kent, R. A.
MacDonald, R. C. See Webster, A. H.
MacDonald, R. D. Sweeping of bubbles by grain boundaries in irradiated UC, (10) 325*g*.
McDonald, R. D. Thermodynamic study of the Mn-O-CO_2 system, (11) 357*f*. See Quon, H. H.
McDonald, R. D., and Sadler, A. G. Metallographic study of manganese zinc ferrite, (9) 272*d*.
MacDonald, R. J., and Ward, J. F. Method for producing a multilayer bearing, P (5) 126*a*.
McDonald, R. S. See Vedder, W.
McDonald, W. S., and Cruickshank, D. W. J. Reinvestigation of the structure of sodium metasilicate, Na_2SiO_3, (1) 31*h*.
McDonnell Aircraft Corp. Optical fiber electroluminescent-photoconductive image intensifier, P (5) 142*j*.
McDonnell Douglas Corp. Apparatus and method for evaporative coating, P (4) 92*j*. Apparatus for producing a laminated glass panel, P (5) 129*c*. Battery containing a sintered aluminosilicate separator, P (7) 204*g*. Fiber optic readout device and method for making it, P (7) 208*g*. Inorganic permselective membranes, P (10) 309*j*. Method for making cathode-ray tube filters, P (4) 95*b*. Method of making cathode-ray tube with integral light trapping filter, P (4) 95*c*. Process for encapsulating materials with a thermoplastic cover, P (2) 42*e*.
MacDowell, J. F. See Duke, D. A.
McDowell-Wellman Engineering Co. Lightweight aggregate from fly ash pellets, P (6) 172*b*.
McDuffie, H. F. Separation of trivalent 4*f* rare earths from molten fluoride compositions with UF_3, P (7) 205*e*.
Macedo, P. B. See Capps, W.; Tauke, J.
Macedo, P. B., Capps, W., and Litovitz, T. A. Two-state model for the free volume of vitreous B_2O_3, (4) 93*j*.
McElearney, J. See Forstat, H.
McElroy, D. E. Method of making an electrical resistor, P (4) 100*c*.
McEuen, R. B. Dielectrophoretic behavior of clay minerals (I) dielectrophoretic separation of clay mixtures, B (6) 192*f*.
McEvoy, J. E. See Cornelius, E. B.
McEvoy, J. E., and Mills, G. A. Clay-supported cracking catalyst, P (8) 250*h*.
McEvoy, J. E., and Shalit, H. Copper chromite-alkali metal oxide high surface area hydrogenation catalyst, P (6) 183*a*.
MacEwan, J. R., and Stoute, R. L. Effect of irradiation on the thermal conductivity of UO_{2-x}, UO_2, and UO_{2+x} at 60°C, (9) 281*h*.
McEwan, M. J., and Phillips, L. F. Dissociation energy of NaO_2, (3) 80*d*.
Macey, J. G. Process for the recovery of lithium and potassium from Great Salt Lake brine, P (1) 25*j*.
McFadden, C. A. High velocity jet firing, (11) 348*e*.
Macfarlane, R. M. Ground-state splitting in ruby, (3) 81*h*.
MacFarlane, W. T. See Cuthbert, J. D.
McFee, J. H. Optical second-harmonic generation produced by interaction of laser beams and drifting carriers in InAs, (11) 355*d*.
McGarry, F. J. See Carrara, A. S.
McGary, T. E. See Smith, J. J.
McGeary, R. K. Mechanical packing of spherical particles, B (3) 90*b*.
McGinnis, P. H., Jr. Spectrophotometric color matching with the least squares technique, (6) 189*b*.
McGlothlin, Q. T. High temperature protective coating, P (3) 63*c*.
McGonnagle, W., and Park, F. Nondestructive testing, (7) 212*g*.
McGrain, P. See Keller, W. D.
McGrath, E. Pneumatic outlet for unloading particulate materials, P (2) 53*f*.
McGraw-Edison Co. Automatic glazing and sanding machine, P (8) 242*d*.
McGuire, I. H. Light diffusion material and method of making and using it, P (2) 56*g*.
McGuire, L. J. See Rockowitz, M.
McGuire, T. R. See Holtzberg, F.; Shafer, M. W.
McGuire, T. R., and Shafer, M. W. Ferromagnetic materials, P (6) 177*i*.
Mach, O. Study of kinetics of volume relaxation of vitreous boron oxide (I) introduction and preparation of vitreous boron oxide, (11) 357*h*.
Machalica, A. See Bialek, F.
McHenry, E. R., and Piper, E. L. High-strength carbon foam, P (9) 270*b*.
Machin, W. D., Montgomery, D. S., and Parsons, B. I. Process for the preparation of metal oxides having an enlarged pore volume, P (2) 47*j*.
Machin, W. D., and Tompkins, F. C. Kinetics of the reaction of water vapor with crystalline lithium hydride, (3) 82*h*.
McHugh, C. O. See Humenik, M., Jr.; Whalen, T. J.
McIlvaine, R. L. Apparatus for conditioning particulate material, P (2) 53*g*.
McIntyre, G. M. See Saia, F. J.
MacIver, B. A. See McKinnon, M. C.
Mack, J. E., McNutt, D. P., and Roesler, F. L. Interferometric spectrometer utilizing three Fabry-Perot etalons in series, P (6) 181*e*.
McKeand, I. J. See Stapleton, E. W.
McKee, R. L. Candid look at the abrasive industry, (9) 261*f*. Elusive art of lapping (I), (1) 1*f*; (II) flat lapping, (3) 61*e*. 1TT Abrasives—case study of the "new look," (5) 123*h*.
McKelvey, J. G. See Milne, I. H.
McKenna, B. D. Refractory construction, P (11) 341*a*.
McKenna, P. M. Process for preparing tungsten monocarbide, P (7) 205*i*.
McKenzie, D. E., and Howe, J. P. Conversion of heat to electricity by electrochemical means using UO_3 melt, P (5) 134*h*.
Mackenzie, F. T., Garrels, R. M., Bricker, O. P., and Bickley, F. Silica in seawater—control by silica minerals, (4) 115*f*.
Mackenzie, J. D. Method for making thin film glass elements, P (7) 209*i*. Photoconductivity and phototropy in noncrystalline solids, B (10) 328*i*. See Allersma, T.; Kennedy, T. N.
McKenzie, L. G. See Chaklader, A. C. D.
Mackenzie, R. C. *De natura luiorum*, B (5) 160*j*.
Mackey, J. H., Jr. EPR study of impurity-related color centers in germanium-doped quartz, (5) 152*g*.
Mackey, J. H., and Nahum, J. Spectral study of the interconversion of Eu^{3+} and Eu^{2+} in silicate glasses, (8) 234*c*.
McKibben, C. K. See Treharne, R. W.
Mackin, M. See Companion, A. L.
McKinley, R. See Blum, S.
McKinnon, M. C., and MacIver, B. A. Vacuum-deposited germanium films on polycrystalline Al_2O_3 substrates, (5) 140*j*.
Mackintosh, I. M. Method of making *pn* junction devices by diffusion, P (10) 310*s*.
Macklen, E. D. Influence of atmosphere on the thermal decomposition of ferrous oxalate dihydrate, (5) 153*b*.
MacLachlan, D. F. A., Planer, G., and Arnold, R. Resistance temperatures of Cr-Si-O cermets, (2) 50*f*.
McLachlan, E. K. See Pullen, F. R.
McLaggan, J. R. See Barradell-Smith, R.
McLain, W. R. Basic refractory furnace structure, P (11) 339*i*.
McLaren, M. G. Plan for continuing education in ceramic engineering, (1) 34*c*. Raw materials for whitewares, B (3) 89*d*.
McLaughlan, S. D., Forrester, P. A., and Fray, A. F. Orthorhombic electron-spin-resonance spectra of Yb^{3+} ions in CaF_2, (11) 355*e*.
McLay, J. F. Joint construction for glass pipe and the like, P (6) 170*i*.
McLean, J. W. Alumina tube post crown, (9) 270*k*. High-alumina ceramics for bridge pontic construction, (9) 270*j*.
Macleod, A. C. High-temperature adiabatic drop calorimeter and the enthalpy of α-alumina, (7) 218*b*.
McLeran, W. A., Jr. Composite method for determination of particle size below 45 microns, (10) 296*d*.
McLintock, C. H., and Stringer, J. Volumetric apparatus for studying solid-gas reactions, (3) 76*b*.
McMackin, J. J. Means for automatically weighing glass containers, P (10) 300*f*.
McMahon, W. R., and Wilder, D. R. Hemispherical spectral emittance of selected rare earth oxides, (5) 153*i*.
McManus, J. J. Ceramic housing for semiconductor components, P (9) 272*a*.
McMaster, H. A. Blasthead structure for tempering glass sheets, P (3) 65*c*.
McMaster, H. A., and Reising, P. J. Method and apparatus for curving glass sheets on a gas support bed, P (7) 199*a*.
McMaster, R. C., and Dettloff, B. B. Sonic transducer, P (5) 143*b*.
McMeekin, J. H. Finish inspection apparatus for glass containers, P (10) 300*h*. See Paruolo, M. J.
McMillan, J. A. Kinetics of glass transformation by thermal analysis (I) glycerol, (5) 127*i*.
McMillan, P. W. Glass-ceramics in chemical engineering, (10) 297*f*.
McMillan, P. W., and Hodgson, B. P. Glass-ceramics, P (7) 198*c*.
McMillan, P. W., and Lawton, D. C. Method of making glass-ceramic and product, P (2) 41*f*.
McMillan, P. W., and Partridge, G. Method of making glass-ceramics by devitrification in a single stage, P (2) 41*h*.
MacMillan, R. A. Single thermocouple differentiating method and system, P (4) 103*h*.
McMullen, J. C. Process and apparatus for effecting solid-state reactions, P (7) 205*d*.
McMurdie, H. F. See Swanson, H. E.
McNally, J. P. See Palmer, W. B.
McNally, R. N. See Alper, A. M.
McNally, R. N., Yeh, H. C., and Balasubramanian, N. Surface tension measurements of refractory liquids using the modified drop weight method, (8) 248*i*.
McNamara, P. See Barry, T. I.
McNamara, V. M. Wet chemical method for the preparation of oxide mixtures applicable to electronic ceramics, (9) 272*h*. See Webster, A. H.
McNeese, L. E. See Richardson, E. W.
McNeil, F. S. See Jester, H. C.
McNutt, D. P. See Mack, J. E.
McPherson, R. Apparatus for dynamic measurement of the elastic modulus of ceramics at elevated temperatures, (10) 313*d*. Intercrystalline thermal stresses in polycrystalline rutile, (5) 153*j*.
McQueen, R. G., Jamieson, J. C., and Marsh, S. P. Shock-wave compression and X-ray studies of titanium dioxide, (4) 115*c*.
McQuitty, J. B., and Martin, A. W. Deep submergence hydrophone, P (5) 140*j*.
McRae, R. C. See Reed, L.
McRae, R. C., and Reed, L. Low dielectric loss metallizing paint composition having a reduced sintering temperature, P (2) 51*f*.
McRae, R. C., Reed, L., Toth, J., and Lindberg, R. Compatibility of alumina and beryllia ceramics with potassium vapor (6) 166*c*.
McRae, W. A. See O'Connor, T. L.
McTaggart, G. D., and Norman, E. K. Immersion-type thermocouple having a sheath of sintered ceramic refractory, P (7) 204*i*.
Macur, G. J. See Raziunas, V.
McVay, T. L. See Hollenbeck, R. P.; Rampacek, C.
McVittie, D. F. Gunned maintenance of iron and steel furnaces, (2) 44*b*.
McWhan, D. B., Compton, V. B., Silverman, M. S., and Soulen, J. R. Crystal structure and superconductivity of a high pressure phase of $CaSi_2$, (8) 252*c*.
McWhan, D. B., and Marezio, M. Structure and superconductivity of the high-pressure phases of InSb, (10) 325*d*.
McWhan, D. B., Souers, P. C., and Jura, G. Magnetic and structural properties of europium metal and EuO at high pressure, (9) 284*i*.
McWhorter, A. L. See Oliver, M. R.
Macy, P. R. See Sanderfur, N. L.
MacZura, G. See Pearson, A.
MacZura, G., and Gitzen, W. H. Production of fused alumina, P (11) 340*j*.
Madar, R. See Fruchart, R.

Madavan, T. R., Viswanathan, K. V., and Majumdar, K. K. Beneficiation of lepidolite ores, (1) 19*f*.
Maddix, H. S. See Chow, K. K.
Maddox, R. E., Hengstler, R. E., and Besner, S. G. Method and apparatus for producing fibrous material, P (7) 161*c*.
Madhavan, R. R., Karve, V. M., and Somnay, J. Y. Selective flotation of beach sands—sillimanite, zircon, and rutile, (1) 25*f*.
Madison, R. P. See Bieler, B. H.
Maeda, M. See Okubo, T.
Maeda, S., Ito, K., Nishida, T., and Tamura, T. Novel catalyst composition, P (6) 183*c*.
Maeda, T. See Kawamura, S.
Maekawa, K. See Nishigaki, S.
Maekawa, S. Corrosion of refractory brick by steelmaking slags—slag quantity for crucible corrosion test, (10) 302*f*.
Maekawa, S., and Kinoshita, N. Electron spin resonance in phosphorus doped silicon at low temperatures, (3) 80*f*.
Maerker, R. Classification of dry process enamels for cast iron bathtubs by a drip test, (5) 125*i*.
Magee, J. S., and Briggs, W. S. Process for producing alumina having a narrow pore size distribution, P (4) 105*d*.
Mager, E. L. See Sentementes, T. J.
Magid, H. S. See Mohr, W. C.
Magidovich, V. I., and Sivokon, V. I. New source of feldspathic kaolin raw material in the Ukraine, (8) 250*h*.
Magison, E. C. Why's of radiation pyrometry, (3) 76*c*.
Magnesita S. A. Adjustable keystone assembly of molded refractory material for arches, walls, etc., P (11) 339*g*.
Magnier, P., Marchal, M., Trouve, J., and Accary, A. Casting and extrusion of refractories, (6) 172*i*.
Magnusson, C. B. O. See Schrewelius, N. G.
Magruder, G. M. Extrusion die for drain tile cluster, P (8) 236*e*.
Mague, J. T. See Cotton, F. A.
Magyar, G. See Bradley, D. J.
Magyar Optikai Muvek. Heater controller for isothermic thermogravimetric analysis, P (1) 23*i*.
Mah, A. D., Pankratz, L. B., Weller, W. W., and King, E. G. Thermodynamic data for cuprous and cupric oxides (4) 118*f*.
Mahadevan, Y. See Narayanan, V. H.
Mahajan, S. P., and Narasimhamurthy, G. S. R. Studies in size reduction—size distribution shift in dry grinding, (5) 148*h*.
Mahan, G. D., and Conley, J. W. Density of states in metal-semiconductor tunneling, (2) 49*f*.
Mahan, J. E., Turk, S. D., and Williams, R. P. Catalyst containing iron oxide, chromium oxide, and a potassium compound, P (8) 250*g*.
Maher, P. K. Process for the preparation of a crystalline zeolite, P (10) 318*b*. See McDaniel, C. V.
Maher, P. K., and McDaniel, C. V. Process for increasing the thermal stability of synthetic faujasite, P (6) 183*d*.
Mahut, R. See Huet, H.
Mai, Chan Ngok. See Chan Ngok Mai.
Maier, Ya., Butt, Yu. M., and Boretski, E. Effect of hydrochloric acid treatment on hydration of basic ashes, (6) 164*b*.
Mailhiot, R. E. See Kruger, O. L.
Maiman, T. H., Hoskins, R. H., Soffer, B. H., Pastor, R. C., and Pearson, M. A. Green luminescing phosphor for color television and method of making, P (11) 343*f*.
Maines, J. D., and Paige, E. G. S. Spatial variation of electric field strength in "amplifying" CdS, (11) 356*f*.
Mairlot, H., and Gilard, P. Setting up a gas chromatograph for the analysis of bubbles in glass, (3) 64*d*.
Maissel, L. I. Deposition of thin films by cathode sputtering, B (8) 260*e*. See Davidse, P. D.; Glang, R.; Jones, R. E.
Maita, J. P. See Kunzler, J. E.; Matthias, B. T.
Majauskas, J. See Abraitis, R.; Grebenyuk, A. A.
Majdic, A. See Schenck, H.
Majourel, P. Behavior of refractories in contact with natural gas flames, (7) 200*g*.
Majumdar, A. J. High temperature studies on individual constituents of high alumina cements, (9) 262*b*. See Chatterji, S.; Rehsi, S. S.
Majumdar, A. J., and Chatterji, S. Studies of the early stages of paste hydration of high alumina cements (II) hydration of iron and silica components, (1) 3*b*.
Majumdar, A. J., and Roy, R. Comparison of the relative merits of thermochemical measurements and calculations as opposed to direct experimental determination of solid-vapor equilibria, (8) 252*h*.
Majumdar, A. K., and Saha, S. C. 1-(*o*-carboxyphenyl)-3-hydroxy-3-phenyltriazene, a new reagent for the direct gravimetric determination of titanium(IV), (5) 145*g*.
Majumdar, K. K. See Madavan, T. R.; Vijayakar, S. V.
Makarov, E. S. See Kirkinskii, V. A.
Makarov, E. S., Smirnov, A. F., and Sokolov, E. B. System Mg_2Si-Mg_2Pb, (10) 326*a*.
Makarov, G. N. See Karshenbaum, A. G.
Makarov, L. P. See Boganov, A. G.
Maki, T., and Tashiro, M. Studies on thermal shock resistant ceramics of the Li_2O-Al_2O_3-SiO_2 system (V) glazes for lithia ceramics, (8) 242*a*.
Makiguchi, T. Results of study on the dissolution of Cr in iron due to corrosion of QC refractories with added Cr_2O_3, (9) 269*c*.
Makishima, S., Yamamoto, H., Tomotsu, T., and Shionoya, S. Luminescence spectra of Sm^{3+} in $BaTiO_3$ host lattice, (3) 83*c*.
Makita, Y. Phase transition in $C_5H_5(SeO_3)_2$, (3) 85*b*.
Maklad, M. See Bishay, A.
Makram, H., Anthony, A. M., and Loc, V. Preparation of high melting single crystals by the flux method, (1) 31*i*.
Maksoud, M. A. See Gad, G.
Malbon, R. M., Walsh, D. J., and Winslow, D. K. Zinc-oxide film microwave acoustic transducers, (3) 88*h*.
Malcheva, N. See Erinui, H.
Malhotra, V. M. Alpine Air Jet sieve—a new method for determining the fineness of cement, (3) 62*b*.
Malicheff, A. See Brichard, E.
Malinovsky, M., and Vrbenska, J. Phase diagram of the system Li_3AlF_6-CaF_2, (7) 220*i*.
Malinowski, R., and Hedberg, B. Effect of pressure on strength of heat-cured high-strength concrete, (8) 228*j*.
Mallard, W. C. See Mathews, J. W.
Mallikarjunan, R. See Halasyamani, P.; Venkatachalam, S.
Mallikarjunan, R., Pai, K. M., and Halasyamani, P. Effect of some surface active reagents on the comminution of quartz and calcite, (1) 21*g*.
Mallory, J. D., and Ryan, L. D. Apparatus for joining glass parts, P (5) 129*b*.
Mallory, P. R., & Co., Inc. Anodic bonding, P (11) 343*e*. Coated ceramic capacitor, P (2) 50*i*. Diffused resistor for an integrated circuit, P (9) 272*f*. Tungsten powder bodies infiltrated with copper-titanium alloys, P (3) 74*e*. Tungsten-indium powder bodies infiltrated with copper, P (3) 74*d*.
Malluschke, A., and Mottke, P. Brickmaking in Iran, (10) 301*e*.
Malm, J. G. See Selig, H.
Malmberg, M. Multiple-chamber rotary kiln, P (4) 104*d*.
Maltner, Heinrich, G.m.b.H. See Heinrich Maltner, G.m.b.H.
Maltner, W., and Dieterle, H. Piezoelectric spark igniter, P (11) 345*a*.
Mal'tsev, V. T. See Bukhalova, G. A.
Mal'tseva, L. F., Lapshov, Yu. K., Marmer, E. N., and Samsonov, G. V. High-temperature heaters of niobium and zirconium carbides, (5) 132*e*.
Maly, Z. See Carniol, B.
Malyukov, B. A., Ukrainskii, Yu. M., and Korolev, V. E. X-ray spectral determination of chlorine in silica films, (10) 327*e*.
Manabe, Y. Alkali resistance of glass enamels (II) attack on low temperature glasses containing ZrO_2 by alkali solution, (1) 3*h*.
Manaila, R. See Grigorovici, R.
Manasevit, H. M., and Simpson, W. I. Epitaxial deposition of silicon on α-alumina, P (10) 309*d*.
Manchester, K. E. Method of making a semiconductor by ionic bombardment, P (9) 274*c*.
Mandel, G., and Morehead, F. F. Method of forming a semiconductor by double diffusion, P (3) 73*j*.
Mandelkorn, J. Semiconductor material and method of making, P (9) 275*a*.
Manders, G. J. Method of forming glass bonded [transducer] heads, P (5) 141*h*.
Manderscloot, W. G. B. See Pretorius, S. T.
Manenc, J. See Charpentier, P.
Manganese Chemicals Corp. Reducing to MnO the MnO_2 of a manganese ore, P (7) 215*d*.
Mankin, C. J. See Bellis, W. H.; Kerns, R. L., Jr.
Mankoff, L. L., and Nakata, R. Electric circuit breaker comprising ceramic capacitor elements connected in parallel with its contacts, P (8) 244*a*.
Manley, A. J. Thinning of sintered uranium dioxide to electron transparency by chemical polishing, (5) 134*i*.
Manley, B. W. See Schagen, P.
Manley, G. W. See McDermott, P. S.
Manly, W. D. Utilization of BeO in reactors, (2) 46*c*.
Mann, D. E. See Linevsky, M. J.
Manning, B. See Kivel, J.
Manning, C. R., Jr., and Stoops, R. F. High-temperature cermets (I) compatibility; (II) wetting and fabrication, (9) 267*c*.
Manning, C. S. Fiber optic cathode-ray tube assembly, P (4) 100*a*.
Manning, D. C. See Capacho-Delgado, L.
Manning, P. G. Absorption spectra of the manganese-bearing chain silicates pyroxmangite, rhodonite, bustamite, and serandite, (9) 279*g*. Cu(II) in octahedral sites in sphalerite, (1) 28*a*. Optical absorption spectra of the garnets almandine-pyrope, pyrope, and spessartine and some structural interpretations of mineralogical significance, (5) 156*d*. Optical absorption studies of the mixed-ion (Cu and Al) doping of sphalerite, (9) 285*a*. Study of the bonding properties of sulfur in bornite, (4) 117*a*.
Manning, W. R., and Hunter, O., Jr. Porosity dependence of Young's and shear moduli of polycrystalline yttrium oxide, (10) 324*b*.
Manogg, P. Light refraction in an elastically stressed plate and the shadow patterns of circular holes and linear cracks, (9) 283*i*.
Manojlovic, L. J. M., Herak, R. M., and Knezevic, G. M. Z. Study of the UO_3-V_2O_5 system, (6) 189*c*.
Manos, C. See Agathonikou-Rokofyllou, E.
Manring, W. H., Billings, D. D., Conroy, A. R., and Bauer, W. C. Reduced sulfur compounds as melting and refining aids for flint soda-lime glass, (2) 40*b*.
Mans, B. Design + designer—Albrecht Klauer-Simonis, (4) 91*h*.
Manser, R. M. See Joy, A. S.
Manske, W. J. Radiant white light source, P (5) 136*f*.
Mansur, L. C. See Marshall, R.; Plendl, J. N.
Marano, C. L. See Reiness, C. G.
Marchal, F. See Veaux, M.
Marchal, M. See Magnier, P.
Marcos, H. M. See Bonner, W. A.
Marcus, J. H. See Ormsby, W. C.
Marek, R. W. See Pearce, M. L.
Marel, H. W. van der. Quantitative analysis of clay minerals (abstract), B (8) 259*h*.
Mareschal, J. See Bertaut, E. F.
Maretheu, A. Mechanical strength at high temperatures (I), (3) 75*g*. See Lecrivain, L.
Maretheu, A., and Miny, J. C. Mechanical strength at high temperatures (II), (3) 75*g*.
Marezio, M. See McWhan, D. B.
Marezio, M., and Remeika, J. P. Bond lengths in α-Ga_2O_3 and the high-pressure phase of $Ga_{2-x}Fe_xO_3$, (11) 350*c*. High-pressure synthesis and crystal structure of α-$LiAlO_2$, (7) 218*a*. Polymorphism of $LiMO_2$ compounds and high-pressure single-crystal synthesis of $LiBO_2$, (7) 220*c*.
Marezio, M., Remeika, J. P., and Jayaraman, A. High-pressure decomposition of synthetic garnets, (10) 321*h*.
Margerum, D. W. See Stehl, R. H.
Margola, G. B. Modern plate production unit, (6) 175*h*. Process and equipment for the industrial manufacture of vitreous china flatware in a totally mechanized cycle, B (9) 291*a*. See Lampani, A.
Margolis, L. Ya. See Kontorovich, S. I.
Margoshes, M., and Scribner, B. F. Emission spectrometry, (10) 314*b*.
Margrave, J. L. (editor). Characterization of High-Temperature Vapors, B (3) 89*c*. See Bautista, R. G.; Chang, C. H.; Ficalora, P. J.; Kent, R. A.; Poland, D. E.; Thompson, J. C.
Marhanka, J. E. See Pearson, A.
Mariano, A. N., and Chopra, K. L. Polymorphism in some IV-VI compounds induced by high pressure and thin-film epitaxial growth, (5) 156*j*.
Mariette, R. See Huet, H.
Marin, G., and Rindone, G. E. Comparing internal friction of fiber glass with that of glass rods, (10) 297*e*.
Marin, G. R. Method of joining electrode bodies of dissimilar thermal coefficients of expansion, P (7) 205*c*.
Marinace, J. C. See Silvestri, V. J.
Marincek, B. Furnace for producing graphite electrodes, P (5) 147*e*.
Marinder, B. O. See Dorm, E.
Marinenko, J. See May, I.
Marinina, V. T. Method of determining the tension at the interface of glass-metal melts, (11) 334*j*.
Marinina, V. T., and Utolina, L. S. Study of wetting and sticking of glass to different refractories, (10) 299*c*.
Marinkovic, M. D., and Antic-Jovanovic, A. M. Spectrographic determination of beryllium in its minerals with a gas-stabilized arc, (2) 55*c*.
Marinozzi, P. See Ferlazzo, N.
Maris, H. J. Temperature and frequency dependence of the velocity of sound in dielectric crystals, (8) 257*c*.
Mark, E. See Nickel, E. H.
Mark, H. F. Nature of polymeric materials, B (11) 358*h*.
Mark, P. See Levine, J. D.
Markelova, M. Ya. See Boguslavskii, I. A.
Markham, A. E. See Felicetta, V. F.
Markiund, I., Karlsson, K., and Andersson, S. Apparatus for crystalline field studies by perturbed angular correlation, (5) 144*h*.
Markotai, T. See Toeroek, L.
Marle, C. Determination of the texture of and the flow in porous bodies, (10) 317*g*.
Marley Tile Co., Ltd. Tiles, P (1) 16*a*.
Marmer, E. N. See Mal'tseva, L. F.
Marotta, R. Process for preparing silica aquasols, P (6) 183*a*. Stable alkaline colloidal silica sols of low viscosity and processes for preparing, P (1) 26*a*.
Marotta, R., and Teicher, H. Chemical compositions and processes, P (5) 148*a*.
Marriott, J. G. Electrically heated transparent panel and protective circuit therefor, P (7) 198*c*.
Marrone, M. J. See Patten, F. W.
Marsden, J. D. Conveyor arrangements, P (6) 179*g*.
Marsden, J. G., and Sterman, S. Filled inorganic structural compositions having improved strength, P (8) 240*d*.
Marsh, S. P. See McQueen, R. G.
Marshall, C. C. See Lozano, R.
Marshall, C. W. See Duke, B. W.
Marshall, D. W., and Pett, E. A. Apparatus for making crystal abrasive, P (7) 193*f*.
Marshall, F. J. Metal/ceramic cathode ray tube, P (8) 245*a*.
Marshall, G. F. Parallel light fibers with longitudinal axes making oblique angle with display surface of cathode-ray tubes, P (4) 100*i*.

Marshall, J. G., Hildon, A. M., Oates, A. E., and Clennett, G. Process for the production of barium hydroxide, P (5) 149*b*.
Marshall, R., Mitra, S. S., Gielisse, P J., Plandl, J. N., and Mansur, L. C. Infrared lattice spectra of α-Al_2O_3 and Cr_2O_3, (6) 186*b*.
Marshall, W. W. See Crofts, J. D.
Marson, R. J. See Lingren, W. E.
Marta, Y. See Kawahara, H.
Martin, A. E., and Edwards, R. K. Uranium-uranium dioxide phase diagram at high temperatures, (11) 358*a*.
Martin, A. R. Heat control for kiln, P (2) 56*c*. Kilns, P (4) 104*d*.
Martin, A. W. See McQuitty, J. B.
Martin, B. D. See Rex, R. W.
Martin, C. C., Goodhue, D. T., and Rengel, D. M. Process for beneficiating diatomaceous earth ores, P (7) 215*b*.
Martin, D. D. See Belasco, M.
Martin, D. G. Study of small defect clusters in irradiated magnesium oxide using long wavelength neutron scattering measurement, (11) 357*j*.
Martin, D. H. See Bloor, D.
Martin, D. L., and Wilkins, D. H. Method of making superconducting wire, P (10) 310*c*.
Martin, E. E. See Charbonnier, F. M.
Martin, F. S. See Christie, G. E.; Steele, B. R.
Martin, F. W. See Dalton, R. H.
Martin, G., and Walker, L. Method for producing sintered nonmetallic magnetic materials, P (9) 274*h*.
Martin, G. D. Selection of porcelain enamel frits, (9) 263*c*.
Martin, G. F. See Parr, N. L.
Martin, J. Method of manufacture of rolls for glass drawing machinery, P (5) 130*h*.
Martin, J. F. See Counsell, J. F.
Martin, J. L. See Krause, H. B.
Martin, J. M., and Stephen, W. I. Nephelometric determination of small amounts of sulfate ion, (2) 54*e*.
Martin, J. S., Jr., and Trond, S. S. Process for preparing yttrium vanadate phosphors, P (4) 101*a*.
Martin, J. W. See Ball, F. E.; Humphreys, F. J.
Martin, Mrs. P. M. See Bradbury, B. T.
Martin, R. See Lecrivain, L.
Martin, R. T. Quantitative fabric of wet kaolinite, B (8) 259*g*.
Martin, W. H. See Brocklehurst, J. E.; Kelly, B. T.
Martin-Marietta Corp. Carbon article coated with beta silicon carbide, P (8) 240*c*. Method of seed-pulling beta silicon carbide crystals from a melt containing silver and the product thereof, P (3) 73*e*. Resin impregnated ceramic heat shield and method of making, P (11) 341*b*. Thermoplastics exhibiting high viscosity at their decomposition temperatures, P (11) 341*a*.
Martin Vivaldi, J. L. Bentonites of Cabo de Gata (southeast Spain) and of Guelaya volcanic province (north Morocco), B (5) 161*b*.
Martinak, B. Apparatus for continuous recovery and separation and cleaning of grit, P (9) 263*e*.
Martindill, R. E. See Orbach, H. K.
Martinek, C., and Hummel, F. A. Linear thermal expansion of three tungstates, (5) 154*j*.
Martinek, R. G. Diffusion furnace with transport means, P (11) 348*i*.
Martinet, J. R. See Hildinger, W. M.
Martinet, J. R., and Hicks, J. C. Refractory structure for a rotary kiln, P (1) 14*b*.
Marty, R. S., and Fabricius, J. H. Electrical resistor, P (5) 141*b*.
Maruno, S., Yamada, T., and Matsuzawa, T. Effects of conditions of anodic oxidation (dc) on the adherence of aluminum enamel to aluminum plate—surface potential diagrams, (8) 229*e*.
Maruyama, M. Ruby crystals grown by the Czochralski technique, (11) 356*g*.
Marvin, O. F. Process for the concentration of beryllium and aluminum minerals, P (7) 205*e*.
Marzocchi, A. Glass fiber-elastomeric systems treated with mercaptan-containing organosilane anchoring agents, P (4) 94*a*. Glass fibers treated for combination with elastomeric materials and method, P (10) 300*a*. Method for the preparation of silica fibers, P (3) 65*j*.
Marzocchi, A., and Janetos, N. S. Structures formed of glass fiber-elastomer systems, P (9) 266*a*.
Marzullo, S. See Franklin, A. D.
Mas, R. J., and Michaud, A. L. Process and apparatus for continuously producing titanium dioxide by the oxidation of vaporized $TiCl_4$, P (3) 78*a*.
Masani, M. R. Single and double firing of whiteware, (9) 271*f*.
Mashkovich, L. A., Klyachko, Yu. A., and Kuteinikov, A. F. Electromechanical principles of the phase analysis of powdered materials, (10) 314*g*.
Maskalick, N. J. Method of making single crystal films and the product, P (10) 310*c*.
Maslen, V. M. See Dawson, B.
Maslennikova, G. N. See Budnikov, P. P.; Lisov, A. A.
Masoero, A. R. Porous ceramic oxides and method, P (10) 304*h*.
Mason, G. R. See Buckley, F. T.
Mason, K. L. Polypropylene glass laminates, (1) 7*a*.
Mason, R. E. A., and Strickland-Constable, R. F. Breeding of crystal nuclei, (3) 79*c*.
Massachusetts Institute of Technology. Method of producing interface-alloy epitaxial heterojunctions, P (2) 51*e*.
Masson, C. R. Ionic equilibria in liquid silicates, (4) 93*h*.
Master Mechanics Co. Hydraulic cement compositions and methods, P (4) 92*d*.
Masters, C. D. Use of sedimentary structures in determination of depositional environments, Mesaverde Formation, Williams Fork Mountains, Colorado, (4) 118*g*.
Masters, K., and Mohtadi, M. F. Study of centrifugal atomization and spray drying, (5) 144*a*, (6) 179*e*.
Masterson, H. G. See Collins, A. C.
Masuyama, T., and Matsuoka, M. Silicon carbide varistors, P (8) 246*i*.
Matchen, B. Refractory products, P (5) 136*b*. See Watson, G. R.
Matejka, J. Possibility of determining the degree of interaction between the porcelain body and the glaze, (5) 136*j*.
Mather, W. B., Jr. See Webb, A. N.
Mathers, J. E. See Mikus, F. F.
Matheson, A. J. See Carpenter, M. R.; Davies, D. B.
Mathews, J. W., Mallard, W. C., and Sibley, W. A. Effect of simultaneous optical bleaching and gamma radiation on the room-temperature colorability of KCl, (11) 352*b*.
Mathews, John, & Co., Ltd. See John Mathews & Co., Ltd.
Mathiak, H. See Lehmann, H.
Mathias, B. B. Apparatus for inspecting the rim of a bottle, etc., which employs polarized light at Brewster's angle, P (3) 64*j*. See Baker, T. C.
Mathias, B. B., Schmersal, L. J., and Sebring, L. W. Apparatus for inspecting containers for wall thickness distribution, P (7) 198*a*.
Mathur, A. P. Rapid analysis of chromite and chrome ore, (10) 315*c*.
Mathur, B. C. See Evans, P. E.
Mathur H. B. See Yagnik, C. M.
Matijevic, E. See Levine, S.
Matoba, T. See Kudaka, K.
Matselaar, R., and Elsken, J. van der. Impurity-induced near-infrared spectra as a source of information about the frequency distributions of the alkali halides, (10) 322*c*.
Matako, J. See Lefever, R. A.
Matsubara, N. See Watanabe, Hideo.
Matsumoto, G., and Iida, S. ^{139}La and ^{55}Mn NMR signals from ferromagnetic $(La_{1-x}Sr_x)MnO_3$, (10) 322*a*.
Matsumoto, H. See Yamauchi, S.
Matsumoto, T., and Nowacki, W. Densest packing of ellipsoids, (8) 252*h*.
Matsumoto, Y. See Tagai, H.
Matsuno, S. See Ando, J.
Matsuo, Y. See Nitta, T.
Matsuo, Y., Fujimura, M., Sasaki, H., Nagase, K., and Hayakawa, S. Semiconducting $BaTiO_3$ with additions of Al_2O_3, SiO_2, and TiO_2, (4) 99*a*.
Matsuoka, M. See Masuyama, T.
Matsushima, I. Automatic greenware replacing device for continuous pottery forming machine, P (4) 98*f*.
Matsushita, H. Numerical calculations for the alkaline error of the glass electrode, (5) 156*b*.
Matsushita Electric Industrial Co., Ltd. Carbon film resistor composition, P (1) 17*a*. Electroconductive composition containing $BaPbO_3$, P (6) 177*e*. Light amplifier including a layer for converting X-rays to visible radiation, P (9) 273*f*. Method for growing single crystals of vanadium dioxide, P (7) 214*g*. Method for the manufacture of solid type electrolytic condensers of titanium, P (4) 100*e*. Piezoelectric ceramic resonator devices, P (1) 18*j*. Production of lead titanate and lead zirconate for ceramic bodies, P (2) 52*i*. Radiating gas burner apparatus, P (10) 317*d*. Semiconductive ceramic compositions with positive temperature coefficient of resistance, P (6) 178*g*. Silicon carbide varistors, P (8) 246*i*.
Matsushita Electronics Corp. Method of forming a *pn* junction in a polycrystalline material, P (9) 273*c*. Method for making semiconductor devices, P (8) 245*a*. Method of making semiconductor devices by double diffusion, P (1) 18*c*. Semiconductor device with novel isolated diffused region arrangement, P (8) 246*f*.
Matsuyama, T. See Hosokawa, M.
Matsuzawa, T. See Maruno, S.
Mattarella, S. P. Spark plug with the insulator tip coated with a lead oxyhalide, P (1) 19*e*.
Matthes, F. See Moebius, R.
Matthews, H. See Dixon, R. W.; Le Craw, R. C.
Matthews, N. F. J., and Warter, P. J., Jr. Transient polarization in insulating CdS, (9) 288*e*.
Matthias, B. T., Geballe, T. H., Longinotti, L. D., Corenzwit, E., Hull, G. W., Willens, R. H., and Maita, J. P. Superconductivity at 20°K, (1) 17*c*.
Mattimoe, P. T., and Hofmann, J. J. Transparent laminates and method for producing, P (9) 266*b*.
Mattiug, A., and Witt, W. Strength of glass-metal joints, (9) 264*j*.
Mattox, D. M. Contamination-nucleated crystal growth at bubble surfaces in glass, (1) 5*g*.
Mattox, W. J., and Gladrow, E. M. Process for ion exchanging crystalline zeolites, P (5) 148*j*.
Mattuck, J. B. See Blackburn, P. E.
Matukura, Y. See Miura, Y.
Matunobu, Y. Motion of a deformed drop in Stokes flow, (10) 323*f*.
Matusik, F. J. Structure, composition, and bond strength, (3) 76*g*. See Bachman, G. S.
Matveenko, I. I. See Dubrovskaya, L. B.
Matveev, G. M. See Matveev, M. A.
Matveev, M. A. See Budnikov, P. P.
Matveev, M. A., and Agarkov, A. S. Influence of the nature of cations on the properties of alkali silicate glasses, (2) 39*a*.
Matveev, M. A., Khodskii, L. G., Fisyuk, G. K., Bolutenko, A. I., and Strugach, L. S. Certain properties of glasses based on the systems BaO-TiO_2-B_2O_3, BaO-TiO_2-P_2O_5, and BaO-TiO_2-SiO_2, (2) 38*h*.
Matveev, M. A., Matveev, G. M., and Kharitonov, F. Ya. Strength of ceramic shapes made of pure oxides, (6) 189*c*.
Matveev, M. A., Pevzner, R. L., Matveev, G. M., and Kharitonov, F. Ya. Use of ceramic materials in steam of high parameters, (8) 240*h*.
Matveev, M. A., Sokolov, A. A., and Krechmar, V. A. Methods of speeding up water glass production, (8) 250*f*.
Matveev, M. A., and Voronin, A. V. Study of the solubility of glasses in the system silica-sodium oxide-cesium oxide, (6) 169*c*.
Matveeva, F. A., and Dyban, Yu. P. Using semi-acid clays of the Kuznets Basin (USSR), (9) 269*i*.
Matzke, H. Effect of TiO_2 additions on sintering of UO_2, (4) 108*f*. Xenon migration and trapping in doped ThO_2, (10) 327*a*.
Mauer, P. B. See De Paolis, P. F.
Maul Brothers, Inc. Apparatus for molding glass, P (6) 170*d*. Glass-molding apparatus, P (8) 235*a*.
Maurel, P. J. P. See Jamey, M. A.
Maurer, K., Hirai, J., Benda, L., and Sternkueker, J. Press for drawing ceramic and other materials in the plastic state, P (6) 170*g*.
Maurer, R. D. Laser employing photochromic glass as a *Q*-spoiling medium, P (5) 130*c*.
Maury-Laribiere, M. Manufacturer's experience and information needs, B (9) 291*d*.
Mauser, J. E. See Fursman, O. C.
Max-Planck-Institut fuer Eisenforschung. Metallurgical furnace lining, P (7) 205*a*. Methods and apparatus for determining the oxygen activity of molten metals, metal oxides, and slags, P (4) 97*a*.
Maxwell, P. S., and Harwood, D. J. Electron microscopy of devitrified glass powder compacts, (11) 333*j*.
May, C. E. High frequency hydraulic actuated jaw crusher, P (9) 297*d*.
May, E. R. W. See Parr, N. L.
May, I., and Marinenko, J. Micropycnometer for the determination of the specific gravity of minerals, (1) 22*b*.
May, J. A. See Frosch, C. J.
May, J. E., and Stoute, R. L. Doped hypostoichiometric dioxide nuclear fuel composition and method of preparation, P (6) 174*b*.
Mayberry, M. L. Chromite refractory, P (4) 97*c*. See Neely, J. E.
Mayer, A., and Cave, E. F. Method of making passivated semiconductor devices, P (5) 142*a*.
Mayer, E. H., and Moore, R. J. Method of depositing films of controlled specific resistivity and temperature coefficient of resistance using cathode sputtering, P (11) 344*f*.
Mayer, I., Shidlovsky, I., and Yanir, E. Low-temperature synthesis of metallic silicides and germanides by an amalgam method, (8) 254*i*.
Mayer, I., Zolotov, S., and Kassierer, F. Crystal structure of rare earth and yttrium oxybromides, (4) 107*e*.
Mayer, J. W. See Zanio, K.
Mayer, M. See Walz, A.
Mayer, R. M. See Walker, D. G.
Mayerhofer, E. See Kahl, P.
Mayfield, B. Discussion of "Effect of mix proportions and method of testing on Poisson's ratio for mortars and concretes," (5) 124*j*.
Mayhall, J. O., and Hallse, R. L. Precision casting fused silica radomes, (4) 96*h*.
Mayland, B. J., Harvin, R. L., Trimarko, C. R., and Brandon, C. S. Catalyst for the stream reforming of naphtha and related hydrocarbons, P (10) 317*i*.
Maynard, G. R. Method and apparatus for making mosaics, P (2) 49*a*.
Maynard, R. N., Skipper, B. R., and Millman, N. Method of beneficiating clay by removal of titanium impurities, P (6) 183*b*.
Mazanti, B. B., and Sowers, G. F. Influence of rock anisotropy and time-dependent deformation on the stress-relief and high-modulus inclusion techniques of *in situ* stress determination, B (3) 90*g*. Laboratory testing of rock strength, B (3) 90*h*.
Mazdiyasni, K. S., Lynch, C. T., and Smith, J. S., II. Preparation and some properties of yttrium, dysprosium, and ytterbium alkoxides, (5) 157*e*. Yttrium, dysprosium, and ytterbium alkoxides, P (3) 69*g*.
Mazieres, C. See Bigare, M.; Livage, J.
Mazurin, O. V. See Dgebuadze, T. P.
Meade, R. H. See Mee, J. E.
Meadowcroft, T. R. See Boyer, A. J. G.
Meagher, E. P. See Newnham, R. E.
Meakin, J. D. Field ion microscopy of refractory metal carbides, (8) 237*j*.
Mears, L. D. See Elleman, T. S.
Meath, W. A., and Neill, J. L. Method and apparatus for spreading chopped fibers, P (4) 94*j*.
Meckel, B. B. Method of determining crystal grain orientation by comparing sputtered patterns, P (11) 348*b*.
Meckler, Yu. B. See Volarovich, M. P.
Mecky, K., and Fiebiger, E. Filter press, P (4) 102*b*.

Mecum, W. D. See Aponyi, T. J.
Medic, N. See Hloch, A.
Medici, M. Use of natural gas as fuel in the silicate industry, (6) 182*a*.
Medicus, G. See Olson, R. A.
Medlin, W. L. Thermoluminescence in quartz, (3) 88*f*. Thermoluminescent characterization of quartziferous materials, P (9) 277*i*.
Medney, J. Apparatus for forming continuous helical coils of resin bonded glass fibers, P (7) 198*a*.
Medvedeva, Z. S. See Koppel, Kh. D.; Luzhnaya, N. P.
Medvedovskaya, E. I., and Vydrik, G. A. Quantitative phase analysis of electrical porcelain, (8) 242*f*.
Mee, C. H. B. See Jones, M. D.
Mee, J. E., Archer, J. L., Meade, R. H., and Hamilton, T. N. Chemical vapor deposition of epitaxial YIG on YAG and epitaxial GdIG on YAG, (5) 150*a*.
Mee, J. E., and Pulliam, G. R. Epitaxial dielectric MgO crystals, P (9) 272*i*.
Megla, G. K. Optical properties and applications of photochromic glass, (9) 264*a*.
Megles, J. E. See Bopp, H. F.; Duke, D. A.
Mehal, E. W. See Bailey, L. G.; Johnson, R. E.
Mehan, R. L., and Feingold, E. Strength and structure of very fine sapphire whiskers, B (4) 121*h*.
Mehra, K. B. See Khanna, S. S.
Mehra, O. K., Hussain, S. Z., and Jena, P. K. Kinetics of chlorination of niobium pentoxide with Cl in the presence of excess graphite powder, (7) 219*b*.
Mehran, F., Brooks, R. A., and Ramsey, N. F. Rotational magnetic moments of alkali-halide molecules, (8) 256*h*.
Mehrotra, P. N. See Chandrashekhar, G. V.; Sastry, R. L. N.
Mehrwald, K. H. Old and new applications of silicon carbide, (9) 268*a*. Role of sodium chloride in the technical production of SiC, (1) 12*c*.
Mehta, R. R., Coppen, P. J., and Heynes, M. S. R. Effect of metal-semiconductor work function difference on the calculation of surface charge density of silicon-silicon dioxide interface, (5) 151*j*.
Meier, H. Self-washing insulators, P (3) 70*g*.
Meieran, E. S. Evaluation of bulk and epitaxial GaAs by X-ray topography, (8) 243*e*.
Meijer, R. J. Rotary [glass ceramic] heat exchangers and hot-gas engines, P (6) 175*b*.
Meiling, G. S., and Uhlmann, D. R. Crystallization and melting kinetics of sodium disilicate, (1) 27*i*.
Meinecke, G., and Luessem, H. Controlling mechanism for a spectrometer, P (5) 147*b*.
Meinhard, J. E. Process for encapsulating materials with a thermoplastic cover, P (2) 42*e*.
Meisalo, V. See Inkinen, O.
Meisel, G. M. Grinding mill and method of operation, P (2) 56*f*.
Meisel-Knone, C. Method of enabling dehumidification of masonry or brickwork, P (1) 10*h*.
Meister, R. Oxygen for heating glass furnaces, (7) 197*a*.
Meitzler, A. H. See Fraser, D. B.
Meker, G. Note on insulating refractories, (9) 268*a*.
Meker, P. Natural gas for laboratory burners and furnaces, (7) 213*i*.
Melhorn, W. N. See Lounsbury, R. W.
Melich, M. E. See Ohlsen, W. D.
Melik-Akhnazaryan, A. F., Tatevosyan, K. M., and Kostanyan, K. A. Electric melting of enamels, (8) 229*f*.
Mellen, E. J., Jr., Webb, J. M., Fasselle, R. J. de, and Dudek, J. A. Injection molding apparatus for making ceramic cores, etc., P (3) 68*h*.
Mellon, M. G. See Boltz, D. F.
Mellor, C. H. Plasma arc spraying of hafnium oxide and zirconium boride mixtures, P (7) 195*e*.
Melngailis, I., and Calawa, A. R. Solution regrowth of planar InSb laser structures, (7) 208*c*.
Melnick, I. See Pruniaux, B.
Mel'nik, G. A. See Lakomskii, V. I.
Melpar, Inc. Capacitor having dysprosium oxide dielectric, P (9) 272*j*. Method of making tunnel diode, P (7) 209*j*. Rhenium thin film resistors, P (8) 246*d*.
Memistor Corp. Adaptive memory element, P (11) 343*c*.
Menashi, W. P. Treatment of surfaces, P (8) 236*b*.
Menelly, R. A. Fluorescent lamp using an indium-mercury amalgam band for pressure control, P (10) 309*f*. Fluorescent lamp with a reflective coating containing TiO_2 and Sb or its oxide, P (7) 198*d*.
Meneret, J. New automatic gun for flame spraying refractory oxides, (10) 296*g*.
Mennucci, L. See Rossini, A.
Men'shikov, A. Z., and Nemnonov, S. A. Electron structure of refractory chromium compounds, (9) 282*a*.
Mentzel, F. A. See Eckardt, D.
Mentzer, E. K. See Hubin, L. W.
Menyuk, N., Dwight, K., and Raccah, P. M. Low temperature crystallographic and magnetic study of $LaCoO_3$, (2) 49*g*.
Menzies, I. A., and Strafford, K. N. Oxidation of uranium-based ceramics—behavior of uranium carbide and uranium oxide contaminated with carbon-containing phases, (10) 324*d*.
Menzinger, F., and Paoletti, A. Magnetic moments and unpaired-electron densities in $CoPt_3$, (9) 284*e*.
Mepham, H. J. Method of manufacture of phosphor screen, P (9) 265*g*.
Mercade, V. Method for preventing activation of silica in ore flotation, P (8) 251*i*.
Mercer, E. E., and McAllister, W. A. Dipole moments of *cis*- and *trans*-trichlorotriaquoruthenium(III), (4) 108*b*.
Mercer, P. D. Analysis of the gases released on cleaving muscovite mica in ultrahigh vacuum and of gases which remain adsorbed on the freshly cleaved surface, (3) 78*i*.
Mercer, R. A. See Miller, R. P.
Merck & Co., Inc. Metallic selenides and tellurides and process for making, P (9) 273*g*. Method of making a semiconductor crystal body, P (5) 142*a*.
Meredith, R. E. See Clark, D. P.
Mering, J., and Brindley, G. W. X-ray diffraction band profiles of montmorillonite—influence of hydration and of the exchangeable cations, B (9) 289*e*.
Mering, J., and Oberlin, A. Electron-optical study of smectites, B (9) 289*b*.
Merkel, H. Method for producing highly pure particularly silicon-free $A^{III}B^{V}$ compounds, P (11) 344*e*.
Merkel, H., and Leibenzeder, S. Method for producing pure polished surfaces on semiconductor bodies, P (10) 310*g*.
Merkle, F. P., Jr. Panelized furnace roof, P (7) 213*j*.
Merkle, G., and Ohnemueller, W. Development of an autoclaved calcium silicate lightweight building material with special consideration of the chemical reaction and the mechanical strength, (1) 2*d*.
Mero & Co., Inc. Drum filter element attaching means, P (3) 78*b*. Filter apparatus, P (4) 102*a*.
Merriam, R. W. Particle size distribution by micromerograph analysis, (2) 54*f*.
Merrill, T. W. See Buker, D. O.
Merritt, F. R., Guggenheim, H. J., and Garrett, C. G. B. Paramagnetic resonance of divalent praseodymium in calcium fluoride, (10) 324*g*.
Merritt, L. L., Jr., and Streib, W. E. X-ray diffraction, (10) 316*e*.
Merryman, R. G. See Kempter, C. P.
Mersol, S. A. See Vahldiek, F. W.
Mertes, H. See Wartmann, R.
Merz, H. Analysis of light elements in nonconductors—preparation of samples, (6) 179*j*.
Merz, E. See Knacke, O.
Merz, K. M. See Huang, C. Y. D.
Merz, M. See Weingaertner, E.
Meserole, R. H. High strength-high temperature yarn, P (5) 130*b*.
Meservey, A. B., Sease, J. D. and Fitts, R. B. Method of fabricating ceramic nuclear fuel product, P (3) 69*b*.
Meshengisser, M. J. See Ermakov, I. S.
Messer, C. E., Cho, T. Y., and Gibb, T. R. P., Jr. Dissociation pressures in the system ytterbium-ytterbium dihydride—a comparison with calcium-calcium dihydride, (8) 253*b*.
Messier, D. R. Vapor pressure of Gd_2O_3 from 2350° to 2590°K, (1) 33*e*.
Messina, M. L. Expansion of fractionated montmorillonites under various relative humidities, B (6) 192*a*.
Messmer, E. Comparative testing of service behavior of plastic-coated and enameled boiling and frying utensils, (7) 195*a*.
Messner, M. E. See Zimmerley, S. R.
Metallgesellschaft Akt.-Ges. Apparatus for separating mixtures of solid particles, P (3) 77*j*. Multicell centrifugal dust separator, P (2) 53*f*. Process for the production of soluble compounds, P (3) 78*d*.
Metalurgitschen Zavod "Lenin." Protecting carbon materials from oxidation, P (2) 48*b*.
Metcalfe, A. G. See Schmitz, G. K.
Metco, Inc. Carbide flame spray material, P (11) 340*b*. High temperature flame spray powder and process, P (7) 195*d*. Radio frequency plasma flame spraying, P (1) 4*j*.
Methfessel, S. J. See Gambino, R. J.; Holtzberg, F.
Mettke, P. See Malluschke, A.
Metzger, C., and Schwiete, H. E. Investigation of the thermal expansion and stability of silica brick, (7) 202*d*.
Meyer, A. Method of metal-coating ceramic bodies, P (1) 18*f*.
Meyer, C. Clay alteration in copper deposits associated with granodiorites (abstract), B (6) 191*j*.
Meyer, H. See Krauth, A.
Meyer, O. Smooth precision dimensional bodies of vitreous material and method and apparatus for producing, P (4) 95*d*, P (5) 130*f*.
Meyer, P., and Humphreys, G. D. Centrifugal air classifiers, P (6) 179*f*.
Meyer, R., and Pastor, H. Titanium and zirconium borides—preparation, properties, and uses, (6) 174*g*.
Meyer, R. A., and Lofftus, F. H. High density ceramic beryllia-nuclear fuel compact containing an additive for the retention of fission products, P (5) 135*e*.
Meyer, R. E., and Zotti, S. M. Rotating disk study of the dissolution of zirconium in HF-H_2SO_4, (4) 115*j*.
Meyer, W. E. See Buddecke, C. L.; Johnson, K. O.
Meyer-Simon, E. See Kloepfer, H.
MHD Research, Inc. Method of producing beryllium halides from beryllium ore in a high intensity arc, P (10) 318*f*.
Miale, J. N., and Weisz, P. B. Production of the hydrogen ion exchanged form of a crystalline zeolite, P (7) 215*a*.
Micaud, G. See Barrachin, A. M.
Miccioli, B. R. Method for making ducted refractory articles, P (1) 13*e*.
Miccioli, B. R., and Wise, D. C. Hot-press ceramics for high strength, precision, (3) 74*j*.
Michael, H. J. Metal treatment, P (9) 265*i*.
Michaels, G. O., and Gambell, J. W. Dehydrogenation process and alumina-supported nickel, molybdenum, and alkali metal catalyst therefor, P (1) 25*a*.
Michalik, E. R., and Misson, G. W. Method of varying the thickness of a glass sheet while on a molten metal bath, P (1) 9*i*.
Michalko, E. Method for preparing high rate zeolitic molecular sieve particles, P (2) 56*i*. Method for preparing spherically shaped crystalline zeolite particles, P (9) 279*e*. Method for producing molecular sieve zeolite particles, P (3) 78*d*. Preparation of crystalline zeolite particles, P (4) 105*c*. Zeolite and method for making the improved zeolite, P (5) 149*d*.
Michaud, A. L. See Mas, R. J.
Michel, A. Method for fluidtightly securing a metal part such as a connection to a glass member, P (4) 95*a*.
Michel, A. E. See Nathan, M. I.
Michel, C. See Buisson, G.
Michel, D. See Collongues, R.
Michel, M., and Courbon, J. Porous alumina products and method of manufacture, P (8) 251*a*.
Michelitsch, M. Method of forming a semiconductor by diffusion by using a crystal masking technique, P (3) 73*i*. See Heilbardt, G.
Michelman, B. See Loiacono, G. M.
Michenaud, J. P., Streydio, J. M., and Luyckx, A. Kinetics of optical charge exchange in copper-doped cadmium sulfide single crystals, (8) 254*d*.
Micheron, F. See Baumberger, C.
Microdot, Inc. Apparatus for adjusting the temperature coefficient of wire strain gages, P (6) 181*c*.
Micromatic Hone Corp. Bonded abrasive grade [hardness] checking apparatus, P (1) 1*f*.
Microwave Associates, Inc. Idler circuit encapsulated in parametric or tunnel diode semiconductor device, P (10) 309*i*.
Midgley, H. G. Composition and possible structure of the quaternary phase in high-alumina cement and its relation to other phases in the system CaO-MgO-Al_2O_3, (7) 216*h*.
Midland-Ross Corp. Gas burner, P (10) 317*a*. Hearth dam, P (7) 204*e*. Method and apparatus for firing ceramic bodies, P (2) 56*d*. Method of reducing carbon deposits on surfaces in contact with carbonaceous gases and subjected to elevated temperatures, P (2) 56*a*.
Midorikawa, M. See Nakamura, T.
Mid-West Abrasive Co. Solid abrasive article and method of making honing elements therefrom, P (11) 331*g*.
Midwest Research Institute. Method of treating glass to reduce helium permeation, P (11) 336*a*.
Midwinter, J. E. Assessment of lithium metaniobate for nonlinear optics, (5) 149*f*. Image conversion from 1.6μ to the visible in lithium niobate, (8) 243*f*.
Mields, A. See Schwiete, H. E.
Mields, A., and Zografou, C. Cristobalite as a component in the structure of porcelain, (3) 69*j*.
Mields, M. Experimental notes by Johann Friedrich Boettger relating to his invention of porcelain in 1708, (4) 98*e*.
Mifalei Yam Hamelah, B. M. Process for the manufacture of low-porosity burned magnesia, P (7) 205*g*.
Mihailovic, Z. See Anthony, A. M.
Mihara, T. See Hirota, E.; Nishikawa, T.
Mikami, H. M. See Wohlleben, K.
Mikami, Y., and Doi, H. Pressure loss due to the elastic energy for viscoelastic capillary flow, (11) 355*d*.
Mikhail, H. See Youssef, Y. L.
Mikhail, R. Sh., and Gouda, V. K. Heats of hydration of mixtures of Egyptian portland cement and fly ash, (5) 125*a*.
Mikhail, R. Sh., Hussein, A. T., and Gouda, V. K. Differential thermal analysis in vacuo of pastes of portland cement and of β-dicalcium silicate, (8) 228*e*.
Mikhailov, M. P. See Fridkin, V. M.
Mikhailov, N. V. See Bykov, V. M.; Gribkova, L. V.
Mikhailova, N. D. See Dombrovskaya, N. S.
Mikheeva, V. I. See Sterlyadkina, Z. K.
Mikoda, M., Kuroda, T., and Hayakawa, S. Preparation and electrical properties of a ow loss dielectric, (6) 168*e*.
Mikoshiba, N. See Ozaki, H.
Mikulec, A. R. Silicon carbide igniter, P (6) 175*b*.
Mikus, F. F., and Mathers, J. E. Europium and bismuth activated yttrium vanadate phosphor, P (4) 99*j*.
Mikus, F. F., Mathers, J. E., and Palilla, F. C. Europium and calcium or manganese activated yttrium vanadate phosphor, P (4) 99*j*.
Milberg, M. E. See Otto, K.
Milberg, M. E., and Daly, M. C. Structure of oriented sodium metaphosphate glass fibers, (5) 128*h*.
Milbourne, C. G. Nickel and nickel oxide catalysts on a nickel spinel base, P (5) 148*f*.
Milch, A., Ahlert, R. H., and Lalak, J. J. Method of forming a refractory metal-to-ceramic seal, P (9) 273*d*.

Milch, A., Lalak, J. J., and Ahlert, R. H. Ceramic-to-metal seal, P (5) 140*g*. Refractory ceramic-to-metal seal, (4) 99*i*, P (5) 142*f*.
Miler, M. Dependence of the infrared reflectivity of silicon oxide on the layer thickness, (10) 319*d*.
Miles, G. D., Sambell, R. A. J., Rutherford, J., and Stephenson, G. W. Fabrication of fully dense transparent polycrystalline magnesia, (5) 152*j*.
Miles, J. L. Method of anodizing by applying a positive potential to a body immersed in a plasma, P (10) 310*c*.
Mileson, J. S. See Glasser, L. S. D.
Milford, F. J. See Kreitman, M. M.; Mills, R. E.
Millea, M. F., and Wilcox, W. R. Etching and crystal growth in the GaAs-Sn system, (3) 81*a*.
Miller, A. E. Rare earth suboxides, P (8) 258*g*.
Miller, A. H., and Starner, J. E. Conveyor apparatus [for glass sheets], P (1) 8*h*.
Miller, B. C., and Cooper, S. A. Material processing tower, P (6) 179*e*.
Miller, C. A. Hysteresis loss and dielectric constant in barium titanate, (5) 138*f*.
Miller, C. F. Bonding machine sighting means, P (8) 243*i*. Jet conveying system, P (8) 244*h*.
Miller, D. P. Tin as a dopant in gallium arsenide crystals, P (10) 311*g*.
Miller, E. A. See Weisberg, L. R.
Miller, E. D., Jr. Manufacture of kiln furniture, P (1) 13*a*. See Einstein, E.; McCreight, D. O.
Miller, E. D., Jr., and Pavlica, S. R. High alumina brick, P (7) 204*f*.
Miller, F. W., and Blair, F. E. Shuttle kiln, P (3) 77*a*.
Miller, G. L., and Wagner, S. E. Semiconductor detector method and apparatus, P (8) 246*e*.
Miller, H. C. Method of making a peripheral diamond grinding wheel, P (5) 123*j*. Peripheral diamond grinding wheel, P (8) 227*h*.
Miller, J. E., Guereca, R. A., Richardson, H. P., and Gordon, J. L. Correction for non-uniformity of the bore of a capillary tube viscosimeter, (1) 20*h*.
Miller, J. G., Haden, W. L., Jr., and Oulton, T. D. Oxidizing power of the surface of attapulgite clay, B (6) 192*b*.
Miller, J. L., Jr., and Ivey, K. H. Method of making paper from mica flakes which have been subjected to hot aqua regia, P (9) 274*a*.
Miller, J. P. Mold cooling control apparatus for a glassware forming machine, P (3) 66*a*.
Miller, K. T. See Ervin, G., Jr.
Miller, L. F. Conductive element, composition, and method, P (9) 272*c*.
Miller, L. F., and Neisser, K. E., Jr. Electrical resistor compositions, elements, and method of making, P (9) 272*f*.
Miller, P. Screen finer—screen faster, (3) 74*j*.
Miller, R. Ocrate treatment increases acid resistance of concrete, (1) 2*h*.
Miller, R. C., and Nordland, W. A. Tunable $LiNbO_3$ optical oscillator with external mirrors, (4) 118*d*.
Miller, R. P., and Mercer, R. A. High temperature behavior of beryl melts and glasses, (1) 6*e*; correction, (3) 63*j*.
Miller, R. S. See Davidson, J. K.
Miller, W. A., and Shott, W. L. Corrosion of refractories by blast furnace slags, (8) 237*b*.
Miller, W. H., and Barson, F. Semiconductor devices and passivation thereof, P (1) 19*c*.
Miller, W. S. Preparation of soda ash, P (7) 215*a*.
Miller Equipment Co. Material processing tower, P (6) 179*e*.
Millet, J. Porous ceramic materials as electrodes in fuel cells, (10) 303*f*.
Millier, A. See Bardin, C.
Millman, N. See Iannicelli, J.; Maynard, R. N.
Millman, R. S. See Evans, P. E.
Mills, D. Structure of sputtered tantalum, (11) 343*a*.
Mills, G. A. See Cornelius, E. B.; McEvoy, J. E.
Mills, J. C. See Cockayne, D. J. H.
Mills, R. E., Kenan, R. P., and Milford, F. J. Green's-function theory of ferrimagnetism with an application to magnetite, (10) 321*d*.
Mills, R. G., Barner, J. O., Johnson, D. E., and Simnad, M. T. Irradiation effects on dispersion-type BeO-UO_2 fuels for EBOR, (4) 96*f*.
Milne, I. H., McKelvey, J. G., and Trump, R. P. Permeability and salt-filtering properties of compacted clay (extended abstract), B (5) 160*k*.
Milnes, G. C. See Hughes, K.
Mil'vidskii, M. G., Osvenskii, V. B., and Stolyarov, O. G. Measurement of the high-temperature microhardness of semiconductors, (11) 346*e*.
Milyukov, E. M. See Mishel, V. E.
Milyukov, E. M., and Ushakov, D. F. Effect of crystallization on the properties of acid resistant vitreous crystalline enamel, (11) 332*g*.
Minaev, A. I. Apparatus for measuring the true heat capacity of solids within a wide range of temperature, (11) 346*c*.
Minagawa, K. See Ikeda, K.
Minagawa, S., Saito, T., and Gejyo, T. Growth patterns on the surface of alumina grown by chemical vapor deposition, (10) 231*d*.
Minami, S., Neyagawaahi, W. M., and Nomura, A. Method for the manufacture of solid type electrolytic condensers of titanium, P (4) 100*e*.
Minchenko, H. M. Electromechanical transducer, P (11) 343*e*.
Mindick, M. See Albrecht, W. L.
Mindick, M., and Reven, L. E. Method of stabilizing silica sols, P (1) 25*g*.
Minenko, N. N., and Nazarchuk, T. N. Determination of nitrogen in nitrides [of B and Si] undecomposable by acids, (1) 11*e*.
Minerais et Metaux. Process for reducing error in the sampling of materials, P (10) 316*c*.
Mineralimpex Magyar Olaj- es Banyatermek Kulkereskedelmi Vallalat. Basic refractory block and method of making, P (2) 46*f*.
Mineral Industries Corp. of America. Reducing particle size of clay and rheology control of clay-water systems, P (2) 57*c*.
Minerals & Chemicals Philipp Corp. Method for improving the brightness of clay, P (3) 78*b*.
Minicozzi, A. S. See Kreisberg, M.
Minier-Cassayre, C. See Dautreppe, D.
Minkiewicz, V., and Nakamura, A. Direct observation of ^{55}Mn NMR in antiferromagnetic $CsMnF_3$, (9) 281*c*. Magnetic properties of $KMnF_3$ (III) nuclear and electron spin resonance, (9) 284*g*.
Minnelli, F. P. Obsolescence of material handling equipment, (2) 53*c*.
Minnesota Mining & Mfg. Co. Acid-resistant enamels, P (8) 229*h*. Crystalline spherules, P (2) 47*a*. Glass bubbles prepared by reheating solid glass particles, P (5) 129*i*. Glass containing dissolved carbon, methods of making and using, and obtaining graphite, P (2) 40*j*. Radiant white light source, P (5) 136*f*. Semiconductive alloy composition having thermoelectric properties, P (4) 101*e*. Small spherical nuclear fuel particles and processes of making, P (3) 69*f*. Soot-resistant roofing granules, P (11) 337*e*.
Mino, M., and Kojima, T. Polyoptical sealing of vacuum tubes, (5) 139*i*.
Minowa, S. See Kosaka, M.; Takayanagi, T.; Yamada, M.
Miny, J. C. See Lecrivain, L.; Maretheu, A.
Miraldi, N. L. Method of making rapid curing foundry cores, P (8) 241*b*.
Miranda, M. D. See Khabata, S. J.
Mircea, S. Decomposition of tricalcium silicate with boric oxide, (7) 194*e*. See Veiser, I.
Mircea, S., and Mogosanu, E. Dolomite blocks bonded with tar and pitch for oxygen-blown converter linings, (9) 267*d*.
Mircea, S., Szabo, A., and Mogosanu, E. Technological study of the sintering of Moldavia and Dobrogea dolomites, (9) 269*d*.
Mironov, A. M., and Churaev, N. V. Dispersion analysis with an automatic weighing sedimentometer, (2) 54*c*.
Mironova, M. L. See Ananich, N. I.
Mirza, M. B. See Ehrlinger, H. P., III.
Misechko, V. I. See Tsibrik, A. N.
Misetich, A. A. See Dietz, R. E.
Misetich, A. A., and Watson, R. E. Gyromagnetic factors and covalency in iron-series complexes, (9) 282*h*.
Mishel, V. E., and Milyukov, E. M. Crystallization of antimony compounds in glasses and enamels, (1) 3*j*.
Mishkind, S. I. Firing ceramic blanks containing organic plasticizers in combustible adsorbents, (3) 76*j*.
Mishra, C. S. See Moorthy, V. K.
Mishriki, A. See Youssef, Y. L.
Misler, Zh. V. See Bergman, A. G.
Missio, D. V. See Luck, C. F., Jr.
Misson, G. W. See Michalik, E. R.
Mistler, R. E., and Coble, R. L. Comments on the use of log-log plots in analyzing grain growth data, (9) 275*j*. Microstructural variation due to fabrication, (5) 154*i*.
Mitchell, A. Cryoscopy of polyborate ions in dilute solution in alkali halides, (3) 79*d*. Infrared absorption of the orthoborate ion, (3) 82*a*.
Mitchell, E. W. J., and Whitehouse, J. E. Scattering and absorption of light by neutron irradiated quartz, (8) 256*i*.
Mitchell, F. Cement composition for high temperature wells, P (7) 194*d*. Low density cement composition, P (7) 194*g*.
Mitchell, J. G., and Stover, W. A. Heat treating of powdered particle material, P (8) 251*d*.
Mitchell, J. K., and El Jack, S. A. Fabric of soil-cement and its formation, B (8) 259*h*.
Mitchell, L. Efficiency in brickmaking—use of machinery, (5) 130*j*.
Mitoff, S. P. Bulk versus surface conductivity of MgO crystals, (5) 149*i*.
Mitra, S. S. See Jasperse, J. R.; Marshall, R.
Mitra, S. S., and Brada, Y. U centers in CsBr, (10) 327*b*.
Mitrofanov, A. S. See Nechiporenko, E. P.
Mitrofanov, K. P. See Gendler, T. S.
Mitsch, P. See Steeb, S.
Mitsche, R. T., and Hayes, J. C. LPG-reforming process in the presence of sulfur and catalyst comprising platinum, alumina, and a molecular sieve, P (5) 148*d*.
Mitsubishi Atomic Power Industries, Inc. Method of producing a sintered uranium dioxide nuclear fuel element containing a boride, P (2) 47*a*.
Mitsubishi Genshiryoku Kogyo Kabushiki Kaisha. Vacuum extrusion shaping of ceramic materials, P (9) 275*g*.
Mitsubishi Jukogyo Kabushiki Kaisha. Method and compositions for inspecting leakage with gas pressure testing, P (9) 277*f*.
Mitsuhashi, H., Chikawa, Jun-ichi, and Nakayama, T. Luminescence from plastically bent crystals of cadmium sulfide, (5) 154*j*.
Mitsuma, T. See Ishikawa, R.
Mittenbuehler, A. Thermal conductivity of basic brick for the steel converter, (7) 203*i*.
Miura, T. See Miyoshi, S.
Miura, Y., and Matukura, Y. Investigation of silicon-silicon dioxide interface using MOS structure, (3) 82*c*.
Miura, Y., Tanaka, S., Matukura, Y., and Osafune, H. Silicon dioxide films doped with phosphorus, (7) 208*b*.
Miwa, H. See Iida, S.
Miyahara, S. See Aso, K.; Kino, Y.; Kondo, H.; Sawaoka, A.
Miyairi, H. See Murakami, K.
Miyake, T. Carrier and potential distribution at high electric field in semiconductive CdS, (8) 252*e*.
Miyake, T., and Onuki, M. High-field Hall effect of semiconducting CdS, (4) 111*f*. Photoconductivity (ac) of CdS crystals, (5) 156*j*.
Miyatake, K., and Kaita, T. Results of tests on the corrosion of cupola refractories by molten pig iron, (9) 269*d*.
Miyatani, K., Kohn, K., Kamimura, H., and Iida, S. Nuclear magnetic resonance of paramagnetic Co_3O_4 (I) experimental study, (4) 113*c*.
Miyayama, A. See Kotera, Y.
Miyazaki, H. Change by heating of calcium sulfate hemihydrate, (2) 36*g*. Effect of hydrothermal treatment temperature and time on the formation of calcium sulfate hemihydrate from its dihydrate, (7) 194*g*.
Miyazaki, K. Use of carbon monoxide in low-temperature sintering of high density UO_2 pellets, (10) 304*i*.
Miyoshi, S. Method for extending the service life (in heats) of a 60-ton LD converter ladle lining, (7) 202*h*.
Miyoshi, S., Miura, T., and Arai, T. Spacers for multiple sheet glass glazing unit, P (2) 42*e*.
Mize, J. P. See Long, R. K.
Mizoguchi, T., and Inoue, M. Nuclear magnetic relaxation in magnetite, (10) 323*i*.
Mizukusa, S. See Aoki, S.; Hayashi, H.; Nakayama, N.
Mizuno, M. See Noguchi, T.
Mizushima, K. See Iida, S.
Mizushima, K., and Iida, S. Effective in-plane anisotropy field in α-Fe_2O_3, (10) 320*b*.
Mizushima, Y. See Yamaguchi, M.
Mizushima, Y., Igarashi, Y., and Ochi, O. Thin film negative resistance semiconductor device, P (5) 143*b*.
Mizuta, H. See Kawamura, S.
M.K.B. Industries, Inc. Shuttle kiln, P (3) 77*a*.
Mlaker, G. J. See Leitner, K.
Moacanin, J., and Simha, R. Some consequences of the Gibbs-DiMarzio theory of the glass transition, (5) 128*i*.
Moak, D. P. See Stellrecht, D. E.
Mobay Chemical Co. Laminated safety glass, P (9) 265*g*. See Monsanto Co.
Moberg, W. L. See Frank, R. I.
Mobil Oil Corp. Alkali metal and alkylammonium phosphatoaluminate complexes and the preparation of crystalline aluminosilicates, P (9) 279*b*. Catalytic conversion of hydrocarbons with the use of a steam treated Y type of crystalline aluminosilicate, P (10) 318*a*. Catalysts having improved thermal stability and method of preparing them, P (10) 317*j*. Cement composition for high temperature wells, P (7) 194*d*. Crystalline zeolite ZK-21, P (3) 78*a*. Electrochemical electrode, P (7) 195*c*. Heat treating of powdered particle material, P (8) 251*d*. Low density cement composition, P (7) 194*g*. Method for removing ammonia from an ammonium zeolite, P (1) 13*j*. Novel cyclic catalytic process for the conversion of hydrocarbons, P (4) 105*a*. Process for producing desiccants, P (4) 105*e*. Production of the hydrogen ion exchanged form of a crystalline zeolite, P (7) 215*a*. Production and use of hydrocarbon conversion catalysts comprising acid treated crystalline aluminosilicates, P (5) 149*d*. Synthetic zeolite, P (7) 215*f*. Thermoluminescent characterization of quartziferous materials, P (9) 277*i*.
Mochel, V. D. Process for making humidity sensing device, P (5) 130*c*. Red emitting Al_2O_3 based phosphors, (7) 208*a*.
Mock, J. A. Control glass properties with films and coatings, (4) 93*e*. Study fracture surfaces to predict metal failures, (3) 76*h*.
Modarresi, H. G. Simple and effective device for gravity separation of heavy mineral grains, (8) 248*g*.
Modde, M. F., and Lawrence, W. G. Foamed clay-water systems for lightweight aggregate production, (4) 95*i*.
Model, F. S. See Chopoorian, J. A.
Moebius, R., and Matthes, F. Thermogravimetry of rare earth metal oxalate hydrates, (4) 118*j*.
Moeck, M. Lightweight aggregate—manufacture and use, (1) 10*i*.
Moehl, R. W. Production of attrition resistant alumina particles, P (7) 215*f*.
Moeller, C. W. See Callaghan, A.
Moffat, A. R. L. Measurement of thermal properties, B (4) 122*f*.
Mogg, D. W., and Shea, F. L., Jr. Manufacture of a lightweight insulating product, P (1) 13*a*.
Mogosanu, E. See Mircea, S.
Moharram, M. A. See Nasser, M. I.
Mohler, D., and Salomon, A. N. Electrical capacitor, P (5) 141*a*.
Mohr, A. J., Jr. See Buyers, A. G.

Mohr, W. C., and Magid, H. S. Evaluation and selection of clays for cast whiteware bodies, (1) 15*j*.
Mohtadi, M. F. See Masters, K.
Moiola, R. J., and Weiser, D. Textural parameters—an evaluation, (9) 287*h*.
Moisand, H. Earthenware and porcelain tableware, (3) 70*a*.
Moiset, P. Separation of the constituents of fly ash, (6) 165*c*.
Moitra, S. L. Improved nozzle for steel plants and foundries, P (3) 68*g*.
Moitra, S. L., and Panda, J. D. High alumina refractory brick, P (5) 135*d*.
Moll, O. See Leitner, K.
Mollard, P. See Montmory, M. C.
Molle, L. See Hanocq, M.
Molnar, P. Modern refractories—modern kilns, (1) 11*i*.
Molthan, H. D. See Gray, F.
Mones, A. H. See Boyd, J. R.
Monfore, G. E. Electrical resistivity of concrete, (10) 294*f*.
Monks, J. R., Jr. Glass melting method, P (4) 94*c*.
Monot, P. Apparatus for the production of a coating layer of glass material, P (10) 300*b*.
Monsanto Co. Alkaline earth metal hydroxylapatites, processes for preparing, and compositions containing them, P (7) 204*d*. Apparatus for densifying powdered solids, P (7) 214*h*. Article containing silicon carbon fibers, P (9) 270*a*. Chemical compositions and processes, P (5) 148*a*. Electric resistance heaters, P (10) 309*b*. Flash photolysis spectroscopic system, P (3) 70*f*. Laminated safety glass, P (11) 336*b*. Preparation of III-V compounds, P (4) 100*j*. Process for the preparation of sintered metallic oxide catalyst pellets, P (1) 25*i*. Process of preparing an organosilica aerogel, P (1) 25*i*. Process for preparing silica aquasols, P (6) 183*a*. Process for the production of boron phosphide, P (11) 349*i*. Stable alkaline colloidal silica sols of low viscosity and processes for preparing, P (1) 26*a*. Treatment of coverplates for glass laminates, P (9) 266*b*. Two-phase thermoelectric body comprising a boron-carbon matrix, P (1) 19*c*.
Monsanto Co. and Mobay Chemical Co. Laminated safety glass, P (9) 265*h*.
Monsanto Chemicals, Ltd. Mold and process of coating foamed pattern with refractory filler and silicon-containing binder, P (2) 47*d*.
Monsanto Research Corp. Graphite containing segmented thermoelement and method of molding, P (10) 304*d*. Method of producing thermoelectric bodies, P (4) 100*g*.
Mont, G. E. See Lavin, E.
Montagmir, J. See Kiehl, J. P.
Montalenti, G. See Ferro, A.
Montecatini Edison S.p.A. Catalytic process for the preparation of nitriles, P (5) 148*a*. Process for preparing spheroidal fluorinating agents containing calcium fluoride suitable for fluid beds and product, P (6) 183*a*.
Montecatini Edison S.p.A. and Vetrocoke S.p.A. Apparatus for continuous glass spinning, P (8) 235*c*.
Montet, G. L. Detection of vacancies in molybdenite, (1) 351*j*.
Montgomery, D. S. See Machin, W. D.
Montgomery, T. S. See Barr, F. A.
Montmollin, J. P. de, and Gugger, R. Method of terminating a heating glass structure, P (8) 235*j*.
Montmory, M. C., Bertaut, E. F., and Mollard, P. Magnetic structure of Cr_2WO_6, (11) 354*j*.
Montmory, R. Process for the epitaxial growth of semiconductor layers on metal supports, P (8) 245*b*.
Moodie, A. F. See Cockayne, D. J. H.
Moody, W. E. See Archer, J. R.
Mooi, J. See Gring, J. L.
Mooney, E. F. See Gerrard, W.
Moore, E. W., and Ross, J. W. Cationic glass electrode response in aqueous solutions of sodium chloride and potassium chloride, (4) 102*f*.
Moore, F. D. Vibratory mill, P (10) 312*i*.
Moore, H. Economic evaluation of all-electric glass melting, (2) 38*j*.
Moore, J. W., and Van Vlack, L. H. Preferred orientation in microstructures of eutectics between compounds, (9) 285*g*.
Moore, M. D., and Birks, R. K. Treatment of metallic ferrites, P (9) 275*c*.
Moore, P. J. System for making a series of temperature measurements, P (10) 316*f*.
Moore, R. E. See Keilholtz, G. W.
Moore, R. J. See Mayer, E. H.
Moore, W. G. Method of preparing manganese dioxide, P (3) 78*c*.
Moore, W. H., and Green, C. A. Process of producing a cast member having a varying graphite structure, P (2) 42*e*.
Moore, W. J. See Barry, T. I.; Lehmann, G.
Moorthy, V. K. Influence of origin of UO_2 on the microstructure of sintered urania pellets, (1) 11*a*.
Moorthy, V. K., and Bhat, R. Sintering of beryllia (III) studies on hot-pressing of beryllium oxide derived from hydroxide, (5) 134*b*.
Moorthy, V. K., and Mishra, C. S. Effect of minor additions on the sintering behavior of uranium dioxide, (1) 11*g*.
Moorthy, V. K., Zope, B. D., and Chakravorty, D. M. Studies on the preparation of uranium carbide, (1) 12*e*.
Morain, M. See Acloque, P.
Moreau, C. See Blum, P.
Morehead, F. F. See Crowder, B. L.; Mandel, G.
Morel, P. See Alexanian, C.
Morey, G. W. See Rowe, J. J.
Morgan, C. S., and Bowen, D. H. Inert gas bubbles in neutron-irradiated magnesium oxide, (4) 111*e*.
Morgan, C. T., and Coulter, W. H. Electronic particle study apparatus and vessel construction therefor, P (11) 347*g*.
Morgan, J.R. See Gastel, D. G.
Morgan, M. E. Pneumatic conveyors for dry portland cement, P (6) 166*a*.
Morgan, T. N. See Nathan, M. I.
Morgan, W. C. Relation of accommodation factors in graphite, (10) 325*b*. See Halas, D. R. de.
Morgan Refractories, Ltd. Refractory products, P (7) 205*d*.
Morganite Carbon, Ltd. Refractory bricks, P (1) 14*g*.
Morganite Crucible, Ltd. Refractory sleeve sheaths, P (2) 48*b*.
Morganite Research & Development, Ltd. Bearings, P (5) 134*d*. Treatment of silicon carbide, P (5) 136*d*.
Morgenstern, N. R., and Tchalenko, J. S. Microscopic structures in kaolin subjected to direct shear, (10) 323*i*. Optical determination of preferred orientation in clays and its application to the study of microstructure in consolidated kaolin (I, II), (9) 285*b*.
Morgenthaler, F. R. See Rezende, S. M.
Mori, S. Summary of discussions on the standardization of corrosion test methods by adopting the crucible method, (10) 304*d*.
Morii, T. See Ichikawa, Y.
Morikawa, H. See Suito, E.
Morikawa, K., and Yamaka, E. Electroluminescence in CdTe diodes, (8) 253*c*.
Morin, L. H. Traveler inserts including ceramic wear resistant element, P (5) 126*c*.
Morioka, S. Nonequilibrium flow of a weakly ionized gas past a magnetized wall, (4) 113*b*.
Morita, A. See Nara, H.; Shindo, K.
Morita, Y. Method of making titanium dioxide nacreous pigment, P (11) 349*b*.
Moriyama, K. See Shoda, K.
Moriyama, K., and Shoda, K. Semiconductor device with novel isolated diffused region arrangement, P (8) 246*f*.
Moriyama, T. See Shiraishi, S.
Morizane, K., Witt, A. F., and Gatos, H. C. Impurity distributions in single crystals (I) impurity striations in nonrotated InSb crystals, (10) 322*b*.
Morize, P. Sintering of beryllium oxide, (6) 173*i*.
Morize, P., and Elston, J. Researches on sinterable BeO powder to obtain sinters of given characteristics, (3) 67*j*.
Morizumi, Y. See Murakami, H.
Morley, H. See Dominey, D. A.
Morlot, G. See Hadni, A.; Plendl, J. N.
Morog, M. See Osterholtz, C. E.
Morozov, E. I., Khromov, A. M., Ivanov, A. I., and Goloschekov, A. S. Method of making resinous shell molds, P (9) 270*f*.
Morozov, I. S., Tverskov, V. A., and Kurapova, G. I. Systems $HfCl_4$-$AlCl_3$-NaCl and $HfCl_4$-$AlCl_3$-KCl, (1) 33*g*.
Morpain, R. See Levavasseur, G.
Morrell, A. M., and Godfrey, R. H. Cathode ray tube with mosaic type phosphor screen, P (3) 72*b*.
Morrell, A. P. See Elliott, J. E.
Morris, B., Johnson, V., and Wold, A. Preparation and magnetic properties of cobalt disulfide, (8) 256*c*.
Morris, C. E. See Pollack, S. R.
Morris, J. B. See Williams, G. H.
Morris, J. W. Glass articles, P (11) 336*a*.
Morris, M. C. See Swanson, H. E.
Morrison, J. J. See Whitehurst, H. B.
Morrissey, J. W. See Bopp, H. F.
Morse, H. E. Customer standards and quality of plain ware, (10) 297*f*.
Morse, L. E. Extraction method for preparing UO_2 microspheres, P (5) 134*j*.
Mortland, M. M. See Cloos, P.; Dowdy, R. H.
Mortlock, A. J. See Harding, B. C.
Morton, W. A. Lehr with transverse temperature control, P (7) 198*i*.
Moser, C. M. See Richards, W. G.
Moser, J. B. See Kruger, O. L.
Moser, J. B., and Kruger, O. L. Thermal conductivity and heat capacity of the monophosphide and monosulfide of plutonium, (8) 258*a*.
Moser, P. See Dautreppe, D.
Mosesson, R. M. Cathode sputtering [triode] apparatus with plasma confining means, P (10) 309*h*.
Moshkina, V. A. See Fridman, Ya. D.
Moskowitz, D. See Humenik, M., Jr.
Moss, H. Cathode-ray tube generating circular beam by lineal filament critically spaced from circular aperture, P (8) 244*a*.
Moss, H. I. See Gordon, I.
Mossler, J. H., and Hayes, J. B. Ordovician K bentonites of Iowa (abstract), B (7) 224*f*.
Mossman, M. H., Freas, D. H., and Bailey, S. W. Orienting internal standard method for clay mineral X-ray analysis, B (9) 289*j*.
Mostetzky, H. See Lapoujade, P.
Mostyn, R. A. See Hoare, H. C.
Moteki, K. See Nishino, T.
Motokawa, M. See Date, M.
Motorola, Inc. Cathode ray tube manufacture, P (3) 72*a*, P (8) 235*c*. Cleaning of semiconductor devices, P (8) 244*c*. High voltage semiconductor rectifier with a sloping surface across barrier edge, P (11) 343*g*. Method of making a semiconductor device having improved *pn* junction avalanche characteristics, P (1) 18*c*. Method of making a semiconductor device by masking and diffusion, P (10) 310*b*. Remote cutoff field effect transistor, P (3) 74*c*.
Motosi, A. Shaking-funnel device for the gravity concentration of solid particles, P (5) 144*f*.
Motson, J. F. Electroluminescent lamp with alternatively defined and undefined indicia, P (11) 343*d*.
Mott, D. L. Spectra of X-ray absorption in the *K* shell of Si in gaseous $SiCl_4$ and in the *L* shell of Ge in gaseous $GeCl_4$, (9) 286*d*.
Mott, N. Solid state, B (11) 358*h*.
Mottershead, D. See Bridge, H.
Motz, H. Microwave emission of indium antimonide, B (10) 329*g*.
Motzfeldt, K. See Herstad, O.
Moulding, K. W. See Beale, J. R. A.
Mountvala, A. See Blum, S.
Mowatt, T. C. See Hower, J.
Mowrey, F. W. Technological progress in the flat glass industry, (2) 40*d*.
Moyer, J. R. Process of cleaning porcelain surfaces, P (8) 229*j*.
Moyer, J. R., Evans, J. C., and Lo, G. Y. S. Raman spectroscopic study of the molten salt system $ZnCl_2$-KCl, (10) 324*d*.
Moyson, J., and Petruzella, J. *Pnpn* switch with $10 < (N_B/N_E) < 100$ so that conductivity modulation results during turnoff, P (3) 73*j*.
Mozley, R. H. See Muller, L. D.
Mozzherin, Yu. V. New method of varioscopic microscopy in crystal optics, (7) 212*f*.
Mozzhukhin, E. I. See Elyutin, V. P.
Mozzi, R. L., and Paladino, A. E. Cation distributions in nonstoichiometric magnesium ferrite, (5) 149*j*.
M & T Chemicals, Inc. Analytical method for determining active fluoride in acid solution, P (10) 316*g*.
Muan, A. See Johnson, R. E.; Schwerdtfeger, K.
Muehe, F. J., and Schumacher, H. Hybrid circuits in thick and thin film techniques, (10) 307*c*.
Muehlhause, C. O. Material radiation environment, B (4) 120*i*.
Muehling, G., and Stoll, W. Plutonium distribution in molten $(U,Pu)O_2$ fuel materials, (7) 202*e*.
Mueller, A., and Wilhelm, M. Quasi-binary section InSb–NiSb in the ternary system In–Sb–Ni, (1) 31*e*.
Mueller, F. Grinding mill plant, P (11) 345*i*. Installation and method for firing materials such as limestone, P (10) 317*b*.
Mueller, H. Separation of substances, P (10) 318*g*.
Mueller, J. See Clasen, H.; Rosendahl, A.
Mueller, L. Filter press, P (1) 20*a*.
Mueller, N. See Hoppe, W.
Mueller, R., and Guenthard, H. H. Spectroscopic study of the reduction of nickel and cobalt ions in sapphire, (7) 221*f*.
Mueller, W. Prefabrication and building with prefabricated parts in France, (10) 328*a*. See Schmidt, A.
Muench, J. L., Sr. Mixer, P (6) 179*f*.
Muenchberg, W. See Obst, K. H.
Muenow, D. W. See Ficalora, P. J.
Muetterties, E. L., and Knoth, W. H. Polyhedral Boranes, B (5) 161*d*.
Muhler, J. C. Prophylactic dental paste compositions comprising zirconium silicate and tin dioxide, P (7) 193*i*.
Muir, A. H., Jr. See Gonser, U.
Muir, A. H., Jr., and Wiedersich, H. Investigation of $CuFeO_2$ by the Moessbauer effect, (3) 71*f*.
Muira, N. See Asai, S.
Mukai, H., and Irita, Y. Indium antimonide tunnel diodes, (5) 138*g*.
Mukerjee, T. See Adams, N.
Mukerji, J., and Biswas, S. R. Solubility of ruthenium in soda-silica glasses, (4) 93*j*.
Mukherjee, A. See Ghosh, S. K.; Sharma, S. K.
Mukherjee, D. K., and Ray, S. Investigation of some Indian clays to replace Rajmahal china clays, (7) 214*e*.
Mukherjee, K. Modified melting law at high pressures, (1) 30*j*.
Mukherjee, P. C. Glass molding device, P (2) 41*a*. Process for making improved silica sand molds, P (2) 47*k*.
Mukhina, R. E. See Zhechkova, L. A.
Mukhopadhyaya, M., and Chatterjee, M. Effect of alkali, lime, TiO_2, Fe_2O_3, etc., on the spalling characteristics of fireclay refractories, (5) 131*h*.
Mulaskey, B. F., Harnsberger, H. F., and Lindquist, R. H. Method for adjusting the initial activity of chromia-alumina catalysts, P (1) 25*d*.
Mulay, I. L. See Mulay, L. N.
Mulay, L. N., and Mulay, I. L. Magnetic susceptibility—aspects of instrumentation and applications to chemistry and solid state science, (8) 248*a*.
Mulder, B. J., and Jonge, J. de. Quantum efficiency of photoconduction in lead oxide, (11) 355*g*.
Mulfinger, H. O. See Upadhyaya, V. G.
Mulford, R. N. R. See Olson, W. M.

Mullan, J. J., and Prentice, W. H. Binder distribution method for producing mineral wool board, P (1) 12*i*.

Mullard, Ltd. High frequency dielectric heating apparatus, P (1) 24*r*.

Mullen, L. R. See Park, J. J.

Muller, L. D., Sayles, C. P., and Mozley, R. H. Apparatus for the separation of granular materials, P (10) 317*h*.

Muller, M. W. See Sher, A.

Muller, R. S. See Dore, B. V.

Mulligan, R., and Jambor, J. L. Tin-bearing silicates from skarn in the Cassiar district, northern British Columbia, (9) 279*a*.

Mullin, J., Berry, J. M., and Gatti, A. Fundamental fracture mechanisms applicable to advanced filament reinforced composites, (10) 303*a*.

Mullin, J. B. See Hurle, D. T. J.

Multer, R. K. Let's make clay an engineering material (I–III), (2) 56*j*.

Mumbach, N. R. See Flanigen, E. M.

Mumpton, F. A. See Naumann, A. W.

Mumpton, F. A., and Thompson, C. S. Stability of brucite in the weathering zone of the New Idria serpentinite, B (8) 259*f*.

Munakata, C. Voltage induced by an electron beam in a bulk semiconductor crystal, (8) 258*b*.

Munakata, C., and Watanabe, Hiroshi. Measurement of resistance by means of electron beam (II), (11) 354*d*.

Mundell, J. M. See Anderson, O. B.

Mungan, N., and Jessen, F. W. Studies in fractionated montmorillonite suspensions, B (5) 160*j*.

Munier, J. M. See Hadni, A.

Munir, Z. A. See Fitzpatrick, R. L.

Munir, Z. A., and Searcy, A. W. Activation energy for the sublimation of gallium nitride, (3) 78*h*.

Munro, D. C. See Bradley, R. S.

Munro, W. Method of fabricating mixed ceramic compacts, P (1) 13*c*.

Munson, R. A. High-temperature behavior of beryl and beryl melts at high pressure, (1) 29*b*.

Murabayashi, M., Yonezawa, K., Koga, Y., and Katura, T. Coprecipitated triple carbonates for receiving tube cathode, (2) 49*d*.

Murakami, H., and Morizumi, Y. Dielectric shield for ultrahigh frequency thermionic tubes, P (4) 99*g*.

Murakami, K. See Tanaka, H.

Murakami, K., Hanada, K., and Miyairi, H. Process for the continuous production of gypsum and iron oxide from waste sulfuric acid pickle liquor and a calcium compound, P (7) 194*i*.

Murakami, T. PTCR effect in $BaTiO_3$ single crystals, (5) 157*j*. See Terasaki, Y.

Muramori, K., Yaguchi, K., Watanabe, Katsumi, and Abe, H. Method for introducing calcium oxide into manganese-zinc ferrite magnetic materials, P (7) 209*f*.

Muramoto, M. See Henderson, J. R.

Murase, C. Logarithmic dependence on impurity density of electrical conductivity, (10) 322*d*.

Murasik, A. See Amin, R.

Murata, Y., and Whitney, E. D. Densification and wear resistance of ceramic systems (II) tantalum mononitride-titanium diboride, (8) 237*c*.

Murbach, E. W. Production of stoichiometric uranium monocarbide from a uranium fluoride, P (1) 14*f*.

Murdock, J. P., and Schroeder, J. E. Method [solder] of forming ohmic contacts in semiconductor devices, P (11) 344*f*.

Mureinik, R. J. See Hall, P. G.

Murphy, C. B. Thermal analysis, (10) 316*a*.

Murphy, J. A. High temperature furnace conveyor, P (9) 278*e*.

Murphy, J. C. See Artman, J. O.

Murphy, N. A., Lightfoot, D. G., and Irlam, P. S. Manufacture of cellular material on a molten metal bath, P (4) 94*e*.

Murphy, R. T. See Ellis, M. P.

Murray, D. W., and King, L. K. Method for fabricating multiple glazing units, P (4) 95*a*.

Murray, F. L., Jr., and Sikina, T. V. Thin-film RC circuits on single substrate, P (8) 246*f*.

Murray, H. H. See Bundy, W. M.

Murray, R. S., and Andrews, R. Mat surface vitreous enamels and articles made therefrom, P (8) 229*i*.

Murray Corp. of America. Crystalline bonded ceramic ware pressing mold and method of making, P (8) 242*d*.

Murthy, M. V. N. See Ray, I.

Murton, C. B. Stopper for a ladle or similar receptacle, P (2) 48*b*.

Musikant, S. See Krakauer, S.

Musikhin, V. I., Sergin, B. I., Lepinskikh, B. M., and Pliner, Yu. L. Methods for the study of the kinetics of fast high-temperature processes, (10) 314*j*.

Musschoot, A., and Thomson, M. G. Method and apparatus for agglomerating on inclined surfaces including vibrating the material at a greater angle than the inclination of the surface, P (5) 144*c*.

Mustacchi, C. See Giuliani, S.

Muszkiewicz, H. See Kopineck, H. J.

Muta, A. Recorder for analyzing particle size distributions of powders, P (7) 213*b*.

Muto, N. See Yabumoto, T.

Myatt, E. R., and Loveland, E. F. Ceramic reed relay, P (9) 272*b*. Ceramic reed relay having flux carrying means associated with the armature, P (9) 272*c*.

Myers, E. See Rubenstein, M.

Myers, E. H. See Jalbing, J. I.

Myers, J. G. See Bienstock, D.

Myers, M. B., and Felty, E. J. Structural characterization of vitreous inorganic polymers by thermal studies, (1) 7*a*.

Myklebust, R. L. See Ampian, S. G.

Myshlyaeva, L. V., and Sedova, I. V. Extractive-conductometric method for the determination of silicon, (10) 314*b*.

Myshlyaeva, V. V., and Osokina, T. A. New standard for methods of chemical analysis of cements, (3) 62*c*.

Nabarro, F. R. N. Steady-state diffusional creep, (8) 257*d*.

Naber, C. T., and O'Neal, J. E. Deposition of silicon on sapphire in ultrahigh vacuum, (10) 306*j*.

Nabutovskaya, O. A. See Strelkov, P. G.

Nachbar, M. S. Electrolysis-resistant electron discharge device, P (5) 141*e*.

Nadgornyi, E. M., Grigor'eva, L. F., and Ivanov, A. P. Effect of heat treatment on mechanical properties of fibers of natural and synthetic amphiboles, (2) 44*a*.

Nadler, M. Anhydrous magnesium chloride production, P (11) 349*e*.

Nadler, M. R. See Kempter, C. P.

Nag, A. See Ward, L.

Nagai, C. Comparison of test results of 60-ton basic electric furnace ladle lining of roseki brick and zircon brick, (7) 200*b*.

Nagai, H. See Ono, M.

Nagai, K. See Tarui, Y.

Nagai, S. Cohesive energy of an MnO crystal, (3) 79*h*.

Nagasawa, M. See Watanabe, T.

Nagase, K. See Matsuo, Y.; Nitta, T.

Nagata, T., Hirohata, H., Ishibashi, M., and Arimura, S. Piezoelectric ceramic resonator devices, P (1) 18*j*.

Nagels, P. See DeConinck, R.

Nagornyi, G. I. See Finkel'shtein, N. A.

Nahin, P. G. Organoclays bonded to polyethylene by ionizing radiation, B (7) 224*j*.

Nahum, J. See Mackey, J. H.

Naidich, Yu. V., and Kolesnichenko, G. A. Investigation of the wetting of diamond and graphite by molten metals and alloys (IV) influence of temperature on the adhesion of metals inert to carbon, (7) 195*f*.

Naidich, Yu. V., and Lavrinenko, I. A. Capillary adhesion forces between solid particles with an intermediate liquid layer at the contact (II) effect of degree of wetting, (9) 279*j*.

Naidu, S. V. N. See Rao, K. V. K.

Naka, S. See Suwa, Y.

Naka, S., Takenaka, O., Sekiya, T., and Noda, T. Effect of pressure on the formation of compounds in the Y_2O_3–Al_2O_3 system, (7) 217*d*.

Nakada, R., Ebina, A., and Takahashi, T. Electron spin resonance of Fe^{3+} in SnO_2, (4) 109*c*.

Nakagawa, J. See Kawashima, C.

Nakagawa, K. See Yanagida, O.

Nakagawa, T. See Nomura, S.

Nakagawa, T., and Nomura, S. Atomic arrangements in $Sr(FeTa)_{1/2}O_3$–$Sr(CrTa)_{1/2}O_3$ system, (10) 319*a*. Crystal distortion in $Sr(Fe_{1/2}Ta_{1/2})O_3$ and some of its solid solutions, (8) 252*j*.

Nakahigashi, K. See Saito, S.

Nakahira, M. Electrical resistance measurements of kaolinite and serpentine powders during dehydroxylation, B (6) 191*f*. See Copp, A. N.

Nakahira, M., and Kato, T. Thermal transformations of pyrophyllite and talc as revealed by X-ray and electron diffraction studies, B (6) 191*f*.

Nakaji, S., and Takada, I. Material for replaceable molten iron tapping spout of blast furnace, (8) 238*d*.

Nakajima, M. See Tagai, H.

Nakajima, N. Method and apparatus for manufacturing glass beads, P (4) 94*i*.

Nakajima, N., Numazawa, T., and Sakamoto, Y. Results of service test on ladle with dolomite brick lining, (7) 203*d*.

Nakajima, S. See Okazaki, C.

Nakajima, T., Tojo, T., and Kondo, M. Measurements of material buckling of U–H_2O assembly, (9) 267*i*.

Nakajima, Y. See Horiba, T.

Nakajima, Y., Gotoh, K., and Tanaka, T. On-line particle size analyzer, (3) 76*b*

Nakamichi, H. See Kawakita, K.

Nakamichi, T. Interpretation of the antiferromagnetic magnetostriction in CoO single crystals, (4) 111*h*.

Nakamoto, M. See Hosokawa, M.

Nakamura, A. See Minkiewicz, V.

Nakamura, K. See Okubo, T.

Nakamura, K., and Kuroo, Y. Method of making a semiconductor device, P (9) 274*b*.

Nakamura, M. See Yamagishi, K.

Nakamura, T. Discontinuous resistance semiconductor device, P (3) 72*d*. Single-oscillator model of the "soft-mode" lattice vibration in the perovskite-type ferroelectrics, (4) 115*g*.

Nakamura, T., and Ishibashi, Y. Temperature dependence of the infrared reflectance spectrum of $BaTiO_3$, (10) 326*d*.

Nakamura, T., and Midorikawa, M. [111] twin in single crystal films of $BaTiO_3$ on LiF, (10) 326*j*.

Nakamura, T., and Nomura, S. Dielectric properties in $BaTiO_3$–$BaSnO_3$ and $BaTiO_3$–$Ba(Fe_{1/2}Ta_{1/2})O_3$ systems, (11) 351*a*.

Nakamura, Y. See Sato, K.; Shinjo, T.

Nakano, T. See Hayashi, T.; Kinoshita, A.

Nakanuma, S. Device for manufacturing epitaxial crystals, P (8) 244*b*.

Nakashima, C. See Ohba, H.

Nakashima, H., Sugano, T., and Yanai, H. Epitaxial growth of SiC film on silicon substrate and its crystal structure, (11) 352*d*.

Nakashiro, F. M. Undulatory range and crystal size of quartz, (1) 33*c*.

Nakata, R. See Mankoff, L. L.

Nakatsuka, K. See Sato, T.

Nakaya, T. Measurement of fractional metastable-state population of Cr ions in ruby under Q-switching operation, (8) 255*d*. Measurement of ground-state population in ruby under optical pumping, (3) 83*j*.

Nakayama, N. See Hayashi, H.

Nakayama, N., Kokiso, S., Mizukusa, S., Hasegawa, K., Hata, T., Ota, E., Kubo, K., Kozuka, T., Sawamoto, H., Yamamoto, T., and Iijima, K. Study of tetrahedral anvil apparatus for high pressure and high temperature research, (9) 277*i*.

Nakayama, T. See Collins, F. C.; Mitsuhashi, H.

Nakayama, T., and Hoffman, L. C. Performance data on thick-film crossovers, (7) 207*e*.

Nakazawa, Y., Uetsuki, T., and Uei, I. Mineral constitutions of zircon-dolomite refractories fired at 1500°C, (8) 239*b*

Nalco Chemical Co. Metal ingot mold with protective [refractory] coating, P (11) 332*i*. Method of stabilizing silica sols, P (1) 25*g*. Nonaqueous silica sols and method of preparing, P (2) 56*j*. Process of making alumina, P (10) 318*a*.

Nale, R. F., and Cassidy, R. W. Dome-shaped electric furnace roof construction, P (3) 68*c*.

Naloichenko, L. V. See Piven, I. Ya.

Nameishi, N. Low temperature burned refractory brick and method of making, P (5) 135*g*. Refractories for LD oxygen converters, (10) 303*j*. See Funahashi, Z.

Nameishi, N., and Inoue, A. Temperature distribution and atmosphere in electric and oil-burning furnaces, (10) 304*f*.

Namikawa, H. Anomalies of dielectric properties in glasses of the BaO–P_2O_5 system, (8) 230*e*.

Namikawa, H., and Asahara, Y. Electrical conduction and dielectric relaxation in BaO–P_2O_5 glasses and their dependence on water content, (8) 231*j*.

Nanda, V. S., and Simha, R. Equation of state of polymer liquids and glasses at elevated pressures, (5) 127*j*.

Nandi, K. Study of garnets of the sillimanite zone in the Darjeeling hills, (3) 87*f*.

Nangoh, T., and Yamazaki, I. Mixer for producing self-hardening molding sands, P (9) 270*a*.

Nanis, L. See Bockris, J. O'M.

Nanney, C. A. See Garno, J. P.

Napier, D. R. Process for producing colloidal-size particles of alumina monohydrate, P (3) 78*c*.

Napier, E. See Everest, D. A.

Napier, J., and Ross, R. F., Jr. Solder method for providing standoff of device from substrate, P (10) 311*e*.

Nara, H., and Morita, A. Shallow donor potential in silicon, (10) 325*f*.

Narain, K. Clay mineral composition of certain Indian clays, (1) 27*c*.

Narasimhamurthy, G. S. R. See Mahajan, S. P.

Narayanan, V. H., Dorairaj, G., Mahadevan, Y., and Doss, K. S. Ferromagnetic detector, (10) 307*a*.

Nash, D. L. See Trumbore, F. A.

Nash, V. E. See Glenn, R. C.

Nash, W. B. See Brown, M. R.

Nassau, K. See Levinstein, H. J.

Nasser, M. I., and Moharram, M. A. Study of cotton fiber structure by infrared irradiation, B (10) 329*g*.

Nasu, S. Magnetic susceptibilities of cubic UO_{2+x} at high temperature, (11) 354*a*.

Nasu, S., Shiozawa, Ken-ichi, and Kikuchi, T. Fission fragment damage in epitaxial film of uranium dioxide, (4) 110*b*.

Natansohn, S., and Baird, D. H. Effect of Cd-for-Zn substitution on magnetic properties of manganese zinc ferrites, (10) 307*b*.

Natanson, A. K. See Elyutin, V. P.

Natarajan, M. See Rao, G. V. S.

Natco Corp. Method for filling structural clay tile, P (1) 10*b*.

Nathan, M. I. Semiconductor lasers, (9) 272*g*.

Nathan, M. I., Morgan, T. N., Burns, G., and Michel, A. E. High-energy emission in GaAs electroluminescent diodes, (11) 353*j*.

National Academy of Science–National Research Council, Materials Advisory Board. Ceramic Processing, B (9) 288*g*. Characterization of Materials, B (8) 258*i*.

National Cash Register Co. Ferromagnetic storage devices having uniaxial anisotropy, P (10) 309*e*.

National Engineering Co. Apparatus for conditioning particulate material, P (2) 53*g*. Rotary mixer, P (6) 179*b*.

National Gypsum Co. Fire resistant wallboard, P (7) 194*e*. Gaseous apparatus for cooling pulverulent material, P (4) 92*c*. High strength gypsum plaster, P (7) 194*f*. Plaster on metal application, P (5) 125*g*.

National Lead Co. Multistage milling, P (8) 247*f*. Production of aqueous suspension of colloidal, crystalline, hydrous oxides of zirconium and hafnium, P (4) 97*f*.

National Research Corp. Process of bonding copper foil to foil containing superconductive layer such as niobium stannide, P (2) 52*c*. Process of growing silicon carbide *pn* junction electroluminescing diodes using a modified traveling solvent method, P (11) 345*d*. Process of joining bodies with boron nitride, P (5) 135*i*. Thermocouple gage control, P (11) 348*b*. Vacuum coated product, P (11) 336*h*.
National Research Council. Method of making *pn* junctions by hydrothermally growing, P (7) 209*h*.
National Research Development Corp. Apparatus for the separation of granular materials, P (10) 317*h*. Grazing incidence diffraction gratings, P (9) 277*e*. Method of glazing silicon nitride shaped body and article, P (10) 304*g*. Method of making film resistors, P (6) 178*c*. Presses for compacting electrically conductive compositions, P (8) 247*g*.
National Tile & Mfg. Co. Method and apparatus for handling and placing tile bodies in precise locations, P (2) 49*a*.
National Video Corp. Color triad tube having heat-absorptive material on aluminum screen backing for cooling shadow mask, P (10) 309*i*. Electron vacuum tube getter and method of using, P (9) 272*h*. Glass cements, P (6) 170*a*.
Natke, C. A. See Greenberg, E.
Nau, T. P., Jr. See Poffenbarger, J. D., Jr.
Naudin, F. See Boinot, J. D.; Plendl, J. N.; Zarzycki, J.
Naumann, A. W., Safford, G. J., and Mumpton, F. A. Low-frequency $(OH)^-$ motions in layer silicate minerals, B (8) 259*j*.
Navarro, J. F. See Fernandez Navarro, J.
Navazio, G. See Crepaz, E.
Navrotsky, A., and Kleppa, O. J. Enthalpy of the anatase-rutile transformation, (1) 29*a*. High-temperature calorimetry in the liquid oxide systems (III) enthalpy of formation of magnesium-aluminum spinel, (6) 186*d*.
Naweed-ul-Islam. See Safdar, M.
Naweed-ul-Islam and Safdar, M. Iron removal from glassmaking sand, (10) 317*k*.
Nayar, P. K. K. Intermetallic diffusion in the uranium-aluminum system, (6) 186*e*.
Naz, M. A. See Safdar, M.
Nazarchuk, T. N. See Minenko, N. N.
Nazarov, K. S. See Kaminskaya, E. I.
Neal, J. E., and Irvin, C. L. Method of producing asbestos-cement sheets containing cellulosic fiber, P (1) 13*g*.
Nebesar, R. J. Glass filament tape, P (10) 300*a*.
Nebrensky, J. See Kocik, J.
Nechiporenko, E. P., Krivoruchko, V. M., and Mitrofanov, A. S. Siliconizing of refractory metals under nonequilibrium conditions, (3) 68*a*.
Nechtow, M. I. Method of making oxide protected semiconductor devices, P (5) 141*j*.
Nedelec, M. Method and apparatus for tempering glass between cold plates, P (5) 130*g*.
Nedev, S. K. See Fedorov, P. I.
Needler, W. Looking at ancient Egypt in the Royal Ontario Museum, (5) 124*e*.
Neely, J. E. Refractory, P (4) 97*g*.
Neely, J. E., and Mayberry, M. L. Refractory shape, P (10) 305*a*.
Neely, J. R. Gyratory fluidized solids feeder, P (3) 75*b*.
Neely, W. C. See Preston, J. B.
Neff, P. J. Mold wash composition, P (8) 241*d*.
Neff, T. L. Equipment for measuring pore pressure in rock specimens under triaxial load, B (3) 90*j*.
Negina, V. R., Kozyreva, E. A., Balakshina, A. V., and Chikisheva, L. S. Potentiometric determination of boron in oxidizing media, (10) 315*g*.
Negoda, G. P. See Radomysel'skii, I. D.
Neichi, Y. See Okazaki, C.
Neiheisel, J., and Weaver, C. E. Transport and deposition of clay minerals in southeastern United States, (5) 148*i*.
Neill, J. L. See Meath, W. A.
Neiman, O. V., and Velikova, M. I. Colloidal phenomena in the formation of precipitates—kinetics of supersaturation change in the formation of calcium sulfate precipitates, (10) 294*b*.
Neisea, H. See Hloch, A.
Neisser, K. E., Jr. See Miller, L. F.
Neiveli Ceramics & Refractories, Ltd. Improved process of enhancing the plasticity of clays, P (5) 148*d*. Improvements in sanitary ware, P (5) 137*e*.
Nelson, B. W. Clay mineral diagenesis in the Rappahannock estuary—an explanation (abstract), B (5) 160*g*.
Nelson, C. J. See Ban, T. E.
Nelson, F. W., and Bacher, J. F. Corrosion protection process for edges of enameled products, (3) 63*c*.
Nelson, R. L. See Tench, A. J.
Nelson, R. P. Interdiffusion studies in the system α-Al_2O_3-Cr_2O_3, (2) 58*c*.
Nelson, R. S. Binding of inert gas bubbles to precipitates, (2) 43*g*. Proton scattering microscopy, (1) 31*d*. See Barnes, R. S.
Nemec, D. Miscibility of pyralspite and grandite molecules in garnet, (8) 255*g*.
Nemec, F. Mechanical behavior of magnesite brick at high temperatures, B (9) 291*b*.
Nemilov, S. V. Study of the structure of glasses of the B_2O_3–Na_2O system by viscometry, (1) 7*h*.
Nemnonov, S. A. See Men'shikov, A. Z.
Nepsha, A. V. Tarred Dolomite Refractories for Converters, B (10) 329*e*.
Neri, D. See Brambilla, G.
Neronov, V. A., and Samsonov, G. V. Preparation and properties of aluminum borides, (2) 45*d*.
Nessim, D. J., and Albright, G. P. Dry chemical feeder, P (4) 101*j*.
Nester, H. H., and Cocca, T. Achieving reliable thick film components, (11) 341*g*.
Nester, J. F., and Schroeder, J. B. Growth of calcite crystals from a molten flux by slow cooling, P (1) 25*c*. Growth of synthetic calcite single crystals, (5) 153*d*.
Nestor, L. R. Glass containing dissolved carbon, methods of making and using, and obtaining graphite, P (2) 40*j*.
Nethercot, A. H., Jr. See Gutfeld, R. J. von.
Netsch, R. Tetrafluoroethylene polymer articles having one readily cementable surface containing glass particles, P (5) 130*g*.
Nette, G. See Wendler, F.
Nettleton, R. E. Switching resonance in crystallites of barium titanate, (10) 325*h*.
Netzsch, E. Mold for the production of a ceramic article in a casting process, and a casting method using the mold, P (7) 211*f*.
Neuberger, M. See Grigsby, D. L.
Neuenschwander, E. Preparation and characterization of ultrafine carbides, nitrides, and metals, (4) 114*j*.
Neufeldt, S. J. See Carnall, W. T.
Neuman, C. H., Lawson, A. W., and Brown, R. F. Pressure dependence of the resistance of VO_2, (5) 157*f*.
Neumann, A. W. See Sell, P. J.
Neumann, H., and Wijn, H. P. J. Polycrystalline hexagonal barium ferrite of the *W* structure type with varying ferrous content, (10) 324*a*.
Neumeier, L. A. See Doerr, R. M.
Nevard, L. A. Tank and furnace walls, P (4) 95*e*.
Neville Chemical Co. Epoxy resin ink for printing on glass, P (9) 265*b*.
Nevorotina, M. I. See Shteinberg, Yu. G.
New Jersey Zinc Co. Titanium dioxide-silica pigment, P (8) 251*j*.
Newell, F. W. See Hesten, F.
Newell, F. W., and Saunders, R. J. Opposed blasthead apparatus for toughening sheets of glass with spaced vertical deflecting shields, P (4) 95*a*.
Newey, C. W. A. See Pascoe, R. T.
Newhall, D. H. High pressure [isostatic] press, P (7) 211*c*.
Newland, B. T. M. See Hoare, H. C.
Newman, A. C. D., and Brown, G. Chemical changes during the alteration of micas, (6) 184*h*.
Newman, A. J. See Gutt, W.
Newnham, R. E. Cation ordering in $Na_{0.4}Bi_{0.4}$-TiO_3, (4) 106*b*. See Farrell, E. F.; Santoro, R. P.; Segal, D. J.
Newnham, R. E., and Meagher, E. P. Crystal structure of $NiTeO_4$, (1) 27*d*.
Newport, J. J., III. See Olstowski, F.; Vaught, L. M.
Newsom, R. R. Method and apparatus for high frequency treatment of materials, P (9) 278*a*.
Newton, L. S. Efficiency in brickmaking—use of manpower, (5) 130*j*. Profitability and industrial training, (7) 223*g*.
Newton, R. G. Internationally based statistical study of the melting behavior of unit melters, (1) 6*h*.
Ney, P. Hardening of nonhydraulic lime mortars as a crystallization process, (3) 62*i*.
Neyagawashi, W. M. See Minami, S.
NGK Spark Plug Co., Ltd. Piezoelectric and electrostrictive ceramic articles of lead zirconate titanate containing manganese and tungsten oxides, P (6) 178*c*.
Nicholas, M. G. See Hodkin, E. N.
Nicholls, A. M. See Ellis, J. D.
Nicholls, G. D., Graham, A. L., Williams, E., and Wood, M. Precision and accuracy in trace element analysis of geological materials using solid source spark mass spectrography, (1) 22*h*.
Nicholls, R. W., and Tyte, D. C. Franck-Condon factors and *r* centroids for band systems of ZrO, (2) 58*i*.
Nichols, F. A. Further comments on the theory of grain growth in porous compacts, (9) 282*f*. Theory of columnar grain growth and central void formation in oxide fuel rods, (2) 46*h*.
Nicholson, G. C. Thermal decomposition of ferrous oxalate dihydrate, (5) 159*b*.
Nicholson, J. L. Large-area planar and nonplanar aluminum oxide films, (4) 98*f*.
Nickel, E. H. Structural stability of minerals with the pyrite, marcasite, arsenopyrite, and loellingite structures, (9) 278*j*.
Nickel, E. H., and Mark, E. Arfvedsonite and aegirine-augite from Seal Lake, Labrador, (1) 26*h*.
Nicol, A. W. Topotactic transformation of muscovite under mild hydrothermal conditions, B (6) 191*e*.
Nicolas, J. See Hildebrandt, M.
Nicolas, J., Quintin, M., and Douillet, P. X-ray fluorescence analysis of silicate rocks using powdered samples dispersed in silica without fusion or pelletization, (10) 316*f*.
Nicoll, F. H. Room temperature lasing of CdS under pulsed electron bombardment, (4) 115*i*.
Nicollian, E. H. See Goetzberger, A.
Nicollian, E. H., and Goetzberger, A. MOS study of interface-state time constant dispersion, (4) 113*g*.
Niebuhr, J. Lower oxides of niobium, (4) 112*c*.
Niedergesaess, G. Measurement and control of gas-heated tunnel kilns, (4) 104*c*.
Niederman, H. H., and Jensen, W. P. Vertical mixer, P (2) 53*g*.
Nielsen, T. H. See Leipold, M. H.
Niemyski, T. See Bliznakov, G.
Niesel, K. See Grzymek, J.
Niesel, K., and Thormann, P. Stability fields of dicalcium silicate modifications, (7) 221*f*.
Nightingale, E. R., Jr. Dehydration of magnesium chloride using gaseous ammonia, P (1) 25*a*.
Nightingale, R. E. See Davidson, J. M.
Nihon Gaishi Kabushiki Kaisha. Method of manufacturing articles by crystallizing glass materials, P (1) 9*e*. Method of manufacturing articles resembling porcelain from blast furnace slag, P (7) 206*h*.
Nii, R. See Yamashita, A.
Niizeki, N., and Hasegawa, M. Direct observation of antiparallel 180° domains in $BaTiO_3$ by X-ray anomalous dispersion method, (5) 151*b*.
Nijhawan, B. R. See Bhandary, V. S.
Nikex Nehezipari Kulkereskedelmi Vallalat. Machine for mixing and dividing test specimens of material, P (1) 23*i*.
Nikitin, E. E. See Kondratiev, V. N.
Nikitin, Yu. P. See Kovalenko, V. G.
Nikitina, L. V. See Larionova, Z. M.
Nikolaiski, E. New method for specifying the sensitivity of optical glasses to acids, (1) 6*b*.
Nilsson, A. See Christensen, A. N.
Nilsson, G. Ejection of uranium atoms from sintered UO_2 by fission fragments in different gases and at different gas pressures, (4) 108*j*.
Nilsson, V. R. Moisture content measuring device including capacitor electrodes differing in size, P (10) 316*c*.
Nippon Atomic Industry Group Co., Ltd. Method of preparing nuclear fuel pellets, P (6) 175*b*.
Nippon Electric Co., Ltd. Device for manufacturing epitaxial crystals, P (8) 244*h*. Dielectric shield for ultrahigh frequency thermionic tubes, P (4) 99*g*. Discontinuous resistance semiconductor device, P (3) 72*d*. Glass molded type semiconductor device, P (7) 208*j*. High frequency semiconductor diode, P (8) 244*e*. Iridium and chromium doped PZT piezoelectric ceramic composition, P (6) 177*f*. Lead zirconate-titanate-stannate piezoelectric ceramic containing thorium and iridium, P (1) 18*f*. Low melting point glass, P (7) 198*j*. Method and apparatus for breaking a semiconductor wafer into elementary pieces, P (11) 344*c*. Method of coating a shaped carbon article with a polycarbon fluoride, P (11) 340*i*. Method of piezoelectrically activating ferroelectric materials, P (4) 100*f*. Piezoelectric ceramic composition, P (2) 52*b*. Piezoelectric lead zirconate titanate ceramic with chromium and thorium additives, P (7) 209*i*. Piezoelectric PZT containing rhodium, P (7) 209*j*. Scribing method for semiconductor wafers, P (10) 311*b*. Semiconductor variable capacitance element, P (8) 246*i*. Tantalum doped nickel-zinc ferrite, P (1) 19*a*.
Nippon Telegraph & Telephone Public Corp. Thin film negative resistance semiconductor device, P (5) 143*b*.
Nippon Toki Kabushiki Kaisha. Automatic greenware replacing device for continuous pottery forming machine, P (4) 98*f*.
Nishanova, I. E. See Popil'skii, R. Ya.
Nishi, Y. Electron spin resonance in SiO_2 grown on silicon, (5) 152*b*.
Nishida, K. Correlation between laser performance and crystal homogeneities of ruby laser rods, (8) 252*i*.
Nishida, T. See Maeda, S.
Nishida, Y. Spin-lattice relaxation of Cr^{3+} coexisting with Ti^{3+} in Al_2O_3, (3) 86*g*.
Nishigaki, S., and Maekawa, K. Fabrication of BeO–UO_2–B fuel pellets, (2) 44*i*.
Nishijima, T., Fukushima, E., Ishihata, A., Wada, T., Kawada, T., and Kitagawa, H. Method of preparing nuclear fuel pellets, P (6) 175*b*.
Nishikawa, T., Ikeda, A., and Mihara, T. Relations among porosity, grain size, and chipping resistance of ferrites, (9) 286*f*.
Nishimura, T. See Kawamura, S.
Nishimura, Y. See Takahashi, H.; Yamamoto, R.
Nishimura, Y., and Berg, P. W. Effects of controlled furnace atmospheres on mechanical strength of fired ceramic body, (1) 15*k*.
Nishimura, Y., and Yamamoto, R. Penetration test of ceramic materials, (1) 22*a*.
Nishino, T., and Moteki, K. Reaction in the system CaO–Cr_2O_3–ZrO_2 (I) $CaZrO_3$–Cr_2O_3, (7) 220*j*.
Nishino, T., Moteki, K., and Nishiyama, S. Reaction in the system CaO–Cr_2O_3–ZrO_2 (II) $CaCr_2O_4$–ZrO_2, (7) 221*a*.
Nishino, T., Moteki, K., and Yoshino, K. Reaction in the CaO–Cr_2O_3–SiO_2 system, (5) 157*c*.
Nishiyama, A., and Kasamatsu, T. Method of manufacturing oxide nuclear fuel containing a boride, P (6) 174*j*.
Nishiyama, M. See Sameshima, Y.
Nishiyama, S. See Ando, J.; Nishino, T.
Nitsche, R. Ferroelectric circuit element material and transducer utilizing same, P (1) 17*h*.
Nitsevich, E. A. See Fridman, Ya. D.
Nitta, T., Taki, H., and Matsuo, Y. Semiconductive ceramic compositions with positive temperature coefficient of resistance, P (6) 178*g*.
Nitta, T., Taki, H., and Nagase, K. Electroconductive composition containing $BaPbO_3$, P (6) 177*e*.

Nitzsche, S., Pirson, E., and Schmidt, E. Method of preparing asbestos sheets from aqueous slurries containing silicone resin emulsions, P (11) 340*c*.
Nixdorf, J. See Dannoehl, W.
Nixon, W. G. See Bloch, H. S.
Nizhenko, V. I. See Eremenko, V. N.
Noake, H. See Yamaguchi, M.
Nobbs, J. McK. Effect of variations in the concentration of atmospheric constituents on the electrical conductivity of zinc oxide, (3) 71*e*.
Noble, D. C. Optic angle determined conoscopically on the spindle stage (II) selected rotation method, (9) 276*i*.
Noble, M. See Perieres, R.
Nobuoka, S., Ado, K., and Ando, T. Variations in the magnetic properties with compression of γ-Fe_2O_3 powders, (2) 50*c*.
Nobuoka, S., and Ando, T. Studies on unusual absorption bands of infrared spectra of α- and γ-FeOOH in potassium bromide disks, (9) 287*a*.
Noda, T. See Naka, S.; Suwa, Y.; Ushio, M.
Noguchi, T., and Kozuka, T. Heating curves of solids obtained by a solar furnace, (4) 111*b*. Temperature and emissivity measurement at 0.65μ with a solar furnace, (4) 117*f*.
Noguchi, T., and Mizuno, M. Freezing points of lanthanide oxides measured with a solar furnace, (4) 110*c*. Phase changes in solids measured in a solar furnace—ZrO_2–TiO_2 system, (4) 113*j*.
Noguera, F. J. G. See Gomis Noguera, F. J.
Nolte, C. R. See Strelow, F. W. E.
Nomura, A. See Minami, S.
Nomura, M. See Tamura, M.
Nomura, M., Tokuyama, T., Tauchi, S., and Takagi, T. Method of forming a semiconductor device by etching and epitaxial deposition, P (1) 18*a*.
Nomura, S. See Nakagawa, T.; Nakamura, T.
Nomura, S., and Nakagawa, T. Magnetic properties and optical and paramagnetic spectra of divalent nickel in $Sr_2(NiW)O_6$, (10) 322*g*. Structural and magnetic transition in $Sr_2(NiMo)O_6$, (7) 221*j*.
Nomura, T. See Ohba, H.
Nomura, Y. See Horiguchi, Y.
Nonoyama, H. See Imaoka, M.
Noorlander, W. Method of making a manganese oxide dielectric coating for barrier-layer capacitors, P (9) 273*j*.
Norburn, L. E. Refractory coated oxygen lance, P (3) 69*d*.
Norcross, A. S. Apparatus for measuring viscosity, P (6) 181*c*.
Norcross Corp. Apparatus for measuring viscosity, P (6) 181*c*.
Nord, S. Bell and spigot pipe joints and method of sealing and locking pipe joints, P (11) 337*f*.
Nordberg, R. C., and Barrios, H. R. Method for heat treatment of vitreous fibers, P (2) 41*c*.
Nordberg Mfg. Co. Feeder for cone crushers and the like, P (4) 105*b*. Feeders for crushers, P (8) 251*b*.
Nordland, W. A. See Miller, R. C.
Noreika, A. J. See Chu, T. L.
Noritake Iron Works Co., Ltd. Filter press, P (4) 102*b*.
Norling, B. K., and Steinfink, H. Crystal structure of neodymium tritelluride, (6) 184*c*.
Norman, E. K. See McTaggart, G. D.
Norman, L. D., Jr. See Driscoll, T. J., Jr.
Norris, D. I. R. Electron microscopy of heavy ion damage in aluminum and nickel, B (10) 329*e*.
North American Philips Co., Inc. Apparatus for manufacturing rings or cylinders of ferromagnetic material, P (5) 140*b*. Base construction for evacuated envelope housing a printed circuit and components, P (4) 99*d*. Ceramic-to-metal seal, P (5) 140*g*. Dispenser cathode, P (6) 177*d*. Electric conductor suitable for being sealed in the wall of an electric discharge tube, P (7) 208*b*. Electric incandescent lamp with levitating incandescent body, P (8) 235*h*. Electromechanical transducer employing piezomagnetic manganese ferrous ferrite, P (7) 208*f*. Field-effect transistor with improved transmission admittance, P (3) 72*g*. Heat and pressure glass bonding of spaced magnetic head portions by forming and using glass overflow channels, P (7) 209*a*. Hermetic electrical lead-in assembly, P (6) 177*c*. Lithium nickel ferrite magnetic switching element, P (7) 209*b*. Low capacity and resistance transistor structure employing a two-conductivity collector region, P (7) 209*c*. Method of etching the contacts on a transistor to improve the power output therefor, P (9) 273*i*. Method of forming glass bonded [transducer] heads, P (5) 141*h*. Method of forming a refractory metal-to-ceramic seal, P (9) 273*d*. Method of making a double diffused semiconductor device by a double masking step, P (4) 100*b*. Method for making electrically conductive vitreous materials, P (1) 9*d*. Method of making a manganese oxide dielectric coating for barrier-layer capacitors, P (9) 273*j*. Method of manufacturing aluminum nitride, P (11) 340*b*. Method for manufacturing lithium-nickel-manganese ferrite magnetic memory cores, P (6) 178*g*. Method of manufacturing a magnetic memory core, P (6) 178*h*. Method of manufacturing semiconductor devices such as transistors and diodes and the devices made, P (9) 274*d*. Method of manufacturing semiconductor plate using molten zone on powder support, P (8) 245*b*. Method of obtaining X-ray interference patterns, P (10) 316*b*. Method of passivating supports for semiconductor sulfides, selenides, and tellurides, P (3) 73*d*. Method of producing black metal-containing surface layers, P (1) 18*g*. Method of producing or recrystallizing boron phosphide, P (3) 78*e*. Methods of producing zinc-doped gallium phosphide, P (10) 311*a*. Optical maser with an adjusting mechanism for a mirror, P (11) 344*j*. Photocathode comprising channeled matrix with conductive inserts in channels tipped with photoconductive material, P (9) 274*b*. Photocathode for electron tubes, P (9) 274*c*. Refractory ceramic-to-metal seal, P (5) 142*f*. Rotary [glass ceramic] heat exchangers and hot-gas engines, P (6) 175*b*. Semiconductor device, P (3) 74*c*. Sodium-vapor discharge lamp having an envelope with a porous inner wall, P (7) 199*a*. Superhigh-pressure mercury vapor discharge lamps, P (8) 236*a*. Television camera tube employing a photosensitive target with a transparent member for absorbing reflected light from the target, P (7) 210*d*. Transistor base and method of making, P (9) 275*b*. Tunnel furnace, P (3) 77*b*. Unipolar transistor with narrow channel between source and drain, P (1) 19*d*. Variable gain transistor structure employing base zones of various thicknesses and resistivities, P (7) 210*g*. Vertical double-pass multiple reflection cell for internal reflection spectroscopy, P (10) 316*g*. Welding wire for electric arc welding of steel in a protective gas atmosphere, P (10) 296*g*.
North American Rockwell Corp. Compacting method and means, P (8) 247*b*. Composite dual dielectric for isolation in integrated circuits and method of making, P (8) 244*f*. Conversion of heat to electricity by electrochemical means using UO_2 melt, P (5) 134*h*. Epitaxial deposition of silicon on alpha alumina, P (10) 309*d*. Epitaxial dielectric MgO crystals, P (9) 272*i*. High frequency diode with small spreading resistance, P (9) 273*d*. Image projection device, P (11) 343*h*. Metal treatment, P (9) 265*i*. Method and materials for obtaining low-resistance bonds to telluride thermoelectric bodies, P (10) 310*f*. Method and materials for obtaining low-resistance bonds to thermoelectric bodies, P (6) 178*i*. Preparation of an actinide metal monocarbide from an oxide thereof, P (9) 270*a*. Semiconductor device and process for producing, P (9) 274*j*. Silicon-containing diffusion coating for ferrous metals, P (11) 333*b*.
North Eastern Gas Board. Gas burners, P (4) 104*c*.
Northern Electric Co., Ltd. Formation of metallic contacts, P (9) 273*a*. Method of making a planar diffused semiconductor voltage reference diode, P (7) 209*g*.
Northrop, D. A. Vaporization of lead zirconate-lead titanate materials (II) hot-pressed compositions at near theoretical density, (8) 243*g*.
Norton, F. H. Refractories, B (9) 290*e*. See Turnbaugh, J. E.
Norton Co. Abrasive belt handling device, P (5) 123*g*. Abrasive disk, P (8) 227*g*. Apparatus for making crystal abrasive, P (7) 193*f*. Apparatus for molding a [resin] bearing surface on a grinding wheel, P (3) 61*f*. Coated abrasives for electrolytic grinding, P (7) 193*h*. Fluid bed kiln, P (10) 317*a*. Furnace for making silicon carbide crystals, P (1) 24*h*. Hub mounting for grinding wheels, P (3) 61*g*. Method of forming a coated abrasive wheel, P (8) 227*f*. Method for producing a crystalline carbide, boride, or silicide, P (2) 47*j*. Process of forming silicon carbide diode by growing separate *p* and *n* layers together, P (7) 210*c*. Production of silicon oxynitride, P (3) 69*c*. Refractory compound and method of production, P (2) 48*c*. Refractory products, P (5) 136*b*.
Norwalk, M. H. Composition and method for making ceramic articles, P (7) 198*g*. Method of making magnesium oxide fibers, P (6) 174*i*. Three-point probe calibration for GaAs, (3) 88*h*.
Nosov, V. N. See Fridkin, V. M.
Nosova, Z. A., and Lyubina, T. M. Foamed magnesia ceramics, (9) 267*b*.
Notari, B., and Tolomei, M. Process for the preparation of bayerite alumina, P (5) 149*a*.
Nottle, R. A., and Brown, B. B. Method of preparing a dry plaster by calcination and compression, P (4) 92*d*.
Nouveau, H. Method for producing an exothermic lining for ingot and foundry molds and hot tops, P (1) 13*g*.
Novak, J. See Coufova, P.; Panek, Z.
Novak, P. E. See Asamoto, R. R.
Nover, J. C., and Williamson, J. Crystallization and decomposition of SnO–SiO_2 glasses, (1) 5*j*.
Novichkova, S. M. See Darvoid, T. I.
Novikov, G. I. See Baev, A. K.
Novikov, V. M., and Vaani, G. N. Optimum temperature conditions for obtaining tin oxide films with minimum absorption, (8) 243*h*.
Novikova, O. S. See Rassonskaya, I. S.
Novokhatskii, I. A. See Lenev, L. M.
Novoselov, S. S. See Kopylov, N. I.
Novoselova, A. V. See Chan Ngok Mai.
Nowacki, W. See Matsumoto, T.
Nowak, E. A. Paste mold machines for making glass articles, P (2) 42*b*.
Nuclear Materials & Equipment Corp. Method for producing uranium tetrafluoride, P (8) 241*c*.
Nuese, C. J., Tietjen, J. J., Gannon, J. J., and Gossenberger, H. F. Electroluminescence of vapor-grown GaAs and $GaAs_{1-x}P_x$ diodes, (8) 243*d*.
Nugent, D. C. Methods of reproducibly [spray] drying organopolysiloxanes, P (8) 236*a*.
Nukem Nuklear-Chemie und Metallurgie G.m.b.H. Apparatus for forming hollows in spherical fuel elements, P (7) 204*e*.
Numazawa, T. See Nakajima, N.
Nutting, J. See Pilliar, R. M.
N. V. Koninklijke Sphinx-Ceramique v/h Petrus Regout. Method of the production of a body from a slip in a porous mold, P (7) 211*d*.
N. V. Vereenigde Glasfabrieken (United Glassworks). Glass molding device, P (7) 198*h*. Paste mold with evaporation grooves, P (11) 336*c*.
Nwoko, V. O., and Uhlig, H. H. Logarithmic oxidation kinetics of zinc, (4) 112*b*.
Nystroem, E. H. B. Method for the production of fibers of glass and like thermoplastic material, P (1) 9*f*.
Nyul, P. See Caplan, S.

Oakes, B. D. See Jones, M. H.
Oakley, G. See Harrop, P. J.
Oates, A. E. See Marshall, J. G.
Oberg, P. E., and Paul, M. C. Spiral vacuum deposition apparatus and method, P (9) 275*c*.
Oberlin, A. See Mering, J.
O'Brien, D. L. See Beck, W. R.
O'Brien, R. J., and Richards, R. G. Failure of a basic checker brick in an open-hearth furnace, (5) 132*c*. Mechanism of wear of an open hearth ladle brick, (10) 303*b*.
O'Brien, R. N. Laser interferometry as a chemical tool, (6) 180*h*.
Obst, K. H. Different zones of erosion in the LD converter and the choice of refractories, (8) 237*d*. See Wuhrer, J.
Obst, K. H., and Muenchberg, W. Technical sintered dolomite—its mineralogical constitution, texture, and use, (8) 240*c*.
Obst, K. H., Stradtmann, J., and Benczek, K. Present position and future prospects of the use of dolomitic refractories in the steel industry, (9) 268*j*.
Obukhov, V. M. Protective devices for thermocouples used in glass furnaces, (8) 233*g*.
Ocenaskova, D. Program for refinement of the structure of monoclinic centrosymmetrical crystals by the least squares method for the NE 8033 computer, (11) 342*d*.
Ochi, O. See Mizushima, Y.
Ochiai, E. See Yamanouchi, T.
Ochiai, T. See Watanabe, Hideo.
Ochs, C. S. Coder for marking randomly spaced containers, P (11) 335*i*.
Ockert, C. E. Fuel pellet for nuclear reactor, P (3) 68*d*.
O'Connell, T. B. See Rahrig, D. D.
O'Connell, T. B., Pierce, G. G., Herrington, R. A., and Shamp, D. E. Apparatus for heat-treating and conveying glass sheets vertically oriented, P (1) 8*j*.
O'Conner, J. R. Optical and laser properties of Nd^{3+}- and Eu^{3+}-doped YVO_4, (4) 113*d*.
O'Connor, F. M. See Drost, W.
O'Connor, J. J. See Armington, A. F.
O'Connor, T. L., and McRae, W. A. Fluidized bed process for the preparation of colloidal silicon carbide, P (5) 135*a*.
O'Dell, T. H. Induced magnetoelectric effect in yttrium iron garnet, (8) 254*j*.
Odier, I. See Skalny, J.
Odier, I., and Bizon, P. Possibilities for rapid and accurate cement analysis, (2) 36*e*.
Odom, I. E. Clay fabric and its relation to structural properties in midcontinent Pennsylvanian sediments, (1) 26*j*.
O'Donnell, T. A. See Canterford, J. H.
O'Donnell, T. A., and Stewart, D. F. Reactivity of transition metal fluorides (I) higher fluorides of chromium, molybdenum, and tungsten, (6) 188*g*.
O'Donnell, T. A., Stewart, D. F., and Wilson, P. Reactivity of transition metal fluorides (II) uranium hexafluoride, (6) 188*g*.
Oel, H. J. See Doerbecker, K.; Frischat, G. H.; Krauth, A.; Tomandl, G.
Oel, H. J., and Gottschalk, A. Temperature of adherence between glass and metals, (8) 234*a*.
Oel, H. J., and Lachenmayr, H. Processes in the boundary layer between refractory and glass or slag, (7) 202*g*.
Oesterrischisch-Amerikanische Magnesit Akt.-Ges. Basic or neutral refractory brick, P (7) 204*g*. Process for manufacturing basic refractory bricks, P (2) 47*i*. Refractory basic or neutral brick for industrial furnaces, P (2) 48*c*, P (5) 136*a*.
Oesterreichische Stickstoffwerke Akt.-Ges. Purification of fluosilicic acid solution by distillation with phosphoric acid solution, P (9) 270*f*.
Oesterreichische Studienges. fuer Atomenergie G.m.b.H. Matrix-type nuclear fuel element including fission product retentive materials, P (2) 47*f*.
Office National Industriel de l'Azote. Process for stabilizing catalysts supported by magnesia or by materials containing it, P (1) 14*d*.
Oftedal, I. Note on minor elements in garnets, (8) 250*i*.
Ogard, A. E., Land, C. C., and Leary, J. A. Thermal expansion of PuC and UC-PuC solid solution, (5) 134*c*.
Ogawa, T. See Ohba, H.

Oglebay Norton Co. Material for hot top, P (6) 174*d*.
Ogura, T. See Watanabe, T.
Ogura, T., and Tanaka, H. Studies on the fine grained crystalline glass-ceramics—crystallization of ZnS-doped Na_2O-CaO-MgO-Al_2O_3-SiO_2 glasses, (1) 7*f*.
Oh, H. L., and Finnie, I. Ring cracking of glass by spherical indenters, (11) 335*a*.
O'Hara, M., and Steinitz, R. Characterization of devitrification of an iron-containing glass by electrical and magnetic properties, (6) 166*g*.
Ohashi, T. See Kitahiro, I.
Ohba, H. Experimental conditions for crucible method corrosion tests including temperature distribution and cooling velocity of furnace, (10) 302*j*. Results of differential method load tests on magnesia brick, (9) 269*b*. See Kato, K.
Ohba, H., Hiragushi, K., and Nakashima, C. High temperature properties of dolomite (I) study of dolomite refractories by high temperature X-ray diffraction, (10) 303*d*.
Ohba, H., Hiragushi, K., and Ogawa, T. Study of the causes of damage of stopper head tops, (9) 269*b*.
Ohba, H., Sugita, K., and Nomura, T. Behavior of carbonaceous materials in tar-bonded dolomite brick for LD converter, (9) 266*i*.
Ohba, H., Sugita, K., and Shimada, K. Reaction of slag on magnesia brick (II) properties of magnesia brick after slag penetration, (10) 303*i*.
Ohbayashi, K., Kohn, K., and Iida, S. Effect of oxygen deficiency on the magnetic properties of copper ferrite, (10) 319*j*.
Ohio Brass Co. Bonded porcelain articles and forming method, P (5) 137*c*. Coated insulator, P (9) 271*f*. Post insulator with composite fillers, P (8) 242*e*.
Ohio State University, Board of Trustees. Electromechanical transducer, P (11) 343*e*. Sonic transducer, P (5) 143*b*.
Ohishi, M. See Furumi, K.
Ohlgren, H. A. Process for preparing carbon articles, P (1) 14*c*.
Ohlsen, W. D., and Melich, M. E. Second-order quadrupole shifts of ^{81}Br in KBr doped with NaBr, (9) 286*i*.
Ohm, A. Franziska Lenz-Gerharz—sculpture and ceramics in stoneware, (10) 293*j*.
Ohmori, K. See Watanabe, Hideo.
Ohnemueller, W. Determination of the hardness of plasters by their drilling strength, (10) 294*j*. See Merkle, G.
Ohnemueller, W., and Schimmel, G. Calcium silicate hydrates in the calcite-quartz interface region in hardened nonhydraulic lime mortars, (7) 194*d*.
Ohnishi, S., and Tsuboi, H. Radiation process of deforming glass fiber materials, P (5) 130*d*.
Ohno, T. See Akashi, T.; Takahashi, M.
Ohse, R. W. High-temperature vapor-pressure studies of UO_2 by the effusion method and its thermodynamic interpretation, (7) 218*e*.
Ohta, K. See Yuasa, T.
Ohwada, K. See Ishihara, T.
Oinuma, K. See Kodama, H.
Oinuma, K., and Kobayashi, K. Quantitative study of clay minerals in some recent marine sediments and sedimentary rocks from Japan, B (8) 259*d*.
Ojakangas, R. W. See Beall, A. O.
Ojha, S. K. Shear strength of rectangular reinforced and prestressed concrete beams, (8) 228*j*.
Okamoto, S. Structure of δ-FeOOH, (11) 357*e*. Structure and magnetic properties of $Ni_{1-x}Fe_{2/3}$ coprecipitate, (3) 87*f*. Structure of the new δ-Fe_2O_3 (hydrate), (2) 59*h*.
Okamoto, Y., and Goswami, J. C. Preparation and properties of barium pernitride, Ba_3N_4, (6) 187*h*.
O'Kane, D. F. Electrically conductive compositions, P (1) 17*g*. See Giess, E. A.
O'Kane, D. F., and Stemple, N. R. Phase diagram for the pseudobinary system InSb-InSe, (11) 355*g*. Phase diagram for the pseudobinary system Sb-SnTe and some electrical properties of the ternary alloys, (11) 355*h*.
Okazaki, A. See Cowley, E. R.
Okazaki, C., Hirota, E., Neichi, Y., Okazaki, H., and Nakajima, S. Magnetic properties of $M_{1-x}Li_xFe_5O_{8-x}F_x$, (7) 219*e*.
Okazaki, H. Crystal chemistry of $M_{3-x}{}^{2+}Li_xM^{4+}O_{8-x}F_x$ crystals, (5) 150*i*. See Okazaki, C.
Okazaki, K., and Takahashi, K. Sintering of ferroelectric ceramics by hot-pressing and their electrical properties, (11) 342*g*.
O'Keeffe, M. See Ebisuzaki, Y.
Okubo, T., Yonemochi, O., Maeda, M., and Nakamura, K. Crystal modifications of binary systems containing zirconia molten and sprayed by arc-plasma, (11) 351*b*.
Okuda, S., and Williamson, W. O. Spatial relations between air bubbles and flocculated kaolinite and dickite, B (6) 191*g*.
Okuto, Y., Kondo, M., and Uchida, I. Stress effect on the microwave emission from Si avalanche diodes, (8) 257*e*.
Olander, D. R. Theory of helium dissolution in uranium dioxide (I) interatomic forces in UO_2; (II) helium solubility, (6) 190*b*.
Olcott, J. S. Method for production of glass article having increased mechanical strength, P (11) 336*i*.
Old, A. F. See Roberts, J. W.
Oldfield, B. See Steele, B. R.
Oldfield, W. Cast iron composition and process for making, P (10) 300*d*.
Olds, L. E., Udy, M. C., and Wesel, J. R. Process for selectively carbiding titanium, iron, and vanadium values, P (9) 270*d*.
Oldshue, J. Y. Mixing, (8) 247*a*.
Oleinikov, N. N. See Tret'yakov, Yu. D.
Olesnevich, S. M. See Pikulin, S. A.
Olin Mathieson Chemical Corp. Weld arresting composition, P (8) 230*a*.
Oliva, R. F. See Cucka, P.
Oliver, J. Flatware dimensions, (3) 70*a*. Screen process reproduction in products finishing, (1) 15*g*.
Oliver, M. R., McWhorter, A. L., and Foyt, A. G. Current runaway and avalanche effects in n-CdTe, (2) 49*f*.
Oliver, R. M. See Jonas, E. C.
Olivier, C. A. See Archambault, M.
Olivier, J. P., and Sennett, P. Electrokinetic effects in kaolin-water systems (I) measurement of electrophoretic mobility, B (9) 289*h*.
Ollinger, J. C. Method of making ceramic acoustical product, P (6) 174*g*.
Olmstead, J. A. Field-effect transistor with gate-insulator variations to achieve remote cutoff characteristic, P (6) 177*j*.
Olphen, H. van. Collapse of potassium montmorillonite clays upon heating—"potassium fixation," B (8) 260*a*. Compaction of clay sediments in the range of molecular particle distances, B (5) 160*e*. Parallel plate interaction in clay-water systems (abstract), B (8) 259*a*. Polyelectrolyte reinforced aerogels of clays—application as chromatographic adsorbents, B (9) 289*j*. See Andrews, D. E.
Olsen, A. R., Douglas, D. A., Hirose, Y., Scott, J. L., and Ullmann, J. W. Properties and prospects of thoria-based nuclear fuels, (11) 338*j*.
Olsen, L. O., and Halpern, C. Bibliography of Temperature Measurement, B (4) 119*j*.
Olsen, O. J. See Wallace, G. B.
Olson, B. J., and Teply, R. J. Memory fabrication method, P (10) 310*c*.
Olson, C. R. Electric glass melting, (11) 333*i*.
Olson, F. A. See Bennett, G. E.
Olson, R. A., and Medicus, G. Dielectric relaxation effects in a metal-oxide-plasma capacitor, (3) 80*a*.
Olson, R. S., Tveter, E. C., Surls, J. P., and Shaw, R. G. Method of producing hydrogen fluoride and solubilized beryllium, P (7) 214*i*.
Olson, W. M., and Mulford, R. N. R. Decomposition pressure and melting point of thorium mononitride, (11) 351*g*.
Olstowski, F. Process for preparing low density graphite structures, P (9) 270*c*.
Olstowski, F., and Newport, J. J., III. Graphite metal body composite, P (8) 240*f*.
Olstowski, F., Watson, J. D., Sr., and Osborn, O. Process for producing compressed vermicular graphite structures, P (9) 270*d*.
Oltman, R. B. See Barrett, M. W.
Olton, D. J., and Fazioli, W. A. Abrasive belt handling device, P (5) 123*g*.
Omar, M. A. Electron screening and the longitudinal velocity of sound in n-type GaSb, (10) 320*e*.
O'Meara B. See Capps, W.
Omel'chenko, O. A. See Zarubitskii, O. G.
Omenetto, N., and Rossi, G. Atomic fluorescence flame spectrometry using a mercury line source, (5) 144*j*.
Omori, Y. See Asada, M.
O'Neal, J. E. See Naber, C. T.
O'Neill, J. S. See Livey, D. T.
Ong Tjing Gie. See Andreas, F.
Onishchenko, A. S. Combined burner for oil and water mixtures, (8) 249*d*.
Onishi, M. See Asada, C.
Ono, F. See Kawai, N.
Ono, M., Hirokawa, S., and Nagai, H. Fading of cobalt glass, (1) 6*b*.
Ono, S., and Sugihara, K. Theory of the transport properties in graphite, (4) 117*g*.
Onodera, G. C. Remote cutoff field effect transistor, P (3) 74*e*.
Onoshima, Y. See Hara, T.
Onuki, M. See Hase, N.; Miyake, T.
Onuma, K., and Yagi, K. System diopside-akermanite-nepheline, (5) 150*a*.
Ooijen, D. J. van, and Goot, A. S. van der. Internal friction of cold-worked niobium and tantalum containing oxygen and nitrogen, (10) 322*f*.
Ooijen, H. van. Heat flow meters, (2) 54*g*.
Ooka, K. See Kishii, T.
Ooka, K., and Kishii, T. Stress in glass caused by ultraviolet radiation (V) thermal release of stress in glass caused by ultraviolet irradiation; (VI) stress buildup in binary borate glasses by ultraviolet radiation, (8) 234*g*.
Oomori, K. See Watanabe, Hideo.
Oosting, M. Titrimetric analysis of organic material in clay, (11) 347*c*.
Opoczky, L. Structural changes during the grinding of portland cement, (3) 62*f*.
Orbach, H. K., Bedjai, J. G., Martindill, R. E., and Kritchevsky, J. Method of producing beryllium halides from beryllium ore in a high intensity arc, P (10) 318*f*.
Orbeck, L. J. See Slone, T. J.
Orcutt, D. R. Laminated window panels, P (3) 65*j*.
Ore, E. L., and Straughan, J. J. Effect of cement hydration on concrete form pressure, (5) 124*g*.
O'Reilly, W. See Banerjee, S. K.
Orell, N. G. Beryllium powder forging, B (3) 89*j*.
Orfila, P. Dielectric properties of solids, (6) 176*c*.
Orhanovic, M. See Wolf, R. H. H.
Oriani, R. A. See Sundquist, B. E.
Orissa Cement, Ltd. High alumina refractory brick, P (5) 135*d*. Improved nozzle for steel plants and foundries, P (3) 68*g*.
Orlov, N. F. See Byurganovskaya, G. V.
Orlova, E. M. See Bogdanova, G. S.
Orman, S. See Baker, M. McD.
Ormsby, W. C., and Marcus, J. H. Rheological properties of kaolins of varying degrees of crystallinity (extended abstract), B (6) 191*f*.
Ornitz, M. N., and English, R. H. Composite carbonaceous members for furnace rolls and other high temperature members, P (2) 46*h*.
Orr, C., Jr., and Hendrix, W. P. Specimen mounting device for porosity determination apparatus, P (2) 55*g*.
Orr, D. S. Traveling belt type drum filter, P (3) 75*c*.
Orr, P. L. See Domicone, J. J.
Orrell, E. W. Ceramic analysis by X-ray fluorescence (I) nonautomatic spectrometer, B (7) 224*h*.
Ortega, R. Measured-quantity intermittent-action dispenser for a particulate material, P (2) 53*c*.
Orth, W. H. Fast firing vs. conventional firing, B (3) 89*e*.
Orton, H. S. Electric resistance furnace, P (11) 348*f*.
Orton, J. W. See Townsend, M. G.
Osafune, H. See Miura, Y.
Osborn, E. F. See Roeder, P. L.
Osborn, O. See Olstowski, F.; Vaught, L. M.
Osborn Mfg. Co. Apparatus for making abrasive articles, P (10) 293*g*. Method of manufacturing grinding wheels, etc., P (7) 193*h*.
Osborne, J. F. See Cronin, G. R.
Osborne, P. S. Ceramic bodies and preparation thereof, P (5) 131*a*.
Osborne, Raymond G., Laboratories, Inc. See Raymond G. Osborne Laboratories, Inc.
Oshima, M. See Takahashi, R.
Osial, T. A. Industrial laser applications, (2) 54*a*.
Osiko, V. V. See Voron'ko, Yu. K.
Osmer, J. A. See Chase, A. B.
Osokina, T. A. See Myshlyaeva, V. V.
Ostberg, J. E. Electrode for arc furnaces, P (10) 317*f*.
Osterholtz, C. E., Baab, K. A., and Morog, M. Design considerations for vacuum vessel refractories, (6) 172*h*.
Osterman, J. Studies on the properties and formation of quick clays, B (6) 191*f*.
Osterried, O., and Gugel, E. Silicon bonded silicon carbide refractories, (3) 68*a*.
Ostertag, W. Rare earth tungsten bronzes ($M_{0.1}WO_3$, where M = rare earth element), (5) 157*c*.
Ostrander, G. W. See Pendleton, W. W.
Ostrander, G. W., and Pendleton, W. W. Crystallized glass ceramic coatings, P (9) 263*a*.
Ostroverkhov, V. I. See Koshkin, I. A.
Ostrowski, J. S. Silver and copper coated articles protected by treatment with aminoazole compounds, P (8) 236*c*.
Ovsenskii, V. B. See Mil'vidskii, M. G.
Ota, E. See Nakayama, N.
Ota, E., Sakai, S., and Takayanagi, H. Performance test for surface grinding wheels (III) grinding of stainless steels, (1) 1*g*.
Otake, T. See Suzuki, T.
Otenbaker, J. T. See Saad, O. C.
Otsuka, N. See Shiraki, Y.
Ottawa, Minister of Mines and Technical Surveys. Process for the preparation of metal oxides having an enlarged pore volume, P (2) 47*j*.
Ottenstein, D. M. Preparation of a support for use in gas chromatography, P (10) 305*a*.
Otto, K. See Stark, G.
Otto, K., and Milberg, M. E. Ionic conduction in alkali and thallium silicate glasses, (7) 196*b*.
Ouchi, H. Piezoelectric properties and phase relations of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics with barium or strontium substitutions, (4) 99*d*.
Ouchi, S. See Kitani, S.
Oulton, T. D. See Miller, J. G.
Ovcharenko, F. D. See Tarasewich, Yu. I.
Over, R. E. Refractory lining for conical portion of a furnace and brick therefor, P (2) 48*e*.
Overkott, E. Determination of the apparent density of granular ceramic raw and finished materials, (1) 21*a*.
Overton, W. C., Jr. See Daybell, M.
Ovo, K. See Beranger, G.
Ovshinsky, S. R. Method of making solid state relay devices from tellurides, P (11) 344*c*.
Owen, A. E. Electronic conduction mechanisms in glasses (I, II), (10) 297*b*.
Owen, A. J., and Whiteley, P. G. Pneumatic steelmaking refractories—slag erosion problems, B (9) 291*b*.
Owen, V. J. See Astbury, N. F.
Owens, B. B. Corresponding-states melting curve for the alkali halides at high pressure, (7) 216*j*.
Owens-Corning Fiberglas Corp. Apparatus for melting and feeding heat-softenable materials, P (3) 65*a*. Apparatus and process for making bulky [glass fiber] yarn, P (9) 264*h*. Apparatus for producing fibers from high temperature fusible material, P (9) 264*h*. Binder composition and method, P (8) 235*e*. Coating dies, P (10) 300*d*. Coating method for glass fabric and product thereof, P (3) 65*e*. Furnace control apparatus, P (10) 300*i*. Glass fiber-elastomeric systems treated with mercaptan-

containing organosilane anchoring agents, P (4) 94*a*. Glass fibers treated for combination with elastomeric materials and method, P (10) 300*a*. High temperature fibrous board, P (2) 41*b*. Integrated body of multifilament strands, P (10) 300*d*. Low density insulation bonded with colloidal inorganic materials, P (3) 68*h*. Method and apparatus for forming and processing continuous filaments, P (3) 65*c*. Method and apparatus for packaging strand material, P (4) 94*i*. Method of making dielectric panels, P (10) 310*b*. Method and means for controlling internal furnace pressures, P (6) 171*c*. Method for the preparation of silica fibers, P (3) 65*j*. Method of preparing metal oxide-metal sulfide plural coated siliceous fibers, P (6) 175*a*. Method for processing heat-softened mineral material, P (10) 301*b*. Method for producing a fibrous mat, P (8) 235*i*. Method for production of glass fibers, P (1) 9*g*. Method for production of mineral fibers, P (6) 171*a*. Reinforced structural panels, P (1) 10*b*. Strand delivery apparatus, P (10) 301*a*. Structural panel and method of producing, P (1) 10*b*. Structures formed of glass fiber-elastomer systems, P (9) 266*a*. Viscosity measuring process and apparatus, P (8) 236*c*. Waste wash water and waste binder reuse system and apparatus for mineral fiber forming process, P (3) 66*e*.

Owens-Illinois, Inc. Apparatus for drawing glass in cylindrical form, P (4) 94*bc*. Apparatus for forming a film of glass, P (5) 129*i*. Apparatus for forming the open end portion of small glass containers, P (1) 8*i*. Apparatus for glazing glass articles, P (11) 335*d*. Apparatus for homogenizing molten glass, P (5) 129*a*. Apparatus for inspecting containers for wall thickness distribution, P (7) 198*a*. Apparatus for inspecting the rim of a bottle, etc., which employs polarized light at Brewster's angle, P (3) 64*j*. Apparatus for joining glass parts, P (5) 129*b*. Apparatus for measuring the thickness of dielectric members, P (10) 316*h*. Article handling apparatus, P (4) 94*d*. Bottle inspection method and apparatus, P (11) 335*h*. Bubbler apparatus for a glass melting furnace, P (11) 335*i*. Cast iron composition and process for making, P (10) 300*d*. Cathode ray tube display screen comprising woven mat of luminescent glass fibers, P (6) 177*b*. Cathode-ray tube having an improved fiber optic faceplate, P (1) 8*e*. Cathode-ray tubes and method of reinforcing the tubes, P (8) 244*a*. Color indicia for glass and method of applying, P (7) 198*f*. Container decorating means with means for holding and indexing work, P (4) 94*f*. Electrically conductive solder glass, P (10) 300*g*. Flask gages, P (1) 8*j*. Flexible pipe coupling, P (10) 300*h*. Fluid film lubrication for extrusion of metal, P (1) 8*j*. Glass aerosol bottles and method for making, P (4) 94*i*. Glass composition and method, P (4) 94*ij*. Glass composition and method and product, P (8) 235*j*. Glass compositions resistant to discoloration, method of making, and articles produced, P (2) 40*h*. Glass container sorting, P (2) 40*i*. Glass forming apparatus, P (3) 65*h*. Glass furnace electrode, P (9) 278*d*. Glass melting method, P (4) 94*c*. Glass semiconductor housing having its interior surfaces covered with an alkali-free solder glass, P (5) 141*j*. Inspecting method and apparatus, P (3) 65*j*. Load-bearing mounting elements for attachment to glass surfaces, P (8) 235*e*. Lubricant coating for glassware molds and equipment, P (1) 9*f*. Mandrel supporting apparatus, P (4) 94*d*. Method and apparatus for cooling glass plungers and molds, P (4) 94*g*. Method and apparatus for eliminating arcing in gas-electric sealing of TV bulbs, P (4) 94*h*. Method and apparatus for inspecting transparent articles for defects by fluorescent radiation, P (10) 300*f*. Method for controlling the reduction of metallic ions in glass compositions, P (1) 9*j*. Method of eliminating foam blanket on the surface of molten glass, P (2) 41*b*. Method for making thermistors, P (10) 310*d*. Method for molding glass articles and releasing the articles from the mold, P (4) 95*c*. Method of treating the surfaces of glass containers, P (2) 41*i*. Methods of reproducibly [spray] drying organopolysiloxanes, P (8) 236*a*. Molten additions of colorants in a glass furnace forehearth, P (1) 9*j*. Multicolor photoluminescent glass systems, P (6) 178*b*. Paste mold machines for making glass articles, P (2) 42*b*. Pressing flanged glass articles, P (9) 265*j*. Process for bonding devitrified surfaces, P (1) 10*a*. Radiation indicating glass, P (4) 95*d*. Spray mist proportioning system for glass machine, P (2) 42*e*.

Owens-Illinois Glass Co. Core structure for an electroluminescent device and formation thereof, P (10) 309*j*. Hinged orifice ring holder for glass feeders, P (10) 300*c*. Method and apparatus for supporting and gaging an article, P (5) 130*f*. Radiation sensitive apparatus for inspecting the bottom wall of hollow transparent containers, P (3) 66*b*.

Oxley, G. H., and Littler, E. S. Manufacture of plate glass, P (5) 130*e*.

Oxley, J. H., and Blocher, J. M., Jr. Production of rigid shapes of refractory metals by decomposition of the metal hexafluoride in the interstices of a green compact, P (6) 175*c*.

Oya, A., and Shimohira, T. Aluminum porcelain enamel of the system PbO-SiO_2-V_2O_5, (11) 332*c*.

Oye, H. A. Transport properties in solid and liquid mixtures of the system Li_2SO_4-Ag_2SO_4, (5) 150*g*.

Oza, B. N. See Shah, R. K.

Ozaki, H., and Mikoshiba, N. Nonlinear theory of current saturation in piezoelectric semiconductors, (10) 323*h*.

Ozaki, S., and Tatematsu, K. Aggregating action of semimacromolecular surfactants on ceramic powder, (11) 350*e*. Reactions of cationic materials with agar and application of the reaction products to slip casting in ceramics, (9) 271*b*.

Ozawa, L. Emission and excitation spectra of Eu_2O_3 compared with Y_2O_3:Eu phosphor, (8) 253*c*.

Ozawa, L., Huzimura, R., and Ato, Y. Europium activated yttrium-thallium oxide phosphor, (5) 152*h*.

Paar, V. F. See Walter, J.

Pablo, L. de. Disordered kaolinite from Concepcion de Buenos Aires, Jalisco, Mexico, B (7) 224*f*.

Pacer, R. A. See Rulfs, C. L.

Pach, L. See Proks, I.

Pacific Vegetable Oil Corp. High-strength lightweight aggregate and method for its manufacture, P (7) 199*g*.

Pack, A. H. See Campbell, W. W.

Pacl, J., and Blaha, M. Control of thixotropy of porcelain slips and the effect of feldspars on slip properties, (6) 175*e*.

Pacovsky, V. See Kriz, M.

Padfield, R. C. Magnesia chrome ore refractory, P (4) 97*g*. See Herron, R. H.

Pagano, M. See Provost, G.; Vilnat, J.

Pagano, M., and Vilnat, J. Determination of the modulus of elasticity of faience tile by different methods, (10) 305*e*.

Page, D. See Ball, M. C.

Page, D. J. Electroluminescent device, P (11) 343*d*.

Page, J. O. Complexometric determination of calcium in impure calcium carbonate and limestone, (10) 313*c*.

Pai, K. M. See Mallikarjunan, R.

Paige, E. G. S. See Maines, J. D.

Pakalns, P. Spectrophotometric determination of traces of phosphorus by an extraction method, (4) 103*a*.

Pake, G. E. Review of magnetic resonance methods applicable to solids, B (10) 328*h*.

Paksaver, S. Impaction process of forming thermionic cathode, P (1) 18*e*.

Paladino, A. E. See Mozzi, R. L.

Palatnik, L. S., Zaichik, R. I., Gladkikh, N. T., and Khotkevich, V. I. Methods for measuring the thickness of thin films, (10) 307*d*.

Palecek, M. See Fanderlik, M.

Palermo, J. A., and Bennett, G. F. Crystallization, (8) 246*j*.

Palermo, J. A., and Lin, K. H. Crystallization, (10) 319*d*.

Palik, E. S. See Kim, S. C.

Palilla, F. C. Trivalent rare earths in inorganic phosphor systems, (8) 243*f*. See Avella, F. J.; Levine, A. K.; Mikus, F. F.; Wacher, P.

Palilla, F. C., Levine, A. K., and Rinkevics, M. Rare earth activated phosphors based on yttrium orthovanadate and related compounds, (3) 85*h*.

Paliwal, K. V. Cation exchange equilibria in Na-K-Ca-Mg systems of some clay minerals, (6) 184*d*.

Palkin, B. A. See Solntsev, S. S.

Palma, M. U. See Cordone, L.

Palmberg, P. W., Rhodin, T. N., and Todd, C. J. Epitaxial growth of gold and silver on magnesium oxide cleaved in ultrahigh vacuum, (5) 152*e*.

Palmer, A. R. See Whitfield, H. J.

Palmer, A. R., Whitfield, H. J., and Clark, R. Release of xenon-133 on postirradiation heating of UO_2-ThO_2-BeO compacts, (2) 45*j*.

Palmer, B. M. See Smucker, C. A.

Palmer, R. C. See Rutland, D. F.

Palmer, R. P. See Longman, G. W.

Palmer, W. B., Smith, R. E., and McNally, J. P. Impregnation and partial polymerization of resin coated wound glass fiber package, P (8) 235*b*.

Palmonari, C. Altered pyroclastic rocks as a source of refractory material, (7) 200*a*.

Palmour, H., III. See Chay, D. M.; Rummler, D. R.

Palmquist, R. L. See Anderson, D. B.

Pammer, E. Method of growing doped crystalline layers of semiconductor material upon crystalline semiconductor bodies, P (2) 51*j*. See Folkmann, E.

Pamplin, B. R., Shah, J. S., and Sullivan, R. A. L. $Zn_xCd_{1-x}SnAs_2$ semiconducting alloy system, (4) 119*d*.

Pampuch, R. See Librant, Z.

Panasevich, V. M. See Grosheva, V. M.

Panda, J. D. See Moitra, S. L.

Pandey, G. K. See Chandra, S.

Pandora Custom Craft. Method and apparatus for making mosaics, P (2) 49*a*.

Panek, Z., Zemanova, D., and Novak, J. Determination of calcium and magnesium in ores and slags after separation of R_2O_3 and P_2O_5 with an aqueous suspension of ZnO, (10) 313*h*.

Panerai, G. See Panerai, M.

Panerai, M., and Panerai, G. Electroluminescent devices, P (10) 309*c*.

Panfilov, B. I., and Feodos'ev, N. N. Enthalpy of formation of the metatitanates of sodium, potassium, and barium, (9) 282*c*. Enthalpy of formation of the titanates of zinc, (3) 80*j*. Heat of formation of the metatitanates of lithium and magnesium, (1) 29*a*. Heats of formation of the metatitanates of calcium, strontium, and barium, (1) 29*a*.

Panfilova, L. I. See Skramtaev, B. G.

Pangborn Corp. Abrasive separator, P (5) 123*h*.

Panish, M. B. Gallium-phosphorus-zinc ternary phase diagram, (11) 353*f*. See Queisser, H. J.

Panizza, E. High speed measurement of two-photon absorption processes, (6) 180*e*. Two-photon absorption in ZnS, (1) 17*g*.

Pankova, N. A. See Agapova, L. K.

Pankratz, L. B. High-temperature heat contents and entropies of dehydrated analcite, kaliophilite, and leucite, (6) 186*h*. See Mah, A. D.

Pankratz, L. B., and Weller, W. W. Thermodynamic properties of three lithium-aluminum silicates, (4) 118*h*.

Panov, V. S. See Funke, V. F.

Pantony, D. A. See Vasantasree, V.

Paoletti, A. See Menzinger, F.

Papacharalambous, H. G. Conventional vs. vibratory milling, (3) 75*e*.

Papalegis, F. E. See Bourdeau, R. G.

Papazian, S. A. See Reisman, A.

Pappis, J. See Li, Pei-Ching.

Pardue, T. E. Ring ohmic contact microelectronic component separation method, P (1) 19*b*.

Parfenov, V. A. See Aleinikov, F. K.

Parfitt, G. D. See Day, R. E.; Lewis, K. E.

Parham, W. E. Lateral clay mineral variations in certain Pennsylvania underclays, B (6) 192*h*. See White, W. A.

Parham, W. E., and Austin, G. Clay mineralogy of the Glenwood formation, southeastern Minnesota, and adjacent areas, (2) 56*g*.

Parikh, P. See Kushida, T.

Paris, R. A. See Clar, E.; Gallet, J. P.

Parish, R. Low threshold GaAs laser diodes, (8) 243*g*.

Parisi, A. J. Physicist at last finds key for spectrometry techniques, (8) 248*b*.

Parisot, J. Notes on carbon refractories, (6) 173*i*.

Park, F. See McGonnagle, W.

Park, J. J. Reactions of uranium with the platinide elements (I) uranium-ruthenium system; (II) uranium-rhodium system, (6) 188*f*.

Park, J. J., and Mullen, L. R. Reactions of uranium with the platinide elements (III) uranium-iridium system, (6) 188*f*.

Park, W. C., and Schot, E. H. Stylolites—their nature and origin, (9) 287*i*.

Park, Y. S., Litton, C. W., Collins, T. C., and Reynolds, D. C. Exciton spectrum of ZnO, (9) 282*h*.

Parker, E. R. See Thomas, G.

Parker, R. See Henning, C. D.

Parker, S. G. Simple apparatus for high temperature-moderate pressure crystal growth, (1) 23*b*. See Johnson, R. E.; Sihvonen, Y. T.

Parnham, H. Calculation of heat losses, temperature gradients, and junction temperatures in refractory walls and structures, (10) 302*f*.

Parr, N. L., and Martin, G. F. Method of glazing silicon nitride shaped body and article, P (10) 304*g*.

Parr, N. L., and May, E. R. W. Technology and engineering applications of reaction-bonded Si_3N_4, (11) 339*e*.

Parshad, R. See Agrawal, V. K.

Parsons, B. I. See Machin, W. D.

Parsons, C. A., & Co., Ltd. Titanates having positive temperature coefficients of resistance, P (7) 210*f*.

Parsons, G. D., and Rayeski, T. J. Alignment structure for a glass mold and plunger, P (10) 290*i*.

Parsons, M. C. Diamond abrasive matrix, P (6) 163*i*.

Parsons, M. K., and English, F. L. Effect of sulfur annealing pressure on resistivity homogeneity of CdS single crystals, (11) 352*e*.

Parsons, W. F. See Carnall, E., Jr.

Parthey, H. See Kanellakopulos, B.

Partridge, G. See McMillan, P. W.

Paruolo, M. J., and McMeekin, J. H. Automatic inspection means for containers, P (7) 198*b*.

Pascoe, R. T., Radford, K. C., Rawlings, R. D., and Newey, C. W. A. Instrumental modifications for compressive testing up to 1800°C, (4) 102*i*.

Pascual, O. S., and Kapauan, P. A. Exploratory trace elements in ancient pottery, (8) 227*j*.

Pashchenko, A. A. See Budnikov, P. P.

Pashinkin, A. S. See Dembovskii, S. A.

Pasierb, E. F. Semiconductor gallium arsenide with germanium connecting layer, P (5) 142*j*.

Pask, J. A. See Borom, M. P.; Brennan, J. J.; Langston, R. B.

Passaglia, E. See Kessler, K. G.

Passmore, E. M. See Vasilos, T.

Pastor, A. C., and Pastor, R. C. Crystal growth above 2200°C by the verneuil method (II), (1) 27*c*.

Pastor, H. See Meyer, R.

Pastor, R. C. See Maiman, T. H.; Pastor, A. C.

Pastor, R. C., Kimura, H., Podoksik, L., and Pearson, M. A. Surface and bulk states of additives in alumina powder, (6) 188*c*.

Pastore, J. R. See Gualtieri, J. G.

Patalong, H. Semiconductor device of the four-layer type, P (10) 311*c*. See Herlet, A.

Patel, A. R., and Agarwal, M. K. Slip and screw dislocations in diamond, (6) 188*c*.

Patel, A. R., and Bahl, O. P. Anisotropy in the oxidation of graphite, (10) 319*a*.

Patel, A. R., and Dessi, C. C. Comparative studies on dislocations in natural and synthetic calcium fluoride from different sources, (6) 184*i*.

Patel, A. R., and Patel, R. P. Etching of cleavages of calcite of scalenohedral habit, (6) 185*e*.

Patel, A. R., and Raju, K. S. Etching of matched fracture faces of quartz, (4) 110*e*.

Patel, R. P. See Patel, A. R.

Patent-Treuhand-Ges. fuer elektrische Gluehlampen m.b.H. Alkali metal vapor lamp, P (8) 243*h*. High pressure electric discharge lamp having a fill including uranium halide, P (5) 141*j*. Shaft furnace for the continuous drawing of quartz tube, P (1) 24*g*.

Paterson, M. S. See Lyall, K. D.

Pathak, A. N. See Singh, P. D.

Patrassi, E. Thermal conductivity of uranium dioxide at very high temperature gradients, (10) 326*h*.

Patrat, G. See Bertaut, E. F.

Patriarche, P., and Letournier, R. Method and means for manufacturing electron tube sockets, P (3) 65*i*.

Patrick, L., Hamilton, D. R., and Choyke, W. J. Growth, luminescence, selection rules, and lattice sums of SiC with wurtzite structure, (9) 282*g*.

Patrick, R. F. See Wehrenberg, T. M.

Patrick, R. F., and Wehrenberg, T. M. Refractory, P (8) 241*d*.

Patten, F. W., and Marrone, M. J. V_K center in NH_4Br and NH_4Cl single crystals, (8) 258*a*.

Patterson, F. K., and Ward, R. Preparation and properties of some ternary nitrides of strontium and barium with rhenium and osmium, (6) 187*i*.

Patterson, J. H. See Brindley, G. W.

Patterson, R. J. See Brau, M. J.

Patterson, R. J., and Haberecht, R. R. Boron nitride film capacitor, P (4) 99*e*.

Patterson, S. H. Halloysitic underclay and amorphous inorganic matter in Hawaii, B (6) 191*c*.

Patterson, W. R., and Torrence, J. D. Spiderless gyratory crusher having frictionless bearings, P (8) 251*i*.

Pattison, W. L. See McBride, J. P.

Pattou, P. See Barrachin, A. M.

Paty, L. Decomposable joint with indium seal for glass vacuum apparatus, (11) 333*j*.

Paul, A., and Douglas, R. W. Coordination equilibria of nickel(II) in alkali borate glasses, (5) 126*i*. Optical absorption of divalent cobalt in binary alkali borate glasses and its relation to the basicity of glass, (7) 196*j*. Ultraviolet absorption of chromium(VI) in binary alkali borate glasses, (1) 8*e*. Ultraviolet absorption of chromium(VI) in some binary and ternary alkali and alkaline earth oxide glasses, (7) 197*f*.

Paul, C., and Pupko, S. Process for stabilizing catalysts supported by magnesia or by materials containing it, P (1) 14*d*.

Paul, C. M. See Sundaram, C. V.

Paul, D. K. See Rao, G. H. S. V. P.

Paul, M. C. See Oberg, P. E.

Paul, R. A., and Forchheimer, O. L. Process for making dead-burned dolomite, P (11) 340*f*.

Paul, R. A., and Shepherd, T. L. Combustion process and apparatus to increase a flame temperature, P (11) 348*h*.

Paulding, B. W., Jr. Role of microstructure in the physical properties of rock, B (3) 90*h*. Techniques used in studying the fracture mechanics of rock, B (3) 90*h*.

Pauleve, J. See Dautreppe, D.

Paulik, F. See Erdey, L.

Paulik, I. See Somody, A.

Paulik, J. See Erdey, L.

Paulsen, J. F., and Steiner, E. F. Economic substrate size for thin film circuits, (3) 71*d*.

Paulson, D. L. See Henry, J. L.

Paulson, E. G. Control of water pollutants in the finishing industries (I), (11) 345*j*.

Pauthenet, R. See Bertaut, E. F.

Pavlica, S. R. See McCreight, D. O.; Miller, E. D., Jr.; Wishon, B. E.

Pavlikov, V. N. See Tresvyatskii, S. G.

Pavliuk, G. See Gumuliauskas, A.

Pavlov, Yu. S. See Bogomolov, B. N.

Pavlushkin, N. M. See Kitaigorodskii, I. I.

Pavlushkin, N. M., Al'takh, O. L., and Prudnikov, V. N. Paramagnetism of Dy^{3+} and Gd^{3+} in silicate glasses, (8) 233*b*.

Pavlushkin, N. M., and Chernyakova, R. M. Colorimetric determination of sulfur in glasses, (6) 166*i*. Kinetics of combustion of sulfides in slag glasses, (2) 39*e*.

Pavlushkin, N. M., and Lisovskaya, G. P. Study of the crystallization of high-lead glasses, (6) 169*d*.

Pavlyuchenko, M. M. See Rubinchik, Ya. S.

Pawlak, J. J. Electroformed welded circuits, (9) 271*j*.

Pawlek, F. E. See Gerlach, J. K.

Pawlowski, S. Bond properties of aluminum phosphates, (1) 11*c*.

Pawluk, S. Characteristics of 14 A [*d* spacing] clay minerals in the *B* horizons of podzolized soils of Alberta, B (5) 160*a*.

Paxton, R. R. Carbon and graphite materials for seals, bearings, and brushes, (2) 49*d*.

Paxton, R. R., and Beyer, G. L. Method for impregnating graphite bodies and the article produced, P (1) 13*d*.

Paymal, J. Acoustic absorption and insulation, (7) 214*c*. Physical basis of thermal conductivity in fibrous insulators, (6) 173*j*.

Payne, J. Mold and process of coating foamed pattern with refractory filler and silicon-containing binder, P (2) 47*d*.

Peacock, J., and Harris, B. Vapor phase oxidation of metal halides to form metal oxides of pigmentary size and apparatus for use therewith, P (8) 251*j*.

Peacor, D. R. See Foit, F. F., Jr.

Pearce, M. L., and Marek, R. W. Formation of silicon and titanium carbides by chemical vapor deposition, (3) 81*f*; correction, (7) 217*g*.

Pearne, F. J., Pearne, F. S., and Robson, F. G. Brick stacker, P (10) 302*b*.

Pearne, F. S. See Pearne, F. J.

Pearne & Lacy Machine Co., Inc. Brick stacker, P (10) 302*b*.

Pearson, A., and MacZura, G. Dry grinding of alumina, P (4) 105*a*.

Pearson, A., Marhanka, J. E., MacZura, G., and Hart, L. D. Dense abrasion-resistant 99.8% alumina ceramic, (8) 241*j*.

Pearson, E. F. See Heslop, R. B.

Pearson, M. A. See Maiman, T. H.; Pastor, R. C.

Peate, E. A. Industrial blue flame burners, (5) 147*d*.

Pebay-Peyroula, J. C. See Chol, G.

Pechiney-Compagnie de Produits Chimiques et Electrometallurgiques. Cooler for finely divided materials and method, P (3) 77*a*. Process for the preparation of crystallized neutral aluminum sulfates having low water content, P (11) 349*b*. Process for the production of purified aluminum nitride, P (11) 340*b*. Rotatable tubular structure embodying a large reserve section and heat exchanger and furnace embodying same, P (8) 229*c*. Solid solutions of fine grain metallic carbides and method, P (8) 241*e*.

Pechkovskii, V. V., and Sofronova, A. V. Study of the thermochemical transformations of copper iodide, (9) 287*h*.

Pecoraro, G. A. Evaluating fireclay refractories for rider arches and tile of preheated glass tank checkers, (11) 337*j*.

Pecuil, T. E. See Weaver, C. E.

Pecuil, T. E., Wampler, J. M., and Weaver, C. E. Study of iron in clay minerals using Moessbauer spectroscopy (extended abstract), B (9) 289*h*.

Peek, S. C., Jr. Incandescent lamp, P (3) 72*j*.

Pei, Y. K. See Keefer, G. E.

Peiser, H. S. See Torgesen, J. L.

Peiser, H. S., and Wachtman, J. B., Jr. Jump rates for point defects in special positions held by a trapping center of noncubic symmetry, (11) 353*j*.

Peisl, H., and Waidelich, W. Lattice parameter change by point defects in irradiated aluminum, B (10) 329*e*.

Peleg, M. See Alcock, C. B.

Pelepelin, V. M. Effect of plastic deformation on the physicomechanical properties of tungsten carbide-cobalt hard alloys, (5) 132*a*.

Peloschek, H. P. See Esveldt, C. J.

Pels Leusden, C. O. See Leusden, C. O. P.

Peltola, V. K. Ultrasonic pyrometer, P (2) 55*h*.

Peltzer, C. See Peters, D. W.

Pena, J. M. G. See Gonzalez Pena, J. M.

Penberthy, H. L. Electrical contact system for ceramic electrodes, P (10) 300*e*.

Pendleton, W. W. See Ostrander, G. W.; Saums, H. L.

Pendleton, W. W., and Ostrander, G. W. Glass composition, conductors and coils insulated therewith, and method of making, P (11) 332*h*.

Penfold, B. R. See Elder, M.

Pennsalt Chemicals Corp. Bismuth diselenide and a method for its preparation, P (2) 50*g*. Molybdenum ditelluride and high-temperature high-pressure synthesis method of preparing, P (8) 241*e*. Tetrafluoroethylene polymer articles having one readily cementable surface containing glass particles, P (5) 130*g*.

Pentronix, Inc. Powder compacting method, P (1) 20*e*.

Peras, A. See Grebenyuk, A. A.

Perchuk, L. L., and Ryabchikov, I. D. Mineral equilibria in the system nepheline-alkali feldspar-plagioclase and their petrological significance, (9) 284*c*.

Percy, J. W. Forty years of temperature measurement, (8) 248*h*.

Perdijon, J. Use of activation analysis for silicates, (6) 181*a*.

Perdue, R. D. See Cohn, M. I.

Pereira, E. See Rossini, A.

Pereira, E., Testa, R. H., and Robredo, J. Thermal behavior of bauxite-clay mixtures, (11) 339*f*.

Perepelitsyn, V. A. See Uglikova, N. S.

Peretti, E. A. See Stegman, R. L.

Peretto, P. See Dautreppe, D.

Perez, A. Vitreous tile and mounting structure therefor, P (2) 49*b*.

Perez-Albuerne, E. A., and Drickamer, H. G. Effect of high pressures on the compressibilities of seven crystals having the NaCl or CsCl structure, (7) 217*c*.

Perez y Jorba, M. Systems GeO_2-Al_2O_3 and GeO_2-Fe_2O_3—comparison with systems based on SiO_2, (10) 326*c*. See Collongues, R.

Perfilova, I. L. See Vasil'kova, I. V.

Peri, J. B. Infrared and gravimetric study of the surface hydration of γ-alumina, (11) 353*d*. Infrared study of adsorption of ammonia on dry γ-alumina, (11) 353*j*. Model for the surface of γ-alumina, (11) 354*f*.

Perieres, R., and Noble, M. Process for the production of purified aluminum nitride, P (11) 340*b*.

Perinet, G. High-temperature X-ray chamber using an image furnace, (3) 75*j*.

Perkin-Elmer Corp. Growth of calcite crystals from a molten flux by slow cooling, P (1) 25*c*. Metal to glass welding, P (4) 94*f*.

Perkins, G. E. See Dudzik, C. J.

Perkins, H. K., and Sienko, M. J. ESR study of manganese-doped α-zinc silicate crystals, (11) 352*f*.

Perlowski, J. S., and Sillick, W. E. Process for manufacturing magnetic oxide, P (2) 52*f*.

Permaglass, Inc. Blasthead structure for tempering glass sheets, P (3) 65*c*. Method and apparatus for curving glass sheets, etc., on a gas support bed, P (7) 199*a*.

Pernot, F. Influence of crucibles on the formation and properties of heavy glasses, (7) 196*a*.

Pernot, F., and Kojima, C. Reactivity of vitreous carbon and glass melts, (7) 197*d*.

Perov, B. V. See Solntsev, S. S.

Perrault, G. Chemical composition and crystalline structure of pyrochlore of Oka, P. Q., (11) 350*f*.

Perron, P. O., and Bell, H. B. Diffusion of phosphorus and sodium in Na_2O-P_2O_5-SiO_2 liquids, (5) 151*a*.

Perry, C. H. See Geick, R.

Perry, D. See Bubb, J. N.

Perry, J. H. Pulpstone mounting flanges, P (5) 123*j*.

Pershan, P. S. See Eisenberger, P.

Peshev, P. See Blieznakov, G.

Pessel, L. Chalcogenide thermoelectric device having a braze comprising antimony compounds and method of forming the device, P (6) 177*c*.

Petch, H. E. See Cuthbert, J. D.

Petch, N. J. See Congleton, J.

Peters, C. E. Electrically heated article, P (7) 198*c*.

Peters, D. W., Feinstein, L., and Peltzer, C. High-temperature electrical conductivity of alumina, (3) 81*b*.

Peters, F. A. See Johnson, P. W.

Peters, F. G. See Sinclair, W. R.

Peters, R. L. Thermal retardation coatings in rocket nozzles and skirts, (2) 46*a*.

Peters, T., Luth, W. C., and Tuttle, O. F. Melting of analcite solid solutions in the system $NaAlSiO_4$-$NaAlSi_2O_6$-H_2O, (2) 58*f*.

Petersen, A. A. Particle classifying-separating apparatus, P (5) 144*d*.

Petersen, D. J. Plaster on metal application, P (5) 125*g*.

Petersen, P. H., and Watstein, D. Shrinkage and creep in prestressed concrete, (9) 262*f*.

Petersen, R. O., and Cutler, I. B. Effects of water vapor on the initial sintering of calcia, (2) 58*c*.

Peterson, D. J., and Logan, T. J. Preparation and methylation of alkali metal phosphides, (1) 12*a*.

Peterson, D. L., Helfferich, F., and Carr, R. J. Measurement of phase equilibria at high pressures by tracer-pulse chromatography, (9) 276*c*.

Peterson, G. E., Bridenbaugh, P. M., and Green, P. NMR study of ferroelectric $LiNbO_3$ and $LiTaO_3$ (I), (5) 139*c*.

Peterson, T. E. Pneumatic controls in the ceramic plant (I, II), (3) 76*d*.

Peterson, W. G. See Gerrard, W.

Petit, G., and Blanc, M. Dilatometric, calorimetric, and ultrasonic techniques for studying saline liquid at high temperatures, (7) 216*h*.

Petri, L. See Jitea, B.; Veiser, I.

Petri, L., Szabo, A., Deica, N., Jitea, B., Dragoman, I., Pommer, E., Corneanu, A., Ivaniov, V., and Strasman, V. Manufacture of superalumina refractories (over 50% Al_2O_3), (9) 267*h*.

Petrov, G. N. See Bushkovich, S. N.

Petrov, K. I. See Korshunov, B. G.

Petrov, S. V. See Kitaigorodskii, I. I.

Petrova, E. V. See Krasotkina, N. I.

Petrovskii, G. T. See Yudin, D. M.

Petrovykh, I. M. See Budnikov, P. P.

Petruzella, J. See Moyson, J.

Petry, E. C. Component sizing apparatus, P (11) 343*i*.

Petry, E. J. Method and apparatus for fabricating crystalline dielectrics having improved shear strength, P (11) 344*c*.

Pett, E. A. See Marshall, D. W.

Pettibone Mulliken Corp. Fine grind hammer mill with adjustable hammer rotor, P (7) 214*c*.

Pettit, F. S. Oxidation mechanisms for nickel-aluminum alloys at 900° to 1300°C, (6) 187*b*.

Pettit, G. D. See Rupprecht, H.

Petzenhauser, I. See Borchert, W.

Petzi, F. See Buchkremer, R.

Petzoldt, J. X-ray investigation in the PbO-ZnO-B_2O_3 oxide system, (3) 88*b*.

Petzoldt, J., and Kordes, E. Investigation of structure in the system MgO-$LiVO_3$, (5) 154*a*.

Peuschel, G. K. Electrostatic separation process and conditioning compositions therefor, P (9) 279*c*.

Pevzner, R. L. See Matveev, M. A.

Pevzner, R. L., and Kharitonov, F. Ya. Methods of testing ceramic materials for strength, (3) 75*j*.

Peyches, P. I. Method and apparatus for glass-making, P (2) 41*f*.

Pfaffenberger, K. Continuous slip-casting line for sanitary ware—production unit of the future? (4) 98*b*.

Pfann, W. G. See Ellis, W. C.

Pfaudler Permutit, Inc. Method of making carbon-containing glass and product thereof, P (7) 199*c*.

Pfaudler-Werke Akt.-Ges. Porcelain enamel composite material, P (1) 4*j*.
Pfizer, Chas., & Co., Inc. See Chas. Pfizer & Co., Inc.
Pfrunder, V. F., and Wickert, H. Accuracy of the complexometric analysis of clinker and cement, (10) 294*a*.
Phelan, R. J., Jr., and Dimmock, J. O. InSb MOS infrared detector, (4) 111*g*.
Phelps, F. L., Jr. See Collins, G. A., Jr.
Phelps, G. W., and Wunnik, J. van. Theory and practice in slip casting, (1) 15*h*.
Phelps, L. A. See Brackpool, J. L.
Philadelphia Quartz Co. Ammonium silicates, P (1) 25*h*. Process for silica and silicates, P (1) 26*a*. Sodium metasilicate pentahydrate product and preparation, P (7) 215*e*.
Philadelphia Quartz Co. of California. Lithium silicate composition, P (10) 318*b*.
Philbrook, W. O. See Tarby, S. K.
Philco-Ford Corp. Fabrication of semiconductor device, P (9) 272*j*. Method of fabricating planar semiconductor devices, P (2) 51*h*. Microcircuits having buried conductive layers, P (8) 245*h*. Photosensitive means for measuring a dimension of an object, P (8) 249*c*. Radiation-sensitive means for detecting flaws in radiation-transmissive materials, P (5) 147*c*. Semiconductive device and method of fabricating, P (6) 178*g*. Thin-film RC circuits on single substrate, P (8) 246*f*.
Philip Carey Mfg. Co. Cement-asbestos products and improvement in the manufacture thereof, P (3) 68*j*.
Philips Electronic & Associated Industries, Ltd. Ceramic ferromagnetic cores for inductors or transformers, P (7) 208*h*. Electrically conductive vitreous materials, P (2) 50*j*. Glass melting, P (7) 198*g*. Glasses which have low thermal conductivities, P (7) 198*h*. Manufacture of compact oxide bodies, P (1) 18*h*. Method of manufacturing glass objects, P (7) 199*d*. Methods and apparatus for manufacturing bodies of semiconductor material, P (2) 51*i*. Methods and apparatus for splitting nonmetallic brittle materials, P (7) 211*f*. Methods of applying a layer containing a metal having a high melting point to a ceramic article, P (5) 142*h*. Methods of bonding refractory bodies, P (7) 205*c*. Methods and devices for rounding off by fire-polishing an edge of a glass object, P (1) 9*j*. Methods of manufacturing glass, P (2) 41*j*. Methods of manufacturing semiconductor bodies of silicon carbide, P (2) 51*i*. Methods of manufacturing semiconductor devices, P (5) 142*i*. Methods of producing semiconductive materials and semiconductor elements made therefrom, P (5) 142*i*. Methods of treating glass articles, P (2) 42*a*.
Philips Electronics & Pharmaceutical Industries Corp. Apparatus with means to measure the characteristic X-ray emission from and the density of a material, P (3) 76*c*. Metal-to-glass-to-ceramic seal, P (3) 73*c*.
Phillips, B. See Chang, L. L. Y.
Phillips, G. See Brown, M. R.
Phillips, L. F. See McEwan, M. J.
Phillips Petroleum Co. Catalyst containing iron oxide, chromium oxide, and a potassium compound, P (8) 250*g*. Method of treating supported chromium oxide catalyst and polymerization therewith, P (4) 105*h*. Titania/chromium oxide catalyst and polymerization process, P (5) 149*c*.
Philpott, A. A., Crump, N. E., and Rado, P. Research into production variables in the manufacture of high-grade alumina for power valves, B (4) 122*d*.
Phinney, W. C. See Himmelberg, G. R.
Physics Technology Laboratories, Inc. Method of determining crystal grain orientation by comparing sputtered patterns, P (11) 348*b*.
Picard, K. E. Prospecting of raw materials for the brick industry in Schleswig-Holstein, (10) 301*i*.
Picard, L. See Serruya, C.
Pickands Mather & Co. Manganese nitride, P (9) 270*e*.
Pickar, P. B. Carbon article coated with beta silicon carbide, P (8) 240*c*. Method of seed-pulling beta silicon carbide crystals from a melt containing silver and the product thereof, P (3) 73*e*.
Pickard, J. E. Glass having dual protective coatings thereon and method for forming such coatings, P (2) 40*j*. Lubricious coating for glass containing polyvinyl alcohol, emulsified polyethylene, and an inorganic acid, P (3) 65*a*. See Lyon, K. C.
Pickavance, A., and Freestone, R. C. Apparatus for press bending and toughening a sheet of glass, P (5) 129*b*.
Picker Corp. X-ray diffraction mechanism in which a monochromator diffracts the X-ray beam in planes transverse to an axis of specimen rotation, P (10) 316*h*.
Pickert, P. E. See Rabo, J. A.
Pickus, M. R. See Williams, M. W.
Picot, P. See Carvelle, B.
Pidgeon, C. R., and Brown, R. N. Interband magnetoabsorption and Faraday rotation in InSb, (11) 353*f*.
Pidgeon, R. T. Rubidium-strontium geochronological study of the Willyama Complex, Broken Hill, Australia, (3) 86*d*.
Piel, T. F. Spray mist proportioning system for glass machine, P (2) 42*e*.
Pierce, E. E. Burner that creates uniform flame size by using progressively smaller holes, P (4) 104*a*.
Pierce, C. I. See Komar, C. A.
Pierce, G. G. See O'Connell, T. B.
Pierce, J. T. Process for preparing improved cryogenic circuits, P (10) 311*g*. See Pritchard, J. P., Jr.
Pierce, R. D. See Wolfe, R.
Pierre, J. See Bonjour, E.
Piezo Technology, Inc. Crystal structures and method of fabricating, P (11) 343*j*.
Pikulin, S. A., and Olesnevich, S. M. Collimated X-ray diffraction analysis of sections in a standard camera, (10) 313*a*.
Pilkington, D. F., and Dickinson, G. A. Method and apparatus for vertically drawing glass from a molten metal bath, P (2) 41*i*.
Pilkington Brothers, Ltd. Apparatus for detecting faults in or on the surface of flat glass, P (4) 94*a*. Apparatus for forming glass ribbon on molten metal with gas seal means, P (2) 40*i*. Apparatus for the manufacture of flat glass on a molten metal bath, P (2) 40*a*. Apparatus for and methods of toughening glass articles, P (10) 300*b*. Apparatus for press bending and toughening a sheet of glass, P (5) 129*b*. Apparatus for skimming dross from a molten metal bath, P (1) 8*c*. Apparatus for supporting a ribbon of glass on a molten metal bath with glass ribbon heel flow means, P (2) 40*b*. Floating refractory drawbar, P (11) 336*a*. Glass, P (5) 129*g*, P (7) 198*d*. Homogenization of molten glass with a flow separator, P (4) 94*d*. Manufacture of cellular material on a molten metal bath, P (4) 94*e*. Manufacture of flat glass, P (2) 41*d*, P (7) 198*j*. Manufacture of flat glass on improved molten metal bath, P (1) 9*h*. Manufacture of flat glass in ribbon form, P (7) 199*a*. Manufacture of plate glass, P (5) 130*e*. Method and apparatus for inhibiting the flow of impurities of a molten bath to the glass sheet thereon, P (11) 336*d*. Method and apparatus for the manufacture of flat glass on a molten metal bath, P (2) 41*g*. Method and apparatus for removing dross from the surface of a molten metal glass sheet float bath, P (9) 265*a*. Method and apparatus for vertically drawing glass from a molten metal bath, P (2) 41*i*. Method of attenuating a ribbon of glass on a molten metal bath, P (2) 41*j*. Method of protecting the surface of the molten bath in a glass sheet float operation, P (3) 66*b*. Method of toughening glass article and article produced, P (4) 95*e*. Methods and apparatus for carrying glass sheets, P (11) 336*b*. Methods and apparatus for toughening sheets of glass with reserve zone, P (11) 336*b*. Methods of heat treating and gas pressure supporting glass in sheet form, P (4) 95*f*. Opposed blasthead apparatus for toughening sheets of glass with spaced vertical deflecting shields, P (4) 95*a*. Pressure rollers for glass ribbon polishing machine, P (6) 171*c*. Protecting slipper for an edge roller in a glass sheet support bath, P (6) 171*e*. Tank and furnace walls, P (4) 95*e*. Toughened sheets of glass, P (4) 95*f*.
Pilkington Brothers, Ltd., and Blood, W. R. Methods of toughening glass articles, P (2) 42*a*.
Pilkington Brothers, Ltd., and Forber, W. E. Mold for glass articles, P (7) 199*e*.
Pilkington Brothers, Ltd., and Hynd, W. C. Manufacture of wired glass, P (2) 41*e*. Refractory elements, P (7) 205*d*.
Pilkington Brothers, Ltd., and Silverwood, F. W. Manufacture of flat glass, P (7) 198*j*.
Pillard, M. Air distributors of burners for solid, liquid, or gaseous fuel, P (4) 104*e*.
Piller, F. See Voross, L.
Pilliar, R. M., and Nutting, J. Solid-solid interfacial energy determinations in metal-ceramic systems, (4) 115*i*.
Pillon, M. See Galabert, P.
Pilsbury, R. C. Labeling nonreturnable soft drink bottles—opportunity or problem, (10) 297*j*.
Piltz, G. Investigations on the origin of cooling damage during firing, (6) 175*f*. Laboratory investigations with direct application to industrial practice, (1) 24*d*.
Pincus, A. G. Forming methods, B (3) 89*d*.
Pink, R. C. See Flockhart, B. D.
Pinney, R. E. See Cone, C.
Pinotti, A. D. See Francel, J.
Pintar, M. See Komac, M.
Pinter, H. J. Welded conductors to carbon and graphite cloth, P (3) 74*f*.
Piot, L. Principles of the modern sheet glass industry contained in an old idea, (6) 168*g*.
Piper, E. G. Calcium sulfate centrifuging, P (7) 194*j*.
Piper, E. L. See McHenry, E. R.
Piper, J. Liverpool lantern, (2) 35*i*.
Piper, R. D. Production of uranium metal from uranium oxide by fused salt electrolysis, (2) 45*f*.
Pirogov, Yu. A. See Boganov, A. G.
Pirson, E. See Nitzsche, S.
Pisarz, E. J. Thermocouple with junction bead compressively supported by plug, P (11) 348*c*.
Pishch, I. V. See Veinberg, T. I.
Piskunova, A. D. See Bokin, P. Ya.
Pistilli, A., and Susin, P. Nonreciprocal ferrite device having a thin dielectric layer encircling the ferrite element, P (2) 52*a*.
Pistorius, C. W. F. T. Effects of pressure on the melting points of the sodium halides, (10) 320*b*. Melting curves of the rubidium halides at high pressures, (6) 187*g*. Phase diagrams of sodium sulfate and sodium chromate to 45 kbars, (6) 187*d*. Phase diagrams of sodium tungstate and sodium molybdate to 45 kbars, (7) 220*j*.
Pistoulet, B. See Delord, J. F.
Pistsov, Yu. N. See Ginzburg, D. B.
Pitak, N. V., and Ansimova, T. A. Reaction of refractories with scale and oxidized steel, (9) 268*f*.
Pitbladdo, R. B. Automatic temperature control for glass molding process, P (6) 170*f*.
Pitt, K. E. G. Evaporated cermet resistors, (11) 342*c*. See Allam, D. S.
Pittsburgh Corning Corp. Cellular glass nodules and method of making, P (3) 65*d*.
Pittsburgh Plate Glass Co. Abrasive marking, P (7) 197*j*. Annealing lehr for glass sheets with reradiating side wall plates, P (9) 264*f*. Apparatus for forming ribbon with lateral force means, P (2) 40*j*. Apparatus for single surface etching of glass plates, P (6) 170*c*. Apparatus for supporting a glass sheet in an upright position for heat treating, P (3) 65*b*. Apparatus for supporting and heating glass sheets on a gas bed, P (6) 170*e*. Conveying glass sheets, P (4) 94*g*. Etching process for producing a nonreflective surface on float glass, P (6) 170*i*. Etching solution and process for producing a nonreflective surface on transparent glass, P (6) 170*i*. Glass articles, P (11) 336*a*. Glass bending stress equalization method, P (5) 129*h*. Glass gripping tongs, P (10) 300*a*. Glass gripping tongs with ballast, P (10) 300*b*. Glass gripping tongs and treatment thereof, P (10) 300*b*. Glass polishing composition containing dissolved zirconium and zirconium oxide, P (9) 265*c*. Glass polishing composition containing an inorganic barium salt, P (9) 265*d*. Glass prepolishing method and apparatus, P (2) 41*a*. Glass sheet press bending apparatus with conveying roller recesses, P (6) 170*d*. Glass sheet press bending apparatus with indexed cover over the shaping surface, P (9) 265*e*. Glass sheet press shaping apparatus with means to adjust the pressing surface curvature, P (5) 130*a*. Glass-cutting control apparatus, P (9) 265*f*. Laminated window panels, P (3) 65*j*. Method and apparatus for equalizing the cooling of a glass sheet supported on a bending mold, P (6) 171*b*. Method of bending and annealing glass sheets with supplemental cooling of hotter areas of the glass, P (9) 265*a*. Method for bending glass sheets, P (3) 65*d*. Method of controlling heat application to glass to repair scored regions, P (2) 41*a*. Method of controlling the thickness of float glass, P (3) 65*d*. Method of drawing a glass sheet, a portion of its surface being untouched, P (1) 9*j*. Method for fabricating multiple glazing units, P (4) 95*a*. Method of forming a glass ribbon on a gas support bed, P (3) 65*f*. Method of heat treating glass sheets on a gaseous support bed, P (1) 9*c*. Method of increasing stain resistance of a glass body subjected to an ion exchange strengthening setup, P (3) 65*g*. Method of making glass polishing composition, P (9) 265*d*. Method of preparing slurries of siliceous pigment, P (7) 214*i*. Method of press bending glass sheets between cold opposed shaping molds, P (6) 171*f*. Method of press bending vertically suspended glass sheets, P (1) 9*f*. Method of removing contaminates from the protective atmosphere of a glass sheet float bath, P (3) 66*c*. Method of shifting glass on a molten metal bath, P (3) 66*d*. Method of strengthening a glass article by ion exchange, P (3) 66*e*. Method of varying the thickness of a glass sheet while on a molten metal bath, P (1) 9*i*. Preliminary pressing of bent glass laminated assemblies, P (2) 42*c*. Press bending mold having modified recesses for the glass sheet engaging means, P (9) 265*j*. Process for packaging siliceous pigments, P (9) 279*c*. Process for preparing metal oxides, P (8) 251*d*. Process for preparing titanium dioxide, P (3) 78*b*. Silver and copper coated articles protected by treatment with aminoazole compounds, P (8) 236*c*.
Piven, I. Ya., and Naloichenko, L. V. Accelerating the grinding of raw materials for radio ceramics, (8) 242*h*.
Pixley, G. W. Automatic molded brick production—basic concept and a practical application, (2) 42*g*.
Pizzarello, F. A. See Dill, H. G.
Plaehn, J. See Weinhold, J.
Plandl, J. N. See Marshall, R.
Planer, G. See MacLachlan, D. F. A.
Plank, C. J. See Wadlinger, R. L.
Plank, C. J., and Rosinski, E. J. Catalytic conversion of hydrocarbons with the use of a steam treated Y type of crystalline aluminosilicate, P (10) 318*a*.
Platov, A. B. See Brokhin, I. S.
Platt, R. O., and Veverka, V. C. Apparatus for handling and impregnating brick, P (4) 96*j*.
Platunov, E. S. Theoretical basis for the measurement of the true specific heat of refractory materials while they are cooling, (5) 146*f*.
Plendl, J. N. See Jasperse, J. R.
Plendl, J. N., Mansur, L. C., Hadni, A., Brehat, F., Henry, P., Morlot, G., Naudin, F., and Strimer, P. Low-temperature far infrared spectra of SiO_2 polymorphs, (8) 254*g*.

Plessey Co., Ltd. Ceramic powders, P (2) 56*f*. Production of carbonaceous bodies containing carbides, P (1) 14*f*.
Plessey-UK, Ltd. Method for producing sintered nonmetallic magnetic materials, P (9) 274*h*.
Pletyushkin, A. A. See Ivanova, L. M.
Plibrico Co., Ltd. Apparatus for applying refractory material to structures, P (2) 46*e*.
Plieth, K., and Saenger, G. Structure of stranskiite, $Zn_2Cu(AsO_4)_2$, (9) 286*h*.
Pliner, Yu. L. See Musikhin, V. I.
Pliskin, W. A. See Wesson, R. A.
Pliskin, W. A., and Esch, R. P. Simple technique for very thin SiO_2 film thickness measurements, (11) 356*b*.
Pliskin, W. A., and Lehman, H. S. Structural evaluation of silicon oxide films, (4) 116*a*.
Plisko, T. A. See Sil'vestrovich, S. I.
Ploche Sklo Narodni Podnik. Method for suppression of harmful recrystallization of glass powders on heating, P (2) 41*i*.
Ploetz, G. L. See Lang, J. E.
Plotnikova, M. V. See Gendler, T. S.
Plueddemann, E. P. Bonding of organic resins or rubbers to inorganic substances, P (11) 335*g*. Bonding of organic resins to siliceous materials, P (11) 335*h*.
Plumat, E. R. Method of and apparatus for protecting sheet glass during the thermal treatment thereof, P (10) 300*i*. New sulfide and selenide glasses—preparation, structure, and properties, (10) 298*g*. Process for producing glass/metal compositions, P (5) 130*c*. Spout for the discharge of molten glass, P (2) 42*e*. See Brichard, E.
Plumat, E. R., and Duperroy, M. Device for the working of pasty fusion products, P (8) 235*g*.
Plumat, E. R., and Jacobs, A. Electrode device for electric furnaces, P (8) 235*h*.
Plyushchev, V. E. See Grizik, A. A.; Samuseva, R. G.
Plyusnina, I. I. Infrared Spectra of Silicates, B (7) 225*f*.
Poch, W. Permanent densification of B_2O_3 glass by hydrostatic and nonhydrostatic pressures up to 55 kbars and 140°C, (1) 6*e*. See Bray, P. J.
Podchernyaeva, I. A. See Samsonov, G. V.
Podest, M., and Jakesova, L. Sintering of ceramics from uranium dioxide (III) dispersity and microagglomerate state of uranium dioxide, (3) 68*d*.
Podgaetskii, V. M., and Chernets, A. N. Polarization of stimulated radiation from neodymium ions in a glass base, (10) 298*h*.
Podini, P. Properties of *F* centers in NaF, (8) 256*i*.
Podini, P., and Spinolo, G. Some relevant parameters of the *F* center, (11) 356*h*.
Podmore, H. L. Grinding operations, P (3) 75*a*.
Podmore & Sons, Ltd., and William Boulton, Ltd. Grinding operations, P (3) 75*a*.
Podoksik, L. See Pastor, R. C.
Podolsky, L. Method of producing oriented graphite, P (1) 13*k*.
Poegel, H. J. Processes in the formation of glass fibers, (10) 298*a*.
Poehler, T. O. Temperature dependence of microwave emission from indium antimonide, (2) 50*h*.
Poehler, T. O., Apel, J. R., and Hochberg, A. K. Millimeter wave radiation from indium antimonide, (5) 154*j*.
Poenisch, A. P. See Kay, E.
Poetke, W. See Jeschar, R.
Poffenbarger, J. D., Jr., and Nau, T. P., Jr. Soft ferrites solve magnetic core problems, (8) 243*d*.
Pogarskaya, T. I. See Brutskus, T. K.
Pohl, F. A. Method of making fuel cell electrodes comprised of borides, carbides, nitrides, and/or silicides of transition metals, P (8) 241*b*.
Poi, H. See Sato, H.
Poindexter, J. M. See Gruber, J. B.
Point, M. A. R. Electrostatic coating system, P (8) 247*c*.
Pointon, A. J. See Robertson, J. M.
Poix, P. Relation between the crystal parameter and the anion-cation distances in compounds with the perovskite structure, (6) 188*h*.
Pokrovskii, B. I. See Komissarova, L. N.
Polak, A. F. See Volkov, O. S.
Polak, L. S. Chemical processes in low-temperature plasmas, (10) 312*b*.
Poland, D. E., Kuriakose, A. K., and Margrave, J. L. Oxidation of titanium monoxide at high temperatures, (11) 355*e*.
Poland, M. E. Insulator body having an electrically conductive surface and method, P (11) 343*i*.
Polinsky, M. A., and Damon, G. F. Method of stabilizing semiconductor devices having exposed surfaces of a hydrophilic oxide [SiO_2], P (2) 51*h*.
Polishchuk, V. S. Experience in producing refractory compounds under industrial conditions, (2) 44*f*.
Politan'ska, U. See Vol'ski, V.
Pollack, H. Alumina-zircon ceramic coatings and bodies, P (8) 240*a*.
Pollack, S. R., and Morris, C. E. Method of improving the electrical characteristics of thin-film metal-insulator [Al_2O_3]-metal structures, P (4) 100*b*.
Pollack, S. S. See Granquist, W. T.
Pollak, F. J. See Shaklee, K. L.
Pollak, P. I. See McAleer, W. J.
Pollard, L. J. See Angell, C. A.
Pollard, R. E. See Wyman, L. L., Sr.
Pollock, B. D. Refractory metal dispersion, P (2) 48*a*.
Pollock, T. "The trouble with you is . . .," (1) 34*d*.
Pollyak, V. V. See Kataeva, G. V.
Poluboyarinov, D. N. See Kuznetsova, I. G.; Skidan, B. S.
Poluboyarinov, D. N., Popil'skii, R. Ya., Galkina, I. P., and Bakunov, V. S. Creep of ceramic materials in the MgO-$MgAl_2O_4$ system, (9) 280*h*.
Poluboyarinov, D. N., Shapiro, E. Ya., Bakunov, V. S., and Akopov, F. A. Change in electrical conductivity and rate of creep of sintered CeO_2 ceramic during its reduction, (6) 184*e*.
Polyachenok, O. G. Enthalpy of formation of the fluorides of lanthanum and praseodymium, (9) 282*c*.
Polysius G.m.b.H. Method of conveying fine granular and pulverous material by gaseous means, P (11) 345*j*.
Pomerantz, D. I. Anodic bonding, P (11) 343*e*.
Pomfrett, J. M. Reflector discharge lamp having frosted envelope and arc [quartz] tube, P (8) 236*b*.
Pommer, E. See Petri, L.
Poncelet, E. F. Modern concepts of fracture and flow (IV) theory of flow, (2) 39*h*.
Ponomarenko, B. F., Samoilov, V. I., and Ulyakov, P. I. Polarization-optical studies of the destruction of transparent dielectrics by laser beams, (10) 308*b*.
Ponomarev, I. F. See Lokot, A. A.
Ponomarev, N. M. See Dolomanov, L. A.
Pontelandolfo, J. M. See White, J. L.
Poole, C. P., Jr., and Itzel, J. F., Jr. Electron spin resonance study of the antiferromagnetism of chromia alumina, (5) 138*f*. Optical reflection spectra of chromia alumina, (5) 156*e*.
Poole, D. M. See Hodkin, E. N.
Poole, J. P. Glass workability, (2) 39*f*. Research in the glass industry, (9) 264*g*. Treatment of melting glass with SO_2, P (7) 199*c*.
Pooley, D., and Runciman, W. A. Production of *F* centers in pure potassium bromide by ultraviolet irradiation, (11) 355*f*.
Popa, S. See Veiser, I.
Popel, S. I. See Sherstobitov, M. A.
Popescu, V. See Dumitrescu, T.
Poph, W. See Haschka, H.
Popichenko, E. Ya. See Dobrovol'skii, A. G.
Popil'skii, R. Ya. See Poluboyarinov, D. N.
Popil'skii, R. Ya., and Nishanova, I. E. Processes in the firing of quartz-glass shapes, (6) 168*h*.
Popova, M. A. See Darvoid, T. I.
Popova, N. M. See Fedorov, T. F.
Popova, O. S. See Satalkin, A. V.
Popper, P. Properties of high-alumina ceramics, B (9) 291*g*. (editor) Use of Ceramics in Valves—Proceedings of a Symposium Held Under the Auspices of the Coordination of Valve Development Organization, Ministry of Defence, at the Laboratories of the British Ceramic Research Association, March 1965, B (4) 122*d*.
Porai-Koshits, M. A. See Ionov, S. P.
Poravski, B. See Vol'ski, V.
Porrenga, D. H. Clay minerals in recent sediments of the Niger Delta, B (8) 259*e*.
Porta, P. D. See Della Porta, P.
Porte, H. A., Greenberg, E., and Hubbard, W. N. Fluorine bomb calorimetry (XII) enthalpy of formation of ruthenium pentafluoride, (11) 352*j*.
Porter, D. D. See Arnold, A. J.
Porter, M. C. See Jones, W. C.
Porter, W. F. Apparatus for forming fibers, P (6) 170*b*. Combustion chamber burner and method for its operation, P (4) 104*a*. Fiber attenuating apparatus, P (2) 40*f*. Fiber attenuating burner, P (6) 170*f*.
Portnoi, K. I., Yimofeeva, N. I., and Fadeeva, V. I. Reaction of oxides of the rare earth elements with chromium, (10) 324*h*.
Porto, S. P. S. See Damen, T. C.; Tell, B.
Porto, S. P. S., Tell, B., and Damen, T. C. Near-forward Raman scattering in zinc oxide, (10) 323*g*.
Posner, A. M. See Laffer, B. G.
Posner, E., and Kennedy, M. C. S. Further study of china bisque placers in Stoke-on-Trent, (6) 191*b*.
Posney, R. V. See Barch, H. W.
Pospisil, Z., and Pospisilova, B. Production of building plaster in rotary drum dryers, (5) 125*h*.
Pospisilova, B. See Pospisil, Z.
Poss, S. M. See Laferty, J. M., Jr.
Post, R. C., III. See McCrary, J. W., Jr.
Posypaiko, V. I. See Dombrovskaya, N. S.
Potain, F. Flowerpots, P (8) 228*b*.
Potie, N. Use of natural gas in tile and brick works—recent development in southwestern France, (10) 317*d*.
Potocki, E. A. See Elarde, V. D.
Potschigmann, W. Blunging of raw kaolin, (10) 312*a*.
Potter, A. See Chu, G. P. K.
Potter, J. F. See MacChesney, J. B.
Potter, N. D. See Hildenbrand, D. L.
Potter, P. E. Studies of the sintering behavior of plutonium dioxide, (8) 257*i*.
Potter, R. M. Process for making *n*-type zinc cadmium sulfide electroluminescent material, P (6) 178*e*.
Potter, T. J. See Elyard, C. A.
Pouchard, M. See Kasper, J. S.; Vandeven, V.
Pouchard, M., Casalot, A., Villeneuve, G., and Hagenmuller, P. Magnetic and electrical properties of vanadium bronzes, $M_xV_2O_5$ (M = Na,K), (1) 29*i*.
Pouchard, M., and Hagenmuller, P. System $K_xV_2O_5$—some new families of vanadium bronzes, (1) 33*f*.
Poulton, J. W. See Jagaciak, G. J.
Pourtau, J. J. Mechanical device for laying tiles or mosaic flooring, P (7) 206*h*.
Powell, D. E., and Spear, B. W. Cathode-ray tubes and method of reinforcing them, P (8) 244*a*.
Powell, R. W. See Ho, C. Y.
Pozdnjakov, P. G. See Vasin, I. G.
Pozhilov, A. S. See Sulimenko, L. M.
Prabhakaram, P. Role of monovalent and divalent cations in the dehydroxylation of kaolinite, (5) 158*c*.
Prager, P. See Klein, A. G.
Pramatus, S. See Rundqvist, S.
Pranatis, A. L. Phase fields and thermal expansion of oxides of copper, (4) 114*b*.
Pranckevicius, G., Dauknys, V., and Jurenas, V. Thermal resistance of refractories (II) high-temperature apparatus to obtain thermal conductivity and thermal shock resistance, (5) 134*h*.
Prasad, J. See Bishui, B. M.
Prasad, P. See Sachdev, P. L.
Prasad, R. S., and Isard, J. O. Dielectric properties of some glasses at 40 Gc/sec, (5) 127*b*.
Prasad, S. N. See Gupta, S. K.; Ram, A.
Prasad, S. N., and Srivastava, K. P. Measurement of viscosity of copper ruby glass by the fiber elongation method, (2) 39*g*.
Prat, R., and Prod'homme, L. Methods of observing the quality of polished glass surfaces, (6) 168*a*.
Pratt, H. R. C. Multistage separation processes (I) ideal and squared cascades; (II) thermodynamic efficiency of separation processes, (5) 143*h*.
Pratt, I. H. Processing and evaluation of rf-sputtered quartz, (10) 308*d*.
Pratt, P. L. See Thompson, D. S.
Prazak, C. J. See Schwartz, J. W.
Precision Sampling Corp. Chromatographic sample injection apparatus, P (3) 76*d*.
Preesz, L. du. See Dyer, H. B.
Preier, H. Contributions of surface states to MOS impedance, (5) 150*g*.
Prentice, J. E. Constitution and behavior of brick clays, (5) 150*g*. Reserves of brickmaking clay in Britain—a geologist's view, (1) 25*e*. Weathering of brick clays, (10) 302*a*.
Prentice, W. H. See Mullan, J. J.
Pressarts, Ltd. Water closet installations, P (10) 306*f*.
Pressley, R. J. See Kiss, Z. J.
Preston, J. B., Carter, R. S., and Neely, W. C. Flash photolysis spectroscopic system, P (3) 76*f*.
Pretorius, S. T., and Mandersloot, W. G. B. Leschonski modification of the Sartorious sedimentation balance for particle size analysis, (1) 21*d*.
Preuss, H. Modern theoretical reviews on the chemical bond, (5) 155*c*.
Pribylov, K. P. See Berg, L. G.
Price, A. M. See Kelly, B. T.
Price, D. Time-of-flight mass spectrometry, (11) 347*a*.
Price, G. H. See Stuart, W. I.
Price, G. H., Stuart, W. I., and Walker, D. G. Crystallite growth of beryllium oxide powders and its inhibition by adsorbed phosphate, (10) 319*c*.
Price, R. B. See Elleman, T. S.
Price, R. J. See Bokros, J. C.
Price, R. J., and Bokros, J. C. Mechanical properties of neutron-irradiated pyrolytic carbons, (10) 323*f*.
Prikhod'ko, L. I. Conditions of preparation of materials based on boron and aluminum nitrides, (8) 237*a*.
Prince, P. Application of statistical methods for quality control in the tile industry, B (9) 291*a*.
Prins, J. A. Characterization of amorphous substances, (6) 180*f*. See Aken, J. E. van.
Prior, H. D., and Thomas, E. A. Application of zircon and Zirmul refractories in glass tank superstructure, (11) 337*g*.
Pritchard, J. P., Jr., and Pierce, J. T. Process for manufacturing multilayer film circuits, P (5) 142*e*.
Process Engineering Co., Inc. Separation of substances, P (10) 318*g*.
Prod'homme, L. See Prat, R.
Prod'homme, L., and Vacherand, C. Light-scattering study of structural changes leading to devitrification, (7) 196*c*.
Prod'homme, M., and Brochet, M. Effect of the surface condition of glasses on their resistance to leaching by soda, (6) 167*b*.
Produits Chimiques Pechiney-Saint-Gobain. Porous alumina products and method of manufacture, P (8) 251*a*.
Prokhodtseva, L. V. See Drozdovskii, B. A.
Prokhorova, I. Ya. See Aleksandrova, T. A.
Prokof'eva, Z. M. See Kordonskaya, R. K.
Prokopets, V. F. Complexometric determination of total amount of lead in Pb_2O_3, PbO_2, and PbF_2 used in the glass industry, (11) 333*g*.
Proks, I. Measurement of kinetics of decomposition of calcium carbonate with a recording thermobalance, (2) 58*g*.
Proks, I., Eliasova, M., Pach, L., and Zlatovsky, I. Calorimeter for measurement of heats of solution, (7) 211*j*.
Prosen, R. J. Biaxially anisotropic magnetic thin film structure with magnetic discontinuities, P (11) 343*f*.

Prost, L. Development of refractory products, (10) 302*d*.
Provance, J. D. See Kelley, L. W.
Provisor, H. Method of producing black metal-containing surface layers, P (1) 18*g*.
Provisor, H., and Lapluye, G. Method of passivating supports for semiconductor sulfides, selenides, and tellurides, P (3) 73*d*.
Provost, G. Apparatus for the measurement of thermal expansivities above 2000°C, (6) 179*i*. See Dumez, P.
Provost, G., and Pagano, M. Apparatus for measuring the modulus of elasticity at high temperatures, (10) 313*f*.
Prshedromirskaya, E. M. See Kukota, Yu. P.; Sleptsov, V. M.
Prshedromirskaya, E. M., Kukota, Yu. P., and Sleptsov, V. M. Strength characteristics of porous material of refractory compounds, (8) 239*h*.
Prshedromirskaya, E. M., and Sleptsov, V. M. Relations in the sintering of porous parts from high-melting-point compounds, (11) 339*c*.
Pruden, G. See King, H. G. C.
Prudnikov, V. N. See Pavlushkin, N. M.
Prunisaux, B., Grunberg, G., Melnick, I., and Cordelle, M. Oxidized aluminum for passive thin-film circuits, (10) 307*f*.
Pruss, T. V. See Sahm, P. R.
Prutton, M. See Chambers, A.
Pryor, A. W. Electrical conductivity of BeO, (3) 67*e*.
Pryor, A. W., and Sabine, T. M. Thermal vibrations in BeO, (3) 68*g*.
Pryor, A. W., Tainsh, R. J., and White, G. K. Thermal conductivity at low temperature of neutron irradiated BeO, (3) 68*f*.
Pryor, J. N. Process for making high strength molecular sieve nodules and extrudates, P (7) 215*d*.
Przhiyalgovskii, S. M., Smirnov, V. N., and Yakubovich, A. L. Determination of titanium by an X-ray fluorescence method using a ^{55}Fe radioactive source, (11) 346*g*.
Pshenichkin, P. A. See Fialkov, A. S.
Pugachev, G. S. See Vitman, F. F.; Volovets, L. D.
Pugh, N. R., and Bell, T. M. Color standardization and control (I) color control depends on management determination; (II) visual color comparisons, (2) 60*d*; (III) setting up a color control program, (3) 89*a*.
Puig Cardona, M. See Coronas Ribera, J. M.
Pukh, V. P. See Vitman, F. F.
Pulker, H. K. Factors influencing the accuracy of a quartz-crystal oscillator as a thickness monitor for thin film deposition, (10) 307*h*.
Pullen, F. R., and McLachlan, E. K. Division wall for soaking pits, P (7) 204*b*.
Pullen, J. B. Carbon-coated alumina and process for making, P (4) 104*h*.
Pulliam, G. R. See Mee, J. E.
Pullman, Inc. Pusher for kilns and method of charging kilns, P (10) 317*c*.
Pulos, A. J. State of decorative arts in the United States, (7) 194*c*.
Pultz, W. W. Method of making macroscopic silicon carbide fibers with a silica sheath, P (6) 174*h*.
Pultz, W. W., and Hertl, W. $SiO_2 + SiC$ reaction at elevated temperatures (I) kinetics and mechanism, (3) 86*g*.
Pulvari, C. F. Electrical devices embodying ferrielectric substances, P (5) 141*a*. Lamellated dielectric of mixed bismuth oxides, P (4) 100*e*.
Pummery, F. C. W. See Faircloth, R. L.
Pungor, E. See Henrion, G.
Punwani, D., Chi, C. W., and Wasan, D. T. Dynamic sorption by hygroscopic salts, (11) 351*j*.
Pupko, S. See Paul, C.
Purcell, T. See Weeks, R. A.
Pure Carbon Co., Inc. Method for impregnating graphite bodies and article produced, P (1) 13*d*.
Purmetall Werner Funke. Pneumatic conveying means for supplying granular material, P (5) 144*e*.
Purvis, T. L. See Roberts, J. W.
Puryga, S. S. See Zaichenko, A. R.
Pusch, R. Quick clay microstructure, (7) 220*f*.
Pusch, W. G., and Stafford, W. L. Consumable product for ingot hot tops, etc., P (2) 46*i*.
Puskar, V. See Allegrini, A. P.
Pustovoit, L. T. See Kosolapova, T. Ya.
Putner, T. Small scale radio frequency sputtering apparatus, (11) 342*i*.
Puttlitz, K. J. See Delaney, R. A.
P'yachev, V. A., and Ragozin, V. V. Titanium-containing blast-furnace slag as a component of cement charge, (3) 63*a*.

Quass, J. F. Coated carbide particles, P (6) 174*a*.
Quakernaat, J., and Gastner, M. Sample changer for oriented clay aggregates in X-ray diffraction, (8) 248*f*.
Quast, R. Spectrophotometric comparison of several iron determination methods, (5) 146*a*.
Quataert, D., and Schleicher, H. W. Study of irradiated and unirradiated coated fuel particles by the electron microprobe, (4) 117*b*.
Quate, C. F. See Lean, E. G. H.
Quebec, Ministere des Richesses Naturelles. Water-soluble lithium compounds, P (1) 26*c*.
Queensberry, Lord. Aesthetics and the trade,(7) 193*j*.
Queisser, H. J. Luminescent semiconductor devices including a compensated zone with a substantially balanced concentration of donors and acceptors, P (9) 273*f*.
Queisser, H. J., and Panish, M. B. Luminescence of zinc doped solution grown gallium arsenide, (8) 255*a*.
Quentin, R. J., and Boone, F. H. Identification of cords in glass, (2) 39*a*.
Quetsch, J. G., Jr., and Saia, F. J. Semiconductor device manufacture, P (4) 101*f*.
Queyroux, F. Existence of a new composition, Yb_4TiO_{11}, in the Yb_2O_3-TiO_2 equilibrium diagram, (7) 217*c*.
Queyroux, F., Harari, A., and Collongues, R. Crystal chemistry of the rare-earth oxides, (6) 184*c*.
Quigley Co., Inc. Furnace wall of blocks with embedded fastening elements, P (7) 204*c*. Method for prolonging the life of refractory linings in furnaces of the Kaldo, Linz-Donawitz, De May, or basic or acid converter types, P (2) 47*c*.
Quincey, G. Glass vs. plastics, (11) 334*f*.
Quinn, J. J., Jr. Economics of spray drying, (8) 246*j*.
Quint, S. M. See Gillis, R. P.
Quint, S. M., and Adams, R. H. Method and apparatus for manufacturing asbestos-cement [pipe], P (5) 135*i*.
Quintin, M. See Nicolas, J.
Quirk, J. P. See Laffer, B. G.
Quirk, R. F. See Butler, K. H.; Ropp, R. C.
Quon, H. H., McDonald, R. D., and Sadler, A. G. Effect of solid solution on the Curie temperature in the Fe_2O_3-Mn_2O_3 and Fe_2O_3-Cr_2O_3 systems, (11) 352*c*.
Qureshi, A. A., Safdar, M., Ali, A. S., and Rehman, A. Metallic lusters, (9) 270*j*.
Qureshi, M. H. See Faruqi, F. A.
Qureshi, M. H., Haq, A., and Faruqi, F. A. Fusion study of Rajdhwari feldspar, (10) 305*i*.

Raab, S. See Lebek, A.
Rabbe, P. See Charpentier, P.
Rabenau, A. Chemical problems in semiconductor research, (3) 71*a*.
Rabo, J. A., Pickert, P. E., and Boyle, J. E. Hydrocarbon conversion catalysts, P (5) 148*c*.
Rabusin, E. See Della Porta, P.
Raccah, P. M. See Longo, J. M.; Menyuk, N.
Raccanelli, A. See Crepaz, E.
Rachev, V. V., Kovba, L. M., and Ippolitova, E. A. High-temperature X-ray study of the system uranium-oxygen in the range $UO_{2.00}$ to $UO_{2.40}$, (3) 81*e*.
Rachev, V. V., Smurova, V. S., Kovba, L. M., and Ippolitova, E. A. Study of the uranium-oxygen system in the range $UO_{2.50}$ to $UO_{2.67}$ by high temperature X-ray phase analysis, (10) 325*e*.
Rachor, L. Apparatus for forming hollows in spherical fuel elements, P (7) 204*e*.
Radchenko, M. E. Determination of the ordering temperature of the Fe_3Si alloy, (3) 79*j*.
Rademacher, G. F. Creepage spark type plug having low voltage igniter seal, P (1) 17*e*.
Rademachers, J. See Zirngibl, H.
Rademaker, J. C. See Williams, S. E.
Radford, C. Particle size measurement—reporting of results, (10) 315*e*.
Radford, C., Austin, L. K., and Collier, J. Effect of flocculants on the plasticity of bone china (I, II), (2) 48*j*.
Radford, K. C. See Pascoe, R. T.
Radhakrishna, B. P., and Rao, N. V. Occurrence of amosite asbestos in the formations of Babubudan, Chikmagalur district, Mysore, (1) 25*d*.
Radhakrishnan, K., and George, T. M. Microelectronics—a review, (5) 139*a*.
Radio Corp. of America. Cathode ray tube with mosaic type phosphor screen, P (3) 72*b*. Chalcogenide thermoelectric device having a braze comprising antimony compounds and method of forming the device, P (6) 177*c*. Composite insulator-semiconductor wafer, P (5) 140*i*. Electrolysis-resistant electron discharge device, P (5) 141*e*. Element and apparatus for generating coherent radiation, P (3) 72*f*. Ferroelectric circuit element material and transducer utilizing it, P (1) 17*h*. Field-effect transistor with gate-insulator variations to achieve remote cutoff characteristic, P (6) 177*j*. High power multiemitter transistor, P (8) 244*f*. Indium doped pickup tube target, P (2) 51*e*. Insulated-gate field-effect transistor, P (6) 177*e*. Insulated-gate field-effect triode with an insulator having the same atomic spacing as the channel, P (3) 73*a*. Latched ferrite circulators, P (2) 51*f*. Low resistance bonds to germanium-silicon bodies and method of making such bonds, P (1) 18*g*. Method of decreasing the minority carrier lifetime by diffusion, P (3) 73*e*. Method of electrically isolating semiconducting circuit components, P (8) 245*e*. Method of fabricating semiconductor device, P (9) 273*j*. Method of forming a p_n junction by vaporization, P (6) 178*a*. Method of making color kinescopes of the line-screen sensing variety, P (5) 141*j*. Method of making a multialkali cathode, P (6) 178*e*. Method of making passivated semiconductor devices, P (5) 142*a*. Method of making reed switches, P (5) 142*a*. Method of making semiconductor devices, P (8) 245*a*. Method for preparing a europium-activated yttrium vanadate phosphor, P (8) 245*c*. Method of salvaging phosphor slurry in a spin coating process for making phosphor screens for cathode-ray tubes, P (4) 100*h*. Method of separating frit sealed parts of an electron tube, P (9) 274*j*. Method of stabilizing semiconductor devices having exposed surfaces of a hydrophilic oxide [SiO_2], P (2) 51*h*. Optical system for use in making color-phosphor mosaic screens, P (8) 245*h*. Process for preparing yttrium vanadate phosphors, P (4) 101*a*. Resistor comprising spaced metal coatings on a resistive layer and traveling wave tube utilizing it, P (5) 142*g*. Semiconductor devices, P (2) 52*d*, P (5) 142*h*. Semiconductor gallium arsenide with germanium connecting layer, P (5) 142*j*. Thermoelectric generator including silicon germanium alloy thermoelements, P (1) 19*b*. Thin film resistor composed of chromium and vanadium, P (4) 101*f*. Vanadium-containing lithium ferrites, P (6) 179*a*.
Rado, P. See Philpott, A. A.
Radomysel'skii, I. D., Barshchevskaya, L. F., and Negoda, G. P. Investigation of the quality of mixing and the productivity of mixing units, (8) 238*j*.
Radomysel'skii, I. D., and Shcherban, N. I. Relations in the pressing of two-component cermet materials, (11) 339*b*. Use of glass in powder metallurgy, (5) 129*f*.
Radosevich, C. L. See Krikorian, N. H.
Radoslovich, E. W. Cell dimension studies on layer-lattice silicates—a summary, B (5) 160*h*. See Burnham, C. W.
Radovskii, I. Z. See Krentsis, R. P.
Radul, N. M. See Tarasewich, Yu. I.
Raebel, G. See Schenck, H.
Raffalovich, A. J. Method of making thin film capacitor, P (11) 344*c*.
Rafikov, T. K. See Abdeeva, M. I.
Ragavan, K. S., and Kuhlmann-Wilsdorf, D. Tensile behavior of single crystal gold films—a phenomenological theory, (5) 159*e*.
Ragland, P. C. See Hermes, O. D.
Ragozin, V. V. See P'yachev, V. A.
Rahe, V. Apparatus for blending glass, P (2) 40*h*.
Rahrig, D. D., O'Connell, T. B., and Ferguson, C. W. Method for tempering and conveying glass sheets, P (6) 171*b*.
Raine, F. F., and Cooper, G. E. Refractory and method, P (3) 69*e*.
Rainville, D. Apparatus for modifying the fluid content of particulate material, P (10) 317*e*.
Raithel, K. Method for indiffusion of foreign material into a monocrystalline semiconductor member, P (7) 209*e*. Method of producing thyristors by [Au] diffusion in semiconductor material, P (1) 18*i*.
Raj, P., and Amirthalingam, V. Calculation of electric-field-gradient tensor for a single crystal of paramagnetic $CuCl_2 \cdot 2H_2O$, (11) 350*c*.
Rajagopalan, K. Process for the manufacture of refractory magnesia chrome basic and chrome magnesia brick, P (5) 136*c*.
Raju, K. S. See Patel, A. R.
Raju, P. V. S. Hydromagnetic flow due to the torsional oscillations of a porous infinite plate, (10) 321*j*.
Rakhshtadt, Yu. A. See Dolomanov, L. A.
Ralls, K. M. See Williams, M. W.
Ralph, B. See Fortes, M. A.; Smith, D. A.
Ralph, J. E. See Halperin, A.
Ram, A., Prasad, S. N., and Srivastava, K. P. Viscosity of copper ruby glass in and below the striking range of temperature, (7) 197*i*.
Ram, Inc. Glass bonded ceramic ware pressing mold and method of making, P (9) 271*g*.
Ramachandran, V. S. See Feldman, R. F.
Ramachandran, V. S., Garg, S. P., and Satiya, R. C. Calcium silicate brick, (3) 62*b*.
Ramachandran, V. S., Kacker, K. P., and Handa, K. N. Identification of clay minerals by IL/DA technique, (5) 145*b*.
Ramakrishnan, P. Hot-pressing of magnesium oxide, (10) 303*f*.
Ramamurthi, T. V. Ferrites—their indigenous development and production, (6) 176*i*.
Ramamurthi, T. V., Ganapathy, C. V., Gupta, S. C., and Govindaswamy, G. Soft ferrite manufacture from mineral iron ore, (8) 243*c*.
Ramamurthy, L. Elastic constants of single crystal corundum below room temperature, (8) 253*a*.
Ramamurthy, P. See Low, M. J. D.
Ramamurti, J., and Teegarden, K. Intrinsic luminescence of RbI and KI at 10°K, (10) 322*a*.
Raman, K. V., and Jackson, M. L. Layer charge relations in clay minerals of micaceous soils and sediments, B (8) 259*i*. Vermiculite surface morphology, B (6) 192*c*.
Ramanath, T. V., Ganapathy, C. V., Sharma, V. N., and Khanduja, R. S. Properties of ferrite antenna rods made from iron ore and their effect on receiver performance, (8) 243*a*.
Ramankulov, M. R. See Timashev, V. V.
Ramasubramanian, N. See Low, M. J. D.
Ramaswamy, P. S., and Bhattacharya, J. Microscopic examination using replica technique, (1) 22*e*.
Rambabu, H., and Rao, G. V. U. Correction factor for volume differences in the estimation of beach sand minerals of Kerala, (10) 313*d*.
Ramberg, E. G., and Epstein, D. W. Optical system for use in making color-phosphor mosaic screens, P (8) 245*h*.
Ramm, D. E. Core structure for an electroluminescent device and method of formation thereof, P (10) 300*j*.

Rampacek, C., Browning, J. S., and McVay, T. L. Process for washing and removing organic heavy liquids from mineral particles, P (1) 26*a*.
Ramsey, N. F. See Mehran, F.
Ramsey, T. H., Jr. Semiconductor element having an organic silicone base cement, P (8) 246*h*.
Ranc, R. See Koch, C.
Rand, M. J. Method for coating semiconductor devices with silicon oxide, P (11) 344*e*. See Schmidt, P. F.
Rand, M. J., and Ashworth, J. L. Deposition of silica films on germanium by the carbon dioxide process, (7) 207*d*.
Rand Corp. Composite material and method for making, P (3) 72*c*.
Randall, G. B. Electric kiln, P (2) 56*b*.
Rangaswami, K. A. See Srinivasan, V.
Rank Organisation, Ltd. Metal/ceramic cathode ray tube, P (8) 245*a*.
Rankin, D. W. Axial angle determinations in Orville's microcline-low albite solid solution series, (6) 183*j*.
Rann, C. H. See Anderson, R. H.
Ransburg Electro-Coating Corp. Electrostatic coating methods and apparatus for conductive coating materials, P (8) 247*c*.
Rao, A. See Rees, L. V. C.
Rao, A., and Rees, L. V. C. Kinetics of ion exchange in mordenite, (3) 82*c*.
Rao, A. D. P. See Rao, G. H. S. V. P.
Rao, C. N. R. See Chandrashekhar, G. V.; Rao, G. V. S.; Sastry, R. L. N.
Rao, G. H. S. V. P., Paul, D. K., and Rao, A. D. P. Limestone deposits of India, (3) 77*j*.
Rao, G. V. S. See Chandrashekhar, G. V.
Rao, G. V. S., Natarajan, M., and Rao, C. N. R. Effect of impurities on the phase transformations and decomposition of $CaCO_3$, (4) 108*b*.
Rao, G. V. U. See Rambabu, H.
Rao, K. R. See Deshpande, V. V.
Rao, K. V. K., Naidu, S. V. N., and Iyengar, L. Thermal expansion of rutile-type GeO_2 by the X-ray method, (9) 288*a*.
Rao, M. G., and Chandra, A. Note on the Tertiary clays in Birbhum District, West Bengal, (8) 250*i*.
Rao, M. R. Liquidus relations in the quaternary subsystem $CiAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, (2) 58*g*. See Sen, P. C.
Rao, N. A. M. See Karanth, P. K.
Rao, N. S. G. Basic requirements of bisque firing and control of bisque losses, (1) 15*a*.
Rao, N. V. See Radhakrishna, B. P.
Rao, P. R. Proposed mean reference line in the study of dispersion of optical glass in the visible and infrared regions of the spectrum, (2) 40*a*.
Rao, P. S. J. Application of measurement and control techniques for the efficient utilization of fuels, (1) 24*b*.
Rao, R. V. G. See Rao, V. V. S.
Rao, V. V. S., Rao, R. V. G., and Biswas, A. B. Thermal decomposition of neodymium oxalate and changes in surface areas of the products, (4) 117*j*.
Rapoport, A. Ya. See Ginzburg, D. B.
Rapoport, E. Model for melting-curve maxima at high pressure, (11) 354*f*.
Rapp, C. F. See Baak, T.
Rapp, H. W., Jr. Costs by the cube, (2) 48*i*.
Rapp, R. A. See Roberson, J. A.
Rapp, R. A., and Frank, D. F. Process of forming passivating internal In_2O_3 bands in silver-indium alloys, P (7) 210*b*.
Rasch, R. Importance of heat storage capacity of refractories for furnace and kiln construction, (8) 237*g*.
Rashkovan, I. L., Kuz'minskaya, L. N., and Kopeikin, V. A. Thermal changes in aluminophosphate binder, (2) 46*j*.
Rasmussen, F. Crushing and drying apparatus, P (1) 25*j*.
Rasmussen, J. K. Cement—production, quality, and development, (2) 36*c*.
Rassonskaya, I. S., and Novikova, O. S. Dehydration of crystal hydrates of double substituted magnesium phosphate, (4) 107*c*.
Rastoin, J. Shielding of nuclear reactors, (7) 203*h*.
Rastrigina, E. F. See Andreeva, N. G.
Rasul, C. G. See Cable, M.
Ratajczyk, F. See Bodnar, Z.
Ratcliffe, S. W., Hall, D., and German, W. L. Glazes for sewer pipe, (10) 301*j*.
Rath, J. Verification of the relation between the modulus of elasticity and the mechanical strength of a ceramic body, (7) 223*a*.
Ratinov, V. B. See Volkov, O. S.
Rau, E., and Kibbel, W. H., Jr. Method of preparing fibers from by-product slag of a phosphorus furnace, P (4) 97*i*. Method of preparing fibers from solidified phosphorus-furnace slag, P (4) 97*j*.
Rau, H. Defect equilibria in cubic high temperature copper sulfide (digenite), (6) 184*i*.
Rau, R. C. Transmission electron-microscope studies of neutron-irradiated beryllium oxide, (8) 258*g*.
Rauber, A., and Schneider, J. Electron spin resonance of a photosensitive $^2S_{1/2}$-state gallium center in ZnS, (11) 352*b*.
Rauch, H. W., Sr. What's new in fibers for strong, light composites, (3) 63*d*.
Rauh, E. G. See Ackermann, R. J.
Rauland Corp. Color television picture tube and mating support members for mounting the color selection mask within the tube, P (3) 72*c*. Impaction process of forming thermionic cathode, P (1) 18*c*. Method of coating cathode-ray tubes, P (7) 209*d*. Method of establishing a light absorbing design on a screen structure of an image reproducer, P (5) 141*f*. Method for making color phosphor screens, P (1) 18*b*. Subtractive type color cathode ray tube having overlapping color phosphor areas, P (1) 19*a*. Thermionic cathode forming process using electrostatic charge attraction, P (1) 19*b*.
Rausch, J. J. See Van Thyne, R. J.
Rauscher, D. H. Semiconductor device, P (2) 52*d*.
Rautiola, N. A. See Fielder, W. S.
Ravetta, L. Production and use of thin-walled hollow brick in lightweight walls and facings in Italy, (10) 301*i*.
Ravikovitch, S. See Banin, A.
Ravizza, M. See Amato, I.
Rawal, N. C., and Aggarwal, K. R. Utilization of fly ash and blast furnace slag in cement mortar and concrete, (6) 165*h*.
Rawlings, R. D. See Pascoe, R. T.
Rawson, H. Inorganic Glass-Forming Systems, B (5) 161*d*.
Rawson, H., and Wlosinski, W. K. Laboratory investigation of glass pressing, (8) 233*c*.
Ray, I., and Murthy, M. V. N. Importance and application of clay mineralogy studies in civil engineering problems, (1) 24*j*.
Ray, S. See Mukherjee, D. K.
Ray Oil Burner Co. System for purging nozzles in dual fuel burners, P (8) 249*i*.
Raybestos-Manhattan, Inc. Heat resistant inorganic bodies, P (9) 270*b*. Manufacture of vulcanized liquid resin bonded abrasive articles, P (8) 227*f*.
Rayeski, T. J. See Carmi, A.; Parsons, G. D.
Raymond G. Osborne Laboratories, Inc. Ceramic bodies and preparation thereof, P (5) 131*a*.
Raymond, J. J. See Comstock, R. L.
Raymond, M. See Hafner, S.
Rayner, J. H., and Brown, G. Structure of pyrophyllite, B (7) 224*c*.
Raytheon Co. Laser crystal with prismatic end surface, P (8) 244*i*.
Raytheon Education Co. Particle measuring and counting system, P (9) 275*g*.
Razi, S., and Anderson, W. W. Electro- and photoluminescence of rare-earth-doped ZnS, (4) 109*e*.
Raziunas, V., Macur, G. J., and Katz, S. Emission spectrum and thermodynamic properties of gallium monoxide, (5) 152*b*.
Razumovskaya, I. V., and Sanditov, D. S. Dependence of the microhardness of glass on the applied load, (10) 297*g*.
Rea, T. W. See Wilms, G. R.
Read, W. B. Flexible pipe coupling, P (10) 300*h*.
Reade, R. F. Some aspects of sensitized fluorescence in $Ca(PO_3)_2$:Sn:Mn glass phosphors, (11) 356*e*.
Readey, D. W., and Handwerk, J. H. Nuclear fuel materials, B (4) 120*j*.
Readey, D. W., and Jech, R. E. Energies and grooving kinetics of [001] tilt boundaries in nickel oxide, (5) 152*d*.
Reamer, H. W. See Krause, H. B.
Reaves, H. L., and Gilmer, T. E., Jr. Quadrupole splitting of the magnetic resonance spectrum of ^9Be in chrysoberyl, (3) 85*e*.
Rebinder, P. A. See Evstatiev, D. G.; Kontorovich, S. I.
Rebouillat, J. P. See Bertaut, E. F.
Reboux, J. See Gayet, B.
Rebull, P. M. See Geuze, E. C. W. A.
Recasens, J. See Goton, R. P.
Recasens, J., and Goton, R. P. Dependence on temperature of the development of various phases in a fused-cast magnesia-chromite brick (Corhart 104), (7) 201*h*.
Rechnitz, G. A., and Lin, Zui-feng. Reaction rate measurements with cation-sensitive glass electrodes—kinetic study of the exchange reaction between Ag(I)-EDTA and Ni(II), (5) 146*g*.
Red Ray Mfg. Co., Inc. Gas burner unit, P (5) 147*e*.
Reddaway, J. L. See Riley, V. R.
Redding, G. B., and Lamb, D. N. Methods of forming nuclear fuel bodies, P (1) 13*j*.
Reddy, J. M. See Abrahams, S. C.
Rediker, R. H. Method of producing interface-alloy epitaxial heterojunctions, P (2) 51*e*.
Redner, S. Nondestructive testing using the photoelastic coating technique, (7) 212*h*.
Redwine, R. H. See Field, M. B.
Ree, T. See Hahn, S. J.
Reeck, G. R. See Lingren, W. E.
Reed, G. C. See Watkins, R. V.
Reed, G. W. See Schneider, P. F.
Reed, L. See McRae, R. C.
Reed, L., and Figone, D. C. Low temperature metallizing paint and method of making, P (2) 38*c*.
Reed, L., McRae, R. C., and Jepson, S. Ceramic-metal seals—manufacture, applications, and future, (2) 37*h*.
Reed, L. W. See Gray, F.
Reed, M. G. See Scott, A. D.
Reed, N. L. See Burke, J. J.
Reed, R. A. See Bennett, H.
Reed, R. F., Sr. Incandescent lamp, P (3) 73*a*.
Reed, R. J. Radiation vs. convection firing (I, II), (2) 55*j*.
Reed, T. B., Fahey, R. E., and Honig, J. M. Growth of single Ti_2O_3 crystals from the melt, (1) 29*j*.
Rees, L. V. C. See Rao, A.
Rees, L. V. C., and Rao, A. Self-diffusion of various cations in natural mordenite, (3) 86*d*.
Rees, R. W. Safety glass, P (1) 10*d*.
Rees, W. M., and Shannon, R. F. High temperature fibrous board, P (2) 41*b*.
Reesman, A. L. See Keller, W. D.
Reesman, A. L., and Keller, W. D. Chemical composition of illite, (1) 26*i*.
Reeves, E. G. Clay preparation plant, (5) 147*i*.
Reeves, P. C. See Stamos, C.
Regester, R. F., Gorsuch, P. D., and Girifalco, L. Structure and properties of aluminum oxide whiskers, (11) 339*f*.
Regis, A. J., and Sand, L. B. Lateral gradation of chabazite to herschelite in the San Simon basin (abstract), B (9) 289*b*.
Regourd, M. See Bigare, M.
Reh, H. H. Vitreous china bodies in literature and practice, (5) 137*a*.
Rehman, A. See Qureshi, A. A.
Rehsi, S. S., and Majumdar, A. J. Use of small specimens for measuring autoclave expansion of cements, (8) 229*c*.
Reichard, W. B. Thin film manufacture, (3) 72*g*.
Reid, A. M. See Burton, C. D. S.; Forber, A.
Reid, L. J., Jr. Production and use of hydrocarbon conversion catalysts comprising acid treated crystalline aluminosilicates, P (5) 149*d*.
Reif, R. B. Basic principles of electrostatic coating, (9) 262*h*. Electrostatic coating of ceramics on metal, (2) 37*i*.
Reijnen, P. Formation of ferrites from the metal oxides, B (7) 226*c*.
Reijnhart, R. See Aken, J. E. van.
Reilly, W. S. C. See Adwick, A. G.
Reimeringer, A. M. Improving the quality of ceramic tile, (9) 270*h*.
Reimschussel, H. C. See Dunsmore, J. M.
Reinberg, A. R. Electron spin resonance of boron in single-crystal BeO, (5) 152*a*.
Reiness, C. G., and Marano, C. L. Optical properties of glass—transmission losses of eyepieces used in mine environment, (6) 168*f*.
Reinke, H. See Eckardt, D.
Reinker, G. E. Container for molten fused silica, P (2) 46*j*.
Reinsch, H. H. Progress in enameling of aluminum for building construction, (1) 4*i*.
Reintjes, G. P. Refractory liner anchorage, P (1) 14*h*.
Reinwall, E. W., Jr. Cathode ray tube manufacture, P (8) 235*c*.
Reising, P. J. Method and apparatus for curving glass sheets, etc., on a gas support bed, P (7) 199*a*. See McMaster, H. A.
Reisman, A. See Berkenblit, M.
Reisman, A., and Berkenblit, M. Method of doping epitaxially grown semiconductor material [Ge], P (4) 100*j*.
Reisman, A., Berkenblit, M., and Alyanakyan, S. A. Method for enhancing efficiency of recovery of semiconductor material in perturbable disproportionation systems, P (3) 73*g*.
Reisman, A., Berkenblit, M., Papazian, S. A., and Cheroff, G. Epitaxial deposition of semiconductor materials, P (1) 17*h*.
Reisman, A., and Rohr, R. L. Chemical polishing of a semiconductor substrate, P (1) 17*c*.
Reiss, F. A. Growth problems of sapphire and ruby of optical quality, (9) 272*e*.
Reiss, H. Chemical properties of materials, B (11) 358*i*.
Reithler, J. C. Balance for magnetic measurements, (3) 75*d*.
Remeika, J. P. See Geller, S.; Le Craw, R. C.; Marezio, M.; Wolfe, R.
Rengel, D. M. See Martin, C. C.
Renkey, A. L. Induction furnace [coreless] construction, P (1) 12*j*. Refractory requirements for large induction furnaces in the ferrous foundry, (6) 173*f*. See Troell, P. T.
Repaher, R. W. Fluorescent lamp envelope with transparent protective coatings, P (7) 208*h*. Stabilized red pigment filter coating in a fluorescent lamp, P (5) 143*c*.
Research Corp. Centrifugal chromatography and electrophoresis device, P (11) 347*e*.
Resnick, W. See Hasson, D.
Resnick, W., and Avriel, M. Method of fractionating mixtures of particulate solid materials, P (2) 53*d*.
Reti, A. R. Short time, high temperature oxidation of cobalt, (4) 115*d*.
Retsky, M. M. See Hendron, J. A.
Reumann, O. Deflocculation of kaolins, clays, and ceramic bodies and the preparation of workable casting slips, (10) 305*e*.
Reven, L. E. See Mindick, M.
Revesz, A. G., Zaininger, K. H., and Evans, R. J. Interface states and interface disorder in the Si-SiO_2 system, (8) 254*b*.
Revesz, G. Photosensitive means for measuring a dimension of an object, P (8) 249*c*. See Ett, A. H.
Revolinsky, E. See Spiering, G. A.
Rex, C. H. Optically round mechanically ovate reflector with radially stepped sections, P (11) 336*e*.
Rex, C. H., and Brom, M. L. Luminaire with optical refracting members, P (11) 336*c*.
Rex, J. P., Jr. Laminated heat insulating product, P (11) 340*f*.
Rex, R. W. Authigenic kaolinite and mica as evidence for phase equilibria at low temperatures, B (7) 224*c*. Authigenic silicates formed from basaltic glass by more than 60 million years' contact with seawater, Sylvania Guyot, Marshall Irlands, B (9) 289*b*. See Gray, D. H.

Rex, R. W., and Bauer, W. R. New amine reagents for X-ray determination of expandable clays in dry samples, B (7) 225*d*.
Rex, R. W., and Martin, B. D. Clay mineral formation in seawater by submarine weathering of K feldspar, B (8) 259*e*.
Rex Roto Corp. Laminated heat insulating product, P (11) 340*f*.
Rexer, J. See Gebhardt, E.
Rexford, H. E. Method of removing airlines in a cathode ray tube, P (1) 9*g*.
Rey, T. Dependence of infrared absorption of $AlPO_4$ and SiO_2 on disordering and temperature, (8) 252*j*.
Reynolds, C. Ceramic color selection, (3) 88*j*.
Reynolds, C. J. Method for molding glass articles and releasing the articles from the mold, P (4) 95*e*.
Reynolds, D. C. Coherent and noncoherent light emission in II–VI compounds, (4) 106*h*. See Park, Y. S.
Reynolds, R. C., Jr. Interstratified clay systems—calculation of the total one-dimensional diffraction function, (7) 218*f*.
Reynolds, W. N. See Goggin, P. R.
Reyrolle & Co., Ltd. High voltage electrical bushing insulators and their manufacture, P (5) 137*e*.
Rezende, S. M., and Morgenthaler, F. R. Frequency conversion of spin waves in pulsed magnetic fields, (4) 110*d*.
Rheinische Kalksteinwerke G.m.b.H. Moisture content measurement [apparatus] having neutron reflecting material to provide optimum counting range, P (2) 55*f*.
Rhety, H. See Rocher, A. L.
Rhodes, E., Smith, W. E., and Ubbelohde, A. R. Relaxation effects in molten nitrates, (7) 221*d*.
Rhodin, T. N. See Palmberg, P. W.
Rhone-Poulenc S. A. Manufacture of laminated safety glass, P (6) 171*a*.
Ribera, J. M. C. See Coronas Ribera, J. M.
Ribes, V. Dressing apparatus for diamond wheels, P (11) 331*f*.
Rice, H. H., and Bennett, R. B. High-temperature alumina-to-niobium article, P (9) 273*c*.
Rice, H. H., and Garey, M. J. Sintering of magnesium fluoride, (1) 25*g*.
Rice, S. B., Jr. Manufacture of ceramic circuit package, P (4) 100*b*.
Rich, C. I. Concentration of dioctahedral mica and vermiculite using a fluoride solution, B (8) 259*j*. See Cook, M. G.
Rich, J., and Arthur, G. Coated boron containing material dispersed in a metal matrix, P (3) 68*j*.
Rich, T. A. Apparatus for determining aerosol particle size comprising a combined diffuser-denuder, P (2) 55*c*.
Richards, P. L. See Allen, S. J., Jr.
Richards, R. A. C. Fourth Spanish Fair, (10) 327*j*.
Richards, R. G. See O'Brien, R. J.
Richards, R. S. Fluid film lubrication for extrusion of metal, P (1) 8*j*.
Richards, S. R. See Bockris, J. O'M.
Richards, T. Z. Variables affecting diamond wheels in carbide grinding (I), (8) 227*f*; (II), (9) 261*h*.
Richards, W. G. See Verhaegen, G.
Richards, W. G., Verhaegen, G., and Moser, C. M. Low-lying energy levels of magnesium oxide, (10) 322*e*.
Richardson, E. W., and McNeese, L. E. Process for making porous sodium fluoride pellets, P (6) 183*c*.
Richardson, F. D. See Baker, E. H.
Richardson, H. M. Deterioration of refractory linings in the lower stack of the blast furnace, B (9) 291*c*.
Richardson, H. P. See Guereca, R. A.; Miller, J. E.
Richardson, K. W., Strain, F., and Wilson, W. L. Process for preparing metal oxides, P (8) 251*d*.
Richardson, L. S., and Fishwick, J. H. Removal of iron from spodumene concentrates by chlorination, (11) 349*c*.
Richardson, M. C. See Bradley, D. J.
Richardson, R. E. Glass bending stress equalization method, P (5) 129*h*. Method of and apparatus for equalizing the cooling of a glass sheet supported on a bending mold, P (6) 171*b*. Press bending mold having modified recesses for the glass sheet engaging means, P (9) 265*j*.
Richardson-Merrell, Inc. Apparatus for removing tipped-over bottles from a conveyor, P (5) 129*d*.
Richland Shale Products Co. Extrusion die for drain tile cluster, P (8) 236*e*.
Richman, I., and Chang, N. C. Two-photon stepwise absorption in Er^{3+} doped salts, (1) 17*g*.
Richter, H. J. See Langer, D. W.
Rickaby, A. See Benson, H.
Ricker, J. M., Bergeron, C. G., and Eagan, R. J. Enthalpy of fusion of $PbO{\cdot}2B_2O_3$, (8) 253*f*.
Ricker, P. W. Deburring tumbling media, P (7) 193*i*.
Riddel, J. W. See Subramanya, B. S.
Riddiford, A. C. See Elliott, G. E. P.
Riddle, G. C. Method of making a sandwich resistor, P (10) 310*b*.
Riddle, J. E. Safety—a production-quality control-cost problem, (2) 60*e*.
Ride, C. New application of propane in the ceramic industry—firing of salt-glazed Alsatian stoneware, (3) 70*h*. Technology of the use of propane in the glass industry, (11) 335*i*.
Rideout, V. L., and Crowell, C. R. Pressure sensitivity of gold-potassium tantalate Schottky barrier diodes, (5) 157*f*.
Ridley, D. F. Forming a semiconductor device by diffusing, P (11) 343*f*.
Riebling, E. F. Nonideal mixing in binary GeO_2-SiO_2 glasses, (8) 233*j*. Structural relations between the liquid and glass states for binary and ternary oxide systems—a density study, (1) 7*c*. Structural similarities between a glass and its melt, (4) 93*d*. Structure of aluminogermanate melts with Na_2O/Al_2O_3 ratio greater than unity, (5) 128*b*. Structure of molten oxides (I) viscosity of GeO_2 and binary germanates containing Li_2O, Na_2O, K_2O, and Rb_2O, (5) 128*d*. Structure of molten oxides in the system $0.25Na_2O$–$(0.75-x)GeO_2$–$xSiO_2$, (5) 128*f*. Structure of sodium aluminogermanate melts with Na_2O/Al_2O_3 ratio equal to unity, (5) 128*k*. Structure of sodium aluminosilicate melts containing at least 50% (mole) SiO_2 at 1500°C, (4) 93*f*.
Riebling, E. F., Blaszyk, P. E., and Smith, D. W. Structure of glasses and melts in the Na_2O-GeO_2-B_2O_3 system, (1) 7*e*.
Riebling, E. F., and Gabelnick, S. D. Electrical conductance of alkali germanate melts at 1300°C, (3) 80*a*.
Rieck, G. D. See Driessens, F. C. M.
Riecker, R. E., and Rooney, T. P. Deformation and polymorphism of enstatite under shear stress, (4) 107*b*.
Riedel, H. J. See Knacke, O.
Riedl, H. R. See Davis, J. L.
Riedl, H. R., and Schoolar, R. B. Photosensitivity in monocrystalline PbS films, (10) 307*i*.
Riek, R. F. See Buckley, F. T.
Riess, J. G., and Van Wazer, J. R. Descriptive chemistry of phosphorus trioxide, (5) 150*h*.
Rigby, F. See Steele, B. R.
Rigby, G. R. Strength of basic brick at 20° and 1400°C with special reference to direct bonded brick, B (9) 291*b*.
Rigby, L. J. See Jones, M. W.
Rigby, W. H., Jr. See Smucker, C. A.
Rigin, V. I., and Batsanov, S. S. Tetrachlorosulfide and selenide of thallium, (9) 287*h*.
Riley, R. E., and Sheinberg, H. Method of preventing segregation during casting of composites, P (5) 135*b*.
Riley, R. J. See McDermott, P. S.
Riley, V. R., and Reddaway, J. L. Tensile strength and failure mechanics of fiber composites, (8) 257*g*.
Rimkus, W. See Jacobsen, A.
Rimmer, W. S. See Evans, P. E.
Rimmer, W. S., Elms, W. A., and Huffadine, J. M. Preparation and properties of high-purity alumina bodies, B (4) 122*d*.
Rimsaite, J. Biotites intermediate between dioctahedral and trioctahedral micas, B (9) 289*i*.
Rindone, G. E. See Graham, P. W. L.; Marin, G.; Taylor, T. D.
Rinehart, D. W. Method of strengthening a glass article by ion exchange, P (3) 66*e*.
Ring, H. F. Composite superconducting structures, P (8) 244*g*. See Forshey, W. O., Jr.
Ringlien, J. A. See Heckman, R. W.
Rinker, F. G. See Cone, C.
Rinkevica, M. See Levine, A. K.; Palilla, F. C.
Riot, A. H. Gas burner with proportional mixer, P (6) 182*c*.
Rioux, J., and Rodot, M. Goniometric supports for supporting crystal during crystal analysis and subsequent cutting, P (8) 249*b*.
Ripple, C. D., and Day, P. R. Suction response due to homogeneous shear of dilute montmorillonite-water pastes, B (8) 259*h*.
Riseman, J. H., Ross, J. W., and Eisenman, G. Glass electrodes, P (3) 65*g*.
Rishel, P. A., Infield, J. M., and Kirchner, H. P. Leaching and machining of polycrystalline alumina, (9) 272*d*.
Ristic, M. M. See Delic, D.
Ritchie, T. Influence of efflorescence o.. decay and expansion of mortar, (11) 337*a*.
Ritter, G. F., Jr. Method and apparatus for bending horizontally conveyed glass sheets between opposed shaping molds, P (4) 94*f*. See Carson, F. J.
Ritter Pfaudler Corp. Method for making joined glass lined pipes, P (9) 265*f*. Preparation and use of silver [aluminosilicate] zeolites of improved exchange capacity, P (8) 251*b*. Semicrystalline glass and method of applying it to metallic bases, P (5) 126*d*. Semicrystallized ground coats and enameled articles manufactured therefrom, P (11) 333*a*.
Rittler, H. L. See Domicone, J. J.
Ritz, V. H. Vacancy-production efficiencies in KBr at low temperatures, (8) 258*b*.
Rival Lamps, Ltd. Capless lamps, P (5) 129*d*.
Rively, C. M., and Livera, P. A. Method of bonding a boron nitride body to a refractory metal, P (1) 13*b*.
Rivin, D. See Hardy, J. F.
Robare, E. P. Perineal bath, P (7) 206*i*.
Robb, R. G. Color and its application in glazes and/or ceramic bodies, (9) 270*j*.
Robbi, A. D. See Gordon, I.
Robbins, M. See Arlett, R. H.
Robbins, W. B. Deposition chamber for manufacture of refractory coated filaments, P (5) 134*h*.
Roberson, C. E. See Hem, J. D.
Roberson, H. E. See Jonas, E. C.
Roberson, J. A., and Rapp, R. A. Observation of markers during the oxidation of columbium, (6) 187*j*.
Robert, N. F. Precision flame control, (8) 249*h*.
Robert Bosch G.m.b.H. Electrolytic capacitor comprising film-forming metal sheet carrying a dielectric oxide film and a metal dioxide electrolyte layer, P (7) 208*e*. Method of producing semiconductor assemblies, P (10) 310*g*. Semiconductors, P (1) 19*c*. Spark plug with the insulator tip coated with spinels of aluminum and cobalt oxides, P (5) 143*b*. Spark plug with a sealing glass mixture with graphite and iron, nickel, or cobalt, P (4) 101*d*.
Roberts, E. W., and Roberts, J. P. Gas permeation through dense mullite ceramics at high temperature, (3) 67*f*.
Roberts, G. L., Jr. See Whately, W. R.
Roberts, G. L., Jr., Bragg, H. A., and Whately, W. R. Digestion of titanium-bearing ores, P (11) 349*g*.
Roberts, G. L., Jr., Hoelscher, H. E., and Cauwenberg, W. J. Process for TiO_2 pigment production in controlled calcination of basic titanium sulfate, P (4) 105*g*.
Roberts, G. L., Jr., and Whately, W. R. Purification of titanium dioxide pigment with organic sequestering agents, P (10) 318*e*.
Roberts, J. E., and Wilson, J. B. Vertical lime kiln, P (3) 63*a*.
Roberts, J. P. See Fryer, G. M.; Roberts, E. W.
Roberts, J. W., Old, A. F., Gibson, R. F., Foster, W. F., Purvis, T. L., and Wycoff, J. C. Uniform lightweight aggregate, P (1) 10*k*.
Roberts, M. J. Alumina in high strength porcelain bodies, (11) 341*d*.
Roberts, M. W., and Ross, J. R. H. Kinetics of the dissociation of hydrogen sulfide by iron films, (3) 82*e*.
Roberts, M. W., and Wells, B. R. Chemisorption and incorporation of oxygen by nickel films, (3) 79*f*.
Roberts, R. F., Jr., Lister, R. H., and James, W. A. Process for removing impurities from the precipitation system of the Bayer process, P (6) 183*c*.
Roberts, R. W. Evaporative application of metal coatings to diamond, P (7) 193*j*.
Roberts & Schaeffer Co., Div. of Thompson-Starrett Co., Inc. Method and apparatus for removing moisture from material, P (9) 278*b*.
Robertson, J. A. Active soda ash compaction, P (7) 214*h*.
Robertson, J. A. L. Nuclear reactor fuel, P (3) 69*e*.
Robertson, J. M., and Pointon, A. J. Cation distribution in nickel ferrite, (11) 350*d*.
Robertson, M. M. See Estill, W. B.
Robertson, R. H. S. Fuller's earth from Pompeii, (7) 194*b*.
Robey & Co., Ltd. Crushers for stone, coal, ore, and other solid materials, P (5) 148*b*.
Robin, G. See Bondy, C.
Robinson, A. J. Bonded molecular sieve catalysts and preparation, P (8) 250*e*.
Robinson, A. S. Apparatus for supporting a ribbon of glass on a molten metal bath with glass ribbon heel flow means, P (2) 40*b*. See Loukes, D. G.
Robinson, A. S., and Silverwood, F. W. Method and apparatus for removing dross from the surface of a molten metal glass sheet float bath, P (9) 265*a*.
Robinson, G. C. Design of clay bodies for controlled microstructure (I) concepts and body design, (6) 172*a*; (II) clay-aggregate bodies, (7) 199*h*; (III) reactive aggregates and quantity of mismatch, (9) 266*e*. Method of making ceramic capacitors, P (8) 245*j*.
Robinson, G. C., Kizer, R. H., Jr., and Duncan, J. F. Raw material parameters determining extrudability, (10) 301*j*.
Robinson, G. Y., and White, R. M. Scanning electron microscopy of ferroelectric domains in barium titanate, (1) 16*g*.
Robinson, H. A. See Warshavsky, M.
Robinson, J. S. Efficiency in brickmaking—setting the theme, (5) 130*j*.
Robinson, M., and Devor, D. P. Thermal switching of laser emission of Er^{3+} at 2.69μ and Tm^{3+} at 1.86μ in mixed crystals of CaF_2:ErF_3:TmF_3, (4) 118*d*.
Robinson, P. D. Use of the binocular microscope for orientation of single crystals, (1) 23*a*.
Robinson, P. T. Method of making a semiconductor device by masking and diffusion, P (10) 310*b*.
Robinson, R. A., and Covington, A. K. Thermodynamics of the ternary system water-potassium chloride-calcium chloride at 25°C, (10) 326*g*.
Robinson, W. T. See Bouchard, R. J.
Robinson Clay Product Co. Methods of making seals for pipe joints, P (3) 66*h*.
Robredo, J. Application of differential thermal analysis to glass technology and research, (11) 333*d*. Refractory materials in glass factories—present trends and forecast, (11) 334*i*. See Dusollier, G.; Pereira, E.
Robson, F. G. See Pearne, F. J.
Robson, H. E. Process for producing synthetic faujasite having a high silica to alumina ratio, P (1) 25*j*.
Robson, J. T. Ceramic refractory flame retention nozzle, P (2) 56*b*.
Roca, M. Spectrochemical determination of Al, Fe, and Si in fluorite, (3) 76*f*.
Rocchiccioli, C. Principles of infrared absorption spectrometry and methods of sample preparation, (6) 181*a*.
Rocchiccioli, C., and Townshend, A. Some interferences in the atomic absorption spectrophotometry of calcium, (9) 286*c*.

Rocher, A. L., and Rhety, H. Manufacture of laminated safety glass, P (6) 171*a*.
Rochow, E. G. See Schwartz, S. E.
Rochow, H. Adherence of hard-solderable metal coatings to ceramic surfaces, (1) 3*f*.
Rockland, J. G. R. Rate equation for sintering by surface diffusion, (10) 324*e*.
Rockowitz, M., and McGuire, L. J. Microwave technique for the detection of voids in honeycombed ablative materials, (7) 212*d*.
Rodbell, D. S. Magnetocrystalline anisotropy of single crystal CrO_2, (4) 112*i*.
Rodbell, D. S., Lommel, J. M., and DeVries, R. C. Electrical resistivity of single crystal CrO_2, (10) 320*b*.
Rodger, M. D. Ejection of uranium atoms from sintered UO_2, (10) 320*d*.
Rodgers, H. G. See Hillman, T. F.
Rodot, M. See Rioux, J.
Rodriguez, A. R., and Cronin, J. Process for manufacturing multilayer ceramic capacitors, P (10) 311*g*.
Roedder, E., and Coombs, D. S. Immiscibility in granitic melts, indicated by fluid inclusions in ejected granitic blocks from Ascension Island, (4) 111*c*.
Roeder, E., and Hornstra, J. Grain growth during hot-pressing of tantalum carbide, (5) 153*b*.
Roeder, M., Herrmann, H., and Dietz, W. Process for manufacturing homogeneous bodies of germanium-silicon, P (5) 142*e*.
Roeder, P. L., Glasser, F. P., and Osborn, E. F. System Al_2O_3-Cr_2O_3-SiO_2, (11) 357*b*.
Roehl, P. O. Stony Mountain (Ordovician) and Interlake (Silurian) facies analogs of recent low-energy marine and subaerial carbonates, Bahamas, (4) 116*g*.
Roelofs, H. See Haans, P. F. A.
Roesler, F. L. See Mack, J. E.
Roessler, D. M., and Walker, W. C. Electronic spectrum of crystalline lithium fluoride, (8) 253*e*.
Roger, A., and Fruchart, R. Magnetic and structural study of the solid solution MnP-MnAs, (6) 176*d*.
Rogers, J. L. See Lood, D. E.
Rogers, M. D. X-ray examination of strontium titanate irradiated by fission fragments, (2) 46*c*.
Rogers, R. N. See Birgeneau, R. J.
Roget, M. Modern methods of drying ceramic products, (9) 275*f*.
Rogovoi, M. I. See Galdina, N. M.
Rohm & Haas Co. Treatment of siliceous fibers with aqueous mixtures of various unsaturated polyimidazoline anchoring agents and resulting article, P (7) 199*d*.
Rohr, R. L. See Reisman, A.
Rokhvarger, A. E. Derivation of a system of statistical models in the study of silicate materials, (10) 313*e*.
Rokosz, F. See Lopenski, S. A.
Roland, P. A. See Bron, W. E.
Roldan, R. Spikes in the light output of room-temperature [stripe geometry] GaAs junction lasers, (11) 357*a*.
Rolfe, B. N., and Hadley, R. F. Weathering and transport of sediment in the Cheyenne River basin, eastern Wyoming, B (6) 192*b*.
Rolfe, J. See Ishii, T.
Rolin, M., and Clausier, M. Calcium fluoride, barium fluoride, magnesium fluoride systems (I) binary diagrams; (II) ternary diagrams, (2) 57*j*.
Roll, K. H. See Hausner, H. H.
Rollins, F. R., Jr. Critical ultrasonic reflectivity—a neglected tool for material evaluation, (7) 212*b*.
Rolls-Royce, Ltd. Ceramic objects and method of manufacturing, P (1) 20*e*. Ceramic shell mold, P (2) 46*g*.
Rom, F. E., Lietzke, A. F., and Hyland, R. E. Reactor fuel element for a nuclear rocket motor, P (7) 205*b*.
Roman, D. Graphite heating element for electric resistance furnace, P (11) 348*f*. See Bruin, H. J. de; Whitfield, H. J.
Romankiw, L. T. Activation of glass for electroless metal deposition of uniform thick metal films, P (6) 170*a*.
Romanova, N. S. See Zhechkova, L. A.
Romberger, K. A., Baes, C. F., Jr., and Stone, H. H. Phase equilibrium studies in the UO_3-ZrO_2 system, (5) 156*b*.
Romo, P. See Geller, S.
Ronceray, R. A. M. Mixer-grinder for foundry sand, P (3) 69*e*.
Ronchi, C. See Blank, H.
Roney, N. J. See Schmidt, P. F.
Ronor S. A. Smooth precision dimensional bodies of vitreous material and method and apparatus for producing, P (4) 95*d*, P (5) 130*f*.
Rood, J. L. See Brewster, G. F.
Rooksby, H. P. Scope of X-ray diffraction analysis, B (7) 224*i*.
Rooney, A. W. Advances in oil firing (I), (6) 181*j*; (II), (7) 213*g*.
Rooney, D. M. See Grossman, L. N.
Rooney, T. P. See Riecker, R. E.
Root, T. F. Supermarket sells more brick, (7) 223*e*.
Ropp, R. C., and Quirk, R. F. Process for the fabrication of improved fluorescent lamps, P (2) 52*e*.
Ropska, H. Mineral composition of typical Polish building clays and their properties in unfired condition, (6) 172*c*.
Rosberry, F. W. Measurement of homogeneity of optical materials in the visible and near infrared, (9) 263*h*.
Roscoe, C., and Thomas, J. M. Identification and some physicochemical consequences of nonbasal edge and screw dislocations in graphite, (1) 29*d*.
Rose, N. F. See Horspool, J. M.
Rose, R. G. Method of preparing a fuel element of fissionable oxide and burnable poison, P (4) 97*a*.
Rosen, H. J. Principles of Specification Writing, B (5) 161*d*.
Rosenbauer, C. H. Method for selective etching of alkali glass, P (6) 171*a*.
Rosenberg, D. J. See Krakauer, S.
Rosenbery, J. W. See Kremith, R. D.
Rosendahl, A., and Mueller, J. Dependence of the hot and cold strength of chemically bonded basic bricks on their temperature-time history, (7) 201*e*.
Rosenecker, C. N. See Bluman, D. E.
Rosenecker, C. N., Coates, N. H., and Lucas, H. G. Power required to circulate gas-solids suspensions, (2) 53*d*.
Rosenqvist, I. T. Norwegian research into the properties of quick clay—a review, (7) 220*d*. Studies in position and mobility of the H atoms in hydrous micas, B (5) 160*d*.
Rosenstein, R. D., and Schor, R. Superlattice Madelung energy of idealized ordered cubic perovskites, (6) 180*d*.
Rosenstock, H. B. and Blanken, G. Interatomic forces in various solids, (10) 322*f*.
Rosenstock, K. H., and Kowalski, B. Method of preparing satin white, P (10) 318*e*.
Rosenthal-Porzellan Akt.-Ges. Porcelaneous dense ceramic material with a high resistance to changes in temperature and a high mechanical strength and method of producing it, P (7) 200*i*.
Rosinski, E. J. See Plank, C. J.; Wadlinger, R. L.
Rosner, D. E., and Allendorf, H. D. Comparative studies of the attack of pyrolytic and isotropic graphite by atomic and molecular oxygen at high temperatures, (7) 200*f*.
Rosolowski, J. H. Discussion of "Theory of grain-boundary degeneration in materials which contain an inert gas," (10) 326*g*.
Ross, A. R. See Fuls, E. N.
Ross, B. See Iles, P. A.
Ross, C. W. Method and apparatus for the optimization of kiln cooler control, P (8) 229*a*. See Bay, T.
Ross, J. F. Process for producing finely divided calcium fluoride having controlled particle size, P (3) 74*b*.
Ross, J. R. H. See Roberts, M. W.
Ross, J. W. See Eisenman, G.; Moore, E. W.; Riseman, J. H.
Ross, J. W., and Hebert, N. C. Glass electrode composition, P (6) 170*c*.
Ross, M. Fourier transform analysis (I) X-ray diffraction effects by finite montmorillonite and mica crystals (abstract), B (9) 289*d*. Precision unit-cell parameter determination of layer silicates by use of electron and X-ray diffraction powder techniques (extended abstract), B (7) 224*c*. Torbernite minerals as model compounds for the hydrous layer silicates, B (7) 224*b*.
Ross, R. D. (editor). Industrial Waste Disposal, B (8) 260*b*.
Ross, R. F., Jr. See Napier, J.
Ross, R. W. See Cross, F. L., Jr.
Rossi, C. E. Shaft kiln discharge mechanism, P (2) 56*d*. See Campbell, W. W.; Leatham, E.
Rossi, G. See Omenetto, N.
Rossi, R. C. Prediction of the elastic moduli of composites, (9) 285*g*. See Janowski, K. R.
Rossi, R. C., and Fulrath, R. M. Densification of refractory compounds, P (1) 12*a*.
Rossin, A. D. Reporting neutron exposure for radiation damage, B (10) 329*f*.
Rossini, A., Pereira, E., and Mennucci, L. Study of silica brick by differential thermal analysis, (11) 339*c*.
Rossington, D. R. See Harris, J. R.
Rossington, D. R., and Runk, E. J. Adsorption of admixtures on portland cement hydration products, (2) 38*c*.
Rostoker, D. See Bush, E. A.
Roth, H. Effects of manufacturing processes on the frost resistance of brick, (10) 301*g*. See Rupprecht, J.
Roth, H. H. Electroluminescent cells, P (4) 99*i*.
Roth, R. J. See Farrow, L. C.
Roth, R. S. See Waring, J. L.
Roth, W. L. See DeVries, R. C.
Rothermel, D. L. Effect of stress on durability of ion-exchanged surfaces, (1) 5*h*.
Rothrock, B. D. See Kirby, R. K.
Rotsey, W. B. See Hickman, B. S.; Hilditch, R. J.; Turner, D. N.; Veevers, K.
Rottmann, H. R. Radiation sensitive apparatus for inspecting the bottom wall of hollow transparent containers, P (3) 66*b*.
Rouannet, M. See Urbain, G.
Rouault, A. See Fruchart, R.
Rouberol, J. M., Tong, M., Conty, C., and Deschamps, P. Combined microprobe-electron microscope, (10) 313*b*.
Rough, R. R. Bubbler apparatus for a glass melting furnace, P (11) 335*d*. Method of eliminating a foam blanket on the surface of molten glass, P (2) 41*b*.
Rouse, R. L. See Freck, D. V.
Roustand, C. See Delord, J. F.
Route, R. See Kino, G. S.
Routschka, G. See Konopicky, K.
Routschka, G., and Konopicky, K. Composition of mullite in chamotte and chamotte brick as a function of temperature, (8) 236*h*. Infrared spectrographic investigation of the drying sensitivity of clays, (7) 218*b*.
Rouzeyre, M. See Delord, J. F.
Rowden, E. Changing pattern of fuel usage in the heavy clay and refractory industries, (3) 76*i*.
Rowe, G. E. Blow molding apparatus for a glassware forming machine, P (11) 335*g*. Take-out tong mechanism for a glassware forming machine, P (4) 95*e*.
Rowe, G. L., and Wilson, J. R. Apparatus for forming large carbonaceous bodies, P (6) 174*i*.
Rowe, J. Efficiency in brickmaking—service to the customer, (5) 130*j*.
Rowe, J. J., Morey, G. W., and Silber, C. C. Ternary system K_2SO_4-$MgSO_4$-$CaSO_4$, (5) 159*f*.
Rowell, M. H. Borate glass ion exchangers for fused salts, (1) 5*b*. Liquid-liquid extraction in the sodium oxide-boron oxide-sodium chloride system, (4) 112*j*.
Roy, A. K. Pseudomorphous replacement of apophyllite by quartz, (10) 324*c*.
Roy, A. K., Ghosh, S. K., and Banerjee, B. K. Studies on some Indian limestones (IIB) estimation of dolomite by X-ray methods, (3) 62*h*.
Roy, H. Electrochemical and viscometric study of some clay minerals, (5) 151*g*. Structure of some clay minerals of ceramic importance, (5) 158*e*. See Ghosh, S. K.; Sharma, S. K.
Roy, N. N. Mineralogy of the potassium-barium feldspar series (I) determination of the optical properties of natural members; (II) studies on hydrothermally synthesized members, (9) 284*d*.
Roy, R. See Balascio, J. F.; Barry, T. L.; Bates, C. H.; Datta, R. K.; Denny, P. J.; McCarthy, G. J.; Majumdar, A. J.; Sarjeant, P. T.
Roy, R., Balgord, W., and Taylor, A. M. Structural change in analcites and Na-P zeolites caused by cation exchange at room temperature and dehydration under controlled pH_2O (abstract), B (9) 289*j*.
Roy, S. K., and Coble, R. L. Solubilities of magnesia, titania, and magnesium titanate in aluminum oxide, (2) 59*g*.
Roy, S. S. Origin of laterite—a review, (1) 25*d*.
Royer, J. J. Rotated *Y*-cut rectangular piezoelectric quartz crystal plates, P (7) 210*e*.
Royer, L. T. See Healy, R. M.
Rozanova, O. N. See Trunov, V. K.
Rozenman, T. See Hasson, D.
Rozhkov, A. N. See Kordonskaya, R. K.
Rubens, H. E. Glass-metal seal, P (3) 65*i*.
Rubenstein, D. Method of making composite decorative structural elements, P (8) 236*j*.
Rubenstein, M. Segregation of silicon in gallium phosphide, (4) 115*b*. Solubilities of GaAs in metallic solvents, (7) 208*b*. See Sagar, A.
Rubenstein, M., and Myers, E. Epitaxial synthesis of GaAs using a flow system, (7) 207*a*.
Rubeska, I. Determination of trace elements in sulfide minerals by atomic absorption spectrophotometry with absorption tubes, (5) 145*b*.
Rubin, J. J. See Geusic, J. E.; Van Uitert, L. G.
Rubinchik, Ya. S., Pavlyuchenko, M. M., Tsybul'ko, I. A., and Leytsina, V. G. Reactions of lanthanum and yttrium oxides with iron oxide, (9) 286*e*.
Rubins, R. S. See Baer, R.
Rubinstein, C. B., and Van Uitert, L. G. Faraday rotator utilizing terbium aluminum garnet and dysprosium aluminum garnet, P (5) 141*g*.
Rubisch, O. High-temperature electric furnace with molybdenum silicide heater elements, P (6) 182*d*. High-temperature resistant structural body, P (9) 270*d*.
Rublevskii, I. P. See Galdina, N. M.
Rubtsov, M. V. See Korshunov, B. G.
Ruch, J. G., and Kino, G. S. Measurement of the velocity-field characteristic of gallium arsenide, (4) 112*j*.
Rudd, D. W. See Ballman, A. A.; Fraser, D. B.
Ruddlesden, S. N. Analysis with the electron microprobe at the British Ceramic Research Association, (10) 313*c*. Applications of the electron probe microanalyzer to ceramics (I) potentialities of the instrument, (6) 179*j*. Electron probe microanalysis of ceramics, B (7) 224*h*.
Ruddlesden, S. N., and Airey, A. C. Applications of the electron probe microanalyzer to ceramics (II) analysis of defects in ware; (III) general research problems, (6) 179*j*.
Rudenko, V. S. See Boganov, A. G.
Ruderer, C. G. See Lynch, J. F.
Rudi, V. P., and Al'bota, N. K. Effect of surfactants on the properties of clays, (2) 58*b*.
Rudman, R. Reported synthesis of gallium dodecaboride, (6) 188*i*.
Rudolph, W. F. See Scherer, J. D.
Rudy, E., Bruki, C. E., and Windisch, S. Constitution of ternary Ta-Mo-C alloys, (6) 184*b*.
Rudy, E., Windisch, S., Stosick, A. J., and Hoffman, J. R. Constitution of binary molybdenum-carbon alloys, (6) 184*f*.
Rudzitis, E., Feder, H. M., and Hubbard, W. N. Fluorine bomb calorimetry (XI) enthalpy of formation of yttrium trifluoride, (11) 352*j*.
Rueb, F. Filter presses for the ceramic industry, (10) 312*f*.
Ruedl, E., Delavignette, P., and Amelinckx, S. Electron microscopic study of the defect structure due to ordering in the alloy Ni_4Mo, (4) 109*a*.

Ruegg, R. Heat transfer from waste gas of a cement kiln to pulverulent raw material, P (8) 229*a*.

Ruegge, F. (editor). Structural Clay Products Yearbook 1968, B (5) 161*e*.

Ruehle, H. Security measures for bonding and shearing stress when using prestressed ribbed floors of ceramic elements, (10) 295*g*.

Ruehle, H., and Bergner, K. Development of ceramic composite structures, (10) 327*i*.

Ruehrwein, R. A. Preparation of III-V compounds, P (4) 100*j*.

Ruffner, L. J. Module capacitor, P (10) 311*b*.

Rugiadi, R. Sand in red stoneware clays, (8) 242*g*.

Ruh, R. See Garrett, H. J.

Ruh, R., Garrett, H. J., Domagala, R. F., and Tallan, N. M. System zirconia-hafnia, (2) 60*b*.

Ruh, R., Wysong, E. D., and Tallan, N. M. Differential thermal analysis sample holder for use to 1700°C, (4) 102*e*.

Rulfs, C. L., Pacer, R. A., and Hirsch, R. F. Technetium chemistry—oxidation states and species, (5) 159*d*.

Rummel, T. Apparatus for the pyrolytic production of rod-shaped semiconductor bodies, P (4) 99*c*.

Rummler, D. R., and Palmour, H., III. Vacuum hot-pressing of magnesium aluminate spinel, (7) 222*j*.

Rumyantsev, P. F. See Toropov, N. A.

Runciman, W. A. See Pooley, D.

Rundle, D. F. Hermetically sealed connector, P (6) 177*d*.

Rundqvist, S. See Aronsson, B.

Rundqvist, S., and Pramatus, S. Crystal structure refinements of Ni_3B, *o*-Ni_4B_3, and *m*-Ni_4B_3, (7) 216*a*.

Runk, E. J. See Rossington, D. R.

Runyan, W. R. See Bean, K. E.

Ruotsala, A. P. See Tobias, T. J.

Rupert, G. N. See Benz, R.

Rupprecht, G. See Geick, R.; Luck, C. F., Jr.

Rupprecht, H., Woodall, J. M., and Pettit, G. D. Efficient visible electroluminescence at 300°K from $Ga_{1-x}Al_xAs$ *pn* junctions grown by liquid-phase epitaxy, (6) 176*e*.

Rupprecht, J., and Roth, H. Pulling nozzle for oriented pulling of semiconductor crystals from a melt, P (10) 311*h*.

Rushton, T. N., and Khalafalla, S. E. Kinetics of the initial reduction stages of magnetite in hydrogen, (9) 283*b*.

Rusk, G. R., and Hagquist, F. M. Abrasive roll, P (5) 123*h*.

Russel, P. G., McClure, D. S., and Stout, J. W. Zeeman splitting of narrow lines in crystalline MnF_2, FeF_2, and CoF_2—evidence for spin-wave excitations, (10) 327*g*.

Russell, A. D. Differential thermal analysis of materials with very volatile components, (4) 102*d*.

Russell, B. Reply to discussion of "Theory of grain-boundary degeneration in materials which contain an inert gas," (10) 326*g*.

Russell, B., and Vela, P. Theory of grain-boundary degeneration in materials which contain an inert gas, (10) 326*g*.

Russell, H., and Smith, J. Survey of thin-film vacuum deposition techniques, (2) 50*k*.

Russell, J. D. Apparatus for adjusting the temperature coefficient of wire strain gages, P (6) 181*c*. See Farmer, V. C.

Russell, J. D., and White, J. L. Infrared study of the thermal decomposition of ammonium rectorite, B (8) 259*c*.

Russell, J. H., and Kelley, H. J. Statistical evaluation of some factors in the preparation of boron by fused-salt electrolysis, (3) 77*f*.

Russell, L. E., Harrison, J. D. L., and Brett, N. H. Method of producing dense sintered bodies of UO_2 or UO_2-PuO_2 mixtures, P (7) 205*c*.

Russell, R., Jr. See Brubaker, B. D.

Russell, R. D. See Brocklehurst, B.

Russell, R. G. Method for production of glass fibers, P (1) 9*g*.

Russell, R. G., Willis, J. H., and Shafer, W. C. Method for production of mineral fibers, P (6) 171*a*.

Rutgaizer, Yu. S. See Bushkovich, S. N.

Rutherford, J. See Miles, G. D.

Rutland, D. F., Palmer, R. C., and Blase, E. F. Thermoluminescent dosimetry system, P (7) 213*c*.

Rutman, D. S., Shchetnikova, I. L., et al. Volatilization of components from zirconia ceramics, (9) 288*d*.

Rutter, F. Microscopical assessment of carbon refractory, (3) 67*a*.

Rutter, J. W., and Clausen, E. M. Method of making electrical heating elements, P (3) 73*b*.

Rutz, R. F. Fast responding semiconductor device using light as the transporting medium, P (5) 141*g*.

Ryabchikov, I. D. See Perchuk, L. L.

Ryabov, V. A. See Botvinkin, O. K.

Ryabov, V. A., and Fedoseev, D. V. Formation of coatings on the pristine surface of a glass rod, (2) 39*h*. Statistical examination of the effect of surface and bulk defects on the strength of glass, (8) 234*d*.

Ryall, W. R., and Threadgold, I. M. Evidence for $[(Si_2O_5)_3]_\infty$ type chains in inesite as shown by X-ray and infrared absorption studies, (2) 58*g*.

Ryan, J. D. Laminated glass structure, P (2) 41*c*.

Ryan, J. R. See Walther, F. H., Jr.

Ryan, L. D. See Mallory, J. D.

Ryan, W. Deflocculation of a blue ball clay (I) sodium hydroxide and sodium carbonate, (7) 216*d*. Properties of Ceramic Raw Materials, B (11) 358*j*.

Ryder, E. J. See Kunzler, J. E.

Ryder, R. M. See Kahng, D.

Rydnik, V. I., and Borovskii, I. B. Methods for local quantitative X-ray fluorescence analysis, (10) 314*i*.

Rysanek, V. Z. Thin dielectric layer technology using vacuum deposition with piezoelectric crystal rate control, (5) 140*f*.

Rzhanitsyn, Yu. P. See Kuznetsova, G. N.

Saad, O. C., and Otenbaker, J. T. Drain tile structure, P (5) 131*b*.

Saalfeld, H. Crystal chemistry of dicalcium silicate, (2) 57*f*.

Saalfeld, H., and Junge, H. Sintering diagram MgO-SiO_2-Al_2O_3 and its dielectric properties, (3) 86*b*.

Sabatier, G. Interferometric method for measuring the principal indices of small crystals, (3) 75*c*.

Sabine, T. M. Interpretation of some X-ray diffraction effects in irradiated BeO, (2) 44*h*. See Klein, A. G.; Pryor, A. W.

Sabisky, E. S. See Anderson, C. H.

Sachdev, P. L., and Prasad, P. Numerical procedure for shock problem using artificial heat conduction, (10) 324*b*.

Sack, W. Method of producing articles containing predominantly cordierite, anorthite, spinel, and/or forsterite, P (5) 135*c*. Substances for producing crystalline heat-resistant coatings and fused layers, P (8) 236*d*.

Sadanaga, R. Recent trend of X-ray crystallographic investigation of inorganic materials, (8) 248*e*.

Sadikova, N. S. See Fedorov, N. F.

Sadler, A. G. Formation of barium iron oxide, $BaFe_{12}O_{19}$, (9) 272*b*. See McDonald, R. D.; Quon, H. H.

Saenger, G. See Plieth, K.

Saermark, K., Tarrow, V., Heidam, N. Z., and Lebech, J. Attenuation of 3 Ghz sound waves in ZnO, (11) 350*j*.

S.A.E.S. Getters S.p.A. Gettering device including a getter metal and a gas releasing material, P (9) 273*b*. Gettering system for electron tubes, P (3) 72*k*. Process for producing within electron tubes, in particular television picture tubes, a thin metallic film capable of sorbing their residual gases, P (9) 274*g*.

Safdar, M. See Naweed-ul-Islam; Qureshi, A. A.

Safdar, M., and Hasan, R. Preparation of strontium salts from celestite, (9) 278*g*.

Safdar, M., and Khan, R. A. Preparation of some ceramic stains (I, II), (9) 271*a*.

Safdar, M., Khan, R. A., and Akbar, M. Frosting of electric lamp bulbs, (9) 263*j*.

Safdar, M., and Naweed-ul-Islam. Preparation and characteristics of an acid-proofing mortar, (9) 268*h*.

Safdar, M., Naz, M. A., and Cheema, A. A. Study on the replacement of imported ball clay by Mianwali plastic clay in ceramic bodies, (9) 271*b*.

Safford, G. J. See Naumann, A. W.

Safonov, N. A. See Yurganov, N. N.

Sagar, A., and Rubenstein, M. Piezoresistance in *n*-type CdTe, (9) 285*d*.

Sagawa, T. K emission band of graphite, (4) 112*h*.

Sager, J. R. See Baker, T. C.

Sah, Chih-Tang. See Bittmann, C. A.

Saha, P. See Ganguli, D.

Saha, S. C. See Majumdar, A. K.

Sahm, P. R., and Pruss, T. V. Pressure-sintered GaSb-GaAs alloys—densification and thermoelectric properties, (4) 99*g*.

Sais, A., and Edelman, R. E. Process of casting a reactive metal, P (8) 241*g*.

Sais, F. J. See Quetsch, J. G., Jr.

Sais, F. J., and McIntyre, G. M. Package for semiconductor devices and method of making, P (3) 73*j*.

Sainsbury, I. E. J. Tendency of refractories to produce bubble in soda-lime-silica glasses, (5) 129*d*.

St. Clair, J. C. Infrared method of rocket motor inspection, (9) 276*a*.

St. John, D. A., and Bastable, P. W. Glazing of ignimbrite building stone, (1) 15*a*.

St. Joseph Lead Co. Zinc oxide compositions and method of making them, P (1) 26*d*.

St. Pierre, G. R. See Adelsberg, L. M.

St. Pierre, P. D. S. High density uranía fuel elements, P (1) 12*h*.

Saito, E. Photoconductive layer and method of making, P (10) 311*e*.

Saito, K. See Tsuzuku, T.

Saito, M. See Sawamura, K.

Saito, S. See Eisenberg, A.; Fukunaga, O.; Yamada, T.

Saito, S., Nakahigashi, K., and Shimomura, Y. X-ray diffraction study of CoO, (7) 223*c*.

Saito, S., Somiya, S., and Kato, K. Effect of binder, grain size, sintering temperature, and atmosphere on moduli of rupture of silicon nitride bodies, (2) 43*i*. Effects of additives on the sintering of Si_3N_4, (2) 44*d*.

Saito, S., and Takei, T. Studies on the formation of ferrites by the hydrothermal method (I) nickel ferrite, (9) 286*i*.

Saito, T. Anomalous thermal expansion of α-ferric oxide, (6) 183*h*. See Minagawa, S.

Sajo, I., and Sipos, B. Rapid analysis of cement and clinker by the thermometric method with direct percentage indication, (8) 228*i*. Rapid thermochemical analysis of chamotte, kaolin, and clay, (11) 347*b*.

Sakai, S. See Aoki, S.; Ota, E.

Sakaino, T. Coloration of glass, (8) 230*i*. See Yamane, M.

Sakamoto, Y. See Nakajima, N.

Sakka, S. See Kokubo, T.

Saksaganskii, A. M. See Kotov, K. I.

Sakudo, T. See Unoki, H.

Sakudo, T., Unoki, H., and Fujii, Y. Electric field effect on ESR of Gd^{3+} in $SrTiO_3$, (10) 320*e*.

Sakurai, T. See Kawakita, K.

Sakurai, T., Kamada, O., Shiahido, K., and Inagaki, K. Construction of a large solar furnace, (4) 104*a*.

Sala Maskingfabriks AB. Device for recovering feebly magnetic material in wet separators, P (1) 25*b*.

Salam, M. A. See Wells, C. F.

Salam, S. A., and Soliman, M. R. Thermodynamics of phase transformations of quartz between 848° and 1953°K, (7) 222*h*.

Salge, H. Measurement of thermal conductivity at high temperatures, (8) 238*e*. See Krueger, R.

Salhana, J. A. See Khabata, S. J.

Salibekov, S. E. See Levinskii, Yu. V.

Salin, A. A., and Dolmatov, Yu. D. Removal of lead from TiO_2 by isomorphous crystallization of strontium and lead sulfates from solutions, (7) 203*a*.

Salman, T. See Yen, W. T.

Salomon, A. N. See Mohler, D.

Salsburg, Z. W. See Frisch, H. L.

Salt, D. L. See Denson, C. D.

Salt, P. J. Formation of glass-to-metal seals by high-frequency induction heating, (2) 37*i*.

Salter, W. J. M. Examination of quantitative electron-probe microanalysis accuracy, (9) 276*f*.

Saltzman, M. N., and Schor, R. Madelung energy of perovskite structures (II) the tetragonal case, (6) 187*c*.

Salvadori, A., Lovy, P., and Beigelman, M. Fuel cell including packed catalytic substance, P (4) 100*a*.

Salyards, D. G. See Conway, J. B.

Salzano, F. J., Aronson, S., and Ingraham, A. Comment on compound formation in the lithium-carbon system, (9) 280*c*.

Salzmann, E. See Arzt, R. M.

Sama, L. See Lublin, P.

Samara, G. A. Effects of hydrostatic pressure to 20 kbars on the dielectric constant of rubidium chloride, (11) 352*f*. See Corll, J. A.

Sambell, R. A. J. See Miles, G. D.

SAMES. See Societe Anonyme de Machines Electrostatiques.

Sameshima, Y., and Nishiyama, M. Bonding mechanism in glass-to-metal seals, (8) 242*j*.

Samoilov, V. I. See Ponomarenko, B. F.

Sampson, O. N. Sinya meerschaum mine, northern Tanzania, (4) 104*g*.

Samsonov, G. V. See Gordienko, S. P.; Mal'tseva, L. F.; Neronov, V. A.

Samsonov, G. V., and Epik, A. P. Coatings of high temperature materials, B (7) 225*f*.

Samsonov, G. V., and Podchernyaeva, I. A. Emission properties of oxides of alkali earth metals, (6) 185*a*.

Samsonov, G. V., Verkhoglyadova, T. S., and Dvorina, L. A. Hardness of the silicides of some rare-earth metals, (9) 282*h*.

Samuseva, R. G., and Piyushchev, V. E. Systems CsF-KF and CsF-RbF, (4) 117*e*.

Sanbongi, K. See Asada, M.

Sanchez, M. G. See Flack, H. P.

Sand, L. B. See Regis, A. J.

Sandbrook, D. E. Kiln, P (11) 348*g*.

Sandejas, J. S. See Hudson, J. B.

Sander, H. H. Transistor having constant gain over a broad temperature range, P (6) 178*i*.

Sanderfur, N. L., Macy, P. R., and Bokros, J. C. Microradiographic technique for determining densities of pyrolytic-carbon coatings, (1) 22*c*.

Sanders, H. H., with Tomimoto, K. World of Japanese Ceramics, B (10) 329*k*.

Sanders, J. V. See Allpress, J. G.

Sanders, L. D. See Hanks, C. F., Jr.

Sanderson, R. T. Bond energies, (4) 106*g*.

Sandhagen, M. Vacuum-tight connection between a ceramic tube and a disk-shaped metal part of an electrical discharge vessel, P (8) 230*a*.

Sanditov, D. S. See Razumovskaya, I. V.

Sandmeyer, K. H. See Brown, R. W.

Sandstrom, D. J. Consolidating metal powders magnetically, B (3) 89*i*.

Sandvikens Jernverks Aktiebolag. Hot top lining, P (10) 304*e*.

San Fernando Laboratories. Gaseous deposition method of making a thermocouple probe, P (1) 23*i*.

Sanford, E. A. See Little, J. R.

Sanford, E. A., Hall, D. H., and Chu, G. P. K. Semicrystalline glass and method of applying it to metallic bases, P (5) 126*d*.

Sanford, R. A. See Johnson, M. F. L.

Sanford, R. A., Johnson, M. F. L., and Williams, N. J. Process for preparing silica-alumina, P (9) 270*d*.

Sanker, P. E. See Town, J. W.

Sano, K. See Kojima, Y.

Sano, S. See Ishii, E.; Kato, S.

Sano, S., Kato, S., Ishii, E., and Iga, T. Reduced pressure sintering of MgO as high frequency insulator (II), (11) 355*f*.
Santangini, J. See Briody, T. F.
Santilli, V. J. Photoconductive target having arsenic-selenium layers of different densities on cryolite layer, P (10) 311*f*.
Santoro, R. P. See Segal, D. J.
Santoro, R. P., and Newnham, R. E. Antiferromagnetism in $LiFePO_4$, (9) 279*h*.
Santos, H. de S. See Souza Santos, H. de.
Santos, P. de S. See Souza Santos, P. de.
Santos Simoes, J. M. dos. See Berendsen, A.
Santos-Ynigo, L. Distribution of iron, alumina, and silica in the Pujada laterite of Mati, Davao Province, Mindanao Island, Philippines, (2) 56*h*.
Sao, T. P. Machine for the manufacture of asbestos-cement sheets, etc., P (5) 144*b*.
Sapoff, M. See Froemel, J. G.
Sapoff, M., and Froemel, J. G. Method of making a thermistor, P (5) 142*b*. Method of manufacturing thin film thermistors, P (10) 310*e*.
Sara, R. V. Method for induction sintering refractory carbide articles, P (2) 47*h*.
Sarjeant, P. T., and Roy, R. New approach to the prediction of glass formation, (6) 168*b*.
Sarukhanishvili, A. V. See Zorina, M. L.
Sarver, J. F. Preparation and luminescent properties of Ti-activated zirconia, (7) 207*h*. Preparation of thorium pyrophosphate, P (2) 52*b*.
Sas, I. See Constantinescu, F.
Sasaki, H. Method for growing single crystals of vanadium dioxide, P (7) 214*g*. Production of lead titanate and lead zirconate for ceramic bodies, P (2) 52*i*. See Kitahiro, I.; Matsuo, Y.; Takeda, T.
Sasaki, K., and Takei, T. Pores in sintered ferrite, (9) 272*e*.
Sasaki, S. See Shibazaki, K.
Sass, A. Simulation of the heat-transfer phenomena in a rotary kiln, (1) 24*g*.
Sastry, R. L. N., Mehrotra, P. N., and Rao, C. N. R. Phase transformation, oxidation, and hydration of praseodymium sesquioxide, (3) 85*a*.
Satalkin, A. V., Solntseva, V. A., and Popova, O. S. Cements of increased expansivity, (2) 36*f*.
Satava, V. Mechanism of transformation of gypsum to hemihydrate in water, (2) 36*e*. See Hulinsky, V.; Komrska, J.
Satava, V., and Komrska, J. Effect of the granulometry of plaster on the strength of its hardened suspensions, (10) 294*c*.
Satchwell Controls, Ltd. Measurement of heat, P (2) 55*f*.
Sathe, R. V. Calcium garnet series from pyroxene scapolite rocks of Goldongiri, Gujarat States, (1) 24*i*.
Satiya, R. C. See Ramachandran, V. S.
Sato, A. Semiconductor variable capacitance element, P (8) 246*i*.
Sato, H. Effect of impurity-vacancy complex on the degree of compensation in compound semiconductors, (10) 320*d*.
Sato, K. Studies on the residual lines of mica, (5) 158*e*. See Kotera, Y.
Sato, K., and Nakamura, Y. Method and apparatus for breaking a semiconductor wafer into elementary pieces, P (11) 344*c*.
Sato, K., and Shibata, M. Reststrahlen reflection characteristics of amorphous silica, (7) 221*f*.
Sato, M. See Tanaka, H.
Sato, M., Taylor, J. B., and Calvert, L. D. Simple low-contamination preparative technique for compounds having high heats of formation, such as rare earth-group Vb compounds, (2) 46*a*.
Sato, R. Stacking faults in hexagonal boron nitride, (10) 325*c*.
Sato, R., Poi, H., and Uchikochi, H. Reduction of U_3O_8 to UO_2, (5) 157*h*.
Sato, T., Nakatsuka, K., Toita, K., and Shimoiizaka, J. Study on artificial magnetite by the wet method, (9) 287*c*.
Sato, Y. See Fujimoto, M.; Wakao, Y.
Satoh, M., and Slichter, C. P. Electron-nuclear double resonance of Ag nuclei in AgCl + Fe^{3+}, (9) 282*a*.
Satow, T. Electrical resistivity, magnetic susceptibility, and thermal expansion of thorium monocarbide, (10) 320*j*. Thermodynamic properties and nonstoichiometry of thorium dicarbide, (10) 326*c*. Thermodynamic properties and nonstoichiometry of thorium monocarbide, (10) 326*c*.
Satterfield, C. N. See Cadle, P. J.
Satterfield, W. R. Temporary high temperature protective coating agents for metals, P (11) 333*a*.
Sauer, H. A. Positive temperature coefficient [La-Ba-Sr] titanate thermistor, P (7) 210*a*.
Saulnier, T. A. Method of making color kinescopes of the line-screen sensing variety, P (5) 141*j*.
Saum, N. M. See Keller, W. D.
Sauman, Z. Study of the hydration of $3CaO \cdot SiO_2$ and β-$2CaO \cdot SiO_2$ with quartz or slag at 20°C, (1) 32*a*.
Saums, H. L., and Pendleton, W. W. Electrical apparatus, insulating composition therefor, and method of making, P (1) 4*g*. Electromagnetic structures for high-temperature service, P (5) 141*f*. Pyrolyzable enamel coated wire comprising manganese and cobalt chelates, P (5) 126*d*.
Saunders, J. H. Laminated safety glass, P (9) 265*g*.
Saunders, R. J. See Newell, F. W.
Sauvage, M., and Authier, A. Study of cross bands and twinning dislocations in calcite, (7) 222*f*.
Savadatti, M. I. See Brocklehurst, B.
Savage, D. W. See Williams, G. H.
Savage, J. See Cable, M.
Savage, L. H. W. Direct firing of vitreous enamel, (4) 92*h*.
Savage, R. O., Jr. See Au Coin, T. R.
Savel'ev, V. G. See Budnikov, P. P.
Saverchenko, D. A. See Anikeeva, T. V.
Savin, E. S., Butt, Yu. M., and Kolbasov, V. M. Evaluation of binder quality in hydrothermal hardening, (6) 164*f*. Study of reactivity of calcium carbonate in the system CaO-SiO_2-$CaCO_3$-H_2O under hydrothermal conditions, (6) 165*f*.
Savitskii, A. N. Freezing and melting of water in glass capillaries, (11) 353*c*.
Savitskii, K. V. See Grigor'eva, V. V.
Sawada, A., and Abe, R. New decoration techniques for revealing antiparallel 180° domains in $BaTiO_3$, (8) 255*h*.
Sawamoto, H. See Nakayama, N.
Sawamoto, K., and Toyoda, H. Surface states on CdS single crystals, (5) 158*j*.
Sawamura, K., and Saito, M. Some properties of an anodized aluminum oxide film of high dielectric strength, (3) 86*f*.
Sawaoka, A., Miyahara, S., Akimoto, S., and Fujisawa, H. Magnetic properties of manganese germanate and titanate, (7) 219*g*.
Sawhney, B. L. Interstratification in vermiculite, B (9) 289*f*.
Saxena, S. K. Intracrystalline chemical variation in certain calcic pyroxenes and biotites, (10) 322*i*.
Sayce, L. A. Grazing incidence diffraction gratings, P (9) 277*e*.
Sayles, C. P. See Muller, L. D.
Scaglioni, O. Use of electric "boosting" in glass melting, (1) 8*g*.
Scala, E. See Schuster, D. M.
Scaramelli, P. See Fieschi, R.
Scarlett, R. M. Semiconductor device, P (3) 74*f*.
Schachner, H. See Tannenberger, H.
Schacht, C. A. Brick press having density control, P (5) 134*f*.
Schaefer, D. L. Image orthicon cathode-ray tube with copper screen target having a chromium supported magnesium oxide film, P (4) 100*d*.
Schaefer, F. W. First reproduction of a *dialretum* glass by the Roman grinding technique, (7) 194*a*.
Schaefer, H. Method of forming a semiconductor by masking and diffusion, P (6) 178*b*.
Schaefer, K. Automatic setting system for brick, (3) 66*f*.
Schaefer, W. H., Jr. Discussion of "Design considerations for vacuum vessel refractories," (6) 172*h*.
Schaetzer, L. Kervite tile, (7) 206*i*.
Schafer, H. Process for the conversion of calcium acid phosphate dihydrate to calcium acid phosphate, P (11) 349*d*.
Schaffer, P. S. See Kingery, W. D.
Schagen, P., and Manley, B. W. Photocathode comprising channeled matrix with conductive inserts in channels tipped with photoconductive material, P (9) 274*b*.
Schaible, P. M. See Glang, R.
Schall, P. Effect of atomic displacements on color center production in MgO, (8) 253*d*.
Schalliol, W. L. See Watkins, R. V.
Schanz, J. J., Jr. Historical statistics of Pennsylvania's mineral industries 1961–1965, (11) 348*j*.
Scharbach, H., and Horsch, R. Composite devitrified-vitrified enamel coating, P (4) 93*a*.
Schatz, E. A. Spectral reflectance of sintered oxides, (6) 189*a*.
Schatz, M. See Hofmann, U.
Schatz, R. See Eggert, H.
Schaudinn, K. Ceramic radio frequency transmitter capacitors, (10) 306*h*.
Schaufele, R. F. See Weber, M. J.
Schaufele, R. F., and Weber, M. J. First- and second-order Raman scattering of $SrTiO_3$, (11) 352*j*.
Schechter, M., Kooi, J., Billiau, R., Charlier, R. A., and Dumont, G. C. Preparation of UO_2 by fused salt electrolysis using UO_2 or UF_4 as starting material, (5) 133*h*.
Scheel, H. J. See Bayer, G.
Scheer, J. J. See Laar, J. van.
Scheidt, R. C., and Freiling, E. C. Ion-exchange processes between immiscible molten phases, (11) 353*h*.
Schembra, F. W. See Hofmann, U.
Schenck, H., Majdic, A., Graf, D., Raebel, G., and Bonner, H. Investigations on carbon monoxide breakdown and its catalytic poisoning, (9) 267*e*.
Schenk, M. See Hauser, O.
Schenke, M., Broers, G. H. J., and Ketelaar, J. A. A. Solubility of oxygen in molten carbonates, (11) 356*e*.
Scherer, J. D., and Rudolph, W. F. Hermetic metal-to-glass seal and application thereof, P (6) 170*f*.
Scheurlen, D. See Hofmann, U.
Schiavo, J. See Varon, J.
Schick, G. E. Welded conductors to carbon and graphite cloth, P (3) 74*f*.
Schiele, E. See Gotthardt, R.
Schieltz, N. C., and Soliman, M. R. Thermodynamics of the various high temperature transformations of kaolinite, B (7) 225*d*.
Schikarski, L., and Teiwes, H. J. Method for melting uranium oxide and plutonium oxide, P (1) 13*f*.
Schiller, K. Ionic concentration in the suspending liquid during the hydration of a slurry, (10) 295*g*.
Schilling, W. A. See Siekanowicz, W. W.
Schillmann, E. See Eggert, H.
Schimmel, G. See Ohnemueller, W.
Schimmer, R. Method of forming a semiconductor by diffusion through the use of a cobalt salt, P (9) 273*f*.
Schindling, J. Multicell centrifugal dust separator, P (2) 53*f*.
Schladitz, H. Self-lubricating structure, P (1) 14*d*.
Schlain, D. See Andrews, R. L.; Cramer, S. D.
Schlegel, W. Handle and the cup, (4) 98*c*.
Schleicher, H. W. See Quataert, D.
Schlesinger, M., and Cohen, A. J. Postulated structures causing the optical color-center bands in amethyst quartz, (7) 220*d*.
Schlotter, C. See Kopineck, H. J.
Schlotzer, G. See Kim, S. C.
Schmeiser, K., Lehmann, K., and Kowalski, W. Process and apparatus for controlling the temperature prevailing in a sintering grate of the type used for drying and calcining shapes, P (1) 24*d*.
Schmersal, L. J. Apparatus for measuring the thickness of dielectric members, P (10) 316*h*. See Mathias, B. B.
Schmid, A., and Hofer, H. Process for firing and cooling particulate solids, P (2) 56*b*.
Schmid, H. Method of producing monocrystalline boracites, P (8) 251*i*.
Schmid, O. Use of basic brick in the glass industry, (8) 240*h*.
Schmidt, A., Mueller, W., and Weinrotter, F. Purification of fluosilicic acid solution by distillation with phosphoric acid solution, P (9) 279*f*.
Schmidt, E. New knowledge concerning brickwork efflorescence, (10) 301*g*. See Nitzsche, S.
Schmidt, E. D. D. See Vedam, K.
Schmidt, E. R. See Taeuber, K. A. G.
Schmidt, J. T. New method for measuring fluorescent brightness and color, (7) 212*e*.
Schmidt, K. High pressure saturation sodium vapor lamp containing mercury, P (8) 235*b*.
Schmidt, P. F., and Rand, M. J. Mutual transformation of thermal and anodic SiO_2 films, (11) 354*h*.
Schmidt, P. F., and Roney, N. J. Anodic oxidation, P (7) 208*f*.
Schmidt, P. W. See Andrews, D. E.
Schmitt, J. Crystallogenesis and physical properties of trichites [whiskers]—preparation of corundum trichites, (6) 172*f*. Present status and possible applications of whiskers (I) comparative survey of whiskers and mineral fibers; (II) whisker-reinforced composite materials, (11) 338*d*.
Schmitten, W. in der. See Hoppe, W.
Schmitz, G. K., and Metcalfe, A. G. Testing of fibers, (11) 335*j*.
Schmitz, H. Multichamber mill, P (10) 312*e*.
Schneeman, J. G. Precision and magnification radiography of miniature electronic components, (7) 212*j*.
Schneider, A. Electric furnaces for the ceramic industry, (7) 213*h*.
Schneider, H. Method of making a casting mold, P (2) 47*h*.
Schneider, I. M_A centers in additively colored KCl, (11) 354*g*.
Schneider, J. See Rauber, A.
Schneider, M. See Auda, D.
Schneider, P. F., Dolton, T. A., and Reed, G. W. Mechanical erosion of charring ablators in ground-test and reentry environments, (9) 267*i*.
Schneider, P. J. Bottle recognition apparatus, P (4) 94*c*.
Schneider, R. R. Rotary kiln, P (1) 24*c*.
Schneider, S. J. See McDaniel, C. L.
Schneider, S. J., and McDaniel, C. L. Effect of environment on the melting point of Al_2O_3, (4) 108*j*. Melting point of Al_2O_3 in vacuum, (1) 30*f*.
Schneider & Co. Apparatus for producing ceramic bodies, P (8) 247*h*.
Schnitzer, M. See Kodama, H.
Schnitzler, P. Elastic surface waves in a layered system of cadmium sulfide on germanium, (11) 352*f*.
Schnoering, H. See Giesekus, H.
Schnuerch, R., Koester, A., and Heise, R. Process for silica and silicates, P (1) 26*a*.
Schober, M. See Selbin, J.
Schoen, K. See Engel, W.
Schoen, R., and White, D. E. Hydrothermal clay minerals in granodiorite of the Main Terrace, Steamboat Springs, Nevada (extended abstract), B (7) 224*e*.
Schoenbrunn, G. Determination of principal stresses in glass articles, particularly cased glass, (6) 166*i*.
Schoendoerffer, M. J. See Halm, L.
Schoenlaub, R. A. Calorimeter apparatus and method of directly determining enthalpy, P (6) 181*d*.
Schofer, R., and Fenner, E. Barrier-free contacting of ceramic bodies, P (2) 50*f*.
Schofield, K. See Sugden, T. M.
Scholes, A. B. Lubricious coating for glass, P (9) 265*i*. See Lyon, K. C.
Scholten, J. J. F., and Konvalinka, J. A. Pretreatment of molecular sieves, P (10) 318*a*.

Scholze, H. Glass—Constitution, Structure, and Properties, B (4) 120*b*. See Galanulis, E.

Scholze, H., and Gliemeroth, G. Investigations of glasses and melts in the system Na_2SiO_3-H_2O, (6) 167*d*.

Schoner, K. Flow and problems of flow during the drying and firing of brick and comparable products, (6) 172*b*.

Schoolar, R. B. See Davis, J. L.; Riedl, H. R.

Schoonover, R. M. See Bowman, H. A.

Schopper, E. See Haase, G.

Schor, H. Method for forming electric lamps and similar devices, P (11) 336*f*.

Schor, R. See Rosenstein, R. D.; Saltzman, M. N.

Schorsch, J. J. See Kraft, W. W.

Schot, E. H. See Park, W. C.

Schott, C. W. Method for making high strength spherical glass bodies, P (9) 265*e*.

Schott, S. C. Method for making large precision die castings from cavityless casting molds, P (10) 304*h*.

Schott Metal Products Co. Method for making large precision die castings from cavityless casting molds, P (10) 304*h*.

Schottmiller, J. C. See Boyd, J. R.

Schoubye, S. See Berendsen, A.

Schraudenbach, P. Paving block, P (1) 10*h*.

Schreffler, R. Z. Apparatus for producing glass flakes, P (1) 8*b*.

Schreiber, C. L., and Kolb, K. E. Laminated structures and method of preparing, P (8) 235*d*.

Schreiber, E. Comment on the elastic modulus-porosity relation, (10) 319*j*. See Soga, N.

Schreiber, K. Supply the proper standard for color matching, (10) 312*j*.

Schreiner, H., and Edlmayr, F. Sintered composition material, P (8) 246*a*.

Schreiner, H., and Wendler, F. Thermoelectric mosaic interconnected by semiconductor leg protrusions and metal coating, P (10) 311*f*.

Schreurs, J. W. H. Study of some trapped hole centers in X-irradiated alkali silicate glasses, (5) 128*j*.

Schrewelius, N. G., and Magnusson, C. B. O. Electric heating resistors, P (1) 12*c*.

Schroder, M. L. See Ehrlinger, H. P., III.

Schroeder, J., and Seweryniak, M. High-temperature flame reactors, (6) 182*a*.

Schroeder, J. B. See Nester, J. F.

Schroeder, J. E. See Murdock, J. P.

Schroeder, U. See Jeschar, R.

Schroeder, W. W. See Krauss, L.

Schroeter, M. See Schwiete, H. E.

Schroth, P. See Baker, B. H.

Schuele, D. E. See Wong, C.

Schueller, K. H. High strength porcelain bodies based on quartz or cristobalite (I–III), (3) 70*b*. Study of a 40-year-old steatite insulator, (10) 306*d*.

Schueller, K. H., and Staerk, K. Relation between grain size and strength of porcelain, (10) 306*d*.

Schuetz, H. Dust extraction from boiler flue gases, (5) 143*i*.

Schuetze, H. J., and Hennings, K. Electrical circuit device, P (4) 99*h*.

Schuller, M. J. Method of making a reliable low-ohmic nonrectifying connection to a semiconductor substrate, P (10) 310*a*.

Schuller, W. H. W. Method of up-drawing glass and apparatus, P (7) 199*e*.

Schultink, L., and Klopman, G. Tunnel furnace, P (3) 77*b*.

Schultz, A. H. See Stubican, V. S.

Schultz, B. J., and Crook, E. H. Ultrafine ion exchange resins, (10) 317*g*.

Schultz, L. G. Lithium and potassium absorption, differential thermal, and infrared properties of some montmorillonites (abstract), B (7) 224*i*. Nonmontmorillonitic composition of some bentonite beds, B (5) 160*e*.

Schulz, E. O. Method for making foam glass, P (2) 41*e*. Production of foam glass, P (4) 95*c*.

Schulze, E., and Becker, G. Method and apparatus for detecting light-deflecting flaws in hollow glass articles, P (9) 265*j*.

Schulze, E., Becker, G., and Sehrt, F. Method and apparatus for the continuous examination of a train of glass articles, P (8) 235*g*.

Schulze, H. C. Method of curing articles manufactured from cement and asbestos, P (3) 69*a*.

Schulze, H. C., and Taeler, D. H. Monolithic pipe joint, (3) 74*h*.

Schumacher, D. P., and Wallace, W. E. Magnetic characteristics of some lanthanide nitrides, (1) 16*g*.

Schumacher, G. See Beisswenger, H.

Schumacher, H. See Muehe, F. J.

Schumann, P. A., Jr., and Dupnock, A. Evaluation of point material for the three-point probe, (11) 346*j*.

Schuster, D. M., and Scala, E. Single and multifiber interactions in discontinuously reinforced composites, (6) 181*e*.

Schwabe, E. A. Continuous process of preparing fired ferrite cores, P (7) 208*j*.

Schwaerzler, G. Ceramic artists and their work—Ida Erdoes-Meisinger, (3) 61*i*. Ceramist Goerge Hohlt, (10) 293*i*. Hoechst porcelain, (10) 293*h*.

Schwartz, A. B., and Wilson, R. C., Jr. Process for producing desiccants, P (4) 105*e*.

Schwartz, A. S. See Bokros, J. C.; Tully, G. R., Jr.

Schwartz, B., and Wilcox, D. L. Laminated ceramics, (3) 71*f*.

Schwartz, H. S. See Hough, R. L.

Schwartz, H. S., and Spain, R. G. Structural plastic composites incorporating new high modulus fibers, (9) 269*j*.

Schwartz, J. W. Color triad tube having heat-absorptive material on aluminum screen backing for cooling shadow mask, P (10) 309*i*.

Schwartz, J. W., and Prazak, C. J. Glass cements, P (6) 170*a*.

Schwartz, S. E., and Rochow, E. G. Alternosorption (II) inorganic oxides at high temperatures, (6) 183*h*.

Schwartzwalder, K. See Subramanya, B. S.

Schwarzenbach, D. Refinement of the structure of the low-quartz modification of $AlPO_4$, (8) 256*c*.

Schweikert, W. F. See Uher, J. F.

Schweinzger, T. C. Centrifugal fan selection, (3) 74*h*.

Schweizer, J. See Laar, B. van.

Schwerdtfeger, K., and Muan, A. Equilibria in the system Fe-Mn-O involving "(Fe,Mn)O" and $(Fe,Mn)_3O_4$ solid solutions, (6) 185*d*.

Schwiete, H. E. Solid state reactions of silicate systems, (7) 221*b*. See Ludwig, U.; Metzger, C.

Schwiete, H. E., Berens, L. W., and Kroenert, W. Effect of the degree of burning on the structure of quicklime, (10) 294*j*.

Schwiete, H. E., Boehme, H. J., and Dohm, K. D. Thermal conductivity measurements on basic brick, (7) 204*a*.

Schwiete, H. E., and Dohm, K. D. Hot-wire method of measuring the thermal conductivity of refractory materials and insulating brick, (6) 173*g*.

Schwiete, H. E., Hennicke, H. W., Mields, A., and Draeger, W. Inner friction of porcelain, B (9) 291*e*.

Schwiete, H. E., Hennicke, H. W., and Schroeter, M. Torsional behavior of magnesite brick under cyclic loading, (8) 240*c*.

SCM Corp. Substantially anhydrous ceramic glazes in propellant-type cans, P (8) 242*f*. Temporary high temperature protective coating agents for metals, P (11) 333*a*.

Scott, A. D., and Reed, M. G. Expansion of potassium-depleted muscovite, B (7) 224*i*.

Scott, A. D., and Smith, S. J. Susceptibility of interlayer potassium in micas to exchange with sodium, B (8) 259*i*. Visible changes in macromica particles that occur with potassium depletion, B (9) 289*h*.

Scott, J. A. N. See Flockhart, B. D.

Scott, J. L. See Olsen, A. R.

Scott, K. T., and Harrison, K. T. Preparation of single phase single crystals of uranium dioxide in the O/U range 2 to 2.25, (5) 133*g*.

Scott, R. C. Economic balance in the ceramic industry, (4) 119*g*. Labor's share of ceramics, (4) 119*f*. Incentive systems in manufacturing, (2) 60*c*.

Scott, R. K. Method of making a shell mold, P (11) 340*a*.

Scott, W. C., and Sturge, M. D. Dynamic Jahn-Teller effect in the $^4T_2$ excited term of Al_2O_3: V^{3+}, (11) 351*j*.

Scott, W. D. Fabrication of bicrystals of aluminum oxide, (5) 152*i*.

Scotto, V. See Westeren, H. W.

Scribner, B. F. See Margoshes, M.

Scroger, M. G. See Chang, L. L. Y.

Scruggs, D. M., Van Vlack, L. H., and Spurgeon, W. M. Reaction between nitrogen and spinel in chromium, (10) 296*e*.

Seabridge, F. T., and Chivers, M. A. Furniture for glost kilns, (3) 70*b*.

Searcy, A. W. See Munir, Z. A.

Searle, T. M. See Glass, A. M.

Sears, G. W., and DeVries, R. C. Morphological development of aluminum oxide crystals grown by vapor deposition, (5) 155*c*.

Sears, J. H. See Klink, J. P.

Sears, M. B., and Ferris, L. M. Hydrolysis of uranium, thorium, and aluminum carbides in D_2O, (4) 111*a*. Reactions of calcium and barium carbides with 0 to 16*M* nitric acid, (5) 157*c*. Reactions of uranium and thorium carbides with aqueous solutions of hydrochloric acid and sulfuric acid, (5) 157*f*.

Sears, M. B., Ferris, L. M., and Gray, R. J. High-temperature immiscibility of uranium mono- and dicarbides, (11) 353*a*.

Sease, J. D. See Meservey, A. B.

Sebring, L. W. See Mathias, B. B.

Secon Metals Corp. Process of producing high temperature resistant insulated wire, such wire, and coils made therefrom, P (2) 38*e*.

Sedgwick, T. O., and Agule, B. J. Bourdon gage determination of equilibrium in the ZnSe(*s*)-I_2(*g*) system, (10) 319*d*.

SEDIVER. See Societe Europeenne d'Isolateurs en Verre.

Sedlakova, L. See Jakes, D.

Sedova, I. V. See Myshlyaeva, L. V.

Seebach, H. M. von. See Sprung, S.

Seeley, F. G. See Crouse, D. J., Jr.

Seevers, D. O. Pulsed NMR study of the interfacial water of a disperse suspension of boehmite (abstract), B (9) 289*i*.

Sefton, W. G. See Westeren, H. W.

Segal, B. B. See Kriek, H. J. S.

Segal, D. J., Santoro, R. P., and Newnham, R. E. Neutron-diffraction study of $Bi_4Si_3O_{12}$, (6) 187*h*.

Segalova, E. E. See Brutskus, T. K.; Tulovskaya, Z. D.

Segnit, E. R. Microstructure of ceramic materials (V1) aluminosilicate refractories, (8) 238*j*. (2); (3), corrosion under service conditions, (8) 239*a*.

Segraves, E. C. See Brumage, W. H.

Segre, G. J. See Ferrari, S.

Seguela, P. Process for the manufacture of sodium carbonate [by use of CO_2], P (5) 149*a*.

Sehrt, F. See Schulze, E.

Seibert, E. See Carpenter, W. W.

Seibert, F., and Seibert, P. Apparatus for producing extruded bodies from a plastic mass, P (10) 304*a*.

Seibert, P. See Seibert, F.

Seidel, H. See Juza, R.

Seider, R. See Kalnin, I. L.

Seidler, R. See Forster, H.

Seifahrt, H. Coated electrode for arc welding of cast iron, P (6) 166*c*.

Seifert, K. E. Electron microscopy of etched plagioclase feldspar, (1) 28*j*.

Seip, H. M. See Almenningen, A.

Seitchik, J. A., and Stein, B. F. Nonohmic current transport phenomena in high-resistivity GaAs, (3) 83*j*.

Seiter, H. See Hornig, M.

Seitz-Werke G.m.b.H. Arrangement for automatically displacing plates and frames, especially in filter presses, P (3) 75*c*. Filter press, P (4) 102*b*.

Seki, T., Tauchi, S., and Takagi, T. Method of making semiconductor devices by double masking, P (1) 18*d*.

Seki, Y. Slip casting and firing of glass powder, (1) 7*f*.

Sekiya, T. See Naka, S.

Selas Corp. of America. Air preheating burner with furnace preheating passage cleaner means, P (4) 104*f*. Metal heating, P (1) 4*h*. Method of forming glass beads in a molten metal bath, P (3) 65*e*. Process for making a filter, P (3) 69*g*. Tube heater, P (4) 104*e*.

Selbin, J., and Schober, M. Chemistry of uranium(IV) (I) uranium-oxygen bonds in some products derived from the hydrolysis of UCl_4, (4) 106*f*.

Seleborg, M. Refinement of the crystal structure of disodium dimolybdate, (5) 157*i*.

Selig, H. Complexes of xenon oxide tetrafluoride, (5) 150*f*.

Selig, H., Claassen, H. H., Chernick, C. L., Malm, J. G., and Houston, J. L. Xenon tetroxide—preparation and some properties, (4) 119*b*.

Selig, T. R. See Whitman, P. C.

Seligmann, P. Nuclear magnetic resonance studies of the water in hardened cement paste, (6) 165*f*.

Sell, P. J., and Neumann, A. W. Surface tension of solids, (3) 76*a*.

Selte, K. See Furuseth, S.

Seltzer, M. S. Activation energies for high-temperature steady-state creep in lead sulfide, (6) 183*g*.

Semba, K. See Ueda, M.

Semba, K., and Hatta, T. Nature and deterioration of clay lining of torpedo (hot metal) car, (8) 239*c*. Relation between creep behavior and texture of fireclay brick, (9) 268*j*.

Sementsova, D. V. See Bukhalova, G. A.

Semlyen, J. A., and Flory, P. J. Analysis of the unperturbed dimensions of the linear polyphosphate chain, (3) 79*b*.

Semmelman, J. O. See Halpern, B. D.

Sen, P. Pottery and design, (1) 2*b*.

Sen, P. C., and Rao, M. R. Development of chrome-magnesite refractories utilizing Indian chrome ores, (5) 131*g*.

Sen, S. K. See Aggarwal, P. S.

Senbokuya, T. Surface contacting thermocouple, P (11) 348*a*.

Senftle, F. E. See Lewis, R. R.

Sennett, P. See Olivier, J. P.

Sensi, J. E., and Galey, W. F. Method of forming a glass ribbon on a gas support bed, P (3) 65*f*.

Sentementes, T. J., and Mager, E. L. Conductive media for electroluminescent devices, and electroluminescent device, P (7) 208*i*.

Seraphim, D. P. See Brennemann, A. E.

Serb-Serbina, N. N. See Evstatiev, D. G.

Serbin, V. P. See Budnikov, P. P.

Serebrennikov, V. V. See Kumok, V. N.

Sereda, P. J. See Soroka, I.

Sereda, P. J., and Swenson, E. G. Apparatus for preparing portland cement paste of high water-cement ratio, (11) 331*h*.

Seredi, B. Development of mechanization and technology of gravel and crushed stone plants, (3) 77*g*.

Serensen, S. V. Development of fatigue tests for materials, (10) 314*c*.

Sergeant, G. A. See Evans, W. H.

Sergin, B. I. See Musikhin, V. I.

Sergiu, P. See Gheorghiu, G.

Serratosa, J. M. Infrared analysis of the orientation of pyridine molecules in clay complexes, B (8) 260*a*.

Serruya, C., Picard, L., and Chilingarian, G. V. Possible role of electrical currents and potentials during diagenesis ("electrodiagenesis"), (1) 31*h*.

Service (Engineers), Ltd. Towing [smoothing] articles of ceramic ware, P (5) 137*c*.

Service National dit Gaz de France. Fuel cell including packed catalytic substance, P (4) 100*a*.

Setaka, N. See Kawashima, C.

Setchfield, J. B., and Allen, S. G. Method of making semiconductor devices, P (7) 209*h*.

Sethi, M. L. Fluorspar in Rajastan, (9) 278*g*.

Setkina, O. N. See Zorina, M. L.

Sett, S. N. Improvements in brick and building blocks, P (5) 131*a*.

Sevast'yanov, E. F., and Sokolov, A. A. Study of thermophysical and electrical parameters of the transfer of heat and electricity in molten glass (I) unit for complex study of effective coefficient of radiant-molecular heat conductivity and volume resistivity of the molten glass; (II) new high-temperature electrical furnace and ceramic flask for studying the thermophysical and electrical properties of molten glass; (III) complex study of effective coefficient of radiant-molecular heat conductivity and volume resistivity of molten glass; (IV) analytical determination of region of allowable temperature gradients in spherical volume of molten glass during study of the effective coefficient of radiant-molecular heat conductivity by heating with a spherical heat source of constant power; (V) calculation of the temperature field and field velocity of molten glass in a glass melting tank; (VI) spherical probe for studying the thermophysical properties of insulating materials at high temperatures, (10) 299*f*.

Sevin, A., and Daudans, J. Attempt to trace the origin of crystalline inclusions in glass, (1) 5*a*.

Seward, T. P., III, and Uhlmann, D. R. Reply to discussion of "Transmission electron microscopy of thin glass samples," (1) 5*g*.

Seward, T. P., III, Uhlmann, D. R., and Turnbull, D. Phase separation in the system BaO-SiO_2, (6) 187*g*.

Sewell, P. A. Physical adsorption on massive glass surfaces, (1) 6*i*.

Seweryniak, M. See Schroeder, J.

Seyferth, C. See Hauffe, K.

Seymour, J. A., and Beth, W. F. Hub mounting for grinding wheels, P (3) 61*g*.

Seymour, S. L. Glass gripping tongs and treatment thereof, P (10) 300*b*. Glass sheet press shaping apparatus with means to adjust the pressing surface curvature, P (5) 130*a*.

Shadden, V. Chemical etchant for PuO_2, (1) 20*j*.

Shade, R. W. See Kiser, K. M.

Shafer, M. W. Magnetic materials and process of preparation, P (6) 177*f*. Method for producing rare earth chalcogenides, P (3) 78*d*. See Guerci, C. F.; McGuire, T. R.

Shafer, M. W., and McGuire, T. R. Studies of Curie-point increases in EuO, (11) 357*f*.

Shafer, M. W., McGuire, T. R., Argyle, B. E., and Fan, G. J. Magnetic and optical properties of transparent $RbNiF_3$, (1) 16*g*.

Shafer, W. C. See Russell, R. G.

Shaffer, G. A., Jr., Campbell, L. R., and Blust, H. L. Method of making reed switches, P (5) 142*a*.

Shaffer, P. C. Cathode ray tube fabrication, P (3) 72*a*.

Shaffer, P. T. B. Ceramic fiber composites, (11) 332*f*. SiC whiskers (I, II), (4) 96*e*. See Webb, W. W.

Shaffer, R. A., and Bonney, L. G., Jr. Electron discharge device with storage target electrode, P (6) 177*f*.

Shah, G. B. Coatings—protective, (1) 3*j*.

Shah, J. S. See Pamplin, B. R.

Shah, R. K., and Oza, B. N. Silica to sesquioxide ratios for some clays of Saurashtra, Gujarat, India, (1) 32*b*.

Shahbender, R. Laminated ferrite memories—review and evaluation, (11) 342*j*.

Shaikh, M. S. See Amsterdam, M. F.

Shainberg, I., and Kemper, W. D. Electrostatic forces between clay and cations as calculated and inferred from electrical conductivity, B (8) 259*a*.

Shakespeare, A. G. FOS (fuel-oxygen-scrap) process, (9) 278*a*.

Shakhov, F. N. See Ermakov, I. S.

Shaklee, K. L., Cardona, M., and Pollak, F. J. Electroreflectance and spin-orbit splitting in III-V semiconductors, (10) 320*i*.

Shalaginov, V. N. See Bessonov, A. F.

Shalit, H. See McEvoy, J. E.

Shall, C. A. See Bolton, H. C.

Shaltiel, D. Nuclear magnetic resonance of $MnCO_3$ in the canted spin state, (8) 255*j*.

Shamp, D. E. See O'Connell, T. B.

Shan, Y. See Sun, Kuan-Han.

Shand, E. B. Breaking stresses of glass determined from fracture surfaces, (2) 38*g*. Weakening defects in glass, (1) 8*h*.

Shand, W. A. See Brown, M. R.

Shankland, T. J. Synthetic forsterite, (1) 25*g*.

Shanley, F. R. Composite material and method for making same, P (3) 72*c*.

Shannon, J. P., Jr., and Lord, C. W. Preservation of unconsolidated sediment cores in plastic, (5) 146*a*.

Shannon, R. F. Reinforced structural panels, P (1) 10*b*. Structural panel and method for producing same, P (1) 10*b*. See Rees, W. M.

Shannon, R. F., and Armstrong, M. C. Low density insulation bonded with colloidal inorganic materials, P (3) 68*h*.

Shapira, Y., Williamson, S. J., and Fischler, S. Quantum oscillations in the ultrasonic attenuation and magnetic susceptibility of InBi, (9) 285*h*.

Shapiro, E. Ya. See Poluboyarinov, D. N.

Shapiro, I. See Krochmal, J. J.

Shapiro, J. J. Self-contained conductivity meter having a tubular glass electrode assembly, P (1) 24*a*.

Shapland, J. T. Steel teeming nozzles, (6) 174*f*.

Shapovalova, N. F. See Syritskaya, Z. M.

Sharan, N. See Sinha, K. P.

Sharivker, S. Yu. See Epik, A. P.

Sharma, B. L. See Borle, W. N.

Sharma, R. See Kumar, R.

Sharma, R. R., and Das, T. P. Crystalline fields in corundum-type lattices, (6) 184*h*.

Sharma, S. K., Mukherjee, A., and Roy, H. Studies on some Indian limestones (IIA) estimation of dolomites by DTA analysis, (3) 62*h*.

Sharma, V. N. See Ramanath, T. V.

Sharp, D. J. Thin film capacitors employing semiconductive oxide electrolytes, P (11) 345*b*.

Sharp, J. H. See Addison, W. E.; Brindley, G. W.

Sharp, R. Felix White—an artist in glass, (2) 35*j*.

Shaver, P. J. Activated tungsten oxide gas detectors, (11) 350*d*.

Shaver, P. J., and Blair, J. Thermal and electronic transport properties of *p*-type ZnSb, (8) 258*c*.

Shaw, H. C. Chemical reaction catalyst and its preparation, P (7) 214*j*.

Shaw, H. J. See Lean, E. G. H.

Shaw, R. G. See Olson, R. S.

Shaw, R. R., and Uhlmann, D. R. Subliquidus immiscibility in binary alkali borates, (8) 257*j*.

Shaw Process (India), Ltd. Manufacture of ceramic shapes and bodies, P (3) 70*f*.

Shcherban, N. I. See Radomysel'skii, I. D.

Shcherbina, O. D. See Zanemonets, V. F.

Shchetnikova, I. L. See Rutman, D. S.

Shchukin, E. D. See Kontorovich, S. I.

Shea, F. L., Jr. See Mogg, D. W.

Sheahan, J. S. See Lane, M. K.

Shearouse, L. A. Bonded porcelain articles and method forming same, P (5) 137*c*.

Sheehan, G. M. See Whately, W. R.

Sheehan, P. J. See Laszlo, T. S.

Sheehan, R. T. Filled-bag [automatic] stacking palletizer, P (8) 251*c*.

Sheenko, I. N. Investigation of hard-facing rods of chromium carbide alloy, (2) 44*h*.

Sheets, H. D., and Duckworth, W. H. Hot-pressed magnesia refractories, (10) 303*f*.

Sheets, H. D., and Lennon, J. W. Material for hot top, P (6) 174*d*.

Sheinberg, H. See Riley, R. E.

Sheinkop, I. M., Tyurin, A. I., and Fel'dman, M. A. Use of booster electric heating in small regenerative glass furnaces, (8) 234*h*.

Sheldon, E. E. Devices for light transfer by fiber optic members, P (1) 8*i*. Vacuum tubes provided with light conducting members and with a screen of a high photoelectric sensitivity, P (7) 210*g*.

Shelimova, L. E., Abrikosov, N. Kh., and Zhdanova, V. V. System Ge-Te in the region of the compound GeTe, (4) 117*d*.

Shell Oil Co. Dehydrogenating olefins to diolefins in the presence of a yellow iron oxide catalyst, P (4) 104*j*.

Shelton, N. F. C. Progress in the development of analytical methods—reports from the working groups (I) refractory materials by wet chemical techniques, B (7) 224*g*.

Shelyubskii, V. I. Method of obtaining glass specimens of variable composition, (10) 298*c*.

Shen, L. See Goldman, M.

Shenango Ceramics, Inc. Kiln loader and unloader, P (4) 98*f*. Method for decorating pottery, P (9) 271*k*. Tile setter, P (5) 137*d*.

Shenango China, Inc. Tunnel kiln, P (9) 278*d*.

Shenberg, N. N. See Vitman, F. F.

Shenker, H. See Swiggard, E. M.

Shenoy, G. K. See Bhide, V. G.

Shepherd, I. W. See Feher, G.

Shepherd, T. L. See Paul, R. A.

Sheppard, R. A. See Gude, A. J., 3d

Sher, A., and Solomon, R. Rare earth fluoride capacitors, P (7) 210*c*.

Sher, A., Solomon, R., Lee, K., and Muller, M. W. Transport properties of LaF_3, (9) 288*f*.

Sher, A., and Thornber, K. K. Resonant electron-phonon scattering in polar semiconductors, (2) 50*g*.

Sherma, J. Ion-exchange paper chromatography of certain metal ions with aqueous-organic wash liquids, (5) 145*c*.

Sherman, W. F. See Cundill, M. A.

Sherstobitov, M. A., Popel, S. I., and Tsarevskii, B. V. Procedure for determining the rate of penetration of melts into materials of capillary porosity, (1) 22*i*.

Sherwin-Williams Co. Molybdated zinc oxide pigments and method for the preparation thereof, P (3) 78*f*.

Sherwood, P. W. New nondestructive techniques for material control in the glass and ceramic industry, (3) 76*a*.

Sherwood, R. C. See MacChesney, J. B.

Sherwood, W. L. Heating and discharge apparatus for fused materials in rotary furnaces, P (3) 68*g*.

Shestakov, A. I. Sintering of graphite powders during thermochemical treatment with carbide-forming elements, (8) 239*a*. See Zemskov, G. V.

Shevchenko, V. I. See Zhukov, V. V.

Shevelevich, R. S. EPR in silicate glass fibers, (2) 39*f*.

Shevtsova, Z. N. See Korshunov, B. G.

Shevyakov, A. M. See Kuznetsova, G. N.

Shibata, M. See Sato, K.

Shibazaki, K., Sasaki, S., Taniguchi, T., and Konishi, H. Compressive strength of seawater magnesite refractory grains at high temperature, (9) 266*j*.

Shibler, B. K. See Chindgren, C. J.

Shidlovsky, I. See Mayer, I.

Shieber, H. Prestressed refractory structure, P (1) 13*f*.

Shields, L. Radiation-induced atomic silver in Pyrex and sodium tetraborate glasses, (5) 128*g*.

Shiga, M. See Shinjo, T.

Shigata, H., Yamasaki, Y., and Sugihara, K. Process for producing a graphite anode, P (1) 14*d*.

Shikama, S. See Takahashi, M.

Shikano, H. Studies on test conditions for measuring hot bending strength of basic brick, (8) 239*j*.

Shiller, S. L. Electrode structure including temperature control means, P (3) 65*c*.

Shilov, I. S. See Beljaev, A. N.

Shimada, K. Low dielectric loss ceramics from wollastonite, (7) 206*a*. See Ohba, H.

Shimada, K., and Kume, K. Studies on the industrial application of Shirasu (I) autoclave-hardened bodies using Shirasu, (8) 250*j*.

Shimada, N., and Koyama, Y. Relation between erosion rate and brittleness index of ladle brick, (7) 202*j*.

Shimada, Y. See Kato, K.

Shimohira, T. See Oya, A.

Shimoiizaka, J. See Sato, T.

Shimoji, M. See Hoshino, H.

Shimoji, M., and Hoshino, H. Thermoelectric power of ionic crystals (I) general theory, (2) 50*i*.

Shimomura, Y. See Saito, S.; Yamada, T.

Shimony, U., and Knudsen, J. M. Moessbauer studies on iron in the perovskites $La_{1-x}Sr_xFeO_3$ ($0 < x \leq 1$), (9) 284*g*.

Shin Nippon Chisso Hiryo Kabushiki Kaisha. Apparatus and method for producing silicon single crystals for semiconductor, P (6) 177*a*.

Shinada, M., Sugano, S., and Kushida, T. Absorption spectrum of optically pumped ruby (II) theoretical analyses, (10) 318*j*.

Shinagawa Fire Brick Co., Ltd. Siliceous graphitic refractory material, P (7) 205*h*.

Shinbo, M. Volatilization loss of sodium borosilicate ternary glasses, (8) 235*b*.

Shindo, K., Morita, A., and Kamimura, H. Spin-orbit coupling in ionic crystals with zinc blende and wurtzite structures, (3) 86*i*.

Shinjo, T. See Bando, Y.

Shinjo, T., and Kosuge, K. Moessbauer effect study of V_2O_3, (10) 323*b*.

Shinjo, T., Kosuge, K., Kachi, S., Takaki, H., Shiga, M., and Nakamura, Y. Antiferromagnetism of V_2O_3 observed by the Moessbauer effect, (4) 106*d*.

Shinoda, S. See Teramoto, I.

Shinohara, K., Idemitsu, Y., Gotoh, K., and Tanaka, T. Mechanism of gravity flow of particles from a hopper, (11) 345*h*.

Shiojiri, M. Crystallization of amorphous titanium dioxide films prepared by vacuum evaporation, (7) 216*b*. See Suito, E.

Shionoya, S. See Makishima, S.

Shionoya, S., Era, K., and Washizawa, Y. Nature of the green-copper luminescence transition in ZnS as elucidated by measurements of the time-resolved spectrum, (10) 323*g*.

Shionoya, S., Kobayashi, Y., and Koda, T. Polarization of the green copper luminescence in hexagonal ZnS single crystal, (3) 85*a*.

Shiozawa, Ken-ichi. See Nasu, S.

Shirafuji, J. See Kodera, H.

Shiraishi, S., and Moriyama, T. Manufacture of alumina cement by burning in a rotary kiln and its physicochemical properties, (8) 238*b*.

Shiraishi Kogyo Kaisha, Ltd. Process for the manufacture of modified clays, P (2) 57*a*.

Shiraiwa, T. See Fujiwara, S.

Shirakawa, S. See Shiraki, Y.

Shiraki, Y., Otsuka, N., and Shirakawa, S. Studies on the sedimentation of clay (III) treatment of acid waste liquor in the clay industry and recovery of a usable by-product, (8) 250*a*.

Shiraki, Y., and Suzuki, S. Thermal and chemical behavior of alunite and its use as a ceramic raw material, (8) 250*b*.

Shirasaki, S. See Kubo, T.

Shirley, D. E. High alumina cements in the heavy clay industry, (9) 266*f*.

Shirn, G. A. See Smyth, D. M.

Shishido, K. See Sakurai, T.

Shklyar, Ya. V. See Ginzburg, D. B.

Shkol'nikov, E. V., and Frish, G. Study of the continuous isothermal crystallization of semiconductor glasses by measurement of the electrical conductivity, (9) 264*e*.

Shleg, A. U. See Sirota, N. N.

Shnypikov, A. D. See Dubrovo, S. K.

Shoaff, R. J. Preparation of anhydrous sodium metasilicate, P (5) 148*g*. Preparation of sodium trisilicate, P (3) 78*a*.

Shockey, D. A., and Groves, G. W. Effect of water on toughness of MgO crystals, (7) 217*f*.

Shockley, W. Semiconductor device having regions of different conductivity types wherein current is carried by the same type of carrier in all the regions, P (11) 345*e*.

Shockley, W., and Curran, D. R. Piezoelectric resonator, P (8) 245*j*.

Shoda, K. See Moriyama, K.

Shoda, K., and Moriyama, K. Method for making semiconductor devices, P (8) 245*a*.

Shoemaker, F. O. Grinding disk, P (9) 261*i*.

Sholine, J. H. See Lawver, J. E.

Shono, Y. See Sugawara, F.

Shore, H. B. See Feher, G.

Short, O. A. Silver compositions containing novel vitreous binders and a vehicle, P (2) 42*c*.

Shott, W. L. See Miller, W. A.

Shover, E. F. Clay-mineral environmental relations in Cisco (U. Penn.) clays and shales, north central Texas, B (6) 192*c*.

Shovic, F. C. See Sorenson, T. I.
Shpakov, V. N. See Voron'ko, Yu. K.
Shpunt, A. A. See Strelkov, P. G.
Shreve, W. T. Automatic optical pyrometer system with automatic gain control, P (3) 76*d*.
Shtefan, M. See Sychev, M. M.
Shteiert, N. P. See Volkonskii, B. V.
Shteinberg, Yu. G. Strontium Glazes, B (10) 329*b*.
Shteinberg, Yu. G., and Nevorotina, M. I. New compositions for strontium leadless colored glazes for earthenware, (8) 242*e*.
Shtipel'man, Zh. V. Spectroscopic determination of alumina and ferric oxide in the raw materials and slimes of alumina manufacture, (10) 315*f*.
Shuih, Chung-Hsiung. See Streib, W. C.
Shukla, B. K. See Trivedi, P. M.
Shull, J. D., Jr. High strength gypsum plaster, P (7) 194*f*.
Shul'man, V. M. See Leonova, T. G.
Shumaker, L. L. Abrasive marking, P (7) 197*j*.
Shur, A. S., Anufriev, Yu. N., and El'kina, N. T. Ultra- and microporosity of quartz crystals, (4) 118*e*.
Shuskus, A. J. Paramagnetic resonance of divalent iron in calcium oxide, (5) 156*j*. Paramagnetic resonance of some S-state ions in single crystals of strontium oxide, (5) 156*a*.
Shuster, J. S. See Englehart, O. D.
Shvaiko-Shvaikovskii, V. E. See Leonov, A. I.
Shveikin, G. P. See Alyamovskii, S. I.
Shwartzman, S. Method of making semiconductor devices, P (8) 245*a*.
Sibert, F. J. Process of making alumina, P (10) 318*a*.
Sibley, W. A. See Mathews, J. W.
Sibley, W. E. Discovery report—the Longol San Miguel burial site, Guimbal, Iloilo, (8) 227*j*.
Siclet, G. See Eyraud, M. C.
Sidorenko, F. A. See Andreeva, L. P.
Sidorko, V. P. See Eremenko, V. N.
Sidorov, A. B., Kulyamina, L. L., and Zhornik, A. I. Stress distribution in internal glass coating of steel pipes due to difference in coefficients of expansion of glass and metal, (10) 298*j*.
Sidorov, T. A., and Tyul'kin, V. A. Study of the EPR spectra of some irradiated two-component glasses, (10) 299*c*.
Siegel, I., and Lorenc, J. A. Paramagnetic resonance of copper in amorphous and polycrystalline GeO_2, (10) 324*g*.
Sieger, J. S. Method of making glass polishing composition, P (9) 265*e*. See Demarest, H. M., Jr.
Sieger, J. S., and Cox, D. E. Glass polishing composition containing dissolved zirconium and zirconium oxide, P (9) 265*c*.
Sieger, J. S., and Gagne, R. Densification of glass under a cutting wheel, (6) 166*j*.
Siegla, D. C. See Bassett, A. T., Jr.
Siegmund, W. P. Fiber optical image-encoding-decoding device, P (4) 94*h*. Method of making fiberscopes, P (8) 235*h*.
Siegmund, W. P., and Cole, H. B. Method for making bubble free fiber optical image-transfer devices, P (3) 65*h*.
Siegmund, W. P., and Gilmore, G. B. Method of making energy-conducting components formed of fiber elements, P (2) 41*e*.
Siekanowicz, W. W., Schilling, W. A., and Bardash, I. Latched ferrite circulators, P (2) 51*f*.
Siem, R. C. Dehydrogenating olefins to diolefins in the presence of a yellow iron oxide catalyst, P (4) 104*j*.
Siemens Akt.-Ges. Apparatus for pyrolytic production of semiconductor material, P (1) 17*j*. Apparatus for uniform feeding of powder into a plasma spray gun, P (9) 263*a*. Barrier-free contacting of ceramic bodies, P (2) 50*f*. Device for the transmission of short electromagnetic waves, especially for highest frequency tubes, P (8) 244*h*. Field-effect pressure transducer, P (7) 208*h*. Hall generator magnetic structure, P (6) 177*b*. Method and apparatus of epitaxially depositing semiconductor material, P (5) 141*e*. Method for indiffusion of foreign material into a monocrystalline semiconductor member, P (7) 209*e*. Method for mass producing semiconductor devices, P (11) 344*e*. Method for producing highly pure particularly silicon-free $A^{III}B^{V}$ compounds, P (11) 344*e*. Method of producing monocrystalline semiconductor bodies, P (7) 209*d*. Method of producing monocrystalline semiconductor members with layers of respectively different conductance, P (4) 100*g*. Method for producing a *pn* junction in a monocrystalline semiconductor member by etching and diffusion, P (7) 209*f*. Method for producing pure polished surfaces on semiconductor bodies, P (10) 310*g*. Method of producing semiconductor members by alloying metal into a semiconductor body, P (9) 274*f*. Method of treating the surface of semiconductor devices for improving the noise characteristics, P (10) 310*j*. Point-contact diode with Au-Pt point, P (3) 74*a*. Pressure-responsive transistor, P (5) 142*c*. Pulling nozzle for oriented pulling of semiconductor crystals from a melt, P (10) 311*h*. Semiconductor device with anisotropic inclusions for producing electromagnetic radiation, P (7) 210*f*. Semiconductor device of the four-layer type, P (10) 311*c*. Semiconductor latching switch with light-coupled triggering means, P (5) 143*a*. Sintered composition material, P (8) 246*a*. Thermoelectric mosaic interconnected by semiconductor leg protrusions and metal coating, P (10) 311*f*. Vacuum-tight connection between a ceramic tube and a disk-shaped metal part of an electrical discharge vessel, P (8) 230*a*.
Siemens & Halske Akt.-Ges. Apparatus for pulling semiconductor crystals, P (1) 17*i*. Apparatus for the pyrolytic production of rod-shaped semiconductor bodies, P (4) 99*c*. Germanium transistors, P (1) 17*j*. Method of growing doped crystalline layers of semiconductor material upon crystalline semiconductor bodies, P (2) 51*j*. Method of metal-coating ceramic bodies, P (1) 18*f*. Method of producing epitaxial layers on semiconductor monocrystals, P (1) 18*h*. Method of producing semiconductor components, P (1) 18*i*. Process for the deposition of a thin layer of a very pure brittle material in crystalline form, P (2) 52*d*. Process for drawing a crystalline semiconductor body from a melt, P (2) 52*d*. Processes for the manufacture of substantially homogeneously doped crystals of semiconductor material, P (2) 52*h*. Processes for the metallization of the surfaces of ceramic bodies, P (1) 19*a*. Semiconductor arrangements, P (1) 19*b*.
Siemens-Planiawerke Akt.-Ges. fuer Kohlefabrikate. Furnace for producing graphite electrodes, P (5) 147*e*. High-temperature electric furnace with molybdenum silicide heater elements, P (6) 182*d*. High-temperature resistant structural body, P (9) 270*d*.
Siemens-Schuckertwerke Akt.-Ges. Apparatus and method of producing semiconductor rods by pulling the same from a melt, P (4) 99*b*. Deposition of semiconducting material from the gas phase, P (2) 50*j*. Manufacture of semiconductor materials, P (1) 18*h*. Method and apparatus for producing a semiconducting compound of two or more components, P (1) 18*i*. Method of and apparatus for use in melting glass or other oxidic substances, P (1) 9*i*. Method of determining the specific resistance of a semiconductor material in the form of a thin layer, P (7) 209*d*. Method of producing monocrystalline semiconductor material, P (5) 142*e*. Method of producing monocrystalline semiconductor rods, P (2) 51*e*. Method of producing selenium midget rectifiers, P (1) 18*h*. Method for producing a selenium rectifier having a high blocking voltage, P (5) 142*f*. Method of producing thin layers of galvanomagnetic semiconductor material, particularly Hall generators of $A^{III}B^{V}$ compounds, P (2) 51*g*. Method of producing thyristors by [Au] diffusion in semiconductor material, P (1) 18*i*. Method for the production and remelting of compounds and alloys, P (5) 142*f*. Process of producing monocrystalline layers of indium antimonide, P (3) 74*c*. Process for the production of a doped zone in a body of semiconductor material, P (2) 52*g*. Process for use in the production of substantially monocrystalline wafers, P (2) 52*k*. Production of monocrystalline semiconductor material, P (2) 52*b*. Production of an oxide coating on a substantially monocrystalline body of semiconductor material, P (2) 52*b*. Production of ultrapure silicon carbide, P (1) 20*c*. Reduction of unwanted thermoelectric effects in semiconductor devices, P (5) 142*f*. Semiconductor components, P (1) 19*c*. Semiconductor thyristor of *pnpn* type, P (5) 143*a*. Sintered contact body, P (1) 19*d*. Stabilized *pnpn* switch with rough area shorted junction, P (5) 143*c*. Treatment of semiconductor bodies, P (5) 143*b*.
Siemers, E. Recovery of alumina from clay with organic polymeric materials, P (5) 149*a*.
Siemssen, E. A. Air preheating burner with furnace preheating passage cleaner means, P (4) 104*f*.
Sienko, M. J. See Crowder, B. L.; Perkins, H. K.
Sigel, S. See Hoekstra, H. R.
Signal Oil & Gas Co. Process for the recovery of lithium and potassium from Great Salt Lake brine, P (1) 25*j*.
Signalite, Inc. Method for forming electric lamps and similar devices, P (11) 336*f*.
Signetics Corp. Multichip integrated circuit assembly with interconnection structure, P (9) 274*a*. Thin film resistor, P (8) 246*f*.
Signode Corp. Method of and apparatus for packaging bricks, P (3) 66*g*.
Signorelli, R. A. See Weeton, J. W.
Sihvonen, Y. T., and Parker, S. G. Printed [FE] transistors and methods of making same, P (5) 142*c*.
Sikina, T. V. See Murray, F. L., Jr.
Silber, C. C. See Rowe, J. J.
Sillick, W. E. See Perlowski, J. S.
Silva, R. Plant savings and the control hierarchy, (10) 328*a*.
Silverman, M. S. Bismuth diselenide and a method for its preparation, P (2) 50*g*. Molybdenum ditelluride and high-temperature high-pressure synthesis method of preparing same, P (8) 241*c*. See McWhan, D. B.
Silverwood, F. W. Apparatus for the manufacture of flat glass on a molten metal bath, P (2) 40*a*. See Lawrenson, J.; Pilkington Brothers, Ltd.; Robinson, A. S.
Silverwood, F. W., and Heyes, R. Apparatus for skimming dross from a molten metal bath, P (1) 8*c*.
Silvestri, V. J., Lyons, V. J., and Marinace, J. C. Semiconductor-metal-semiconductor structure, P (9) 275*b*.
Sil'vestrovich, S. I. See Kitaigorodskii, I. I.
Sil'vestrovich, S. I., and Firsov, V. M. Peculiarities of chemical etching of hardened glasses, (6) 168*g*.
Sil'vestrovich, S. I., and Pliska, T. A. Thermographic studies of structural changes in glass after γ-radiation, (8) 234*g*.
Simha, R. See Moacanin, J.; Nanda, V. S.
Simison, A. L. Method for producing a fibrous mat, P (8) 235*i*.
Simkins, A. C. Efficiency in brickmaking—drying, (5) 130*j*.
Simm, W. See Tannenberger, H.
Simmingskold, B. Stronger glass (I, II), (5) 128*a*. See Lakatos, T.; Zinggl, H.
Simmler, F. See Lukacs, J.
Simnad, M. T. See Mills, R. G.
Simoes, J. M. dos S. See Santos Simoes, J. M. dos.
Simon, G. See Glaser, W.
Simonacco, Ltd. Filtration, P (7) 211*b*.
Simonds Abrasive Co. Diamond abrasive article containing hexagonal crystalline boron nitride particles, P (8) 227*h*.
Simonyan, K., and Kim, H. Testing apparatus for a sequence of transistors, etc., having a condition responsive marker, P (1) 19*b*.
Simpson, G. R. See Dixon, E. O.
Simpson, H. E. Glass industry 1967 (I–IV), (11) 334*c*.
Simpson, W. I. See Manasevit, H. M.
Sims, C. T. See Girard, R. T.
Sinclair, D. Method and apparatus for determining the dewpoint of a gaseous mixture, P (9) 277*e*.
Sinclair, W. R. Inorganic glass films—preparation, properties, and uses, (11) 334*f*. Preparation of metal oxides by reactive sputtering of carbides, P (11) 345*b*.
Sinclair, W. R., and Calbick, C. J. Orientation effects of an applied dc field on NaCl films deposited on silica glass, (5) 156*f*.
Sinclair, W. R., Peters, F. G., Stillinger, D. W., and Koonce, S. E. Devitrification of tin oxide films (doped and undoped) prepared by reactive sputtering, (4) 107*i*.
Sinclair, W. R., and Stillinger, D. W. Method of preparing a film resistor by sputtering a ternary alloy of tin, antimony, and indium in the presence of oxygen, P (9) 274*e*.
Sinclair Refining Co. Boehmite alumina products, P (7) 214*i*.
Sinclair Research, Inc. Catalyst containing silica-alumina and finely divided CaF_2, MgF_2, SrF_2, AlF_3, or InF_3, P (4) 104*i*. Dehydrogenation process and alumina-supported nickel, molybdenum, and alkali metal catalyst therefor, P (1) 25*a*. Method of ion exchanging crystalline aluminosilicates, P (8) 251*g*. Method [flotation] of separating catalyst particles into fractions of differing surface area, P (4) 105*h*. Olefin polymerization using group VIII metal and zinc fluoride or boria on activated alumina as catalyst, P (4) 105*b*. Process for preparing silica-alumina, P (9) 279*d*.
Sines, G. See Babel, H. W.
Sinfelt, J. H. See Taylor, W. F.
Sinfelt, J. H., Taylor, W. F., and Dembinski, G. W. Catalyst compositions and process for preparation thereof, P (1) 25*i*.
Singer, A. See Davis, B. C.
Singer, J. Method of fusing single layer fiber optic strip, P (1) 9*c*.
Singer, J., and Faeth, P. A. Orientation of Cu_2S formed on single crystal CdS, (2) 50*a*.
Singer, L. S., and Stamires, D. N. Trace ferromagnetism in zeolites, (3) 88*k*.
Singh, A. Determination of swelling pressure of expansive clays, (1) 24*i*. See Chadha, O. P.
Singh, G. Building lime from press mud, (3) 66*g*. Pattern of laboratory investigation for large scale use and manufacture of pozzolans, (3) 62*d*.
Singh, M., and Kumar, R. Electrical conductivity of Al-Si and Al-Si-Mg alloys, (1) 16*e*.
Singh, P. D., and Pathak, A. N. Vibrational transition probabilities and *r* centroids of the A→X band system of ZrO, (2) 60*c*.
Singh, S. See Geusic, J. E.
Singh, V. N. Variation in the character of montmorillonite as revealed by optical, electron microscope, X-ray diffraction, thermal, and dilatometric studies, (1) 33*i*.
Singman, D. Preliminary evaluation of ceria-lanthana as a solid electrolyte for fuel cells, (7) 207*g*.
Sinha, A. N., and Balasundaram, L. J. Curie temperature of iron-aluminum and iron-silicon alloys, (5) 137*g*.
Sinha, A. P. B. See Chandra, P.; Jogalekar, P. P.
Sinha, B. C. See Kumar, S.
Sinha, J. See Dell, C. C.
Sinha, K. P. See Agarwal, V. S.
Sinha, K. P., and Sharan, N. Effect of mold materials on the microstructure, shrinkage, and mold wall movement of aluminum-4.5% Cu alloy, (2) 44*c*.
Sinitsyn, B. V. See Dolomanov, L. A.
Sinitsyn, N. M., and Zvyagintsev, O. E. Thermal stability of complex compounds of ruthenium containing the NO group, (10) 326*a*.
Sinner, W. E. Electrode for glass melting furnaces, P (7) 198*d*.
Sipos, B. See Sajo, I.
Sippel, R. F., and Glover, E. D. Structures in carbonate rocks made visible by luminescence petrography, (5) 146*b*.
Sirazhiddinov, N. A. See Toropov, N. A.
Sircar, N. R. Microstructure of refractories, (5) 132*i*. See Banerjee, J. C.
Sirhal, H. Line production in the brick and tile industry by stabilizing technological conditions, (1) 10*j*.

Sirhal, H., and Kastanek, J. Achieving the optimal preparation equipment for plastic brick materials through a knowledge of the technological characteristics of the machines, (10) 301*e*. Changes in the physical-mechanical properties of ceramic bodies during firing as a base for determining the optimum firing schedule, B (9) 291*e*.

Sirkis, M. D. See Johnson, M. R.

Sirota, N. N., Lekhnovich, N. M., and Shieg, A. U. (Editorial Board). Chemical Bond in Semiconductors and Thermodynamics, B (8) 259*e*.

Sirotkina, E. I. See Kovba, L. M.

Sirtl, E. See Heywang, W.

Sirtl, E., and Dersin, H. Method of producing epitaxial layers on semiconductor monocrystals, P (1) 18*h*.

Sirvydas, V. C. See Goldman, R. L.

Sistermanns, A. See Gebhardt, F.

Sites, L. K., Jr. See Aiken, H. H.

Sitnikova, A. Ya. Effect of powdered metal fillers on the properties of silicate enamels, (5) 125*i*.

Sivokon, V. I. See Magidovich, V. I.

Sivolobova, T. S. Development of X-ray spectral analysis of silicate materials, (11) 346*i*.

Skalla, N. F. See Leitner, K.

Skalny, J. See Grzymek, J.

Skalny, J., and Odler, I. Effect of chlorides on the hydration of portland cement and on some clinker materials, (8) 228*h*.

Skalyo, J., Jr. See Uryu, N.

Skancke, A., and Kierkegaard, P. X-ray studies of some wolfram [tungsten] oxide phosphate glasses, (6) 169*i*.

Skarbye, H. Influence of glaze on strength of high tension porcelain, B (9) 291*f*.

Skidan, B. S., Vlasov, A. S., and Poluboyarinov, D. N. Determination of toughness of ceramic materials, (6) 180*h*. Impact strength of cermets of the Al_2O_3-M system, (7) 202*a*.

Skipper, B. R. See Maynard, R. N.

Skirvin, F. A., Campbell, T. T., and Block, F. E. Purification of tungsten hexachloride, (4) 114*d*.

Sklyarenko, L. I. See Bremenko, V. N.

Skoblo, L. I. See Klyucharov, Ya. V.

Skolozdra, R. V. See Fedorov, T. F.

Skomorowski, E. See Grzymek, J.

Skorik, Yu. I., Kukharskaya, E. V., Fedoseev, A. D., and Klimova, K. P. Modification of chrysotile asbestos with organosiloxanes in an acoustic field, (7) 202*a*.

Skramtaev, B. G., Panfilova, L. I., and Trinker, B. D. Measures for combating false set of cement, (2) 36*d*.

Skrylev, L. D. See Kalitina, L. N.

Skvara, F., and Zbuzek, B. Microscopic study of the dissolution of α-$CaSO_4 \cdot {}^1/_2H_2O$ crystals in water, (1) 30*g*.

Skvor, F. See Jakes, D.

Sladek, R. J. See Ghanekar, K. M.

Slagle, K. A., and Tamura, T. Method of disposing of waste materials, P (7) 223*g*.

Slaughter, M. Petrogenesis of bentonites (abstract), B (6) 191*c*.

Slavic, I. See Stojic, M.

Sleight, A. W. Cu^{2+} or Cu^{1+} in chalcogenide spinels? (4) 107*i*.

Sleighter, G. E. See Chisholm, R. S.; Fredley, J. C.

Sleppy, W. C. Reaction of sodium with graphite at 400°, (6) 188*d*.

Sleptsov, V. M. See Kukota, Yu. P.; Prshedromirskaya, E. M.

Sleptsov, V. M., Prshedromirskaya, E. M., and Kukota, Yu. P. Porous materials from carbides and borides of the transition metals, (5) 133*c*. Preparation and properties of spherical powders of refractory compounds, (5) 133*f*.

Slichter, C. P. See Satoh, M.

Slinn, G. G. See Beasley, E. S. G.

Sloane, R. L. Early reaction determination in two hydroxide-kaolinite systems by electron microscopy and diffraction, B (7) 225*a*.

Sloane, R. L., and Guilbert, J. M. Electron-optical study of alteration to smectite in the Cheto clay deposit, B (9) 289*d*.

Sloane, R. L., and Kell, T. R. Fabric of mechanically compacted kaolin, B (8) 259*g*.

Sloka, W. E., and Vaaler, L. E. Contact resistance of graphite lead-in rods, (10) 306*h*.

Slone, T. J., and Orbeck, L. J. Electrical porosimeter, P (6) 181*e*. Porosimeter, P (6) 181*f*.

Slysh, R. S., and Kagan, G. M. Modified cement mortar containing emulsion polymer of 2 methyl α olefin and mixed dialkyl fumarate, P (6) 166*a*.

Smakula, P. H., and Claspy, P. C. Electrooptic effect in $LiNbO_3$ and KTN, (4) 109*f*.

Smallbone, A. H. Apparatus for preparing samples for X-ray analysis, P (9) 277*d*.

Smart, P. Particle arrangements in kaolin, B (9) 289*d*.

Smeggil, J. See Franzen, H. F.

Smetana, Z. Simple cryostat for the range −190° to +200°C, suitable for the measurement of ferromagnetic resonance, (11) 347*h*.

Smialek, L. J. See Ishler, W. E.

Smidth, F. L., & Co. Crushing and drying apparatus, P (1) 25*j*. Preheating apparatus for cement raw meal, P (4) 92*f*. Rotary kiln assemblies, P (6) 182*b*. Rotary kiln installations, P (2) 56*c*, P (4) 104*e*. Silo plant, P (2) 53*g*.

Smirnov, A. F. See Makarov, E. S.

Smirnov, G. V. See Arslambekov, V. A.

Smirnov, M. V., Komarov, V. E., and Chukreev, N. Ya. Fluoride complexes of beryllium in a chloride-fluoride melt, (10) 321*e*.

Smirnov, S. N. See Golubev, B. P.

Smirnov, V. N. See Przhiyalgovskii, S. M.

Smiser, L. W. See Eppler, R. A.

Smith, A. B. See Jones, R. V.

Smith, A. E. See Levey, R. P., Jr.

Smith, A. W. See Giess, E. A.

Smith, B. R. Iron alloy, P (6) 170*h*.

Smith, C. F., Jr., and Crandall, W. B. Method of making carbon-containing glass and product thereof, P (7) 199*c*.

Smith, C. S. Materials, B (11) 358*h*.

Smith, D. A. See Fortes, M. A.

Smith, D. A., Ralph, B., and Williams, W. S. Field-ion microscopy of titanium carbide, (8) 253*h*.

Smith, D. C. See Combe, E. C.; Hinson, A. L.

Smith, D. F., and Cagle, C. V. Ultrasonic testing of adhesive bonds using the Fokker Bond Tester, (7) 213*b*.

Smith, D. G. W. Petrology and mineralogy of some lower Devonian bentonites from Gaspe, P. Q., (5) 148*e*.

Smith, D. G. W., and McConnell, J. D. C. Comparative electron diffraction study of sillimanite and some natural and artificial mullites, (1) 27*d*.

Smith, D. K., Jr. See Borg, I. Y.

Smith, D. K., Jr., Cline, C. F., and Austerman, S. B. Crystal structure of β-BeO, (3) 67*a*.

Smith, D. K., Jr., and Weissmann, S. Residual stress and grain deformation in extruded polycrystalline BeO ceramics, (7) 221*f*.

Smith, D. W. See Riebling, E. F.

Smith, E. Fracture initiation at a sharp notch, (9) 282*c*.

Smith, E. A. Size reduction to the lower micron size range, (4) 101*j*.

Smith, F. G. Machine plotting of liquidus data of binary and ternary salt systems, (5) 154*b*.

Smith, G. A. Forklift trucks—gas or electric? (2) 53*a*.

Smith, G. P. Photochromic silver halide glasses, (11) 334*c*.

Smith, G. S. See Evans, P. E.

Smith, G. S., Johnson, Q., and Tharp, A. G. Crystal structure of Sm_5Ge_4, (2) 57*g*.

Smith, H. I. See Vaart, H. van de.

Smith, I. L. Blue electroluminescent phosphor and method for its production, P (9) 272*i*. Green electroluminescent zinc sulfide phosphor, P (6) 177*b*. Preparation of halophosphate phosphor, P (7) 210*a*.

Smith, J. See Russell, H.

Smith, J. G. See Fitch, F. T.; Flack, H. P.

Smith, J. G., and Fitch, F. T. Process for preparing uranium dioxide-yttrium oxide-zirconium dioxide microspheres, P (3) 69*h*.

Smith, J. J., and McGary, T. E. Tracer studies with samarium via instrumental neutron-activation analyses, (11) 335*b*.

Smith, J. M. See Adams, N.; Jones, L. H.; Kortkamp, D. H.

Smith, J. S., II. See Mazdiyasni, K. S.

Smith, J. T. See Goldsmith, H. J.

Smith, J. W., and Keene, C. W. Basic oxygen furnace lining construction, P (11) 339*i*.

Smith, K. See Kelly, B. T.

Smith, L. N. Design and fabrication of sheet steel parts for porcelain enameling, (9) 262*j*.

Smith, M. A. See Gutt, W.

Smith, M. J. A., and Angel, B. R. Some electron spin resonance properties of heat-treated synthetic diamond, (1) 32*f*.

Smith, P. D. See Turner, D. N.

Smith, P. E., and Gilles, P. W. High temperature rare earth-boron-carbon studies (III) LnB_4C_2 and the ternary phase diagram, (6) 186*i*.

Smith, R. See Billmeyer, F. W., Jr.

Smith, R. C. See Colles, M. J.; Hacskaylo, M.

Smith, R. E. Method of softening glass for punching holes therein by heating with a high frequency pulse current, P (5) 130*a*. See Palmer, W. B.

Smith, R. M., and Wells, L. J. Glass aerosol bottles and method for making same, P (4) 94*i*.

Smith, R. T., Achenbach, G. D., Gerson, R., and James, W. J. Dielectric properties of solid solutions of $BiFeO_3$ with $Pb(Ti,Zr)O_3$ at high temperature and high frequency, (9) 280*f*.

Smith, R. W. Visual indicating spark plug with an integral gas lamp, P (1) 19*d*.

Smith, S. J. See Scott, A. D.

Smith, T. P. Method for producing hermetic glass to metal seals, P (6) 171*g*.

Smith, W. A. See Williams, D. T.

Smith, W. C. Miniature transistor enclosed in a glass disk-shaped housing, P (7) 209*h*. See Domicone, J. J.

Smith, W. E. Glass composition and method and product, P (8) 235*j*. See Rhodes, E.

Smith, W. M. See Gladrow, E. M.

Smoak, R. H. See Hulbert, S. F.

Smock, G. E., and Fulk, W. F. Integrated body of multifilament strands, P (10) 300*d*.

Smoke, E. J. Effect of fine silica on the properties of typical porcelain, (2) 48*i*. Prereacted raw materials, B (3) 89*d*.

Smoke, E. J., and Bersch, C. F. Radome research yields unique approaches, (3) 67*i*.

Smoke, E. J., and Snyder, N. H. Prereacted raw materials technique for attaining high quality ceramics, P (4) 97*d*.

Smoluchowski, R. See Dienes, G. J.

Smothers, W. J. Coated insulator, P (9) 271*f*. See Kreglo, J. R., Jr.; Ulmer, G. C.

Smrdel, J. A. See Allen, E. M.

Smucker, C. A., Rigby, W. H., Jr., Klein, P. H., Jr., and Palmer, B. M. Waste wash water and waste binder reuse system and apparatus for mineral fiber forming process, P (3) 66*e*.

Smucker, C. A., Rigby, W. H., Jr., and McCombs, F. P. Binder composition and method, P (8) 235*e*.

Smudski, P. A. Metal carbide and boride production, P (7) 204*j*.

Smulikowski, K., and Walenczak, Z. Lithium content in quartz from mica schists, gneisses, and granitoids of various origin in Lower Silesia, (7) 219*d*.

Smurova, V. S. See Rachev, V. V.

Smyly, J. P. Ceramic dielectrics, P (4) 99*f*.

Smyth, D. M., Tripp, T. B., and Shirn, G. A. Heat treatment of anodic oxide films on tantalum (IV) anodization in phosphoric acid solutions, (7) 207*b*.

SNAM Progetti S.p.A. Method of forming spheroids of particulate agglomeration-resistant refractory metal oxides, P (11) 349*a*.

SNAM S.p.A. Process for the preparation of bayerite alumina, P (5) 149*a*.

Snaper, A. A. Color-producing tube having screen containing plurality of birefringent materials, P (10) 309*i*.

Snell, R. G. See Linn, F. C.

Snellman, R. Refractory pouring tube for degassing vessels, P (3) 69*f*. Shapes and method for lining a rotary kiln, P (8) 241*e*.

Snetsinger, K. G., and Keil, K. Microspectrochemical analysis of minerals with the laser microprobe, (7) 212*j*.

Snitzer, E. Glass lasers (I, II), (2) 39*i*. Glass lasers, (9) 263*f*. High resolution filter for laser-emissive energy, P (6) 177*d*. Laser amplifier device, P (11) 343*j*. Optical frequency harmonic generating structure, P (11) 336*d*. Quantum counters, P (7) 199*f*.

Snow, E. H., and Deal, B. E. Polarization effects in insulating films on silicon—a review, (10) 307*j*. Polarization phenomena and other properties of phosphosilicate glass films on silicon, (7) 207*f*.

Snow, G. E. See Hafford, B. C.

Snow, R. H. See Work, L. T.

Snyder, C. R. Glass technology applied to infrared detector housings, (3) 63*j*.

Snyder, L. R. Principles of Adsorption Chromatography—The Separation of Nonionic Organic Compounds, B (9) 290*c*.

Snyder, N. H. See Smoke, E. J.

Snyder, W. T. Metal ingot mold with protective [refractory] coating, P (11) 332*i*.

So, J. J. Short-channel field-effect transistor having an impurity gradient in the channel increasing from a midpoint to each end, P (11) 345*f*.

Soardo, G. P. See Ferro, A.

Sobotka, Z. Differential relations for rheological models of viscoelastic bodies with Kelvin elements, (11) 351*d*.

Societa Ceramica Italiana Richard-Ginori S.p.A. Apparatus for drying ceramic ware, P (8) 249*j*.

Societa Italiana Telecommunicazioni Siemens S.p.A. Nonreciprocal ferrite device having a thin dielectric layer encircling the ferrite element, P (2) 52*a*.

Societe Anonyme Glaverbel. Apparatus for the manufacture of sheet glass on a molten bath, P (3) 64*j*. Bending chamber for the manufacture of sheet glass by drawing, P (3) 65*b*. Device for the working of pasty fusion products, P (8) 235*g*. Electrode device for electric furnaces, P (8) 235*h*. Glass manufacture, P (7) 198*g*. Manufacture of sheet glass, P (1) 9*i*. Means for the thermal homogenization of glass for drawing it in sheet form, P (3) 65*a*. Melting and refining of vitrifiable or other materials, P (5) 130*f*. Method and apparatus for heating glass, P (7) 199*b*. Method and apparatus for protecting sheet glass during thermal treatment, P (10) 300*i*. Process and apparatus for the homogenization of molten glass in the chamber connecting the refining furnace to the working compartment, P (2) 42*c*. Process for casting [refractory] articles, P (8) 241*g*. Process for producing glass/metal compositions, P (5) 130*c*. Processes and apparatus for the manufacture of sheets of glass by drawing, P (2) 42*f*. Protective salts bath for use in glass ribbon manufacture, P (7) 199*f*. Spout for the discharge of molten glass, P (2) 42*e*.

Societe Anonyme de Machines Electrostatiques. Electrostatic coating system, P (8) 247*c*.

Societe le Carbone-Lorraine. Method and apparatus for metallic impregnation of carbon and graphite, P (11) 340*h*.

Societe d'Electronique et d'Automatisme. Manufacturing thin monocrystalline layers, P (8) 244*j*.

Societe Europeenne d'Isolateurs en Verre. Insulator and method of making using electrostatically applied dielectric fibers as spacer pads and gaskets, P (10) 310*a*.

Societe Fives Lille-Cail. Tire fastening for a rotary shell, P (8) 249*j*.

Societe des Forges et Ateliers du Creusot. Pyrometric probe, P (11) 348*d*.

Societe Metallurgique d'Imphy. Gas burner with proportional mixer, P (6) 182*c*.

Societe Nationale d'Etude et de Construction de Moteurs d'Aviation. Method of coating graphite with a refractory coating and products obtained, P (5) 135*j*.

Societe a Responsabilite Limitee Doittau Produits Metallurge. Method for producing an exothermic lining for ingot and foundry molds and hot tops, P (1) 13*g*.

Societe des Soudures Castolin S. A. Coated electrode for arc welding of cast iron, P (6) 166*c*.

Societe Suisse pour l'Industrie Horlogere S.A. Transistor-capacitor integrated circuit structure, P (8) 246*g*.
Soederquist, R., and Dickens, B. Studies in solid-state chemistry (I) solid-state mechanism for the polymorphic transformation of orthorhombic to tetragonal PbO, (6) 189*a*.
Soeya, T., and Kimura, Y. Dc electroluminescence in thin films of zinc sulfide, (8) 252*h*.
Soffer, B. H. See Maiman, T. H.
Sofronova, A. V. See Pechkovskii, V. V.
Soga, N. See Chu, G. P. K.
Soga, N., and Schreiber, E. Porosity dependence of sound velocity and Poisson's ratio for polycrystalline MgO determined by resonant sphere method, (9) 285*d*.
Soga, N., and Tashiro, M. Effects of colloidal gold and K_2O on the formation of lithium metasilicate crystallites in photosensitive opal glass, (1) 5*h*.
Sokolov, A. A. See Matveev, M. A.; Sevast'yanov, E. F.
Sokolov, E. B. See Makarov, E. S.
Soldano, A. J. Electroluminescent translator utilizing thin film transistors, P (7) 208*e*.
Solid State Radiations, Inc. *Pn* junction device with interstitial impurity means to increase the reverse breakdown voltage, P (5) 142*b*.
Soliman, M. R. Thermodynamics of the various high-temperature reactions of kaolinite (abstract), B (6) 191*i*. See Salam, S. A.; Schieltz, N. C.
Soliman, M. T. M., and Yu, C. W. Flexural stress-strain relationship of concrete confined by rectangular transverse reinforcement, (8) 228*c*.
Soling, H. See Engberg, A.
Solite Corp. Apparatus and method for determining specific gravity, P (4) 103*f*. Uniform lightweight aggregate, P (1) 10*i*.
Solntsev, S. S., Pal'ti, B. A., Perov, B. V., and Gudimov, M. M. Apparatus for the mechanical testing of brittle materials at 20° to 1200°C, (10) 313*g*.
Solntseva, V. A. See Satalkin, A. V.
Soloducha, N. Method of producing titanium hydroxide and high grade pigments produced therefrom, P (5) 148*c*.
Solomchenko, N. Ya. See Evstatiev, D. G.
Solomir, J. G., Akeret, R., and Douady, P. Apparatus for the manufacture of dense sintered articles, P (1) 20*b*.
Solomon, R. See Sher, A.
Solonin, M. D. See Solonin, S. M.
Solonin, S. M., and Solonin, M. D. Dependence of compaction pressure on the ratio of the compacting surface area and the area of the friction surface between the powder and the die walls, (2) 54*b*.
Soloveichik, A. I. See Figner, A. I.
Solow, B. Metal film resistor for low range and linear temperature coefficient, P (3) 73*c*.
Solvay & Cie. Process for the manufacture of sodium carbonate [by use of CO_2], P (5) 149*a*.
Somerville, D. W. B., and Tervo, R. O. Process of forming silicon carbide diode by growing separate *p* and *n* layers together, P (7) 210*c*.
Somiya, S. See Saito, S.
Sommer, A. See Jennings, V. J.; Leibowitz, D.
Somnay, J. Y. See Madhavan, R. R.
Somody, A., and Paulik, I. Process of glass bubble formation and homogenization in glass melts, (4) 93*i*.
Somov, A. I., Svinarenko, A. P., and Tyutyunnik, A. G. Preparation of corundum monocrystals by electron-beam zone melting, (9) 272*f*.
Soncini, G., and Svelto, O. Single transverse mode pulsed ruby laser, (11) 356*d*.
Sonderegger, H. C. Piezoelectric building units, P (9) 274*d*.
Sonnenschein, G. Method and materials for obtaining low-resistance bonds to telluride thermoelectric bodies, P (10) 310*f*.
Sony Corp. Method of making color screen of a cathode ray tube, P (9) 265*d*. Method of making a semiconductor device, P (9) 274*b*. Photoconductive layer and method of making, P (10) 311*e*.
Sorensen, G. See Andersen, T.
Sorenson, T. I., and Shovic, F. C. Weighing device with electronic computer, P (2) 53*h*.
Sorocopud, L. See Gheorghiu, G.; Veiser, I.
Soroka, I., and Korin, U. Effect of mechanical activation on properties of mortars, (4) 92*c*.
Soroka, I., and Sereda, P. J. Interrelation of hardness, modulus of elasticity, and porosity in gypsum systems, (7) 194*h*.
Sorrell, C. A. Synthesis of rhenium ditelluride, (6) 189*j*.
Sosedko, T. A. See Frank-Kamenetskii, V. A.
Soudek, J. See Kaspar, J.
Souers, P. C. See McWhan, D. B.
Soukup, V. G. See Kozdemba, S. E.
Soulen, J. R. See McWhan, D. B.
Soulhier, R., and Hairion, J. P. Fission gas in uranium oxide, (6) 173*f*.
Soustruznik, G. See Keith, C. D.
South African Inventions Development Corp. Spectrochemical analysis apparatus supplying substantially the same energy to the gap for all waveforms, P (3) 76*g*.
Southern, T. M., and Wendlandt, W. W. High-temperature acid-base reactions (II) methylammonium chloride with certain metal oxides, (6) 186*c*.
Southern, T. M., Williams, J. R., and Wendlandt, W. W. High-temperature acid-base reactions (I) aliphatic amine onium salts with strontium and barium carbonates, (6) 186*b*.
Southington Mfg., Inc. Method and apparatus for accurately proportioning foundry sand ingredients, P (3) 69*a*.
Southwestern Engineering Co. Self-cleaning [dual] screen structure for vibratory separators, P (5) 144*e*.
Souza Santos, H. de. See Souza Santos, P. de.
Souza Santos, P. de., Brindley, G. W., and Souza Santos, H. de. Mineralogical studies of kaolinite-halloysite clays (III) a fibrous kaolin mineral from Piedade, Sao Paulo, Brazil; (IV) a platy mineral with structural swelling and shrinking characteristics, (5) 154*j*.
Sowers, G. F. See Mazanti, B. B.
Sowers, M. L. See Davis, M.
Sowman, H. G., and Johnson, J. R. Crystalline spherules, P (2) 47*a*.
Spain, R. G. See Schwartz, H. S.
Spaite, P. W., and Harrington, R. E. Endurance of fiber glass filter fabrics, (6) 167*d*.
Spaldon, E., and Tkacova, K. Activation of the quartz surface for the adsorption of anionic polyelectrolytes, (3) 78*b*.
Spangler, C. W., Lott, S. K., and Joncich, M. J. Reactions of graphite under exploding wire conditions, (2) 45*i*.
Spear, B. W. See Powell, D. E.
Spector, M. L., Suriani, E., and Stukenbroeker, G. L. Thermite process for the fixation of high level radioactive wastes, (4) 101*k*.
Spectra-Physics, Inc. Vacuum sealing of gas laser windows, P (9) 266*a*.
Speeckaert, P. Conversion of fluorides into chlorides, bromides, or iodides, (5) 150*i*.
Speedie, I. B. See Strauss, W.
Speidel, D. H., and Heald, E. F. Gaseous equilibria in portions of the system C–H–O–S, (5) 153*a*.
Speight, M. V. Discussion of "Theory of grain-boundary degeneration in materials which contain an inert gas," (10) 326*g*.
Speiser, R. See Adelsberg, L. M.
Spencer, E. G. See Holmes, C. H.; Lenzo, P. V.
Spencer, J. D. See Bluman, D. E.
Spencer-Strong, G. H. Preparing tomorrow's enamels, (9) 263*b*.
Sperr, F. See Kloepfer, H.
Sperry Rand Corp. Memory fabrication method, P (10) 310*c*. Method of improving the electrical characteristics of thin film metal-insulator [Al_2O_3]-metal structures, P (4) 100*b*. Precision electrical component adjustment method, P (9) 274*d*.
Speth, S. Blast nozzle for forming silicate fibers, P (2) 40*e*.
Spicer, W. E. See Dore, B. V.
Spiegel, H. Mastering future problems in the [German] building industry by rational methods and by the use of brick, (10) 301*f*.
Spiegler, A. Measurements on brick augers, (10) 301*g*.
Spielberg, N. Method of obtaining X-ray interference patterns, P (10) 316*b*.
Spielberger, R. K. See Delaney, R. A.
Spielmann, H. Ceramic artists and their work—Barbara Stehr, (1) 1*j*.
Spielmann, W. See Ebert, E.
Spiering, G. A., Revolinsky, E., and Beerntsen, D. J. Superconductor having variable transition temperature, P (4) 101*d*.
Spies, J. Measurement of thermal conductivity of solids, especially of ceramic nuclear fuels, at the highest temperatures, (1) 11*f*.
Spijkerman, J. J. See DeVoe, J. R.
Spindler, W. E. See Baldock, P. J.
Spinner, S., and Waxler, R. M. Relation between refractive index and density of glasses resulting from annealing compared with corresponding relation resulting from compression, (9) 264*f*.
Spinolo, G. See Podini, P.
Spitzer, D. P. Single phase ternary semiconducting compounds of silver or copper, thallium, and sulfur or selenium, P (11) 345*g*.
Splann, M. T. See Hansen, K. W.
Spore, W. D. Fast firing vs. conventional firing, B (3) 89*d*.
Sposito, G., and Babcock, K. L. Equilibrium theory of the kaolinite-water system at low moisture contents, with remarks on adsorption hysteresis, B (8) 259*b*.
Sprague Electric Co. Chopper amplifier having high breakdown voltage, P (5) 140*b*. Electrical resistor, P (5) 141*b*. Field effect transistor with an induced *p*-type channel by means of high work function metal or oxide, P (8) 244*c*. Induced region semiconductor device, P (4) 100*d*. Method of making a semiconductor by ionic bombardment, P (9) 274*c*. Method and reagent for surface polishing, P (8) 245*g*. Mica capacitor, P (4) 100*b*. Small junction area S-M-S transistor, P (10) 311*d*. S-M-S device with partial semiconducting layers, P (7) 210*a*.
Spratt, J. P. See Kane, W. M.
Spremulli, P. F. See Blanding, W. S.
Sprengers, J. W. C. See Zalm, P.
Spriggs, R. M. Microstructure and its influence on strength, B (4) 121*g*.
Spriggs, R. S. See Lood, D. E.
Springer, G. Correction for continuous fluorescence in electron probe microanalysis, (3) 75*e*.
Spritzer, C. See Gervais, H.
Sprung, S., and Seebach, H. M. von. Fluorine balance and fluorine emission from cement kilns, (8) 228*c*.
Spurgeon, W. M. See Scruggs, D. M.
Spyridelis, J., Delavignette, P., and Amelinckx, S. High resolution electron microscopic observations of the superstructure of tantalum pentoxide, (5) 153*i*.
Squire, G. L., and Ward, J. M. Glass fiber mats, P (3) 65*h*.
Squires, A. M. Air pollution—control of SO_2 from power stacks (I) removal of sulfur from fuels; (II) removal of SO_2 from stack gases by CaO or MgO, (4) 101*h*.
Srail, R. C. See Charvat, V. K.
Sreenivasan, V. R. See Brandt, W. W.
Srinivas, R. A. See Deckker, B. E. L.
Srinivasan, N. R. Outlook for Indian ceramics, (1) 34*c*.
Srinivasan, V., and Rangaswami, K. A. Economic aspects of processing and activation of clays occurring in and around Srinagar in Andhra Pradesh, India, (3) 77*h*.
Srivastava, K. P. See Prasad, S. N.; Ram, A.
Srivastava, M. C., and Banerji, S. K. Use of some substituted 8-hydroxyquinolines as colorimetric reagents in the detection of metal ions, (1) 23*b*.
Sroubek, Z., and Zdansky, K. Electron spin resonance of Cu^{2+} ion in $CdWO_4$, $ZnWO_4$, and $MgWO_4$ crystals, (7) 217*g*.
Stacey, D. S. High speed ultraviolet thin spot detector, P (1) 9*e*.
Stachiw, J. D. Design parameters for glass and ceramic underwater structures, (3) 63*e*. Hulls for deep submergence capsules, (3) 64*a*.
Stachiw, J. D., and Vonada, P. A. Mechanical coupling for glass and ceramic articles, P (1) 9*i*.
Staerk, K. Chemical deposition of metals in the production of metal film resistors, (10) 306*i*. See Eckert, O.; Schueller, K. H.
Stafford, F. E. See Verhaegen, G.
Stafford, F. E., and Borkowitz, J. Mass-spectrometric study of the reaction of water vapor with solid barium oxide, (5) 154*d*.
Stafford, W. L. See Pusch, W. G.
Staffordshire Potteries (Holdings), Ltd. Manufacture of pottery, P (2) 49*c*.
Stager, C. V. See Gornostansky, S. D.
Stagg, M. S. See Turnbull, J. A.
Staicopolus, D. N. Computation of surface tension and of contact angle by the sessile-drop method (III), (9) 275*j*.
Stakebake, J. L., and Dringham, M. R. Adsorption of oxygen on sintered plutonium dioxide, (5) 131*d*.
Stalego, C. J. Method and apparatus for forming and processing continuous filaments, P (3) 65*c*. Method of preparing metal oxide-metal sulfide plural coated siliceous fibers, P (6) 175*a*.
Staley, J. Method of reacting materials at high temperature, P (4) 97*a*.
Stambaugh, E. P. Pressure precipitation of oxides, (8) 247*b*.
Stamicarbon, N. V. Apparatus for the wet-screening of particles, P (3) 78*a*. Pretreatment of molecular sieves, P (10) 318*a*.
Stamires, D. N. See Singer, L. S.
Stammen, P. M. Ways of rationalizing brick packaging, (4) 95*h*.
Stamos, C., Reeves, P. C., and Wender, J. D., Jr. Method and apparatus for removing moisture from material, P (9) 278*b*.
Standard Oil Co. Hydrocarbon conversion process and catalyst, P (7) 214*d*. Hydrofining catalyst and process using it, P (10) 318*a*. Hydroforming process with mordenite, alumina, and platinum catalyst, P (7) 214*e*.
Standard Telephone & Cables, Ltd. Ceramic-metal seals, P (2) 58*c*.
Standley, C. L. See Jones, R. E.
Stanford, A. L., Jr. See Archer, J. R.; Arnold, R. T.
Stanley, I. W. Damping of sustained current oscillations in semiconducting cadmium sulfide at high fields, (4) 107*j*.
Stanley, R. A. See Conway, J. B.
Stanton, R. L. Composition of stratiform ores as evidence of depositional processes, (4) 104*g*.
Staples, J. L. Method for providing electrical contacts to a wafer of GaAs, P (9) 274*i*.
Stapleton, E. W., and McKeand, I. J. Resistor substrate having integral metal terminations, P (4) 101*c*.
Stapleton, H. J. See Brower, K. L.
Stapleton, R. E., and Towner, R. J. Hot-pressed alumina-niobium graded composites, (7) 202*a*.
Stark, G., and Otto, K. Method of producing thin layers of galvanomagnetic semiconductor material, particularly Hall generators of $A^{III}B^{V}$ compounds, P (2) 51*g*.
Stark, J. P. Invariant of diffusion in binary systems, (10) 322*a*.
Stark, R. A., and Barakat, D. Coated ceramic capacitor, P (2) 50*i*.
Starner, J. E. See Miller, A. H.
Staron, I. Making dense magnesite powder from rotary kiln dust, (9) 267*f*. Results and problems in the production of high-fired magnesite-chromite bricks, (7) 203*b*.
Stary, J., and Kratzer, K. Determination of extraction constants of metal diethyldithiocarbamates, (4) 104*h*.
Starzacher, A. Investigation of basic bricks by the torsional method, (8) 238*e*.
Stasovskaya, V. V. Measurement of the abrasive capacity of powders of carbides and borides of refractory metals, (3) 67*i*.
Statham, K. E. See Brixey, J. C., Jr.
Statni Vyzkumny ustav Sklarsky. Electric glass furnace, P (7) 198*j*.
Stearns, R. I., and Greene, P. E. Phase stability regions of boron phosphides in the Ni–B–P system, (4) 114*c*.

Steatit-Magnesia Akt.-Ges. Manufacture of ceramic insulating bodies, P (5) 137*a*.
Steatite & Porcelain Products, Ltd. High voltage insulators, P (1) 15*j*.
Stec, C. L., Sr. Method of making gas lubricated bearings, P (4) 95*d*.
Stecher, P., and Lux, B. Oxidation protection of molybdenum through a $MoSi_2$/SnAl protective layer, (10) 296*h*.
Stedman, C. E. Apparatus for producing acoustical [perlite] tile, P (3) 63*a*.
Stedman, D. F. Preparation of silicon chlorides, P (7) 215*a*.
Steeb, S., and Brucklacher, D. Structure of modified U_3O_8 (β-U_3O_8)—high temperature and sintering behavior, (4) 116*d*.
Steeb, S., and Knoll, W. Electrical resistance and thermoelectric power of uranium during oxidation at 10^{-3} torr and 500° to 800°C, (4) 109*e*.
Steeb, S., and Mitsch, P. Determination of the interstitial distribution of oxygen atoms by electron diffraction of single-crystalline uranium dioxide layers, (5) 150*h*. Electron diffraction investigation of the oxidation of UO_2 and the structure of a U_3O_{8-x} superstructure phase, (5) 151*h*.
Steel, G. C. Trends in iron and steel plant refractories, (5) 134*j*.
Steele, B. R., Hibbert, N. S., Rigby, F., Oldfield, B., and Martin, F. S. Preparation and characterization of ceramic grade BeO, (3) 67*e*.
Steele, B. R., and Rigby, F. Preparation of beryllium oxide of fine particle size through crystallization and calcination, P (1) 25*g*.
Steele, G. Refractory gunning in blast furnaces, (6) 173*e*.
Steele, R. Process of producing oxides of platinum and palladium, P (3) 78*c*.
Steelman, D. M. Electronic equipment for process control (I,II), (2) 52*j*.
Steere, R. C. See Hager, N. E., Jr.
Steeves, R. W. See Allen, L. R.; Baer, C. A.
Stefan, B. Rheological properties and forming process of fireclay bodies, (6) 173*g*.
Stegemann, E. Increasing the breaking strength of unfired ware [especially tile] by pressing from both sides, (10) 312*f*.
Stegman, R. L., and Peretti, E. A. Study of the indium telluride-indium antimonide quasi-binary phase diagram, (4) 117*a*.
Stehl, R. H., Margerum, D. W., and Latterell, J. J. Determination of trace metals using coordination chain reactions with masking agents and with automated rate measurement, (5) 145*c*.
Steigelman, H. A. See Carl, D. G.
Stein, A. J., Jr. Flux for fusing tin to gallium arsenide and method of making and using same, P (9) 273*a*.
Stein Atkinson Stordy, Ltd. Electrodes for electrically heated glass furnaces, P (1) 24*h*.
Stein, B. F. See Seitchik, J. A.
Stein, H. N. Influence of quartz on the hydration of $3CaO{\cdot}Al_2O_3$, B (7) 226*d*. Reaction of $3CaO{\cdot}Al_2O_3$ with water in the presence of $CaSO_4{\cdot}2H_2O$, (10) 295*j*.
Stein, H. N., and Stevels, J. M. Mechanism of hydration of $3CaO{\cdot}SiO_2$, (9) 262*d*.
Stein, John G., & Co., Ltd. See John G. Stein & Co., Ltd.
Stein, J. L. Refractory brick and method of making, P (7) 205*c*.
Stein, P. 30 years of strain gages, (6) 181*h*.
Steinberg, R. F. Photoemission from GaAs thin films, (8) 243*i*.
Steinberger, I. T. See Brafman, O.
Steindler, M. J. See Anastasia, L. J.
Steinecke, V. See Wartmann, R.
Steiner, E. F. See Paulsen, J. F.
Steinert Elektromagnetbau. Magnetic separating apparatus, P (11) 345*j*.
Steinfink, H. See Cox, W. L.; Norling, B. K.; Wang, R.
Steinike, U. Production of aluminum hydroxides and investigations of the X-ray and catalytic properties of the oxide, (5) 157*g*.
Steinitz, R. See O'Hara, M.
Steinmaier, W. Method of manufacturing semiconductor devices such as transistors and diodes and the devices made, P (9) 274*d*.
Steinmetz, H., and Brull, E. Thermoluminescence of fluorite, (9) 288*d*.
Steinmueller, R. E. See Dietert, H. W.
Steinnes, E. See Brunfelt, A. O.; Johansen, O.
Stejskal, E. O. See Boss, B. D.
Stelle, R. T. Process for making lightweight fired ceramic bodies, P (9) 266*f*.
Stellrecht, D. E., Farkas, M. S., and Moak, D. P. Compressive creep of uranium carbide, (9) 266*i*.
Stelmah, J. Method and apparatus for processing heat softenable material, P (11) 336*c*.
Stelmak, J. P. Hermetically sealed semiconductor device, P (8) 244*d*.
Stelt, E. O. W. van der. See Burggraaf, A. J.
Stelzer, E. L. See Tufte, O. N.
Stemple, N. R. See O'Kane, D. F.
Steneck, W. G. See Brockman, F. G.
Stenerson, R. N. Brazing preform, P (2) 40*f*.
Stenning, G. P. Cold cathode gas discharge tubes having an optically opaque masking plate, P (5) 140*i*.
Stepanek, R. W. Fine grind hammer mill with adjustable hammer rotor, P (7) 214*c*.
Stephan, K. See Kloepfer, H.
Stephanoff, N. N. Apparatus for pulverizing and drying solids, P (4) 101*j*.
Stephen, R. A., & Co., Ltd. Radioactive radiation dosimeter of the silver phosphate glass type, P (8) 246*d*.
Stephen, W. I. See Martin, J. M.
Stephens, J. D. See Adamson, D. L.
Stephenson, G. W. See Miles, G. D.
Stephenson, I. M., and White, J. Factors controlling microstructure and grain growth in two-phase (one solid + one liquid) and in three-phase (two solid + one liquid) systems, (5) 152*a*.
Steppat, C. H. M. Formation of metallic contacts, P (9) 273*a*.
Sterk, A. A. Proton-excited soft X-ray [chemical] analyzer having a rotatable target for selectively directing the X rays to different detectors, P (5) 147*b*.
Sterling, H. F. See Joyce, R. J.
Sterlyadkina, Z. K., Kryukova, O. N., and Mikheeva, V. I. Reaction of sodium borohydride with sulfur, (3) 85*i*.
Sterman, S. See Marsden, J. G.
Stern, K. H. Electrode potentials in fused systems (1X) liquid junction potentials in the AgCl–AgBr system, (5) 151*h*.
Stern, S. V. See McCarthy, J. W.
Sternberg, J. C. Fragmentation inlet for gas chromatography and method of loading a sample thereinto, P (1) 23*h*.
Sterne, J. H., III. See Floyd, J. R.
Sterne, J. H., III, and Stratton, C. L. Dry ball mill grinding of ceramic aluminas, (4) 101*h*.
Sternkueker, J. See Maurer, K.
Stett, M. A., and Fulrath, R. M. Chemical reaction in a hot-pressed Al_2O_3-glass composite, (1) 26*j*. Strengthening by chemical bonding in brittle matrix composite, (11) 332*f*.
Stevels, J. M. Permitted and forbidden structural units in vitreous systems, (11) 334*a*. Radiation induced color centers in vitreous systems, (11) 334*g*. See Beekenkamp, P.; Stein, H. N.
Stevens, J. P., & Co., Inc. Ion exchange of glass fibers, P (8) 235*c*. Treatment of fibrous glass, P (7) 199*b*.
Stevens, K. W. H. Chromous ions in magnesium oxide, (11) 350*g*.
Stevenson, C. L., and Emrich, H. W. Probability sizing of clay materials, (10) 301*h*.
Stewart, D. B., and Limbach, D. von. Thermal expansion of low and high albite, (6) 190*b*.
Stewart, D. F. See O'Donnell, T. A.
Stewart, D. R. Chemical strengthening of untouched glass rods, (7) 195*i*.
Stewart, G. H. (editor). Science of Ceramics (Vol. 3) Proceedings of the Third Conference of the British Ceramic Society and the Nederlandse Keramische Vereniging Held Under the Auspices of the European Ceramic Association at the University of Bristol, July 1965, B (7) 226*d*.
Stewart, H. B. See Goodjohn, A. J.
Stewart, J. A. Blues and greens over 50% of the color spectrum, (11) 332*e*.
Stewart, M. M. Coprecipitated silica-alumina catalyst process and composition, P (1) 25*i*.
Stewart, R. F. See Carter, C. J.
Stiegler, J. O. See DuBose, C. K. H.
Stilley, G. W., and Kelly, J. D. Glass gripping tongs, P (10) 300*a*.
Stillinger, D. W. See Sinclair, W. R.
Stirland, D. J. Structure of gold deposits on rock-salt substrates, (10) 308*f*.
Stirling, P. H. What's new in process instrumentation, (4) 101*i*.
Stirn, R. J., and Becker, W. M. Weak-field magnetoresistance in *n*-type aluminum antimonide, (8) 258*c*.
Stites, R. S. See Buddecke, C. L.
Stobbs, J. J. Oxidation mechanism of pure uranium in carbon dioxide between 350° and 650°C, (3) 84*j*.
Stoch, L. Effect of cationic field strengths on the liquidus of oxide systems, (9) 281*f*.
Stocker, T. L. See Birnbaum, M.
Stoddard, S. D. See Gloyna, E. F.
Stoecker & Kunz G.m.b.H. Discharge brick for casting ladles, intermediate containers, and the like, P (7) 204*a*.
Stoeckmann, H. See Decker, H.
Stoerr, M. Bonding of the iron in fine-ceramic kaolins, (1) 15*b*.
Stoever, U. Enamel—ornaments for [German] town council chains of office, (7) 194*a*.
Stojadinovic, S. See Delic, D.
Stojic, M., and Slavic, I. Diffusion of phosphorus in silicon and the making of *pn* junction semiconductor detectors, (7) 216*f*.
Stokes, R. J. Basic mechanisms of strain-hardening in ceramics, B (4) 121*f*.
Stoll, E. See Andresen, A. F.
Stoll, H. Conversion of the physical values in ceramic engineering to the International System, (10) 327*j*.
Stoll, R. See Forman, P. F.
Stoll, W. See Muehling, G.
Stoller, A. I. Method of electrically isolating semiconducting circuit components, P (8) 245*c*.
Stolyarov, O. G. See Mil'vidskii, M. G.
Stone, A. J. See Burns, R. G.
Stone, H. H. See Romberger, K. A.
Stone, S. Lens-grinding wheel, P (7) 193*f*.
Stonehart, P., Koren, J. G., and Brinen, J. S. Quantitative electrochemical formation of phosphotungstate heteropolyanion blues, (5) 157*a*.
Stook, P. W. See Bassett, W. A.
Stookey, S. D. See Araujo, R. J.
Stoops, R. F. See Manning, C. R., Jr.
Storms, E. K. Refractory Carbides, B (7) 225*i*. See Kempter, C. P.
Storms, E. K., and Kempter, C. P. Thermal expansion of some vanadium carbides, (5) 134*g*.
Stosick, A. J. See Rudy, E.
Stout, J. W. See Russel, P. G.
Stoute, R. L. See MacEwan, J. R.; May, J. E.
Stovbur, A. V. See Tsigler, V. D.
Stover, E. R. Heat treating pyrolytic graphite and boron nitride bodies with simultaneous application of multiaxial tension, P (2) 47*a*.
Stover, W. A. See Dwyer, F. G.; Mitchell, J. G.
Strack, H. Electroluminescence of iron-sulfur diffused GaAs junctions, (4) 109*h*.
Stradley, N. H. Acid-resistant enamels, P (8) 229*h*.
Stradtmann, J. See Obst, K. H.
Strafford, K. N. See Menzies, I. A.
Strain, F. See Richardson, K. W.
Strasman, V. See Petri, L.
Strassen, H. zur. See Dosch, W.
Strategic Materials Corp. Process for selectively carbiding titanium, iron, and vanadium values, P (9) 270*d*.
Stratton, C. L. See Sterne, J. H., III.
Stratum, A. J. A. van. See Zalm, P.
Straughan, J. J. See Ore, E. L.
Straumanis, M. E., Faunce, C. A., and James, W. J. Defect structure and bonding of zirconium nitride containing excess nitrogen, (6) 184*j*.
Strausbaugh, G. E. Hinged orifice ring holder for glass feeders, P (10) 300*c*.
Strauss, A. J. Retrograde solubility of lead in *n*-type PbS, (6) 188*a*.
Strauss, E. L. Resin impregnated ceramic heat shield and method of making, P (11) 341*b*. See Kramer, I. R.
Strauss, G. H. Nuclear magnetic resonance determination of some microscopic parameters of $LiAl_5O_8$, (5) 156*a*.
Strauss, H. L., Jr. Method of bonding diamond and metal, P (9) 261*f*.
Strauss, K. Old Bunzlau stoneware, (1) 2*a*.
Strauss, W. See Angell, C. A.
Strauss, W., and Speedie, I. B. Formation of acid smuts in oil-fired kilns and boilers, (8) 249*f*.
Stream, R. M. See Langlois, R. E.
Street, N. Axial ratio of clays, (4) 106*e*.
Streib, W. C., and Shuih, Chung-Hsiung. Phosphoric acid bonded asbestos fiber sheets and method of manufacture, P (8) 241*e*.
Streib, W. E. See Merritt, L. L., Jr.
Strekalovskii, V. N. See Beketov, A. R.
Strelkov, P. G., Shpunt, A. A., and Nabutovskaya, O. A. Use of NaCl crystals as a standard measure of microhardness, (10) 316*d*.
Strelov, K. K., and Lazarev, M. F. Apparatus for determining the maximum size of capillaries in refractories, (10) 313*d*.
Strelow, F. W. E., and Zyl, C. R. van. Separation of uranium from other elements by ion exchange chromatography, (2) 55*c*.
Strelow, F. W. E., Zyl, C. R. van, and Nolte, C. R. Separation of alkaline earth elements by cation-exchange chromatography in ammonium malonate media, (4) 103*f*.
Streydio, J. M. See Michenaud, J. P.
Strickland, R. D. Electrophoresis, (10) 314*a*.
Strickland-Constable, R. F. See Mason, R. E. A.
Strieter, F. J. Method of forming small geometry diffused junction semiconductor devices, P (9) 273*g*.
Strimer, P. See Plendl, J. N.
Strimple, J. H. Titanium dioxide—type determines results, (11) 349*d*.
Stringer, J. Effect of nitrogen on the oxidation of tantalum at high temperatures, (4) 108*d*. See McLintock, C. H.
Strolk, E. R. Thermocouple with cast iron contacting junction, P (9) 277*h*.
Strong, E. R., Jr. See Bertolacini, R. J.
Strong, H. M. Catalytic effects in the transformation of graphite to diamond, (5) 149*j*. Graphite–catalyst charge element for the preparation of diamond, P (1) 1*h*.
Strong, H. M., and Hanneman, R. E. Crystallization of graphite and diamond, (11) 351*f*.
Strong, K. A. See Brugger, R. M.
Stroud, J. S. Color-center kinetics in cerium containing glass, (5) 126*h*.
Strugach, L. S. See Matveev, M. A.
Struk, L. I. Process of compaction of molybdenum disilicide, (11) 338*e*. Study of the densification of refractory compound powders by the electrical conductivity method, (8) 240*a*.
Stuart, M. C. See Gross, P.
Stuart, R. A., and Whitworth, R. W. Potential differences produced in sodium chloride crystals by plastic deformation at 4.2°K, (4) 114*i*.
Stuart, W. I. See Adams, R. B.; Price, G. H.
Stuart, W. I., and Price, G. H. High temperature reaction between BeO and water vapor, (4) 96*e*.
Stuart, W. R. Metal-to-ceramic seal for high voltage electron tubes and methods of fabrication, P (11) 344*b*. Thermal connector for electron tubes and the like, P (4) 97*i*.
Stuber, C. D. Alumina-boron fiber composite material, P (8) 240*j*.
Stubican, V. S. Exsolution phenomena in some polycrystalline oxide systems, B (7) 220*e*. See Greskovich, C.; Tressler, R. E.
Stubican, V. S., and Schultz, A. H. Spinodal decomposition in the system TiO_2–SnO_2, (6) 189*b*.
Studer, H. P. Mineral analysis of natural zeolite deposits (abstract), B (9) 289*a*.
Stukenbroeker, G. L. See Spector, M. L.
Sturge, M. D. Effect of stress on the level splittings of ruby—origin of the ground-state splitting, (5) 137*i*. See Scott, W. C.
Sturgill, D. T. See Harget, P. J.
Sturhahn, H. H. See Hennicke, H. W.
Sturman, V. K. See Budnikov, P. P.
Su, G. J. See Borrelli, N. F.
Suarez, H. E. See Eisner, R. L.
Subbarao, E. C. See Chandrashekhar, G. V.

Subramanium, R. B., and Sundaram, D. V. Pilot-plant production of nuclear grade zirconium sponge from Indian zircon, (1) 11*j*.

Subramanya, B. S., Riddel, J. W., and Schwartzwalder, K. Method of manufacturing a spark gap semiconductor, P (7) 209*a*.

Subramanyam, C. G. See Bhatt, K. V.

Sucov, E. W. Evaluation of specially grown ruby laser rods, (5) 138*h*.

Sudakas, L. G. See Golynko-Vol'fson, S. L.

Suddarth, S. K. See Jayne, B. A.

Suemune, Y. Thermal conductivity of KH_2PO_4-type single crystals, (7) 222*d*. Thermal conductivity of manganese ferrite single crystals at low temperatures, (5) 159*b*.

Suesser, V. See Vach, J.

Sugano, S. See Shinada, M.

Sugano, T. See Nakashima, H.

Sugawara, F., Iida, S., Shono, Y., and Akimoto, S. New magnetic perovskites, $BiMnO_3$ and $BiCrO_3$, (3) 83*d*.

Sugden, T. M., and Schofield, K. Heats of dissociation of gaseous alkali earth dihydroxides, (3) 81*j*.

Suggitt, R. M. See Webb, A. N.

Sugihara, K. See Ono, S.; Shigata, H.

Sugimoto, H. See Yabumoto, T.

Sugimoto, M. Crystal growth of manganese zinc ferrite, (8) 252*c*.

Sugimura, Y. See Kuno, H.

Sugita, K. See Kato, K.; Ohba, H.

Sugiura, M. See Ida, I.

Sugiyama, T. See Asada, C.

Suito, E. See Hasegawa, H.

Suito, E., Shiojiri, M., and Morikawa, H. Electron microscopic observation on thermal oxidation of vacuum-deposited aluminum films, (11) 352*j*.

Sulimenko, L. M. See Butt, Yu. M.

Sulimenko, L. M., Pozhilov, A. S., Avdeev, Yu. G., and Barbashov, G. K. Increasing the strength of raw material granules, (3) 62*a*.

Sullivan, R. A. L. See Pamplin, B. R.

Sullivan, R. E. See Kiser, R. W.

Sullivan, S. J., and Albright, M. W. Noble metal coated ceramic substrate for glass seals and electronic connector elements, P (10) 311*d*.

Sulzer Brothers, Ltd. Method of making a casting mold, P (2) 47*k*. Sealing compound for high temperature use, P (11) 341*c*.

Sumita, K. See Takahasi, A.

Sumitomo Chemical Co., Ltd. Novel catalyst composition, P (6) 183*c*.

Sumitomo Electric Industries, Ltd. Method of manufacturing oxide nuclear fuel containing boride, P (6) 174*j*.

Summergrad, R. N. See Khan, I. H.

Sumski, S. Temperature gradient zone melting and growing of semiconductor material, P (4) 101*c*.

Sun, Kuan-han, Chen-Tsai, Ching-Tang, and Shan, Y. Radioactive fluophosphate glass composition, P (6) 171*e*.

Sun, Shiou-Chuan, Chao, T., Hirsh, W., and Freed, B. A. Extraction of alumina and the removal of iron from Pennsylvania aluminous clays, (5) 147*j*.

Sun Enterprises, Ltd. Apparatus for assembling glass sheets during manufacture of double glazed windows, P (10) 299*i*.

Sun Oil Co. Automatic control system for an X-ray diffraction apparatus, P (2) 55*c*.

Sunbeam Corp. Lehr with transverse temperature control, P (7) 198*i*.

Sundaram, C. V., and Paul, C. M. Ultrapurification of group IV*a* metals, (8) 248*j*.

Sundaram, D. V. See Subramanium, R. B.

Sunderland, P. W., and Chaklader, A. C. D. Deformation during dehydroxylation of hydroxides, (4) 107*a*.

Sunderman, D. N. See Elleman, T. S.

Sundheim, B. R., and Kellner, J. D. Thermoelectric properties of the molten silver nitrate-sodium nitrate system, (11) 357*g*.

Sundquist, B. E., and Oriani, R. A. Thermodynamics of a miscibility gap system and a test of nucleation theory, (7) 222*g*.

Sundstrom, R. N., and Wilder, A. H. Apparatus for and method of shaping the open end of glass tubes between cooperating rollers, P (4) 94*d*.

Super-Cut, Inc. Method of making a peripheral diamond grinding wheel, P (5) 123*j*. Peripheral diamond grinding wheel, P (8) 227*h*.

Suplin, Yu. G. See Karyuk, G. G.

Surek, T. See Cox, C. D.

Suriani, E. See Spector, M. L.

Surls, J. P. See Olson, R. S.

Susin, P. See Pistilli, A.

Suski, L. Galvanostatic cathodic reduction of fused sodium chloride on graphite, Ni, Fe, or liquid aluminum [at 800° to 950°C], (7) 217*g*.

Suter, H. Applying melting point determinations, (1) 20*j*.

Sutherland, G. See Bergstrom, J. W.

Sutton, J. S. Glass knife, P (6) 170*c*.

Sutton, W. H., and Chorne, J. Factors affecting the tensile strength of metals reinforced with strong fibers, B (4) 121*i*.

Suwa, Y., Naka, S., and Noda, T. Preparation and properties of yttrium magnesium silicate with apatite structure, (7) 220*d*.

Suydam, W. H. Method of lining a rotary kiln, P (4) 97*h*.

Suzuki, A. See Kuno, H.

Suzuki, A., and Tanaka, T. Crushing efficiency in relation to some operational variables and material constants, (7) 211*e*.

Suzuki, C. See Tanaka, T.

Suzuki, H. Electron affinity of semiconducting CdSe, (11) 352*j*.

Suzuki, H., Hayashi, K., and Kawakatsu, I. Properties of WC-TiC-10%Co (10% β-Co) two phase alloys in relation to the carbon content of the alloys, (8) 256*i*.

Suzuki, H., and Ishizaki, K. Method for electroslag welding, P (2) 38*d*.

Suzuki, H., Yamamoto, T., and Hayashi, K. Magnetic saturation of cemented carbides, (9) 284*g*.

Suzuki, H., Yamamoto, T., and Kawakatsu, I. Effects of carbon content on the properties of WC-10%Fe and WC-10%(Fe-Co) cemented carbides, (9) 281*c*. Relations between some properties of WC-5%TaC-10%Co alloys and the methods of adding tantalum carbide, (8) 256*c*.

Suzuki, K. Corrosion tests by the crucible method and observations on heating conditions, (10) 302*g*. See Katsuraki, H.

Suzuki, K., Hiraiwa, O., and Suzuki, T. Changes in the properties of magnesia brick used in the floor of an open-hearth furnace idle for a long period, (9) 266*h*.

Suzuki, M. See Ida, I.

Suzuki, M., and Tauchi, S. Method for manufacturing at least one electrically isolated region of a semiconductive material, P (6) 178*f*.

Suzuki, S. See Shiraki, Y.

Suzuki, T. See Suzuki, K.

Suzuki, T., Kawai, N., Ino, S., Toyama, S., Kodama, K., and Otake, T. Process development of synthetic lightweight aggregate from fly ash with pulp waste liquor, (6) 165*j*.

Svedberg, P. G. J. Semiconductor devices, P (10) 311*c*.

Svedja, H. Statistical study of the influence of sulfate, oxalate, and perchlorate ions on sodium and potassium determination in important materials in silicate technology, (7) 212*j*.

Svelto, O. See Soncini, G.

Svet, D. Y. Thermal Radiation—Metals, Semiconductors, Ceramics, Partly Transparent Bodies, and Films, B (4) 121*i*.

Svet, V. I., and Lokshina, S. E. Analysis of agglomerates with the FES-1 photoelectric stylometer, (11) 346*b*.

Svinarenko, A. P. See Somov, A. I.

Sviridov, V. M. See Yamshchikov, V. S.

Swain, A. B., and Keshari, H. R. Glass composition and method, P (4) 94*j*.

Swallow, D. M. Self-cleaning [dual] screen structure for vibratory separators, P (5) 144*e*.

Swann, P. C. Connoisseurship and His Majesty King Gustav VI Adolph of Sweden, (4) 91*g*.

Swanson, A. B., and Anderson, J. S. Indium tungsten bronze, (7) 218*i*.

Swanson, H. E., McMurdie, H. F., Morris, M. C., and Evans, E. H. Standard X-ray diffraction powder patterns, (9) 277*d*.

Swanson, L. W. See Charbonnier, F. M.

Swanson, R. E. Small spherical nuclear fuel particles and processes of making same, P (3) 69*f*.

Swaroop, B., and Wagner, J. B., Jr. Vacancy concentrations of wustite (FeO_x) near the p to n transition, (6) 190*c*.

Swart, R. See Weller, B. L.

Swaving, E. C. J., and Guilonard, P. J. G. Metallization of different aluminas by the molybdenum-manganese process, B (4) 122*e*.

Swedlund, L. E. High contrast fluorescent screen having spaced phosphor layer and method of manufacture, P (4) 100*c*.

Sweet, R. C. See Bronnes, R. L.

Swenson, E. G. See Sereda, P. J.

Swenson, E. G., and Gillott, J. E. Alkali reactivity of dolomitic limestone aggregate, (4) 91*j*.

Swett, K. Authigenic feldspars and cherts resulting from dolomitization of illitic limestones—a hypothesis, (9) 279*i*.

Swiggard, E. M., and Shenker, H. Preparation of doped germanium for far infrared detectors, (7) 207*g*.

Swindeman, R. W. Thermal shock tests in BeO, (4) 96*i*.

Swiss Aluminum, Ltd. Apparatus for the manufacture of dense sintered articles, P (1) 20*b*.

Swoboda, A. R. See Thomas, G. W.

Swoboda, A. R., and Kunze, G. W. Infrared study of pyridine adsorbed on montmorillonite surfaces, B (7) 224*j*. Infrared techniques for studying the adsorption of volatile vapors by clays, (6) 180*g*.

Sychev, M. M., Zozulya, P. V., Shtefan, M., and Ivantsova, S. M. Effect of impurities of raw materials and alloying additives on viscosity of liquid phase of portland cement clinker, (3) 62*e*.

Syeles, A. M. See Wang, F. E.

Sylvania Electric Products, Inc. Cathode ray tube fabrication, P (3) 72*a*. Composite protective coat for thin film devices, P (5) 140*j*. Conductive media for electroluminescent devices, and electroluminescent device, P (7) 208*i*. Conveying and orienting apparatus, P (7) 208*a*. Electric discharge device having polycrystalline alumina end caps, P (4) 99*h*. Electroluminescent lamp having a high resistivity electrode, P (2) 50*j*. Europium and bismuth activated yttrium vanadate phosphor, P (4) 99*j*. Europium and calcium or manganese activated yttrium vanadate phosphor, P (4) 99*j*. Fluorescent lamp with a reflective coating containing TiO_2 and Sb or its oxide, P (7) 198*d*. Fluorescent lamp using an indium-mercury amalgam band for pressure control, P (10) 309*f*. High energy tubular incandescent lamp having heat dissipative sleeves, P (3) 72*i*. High pressure electric discharge device containing a fill of mercury, halogen, and an alkali metal and barrier refractory oxide layers, P (2) 51*d*. In a high pressure lamp, protective metal oxide layers on the inner wall of the quartz envelope, P (7) 209*b*. Incandescent lamp, P (3) 72*j*, 73*a*, Lamps having a molybdenum phosphate phosphor, P (4) 100*f*. Method of processing halophosphate phosphors, P (2) 51*c*. Method of producing semiconductor devices, P (9) 274*c*. Process for the fabrication of improved fluorescent lamps, P (2) 52*e*. Process of preparing calcium fluoride, P (5) 149*b*. Process for purifying molybdenum trioxide, P (10) 318*c*. Quartz-halogen incandescent lamp having a filament and a support made of rhenium-tungsten alloy, P (10) 311*a*. Single ended quartz type incandescent lamp, P (2) 42*d*.

Syono, Y., and Akimoto, S. High pressure synthesis of fluorite-type PbO_2, (7) 218*a*.

Syritskaya, Z. M., and Shapovalova, N. F. Thermal expansion and softening point of glasses in the system Al_2O_3–TiO_2–P_2O_5, (10) 299*f*.

Szabo, A. See Jitea, B.; Mircea, S.; Petri, L.; Veiser, I.

Szabo, J. M., Jr. Fabrication of beam lead semiconductor devices, P (9) 272*i*.

Szaj, A. P. See Gasparac, R. J.

Szedon, J. R. See Chu, T. L.

Szego, L., and Calvert, J. M. Naphthenic acid extraction of calcium for determination by atomic absorption spectrophotometry, (10) 315*c*.

Szepesi, K. See Kilian, J.

Szklarz, E. J. See Giordi, A. L.

Szliva, J. Homogenization of raw meal in the cement industry, (3) 62*j*.

Szwaja, A. Spectrographic determination of zirconium in ceramic raw material and bodies, (2) 55*e*.

Szwarc, R., and Latta, R. E. Vapor pressure of hypostoichiometric uranias as a function of composition, (6) 190*c*.

Szymborski, W. See Bialek, F.

Tabeling, R. W. See Johnson, D. R.

Taeler, D. H. Blending 2 materials yields 19 shades, (7) 199*g*. Bonded abrasive media for mass finishing, (11) 331*f*. Computer-aided bottle-glass production, (7) 195*i*. Die design and material control, (2) 52*j*. Expanded markets and increased profits, (2) 42*h*. Float-glass production is computerized, (10) 297*e*. Future of hard ferrites, (11) 342*g*. Glass-ceramics capture $2 million telescope-mirror contract, (11) 334*b*. How to make a "power tower," (10) 305*j*. 158-inch fused quartz mirror blank, (6) 168*f*. Progress in electric glass melting, (2) 40*a*. Sayre Electronics, (10) 306*f*. Tar-bonded, tar-impregnated basics, (11) 339*d*. See Bergstrom, J. W.; Schulze, H. C.; Tatnall, R. F.

Taeuber, K. A. G., and Schmidt, E. R. Surface coloring of brick and other structural clay products, (10) 302*a*.

Tagai, H. See Zisner, T.

Tagai, H., Iseki, T., Fujimura, Y., Matsumoto, Y., and Nakajima, M. Diffusion constant of Fe ion in magnesia, (9) 267*d*.

Tagai, H., and Zisner, T. High-temperature creep of polycrystalline magnesia (1) effect of simultaneous grain growth, (7) 218*d*.

Tai, S. See Imaoka, M.

Tainsh, R. J. See Pryor, A. W.

Tajima, M. See Harazono, S.

Takada, I. See Nakaji, S.

Takada, T. See Bando, Y.; Hamamura, A.

Takagi, H. See Hayashi, H.

Takagi, H., and Hayashi, H. Chemical purification of Izumiyama pottery stone and its effects, (9) 278*f*.

Takagi, T. See Nomura, M.; Seki, T.

Takahashi, H., and Nishimura, Y. Formation of zeolite type A from halloysite and allophane (extended abstract), B (9) 289*a*.

Takahashi, K. See Okazaki, K.

Takahashi, M. See Akashi, T.

Takahashi, M., and Shikama, S. Life characteristics of reliable germanium alloy transistors baked in oxygen, (5) 138*h*.

Takahashi, M., Shikama, S., and Yamashita, N. Reliable germanium alloy transistors baked in oxygen, (5) 139*e*.

Takahashi, M., Tsubouchi, N., Ohno, T., and Yamauchi, F. Method of piezoelectrically activating ferroelectric materials, P (4) 100*f*.

Takahashi, R., Oshima, M., and Kobayashi, A. Photoconductivity of ZnTe crystals, (5) 156*j*.

Takahashi, T. See Bassett, W. A.; Nakada, R.

Takahashi, T., Ebina, A., and Kamiyama, A. Vapor reaction growth of ZnO single crystal, (5) 159*h*.

Takahasi, A., and Sumita, K. Pulse propagation of thermal neutrons in graphite, (9) 268*d*.

Takaki, H. See Bando, Y.; Shinjo, T.

Takamizawa, H. See Akashi, T.

Takamori, T., and Iriyama, K. Thermal shrinkage of microporous glasses, (1) 8*c*.

Takashima, H., and Kato, E. Relation between the content of ferrous oxide and the shade of iron glazes, (9) 271*d*.

Takayanagi, H. See Ota, E.

Takayanagi, S. See Yoshioka, S.

Takayanagi, T. See Kosaka, M.

Takayanagi, T., Kosaka, M., Kato, M., and Minowa, S. Corrosion of Al_2O_3–SiO_2 system crucible by molten aluminum, (11) 350*j*.

Takeda, S. See Hirose, Y.

Takeda, T., and Watanabe, A. Electron spin resonance of Gd^{3+} in reduced $BaTiO_3$, (4) 109*c*. Electron spin resonances in reduced $BaTiO_3$, (4) 109*c*.

Takeda, T., Watanabe, A., and Sasaki, H. Resistivity of Gd^{3+} doped $BaTiO_3$ crystals grown in molten KF, (10) 325*c*.
Takei, H., and Chiba, S. Vacancy ordering in epitaxially grown single crystals of γ-Fe_2O_3, (10) 327*c*.
Takei, H., and Koide, S. Growth and electrical properties of vanadium oxide single crystals grown by oxychloride decomposition, (7) 217*h*.
Takei, T. See Saito, S.; Sasaki, K.; Ueoka, H.; Yoshida, T.
Takematsu, M. Slow viscous flow past a cavity, (10) 325*i*.
Takemoto, T., Ishihara, T., and Akiyama, K. Investigation of Si–Ta_2O_5 system prepared by reactive sputtering, (9) 283*i*.
Takenaka, O. See Naka, S.
Takeuchi, Y. Structures of brittle micas, B (7) 224*j*.
Taki, H. See Nitta, T.
Taksis, G. A. See Bessonov, A. F.
Talas, J. X-ray diffraction goniometer with specific drive mechanism for the specimen holder and detector, P (4) 103*j*.
Tallan, N. M. See Ruh, R.
Talley, R. W. See Fishwick, J. H.
Talley, W. J., Jr. Role of marketing in setting product specifications, (7) 223*d*.
Talrose, V. L. See Kondratiev, V. N.
Tamamoto, S. Measures for lengthening the life of a 160-ton converter ladle lining and test results, (7) 202*g*.
Tamas, F. Amorphous phase in the system CaO–Al_2O_3–$CaCl_2$–H_2O—preliminary report, (7) 215*h*. Equilibrium index—its principle and applications, B (7) 226*d*. See Kalmar, I.
Tambussi, W. C. Molding composition and method of use, P (4) 92*f*.
Tamura, M. Method of making color screen of a cathode ray tube, P (9) 265*d*.
Tamura, M., and Nomura, M. Observation of chemical-vapor-deposited silicon on sapphire by transmission electron microscopy, (5) 156*c*.
Tamura, T. See Maeda, S.; Slagle, K. A.
Tanaka, A. See Yamamoto, R.
Tanaka, H. See Ogura, T.
Tanaka, H., Murakami, K., and Komatsu, T. Effects of sucrose, *d*-glucose, and dextrin on the hydration of portland cement and its clinker minerals, (11) 331*j*.
Tanaka, H., Murakami, K., and Sato, M. Hydration of the calcium aluminoferrite phase and its glass in portland cement clinkers, (8) 228*c*.
Tanaka, M. See Harada, J.; Tsubaki, T.
Tanaka, M., Tokoro, T., and Aiyama, Y. Jahn-Teller effects on Moessbauer spectra of ^{57}Fe in $FeCr_2O_4$ and FeV_2O_4, (4) 112*h*.
Tanaka, S. See Asai, S.; Miura, Y.
Tanaka, T. See Nakajima, Y.; Shinohara, K.; Suzuki, A.
Tanaka, T., Suzuki, C., Fukui, T., and Futami, K. Laser operation in a wedge shaped ruby, (4) 112*h*.
Tanaka, Y., Ikeda, T., and Toyoda, H. Piezoelectric ceramics of lead zirconate–titanate systems, (5) 139*h*.
Tananaev, I. V., Belyakov, I. M., Dzhurinskii, B. F., and Berul, S. I. Reaction of neodymium and cerium oxides with sodium borate melts, (6) 188*b*.
Taneja, C. A. See Chopra, S. K.
Tanemura, F., Tsukino, M., and Adachi, S. Effect of alkali on refractories in cement kilns, (10) 302*g*.
Tanida, M. See Hibino, T.
Taniguchi, T. Refractory specialties bonded by aluminum phosphate, (8) 239*j*. See Shibazaki, K.
Tanimoto, S. See Harazono, S.
Tannenberger, H., Schachner, H., and Simm, W. Fuel cell having solid stabilized zirconium oxide electrolyte, P (2) 51*b*.
Tannhauser, D. S. See Bransky, I.; Fisher, B.; Hed, A. Z.
Tansal, S. See Brennemann, A. E.
Tantilla, W. H. See Veigele, W. J.
Tanzman, D. P. See Wishnie, F. T.
Tappin, G. See Davidge, R. W.
Tarasewich, Yu. I., Radul, N. M., and Ovcharenko, F. D. Investigation of *n*-propyl alcohol adsorption on montmorillonite by infrared spectroscopy, (11) 353*f*.
Tarasov, L. P. Theory of grinding (I,II), (2) 35*h*.
Tarasov, V. V. See Turdakin, V. A.
Tarby, S. K., and Philbrook, W. O. Rate and mechanism of the reduction of FeO and MnO from silicate and aluminate slags by carbon-saturated iron, (2) 45*g*.
Tare, V. B. See Chandra, P.
Tarkan, S. E. See Ellis, J. L.
Tarkan, S. E., and Ellis, J. L. Heat-treatable nickel-containing refractory carbide tool steel, P (5) 135*d*.
Tarneja, K. S. See Amsterdam, M. F.
Tarrow, V. See Saermark, K.
Tartakovskii, I. P. See Ivashchenko, V. V.
Tarte, P. Isomorphism and polymorphism of the compounds Li_3PO_4, Li_3AsO_4, and Li_3VO_4, (5) 154*b*.
Tarui, Y., Komiya, Y., Teshima, H., and Nagai, K. Surface states of silicon-silicon dioxide interface grown by vapor deposition, (8) 257*a*.
Tarumi, S. See Eguchi, K.
Tarver, D. A. Tungsten carbide coated article of manufacture, P (9) 263*c*. See Darnell, J. R.
Tasaka, K. See Eguchi, K.
Tashima, N. See Ueoka, H.
Tashiro, M. See Kokubo, T.; Maki, T.; Soga, N.
Tate, M. C., and Bradley, C. D. Batch weigher with respective dials for successive loads and total weight, P (3) 75*a*.
Tatematsu, R. See Ozaki, S.
Tateno, J. Analysis of DTA curve using transfer function, (3) 78*h*.
Tatevosyan, K. M. See Melik-Akhnazaryan, A. F.
Tatnall, F. G. Evaluation of the Universal Testing Machine, (3) 75*i*.
Tatnall, R. F. Automatic control for periodic kilns from 100° to 2000°F, (1) 10*c*. Beckman Instruments' thick-film capability, (11) 341*j*. Ceramic engineers salary survey, (7) 223*d*. Computer controlled batching, (2) 38*g*. Economic life of forklift trucks, (3) 74*i*. Laboratory designed for efficiency, flexibility, (3) 66*h*. Masters 4000 item inventory, (2) 42*j*. One-high brick plant produces profits, (10) 301*g*. Thermistors and varistors, (3) 72*f*. See Brown, R. W.
Tatnall, R. F., and Taeler, D. H. Can ceramic technicians help solve the engineer shortage? (4) 119*f*.
Tauber, A. See AuCoin, T. R.
Taubmann, H. Burners for liquid, gaseous, and pulverulent fuels, P (5) 147*h*.
Taubmann, H., and Boderke, H. Apparatus for operating a burner fired shaft furnace, P (6) 182*b*.
Tauc, J. Optical properties and electronic structure of amorphous Ge and Si, (5) 156*c*.
Tauchi, S. See Nomura, M.; Seki, T.; Suzuki, M.
Taukchi, V. N. See Balyuk, S. T.
Tauke, J., Litovitz, T. A., and Macedo, P. B. Viscous relaxation and non-Arrhenius behavior in B_2O_3, (4) 93*j*.
Taulli, T. A. Process of preparing an organosilica aerogel, P (1) 25*i*.
Tavendale, A. J. Method of making lithium-drift diodes by diffusion, P (6) 178*d*.
Taxer, K. See Buerger, M. J.
Taylor, A. M. See Flanigen, E. M.; Roy, R.
Taylor, A. R., Jr. See Gardner, T. E.
Taylor, A. W. B. See Hyland, G. J.
Taylor, E. D. See Hecht, H. G.
Taylor, G. W. Electrical properties of niobium-doped ferroelectric Pb(Zr,Sn,Ti)O_3 ceramics, (5) 138*c*. See Wentworth, C.
Taylor, H. F. W. Crystallographic aspects of high temperature transformations of clay minerals (extended abstract), B (6) 191*c*.
Taylor, H. L. Role of inspection and quality control in the enamel shop, (9) 263*c*.
Taylor, J. A. G. See Hambleton, F. H.
Taylor, J. B. See Sato, M.
Taylor, K. Method of preparing calcium carbonate, P (1) 25*d*.
Taylor, L. O. See Yong, R.
Taylor, M. J. Gelation of aqueous bentonite dispersions by organic ammonium ions, (10) 321*d*.
Taylor, M. L. See Amano, C. K.
Taylor, R. C., and Conn, J. B. Metallic selenides and tellurides and process for making same, P (9) 273*g*.
Taylor, R. C., and Title, R. C. EPR study of the effect of substrate orientation on vapor-grown GaP, (11) 352*c*.
Taylor, R. K. Methylene blue adsorption by fine grained sediments, (5) 148*d*.
Taylor, T. D., and Rindone, G. E. Internal friction of ion-exchanged glasses, (6) 167*b*.
Taylor, W. C. Basic brick application in electric furnace roofs, (9) 266*h*.
Taylor, W. F. See Sinfelt, J. H.
Taylor, W. F., and Sinfelt, J. H. Promoted catalyst used for town gas production, P (11) 350*a*.
Tchalenko, J. S. See Morgenstern, N. R.
Tchoubar, C. Formation of kaolinite from albite altered by water at 200°C—study by electron microscopy and electron diffraction, (7) 217*c*.
TDK Electronics Co., Ltd. Ceramic dielectrics, P (1) 17*b*, P (2) 50*h*.
Teaford, E. Q. Consolidation by chemical sintering, P (4) 97*d*.
Teague, E. C. See Krause, G. O.
Teague, J. M., Jr. Apparatus for forming a film of glass, P (5) 129*i*.
Technical Industries, Inc. Means for controlled deposition and growth of polycrystalline films in a vacuum, P (6) 177*k*.
Technicon Corp. Spectroscopy apparatus for transmitting light longitudinally of a spectral flame, P (8) 249*b*.
Technion Research & Development Foundation, Ltd. Method of fractionating mixtures of particulate solid materials, P (2) 53*d*.
Tecotzky, M. See Hurley, F. R.
Teeg, R. O., and Hallman, R. W. Infrared imaging device utilizing a vanadium dioxide film, P (5) 141*b*.
Teeg Research, Inc. Infrared imaging device utilizing a vanadium dioxide film, P (5) 141*b*.
Teegarden, K. See Huggett, G. R.; Ramamurti, J.
Teicher, H. See Marotta, R.
Teichner, S. J. See Cuer, P.; Vergnon, P.
Teiwes, H. J. See Schikarski, L.
Tektronix, Inc. High contrast fluorescent screen having spaced phosphor layer and method of manufacture, P (4) 100*c*. Method of manufacture of phosphor screen, P (9) 265*g*.
Teledyne, Inc. Integrated circuit having active and passive components in same semiconductor region, P (4) 100*c*. Temperature controlled microcircuit, P (11) 345*b*.
Teleflex, Inc. Method for making ceramic bodies, P (2) 47*i*.
Telefunken Patentverwertungs-G.m.b.H. Electrical circuit device, P (4) 99*h*. Method of forming a semiconductor by masking and diffusion, P (6) 178*b*. Method for making semiconductor device, P (4) 100*d*.
Tell, B. See Damen, T. C.; Porto, S. P. S.
Tell, B., Damen, T. C., and Porto, S. P. S. Raman effect in cadmium sulfide, (9) 286*a*.
Tench, A. J., and Nelson, R. L. Electron spin resonance of F centers in irradiated ^{16}CaO and other alkaline earth oxides, (4) 109*b*.
Tennery, V. J. Dielectric properties and phase transitions of sodium-strontium-cadmium niobates, (5) 137*i*. Study of the phase transitions in $PbZrO_3$, (4) 117*d*. See Weirauch, D. F.
Tennery, V. J., and Hang, K. W. Heats of transition in $NaNbO_3$, (9) 283*a*.
Tennissen, A. C. Clay mineralogy and ceramic properties of lower Cabaniss underclays in western Missouri, (1) 10*c*.
Tenoutasse, N. Study of the kinetics of hydration of tricalcium aluminate in the presence of calcium sulfate and calcium chloride, (3) 62*i*.
Teply, R. J. See Olson, B. J.
Terai, R., and Ueno, T. Volatilization of the components of glasses containing large amounts of lead oxide at high temperature, (8) 234*j*.
Teramoto, I., Iwasa, H., and Shinoda, S. Method of making semiconductor devices by double diffusion, P (1) 18*c*.
Terasaki, Y., Murakami, T., and Toyoda, H. Preparation and properties of vacuum deposited CdS and CdSe films, (5) 139*a*.
Terekhovskii, B. I. See Tresvyatskii, S. G.
Terrier, P. Optical microscopy of hydraulic cements, (7) 194*h*.
Terunuma, Y. See Hurusho, K.
Tervo, R. O. See Somerville, D. W. B.
Teshima, H. See Tarui, Y.
Tesla, Narodni Podnik. Circuit arrangement for accurate measurement of temperatures or small temperature changes, P (1) 23*h*. Press for drawing ceramic and other materials in the plastic state, P (6) 179*g*.
Testa, R. H. See Pereira, E.
Tetelman, A. S. See Barnett, D. M.
Teter, A. R. Binders for machinable ceramics, (2) 56*g*.
Tettamanzi, N. Chemical inhomogeneity in glass sheets, (1) 5*c*. See Tribuno, C.
Tettenhorst, R. See Brunton, G.
Tettenhorst, R., and Johns, W. D. Interstratification in montmorillonite, B (7) 224*c*.
Teufer, G. See Lewis, G. L.
Teviotdale, J. R. See Wilcox, W. R.
Texaco, Inc. Preparation of metal aluminides, P (10) 318*i*.
Texas Instruments, Inc. Alloy contact containing aluminum and tin, P (3) 72*j*. Application of glass to semiconductor devices, P (3) 72*j*. Boron nitride film capacitor, P (4) 99*c*. Capacitor for miniature electronic circuits or the like, P (2) 50*g*. Ceramic brazing means, P (8) 244*c*. Diode array and process for making same, P (8) 244*i*. Electrical temperature sensors with connected heat conductive means, P (11) 347*f*. Electrically conductive compositions, P (1) 17*g*. Flux for fusing tin to gallium arsenide and method of making and using same, P (9) 273*a*. Gallium arsenide semiconductor device and contact alloy therefor, P (6) 177*e*. Gallium arsenide semiconductor doped with chromium and a shallow acceptor impurity, P (10) 309*g*. Gallium arsenide transistor and methods of making it, P (1) 17*j*. Ge-Sb-Se glass compositions, P (4) 94*h*. Ge-Se-Te glass and infrared detection system, P (1) 9*b*. Ge-S-Te glass compositions and infrared detection system, P (6) 170*j*. Ge-Te-As glasses and method of preparation, P (1) 9*b*. Glasses and method of making same, P (6) 170*e*. High resistivity chromium doped gallium arsenide and process of making same, P (1) 18*c*. Inorganic glass composition, P (6) 170*g*. Manufacture of ceramic circuit package, P (4) 100*h*. Method for depositing a single crystal on an amorphous film, method for manufacturing a metal base transistor, and a thin-film metal base transistor, P (6) 177*j*. Method for diffusing an impurity from a doped oxide of pyrolytic origin, P (3) 73*f*. Method for fabricating electrically isolated semiconductor devices in integrated circuits, P (6) 178*a*. Method for forming a lens on a metal ring, P (1) 9*a*. Method of forming a metal contact on a semiconductor device, P (9) 273*a*. Method of forming a small area junction semiconductor, P (6) 178*b*. Method of forming small geometry diffused junction semiconductor devices, P (9) 273*g*. Method of forming a [zener] diode by using a mask and diffusion, P (3) 73*b*. Method for making compound semiconductor materials, P (10) 310*g*. Method of making dielectric bodies having conducting portions, P (9) 273*i*. Method of treating planar junctions, P (9) 274*j*. Printed [FE] transistors and methods of making same, P (5) 142*c*. Process for adherently depositing a metal carbide on a metal substrate, P (5) 126*b*. Process of growing cubic zinc sulfide crystals in a molten salt solvent, P (6) 183*c*. Process for manufacturing multilayer film circuits, P (5) 142*e*. Process for preparing improved cryogenic circuits, P (10) 311*g*. Process for purifying gallium arsenide, P (4) 101*a*. Production of dislocation-free silicon single crystals, P (11) 345*d*. Production of solid state PTC sensors, P (2) 52*b*. Resistors for integrated circuits, P (4) 101*d*. Semiconductor device utilizing glass and oxides as an insulator for hermetically sealing the junctions, P (8) 246*g*. Semiconductor devices and methods for making same, P (3) 74*a*. Semiconductor element having an organic silicone base cement, P (8) 246*h*. Semiconductor wafer with at least one epitaxial

layer and methods of making same, P (7) 210*g*. Silicon carbide coating on graphite bores of heat exchanger, P (10) 305*a*. Surface-oriented high frequency diode, P (11) 345*a*. Surface-oriented semiconductor diode, P (6) 178*h*. Tin as a dopant in gallium arsenide crystals, P (10) 311*g*. Tungsten carbide coated article of manufacture, P (9) 263*c*.

Textron, Inc. Lens-grinding wheel, P (7) 193*f*. Method and apparatus for manufacturing optical lenses, P (2) 41*h*.

Thach Lan Tran. Phase separation in some types of glass (I) internal structure of sodium borosilicate glasses, (6) 168*j*; (II) structure of sodium silicate glasses, (7) 197*b*. Study of the products of devitrification of sodium silicate glasses by X-ray diffraction and infrared spectrometry, (4) 93*h*.

Thacker, C. H., and Uhlig, A. F. Flask gages, P (1) 8*j*.

Thakur, R. L. See Das, S. K.

Thall, E. S. Resistor comprising spaced metal coatings on a resistive layer and traveling wave tube utilizing the same, P (5) 142*g*.

Tharp, A. G. See Smith, G. S.

Theard, L. P. See Hildenbrand, D. L.

Theodore, J. G. See Beaver, W. W.

Thermal Syndicate, Ltd. Process for producing cellulated silica, P (11) 349*i*.

Thermo Electron Engineering Corp. High temperature generating high intensity burners, P (3) 77*b*.

Thery, J. See Collongues, R.; Harari, A.

Theuerer, H. C. Method of sputtering highly pure refractory metals in an anodically biased chamber, P (10) 310*i*.

Thiele Kaolin Co. Fractured clay, P (1) 25*b*.

Thiem, D. W., and Gottschalk, G. W. Hot top bottom ring and method for forming same, P (7) 204*i*.

Thiemann, H. Andrew Walford—a young English potter in Germany, (1) 1*i*. Horst Kerstan of Kandern in the Black Forest, (4) 91*i*.

Thim, H. W., and Knight, S. Carrier generation and switching phenomena in *n*-GaAs devices, (6) 176*b*.

Thiokol Chemical Corp. Sampling apparatus for unground solids, P (8) 249*a*.

Thoene, H. H. Economic production of expanded (lightweight) clay, (4) 95*g*.

Thoenes, H. W. See Konopicky, K.

Thomas, D. E. High temperature nuclear fuel elements, P (1) 12*i*.

Thomas, D. L. Method of press bending vertically suspended glass sheets, P (1) 9*f*.

Thomas, D. W. Vitreous body without free silica, (3) 70*e*.

Thomas, E. A. See Prior, H. D.

Thomas, F. New apparatus for testing high speed tools, (10) 293*g*.

Thomas, G. See Wang, S.

Thomas, G., Zackay, V. F., and Parker, E. R. Structure and high-strength metals, B (4) 121*f*.

Thomas, G. W., and Swoboda, A. R. Cation exchange in kaolinite-iron oxide systems, B(5) 161*b*.

Thomas, H. B. Ultrahigh temperature thermocouples, (8) 249*j*.

Thomas, H. C. See Howery, D. G.

Thomas, J. A. Diamond abrasive article containing hexagonal crystalline boron nitride particles, P (8) 227*h*.

Thomas, J. M. See Roscoe, C.

Thomas, K. T. See Jha, J. C.

Thomas, L. H. Temperature variation of viscosity and the structure of liquids, (3) 87*a*.

Thomas, M. J. B. See Butler, K. H.

Thomas, P. M., Wright, L. W., Burge, R. W., and Crile, E. E. Bricklaying machine, P (8) 236*g*.

Thomas, R. E. See Crane, P. J.

Thomas, T. G., and Wilson, S. G. Processes for the recovery of uranium, P (1) 14*e*.

Thomas, W. J., Sr. Method of making a refractory brick, P (11) 340*j*.

Thomas & Betts Co. Thermocouple junctions, P (7) 213*c*.

Thome, W. L., Beggs, D., and McCully, J. B. Method and apparatus for firing ceramic bodies, P (2) 56*d*.

Thompkins, F. C. See Delchar, T. A.

Thompsen, R. S. Evaluation of the direct-on cover coat process, (9) 262*h*. See Farrow, L. C.; Linhart, O. C.

Thompson, A. L. Apparatus for separating granular materials, P (11) 349*e*.

Thompson, C. E. Method of making a porous electrode, P (11) 340*i*.

Thompson, C. S. See Mumpton, F. A.

Thompson, D. S., and Pratt, P. L. Structure of silicon nitride, B (7) 226*c*.

Thompson, G. G. See Holmes, W. T., II.

Thompson, J. C., and Margrave, J. L. Chemistry of silicon difluoride, (4) 100*f*.

Thompson, J. W. See Kruger, O. L.

Thompson, M. A. See Guyton, J. L.

Thompson, R. L., and Dwyer, F. B. Method of ore sorting based on differential infrared emission, P (11) 349*c*. Method of rendering asbestos ore particles differentially fluorescent [for economical separation], P (1) 25*f*.

Thompson, S. G. See Bowman, H. R.

Thompson, V. S., and Whittemore, O. J., Jr. Structural changes on reheating of plasma-sprayed alumina, (8) 239*j*.

Thomson, A. J. See Barnes, J. C.

Thomson, M. G. See Musschoot, A.

Thormann, P. Importance of separate grinding of limy clay and sand for clinker mineral formation during cement burning, (10) 294*i*. See Niesel, K.

Thormann, P., and Buchmayer, P. New vertical dilatometer for use up to 1600°C, (5) 145*f*.

Thorn, R. J. See Ackermann, R. J.

Thorn, R. J., and Winslow, G. H. Chemical problems associated with lattice defects—uranium dioxide phase, B (4) 120*j*. Nonstoichiometry in uranium dioxide, (7) 220*c*. Oxygen self-diffusion in uranium oxide, (7) 220*g*.

Thornber, K. K. See Sher, A.

Thornberry, J. R. See Titus, L.

Thorne, D. J. See Watt, J. D.

Thorne, D. J., and Watt, J. D. Composition and pozzolanic properties of pulverized fuel ashes (II) pozzolanic properties of fly ashes as determined by crushing strength tests on lime mortars, (10) 294*d*.

Thornton, C. G. Microcircuits having buried conductive layers, P (8) 245*h*.

Thornton, L. W. Visual records update maintenance program, (3) 75*a*.

Thornton, P. R. See Wayte, R. C.

Thornton, W. A., Jr. Electroluminescent device comprising electroluminescent films emitting light of complementary colors, P (9) 272*g*. Electroluminescent device which incorporates barrium oxide films as breakdown protection, P (7) 208*d*.

Thorp, T. L. See Cashion, J. D.

Thorpe, R. I. See Harris, D. C.

Threadgold, I. M. See Ryall, W. R.

Thring, M. W. Plasma engineering, (10) 312*g*.

Thrower, P. A. Burgers vector of dislocation loops in graphite, (1) 26*f*. Interaction between dislocation loops and straight dislocations in an anisotropic material, graphite, (1) 29*f*. Interstitial loops in graphite, their motion and their effect on elastic modulus, (4) 111*i*.

Thulin, L. U. See Forland, T.

Thun, R. E. See Hass, G.

Thurman, R. R. T. See Ball, M. C.

Thurmond, C. D. See Frosch, C. J.

Thwing-Albert Instrument Co., Inc. Micro creep-testing, P (10) 316*b*.

T.I. (Group Services), Ltd. Electron probe microanalysis with specific X-ray spectrometer structure, P (5) 147*b*.

Tichelaar, G. W., Essers, W. G., and Verhagen, J. G. Welding wire for electric arc welding of steel in a protective gas atmosphere, P (10) 296*f*.

Tichelaar, J. See Berendsen, A.

Tichy, O. Effect of reducing atmospheres on thermocouples based on platinum (I) unprotected thermocouples, (5) 145*g*. Use of ultrasonics for the nondestructive testing of electrical porcelain, (6) 181*a*.

Tickle, R. E. Electrical conductance of molten alkali silicates (I) experiments and results; (II) theoretical discussion; corrections, (2) 39*a*.

Ticknor, W. A. Method and means for controlling internal furnace pressures, P (6) 171*e*.

Tiede, R. L., Glaser, H. I., and Willis, J. H. Apparatus for melting and feeding heat-softenable materials, P (3) 65*a*.

Tiedemann, J. See Juza, R.

Tiemann, J. J. Semiconductor devices, P (3) 74*g*.

Tien, T. Y., and Hummel, F. A. Solid solutions in the system $SrTiO_3$–$(La_2O_3{:}3TiO_2)$, (1) 32*d*.

Tien, T. Y., Hummel, F. A., and Cross, L. E. Dielectric relaxation in strontium titanate solid solutions containing mixed cations, (7) 216*e*.

Tietjen, J. J. See Nuese, C. J.

Tilbrook, K. B. Glass fiber cooling means, P (10) 300*j*.

Till, R. See Davies, P. J.

Tiller, J. A. Plumbing fixture installation, P (5) 137*c*.

Tillmann, P., Kuelling, A., and Hitzemann, G. Means for the production of fine particle size titanium dioxide, P (4) 105*f*. Multitube burner, P (3) 77*b*.

Tilton, R. L. Annealing lehr for glass sheets with reradiating side wall plates, P (9) 264*f*.

Timashev, V. V. See Anikeeva, T. V.; Butt, Yu. M.; Kaushanskii, V. E.

Timashev, V. V., and Ramankulov, M. R. Dibasic compounds of calcium, barium, and strontium and their solid solutions, (6) 164*i*.

Timmermans, A. See Holmes, T.

Timmers, H. J. Some physical aspects of the drying of ceramic products, (2) 43*b*.

Timms, P. L. Production of titanium diboride, P (2) 48*b*.

Timofeeva, N. I. See Portnoi, K. I.

Timperley, G. K. Impact of legislation on the refractories industry, (2) 44*g*.

Timusk, T., and Klein, M. V. Sidebands of the infrared U center in KBr, (8) 257*a*.

Tinklepaugh, J. R. Ceramic-metal fiber composite systems, B (4) 121*i*.

TISCO, Ltd. Magnesite brick and a method of improving their spalling resistance, P (2) 47*d*.

Titan Abrasives Co. Grinding disk, P (9) 261*i*.

Titangesellschaft m.b.H. Means for the production of fine particle size titanium dioxide, P (4) 105*f*. Multitube burner, P (3) 77*b*. Separation of titanium dioxide, P (1) 26*a*.

Title, R. C. See Taylor, R. C.

Tittel, F., and Kamel, N. Radiation effects in glass lasers, B (10) 329*a*.

Titus, L., Thornberry, J. R., and Breuer, R. G. Process for the production of refractory hard metal materials, P (2) 48*a*.

Tkacova, K. See Spaldon, K.

Tlapek, J. W., and Keller, W. D. Stabilities of three-layer phyllosilicates related to their ionic-covalent bonding, B (6) 191*i*.

Toa Electric Co., Ltd. Particle counting device including fluid conducting means breaking up particle clusters, P (9) 277*g*.

Tobias, T. J., and Ruotsala, A. P. Long-term settling characteristics of some clays, B (7) 225*c*.

Tocci, L. See Epstein, D. J.

Todd, C. J. See Palmberg, P. W.

Todd, F. A. Development of a high speed blunger, (5) 143*h*.

Toeroek, L., Markotai, T., and Bogar, I. Machine for mixing and dividing test specimens of material, P (1) 23*i*.

Toita, K. See Sato, T.

Tojo, T. See Nakajima, T.

Tokar, M. Increase in preferred orientation in lead ferrite by firing, (11) 342*j*.

Tokoro, T. See Tanaka, M.

Tokumoto, Y. See Kuroki, H.

Tokunaga, H. See Ida, I.

Tokuyama, T. See Nomura, M.

Tolley, G. C. See Howard, R. A.

Tolomei, M. See Notari, B.

Tomandl, G., and Oel, H. J. Electrical and mechanical aftereffects in glass, (8) 231*e*.

Tomimoto, K. See Sanders, H. H.

Tomita, T. See Yuasa, T.

Tomkins, B. See Cribb, J. L.

Tomkins, D. E. Tunnel kiln, P (9) 278*d*.

Tomlinson, J. W., and Welch, B. G. Solubilities of MgO and UO_2 in molten MgF_2, (4) 115*j*.

Tomotsu, T. See Makishima, S.

Tompkins, F. C. See Machin, W. D.

Tondon, V. K. See Awasthi, S. K.

Tong, M. See Rouberol, J. M.

Tonning, A. See Engan, H.

Tooi, A. See Watanabe, M.

Topil'skii, G. V., Butt, Yu. M., and Kolbasov, V. M. Influence of water/cement ratio on the hardening, structure, and properties of cement at reduced temperatures, (6) 165*c*.

Torgesen, J. L., and Peiser, H. S. Method and apparatus for growing [large] single crystals of slightly soluble substances, P (6) 190*h*.

Torii, T. See Inagaki, K.

Torii, Y. See Hayashi, H.

Torok, J. J. Apparatus for drawing glass in cylindrical form, P (4) 94*b*. See Cozine, H. E.; Eyles, T. E.

Toropov, N. A. See Degen, M. G.

Toropov, N. A., Bondar, I. A., and Valtere, A. Ya. Spectral properties of monocrystals and glasses containing rare earth elements, (6) 188*j*.

Toropov, N. A., and Fedorov, N. F. Phase diagram of the system Ca_2SiO_4–$Y_4(SiO_4)_3$, (3) 84*f*. System Ca_2SiO_4–Ba_2SiO_4, (1) 33*d*.

Toropov, N. A., Fedorov, N. F., and Khentov, V. I. Solid solutions of calcium orthophosphate in dicalcium silicate, (6) 188*f*.

Toropov, N. A., and Rumyantsev, P. F. Factors that control the rate of portland-cement clinker formation, (5) 124*j*. Kinetics of solution of clinker minerals in liquid phase of portland cement clinker, (8) 228*f*.

Toropov, N. A., and Sirazhiddinov, N. A. Dependence of microhardness of crystallized glass materials on the morphology of crystalline phases in the spinel-silica system, (9) 280*c*.

Toropov, N. A., Zhukauskas, R. S. M., and Aleinikov, F. K. Formation and recrystallization of quartz-like phases during crystallization of glasses in the SiO_2–Al_2O_3–MgO system, (6) 185*j*. Structural conversions in synthetic cordierite, (6) 189*d*.

Toropova, N. K. See Kokovin, G. A.

Torrence, J. D. See Patterson, W. R.

Toshiba Tungaloy Co., Ltd. High-pressure high-temperature apparatus, P (8) 247*d*.

Toth, J. See McRae, R. C.

Toth, K. See Macdonald, A. M. G.

Toth, L. E. High superconducting transition temperatures in the molybdenum carbide family of compounds, (4) 98*i*.

Totsenko, S. B. See Kainarskii, I. S.

Totsenko, S. B., Kainarskii, I. S., and Degtyareva, E. V. Properties of spinel and spinel-corundum sintered refractory materials, (8) 239*f*.

Touchy, W., Toussaint, H. N., and Krieger, F. Pressure-responsive transistor, P (5) 142*c*.

Touloukian, Y. S. (editor). Thermophysical Properties Research Literature Retrieval Guide, B (5) 161*f*.

Toussaint, C. J. See Conti, R.

Toussaint, H. N. Semiconductor latching switch with light-coupled triggering means, P (5) 143*a*. See Touchy, W.

Toussaint, H. N., and Krieger, F. Field-effect pressure transducer, P (7) 208*h*.

Towle, L. C. Empirical relation between shear strength, pressure, and temperature, (5) 152*c*.

Town, J. W., Sanker, P. E., and White, J. C. Liberation and concentration of phosphate minerals by attrition grinding and sizing, (1) 25*a*.

Towner, R. J. See Stapleton, R. E.

Townsend, M. G. Electron spin resonance and electronic absorption spectra of Rh(II) in $ZnWO_4$, (6) 185*i*.

Townsend, M. G., and Orton, J. W. Spin-lattice relaxation of Rh(II) in single crystals of $ZnWO_4$, (10) 325*a*.

Townshend, A. See Rocchiccioli, C.

Toyama, M. Electron spin resonance parameters in 6H polytype of silicon carbide crystal doped with boron, (3) 80*e*.

Toyama, S. See Suzuki, T.

Toyoda, H. See Ashida, T.; Itakura, M.; Sawamoto, K.; Tanaka, Y.; Terasaki, Y.

Trainor, J. T., and Kaufman, E. R. Heat resistant inorganic bodies, P (9) 270*b*.

Tran, Thach Lan. See Thach Lan Tran.

Transistor Automation Corp. Sealing head for glass diodes, P (10) 301*d*.
Transitron Electronic Corp. Means for forming planar junctions and devices, P (4) 100*i*. Semiconducting device, P (5) 142*h*. Silicon transistor device, P (4) 101*b*.
Trap, H. J. L. Method for making electrically conductive vitreous materials, P (1) 9*d*.
Trask, R. B. Multiple section graphite electrode, P (4) 97*d*.
Traulsen, K. See Heymer, G.
Trautz, O. R. See LeGeros, R. Z.
Traverse, J. P. See Foex, M.
Tredgold, R. H. Space Charge Conduction in Solids, B (9) 290*h*. See Cox, G. A.
Treffner, W. S. Discussion of "Deterioration of cement rotary kiln linings by alkali sulfides and sulfates," (8) 237*c*.
Treffner, W. S., and Wohlleben, K. Changes in the basic brick in oxygen process steel converters, (7) 200*j*.
Treharne, R. W., and McKibben, C. K. Direct reading wavelength independent radiometer employing a pyroelectric crystal detector, P (11) 343*b*.
Treillou, A. See Accary, A.
Treinin, A. See Feldmann, T.; Zaliouk-Gitter, A.
Treinin, A., and Zaliouk-Gitter, A. Inorganic radicals trapped in glasses at room temperature (III) IBr^- in boric acid glass, (5) 127*f*.
Treptow, A. W. See DiMarcello, F. V.
Tressler, R. E., and Stubican, V. S. Magnetic properties of A^{2+} Cr_2S_4 compounds with the NiAs structure [A = Mn, Fe, Co], (8) 255*c*. Preparation of thin films of sulfospinels, (4) 114*b*.
Tressler, R. E., and Williamson, W. O. Particle arrangements and differential imbibitional swelling in deformed or deposited kaolinite-illite clay, B (7) 225*c*.
Tresvyatskii, S. G., Boichun, V. Yu., Yaremenko, Z. A., and Klimenko, V. S. Some properties of foam quartz glass, (10) 298*d*.
Tresvyatskii, S. G., Pavlikov, V. N., and Lopato, L. M. Phase diagram of the Sc_2O_3–Cr_2O_3 system, (6) 187*b*.
Tresvyatskii, S. G., Terekhovskii, B. I., et al. Effect of adding boron nitride on some properties of aluminosilicate refractories, (9) 267*c*.
Tretheway, W. C. Controlling a recuperative-fired glass furnace, (3) 63*h*. Direct digital control, (9) 275*f*. Viscosity measuring process and apparatus, P (8) 236*c*.
Tret'yakov, Yu. D, Oleinikov, N. N. Evaluation of the defects of spinel structures on the basis of chemical analysis data, (9) 282*g*.
Tribuno, C., and Tettamanzi, N. Possible interpretation of striae in glass, (11) 334*d*.
Trigg, G. W. Graphite brick structures, P (1) 12*g*.
Trigg, W. M. Thin film resistor composed of chromium and vanadium, P (4) 101*f*.
Trillat, J. J., Legrand, C., Barbezat, S., and Goton, R. P. Projection microradiography and its application to the study of ceramics and refractories, (6) 173*c*.
Trimarke, C. R. See Mayland, B. J.
Trinker, B. D. See Skramtaev, B. G.
Tripathi, K. C. Use of radioisotopes in mineral prospecting, (1) 25*g*.
Triplex Safety Glass Co., Ltd. Laminated transparent panels incorporating heating wires, P (7) 198*i*.
Tripp, T. B. See Smyth, D. M.
Trivedi, P. M., and Shukla, B. K. Sorel cement (II) tile, (5) 125*a*.
Troell, P. T. See Cook, M. D.
Troell, P. T., and Renkey, A. L. Aluminum induction furnace lining construction using zircon and calcium aluminate, P (3) 68*h*.
Troitskii, O. A. Defects in glass, (8) 230*h*.
Trojer, F. Damage to magnesite brick by carbon at CO decomposition temperatures, (9) 267*b*. Deterioration of cement rotary kiln linings by alkali sulfides and sulfates, (8) 237*c*. Sulfate resistance of Ferrari cements, (10) 296*b*.
Trond, S. S. See Martin, J. S., Jr.
Troshin, Yu. P. See Anfilogov, V. N.
Troup, G. J., and Walter, J. Nuclear magnetic resonance of ^9Be in single crystals of BeO, (3) 67*c*.
Trouve, J. See Accary, A.; Gayet, B.; Magnier, P.; Val, C.
Trouve, J., and Accary, A. Solidification characteristics in the continual casting of uranium carbide, (6) 174*c*.
Troy, E. C. Rotary mixer, P (6) 179*h*.
Trucco, R. See Cerrai, E.
Truesdell, A. H. See Hostetler, P. B.
Trumbo, P. W., Carpenter, J. H., and Hendrickson, T. A. Discharge grate and hopper for shaft kiln, P (4) 104*b*.
Trumbore, F. A. See Logan, R. A.
Trumbore, F. A., White, H. G., Kowalchik, M., Logan, R. A., and Luke, C. L. Solubility and electrical behavior of zinc, sulfur, selenium, and tellurium in gallium phosphide, (3) 86*c*.
Trumbore, F. A., White, H. G., Kowalchik, M., Luke, C. L., and Nash, D. L. Solubility and electrical behavior of group IV impurities in solution grown gallium phosphide, (4) 116*b*.
Trump, R. P. See Milne, I. H.
Trunov, V. K. See Kovba, L. M.
Trunov, V. K., Rozanova, O. N., and Kovba, L. M. Double oxides of uranium and molybdenum, (10) 319*f*.
TRW, Inc. Method and apparatus for removal of condensed deposits from mold covers, P (8) 240*i*. Method of fabricating thin film resistors, P (8) 245*f*. Thermal shock resistant rocket nozzle insert, P (8) 241*f*.
Tsai, Y. M., and Kolsky, H. Study of the fractures produced in glass blocks by impact, (1) 7*h*. Theoretical and experimental investigation of the flaw distribution on glass surfaces, (1) 8*a*.
Tsarevskii, B. V. See Sherstobitov, M. A.
Tseitlin, L. A., and Gubatenko, A. P. Refractory bodies for repairing Dinas and chamotte structures in industrial furnaces, (9) 268*j*.
Tsibrik, A. N., and Misechko, V. I. Localized-heating microchamber for high-temperature research, (10) 314*f*.
Tsigler, V. D., and Bulakh, V. L. Wear of Dinas in Bessemer converters, (9) 269*i*.
Tsigler, V. D., Bulakh, V. L., and Stovbur, A. V. Experience in pressing Dinas bodies on hydraulic presses (9) 267*j*.
Tsou, I. H. Molding composition comprising a refractory material and, as a binder, the reaction product of formaldehyde, furfuryl alcohol, and a urea, P (4) 97*c*.
Tsubaki, T., Hattori, M., and Tanaka, M. Thermal conductivity of mixtures of vermiculite and asbestos and their cement mortars, (8) 240*d*.
Tsuboi, H. See Ohnishi, S.
Tsubouchi, N. See Akashi, T.; Takahashi, M.
Tsuboya, I. Magnetic properties of pulverized cobalt ferrite, (5) 154*b*.
Tsuchihashi, S., Yano, T., Komatsu, T., and Adachi, K. Infrared absorption spectra of As-S glasses, (8) 232*j*.
Tsuji, S., and Koyama, T. Glass molded type semiconductor device, P (7) 208*j*.
Tsujii, S. High-pressure high-temperature apparatus, P (8) 247*d*.
Tsukino, M. See Tanemura, F.
Tsunoda, Y. Single crystal growth on α-Al_2O_3 substrate, (10) 325*g*. Vapor etching of sapphire by H_2-$SiHCl_3$ gas mixtures, (4) 118*j*.
Tsurikova, G. A. See Yudin, D. M.
Tsurumiya, K. See Kobayashi, M.
Tsutsumi, N. Cupola, (10) 302*j*. Results of tests on the corrosion of cupola refractories with added Cr_2O_3 and the dissolution of Cr in the iron, (9) 269*c*.
Tsuyama, A. Watanabe, Kenichi.
Tsuzuku, T., and Saito, K. Electric conduction in glassy carbons, (8) 253*b*.
Tsvetaev, A. A. See Zuikov, N. V.
Tsybul'ko, I. A. See Rubinchik, Ya. S.
Tucker, E. B. Spin-lattice coupling of a Kramers doublet—Co^{2+} in MgO, (9) 286*e*.
Tucker, T. N. Semiconductor integrated circuits and method of making same, P (11) 345*f*. See Haga, L. J.
Tuddenham, W. M. See Adamson, D. L.
Tufte, O. N., and Stelzer, E. L. Piezoresistive properties of reduced strontium titanate, (8) 256*a*.
Tuinstra, F. See Aken, J. E. van.
Tully, G. R., Jr. See Bokros, J. C.
Tully, G. R., Jr., Schwartz, A. S., and Bailey, L. Process for making graphite, P (8) 241*a*.
Tulovskaya, Z. D. See Brutskus, T. K.
Tulovskaya, Z. D., Brutskus, T. K., and Segalova, E. E. Structure formation in dilute asbestos and asbestos-cement suspensions, (10) 295*i*.
Tumakova, E. I. See Guzman, I. Ya.
Tumanov, S. G., and Filippova, E. A. Conditions for forming pink pigments and their structure, (8) 250*c*.
Tumanov, V. I. See Funke, V. F.
Tunis, C. J. See Gamblin, R. L.
Turdakin, V. A., and Tarasov, V. V. Specific heat of boric anhydride and soda-borate glass at low temperatures, (7) 197*j*.
Turk, S. D. See Mahan, J. E.
Turkalo, A. M. Technique for obtaining thin glass sections for transmission electron microscopy, (9) 277*b*.
Turkevich, J. See Iyengar, R. D.
Turnbaugh, J. E., and Norton, F. H. Low-frequency grain-boundary relaxation in alumina, (7) 219*e*.
Turnbull, D. See Bagley, B. G.; Greet, R. J.; Seward, T. P., III; Uhlmann, D. R.
Turnbull, J. A., and Stagg, M. S. Multilayer vacancy loops in graphite, (1) 30*b*.
Turner, C. W., and Crow, J. Acoustoelectric oscillations with field-dependent period in indium antimonide, (5) 149*e*.
Turner, D. N., Smith, P. D., and Rotsey, W. B. Hertzian stress cracks in beryllia and glass, (1) 29*b*.
Turner, F. J. Thermodynamic appraisal of steps in progressive metamorphism of siliceous dolomitic limestones, (3) 77*f*.
Turner, G. I. See Luxmoore, A. R.
Turner, G. J., and Legal, C. C., Jr. Metal phosphate gels and methods for producing same, P (8) 251*f*.
Turner, N. C., and Cavitt, J. H. High power multiemitter transistor, P (8) 244*f*.
Turner, W. H. Discussion of "Optical absorption spectra of iron in the rock-forming silicates," (6) 185*e*. See Albinak, M. J.
Turner, W. H., and Lee, H. A. Absorption, luminescence, and excitation spectra of "reduced" fused silica, (5) 126*g*.
Tuska, J. W. See Gordon, I.
Tuttle, O. F. See Luth, W. C.; Peters, T.
Tuvell, M. E. Alkaline earth metal hydroxyl-apatites, processes for preparing, and compositions containing the same, P (7) 204*d*.
Tverskov, V. A. See Morozov, I. S.
Tveter, E. C. See Olsen, R. S.
Tykachinskii, I. D. See Gendler, T. S.
Tyrrell, M. E. See Hollenbeck, R. P.; Johnson, S. S.
Tyson, W. R. See Kelly, A.
Tyte, D. C. See Nicholls, R. W.
Tyul'kin, V. A. See Sidorov, T. A.
Tyurin, A. I. See Sheinkop, I. M.
Tyutyunnik, A. G. See Somov, A. I.
Tyvaert, P. See LeGouestre, J.

Ubbelohde, A. R. Making electrical contacts to solid nonmetallic conductors, (4) 99*a*. Mechanisms of melting, (1) 30*e*. Melting and crystal structure—some current problems, (5) 154*f*. See Rhodes, E.
Uchida, I. See Okuto, Y.
Uchida, K. See Gomes, J. M.
Uchikochi, H. See Sato, R.
Udy, M. C. See Olds, L. E.
Uebbing, J. J., and Bell, R. L. Cesium-GaAs Schottky barrier height, (11) 350*e*.
Ueda, K., Yamamoto, H., and Kuwahara, Y. Effect of charge condition on vibration milling, (1) 19*i*.
Ueda, M., Semba, K., and Kido, K. Fundamental investigation of clay-grog mixtures for use in the auger, (10) 301*h*.
Uei, I. See Nakazawa, Y.
Ueno, T. See Terai, R.
Ueno, T., and Hayashi, M. Contour of absorption lines $n = 2$ of the yellow and the green series in Cu_2O, (4) 107*d*.
Ueoka, H., Tashima, N., and Takei, T. Nature of manganese-bearing sintered wustite (I) observation of thermal disintegration by microscopic and X-ray analysis, (9) 284*g*.
Uetsuki, T. See Nakazawa, Y.
Uglikova, N. S., and Perepelitsyn, V. A. Testing the bond of refractory concretes in zinc scrap melts, (9) 269*d*.
Ugorets, M. Z. See Buketov, E. A.
Uher, J. F., and Schweikert, W. F. Deposition of nickel by displacement reactions, (9) 262*i*.
Uhlig, A. F. See Thacker, C. H.
Uhlig, H. H. See Nwoko, V. O.
Uhlir, A., Jr. Idler circuit encapsulated in parametric or tunnel diode semiconductor device, P (10) 309*i*.
Uhlmann, D. R. See Hakim, R. M.; Meiling, G. S.; Seward, T. P., III; Shaw, R. R.
Uhlmann, D. R., Hays, J. F., and Turnbull, D. Effect of high pressure on B_2O_3—crystallization, densification, and the crystallization anomaly, (1) 28*g*.
Ukrainskii, Yu. M. See Malyukov, B. A.
Ukrainsky Nauchno-Issledovatelsky Institute Khimicheskogo Mashinostroenija. Automatic chamber pressure filter, P (1) 20*c*.
Ulbrich, R. W. Linings of furnaces, ovens, kilns, and the like, P (7) 204*j*.
Ullman, F. G. Photoconduction and trapping in sputtered tantalum oxide films, (3) 72*a*.
Ullmann, J. W. See Olsen, A. R.
Ulmer, G. C., and Smothers, W. J. Application of mercury porosimetry to refractory materials—correction, (1) 11*a*. System MgO-Cr_2O_3-Fe_2O_3 at 1300°C in air, (7) 222*a*.
Ultee, C. J. Infrared studies of the B_2O_3–BF_3 system, (5) 153*c*.
Ulyakov, P. I. See Ponomarenko, B. F.
Umanskii, Ya. S., and Fadeeva, V. I. Diffuse X-ray scattering by the solid solution NbC-TaC, (9) 280*g*.
Umbel, F. K. Glasscutting control apparatus, P (9) 265*f*.
Umblia, E. Japanese glass industry, (5) 127*i*.
Umebayashi, H., and Ishikawa, Y. Motion of a single domain wall in a parasitic ferromagnet, $YFeO_3$, (3) 83*b*.
Umeda, S. Current and temperature responsive magnetic control device, P (9) 272*e*.
Umeya, K., Watanabe, T., and Kondo, Y. Vacuum extrusion shaping of ceramic materials, P (9) 275*g*.
Union Carbide Canada, Ltd. Method of control of particle size utilizing viscosity, P (4) 103*g*.
Union Carbide Corp. Abrasive compositions and structures thereof comprising a thermosetting resin and a thermoplastic polyarylene polyether, P (3) 61*g*. Apparatus for forming large carbonaceous bodies, P (6) 174*i*. Chemical reaction catalyst and its preparation, P (7) 214*j*. Coating carbon substrates with refractory metal carbides, P (10) 304*c*. Filled inorganic structural compositions having improved strength, P (8) 240*d*. Green luminescing phosphor for color television and method of making same, P (11) 343*f*. High-strength carbon foam, P (9) 270*b*. High strength inorganic cement compositions, P (5) 125*c*. Hydrocarbon conversion catalysts, P (5) 148*c*. Method for induction sintering refractory carbide articles, P (2) 47*h*. Method for making high strength spherical glass bodies, P (9) 265*e*. Mineral working burner apparatus, P (8) 251*a*. Process for growing high perfection crystals, P (5) 150*j*. Process for preparing crystalline zeolitic molecular sieves, P (10) 318*b*. Process for producing coatings on carbon and graphite filaments, P (5) 136*c*. Process for producing pyrolytic graphite whiskers, P (7) 205*j*. Radiation sensitive evaporative analyzer, P (11) 348*a*. Thermally stable carbon articles, P (10) 305*b*. Treat solution for rendering carbonaceous articles oxidation resistant, P (2) 48*d*. Vanadium carbide process, P (8) 241*g*. Vertical lime kiln, P (3) 63*a*. Wet attrition-resistant molecular sieve bodies and their manufacture, P (8) 252*a*. Zeolite A bodies and their preparation, P (11) 350*a*.

Union Oil Co. of California. Caustic treated zeolites, P (6) 182*f*. Hydrocarbon conversion process and catalyst comprising a Y type crystalline aluminosilicate promoted with a polyvalent metal, P (4) 105*c*. Pelleted zeolite compositions, P (10) 318*g*. Pelleted zeolite compositions possessing improved crushing strength, P (3) 78*a*. Stabilized zeolites and use thereof for hydrocarbon conversions, P (3) 78*f*.

UNITEC. Apparatus for the separation of materials of different densities, P (1) 20*c*.

United Aircraft Corp. Integrated circuit modules, P (5) 141*b*. Method for producing silicon carbide layers on silicon substrates, P (9) 274*g*. Tungsten carbide base cermet, P (6) 175*d*.

United Engineers & Constructors, Inc. Nickel and nickel oxide catalysts on a nickel spinel base, P (5) 148*f*.

United Glass, Ltd. Treatment of hollow glass containers, P (5) 130*h*.

United Glassworks. See N. V. Vereenigde Glasfabrieken.

United Kingdom Atomic Energy Authority. Apparatus for use in the production of spherical particles, P (5) 144*e*. Ceramic fuel element for a gas-cooled nuclear reactor including a metallic fuel container provided with an oxidation resistant coating, P (4) 97*c*. Cermets, P (2) 46*g*. Glass composition comprising radioactive waste oxide material contained within a steel vessel, P (5) 129*j*. Graphite brick structures, P (1) 12*g*. Graphite structures in nuclear reactors, P (7) 204*d*. Hydrostatic extrusion processes, P (8) 247*d*. Manufacture of uranum/zirconium carbide, P (5) 135*h*. Method of fabricating mixed ceramic compacts, P (1) 13*c*. Method of producing dense sintered bodies of UO_2 or UO_2-PuO_2 mixtures, P (7) 205*c*. Methods of forming nuclear fuel bodies, P (1) 13*j*. Nuclear reactor fuel elements, P (2) 47*d*. Preparation of beryllium oxide of fine particle size through crystallization and calcination, P (1) 25*g*. Processes for the recovery of uranium, P (1) 14*e*. Processing of metal fluorides including uranium hexafluoride with anhydrous hydrogen fluoride, P (8) 241*c*. Refractory oxides doped with silicon carbide and silicon nitride, P (1) 14*j*. Sintered uranium dioxide containing yttrium oxide, P (1) 14*e*. Sintered uranium-iridium composition and method of preparation, P (1) 14*f*.

United Kingdom of Great Britain and Northern Ireland, Minister of Aviation. Production of crystalline material, P (7) 215*f*.

United Kingdom, Minister of Aviation. Optical frequency-changing devices and materials for use therein, P (11) 344*b*.

United Kingdom, Minister of Technology. Manufacture of silicon nitride, P (11) 340*g*.

United States of America, Administrator of the National Aeronautics and Space Administration. Arc electrode of graphite with ball tip, P (11) 347*e*. Conforming polisher for aspheric surfaces of revolution, P (1) 20*f*. Foamed-in-place ceramic refractory insulating material, P (8) 240*d*. Prestressed refractory structure, P (1) 13*f*. Reactor fuel element for a nuclear rocket motor, P (7) 205*b*. Thermal control coating, P (11) 333*a*.

United States of America, Secretary of the Air Force. Aircraft nose radome with ceramic cover mounted on metallic framework, P (11) 339*g*. Alumina-boron fiber composite material, P (8) 240*j*. Apparatus for depositing material on a filament from ionized coating material, P (9) 275*e*. High temperature dielectric reinforced composite, P (9) 270*c*. High-temperature reflective and thermally protective coatings, P (4) 93*a*. Method of making divalent rare earth laser crystals in an electric field, P (10) 310*i*. Method of making refractory metal nitride fibers, flakes, and foil, P (6) 174*j*. Microwave modulator using anisotropic effects of ferromagnetic resonance in single crystals, P (11) 344*g*. Process of forming passivating internal In_2O_3 bands in silver-indium alloys, P (7) 210*b*. Single thermocouple differentiating method and system, P (4) 103*h*. Time measurement as indication of temperature, P (1) 24*a*. Vapor deposition of pyrolytic graphite on tungsten, P (7) 195*f*. Yttrium, dysprosium, and ytterbium alkoxides, P (3) 69*g*.

United States of America, Secretary of the Army. Image orthicon cathode-ray tube with copper screen target having a chromium supported magnesium oxide film, P (4) 100*d*. Method of growing single crystals of $Ba_2Zr\ Fe_{10}O_{22}$, P (8) 245*h*. Method of making thin film capacitor, P (11) 344*c*. Method and means for orienting crystals by alternate application of angularly spaced magnetic fields, P (7) 213*a*. Optical laser configuration, P (11) 344*i*. Process of casting a reactive metal, P (8) 241*g*. Shaped charge liners, P (7) 205*f*. Stage interferometer for microinterferometry, P (2) 55*h*.

United States of America, Secretary of Commerce. Method and apparatus for growing [large] single crystals of slightly soluble substances, P (6) 190*h*.

United States of America, Secretary of the Interior. Consolidation and forming by high-energy-rate extrusion of powder material, P (10) 312*b*. Fluormicas and fluoramphiboles and methods for making same, P (4) 105*b*. Magnetic separator with a combination field, P (8) 251*e*. Method of making paper from mica flakes which have been subjected to hot aqua regia, P (9) 274*a*. Method of preparing zirconium carbide fibers and the product thereof, P (8) 241*c*. Process for washing and removing organic heavy liquids from mineral particles, P (1) 26*a*. Synthesis of aluminum borate whiskers, P (2) 48*c*.

United States of America, Secretary of the Navy. Deep submergence hydrophone, P (5) 140*j*. Electroluminescent device comprising electroluminescent films emitting light of complementary colors, P (9) 272*g*. Gyratory fluidized solids feeder, P (3) 75*b*. Method of constructing radome, P (8) 245*d*. Method for growing single crystals, P (2) 51*j*. Method of making a ceramic-plastics composite material, P (4) 93*a*. Method of producing pyrolytic graphite, P (6) 175*c*. Method of providing refractory metals with protective coatings and resulting article, P (4) 93*b*. Prereacted raw materials technique for attaining high quality ceramics, P (4) 97*d*. Segmented ferrite sonar transducer with permanent magnet bias, P (8) 246*e*. Thermoluminescent glass and method of preparing the same, P (11) 336*h*. Transformer having windings between two ferrite strips [Mn-ZnO], P (2) 52*h*.

United States of America, U. S. Atomic Energy Commission. Boron carbide article and method of making, P (5) 134*e*. Densification of refractory compounds, P (1) 12*a*. Electrical potential method for dispersion of metal oxide microspheres, P (2) 53*a*. Extraction method for preparing UO_2 microspheres, P (5) 134*j*. Fabrication of materials by high energy-rate impaction, P (1) 12*d*. Fluoride adsorption by thorium oxide in aqueous thorium nitrate solutions, P (11) 340*c*. Formation of submicron uranium carbide particles in metallic uranium, P (1) 12*e*. Fuel element containing activated carbon, P (3) 68*c*. Fuel pellet for nuclear reactor, P (3) 68*d*. High density ceramic beryllia-nuclear fuel compact containing an additive for the retention of fission products, P (5) 135*e*. High-temperature isostatic pressing of articles, P (4) 102*c*. Method of fabricating ceramic nuclear fuel product, P (3) 69*b*. Method of making refractory products, P (1) 13*f*. Method for melting uranium oxide and plutonium oxide, P (1) 13*f*. Method of preventing segregation during casting of composites, P (5) 135*b*. Oxidation-reduction procedure for particle-size reduction of UO_2, P (1) 13*d*. Oxidation-resistant beryllium articles and process of making, P (1) 13*c*. Plutonium carbonitride, P (5) 135*g*. Preparation of dense thoria and sulfate containing thoria from an aqueous thorium nitrate solution, P (5) 135*g*. Preparation of high quality uranium carbide, P (10) 304*j*. Preparation of pure dense hypostoichiometric uranium carbide, P (11) 340*e*. Process for the fusion of metal oxides, P (9) 270*b*. Process for maintaining straightness in extruded ceramic sections, P (10) 317*b*. Process for making graphite, P (8) 241*a*. Process for making porous sodium fluoride pellets, P (6) 183*e*. Process of making uranium mononitride nuclear fuel, P (1) 14*a*. Process for separating beryllium values from aqueous solutions, P (4) 105*f*. Process of vapor coating nuclear fuel with beryllium oxide and carbon, P (11) 340*i*. Production of stoichiometric uranium monocarbide from a uranium fluoride, P (1) 14*f*. Pyrolytic graphite and nuclear fuel particles coated therewith, P (4) 97*f*. Rare earth suboxides, P (8) 258*g*. Refractory metal dispersion, P (2) 48*a*. Selective decladding of nuclear fuel elements, P (1) 14*c*. Semiconductor detector method and apparatus, P (8) 246*e*. Separation of trivalent 4*f* rare earths from molten fluoride compositions with UF_3, P (7) 205*e*. Transistor having constant gain over a broad temperature range, P (6) 178*i*. Tungsten-rhenium coated ceramic reactor fuel particles, P (11) 341*b*. Urania sol forming method in the presence of formic acid and a palladium-on-thoria catalyst, P (4) 97*j*. Uranium carbide-plutonium phosphide as a reactor fuel, P (4) 97*j*. X-ray diffraction camera employing two curved crystal transmission type monochromators, P (7) 213*e*.

United States Borax & Chemical Corp. Method for bonding aluminum to borides, P (6) 174*f*. Process for producing noncaking borax, P (8) 251*e*. Production of titanium diboride P (2) 48*b*. Sodium calcium metaborate, P (10) 318*h*.

United States Bureau of Mines. Minerals Yearbook, 1966 (Vols. I–II) Metals, Minerals, and Fuels, B (8) 260*b*.

United States Concrete Pipe Co. Hole cutting apparatus for pipe sections, P (5) 131*c*.

United States Gypsum Co. Apparatus for distributing melt and forming fibers therefrom, P (9) 264*g*. Apparatus for forming fibers, P (6) 170*b*. Calcining kettle discharge apparatus, P (7) 194*i*. Combustion chamber burner and a method for its operation, P (4) 104*a*. Fiber attenuating apparatus, P (2) 40*f*. Fiber attenuating burner, P (6) 170*j*. Gypsum composition having dehydration resistant characteristics, P (10) 296*b*. Method of making a stable electrically conductive sheet and product thereof, P (1) 18*e*. Method of producing gypsum articles having improved strength to density ratio, P (4) 92*e*.

United States Perlite Corp. Apparatus for producing acoustical [perlite] tile, P (3) 63*a*.

United States Steel Corp. Basic refractory furnace structure, P (11) 339*i*. Determination of vapor coating rate by X rays emitted from said vapor, P (6) 181*d*. Kiln, P (11) 348*g*. Method of operating a blast furnace to produce pig iron and cement slag, P (7) 194*k*. Stockline lining for a blast furnace, P (4) 97*i*.

United States Stoneware, Inc. Drum roller, P (6) 179*c*. Drum-tumbler holder, P (7) 211*b*. Mill-jar support, P (3) 75*b*. Vibratory mill, P (2) 57*c*, P (10) 312*i*.

Universal Oil Products Co. Catalyst manufacture, P (8) 250*k*. Hydrocracking nitrogen-contaminated hydrocarbon charge stocks, P (4) 105*d*. LPG-reforming process in the presence of sulfur and catalyst comprising platinum, alumina, and a molecular sieve, P (5) 148*d*. Method of catalyst preparation, P (1) 25*d*. Method for preparing high rate zeolitic molecular sieve particles, P (2) 56*i*. Method for preparing spherically shaped crystalline zeolite particles, P (9) 270*e*. Method for producing molecular sieve zeolite particles, P (3) 78*d*. Particle classifying-separating apparatus, P (5) 144*d*. Preparation of crystalline zeolite particles, P (4) 105*c*. Production of alumina, P (1) 14*e*. Production of attrition resistant alumina particles, P (7) 215*f*. Treatment of combustible waste products and catalyst therefor, P (5) 149*c*. Zeolite and method for making the improved zeolite, P (5) 149*d*.

Universal Refractories Corp. Hot top bottom ring and method for forming same, P (7) 204*i*.

Unoki, H. See Sakudo, T.

Unoki, H., and Sakudo, T. Electron spin resonance of Gd^{3+} and Eu^{2+} in $KTaO_3$, (10) 320*e*.

Unzicker, A. E., and Zajac, B. J. Method and apparatus of controlling thin film deposition in a vacuum, P (8) 245*c*.

Upadhyaya, V. G., Mulfinger, H. O., and Dietzel, A. Study of the gases evolved or formed during enameling and the influence of gases on the enameling of cast iron, (4) 92*j*.

Upp, E. L. Proving liquid and gas flow measuring devices, (8) 248*d*.

Upton, L. O. Sealing porosity of fiber faceplates by yttrium resinate, P (7) 199*a*.

Urbain, G., and Rouannet, M. Secondary reference points on the International Practical Temperature Scale—experimental determination of the melting point of alumina, (1) 32*a*.

Urban, C. Spraying by plasma gun, (6) 166*c*.

Uryu, N., Skaiyo, J., Jr., and Friedberg, S. A. Crystal-field effects in $CoCl_2 \cdot 6H_2O$, (9) 280*b*.

Ushakov, D. F. See Milyukov, E. M.; Zorina, M. L.

Ushio, M., and Noda, T. Measurement of pressure distribution in a simple press by the use of quartz glass powder, (11) 346*f*.

Uskov, I. A. See Uskova, E. T.

Uskova, E. T., Vasil'yev, N. G., and Uskov, I. A. Ionic exchange on hydrogen and aluminum forms of kaolinite, (11) 353*h*.

Usvitskii, M. B. Study of thermal properties of glass in the anomalous interval by DTA, (10) 299*e*.

Utakoji, M., and Imaoka, M. Method of hot extrusion of metallic articles, P (9) 265*c*.

Utolina, L. S. See Marinina, V. T.

Uy, O. M. See Ficalora, P. J.

Uzberg, A. I. Unfired volume-stable magnesite-chromite refractories, (9) 269*h*.

Vaaler, L. E. Graphite electrolytic anodes, (2) 49*d*. See Sloka, W. E.

Vaart, H. van de, and Smith, H. I. High efficiency polarization reversal of magnetoelastic waves in YIG by optical-contact bonding of YAG disks, (3) 71*b*.

Vach, J., and Suesser, V. Electric glass furnace, P (7) 198*j*.

Vacherand, C. See Prod'homme, L.

Vachuska, J. See Landsperaky, H.

Vagh, A. S. See Joshi, M. S.

Vagnard, G., and Washburn, J. Plastic deformation of cuprous oxide, (3) 85*a*.

Vahldiek, F. W. Electrical resistivity, elastic modulus, and Debye temperature of titanium diboride, (8) 253*c*. Microstructure of single-crystal titanium carbide, (8) 255*e*. Phase transition of titanium dioxide under various pressures, (3) 85*e*.

Vahldiek, F. W., Mersol, S. A., and Lynch, C. T. Dislocation etch pits and phase relations in dimolybdenum carbide single crystals, (9) 281*d*.

Vaidya, S. N. See Viswanathan, B.

Vakhovskaya, M. R. See Kreimer, G. S.

Val, C., Trouve, J., and Accary, A. Effect of dispersed metallic uranium or uranium dicarbide on the mechanical properties of uranium monocarbide, (6) 172*i*.

Valdsaar, H. Thermoelectric modules, P (4) 101*e*.

Valentich, J. Rate of fracture propagation in porcelain, (1) 15*f*.

Vallee, B. L., and Fuwa, K. Spectroscopy apparatus for transmitting light longitudinally of a spectral flame, P (8) 249*b*.

Valletta, R. M. See Hallen, R. L.

Valley Co., Inc. Process of making an article having a hard carbide, boride, or silicide outer region, P (2) 47*g*.

Valspar Corp. Method of plastering wall surfaces and joint sealing compound used therein, P (8) 229*b*.

Valtere, A. Ya. See Toropov, N. A.
Valtschev, A. J., and Valtscheva, T. N. Protecting carbon materials from oxidation, P (2) 48*b*.
Valtscheva, T. N. See Valtschev, A. J.
Vanadium Corp. of America. Process for making vanadium carbide briquets, P (1) 14*b*.
Van Asselt, R. L. Indium doped pickup tube target, P (2) 51*e*.
Van Bemst, A., and Delaunois, C. Role of titanium oxide in the system silica-titanium oxide-potassium oxide (I) viscosity measurements, (7) 197*e*; (II) expansion measurements, (11) 335*c*.
Van Bragt, H. E. Glass valve for scientific purposes, P (5) 130*b*.
Van Buren, C. E., and Hirsch, H. H. Hydrostatic pressing of powders, B (3) 89*h*.
Vance, F. P. Statistical properties of dry blends, (9) 275*h*.
Vanden Heuvel, R. C. Occurrence of sepiolite and attapulgite in the calcareous zone of a soil near Las Cruces, New Mexico, B (7) 224*g*.
Van Den Hul, H. J., and Lyklema, J. Determination of specific surface areas of dispersed materials by negative adsorption, (9) 276*a*.
Vanderpool, C. D., and Chiola, V. Lamps having a molybdenum phosphate phosphor, P (4) 100*f*. Process for purifying molybdenum trioxide, P (10) 318*c*.
Vanderslice, T. A. Process of coating diamond with an adherent metal coating using cathode sputtering, P (2) 52*d*. See Hull, E. H.
Vanderveldt, H., and Liebowitz, H. Carrying capacity and fracture of notched glass fiber composite columns, (10) 297*d*.
Van der Voort, F. H. See Macdonald, A. M. G.
Vandeven, V., Galy, J., Pouchard, M., and Hagenmuller, P. Structural evolution as a function of temperature of some tungsten bronzes low in the inserted element, (1) 32*h*.
Van Dreser, M. L. High magnesia product and process of making the same, P (7) 204*g*.
Van Drunen, C. J. See Bradhurst, D. H.
Van Dyke, B. See Arnold, A. J.
Van Dyke, D. See Arnold, A. J.
Vanik, M. C. See Hurley, F. R.
Van Oberbeek, A. J. W. M. Field-effect transistor with improved transmission admittance, P (3) 72*g*.
Van Rutten, F. See Cometta, C.
Van Ruyven, L. J., and Williams, F. D. Valence-band bending to the Fermi level and radiative recombination in ZnS with liquid electrodes, (11) 358*c*.
Van Sciver, W. J. See Kunz, A. B.
Van Sickler, R. H., and Dagley, J. F. Filament supports for tubular incandescent lamps, P (9) 265*c*.
Van Thyne, R. J., and Rausch, J. J. Oxidation-resistant beryllium articles and process of making, P (1) 13*e*.
Van Uitert, L. G. See Bonner, W. A.; Geusic, J. E.; Grodkiewicz, W. H.; Rubinstein, C. B.
Van Uitert, L. G., Levinstein, H. J., Rubin, J. J., Capio, C. D., Dearborn, E. F., and Bonner, W. A. Some characteristics of niobates having filled tetragonal tungsten bronze-like structures, (5) 158*c*.
Van Vlack, L. H. Microstructures of refractories, (2) 45*c*. See Moore, J. W.; Scruggs, D. M.
Van Vleck, J. H. Evolution of crystal field parameters for rare earth salts, B (10) 329*g*.
Van Wazer, J. R. See Riess, J. G.
Van Zandt, L. L., Honig, J. M., and Goodenough, J. B. Resistivity and magnetic order in Ti_2O_3, (11) 356*f*.
Vargin, V. V. (editor). Technology of Enamels, B (2) 60*h*. See Byurganovskaya, G. V.
Vargin, V. V., and Kheifets, V. S. Crystalline phases in the glass systems Na_2O-B_2O_3-ZrO_2-SiO_2, (3) 63*h*.
Varian Associates. Low dielectric loss metallizing paint composition having a reduced sintering temperature, P (2) 51*f*. Low temperature metallizing paint and method of making same, P (2) 38*c*. Metal-to-ceramic seal for high voltage electron tubes and methods of fabrication, P (11) 344*b*. Rare earth fluoride capacitors, P (7) 210*c*. Thermal connector for electron tubes and the like, P (4) 97*i*.
Varley, E. R. Sillimanite—Andalusite, Kyanite, Sillimanite, B (11) 358*h*.
Varma, C. K. R. Etch pits and trigons on diamond, (8) 253*f*. Studies on natural diamonds of the dodecahedral form, (8) 257*g*.
Varon, J., Schiavo, J., and Janus, T. P. Ultrathin Al_2O_3 support films for electron microscopy, (1) 23*j*.
Varsanyi, F. L. Laser device using Nd:$PrCl_3$, P (3) 73*b*.
Varshneya, A. K. See Cooper, A. R.
Vasantasree, V., Pantony, D. A., and Hocking, M. G. Gastight thermobalance-load seal, (2) 54*e*.
Vascik, R. A. See Babcock, E. W.
Vasil'eva, G. A. See Golubev, B. P.
Vasil'kova, I. V., and Perfilova, I. L. Enthalpy of formation of M_3VCl_6 and M_2VCl_5, (10) 321*b*.
Vasilos, T. See Wuensch, B. J.
Vasilos, T., and Passmore, E. M. Effect of microstructure on creep mechanisms in ceramics, B (4) 121*f*.
Vasil'yev, N. G. See Uskova, E. T.
Vasin, I. G., and Pozdnjakov, P. G. Quartz resonator, P (7) 210*c*.
Vasko, A. Examination of internal defects in chalcogenide glasses by infrared defectoscopy methods, (6V) 167*e*.
Vasni, G. N. See Novikov, V. M.
Vassell, W. C. See Cole, T.
Vassiliev, A. See Hildebrandt, M.
Vaught, L. M., Newport, J. J., III, and Osborn, O. Vermicular graphite structures and process of making, P (9) 270*e*.
Vaugoyeau, H. See Guinet, P.
Vautier, M. Ferrites, (9) 272*a*. Magnetic properties of ceramics, (6) 176*c*.
Vaz, J. E., and Zeller, E. J. Thermoluminescence of calcite from high gamma radiation doses, (3) 88*c*.
Vdas, G. R., and Krishnamurthy, P. Rich fluorite deposit at Hingoria, Broach, Gujarat State, (10) 317*j*.
Veale, C. R. Kinetics of the oxidation of tellurium, (5) 154*i*.
Veaux, M., and Marchal, F. Magnetic forming apparatus, device, and method for making deep grooves on parts made of conducting materials, particularly tubes made of metal or ceramic-metal materials, P (2) 47*e*.
VEB Guss- und Farbenglaswerke Pirna-Copitz. Apparatus for continuous manufacture of continuous profiled glass members, P (1) 8*h*.
VEB Schaumglaswerk Taubenbach. Method for making foam glass, P (2) 41*e*. Production of foam glass, P (4) 95*c*.
Vecchi, G., and Vecchi, L. Determination of soluble sulfates in fired ceramic products, (8) 236*e*.
Vecchi, L. See Vecchi, G.
Vecchio, M., Fattore, V., and Cammarata, I. Process for preparing spheroidal fluorinating agents containing calcium fluoride suitable for fluid beds and product resulting therefrom, P (6) 183*a*.
Vecht, A. Methods of activating and recrystallizing thin films of II-VI compounds, B (8) 260*e*.
Vedam, K., and Schmidt, E. D. D. Variation of refractive index of MgO with pressure to 7 kbars, (11) 358*d*.
Vedder, W., and McDonald, R. S. Vibrations of the OH ions in muscovite, (5) 159*i*.
Veduta, A. P., and Kirsanov, B. P. Variation of the refractive indices of liquids and glasses in strong ruby laser fields, (10) 327*e*.
Veenemans, B. See Dijkmeijer, H. E.
Veevers, J. J. Combined analysis of size, shape, and compositional mode of grains in altered sandstones, (5) 144*i*.
Veevers, K. See Hickman, B. S.; Hilditch, R. J.
Veevers, K., and Rotsey, W. B. Effect of machining on the modulus of rupture of extruded and sintered BeO, (5) 131*j*. Mechanical properties of dispersions of thoria in beryllia, (1) 30*c*.
Veevers, K., Whatham, J. P., and Wright, W. J. Study of variables in the mechanical testing of BeO, (4) 96*i*.
Veigele, W. J. ^{71}Ga quadrupole interaction in α-Ga_2O_3 powder, (5) 152*i*.
Veigele, W. J., Bevan, A. W., Jr., and Tantilla, W. H. Temperature dependence of the Al nuclear quadrupole interaction in ruby, (5) 159*e*.
Veinberg, T. I., Pishch, I. V., and Kirova, S. M. Optimum quantity of decolorizers in tableware glass, (8) 233*a*.
Veiser, I., Szabo, A., Petri, L., Mircea, S., Sorocopud, L., Popa, S., Bolboceanu, V., Guriuc, V., Corneanu, A., and Ivaniov, W. Technological study of silicoaluminous refractory raw materials of Romania, (9) 269*c*.
Vela, P. See Russell, B.
Velde, B. Effect of chemical reduction on the stability of pyrophyllite and kaolinite pelitic rocks, (9) 281*g*. Mixed-layer mineral associations in muscovite-celadonite and muscovite-chlorite joins (extended abstract), B (7) 224*a*.
Velden, P. F. van. Equilibrium between (Li,Na,K,Mg) carbonate melt, gaseous CO_2, and MgO, (7) 217*a*.
Velikova, M. I. See Neiman, O. V.
Vemuri, V. Ceramic titanate rectifying barriers, (5) 137*i*.
Venable, R. L., Wade, W. H., and Hackerman, N. Heats of immersion (VIII) differential heats of adsorption as a function of particle size for the alumina-water system, (11) 353*i*.
Vendelin, G. D. Surface-oriented high frequency diode, P (11) 345*a*.
Vendrell, J. R., Jr. See Kondner, R. L.
Venet, P. See Huschka, H.
Venkatachalam, S. See Halasyamani, P.
Venkatachalam, S., and Mallikarjunan, R. Depression of quartz with ascorbic acid, (5) 143*g*.
Ventel, V. See Gheorghiu, G.
Verbaere, A. R. Apparatus for the separation of materials of different densities, P (1) 20*c*.
Verdier, A. L. Grinding of materials in grinders having rolls with stepwise-increasing speeds, P (6) 179*d*.
Verdone, J. See Dautreppe, D.
Verduch, A. G. See Garcia Verduch, A.
Veres, F. Electrically conductive solder glass, P (10) 300*g*.
Verghese, P. C., and Kumar, J. A. Results of tests on ultimate strength of brick piers made from handmolded brick, (2) 43*a*.
Vergnon, P. Compressibility of powders, (1) 27*e*.
Vergnon, P., and Juillet, F. Sintering mechanisms, (1) 32*b*.
Vergnon, P., Juillet, F., and Teichner, S. J. Effect of rate of temperature rise on the sintering of pure alumina homodispersed particles, (1) 28*a*. Porous bodies from alumina microspheres, (10) 303*e*.
Verhaegen, G See Richards, W. G.
Verhaegen, G., and Richards, W. G. Valence levels of beryllium oxide, (10) 327*e*.
Verhaegen, G., Stafford, F. E., and Drowart, J. Mass-spectrometric study of the systems boron-carbon and boron-carbon-silicon, (5) 154*d*.
Verhagen, J. G. See Tichelaar, G. W.
Verheyden, L. See Klein, K.
Verkhoglyadova, T. S. See Dvorina, L. A.; Samsonov, G. V.
Verkhoglyadova, T. S., Vivchar, O. I., and Gladyshevskii, E. I. Solubility of the disilicides of the transition metals in $MoSi_2$ and WSi_2, (11) 339*h*.
Verlotskii, A. A. See Galdina, N. M.
Verma, G. S. See Gaur, N. K. S.
Vernay, M. Rotary drum filter, P (1) 20*f*.
Verneker, V. R. P., and Blais, M. Mechanism of uptake of impurities by azide crystals, (7) 219*a*.
Vernik, E. B. See Katrus, O. A.
Vernon, R. H. Microstructures of high-grade metamorphic rocks at Broken Hill, Australia, (9) 284*b*.
Verreries Pochet et du Courval. Electric glass-making furnace, P (7) 198*a*.
Verson Mfg. Co. Pressure forming system, P (7) 211*g*.
Verstappen, G. See DeMeester, P.
Vertes, P. See Huet, H.
Vesuvius Crucible Co. Exothermically heated molten metal pouring nozzle, P (10) 304*c*. Nozzle for a bottom pour ladle for molten metal, P (11) 340*d*. Stopper for a ladle or similar receptacle, P (2) 48*b*.
Vetrocoke, S.p.A. See Montecatini Edison S.p.A.
Veverka, V. C. See Platt, R. O.
Vickery, R. C. Cermet electrical resistance material and method of using the same, P (1) 12*j*.
Victory Engineering Corp. Method of making a thermistor, P (4) 100*c*, P (5) 142*b*. Method of manufacturing thin film thermistors, P (10) 310*c*.
Vidal, J. P. See Bondy, C.
Vidavskii, L. M., Byakhova, N. I., and Ippolitova, E. A. Enthalpy of the reaction of gamma UO_3 with fluoric acid and the enthalpy of formation of gamma UO_3, (9) 282*d*.
Vie, G. Portuguese raw material resources for the ceramic industry, (9) 278*j*.
Viehmann, W. See Chu, K. C.
Vielhaber, E., and Hoppe, R. Oxyzincates of alkali metals, (5) 156*h*.
Vigier, P. See Dautreppe, D.
Vigne, J. Quality control policy in the brick and tile industry, (3) 66*h*.
Vijayakar, S. V., and Majumdar, K. K. Role of high tension separation in the beneficiation of beach sand minerals, (1) 19*j*.
Villeneuve, G. See Pouchard, M.
Villers, G., Gibart, P., Druilhe, R., and Burlet, P. Magnetic oxides crystallizing in the rutile structure, (11) 354*j*.
Vilnat, J. Application of lasers to spectral analysis, (7) 211*i*. Arc emission spectrography—applications to silicates, (6) 180*e*. See Pagano, M.
Vilnat, J., Liodec, N., and Debras-Guedon, J. Spectrographic determination of Cr and Ni in steel using a laser as excitation source, (10) 315*e*.
Vilnat, J., and Pagano, M. Colorimetric tests in ceramics, (10) 313*b*.
Vince, P. M. Electrical insulator having improved surface electrical stress distribution, P (5) 137*d*.
Vincenzini, P. Glass-ceramics (I, II), (8) 232*d*.
Vingas, G. J., and Zrimsek, A. H. Thermal stability of bentonites in foundry molding sand, B (7) 225*b*.
Vinogradov, B. N. See Budnikov, P. P.
Vinogradov, G. A. See Katrus, O. A.
Vinogradova, G. Z. See Dembovskii, S. A.
Vinson, P. Powder compacting method, P (1) 20*e*.
Visman, J. Apparatus for specific gravity separation of solid particles, P (3) 77*j*. Cyclone apparatus, P (5) 144*e*.
Visser, J. E., and Vrolijks, M. H. M. Heat and pressure glass bonding of spaced magnetic head portions by forming and using glass overflow channels, P (7) 209*a*.
Vissy, L. Refractories for glass melting tanks, (1) 12*c*.
Viswanathan, B., Vaidya, S. N., and Gopal, E. S. R. Behavior of specific heat, thermal expansion, and isothermal compressibility near ferroelectric transitions, (10) 319*d*.
Viswanathan, K. V. See Madavan, T. R.
Vitkovskaya, E. V. See Yastrebova, L. S.
Vitman, F. F., Pugachev, G. S., Pukh, V. P., and Shenberg, N. N. High strength of sheet glass after etching in hydrofluoric acid, (1) 6*c*.
Vitramon, Inc. Bismuth-free barium titanate ceramic compositions, P (5) 140*d*. Method of calibrating electrical components, P (10) 310*d*.
Vitreous Steel Products Co. Radiant heating panels and resistive compositions for the same, P (11) 332*j*.
Vitta Corp. Method of applying uniform thickness of frit on semiconductor wafers, P (6) 177*i*.
Vivaldi, J. L. M. See Martin Vivaldi, J. L.
Vivchar, O. I. See Verkhoglyadova, T. S.
Vlasov, A. S. See Skidan, B. S.
Vlasov, V. G. See Beketov, A. R.
Voboril, M. See Imris, P.; Landspersky, H.
Vogel, F. L., Jr. See Garnache, R. R.
Vogelpohl, R. L. Load-bearing mounting elements for attachment to glass surfaces, P (8) 235*e*. Pressing flanged glass articles, P (9) 265*j*.

Volarovich, M. P., and Meckler, Yu. B. Problem of correlation between hydrodynamic and electrical coefficients of tortuosity for porous media, (5) 148*f*.
Voldan, J. Monomineral crystallization of melted basalts, (11) 338*a*. Raw materials for the rock-melting industry, (5) 148*f*.
Volk, V. V., and Jackson, M. L. Inorganic pH dependent cation exchange charge of soils, B (6) 191*j*.
Volk, W. Reduction of metallic oxides, P (8) 251*h*.
Volkonskii, B. V., and Shteiert, N. P. Cement for seismic-stable construction, (5) 124*g*.
Volkov, O. S. See Larionova, Z. M.
Volkov, O. S., Karlova, L. G., Polak, A. F., and Ratinov, V. B. Hydration kinetics of cement constituting minerals, (2) 36*c*.
Volkova, N. M., Gel'd, P. V., and Alyamovskii, S. I. Phase transformation of the higher carbide of vanadium, (9) 285*i*.
Vollmer, H., and Huchler, K. Furnace for treatment of wax-bonded sinterable preforms, P (4) 104*b*.
Volodina, D. A., and Kozlova, R. F. Microspectral method for investigating the interaction between solders and metallized coatings on ceramic materials, (10) 307*e*.
Volovets, L. D., and Pugachev, G. S. Measurement of the strength of sheet glass on a flexible plate, (10) 298*c*.
Vol'ski, V., Politan'ska, U., Poravski, B., and Bokhyn'ska, A. Ferromagnetic phases in the products of thermal decomposition of nickel ferricyanide, (10) 321*d*.
Volterra, V. See Feldmann, T.
Volynets, F. K. See Donskoi, A. V.
Vonada, P. A. See Stachiw, J. D.
Vondra, B. L., and Ward, J. A., Jr. Method for producing uranium tetrafluoride, P (8) 241*c*.
Von Pless, J. A. Coordination in cleaning, (9) 262*h*.
Vorce, L. H., and Belanger, L. G. Abrasive disk, P (8) 227*g*.
Vorob'eva, M. A. See Dregoi, I.
Vorob'eva, O. V., and Bessonova, E. S. Mechanical properties of glasses with films of iron oxide, (10) 298*d*.
Voronin, A. V. See Budnikov, P. P.; Matveev, M. A.
Voronin, K. K. See Donskoi, A. V.
Voron'ko, Yu. K., Dmitruk, M. V., Kaminskii, A. A., Osiko, V. V., and Shpakov, V. N. Continuous induced radiation from a LaF_3-Nd^{3+} laser at room temperature, (10) 306*i*.
Voross, L., and Piller, F. Determination of the producibility of double-layer stoneware floor tile by laboratory methods, (2) 42*h*.
Vos, G. See Conti, R.
Vos, J. C. de. Rationalization and mechanization of the ceramic industry, B (9) 291*g*.
Voskuil, J. Study of the flow of gases in a chamber brick kiln by means of water and air models, B (9) 291*f*.
Voter, R. C. Multicrystalline diamond abrasive composition and article, P (8) 227*g*.
Vratny, F., Vromen, B. H., and Harendza-Harinxma, A. J. Anodic tantalum oxide dielectrics prepared from body-centered-cubic tantalum and beta tantalum films, (3) 70*i*.
Vrbenska, J. See Malinovsky, M.
Vries, J. de. Survey of common industrial dryers, (11) 348*g*. See Blasse, G.
Vrolijks, M. H. M. Dense nickel-zinc ferrites and their use in magnetic heads, (4) 98*h*. See Visser, J. E.
Vromans, P. H. G. M. See Kwestroo, W.
Vromen, B. H. See Vratny, F.
Vrugt, J. W. ter. See Wanmaker, W. L.
Vuillard, G., and Walder, A. Surface boronation of zirconium, (1) 4*c*.
Vukovich, M., Jr. Fast firing vs. conventional firing, B (3) 89*d*.
Vydrik, G. A. See Luginina, I. G.; Medvedovskaya, E. I.
Vysotskaya, V. N., and Kurilovich, T. I. Determination of silica in sparingly soluble fluoride slags, (10) 314*b*.

Waal, H. de. Internal friction of a sodium silicate glass after ion exchange, (11) 334*g*.
Waard, D. de. Occurrence of garnet in the granulite facies terrane of the Adirondack Highlands and elsewhere—an amplification and a reply, (3) 84*b*.
Wacher, P., Bracco, D. J., and Palilla, F. C. Particle size distribution of yttrium vanadate phosphors as a function of preparation parameters, (5) 139*e*.
Wachtel, A. Sb^{3+} and Mn^{2+} activated calcium halophosphate phosphors from flux-grown apatites, (7) 208*a*.
Wachtman, J. B., Jr. See Franklin, A. D.; Peiser, H. S.
Wachtman, J. B., Jr., Brower, W. S., and Farabaugh, E. N. Elastic constants of single crystal calcium molybdate ($CaMoO_4$), (7) 217*f*.
Wacker-Chemie G.m.b.H. Method of preparing asbestos sheets from aqueous slurries containing silicone resin emulsions, P (11) 340*c*.
Wackman, P. H., Hirthe, W. M., and Frounfelker, R. E. Cohesive energy of TiO_2 (rutile), (8) 252*f*.
Wada, M. Carbon film resistor composition, P (1) 17*a*.
Wada, T. See Nishijima, T.
Waddington, T. C. Ionic radii and the method of the undetermined parameter, (3) 82*d*.
Wade, W. H. Coordination number of small spheres, (11) 350*j*. See Venable, R. L.
Wadham, A. See Bloor, D.
Wadham, E. See Knott, R. D.
Wadlinger, R. L., Rosinski, E. J., and Plank, C. J. Synthetic zeolite, P (7) 215*f*.
Wadsworth, M. E. See Holt, J. B.
Waestlund, G. Cement and concrete research—a general review and results from the Cement and Concrete Institute of Sweden, (2) 36*e*.
Wagenfeld, H. See Klein, A. G.
Wagner, C. W. Cold-palladium conductor compositions and conductors made therefrom, P (1) 17*j*.
Wagner, G. R. See Feldman, D. W.
Wagner, H. B. Hydration-limited polymer-modified hydraulic cements, (4) 92*d*.
Wagner, J. B., Jr. See Fueki, K.; Swaroop, B.
Wagner, J. W., and Woolley, J. C. Phase studies of the $Pb_{1-x}Sn_xTe$ alloys, (4) 114*c*.
Wagner, P. E. See Lampe, D. R.
Wagner, P. R. See Crowder, B. L.
Wagner, R. S. See Ellis, W. C.
Wagner, S. E. See Miller, G. L.
Wagner Electric Corp. Thermionic emissive cathode, P (5) 143*d*.
Wagstaff, F. E. Crystallization kinetics of internally nucleated vitreous silica, (9) 280*b*. Crystallization resistant vitreous silica formed by the addition of silicon to silica, P (6) 170*h*. See Charles, R. J.
Wahi, F. M., and Grim, R. E. High-temperature DTA and X-ray diffraction studies of reactions, B (6) 191*h*.
Wahlbeck, P. G. See Gilles, P. W.
Wahlbeck, P. G., and Gilles, P. W. Dissociation energy of TiO(*g*) and the high-temperature vaporization and thermodynamics of the titanium oxides (II) trititanium pentoxide, (11) 351*e*.
Waidelich, W. See Peisl, H.
Wainio, A. W. Electric discharge lamp having a resiliently suspended fragile member therein that decreases the diffusion length of the discharge, P (7) 208*c*.
Waintal, A., and Chenavas, J. Transformation under high pressure of the hexagonal form of $MnT'O_3$ (T' = Ho, Er, Tm, Yb, Lu) to a perovskite form, (1) 33*j*.
Waintal, A., and Gondrand, M. Transformation under very high pressure and at very high temperature of the compounds $SmLiO_2$, $EuLiO_2$, $GdLiO_2$, and $TbLiO_2$, (1) 33*a*.
Waisberg, J. Bottles or like containers, P (1) 8*e*.
Wajda, E. S. See Dhaka, V. A.
Wakabayashi, J. Paramagnetic resonance spectrum of Fe^{3+} in calcite, (5) 156*a*.
Wakao, Y., and Sato, Y. Study of binders of molding sand (I) effect of heating temperature on the quality of bentonites, (11) 339*a*.
Wakatsuki, M. New catalysts for synthesis of diamond, (5) 155*d*.
Wakefield, J. See Freck, D. V.
Wakelyn, N. T. Thermal control coating, P (11) 333*a*.
Waku, S. Barium titanate (I), (5) 137*h*. Studies on the boundary layer ceramic capacitor, (5) 140*a*.
Walchhuetter, U. Friction and screw press for the manufacture of ceramic articles, P (4) 102*b*.
Waldbaum, D. R. Enthalpies of fusion of $KAlSiO_4$ and $NaAlSiO_4$, (2) 58*g*.
Waldeck, W. F. Process for slaking high calcium quicklime, P (5) 125*h*.
Walder, A. See Vuillard, G.
Waldron, G. W., Jr., and Krimbill, H. W. Production of magnesium hydroxide, P (5) 149*c*.
Walenczak. Z. Geochemistry of gallium and aluminum in quartz, (7) 217*h*. See Smulikowski, K.
Walker, A. See Carnall, W. T.
Walker, C. T. Evaluation of boron as a paleosalinity indicator and its application to offshore prospects, (9) 282*f*.
Walker, D. E. Y. Oxidation of uranium dioxides, (1) 30*i*.
Walker, D. G. Electron irradiation of BeO, (2) 44*f*. Metal processing prior to porcelain enameling, (9) 263*a*. See Chute, J. H.; Hickman, B. S.; Price, G. H.
Walker, D. G., Mayer, R. M., and Hickman, B. S. X-ray diffraction studies of irradated BeO, (2) 46*c*.
Walker, E. G. See Holdridge, D. A.
Walker, E. G., and Holdridge, D. A. Quantitative estimation of cristobalite and quartz, (10) 315*a*.
Walker, G. F. See Graham, J.
Walker, G. F., and Garrett, W. G. Silicate layer minerals and [grease] products made therefrom, P (3) 78*c*.
Walker, L. See Martin, G.
Walker, L. M. See Guereca, R. A.
Walker, R. E. See Kirchner, H. P.
Walker, W. C. See Roessler, D. M.
Wall, C. J. Agglomerative drying, P (10) 312*a*.
Wall, H. A. Consistency measuring apparatus, P (5) 147*a*.
Wall Colmonoy Corp. Diamond abrasive matrix, P (6) 163*i*.
Wallace, G. B., and Olsen, O. J. Deformation moduli of rocks, B (3) 90*b*. Foundation testing techniques for arch dams and underground powerplants, B (3) 90*b*.
Wallace, R. W., and Criss, G. H. Thermal conductivity of castable refractories in relation to bulk density, (3) 68*f*.
Wallace, T. C. See Krikorian, N. H.
Wallace, W. E. See Schumacher, D. P.
Wallace, W. K. Clay products and the like, P (7) 214*j*.
Wallace, W. M. Filtration, P (7) 211*b*.
Wallen, E. O. L. Screen, P (7) 211*g*.
Wallenstein, M. B. See Brady, E. L.
Wallmark, J. T. Insulated-gate field-effect transistor, P (6) 177*e*. See Gordon, I.
Wallner, W. Arc welding electrode providing welds having high yield and rupture value, P (1) 4*f*.
Wallouch, R. W. Treat solution for rendering carbonaceous articles oxidation resistant, P (2) 48*d*.
Walpole, L. J. Elastic field of an inclusion in an anisotropic medium, (9) 281*g*.
Walrond, J. E. Zinc oxide compositions and method of making them, P (1) 26*d*.
Walsh, D. J. See Malbon, R. M.
Walter, F. Plasma spraying of oxide ceramic protective coatings and their properties, (1) 15*e*.
Walter, J. See Troup, G. J.
Walter, J., and Paar, V. F. Ceramic uses of leucophyllite, (6) 182*f*.
Walter, J. L. Glass-doped iron—a model for doped tungsten, (9) 262*h*.
Walters, E. L., and Boicey, J. H. Testing apparatus, P (8) 236*a*.
Walters, E. L., and McCown, W. E. Glass breaking apparatus, P (6) 170*j*.
Walters, L. C., and Grace, R. E. Diffusion of point defects in strontium titanate, (3) 71*c*. Formation of point defects in strontium titanate, (3) 71*i*.
Walters, R. B. Projection lamp with multiple reflectors, P (8) 236*a*.
Walther, F. H., Jr., and Ryan, J. R. Continuous casting apparatus with improved nozzle composition, P (3) 68*a*.
Walton, H. F. Ion exchange chromatography, (10) 314*e*.
Walz, A., and Mayer, M. Theoretical and experimental studies of the manufacture of mineral and glass wool in blast nozzles (I, II), (8) 234*c*.
Wampler, J. M. See Pecuil, T. E.; Weaver, C. E.
Wang, F. E., Syeles, A. M., Clark, W. L., and Buehler, W. J. Method for growing single crystals, P (2) 51*j*.
Wang, R., Bodnar, R., and Steinfink, H. Structure of $YbSb_2$, a $ZrSi_2$ isotype, (6) 189*i*.
Wang, R., Steinfink, H., and Bradley, W. F. Crystal structure of lanthanum telluride and tellurium-deficient neodymium telluride, (5) 150*b*.
Wang, S., and Thomas, G. Spin-wave interaction with a laser beam in YIG, (1) 17*b*.
Wangard, W., II. See Hendron, J. A.
Wanie, W. Ceramic substrates colored coating process, P (5) 144*e*. Drying and firing in the porcelain industry, (7) 206*a*. Granulated zinc white for glazes, enamels, and ceramic colors, (7) 206*g*. Manufacture of ceramic coloring material containing zinc oxide, P (7) 214*e*.
Wanklyn, J. N. See Harrop, P. J.
Wanless, L. Technique of particle size analysis of zircon using the Coulter counter, (10) 315*i*.
Wanmaker, W. L. See Bril, A.
Wanmaker, W. L., Bril, A., and Vrugt, J. W. ter. Fluorescent properties of terbium-activated alkaline earth alkali borates, (4) 110*b*.
Wappling, R. Versatile Moessbauer spectrometer, (5) 146*h*.
Ward, J. A., Jr. See Vondra, B. L.
Ward, J. F. See MacDonald, R. J.
Ward, J. M. See Squire, G. L.
Ward, L., and Nag, A. Theoretical study of the sensitivities of some normal incidence methods for measuring the optical constants and thicknesses of thin films, (6) 190*a*.
Ward, M. E. Gas burner, P (10) 317*a*.
Ward, R. See Callaghan, A.; Donohue, P. C.; Patterson, F. K.
Ward, R. G. See Gaskell, D. R.
Ward, W. T. See Hill, D. G.
Ware, F. Fire-resistant cementitious plaster composition, P (6) 165*j*.
Warga, J. de. Mechanics and potential applications of semiconductor rectifiers, (1) 16*k*.
Waring, J. L., and Roth, R. S. Effect of oxide additions on the polymorphism of tantalum pentoxide (system Ta_2O_5-TiO_2), (9) 281*a*.
Warkentin, B. P. See Yong, R.
Warman, M. O., and Budworth, D. W. Criteria for the selection of additives to enable the sintering of alumina to proceed to theoretical density, (1) 27*i*. Effects of residual gas on the sintering of alumina to theoretical density in vacuum, (1) 28*d*.
Warmkessel, B. M. See Whitehurst, H. B.
Warner, N. A. See Baker, L. A.
Warner, P. D. Array of transistors having a layer of soft metal film for dividing, P (4) 99*d*.
Warner-Lambert Pharmaceutical Co. Method for making bubble free fiber optical image-transfer devices, P (3) 65*h*.
Warren, R., and Hinchliffe, R. Slip classifying by hydrocyclones, (7) 206*c*.
Warren, R. E. See McCown, W. E.
Warrington, H. G. Magnesium alloy drill rod assembly with ceramic coated coupling member, P (4) 93*c*.
Warshavsky, M., and Robinson, H. A. Internal friction in vibrating granular reeds and its application to vitreous silica, (9) 283*g*.
Warshaw, S. I. See Kalnin, I. L.
Wartenberg, K. See Kersting, A.
Warter, P. J., Jr. See Matthews, N. F. J.

Wartmann, R., Mertes, H., and Steinecke, V. Temperature distribution in the hearth of a blast furnace with air-cooled hearth bottom, (6) 174*f*.

Wasan, D. T. See Punwani, D.

Wasan, V. P., and Gupta, C. L. Thermocouples for high temperature measurement, (8) 249*i*.

Waseleski, J. W., Jr., and Landis, H. M. Production of solid state PTC sensors, P (2) 52*b*.

Washburn, J. See Vagnard, G.

Washburn, M. E. Production of silicon oxynitride, P (3) 69*c*.

Washizawa, Y. See Shionoya, S.

Wasko, J. H. See Zemon, S.

Wasserman, A. Mechanism for damage in solids by intense light, (4) 112*j*.

Watanabe, A. See Kitahiro, I.; Takeda, T.

Watanabe, Hideo, and Ohmori, K. Performance of direct-bonded basic brick in an open-hearth furnace, (9) 268*b*.

Watanabe, Hideo, Oomori, K., Ochiai, T., Arima, R., and Matsubara, N. Comparison of test results on ladle lining of unburned brick with bloating tendency and on ladle lining of burned test brick, (7) 200*g*.

Watanabe, Hiroshi. See Munakata, C.

Watanabe, Katsumi. See Muramori, K.

Watanabe, Kenichi, Kataoka, K., Hirai, T., and Tsuyama, A. Effect of additives on the transformation of titanium dioxide prepared by the gas phase reaction from $TiCl_4$, (5) 151*f*.

Watanabe, M., and Tooi, A. Formation of SiO_2 films by oxygen-ion bombardment, (9) 282*a*.

Watanabe, N. See Yoshizawa, S.

Watanabe, O. See Hibino, T.

Watanabe, T. See Umeya, K.

Watanabe, T., Ogura, T., Kondo, Y., and Nagasawa, M. Method of producing a sintered uranium dioxide nuclear fuel element containing a boride, P (2) 47*a*.

Waters, W. P., and Lovelace, B. K. Method of forming a metal contact on a semiconductor device, P (9) 273*a*.

Watkins, C. H. Hydrocracking nitrogen-contaminated hydrocarbon charge stocks, P (4) 105*d*.

Watkins, R. V., Reed, G. C., and Schalliol, W. L. Hot extruded chromium composite powders, B (3) 89*j*.

Watson, B. C. See Grabmaier, J. G.

Watson, D. See Joy, A. S.

Watson, D. R. See Cook, M. D.

Watson, G. M. See Bruin, H. J. de.

Watson, G. R., and Matchen, B. Method for producing a crystalline carbide, boride, or silicide, P (2) 47*j*.

Watson, J. D., Sr. See Olstowski, F.

Watson, J. F., and Goeddel, W. V. Fuel element containing activated carbon, P (3) 68*c*.

Watson, R. E. See Misetich, A. A.

Watson, W. C. Tile feeding apparatus for depositing tiles on tile boards, P (7) 206*j*.

Watstein, D. See Petersen, P. H.

Watt, J. D. See Thorne, D. J.

Watt, J. D., and Thorne, D. J. Composition and pozzolanic properties of pulverized fuel ashes (I) composition of fly ashes from some British power stations and properties of their component particles, (10) 294*d*.

Watters, R. L. See Young, J. R.

Watts, A. G. See Lenahan, W. M.

Waubke, N. V. Control of cement hydration by an ultrasonic method, (10) 294*g*.

Waugh, A. See Kingery, W. D.

Waxler, R. M. See Spinner, S.

Waxter, W. E. See McDaniel, C. V.

Wayman, C. H. Solid-gas interface in weathering reactions, B (5) 160*b*.

Waymouth, J. F. See Koury, F.

Wayte, R. C., and Thornton, P. R. Specimen cooling stage for the scanning electron microscope, (2) 55*d*.

Weagley, R. J. See Hatch, S. E.

Weakliem, H. A. See Anderson, C. H.

Weatherley, E. G. Process for diffusing metal into a refractory or ceramic oxide using a nitrate promoter, P (7) 205*f*.

Weaver, C. E. See Neiheisel, J.; Pecuil, T. E.

Weaver, C. E., Wampler, J. M., and Pecuil, T. E. Moessbauer analysis of iron in clay minerals, (2) 59*g*.

Weaver, E. A., Heckman, R. W., and Williams, E. L. Determining hydrogen diffusion in doped fused silica from the fluorescence, (7) 195*j*.

Weaver, E. P. Refractory shapes and method of producing the same, P (6) 175*a*.

Weaver, E. P., and Davies, B. Chemically bonded refractory shapes, P (2) 46*g*.

Weaver, R. E. See Wolkodoff, V. E.

Webb, A. N., Mather, W. B., Jr., and Suggitt, R. M. Studies of the molten carbonate electrolyte fuel cell, (4) 116*g*.

Webb, J. E. Inorganic solid film lubricants, P (11) 349*j*. Method of changing the conductivity of vapor deposited gallium arsenide by the introduction of water into the vapor deposition atmosphere, P (11) 344*d*. Method of electrolytically binding a layer of semiconductors together, P (11) 344*g*. Multislot film cooled pyrolytic graphite rocket nozzle, P (3) 69*c*.

Webb, J. L. Conveying glass sheets, P (4) 94*g*.

Webb, J. M. See Mellen, E. J., Jr.

Webb, W. W., Batha, H. D., and Shaffer, P. T. B. Strength characteristics of whisker crystals, macrocrystals, and microcrystals, B (4) 121*k*.

Weber, C. W. See Lee, T.

Weber, G. Apparatus for separating mixtures of solid particles, P (3) 77*j*.

Weber, J. B. Molecular structure and pH effects on the adsorption of 13 *s*-triazine compounds on montmorillonite clay, (5) 155*a*.

Weber, J. N. Quantitative mineralogical analysis of carbonate sediments—comparison of X-ray diffraction and electron probe microanalyzer methods, (8) 248*d*.

Weber, M. J. See Schaufele, R. F.

Weber, M. J., and Schaufele, R. F. Radiative and nonradiative transitions in the fluorescence decay of Eu^{3+} in $SrTiO_3$, (6) 188*b*.

Weber, N., and Goldstein, M. Stress-induced migration and partial molar volume of sodium ions in glass, (5) 128*a*.

Webster, A. H., MacDonald, R. C., and Bowman, W. S. System PbO-ZrO_2-TiO_2 at 1100°C, (9) 287*f*.

Webster, A. H., Weston, T. B., and Craig, R. R. Some ceramic and electrical properties of bodies fabricated from coprecipitated lead-zirconium-titanium hydroxide, (9) 272*h*.

Webster, A. H., Weston, T. B., and McNamara, V. M. Effects of some variations in fabrication procedure on the properties of lead zirconate-titanate ceramics made from spray-dried coprecipitated powders, (11) 341*i*.

Webster, G. A. Apparatus for producing rapid temperature changes during mechanical behavior tests, (1) 20*k*.

Weed, S. B. See Leonard, R. A.

Weeks, R. A. Some defect electron states of pure fourfold coordinated oxides—expectations and realization, B (10) 328*i*. See Abraham, M. M.

Weeks, R. A., and Abraham, M. M. Electron spin resonance of irradiated quartz—atomic hydrogen, (3) 80*d*.

Weeks, R. A., and Purcell, T. Electron spin resonance and optical absorption in GeO_2, (3) 80*e*.

Weerden, T. J. van der. See Esveldt, C. J.

Weeton, J. W., and Signorelli, R. A. Fiber-metal composites, B (4) 121*i*.

Wefers, K. Chemical technology of bauxite decomposition (I) system Na_2O-Al_2O_3-H_2O, (2) 57*d*. Phase relations in the system Al_2O_3-Fe_2O_3-H_2O, (3) 84*i*. System ferric oxide-water—correction, (1) 33*e*. System Na_2O-TiO_2-H_2O, (?) 60*b*. See Ginsberg, H.

Wegman, P. Efficiency in brickmaking—firing, (5) 130*j*. Modern tunnel kiln practice, (9) 278*a*.

Wegmann, L. Combined electron microscope and diffraction apparatus for the electron-optical inspection of the surfaces of objects, P (4) 103*f*.

Wehner, A. Oscillating screen frame, P (10) 312*f*.

Wehrenberg, T. M. See Patrick, R. F.

Wehrenberg, T. M., Begley, E. R., and Patrick, R. F. Isostatic pressing of large refractory blocks, (8) 238*a*.

Weidel, R. A. See Blair, G. E.; Brewster, G. F.

Weidemueller, C. See Koenig, G.

Weidersich, H. See Gonser, U.

Weidner, A. Proving of Simultansinter brick under different service conditions, (8) 239*h*.

Weiland, W. Westerwald (Germany) ceramic factories are to build a communal body preparation plant, (1) 15*i*.

Weimer, G. Enameling defects, (7) 195*d*.

Weingaertner, E., Fuechs, G., Jordan, W., and Merz, M. Process for the hydrolysis of aluminum alkoxides, P (11) 349*f*.

Weingarten, M. R. Method of salvaging phosphor slurry in a spin coating process for making phosphor screens for cathode-ray tubes, P (4) 100*h*.

Weinhold, J., and Plaehn, J. Design and use of a single cylinder hydraulic machine for testing full size building elements under 200-Mp load, (10) 294*i*.

Weinrotter, F. See Schmidt, A.

Weinryb, E. AMX microanalyzer, (10) 313*a*.

Weinstein, H. Process for diffusion of contoured junction, P (11) 345*c*.

Weinstock, H. See Forstat, H.

Weir, B. Temperature controlled microcircuit, P (11) 345*b*.

Weirauch, D. F., and Tennery, V. J. Electrical, X-ray, and thermal expansion studies in the system $KNbO_3$-$AgNbO_3$, (1) 16*e*.

Weisbeck, R. Production of highly pure hexagonal crystals of cadmium and zinc chalcogenides by sublimation, P (4) 101*b*.

Weisberg, H. See Desmond, T. J.

Weisberg, L. R., and Miller, E. A. Vacuum deposition of single-crystalline silicon on sapphire, (10) 309*e*.

Weisend, C. F. Cement additives containing polyvinylpyrrolidone and a condensate of sodium naphthalene sulfonate with formaldehyde, P (4) 92*b*.

Weiser, D. See Moiola, R. J.

Weislehner, G. Homogenization chamber for granular material, P (10) 312*d*.

Weiss, H. Semiconductor device with anisotropic inclusions for producing electromagnetic radiation, P (7) 210*f*.

Weiss, R. L. See Bicking, C. A.

Weiss, S. I. Methods and apparatus for making annular cutting wheels, P (3) 61*h*.

Weiss, V. See Burke, J. J.

Weiss, W. A. New Globe plant features three automatic setters, (4) 96*h*.

Weissmann, S. See Smith, D. K., Jr.

Weisz, P. B. See Chen, N. Y.; Miale, J. N.

Welch, B. G. See Tomlinson, J. W.

Weldes, H. H. W., and Deroif, M. R. Ammonium silicates, P (1) 25*h*.

Weller, B. L., Swart, R., and Caires, E. J. Method of calibrating electrical components, P (10) 310*d*.

Weller, P. F. Electrical and optical properties of rare earth doped cadmium fluoride single crystals, (4) 109*b*. Electrical and optical studies of doped CdF_2-CaF_2 crystals, (5) 151*d*. Semiconductivity in $Cd_{1-x}Ca_xF_2$:In^{3+} single crystals, (1) 16*h*. Single crystal growth of SnTe and GeTe, (10) 325*h*.

Weller, W. W. See Mah, A. D.; Pankratz, L. B.

Welles, S. J. See Grigsby, D. L.

Wellman Incandescent Furnace Co., Ltd. Process for the manufacture of a fluosilicate of a metal, P (5) 148*j*.

Wells, B. R. See Roberts, M. W.

Wells, C. F., and Salam, M. A. Complex formation between Fe(II) and inorganic anions (I) effect of simple and complex halide ions on the $Fe(II) + H_2O_2$ reaction, (7) 216*f*.

Wells, L. J. See Smith, R. M.

Wells, L. L. Experience with the use of direct-bonded basic brick in open-hearth roofs, (6) 173*b*.

Wells, M. R. See Cashion, J. D.

Wells, R. L., and Collins, A. L. Dehydrohalogenation and cleavage reactions in silicon-nitrogen-boron systems, (6) 185*b*.

Welsh, J. Y. Reducing to MnO the MnO_2 of a manganese ore, P (7) 215*d*.

Welsh, W. E., Jr., and Ching, A. New technique for mechanical strength testing of rapidly charred ablation materials, (8) 229*i*.

Welwyn Electric, Ltd. Manufacture of oxide mixes, P (2) 56*h*.

Wenban-Smith, A. K. Computer program for determining optical parameters and optical and crystallographic directions directly from universal stage readings, (5) 144*j*.

Wende, P. T. See Belasco, M.

Wendell, C. B. Apparatus for producing metal oxides, P (6) 182*c*. See Carpenter, C. L.

Wendell, C. B., Carpenter, C. L., and Greene, M. J. Vapor phase process for producing metal oxides, P (2) 57*b*.

Wender, J. D., Jr. See Stamos, C.

Wendland, P. H. High brightness luminescent evaporated film, P (1) 18*b*.

Wendlandt, W. W. See Southern, T. M.

Wendler, F. See Schreiner, H.

Wendler, F., and Nette, G. Apparatus for uniform feeding of powder into a plasma spray gun, P (9) 263*a*.

Wenk, H. R., Baker, D. W., and Griggs, D. T. X-ray fabric analysis of hot-worked and annealed flint, (2) 60*a*.

Wentorf, R. H., Jr. Modern very-high-pressure research, (2) 50*f*. See Bundy, F. P.

Wentworth, C. See Gordon, I.

Wentworth, C., and Taylor, G. W. Processing parameters and electric properties of doctor-bladed ferroelectric ceramics, (1) 16*d*.

Wenzel, R. Dust problems in the ceramic industry, (5) 143*i*.

Werner, H. R. Electric discharge lamp envelope having molten inner surface at operating temperature, P (9) 265*a*.

Werner, S. A. See Kendrick, H.

Wernimont, G. Evaluating laboratory performance of spectrophotometers, (1) 21*b*.

Wertheim, G. K. See Banks, E.

Wertz, J. E. See Auzins, P. V.

Wertz, J. E., and Auzins, P. V. Doubly associated cation-vacancy centers in magnesium oxide, (8) 253*d*.

Wertz, J. E., Hall, L. C., Helgeson, J., Chao, C. C., and Dykoski, W. S. Luminescence phenomena in magnesium oxide, B (10) 329*f*.

Wesel, J. R. See Olds, L. E.

Wessel, G. See Baer, R.

Wesselink, G. A. Optical maser with an adjusting mechanism for a mirror, P (11) 344*f*.

Wesson, R. A., Young, H. W., and Pliskin, W. A. Reflectivity thickness corrections for silicon dioxide films on silicon, (11) 356*d*.

West, G. W. See Graham, J.

West, H. W. H., Everill, J. B., and Beech, D. G. Testing of bricks and blocks for loadbearing brickwork, B (9) 291*f*.

West, H. W. H., and Ford, R. W. Empirical drying test, (6) 180*b*.

West, P. Advanced-fiber composites spark materials revolution, (2) 58*e*. For deep dives, oceanologists plan materials in combination, (4) 104*i*. Quality mass markets open for reinforced plastics, (10) 298*c*. See Hannavy, A.

West, R. Characteristics of filter pressed kaolinite-water pastes, B (6) 191*g*. Dilatometry of structural clay products, (9) 276*b*. Effectiveness of whiteware control tests, (9) 270*j*. Evaluation of whiteware control tests by computer, (4) 98*e*.

West, T. S., and Williams, X. K. Atomic-fluorescence spectroscopy of magnesium with a high-intensity hollow-cathode lamp as line source, (10) 313*h*.

West, W. There's a difference in diamond lapping powders, (8) 227*f*.

Westbrook, J. H. Impurity effects at grain boundaries in ceramics, B (7) 226*e*.

Westbrook, R. Drinking pottes, tygs, and possets, (3) 61*j*.

Westdorp, W. A. Preparation of aluminum and chromium sesquioxide fibers, P (10) 304*i*.

Westeren, H. W., Scotto, V., and Sefton, W. G. High temperature furnace, P (1) 24*c*.

Western Electric Co., Inc. Controlled electrolytic treatment of materials, P (9) 272*c*. Methods of applying doping compositions to base materials, P (3) 73*g*. Methods of severing

brittle material along prescribed lines, P (8) 247*f*. Multilayer thin-film coated substrate with metallic parting layer to permit selective sequential etching, P (9) 274*b*. Thin film capacitors employing semiconductive oxide electrolytes, P (11) 345*b*. See Bell Telephone Laboratories, Inc.

Westerveld, W., and Graaf, W. P. de. Methods of producing zinc-doped gallium phosphide, P (10) 311*a*.

Westinghouse Brake & Signal Co., Ltd. Semiconductor diodes and their manufacture, P (5) 142*i*. Semiconductor junction with a depletion layer, P (3) 74*a*.

Westinghouse Electric Corp. Anodic oxidation, P (7) 208*f*. Apparatus for producing dendrites, P (1) 17*i*. Apparatus for producing vapor growth of silicon crystals, P (6) 177*a*. Blue-white europium activated aluminosilicate phosphor, P (4) 99*e*. Cathode-ray tube generating circular beam by lineal filament critically spaced from circular aperture, P (8) 244*a*. Constant current gain composite transistor, P (10) 309*i*. Dielectric glasses and capacitors employing such glasses, P (7) 198*i*. Electric discharge lamp having a resiliently suspended fragile member therein that decreases the diffusion length of the discharge, P (7) 208*c*. Electroluminescent device, P (11) 343*d*. Electroluminescent device which incorporates barium oxide films as breakdown protection, P (7) 208*d*. Electron tube with storage target electrode, P (6) 177*f*. Electrostatic coating apparatus for uniformly applying phosphor powders, P (4) 99*f*. Fabrication of semiconductor controlled rectifiers, P (4) 100*a*. Ferrite magnets, P (6) 177*h*. Fluorescent lamp envelope with transparent protective coatings, P (7) 208*h*. Green-yellow emitting europium aluminosilicate phosphor, P (4) 100*b*. Guard junctions for *pn* junction semiconductor devices, P (10) 309*i*. Hermetically sealed semiconductor device, P (8) 244*d*. High temperature nuclear fuel elements, P (1) 12*i*. High voltage [single crystal] rectifier having controlled current leakage, P (1) 18*d*. Lamp sealing apparatus with double revolving and orienting sealing heads, P (6) 170*f*. Method of angularly pulling continuous dendritic crystals, P (6) 190*h*. Method of bonding a boron nitride body to a refractory metal, P (1) 13*b*. Method of constructing cast electrical bushings, P (11) 344*e*. Method of forming a semiconductor integrated circuit that includes a fast switching transistor, P (8) 245*h*. Method for growing germania films, P (1) 18*a*. Method of making *pn* junction devices by diffusion, P (10) 310*a*. Method of preparing a fuel element of fissionable oxide and burnable poison, P (4) 97*a*. Method of varying the thickness of dendrites by addition of an impurity which controls growth in the (111) direction, P (11) 344*f*. Modified carbide fuels, P (1) 13*b*. Permanent magnet material and process for manufacturing same, P (8) 245*i*. Photoconductive target having arsenic-selenium layers of different densities on cryolite layer, P (10) 311*f*. Photovoltaic series array comprising *pn* and *np* cells, P (6) 178*c*. Polyphase arc furnace with control system to raise one electrode prior to all electrodes striking an arc, P (7) 214*a*. Porcelain casing head construction, P (3) 70*g*. Radioactive fluophosphate glass composition, P (6) 171*e*. Semiconductor devices with low leakage current across junction, P (4) 101*g*. Stabilized red pigment filter coating in a fluorescent lamp, P (5) 143*c*. Structures for semiconductor integrated circuits and methods of forming them, P (1) 19*e*. Use of halogens and hydrogen halides in insulating oxide and nitride deposits, P (6) 178*j*.

Westlin, K. L. Dust collector apparatus, P (1) 20*a*.

Westofen G.m.b.H. Burners for liquid, gaseous, and pulverulent fuels, P (5) 147*h*.

Weston, P. L., Jr. See Khalafalla, S. E.

Weston, T. B. See Webster, A. H.

Westrum, E. F., Jr., and Barber, C. M. Uranium mononitride—heat capacity and thermodynamic properties from 5° to 350°K, (10) 327*b*.

Westwood, A. R. C. Effects of adsorption on strength, B (4) 121*h*.

Westwood, A. R. C., Goldheim, D. L., and Lye, R. G. Rebinder effects in MgO, (8) 256*a*.

Weyl, W. A. Interaction of light absorption and emission with the phonon spectrum of crystals and glasses, B (10) 329*g*.

Weymouth, J. H. See Ellson, D. B.

Whalen, T. J., McHugh, C. O., and Humenik, M., Jr. Dispersion-strengthened ceramics, B (4) 121*g*.

Whaley, H. P., and Hovland, M. L. Product sizing control in a grinding circuit closed by a separating means, P (11) 346*a*.

Whaley, H. P., and Johnson, G. F. Gyratory crusher liner, P (3) 78*b*.

Wharton, L. See Kaufman, M.

Wharton, L., Berg, R. A., and Klemperer, W. Geometry of the alkaline-earth dihalides, (5) 153*b*.

Wharton, L., and Klemperer, W. Microwave spectrum of BaO, (5) 154*i*.

Whately, W. R. See Roberts, G. L., Jr.

Whately, W. R., Roberts, G. L., Jr., Sheehan, G. M., and Castor, W. S., Jr. Titanium dioxide pigment and preparation, P (1) 26*b*.

Whatham, J. F. See Veevers, K.

Wheatley, J. C. See Abel, W. R.

Wheelabrator Corp. Baghouse construction, P (6) 179*f*.

Wheeler, B. E. Ultraviolet reflectivity of α- and β-SiC, (11) 357*j*.

Wheeler, J. St. C. Calcium silicate brick development, P (2) 37*d*.

Wheeler, R. W. Glass sheet press bending apparatus with conveying roller recesses, P (6) 170*d*.

Wheeler, V. J. See Dell, R. M.

Wheildon, W. M. See King, A. G.

Whelan, M. V., Goemans, A. H., and Goossens, L. M. C. Residual stresses at an oxide-silicon interface, (5) 158*a*.

Whitaker, G. See Harris, M. R.

Whitaker, J., and Bolger, D. E. Shallow donor levels and high mobility in epitaxial gallium arsenide, (11) 356*a*.

Whitcher, R. E. See Gibbs, W. E. K.

White, D. Structure of organic montmorillonites and their adsorptive properties in the gas phase, B (6) 191*j*. See Ashbee, K. H. C.; Linevsky, M. J.

White, D., and Gregg, D. Optical distortion in ruby lasers during pumping, (5) 139*d*.

White, D. E. See Schoen, R.

White, E. W. Electron microprobe in ceramics, (6) 180*b*.

White, G. K. See Pryor, A. W.

White, H. G. See Frosch, C. J.; Logan, R. A.; Trumbore, F. A.

White, J. Direct-on enameling in Canada, (11) 332*e*. See El-Shahat, R. M.; Stephenson, I. M.; Willshee, J. C.

White, J. C. See Town, J. W.

White, J. G. See Arlett, R. H.

White, J. G., and Dismukes, J. P. Crystal structure of scandium sesquitelluride (Sc_2Te_3), (4) 107*g*.

White, J. L. See Diamond, S.; Ledoux, R. L.; Russell, J. D.

White, J. L., Jelli, A. N., Andre, J. M., and Fripiat, J. J. Perturbation of OH groups in decationated Y zeolites by physically adsorbed gases, (7) 220*g*.

White, J. L., and Koyama, K. Graphitic materials hot-worked with a dispersed liquid carbide—thermal and electrical conductivity, (8) 254*d*.

White, J. L., and Pontelandolfo, J. M. Method of making refractory products, P (1) 13*f*.

White, J. W. Multichannel analyzer system for high sensitivity mass spectrometry, (1) 22*f*.

White, L. C. Silicon transistor device, P (4) 101*b*.

White, L. R., and Davis, H. T. Thermal conductivity of molten alkali nitrates, (7) 197*b*.

White, M. B. See Doyle, W. M.

White, R. M. See Robinson, G. Y.

White, W. A., and Bremser, S. M. Effects of a soap, a detergent, and a water softener on the plasticity of earth materials, (1) 24*j*.

White, W. A., and Parham, W. E. Clay and shale resources of Clark, Crawford, Cumberland, Edgar, Effingham, Jasper, and Vermillion Counties, Illinois, (1) 10*f*.

White, W. B. Reply to discussion of "Optical absorption spectra of iron in the rock-forming silicates," (6) 185*e*. See Balascio, J. F.; Bates, C. H.; McCarthy, G. J.

White, W. B., and Keester, K. L. Optical absorption spectra of iron in the rock-forming silicates, (3) 84*c*.

Whitehouse, J. E. See Mitchell, E. W. J.

Whitehurst, H. B., Morrison, J. J., English, F. L., Warmkessel, B. M., and Kevane, C. J. Time dependent conductivity in titanium oxide, (6) 190*a*.

Whiteley, P. G. See Owen, A. J.

Whitfield, H. J. See Palmer, A. R.

Whitfield, H. J., and Freeman, A. G. Moessbauer study of amphiboles, (5) 155*i*.

Whitfield, H. J., Roman, D., and Palmer, A. R. X-ray study of the system ThO_2-CeO_2-Ce_2O_3, (4) 119*a*.

Whitfield, M. See Bradley, R. S.

Whitley, J. E. See Garbrah, B. W.

Whitlock, R. G. Dust control, (2) 52*j*.

Whitman, P. C., and Selig, T. R. Double heat sink semiconductor diode with glass envelope, P (8) 244*a*.

Whitman, P. C., and Willis, W. Glass encapsulated double heat sink diode assembly, P (4) 100*b*.

Whitmire, L. S. Method of bending and annealing glass sheets with supplemental cooling of hotter areas of the glass, P (9) 265*a*.

Whitmore, D. H. See Janninck, R. F.

Whitney, E. D. See Murata, Y.

Whitney, J. M. Engineering constants of laminated composite materials, (10) 296*f*.

Whitney, W. P., II. See Williams, J. P.

Whittaker Corp. Lamination of amorphous fluorocarbon polymer and glass and method of making same, P (6) 170*i*.

Whittemore, O. J., Jr. See Thompson, V. S.

Whittig, L. D. See Hendricks, D. M.; Lynn, W. C.

Whittle, D. P., and Wood, G. C. Scale initiation on copper-nickel alloys, (11) 356*b*.

Whitworth, R. W. Measurement of the charge on edge dislocations in a sodium chloride crystal, (1) 30*b*. See Stuart, R. A.

Whyman, D. Rotating-wall dc-arc plasma furnace, (2) 54*j*.

Wickersheim, K. A., and Korpi, G. K. Interpretation of the infrared spectrum of boehmite, (3) 82*j*.

Wickert, H. See Pfrunder, V. F.

Wickham, D. G. Preparation of ferromagnetic $NiMnO_3$, P (8) 245*j*.

Widaj, J., Kurbiel, Z., Ciesla, M., Budzinowski, F., and Baraskiewicz, P. New steatite body for thermoplastic forming, (2) 48*i*.

Widmann, H. See Hartmann, H. J.

Widrow, B., Frick, G., and Gordon, R. H. Adaptive memory element, P (11) 343*c*.

Wiedersich, H. See Muir, A. H., Jr.

Wiegand, D. A. See Crose, G. J.

Wiegand, Edwin L., Co. See Edwin L. Wiegand Co.

Wieja, C. See Grzymek, J.

Wiens, B. E. See Baak, T.

Wiesler, M., and Goren, A. Sealing head for glass diodes, P (10) 301*d*.

Wiesner, R. Method for producing a *pn* junction in a monocrystalline semiconductor member by etching and diffusion, P (7) 209*f*.

Wiggins, J. H., Jr. Effect of sonic boom on structural behavior, (11) 331*i*.

Wijn, H. P. J. See Neumann, H.

Wijn, H. W. de, and Balderen, R. F. van. Electron spin resonance of manganese in borate glasses, (5) 127*i*.

Wikdahl, N. A. L. Method of separating particles in liquid suspension in a hydrocyclone for separating articles in liquid suspension, P (2) 53*d*.

Wikswo, J. P. Process for the oxidation of $TiCl_4$ to produce TiO_2, P (2) 57*a*.

Wilcox, D. L. See Schwartz, B.

Wilcox, R. E., and Izett, G. A. Optic angle determined conoscopically on the spindle stage (I) micrometer ocular method, (9) 276*g*.

Wilcox, W. R. See Millea, M. F.

Wilcox, W. R., Teviotdale, J. R., and Corley, R. A. Chemical vapor deposition of hafnium carbide, (10) 306*j*.

Wilczynski, J. S., and Harper, J. S. Multiple color, multiple beam interferometer, P (4) 103*k*.

Wild, R. K. See Evans, T.

Wild, R. K., Evans, T., and Lang, A. R. Birefringence, X-ray topography, and electron microscope examination of the plastic deformation of diamond, (1) 26*j*.

Wild Barfield, Ltd. Shaker hearth furnaces, P (8) 249*k*.

Wilde, D., and Kenworthy, R. Methods of and apparatus for carrying glass sheets, P (11) 336*b*.

Wildeboer, N., and Landsittel, D. T. Metal-to-glass-to-ceramic seal, P (3) 73*c*.

Wilder, A. H. See Sundstrom, R. N.

Wilder, D. R. See Carrell, M. A.; McMahon, W. R.

Wiley, R. F. Variable index mechanism for glass press, P (4) 95*f*.

Wilgocki, M. Parameters of preliminary forming of tubes and rods drawn by the Danner method, (10) 298*g*.

Wilhelm, M. See Mueller, A.

Wilhelm Loh K. G. Optikmaschinenfabrik. Charging device for machines for working optical lenses, P (3) 65*e*.

Wilke, C. R. See Faith, L. E.

Wilkins, D. H. See Martin, D. L.

Wilkins, R. W. T. Hydroxyl-stretching region of the biotite mica spectrum, (8) 254*i*.

Wilkins, R. W. T., and Ito, J. Infrared spectra of some synthetic talcs, (7) 218*a*.

Wilkinson, W. T. See Dinsdale, A.

Wilks, E. M. Effect of neutron irradiation on some mechanical properties of diamond (I) abrasion hardness and cleavage, (2) 35*g*.

Wilks, P. A., Jr. Survey of infrared spectrophotometers, (11) 347*a*.

Wilks, R. S. Gas formation by transmutation of MgO and Al_2O_3, (4) 110*e*. Observation of dislocations in BeO by transmission electron microscopy, (2) 45*e*. See Clarke, F. J. P.

Willdig, E. See Craig, R. D.

Willem, M. H. Insulator and method for making same using electrostatically applied dielectric fibers as spacer pads and gaskets, P (10) 310*a*.

Willems, J., and Konopicky, K. American and German methods of testing basic brick for steel converters, (8) 236*h*.

Willens, R. H. See Matthias, B. T.

Willer, A. M. Location, protection, and connection, (4) 102*j*.

William Boulton, Ltd. See Podmore & Sons, Ltd.

Williams, B. B. See Lowery, C. J.

Williams, C. E. High purity $Mg(OH)_2$, a good starting material for high density ceramics, (2) 56*j*.

Williams, C. W. See Gifford, F. B.

Williams, D. A. Particle measuring and counting system, P (9) 275*g*.

Williams, D. T., and Smith, W. A. Plasma heat transfer in verneuil crystal growth, (2) 59*a*.

Williams, E. De-enameling, (4) 92*h*. See Nicholls, G. D.

Williams, E. L. See Heckman, R. W.; Weaver, E. A.

Williams, E. L., Jr., and Wilson, H. H. Low-temperature cementation effects in nickelous nitrate-water-magnesium oxide system, (1) 29*i*.

Williams, E. W. See Conrad, R. W.; Woolley, J. C.

Williams, E. W., and Blacknall, D. M. Observation of defects in GaAs using photoluminescence at 20°K, (4) 113*c*.

Williams, F. D. See Van Ruyven, L. J.

Williams, F. E. See Fair, H. D., Jr.

Williams, F. V. Hall mobilities in heavily doped *n*-type gallium arsenide, (3) 81*i*. Structural defects in epitaxial $GaAs_{1-x}P_x$, (6) 189*f*.

Williams, G. H., Morris, J. B., and Savage, D. W. Dispersion and breakage of coated particles consolidated in a graphite matrix by hot-pressing, (11) 337*j*.

Williams, H. J. See MacChesney, J. B.
Williams, J. P. See Desjardins, M.
Williams, J. P., and Whitney, W. P., II. Diffusion of glass constituents in refractories, (3) 63*f*.
Williams, J. R. See Southern, T. M.
Williams, J. R., and Henderson, J. Fixed point thermocouple calibration facility, (4) 102*e*.
Williams, K. L. Electron probe microanalysis of sphalerite, (6) 185*h*.
Williams, L. S. Method of producing compacts by reacting particulate ingredients, P (3) 69*d*. See Barker, W. W.
Williams, M. W., Rails, K. M., and Pickus, M. R. Superconductivity of cubic niobium carbonitrides, (8) 257*j*.
Williams, N. J. See Sanford, R. A.
Williams, P. P. Crystal structure of a fluoride derivative of $12CaO \cdot 7Al_2O_3$, (10) 319*a*.
Williams, R. P. See Mahan, J. E.
Williams, S. E., Dunbar, R. B., and Rademaker, J. C. Manufacture of calcium silicate insulating products, P (2) 47*e*.
Williams, W. S. See Smith, D. A.
Williams, X. K. See West, T. S.
Williamson, J. See Nover, J. C.
Williamson, S. J. See Shapira, Y.
Williamson, W. O. Structure and behavior of extruded clay (I) surveying microstructure and flow patterns; (II) piston and auger extrusion; (III) effects of extrusion, (2) 43*c*. See Kilgore, R. V.; Okuda, S.; Tressler, R. E.
Willis, J. E. See Johnson, M. F. L.
Willis, J. H. See Russell, R. G.; Tiede, R. L.
Willis, J. R. Comparison of the fracture criteria of Griffith and Barenblatt, (1) 5*e*. Crack propagation in viscoelastic media, (1) 5*i*.
Willis, N. Compositions and methods for production of colored glass fibers, P (9) 264*j*.
Willis, W. See Whitman, P. C.
Willshee, J. C., and White, J. Investigation of equilibrium relations in the system MgO-FeO-Fe_2O_3 up to 1750°C in air, (7) 218*h*.
Wilms, G. R. Environmental effects on the tensile creep properties of chromium alloys, (10) 302*i*. Influence of ceramic environment on mechanical properties of metals, (1) 29*e*.
Wilms, G. R., and Rea, T. W. Effect of a ceramic environment on the creep properties of chromium alloys, (8) 253*f*.
Wilshaw, T. R. Measurement of tensile strength of ceramics, (3) 75*f*.
Wilson, C. Pump solves abrasive slurry handling problem, (2) 53*e*.
Wilson, C. P., Jr., Carr, B., and Ciapetta, F. G. Process for making silica-magnesia-magnesium fluoride cracking catalysts, P (11) 349*g*. Process for producing alumina gel, P (2) 47*j*.
Wilson, D. K. See Furnanage, R. A.
Wilson, F. L. Statistical analysis of thermal shock in disks (flat faces insulated), (11) 357*c*.
Wilson, H. C. Design of sheet steel parts for porcelain enameling, (9) 262*j*.
Wilson, H. E. Performance of construction materials for domestic water piping systems, (5) 130*j*.
Wilson, H. H. See Williams, E. L., Jr.
Wilson, H. N., and Duff, G. M. S. Industrial gas analysis—a literature review, (5) 147*e*.
Wilson, J. B. See Roberts, J. E.
Wilson, J. R. See Rowe, G. L.
Wilson, Lee, Engineering Co., Inc. See Lee Wilson Engineering Co., Inc.
Wilson, P. See O'Donnell, T. A.
Wilson, R. B. Precision polishing of thin single crystal layers, (2) 54*g*.
Wilson, R. C., Jr. See Schwartz, A. B.
Wilson, S. G. See Thomas, T. G.
Wilson, W. See Dienes, G. J.
Wilson, W. D., and Hall, H. B. Method for synthesis of carbon crystals, P (8) 251*j*.
Wilson, W. J. See Browning, N. F.
Wilson, W. L. Process for preparing titanium dioxide, P (3) 78*b*. See Richardson, K. W.
Winchell, R. Build on strong points, minimize weaknesses, (7) 223*d*. Can brick be dried with waste heat from tunnel kilns? (2) 42*k*. Does the cost of hauling raw material matter more than the cost of land? (4) 119*f*. Incentive program for brick salesmen, (10) 301*e*. Proper scheduling makes money for a brickyard, (7) 199*i*. Two ways to increase the capacity of many tunnel kilns, (7) 213*j*.
Windisch, S. See Rudy, E.
Windreich, S. See Hasson, D.
Winer, A. A., and Wright, I. F. Practical problems in particle size and surface area measurements, (11) 346*j*.
Winkler, H. G. F. See Froese, E.
Winkler, H. J. See Hase, H.
Winkler, R. H. High frequency power transistor having electrodes forming transmission lines, P (9) 273*d*.
Winogradoff, N. N. See Kessler, K. G.
Wins, J. Glass tank furnace wall structure, P (1) 9*d*.
Winsker, H. See Kravitz, B. L.
Winslow, D. K. See Malbon, R. M.
Winslow, G. H. See Thorn, R. J.
Winslow, J. S. See Kazan, B.
Winter, A. Effect of the method of melting on the homogeneity of glass as shown by light scattering, (11) 333*h*. General concepts applied to glasses, (7) 198*i*. Glass refining studied by light scattering, (11) 334*e*. See Hampe, R.
Winter, H. W. Spiderless gyratory crusher with relief valve system, P (6) 183*e*. See Kemnitz, R. H.
Winterbottom, W. B. Our amazing business, (1) 2*b*.
Winterburn, J. A. Process for producing cellulated silica, P (11) 349*i*.
Winterling, G. See Heinicke, W.
Winters, D. E. See Kalb, J. W.
Winters, H. K. System for purging nozzles in dual fuel burners, P (8) 249*i*.
Winyall, M. E. Silica gel-asbestos compositions, P (7) 215*d*.
Wirtz, G. P., and Fine, M. E. Precipitation and coarsening of magnesioferrite in dilute solutions of iron and MgO, (8) 256*b*. Superparamagnetic magnesioferrite precipitates from dilute solutions of iron in MgO, (5) 140*b*.
Wischmann, U. Adjustable damping resistor 67DR, (10) 306*g*.
Wise, D. C. See Miccioli, B. R.
Wisely, H. R. See Girard, R. T.
Wishnie, F. T., and Tanzman, D. P. Method of flame spraying and powder, P (6) 166*c*.
Wishon, B. E., and Pavlica, S. R. Alumina refractories, P (3) 68*g*.
Wisman, E. C., and Abernathy, J. H., Jr. Method of forming a small area junction semiconductor, P (6) 178*b*.
Wisniak, J., Fertilio, A., and Freed, C. Critical moisture of sand and its properties, (3) 74*i*.
Wisnyi, L. G. See Lang, J. E.
Witheford, J. M. See Colgan, J. D.
Witsell, W. A. See Engelman, J. H.
Witt, A. F. See Morizane, K.
Witt, F. J., and Greenstreet, B. L. Influence of cross-sectional shape on irradiation-induced stresses in graphite columns, (3) 81*j*.
Witt, J. C. Portland Cement Technology, B (3) 90*c*.
Witt, W. See Matting, A.
Wittels, W. Process for producing fused ceramic blocks, P (4) 95*i*.
Wittig, J. Superconductivity of metallic aluminum antimonide, (4) 117*f*.
Wittke, J. P. Diffusion of transition metal ions into rutile (TiO_2), (10) 319*c*. Solubility of iron in TiO_2 (rutile), (1) 32*f*.
Wittmann, F. Measurements of the compound $2CaO \cdot (Al_2O_3)_x \cdot (Fe_2O_3)_{1-x}$ by the Moessbauer effect, (9) 284*a*.
Wittmer, A. L. Recent developments in combustion equipment and controls for the glass industry, (9) 264*f*.
Wlosinski, W. K. See Rawson, H.
Woelk, H. See Wohlleben, K.
Woermann, E. See Bigare, M.
Woermann, E., Eysel, W., and Hahn, T. Chemical and structural studies on the formation of solid solutions of tricalcium silicate, (2) 36*g*.
Wohl, M. H. Designing for non-Newtonian fluids (I); (II) rheology of non-Newtonian materials; (III) instruments for viscometry; (IV) isothermal laminar flow of non-Newtonian fluids in pipes, (9) 275*j*.
Wohlleben, K. See Treffner, W. S.
Wohlleben, K., Mikami, H. M., and Konopicky, K. Formation of new minerals in chromites by firing in weakly reducing and oxidizing atmospheres, (5) 132*g*.
Wohlleben, K., Woelk, H., and Konopicky, K. Investigation of spherical inclusions in flat glass with the electron microprobe, (8) 232*c*.
Wold, A. See Bouchard, R. J.; Lee, H. N. S.; Morris, B.
Wolf, F., and Haedicke, U. Effective pore radii of ion-exchanged forms of synthetic zeolite X, (1) 28*b*. Kinetics and ion-exchange equilibrium of synthetic zeolite type X, (1) 29*g*. Structural changes of zeolite X caused by ion exchange and temperature, (1) 32*f*.
Wolf, J. See Jakes, D.
Wolf, R. H. H., and Orhanovic, M. Simple method for colorimetric and spectrophotometric determination of ferric iron in a high concentration range, (1) 23*c*.
Wolf, W. P. See Hutchings, M. T.
Wolfe, C. M., Foyt, A. G., and Lindley, W. T. Epitaxial gallium arsenide for high-efficiency Gunn oscillators, (10) 307*c*.
Wolfe, R., Pierce, R. D., Haszko, S. E., and Remeika, J. P. Temperature-induced spin reorientation in rare earth orthoferrites—hysteresis loop studies, (6) 176*j*.
Wolfe, R. W. Apparatus and method for introducing vaporizable materials into an electron tube envelope, P (5) 140*b*.
Wolff, G. A., and Das, B. N. Removal of dislocations in crystals grown by traveling solvent method, (11) 356*f*.
Wolff, G. A., LaBelle, H. E., Jr., and Das, B. N. Solution growth of (Zn,Hg)Te and Ga(P,As) crystals, (10) 308*j*.
Wolfgram, E. W. Cathode ray tube manufacture, P (3) 72*a*.
Wolkodoff, V. E., and Weaver, R. E. Alumina ceramic, P (7) 206*g*.
Wollast, R. Discussion of "Structures of $AlPO_4$ and SiO_2," B (7) 226*c*. Effect of mineralizers on the polymorphic transformation of SiO_2, (7) 217*d*. See De Keyser, W. L.
Wolley, E. D. See Kao, Yu. C.
Wolten, G. M., and Chase, A. B. Data for $LaTaO_4$ and $PrTaO_4$, a new structure type, and a series of new rare earth compounds, $K_{0.5}Ln_{0.5}Ta_2O_6$, with the $PbNb_2O_6$ structure, (5) 150*g*.
Womack, E. A., Lazarus, A. J., and Liu, S. W. W. Linear relationship for heavy-ion pulse heights in alkali halides, (9) 283*j*.
Womeldorph, R. C. See Day, F.
Wong, C., and Schuele, D. E. Pressure derivatives of the elastic constants of CaF_2, (8) 256*f*.
Wong, H. Y. Hardness testing at elevated temperatures, (2) 54*f*.
Wood, A. A. R. See Cocks, A. C.
Wood, D. L. Absorption, fluorescence, and Zeeman effect in emerald, (3) 78*g*. Energy levels of Yb^{3+} in garnets, (5) 152*d*. See Ferguson, J.; Kolb, E. D.
Wood, G. C. See Whittle, D. P.
Wood, G. C., and Hodgkiess, T. Characteristic scales on pure nickel-chromium alloys at 800° to 1200°C, (7) 207*b*.
Wood, M. See Nicholls, G. D.
Wood, R. P. Coating dies, P (10) 300*d*.
Wood, S. E. See Battino, R.; Johnson, C. E.
Wood, W. A., Burnie, G., and Zeldin, C. A. Mandrel for continuous casting mold, P (1) 12*j*.
Woodall, J. M. Donor and carrier distributions in oxygen-grown GaAs, (4) 103*f*. See Ruppreeht, H.
Woodall, R. A. Vitreous enameling of signs, (4) 92*j*.
Woodcock, R. F. Apparatus for making fiber optical image transfer devices, P (6) 170*d*.
Woodmansee, W. E. Cholesteric liquid crystals and their application to thermal nondestructive testing, (7) 211*j*.
Woodruff, M. D. Eccentric head hydrocyclone, P (8) 247*c*.
Woodruff, R. W., and Davies, B. Electric furnace roof construction, P (5) 134*j*.
Woods, J. F. See Lorenz, N. R.
Woolley, J. C. Alloys of InSb with InTe, In_2Te_3, and tellurium, (7) 207*e*. Solid solution in the GeTe-InTe system, (3) 86*a*. See Wagner, J. W.
Woolley, J. C., Williams, E. W., and Gagnon, R. Cross substitution in InAs, (4) 107*d*.
Wooten, F. T. Method for mounting thin films without substrates, (1) 22*a*.
Worchel, G. S. See Bryan, W. S.
Work, L. T. Size reduction, (8) 247*c*.
Work, L. T., and Snow, R. H. Size reduction, (9) 275*g*.
Workman, G. M., and Davidson, J. A. C. Refractories keep pace with rising output rates in iron and steel plants, (2) 45*j*.
Worner, H. K. Process and apparatus for continuous production of alpha gypsum, P (6) 166*a*.
Worrall, W. E., and Cooper, A. E. Ionic composition of a disordered kaolinite, (6) 186*f*.
Worrall, W. E., and Davis, G. A. Adsorption by clays of dyestuffs from nonaqueous systems, (1) 26*f*.
Wotherspoon, J. G. Roofing tile, P (2) 43*c*.
Woulbroun, J. M. See Casale, R.
Woyski, M. M., Bradford, J. L., and Elliott, H. H. Process for treating rare earth-fluorine materials, P (3) 74*d*.
Wratil, J. Gas reactions and their consequences in enameling, (11) 332*j*.
Wrench, R. F. Apparatus for decorating glassware, P (10) 299*j*.
Wright, A. J. See Lewis, T. J.
Wright, H. E., and Leofsky, E. E. Overvoltage protective device, P (10) 311*e*.
Wright, H. G. Determination of indicatrix orientation and $2V$ with the spindle stage—a caution and a test, (1) 21*b*.
Wright, I. F. See Winer, A. A.
Wright, J. C. Hot top and composition thereof, P (6) 174*c*.
Wright, J. W. T. Electric incandescent lamps, P (1) 8*i*.
Wright, L. W. See Thomas, P. M.
Wright, M. A. Growth of α-SiC from various chromium alloys by a traveling solvent method, (4) 110*i*.
Wright, T. G. Apparatus for supporting and heating glass sheets on a gas bed, P (6) 170*e*.
Wright, W. J. See Veevers, K.
Wronski, J. Methods for measuring fiber length distribution, (3) 75*i*.
Wuellenweber, E. Future changes in brick in Western European countries, (10) 301*i*.
Wuensch, B. J., and Vasilos, T. Diffusion of Zn^{2+} in single-crystal MgO, (3) 80*c*.
Wuhrer, J., and Obat, K. H. Manufacture of refractory material, P (8) 240*h*.
Wulf, G. Process of preparing silicic acid in a two-dimensional structure, P (1) 25*i*.
Wulfinghoff, M. F. See Bennett, H.
Wunnik, J. van. Practical control of slip properties, (1) 15*e*. See Phelps, G. W.
Wurm, J. G. See Beucherie, P.
Wycoff, J. C. See Roberts, J. W.
Wyman, J. H. Glass-container sorting, P (2) 40*i*.
Wyman, L. L., Sr., Everts, J. C., and Pollard, R. E. Shaped charge liners, P (7) 205*f*.
Wymer, R. G. See Helton, D. M.
Wynne, H. C. See Brewin, J. D.
Wys, E. C. de, and Leipold, M. H. Indications of preferred orientation in recrystallized hot-pressed MgO, (1) 29*d*.
Wysong, E. D. See Ruh, R.
Wytmar, R. J. Management obsolescence, (3) 89*a*.

Yabumoto, T., Sugimoto, H., and Muto, N. Thermoluminescence and electroluminescence in ZnS:Cu,Al phosphors, (3) 88*e*.
Yacura, S. B. Pusher for kilns and method of charging kilns, P (10) 317*c*.
Yaggy, L. S. Cathode ray tube with a perforated aluminum film graticule overlying the illuminescent layer, P (3) 72*b*.
Yagi, K. See Onuma, K.
Yagi, T. See Koide, Y.

Yagnik, C. M., and Mathur, H. B. Moessbauer and X-ray diffraction study on the cation distribution in $FeAl_2O_4$, (11) 354*g*.

Yagub'yan, E. S., Bukhalova, G. A., and Khliyan, T. M. Enthalpy of formation of $K_2Cl_2 \cdot BaCl_2$, (10) 321*a*.

Yaguchi, K. See Muramori, K.

Yajima, S., Furuya, H., and Hirai, T. Lattice and grain boundary diffusion of uranium in UO_2, (4) 112*i*.

Yajima, T. Optical mixing due to third order nonlinear polarization in quartz, (10) 324*c*.

Yakel, H. L. See Harris, L. A.

Yakimenko, V. D. See Kuzenkova, M. A.

Yakowitz, H., Jenkins, W. D., and Hahn, H. Role of nickel in Al-10% Si composites containing nickel-coated sapphire whiskers, (10) 304*b*.

Yakubovich, A. L. See Przhiyalgovskii, S. M.

Yamada, E. See Komatsubara, K. F.

Yamada, M. See Kosaka, M.

Yamada, M., Kato, M., and Minowa, S. Formation and reduction of hercynite ($FeAl_2O_4$) (I) formation, (3) 81*e*; (II) reduction of synthesized hercynite with hydrogen, (10) 321*i*.

Yamada, T. Magnetic anisotropy, magnetostriction, and magnetic domain walls in NiO (I) theory, (4) 112*h*. Spin configuration in antiferromagnetic domain walls of the NiO-type crystals, (4) 116*d*. See Maruno, S.

Yamada, T., Saito, S., and Shimomura, Y. Magnetic anisotropy, magnetostriction, and magnetic domain walls in NiO (II) experiment, (4) 112*h*.

Yamagishi, K., and Nakamura, M. Method and apparatus for vapor deposition employing an electron beam, P (1) 18*j*.

Yamaguchi, G., Imoto, F., Aoki, H., and Kaneno, M. Diffusion of silver and potassium ions in glass, (7) 196*d*.

Yamaguchi, M., Mizushima, Y., Hirota, S., and Noake, H. Cristobalite formation on vitreous silica boats and the relation to GaAs crystal growing, (7) 207*c*.

Yamaguchi, S. Ferroelectric field of $BaTiO_3$ as measured by electron diffraction, (5) 138*j*. Ferroelectric structure of $BaTiO_3$ as revealed by an electron-beam technique, (5) 138*j*.

Yamaguchi, S., Koiwa, M., and Hirabayashi, M. Interstitial superlattice of Ti_2O and its transformation, (10) 322*g*.

Yamaguchi, T. See Inoue, E.; Kuno, H.

Yamaka, E. See Morikawa, K.

Yamakawa, O. See Ando, J.

Yamamoto, D. Effect of gamma-ray irradiation upon glycol-bentonite and application of irradiation effect to gamma-ray dosimetry, (6) 185*f*.

Yamamoto, H. See Makishima, S.; Ueda, K.

Yamamoto, K. Symmetrical negative resistance in valence-exchange-type semiconductor glass junctions, (3) 87*h*.

Yamamoto, N. See Bando, Y.

Yamamoto, R. See Nishimura, Y.

Yamamoto, R., Nishimura, Y., and Kurokawa, R. Dispersion of clay for particle size determination, (1) 21*d*.

Yamamoto, R., Tanaka, A., and Hattori, T. Effect of particle size distribution on bodies for glazed roofing tile, (1) 15*e*.

Yamamoto, S. See Yuri, Y.

Yamamoto, T. Investigation of corrosion test methods for refractory brick, (10) 303*i*. See Kozuka, T.; Nakayama, N.; Suzuki, H.

Yamane, M., and Sakaino, T. Chemical composition of phase-separated droplets in soda-lime-silica glass, (4) 93*d*.

Yamanouchi, T., Ochiai, E., and Iwai, F. Photoconductive properties of zinc oxide modified by hydrogen sulfide, (5) 156*i*.

Yamasaki, Y. See Shigata, H.

Yamase, H. Apparatus and method for producing silicon single crystals for semiconductor, P (6) 177*a*.

Yamashita, A., Hagiwara, H., and Yamauchi, I. Effect of Cu_2O on the polarization of (Zn, Cd)S, (11) 352*a*.

Yamashita, A., and Nii, R. Field distribution in *n*-type GaAs under high electric field, (5) 138*a*.

Yamashita, N. See Takahashi, M.

Yamauchi, F. See Akashi, T.; Takahashi, M.

Yamauchi, I. See Yamashita, A.

Yamauchi, S., Yanagi, M., and Matsumoto, H. Measurement of particle size distribution with the Bahco type classifier, (1) 21*e*.

Yamazaki, I. See Nangoh, T.

Yamshchikov, V. S., Levushkin, L. N., Bondarenko, V. G., and Sviridov, V. M. Control of carbonate rock quality by ultrasonics, (3) 77*e*.

Yanagawa, T. Scribing method for semiconductor wafers, P (10) 311*b*.

Yanagi, M. See Yamauchi, S.

Yanagida, K. See Funahashi, Z.

Yanagida, O., Nakagawa, K., and Izumitani, T. Defects of highly siliceous borosilicate glasses during melting, (8) 230*i*.

Yanai, H. See Nakashima, H.

Yando, S. Piezoelectric-electroluminescent display device containing nonlinear resistance layer, P (7) 209*i*.

Yanir, E. See Mayer, I.

Yannaquis, N. See Bigare, M.

Yano, T. See Tsuchihashi, S.

Yans, F. M. See Gardner, N. R.

Yaremenko, Z. A. See Tresvyatskii, S. G.

Yartsev, M. A. See Kaibicheva, M. N.

Yastrebova, L. S., Vitkovskaya, E. V., and Bessonov, A. A. Effect of small additions of aluminum oxide on the chemical stability and structure of high-alkali potassium silicate glasses, (2) 38*j*.

Yasufuku, M., Kawamura, T., and Hayashi, T. Method of making semiconductor devices by diffusing and forming an oxide, P (11) 344*b*.

Yasuoka, H. ^{55}Mn nuclear magnetic resonance of Mn^{2+} ions located at B-sites in manganese ferrite, (4) 113*f*. See Kubo, T.

Yasutake, Y. See Hayakawa, M.

Yates, D. J. C. Stability of metallic cations in zeolites, (11) 357*b*. Studies on the surface area of zeolites as determined by physical adsorption and X-ray crystallography, (11) 357*g*.

Yates, G. See Bramman, J. I.

Yavorsky, P. J. Zirconia-magnesia composition and method of making and using the same, P (5) 136*d*. See King, A. G.

Yawata Welding Electrode Co., Ltd. Method for electroslag welding, P (2) 38*d*.

Yazicizade, A. Y. Investigation of heat transfer and pressure drop in regenerators with granular or chimney-flue-like heat reservoirs, (6) 167*b*.

Yeda Research & Development Co., Ltd. Method and apparatus for controlled deposition of a thin conductive layer, P (6) 177*h*.

Yeh, H. C. See McNally, R. N.

Yeh, Tsu-Hsing. See Fang, F. F.

Yell, B. R. See Goodson, S. O.

Yen, W. T., and Salman, T. Calibration of the surface meter with BET gas adsorption method in measuring specific surface of fine mineral particles, (11) 346*d*.

Yep, T. O., and Becker, W. M. Shubnikov-de Haas effect in lithium-diffused tellurium-doped *n*-type gallium antimonide, (9) 286*c*.

Yetter, L. R. See McDermott, P. S.

Yissum Research Development Co. Method and apparatus for the determination of K and Na, P (11) 347*j*.

Yodis, A. W. See Kelly, D. H.

Yohe, G. R. Clays as binding materials, (1) 10*g*.

Yokoi, A., and Kitada, A. Properties of fireclay from Irao Province, Kumamoto Prefecture, (9) 268*c*.

Yokokawa, T., and Kleppa, O. J. High-temperature calorimetry in the liquid oxide systems (II) enthalpies of solution of oxides of type MO in vanadium(V) oxide, (6) 186*c*.

Yokoyama, M. See Kuno, H.

Yonemochi, O. See Okubo, T.

Yonezawa, K. See Murabayashi, M.

Yong, R., Taylor, L. O., and Warkentin, B. P. Swelling pressures of sodium montmorillonite at depressed temperatures, B (5) 160*j*.

Yoshida, H. Results of service tests conducted on 60, 90, and 100% zircon ladle bricks, (7) 203*f*. Results of use tests on direct-bonded basic brick in an open-hearth furnace roof, (9) 269*c*.

Yoshida, T., and Takei, T. Acceleration of the crystallization of highly refractory glass-ceramic fiber by salt treatment, (8) 230*d*.

Yoshikawa, H. Mechanical properties of abrasive grain, (11) 331*g*.

Yoshino, K. See Nishino, T.

Yoshioka, H. See Hirose, T.

Yoshioka, S., and Takayanagi, S. Growth of silica films, (8) 254*f*.

Yoshioka, T. See Ichinose, N.

Yoshizawa, S., and Watanabe, N. Method of coating a shaped carbon article with a polycarbon fluoride, P (11) 340*i*.

Youkers, H. A., and Lush, J. Mold holder actuating mechanism, P (3) 66*a*.

Youmans, A. P. Thin film resistor, P (8) 246*f*.

Young, B. See Daem, R. C.

Young, C. G. See Landry, R. J.

Young, D. A. Caustic-treated zeolites, P (6) 182*j*. Pelleted zeolite compositions possessing improved crushing strength, P (3) 78*a*. See Domingy, D. A.

Young, H. F. See Bange, G. R.

Young, H. S. Germanium selenides and processes for their production, P (7) 208*i*. See Bither, T. A.

Young, H. W. See Wesson, R. A.

Young, J. R., Hudson, J. B., and Watters, R. L. Monopole mass spectrometer having one ceramic electrode coated with metal to within a short distance of each end, P (2) 55*g*.

Young, R. A. Physical properties of quartz at and near the transition (extended abstract), B (6) 19 *i*.

Youngblood, J. L. See Heckel, R. W.

Yount, J. G., Jr. Hot gunning materials for basic oxygen furnace maintenance, (4) 96*c*.

Youssef, Y. L., Mishriki, A., and Mikhail, H. Effect of illumination on the surface potential of cadmium sulfide, B (10) 328*f*.

Yousuf, M., Latif, M., and Ariff, M. R. Optimum conditions for the casting of conventional semi-porcelain body, (9) 271*a*.

Yu, C. Method for applying photographic images or designs to ceramic objects and improved photographic emulsion for the production of multicolor images or designs on such objects, P (5) 137*b*.

Yu, C. W. See Arthanari, S.; Soliman, M. T. M.

Yu, H. N. Formation of semiconductor devices, P (5) 141*i*. See Fang, F. F.

Yuasa, T., Tomita, T., and Ohta, K. Crystal structure of SiC 14H, (10) 319*a*.

Yudin, B. F. See Borisov, V. G.

Yudin, D. M., Tsurikova, G. A., and Petrovksii, G. T. Paramagnetic resonance of fluoberyllate glasses with cobalt and nickel, (3) 64*a*.

Yurganov, N. N., Safonov, N. A., and Brodkina, E. R. Reducing circulating alkalis during dust recycle in a rotary kiln, (2) 36*g*.

Yuri, Y., Asai, K., and Yamamoto, S. Studies on clay-bonded silicon carbide refractories (I) effects of grading of silicon carbide (as aggregate) on the properties of refractories, (9) 269*a*.

Yuster, P. H. See Delbecq, C. J.

Yutina, A. S., Zhukova, Z. D., and Lysak, S. V. Reaction of phosphoric acid with some forms of alumina, (9) 268*c*.

Zackey, V. F. See Thomas, G.

Zaeschke, W. Prefabricated joints for stoneware pipes, (4) 95*j*.

Zagar, L., and Krause, G. Determination of specific surface of glass powders and its relation to the parameters determined statistically by grain size analysis, (6) 166*j*.

Zaichenko, A. R., and Puryga, S. S. Cooling in the unloading area, (10) 312*c*.

Zaichik, R. I. See Palatnik, L. S.

Zaininger, K. H. See Reveen, A. G.

Zajac, B. J. See Unzicker, A. E.

Zakharchenko, M. A. See Gladushchenko, V. A.

Zakhm, F. G. A. See Barakat, N.

Zaliouk-Gitter, A. See Treinin, A.

Zaliouk-Gitter, A., and Treinin, A. Inorganic radicals trapped in glasses at room temperature (I) iodine atoms and I_2^- in boric acid glass, (5) 127*f*.

Zalm, P., Sprengers, J. W. C., Stratum, A. J. A. van, and Linden, P. C. van der. Dispenser cathode, P (6) 177*d*.

Zambernard, M. J. Process for maintaining straightness in extruded ceramic sections, P (10) 317*b*.

Zanaboni, P. Apparatus for continuous glass spinning, P (8) 235*c*.

Zanchi, G. B. Quality of sanitary ware—a mutual guarantee for the manufacturer and user, (9) 271*b*.

Zane, R. Flexible abrasive disk, P (3) 61*f*.

Zanemonets, V. F., Grosheva, V. M., and Shcherbina, O. D. Method and apparatus for the rapid determination of the thermal diffusivity of refractory materials over a wide temperature range, (11) 346*h*.

Zanio, K., Akutagawa, W., and Mayer, J. W. Transport properties of semi-insulating CdTe using nuclear particles, (3) 72*h*.

Zanni, M. See Golmard, M.

Zaporozhskaya, Z. P. See Botvinkin, O. K.

Zaporozhskii, A. I. See Botvinkin, O. K.

Zapp, H. R. See Auld, B. A.

Zaromb, S. Conductive oxide-coated articles, P (7) 198*g*. Electrically conductive optical element, P (7) 208*c*.

Zarubitskii, O. G., Belen'kii, B. S., and Omel'chenko, O. A. Investigating the resistance of some refractories in lead chloride melts, (9) 267*d*.

Zarzycki, J. Coordination in glasses, (6) 166*j*. See Boinot, J. D.

Zarzycki, J., and Naudin, F. Study of kinetics of the metastable phase separation in the PbO-B_2O_3 system by small-angle scattering of X rays, (1) 32*c*.

Zauner, O. Article handling apparatus, P (4) 94*d*.

Zawadzki, A. Aspects of the process of continuous drawing of glass fibers, (10) 297*a*.

Zaytseva, L. I., Il'yashenko, V. S., Konarev, M. I., Konovalov, L. N., Lipis, L. V., and Chebotarev, N. T. Physicochemical properties of the crystal hydrates of the sulfates of the rare earth elements in the terbium subgroup, (9) 285*c*.

Zbuzek, B. See Skvara, F.

Zdansky, K. See Sroubek, Z.

Zdanuk, E. J., and Krock, R. H. Tungsten-indium powder bodies infiltrated with copper, P (3) 74*d*. Tungsten powder bodies infiltrated with copper-titanium alloys, P (3) 74*e*.

Zecchin, L. Murano terminology in the book by Neri, (1) 6*j*.

Zechanowitsch, G. See Barkley, D. J.

Zeiss, C. See Carl-Zeiss-Stiftung.

Zeitlin, A., and Brayman, J. Apparatus for pressurizing a liquid, P (5) 144*d*.

Zejma, G. S. Method for fluid tightly securing a metal part to a glass member, P (4) 95*a*.

Zeldin, C. A. See Wood, W. A.

Zeller, E. J. See Vaz, J. E.

Zeller Corp. Spark plug and process of manufacturing the same, P (6) 175*h*.

Zellers, J. T., Jr. Sheet glass apparatus, P (11) 336*g*.

Zemanova, D. See Panek, Z.

Zemlicka, J. See Barta, C.

Zemon, S., Wasko, J. H., Hope, L. L., and Zucker, J. Frequency spectrum of acoustic waves generated in photoconducting CdS in high electric fields, (2) 49*j*.

Zemskov, G. V., and Shestakov, A. I. Diffusional metallization of graphite powders, (2) 43*g*.

Zen, E-an. Application of one-dimensional lattice model to mixed-layer muscovite-montmorillonite (abstract), B (9) 289*e*. Mixed layer minerals as one-dimensional crystals, (7) 219*a*.

Zengals, L. K. See Brady, J. B.

Zenner, G. P. Method of making a planar diffused semiconductor voltage reference diode, P (7) 209*g*.

Zeold, I. Up-to-date brickmaking technology (1) 10*g*.

Zettl, S. M. See Meyer, R. E.

Zevin, L. S. See Bogdanova, G. S.

Zhdanova, V. N. See Grigor'eva, V. V.

Zhdanova, V. V. See Shelimova, L. E.

Zhechkov, G. See Kolev, M.

Zhechkova, L. A., Mukhina, R. E., and Romanova, N. S. Determination of titanium in titanium dioxide, (10) 314*d*.
Zhitov, B. N. See Karshenbaum, A. G.
Zhornik, A. I. See Sidorov, A. B.
Zhukauskas, R. S. M. See Toropov, N. A.
Zhukov, V. V., Zyat'kov, A. I., and Shevchenko, V. I. Method for determining the gas permeability of refractory concrete, (10) 303*d*.
Zhukov, Yu. A., Kind, V. V., and Kuntsevich, O. V. Alkali activity of slag portland cement, (5) 124*f*.
Zhukova, Z. D. See Yutina, A. S.
Ziegler, G. Process of producing monocrystalline layers of indium antimonide, P (3) 74*c*.
Ziehr, G., and Drosdziok, H. Process for the treatment of metal surfaces prior to enameling, P (5) 126*c*.
Ziemba, F. P. *Pn* junction device with interstitial impurity means to increase the reverse breakdown voltage, P (5) 142*b*.
Ziemendorf, E. F., and Lampus, J. R. Electrical welding method and apparatus, P (5) 141*c*.
Ziemke, M. C. Heat flux transducers, (4) 102*k*.
Ziman, J. Thermal properties of materials, B (11) 358*i*.
Zimina, T. D. See Bergman, A. G.
Zimmer, W. H. Air cleaner, P (6) 179*f*.
Zimmerley, S. R., and Messner, M. E. Process for producing molybdic oxide from molybdate solutions, P (2) 57*b*.
Zimmerman, D. W., and Jones, D. E. Photo- and thermoluminescence of LiF:(Mg, Ti), (4) 114*d*.
Zimmerman, H. N. See Lepiane, D. C.
Zimmerman, J. B. See Barkley, D. J.
Zimmermann, K. A. See Koenitzer, J.
Zingaro, R. A. See Irgolic, K.
Zinggl, H., and Simmingskold, B. Measurement of the effect of surface coatings on friction between glass containers, (5) 127*j*.
Zinov'yev, Yu. Z. See Klassen, V. I.
Ziolkowski, J. See Deren, J.
Zirconium Corp. of America. Zirconia-magnesia composition and method of making and using the same, P (5) 136*d*.
Zirngibl, H., and Rademachers, J. Process for the production of titanium tetrachloride, P (4) 105*f*.
Zisner, T. Process for the manufacture of low-porosity burned magnesia, P (7) 205*g*. See Tagai, H.
Zisner, T., and Tagai, H. High-temperature creep of polycrystalline magnesia (II) effects of additives, (7) 218*d*.
Zitkus, W. J. Apparatus for homogenizing molten glass, P (5) 129*a*.
Zittel, H. E., and Florence, T. M. Voltammetric method for fluoride, (4) 103*e*.
Zivanovic, B. See Delic, D.
Zlatovsky, I. See Proks, I.
Zloczower, W. Solid state triode having gate electrode therein subtending a portion of the source electrode, P (4) 101*c*.
Zmbov, K. F. See Cvjeticanin, D.; Kent, R. A.
Zoerb, H. M. See Gasparac, R. J.
Zografou, C. See Mields, A.
Zolotov, S. See Mayer, I.
Zoltai, T. See Jahanbagloo, C.
Zope, B. D. See Moorthy, V. K.
Zorin, A. P., and Zorina, M. L. Properties and structure of glasses in the system BaO-SiO_2-TiO_2, (9) 264*c*.
Zorina, M. L. See Zorin, A. P.
Zorina, M. L., Sarukhanishvili, A. V., and Setkina, O. N. Study of crystallization of multicomponent ferruginous glasses by infrared spectroscopy, (10) 299*b*.
Zorina, M. L., Setkina, O. N., and Ushakov, D. F. Infrared spectroscopic study of crystallization in vitreous crystalline enamels, (8) 229*h*.
Zozulya, P. V. See Sychev, M. M.
Zrimsek, A. H. See Vingas, G. J.
Zubik, A. R. See Lillard, J. G.
Zucker, J. See Zemon, S.
Zuegel, M. A. Vapor phase equilibria in the gallium-chlorine and gallium arsenide-chlorine systems, (4) 118*j*. See Buchanan, R. C.
Zuev, L. B. See Finkel, V. M.
Zuikov, N. V., Tsvetaev, A. A., and Bardyukov, M. E. Thermocouple to measure temperatures up to 2500°K, (5) 146*g*.
Zuk, P. Fabrication of semiconductor integrated devices with a *pn* junction running through the wafer, P (6) 177*h*.
Zukas, E. G. See Green, W. V.
Zuleeg, R. Combination of thin-filmed [integrated] electrical devices, P (5) 140*i*. High frequency field-effect triode device, P (8) 244*e*. See Hinkle, V. O., Jr.
Zuleeg, R., and Hinkle, V. O., Jr. Planar multichannel field-effect triode, P (8) 245*j*.
Zuleeg, R., and Knoll, P. Space-charge-limited currents in heteroepitaxial films of silicon grown on sapphire, (5) 158*g*.
Zunkel, A. D., and Larson, A. H. Slag-metal equilibria in the Pb-PbO-Sb_2O_3 system, (4) 115*g*.
Zvonik, V. A. See Klimov, V. V.
Zvyagin, B. B. Electron-Diffraction Analysis of Clay Mineral Structures, B (10) 328*i*.
Zvyagintsev, O. E. See Sinitsyn, N. M.
Zweig, G. Chromatography, (10) 313*j*.
Zwetsch, A. Frost damage on earthenware wall tile, (7) 206*a*.
Zyat'kov, A. I. See Zhukov, V. V.
Zykova, Z. K. See Bluvshtein, M. N.
Zyl, C. R. van. See Strelow, F. W. E.
Zysk, E. D. Noble metal thermocouple having base metal leads, P (6) 181*f*.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1968

The number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin*, see indexes to the *Journal* and the *Bulletin*.

Ablation, ablators, charring, mechanical erosion in ground-test and reentry environments, (9) 267*i*.
material performance under high-shear reentry conditions, (9) 268*g*.
materials, rapidly charred, technique for mechanical strength testing of, (8) 229*i*.
Abrading apparatus. See *Grinding apparatus.*
Abrasion, of Cr–SiO cermet resistors, phenomenon associated with, (10) 307*h*.
of oxide ceramics under influence of surfactants, (7) 210*j*.
Abrasives. See also *Aluminum oxide; Carbides; Diamonds; Grinding apparatus; Polishing apparatus; Silicon, carbide.*
article, solid, and method of making honing elements from, P (11) 331*g*.
bauxite, particles, microcrystalline sintered, P (9) 261*g*.
belt handling device, P (5) 123*g*.
blasting techniques, inhibitive, comparison, (11) 331*g*.
bonded media, for mass finishing, (11) 331*f*.
capacity, of powders of carbides and borides of refractory metals, measurement, (3) 67*i*.
coated, for electrolytic grinding, P (7) 193*h*.
coated, flexible products, P (9) 261*h*.
composition, for accelerated grinding, P (1) 1*g*.
compositions and structures with thermosetting resin and thermoplastic polyarylene polyether, P (3) 61*g*.
crystal, apparatus for making, P (7) 193*f*.
cutting and grinding devices, P (1) 1*g*.
cutting insert for chip cutting machining, and means for manufacturing, P (5) 123*i*.
cutting tools, dispersion strengthened Al_2O_3 with tungsten or molybdenum as, P (5) 123*i*.
diamond, "D" dropped in designation, (5) 123*g*.
diamond, in lapping forsterite, (5) 123*g*.
disk, P (8) 227*g*.
disk, flexible, P (3) 61*f*.
grain, mechanical properties, (11) 331*g*.
grains, coarse, evaluation of shape, (9) 261*f*.
improved, P (7) 193*f*.
industry, current achievements, (9) 261*f*.
demands in the future, (5) 123*f*.
ITT, case study, (5) 123*h*.
metal-carbide, method of forming, including grinding and chemically dressing, P (7) 205*b*.
pulpstone mounting flanges, P (5) 123*j*.
roll, P (5) 123*h*.
separator, P (5) 123*h*.
wheels. See *Grinding apparatus.*
Absorption, of aggregates, accurate laboratory test for determining, (4) 102*d*.
of atmospheric CO_2 in tricalcium aluminate hexahydrate, (2) 36*b*.
atomic, for partial analysis of silicate rocks, (1) 22*i*.
atomic, to study kinetics of reaction between MgO and Cr_2O_3, (4) 96*i*.
bands, ultraviolet, of vitreous sodium silicates, development during melting, (9) 280*c*.
in emerald, (3) 78*g*.
free-carrier, in reduced $SrTiO_3$, (9) 282*e*.
infrared, of $AlPO_4$ and SiO_2, dependence on disordering and temperature, (8) 252*j*.
due to donor electrons in semiconductors, (10) 322*e*.
due to free electrons in CdSe, (5) 153*c*.
of Mg_2Ge, (8) 254*a*.
of orthoborate ion, (3) 82*a*.
magneto-, interband, in InSb, (11) 353*f*.
modulated F-center in KCl, (10) 323*a*.
of neodymium, in germanium glasses, (6) 169*a*.
nitrogen and water-vapor, for characterization of rutile surface, (7) 216*b*.
optical, of Cr^{3+} in phosphate glass, (5) 127*i*.
of divalent Co in binary alkali borate glasses, and relation to basicity of glass, (7) 196*j*.
in GeO_2, (3) 80*c*.
of irradiated doped vitreous silica, (7) 197*e*.
of photoelectrons in CdS, (11) 355*d*.
in rare earth doped Y_2O_3 and LaF_3 single crystals, (10) 324*b*.
in semiconductors, application of solvable model of hydrogenic system in strong electric field to, (10) 325*a*.
studies of mixed-ion (Cu and Al) doping of sphalerite, (9) 265*a*.
in SnS_2 and $SnSe_2$, (9) 282*e*.
of phosphor YVO_4:Eu, empirical studies, (4) 109*g*.
selective, of circularly polarized light in broad bands by Zeeman components of divalent thulium in calcium fluoride, (9) 286*j*.
Absorption (*continued*)
spectra. See *Spectra.*
two-magnon, in antiferromagnetic MnF_2, (10) 327*a*.
two-photon, in alkali halides with pulsed N_2 laser, (11) 357*j*.
processes, high speed measurement, (6) 180*e*.
stepwise, in Er^{3+} doped salts, (1) 17*g*.
ultraviolet, of chromium(VI) in binary alkali borate glasses, (1) 8*e*.
of chromium(VI) in binary and ternary alkali and alkaline earth oxide glasses, (7) 197*f*.
of glass, (5) 129*f*.
of ruby and sapphire, (7) 222*j*.
Acids. See also specific types.
-base, high-temperature reactions: I, aliphatic amine onium salts with strontium and barium carbonates; II, methylammonium chloride with metal oxides, (6) 186*b*.
hydroxylated carboxylic, type admixture, effect on false set of cement, (11) 331*i*.
organic, effects on setting of gypsum plaster, (10) 294*e*.
silicic, process of preparing in two-dimensional structure, P (1) 25*i*.
silicic, surface states, comparison with quartz and cristobalite, (10) 319*j*.
Acoustics. See also *Insulation, acoustical; Sound.*
absorption and insulation, (7) 214*c*.
acoustooptical deflection and modulation devices, (9) 277*c*.
-dilatometric studies of borosilicate glasses, structural parameters, (10) 296*i*.
nonlinear frequency mixing, detection with optical Bragg diffraction, (11) 350*c*.
waves, frequency spectrum generated in photoconducting CdS in high electric fields, (2) 49*j*.
Actinide, metal monocarbide, preparation from oxide of, P (9) 270*a*.
Activation, parameters, for dislocation glide, (4) 105*i*.
Additives, method for applying doping compositions, P (3) 73*g*.
Adherence. See also *Enamels.*
of glass to metal, temperature, (8) 234*a*.
Adhesion, capillary forces, between solid particles with intermediate liquid layer at contact: II, effect of degree of wetting, (9) 279*j*.
of plasma coatings to base, (8) 237*a*.
Adhesives, for fixing ceramic tiles, P (1) 15*j*.
Adsorption, of admixtures on portland cement hydration products, (2) 36*c*.
of ammonia on dry γ-alumina, infrared study, (11) 353*f*.
of argon on anatase at low relative pressures, (1) 26*e*.
behavior, of hydrous BeO in media of varying pH, (7) 215*h*.
of CO_2 at high pressures by Al_2O_3, determined from measurement of dielectric constant, (3) 78*i*.
of dyestuffs by clays from nonaqueous systems, (1) 26*f*.
fluoride, by thorium oxide in aqueous thorium nitrate solutions, P (11) 340*c*.
krypton gas, method for measurement of surface areas of powders, (1) 21*g*.
methylene blue, by fine grained sediments, (5) 148*d*.
n-propyl alcohol, on montmorillonite, investigation by infrared spectroscopy, (11) 353*g*.
of orthophosphate, on ternary borate glasses, radiochemical study, (8) 233*j*.
of oxygen, on sintered plutonium dioxide, (5) 131*d*.
physical, for determination of surface area of zeolites, (11) 357*g*.
physical, on massive glass surfaces, (1) 6*i*.
at solid/liquid interface, factors involved, (4) 110*i*.
stepwise, of colloidal CdS particles on glass, (10) 298*g*.
of 13 *s*-triazine compounds on montmorillonite clay, molecular structure and pH effects on, (5) 155*a*.
of volatile vapors by clays, infrared techniques for studying, (6) 180*g*.
of water vapor on silica-alumina treated with potassium chloride, (3) 78*g*.
Aegirine, -augite, from Seal Lake, Labrador, (1) 26*k*.
Aerogels. See *Colloids; Silicon dioxide.*
Aerosil, silicas, investigation by infrared spectroscopic methods of deuterium exchange properties of, (3) 82*a*
silicas, investigation of 1800 to 1400 cm^{-1} region of infrared spectrum, (3) 82*j*.
Aerosols. See *Colloids.*
Agglomerates, ternary metallic oxide, and method of preparation, P (6) 175*c*.
Agglomeration, on inclined surfaces including vibrating material at greater angle than inclination of surface, method and apparatus, P (5) 144*c*.
Aggregates, centers, formation in additively colored KCl, (8) 253*i*.
for concrete, blast furnace slag as, (4) 92*b*.
dolomitic limestone, alkali reactivity, (4) 91*j*.
heavy, for shielding nuclear reactors, (7) 203*k*.
lightweight, from fly ash pellets, P (6) 172*b*.
high-strength, and method for making, P (7) 199*g*.
manufacture and use, (1) 10*i*.
shale, sources in New Mexico, (7) 214*g*.
shales for in Appalachian region, Kentucky and Tennessee, (10) 301*j*.
by sintering process, for concrete, (10) 301*f*.
uniform, P (1) 10*i*.
macroscopically isotropic, of cubic crystals, bounds of shear modulus of, (4) 106*j*.
producing by heating solid inorganic material, P (1) 3*e*.
synthetic lightweight, process development from fly ash with pulp waste liquor, (6) 165*j*.
use in structural clay body design, (6) 172*a*.
Aging, effect, magnetic, of Fe_3O_4-γ-Fe_2O_3 solid solution, (3) 83*g*.
Air, cleaner, P (6) 179*f*.
compressed, system, (2) 53*b*.
industrial cleaning, (6) 179*c*.
pollution—control of SO_2 from power stacks: I, removal of sulfur from fuels; II, removal of SO_2 from stack gases by CaO or MgO, (4) 101*k*.
dust extraction, economical in ceramic factory, (4) 101*i*.
field control of dolomite plant, (6) 190*j*.
special industrial processes, (6) 179*b*.
testing, and dust sampling in industry, (4) 101*i*.
Aircraft ceramics. See *Cermets; Spacecraft; Turbines.*
Albite, low and high, thermal expansion, (6) 190*b*.
solid solution series, Orville's microcline-low, axial angle determinations in, (6) 183*j*.
Alite, composition, (6) 164*b*.
Alkaline earths. See also specific types.
dihydroxides, gaseous, heats of dissociation, (3) 81*j*.
rare earth-, oxide compounds, (5) 155*f*.
Alkalis. See also specific types.
action, on transition-metal carbides, (5) 149*g*.
borates, binary, subliquidus immiscibility in, (8) 257*j*.
circulating, reducing during dust recycle in rotary kiln, (2) 36*g*.
effect on refractories in cement kilns, (10) 302*f*.
effect on spalling characteristics of fireclay refractories, (5) 131*h*.
halides. See *Halides, alkali.*
iodides, Debye-Waller factor and second-order Doppler shift of ^{129}I in, (9) 280*c*.
metal phosphides, preparation and methylation, (1) 12*a*.
metal titanates, thermally stable fibrous, P (8) 246*d*.
nitrates, molten, thermal conductivity, (7) 197*b*.
oxides, in glasses and silicate raw materials, flame-photometric method for determination, (10) 314*d*.
systems. See *Systems.*
Alloys, Al–Al_2O_3, blended and ball-milled, physical and mechanical properties, (2) 45*e*.
aluminum-4.5% Cu, effect of mold materials on microstructure, shrinkage, and mold wall movement, (2) 44*c*.
and compounds, production and remelting, P (5) 142*f*.
containing chromium and dispersed refractory metal oxide particles, process for producing, P (10) 305*b*.
copper-nickel, scale initiation on, (11) 356*h*.
hard, with uneven distribution of carbide phase, conditions of formation, (8) 238*h*.
of InSb with In_2Te_3 and tellurium, (7) 207*a*.
iron-aluminum and iron-silicon, Curie temperature, (5) 137*g*.

Alloys (*continued*)
iron-carbon, toughness, effect of noble metal additions on, (6) 185*b*.
$Pb_{1-x}Sn_xTe$, phase studies, (4) 114*c*.
molybdenum-carbon, binary, constitution, (6) 184*j*.
nickel-aluminum, oxidation mechanisms at temperatures between 900° and 1300°C, (6) 187*b*.
nickel-chromium, pure, characteristic scales at 800° to 1200°C, (7) 207*b*.
silver-indium, forming passivating internal In_2O_3 bands in, P (7) 210*b*.
Ta–Mo–Co, constitution, (6) 184*b*.
ternary, in pseudobinary system Sb–SnTe, electrical properties, (11) 355*b*.
WC–Co, effect of plastic deformation on, (5) 132*a*.
WC–Co, reaction with oxygen at 1000° and 1100°K, (2) 45*i*.
WC–TaC–Co and WC–NbC–Co, structure and physical properties, (7) 203*d*.
WC–5%TaC–10%Co, properties, relations with methods of adding TaC, (8) 256*e*.
WC–TiC–10%Co (10% β-Co) two phase, properties in relation to carbon content of, (8) 256*i*.
uranium-carbon, effects of thermal cycling, (6) 172*j*.
ZrB_2 and $MoSi_2$, preparation, and determination of properties, (2) 46*g*.
Alumina. See *Aluminum, oxide*.
Aluminates. See also *Alkaline earth*.
divalent metal, single crystal growth, P (6) 190*g*.
tricalcium, hexahydrate, absorption of atmospheric CO_2 in, (2) 36*b*.
Aluminosilicates, crystalline, chemistry: I, factors affecting formation of zeolite A; II, III, synthesis and properties of zeolite ZK-4 and ZK-5, (10) 319*h,i,j*.
crystalline, nodules or extrudates, process for making, P (7) 215*d*.
crystalline, preparation, and alkali metal and alkylammonium phosphatoaluminate complexes, P (9) 279*b*.
synthesis, (1) 30*d*.
Aluminum, alkoxides, hydrolysis, P (11) 349*f*.
AlAs-GaAs mixed crystals, preparation and properties, (7) 207*i*.
Al_2O, gaseous, infrared spectrum and structure, (5) 153*e*.
-Al_2O_3 alloys, blended and ball-milled, physical and mechanical properties, (2) 45*e*.
-Al_2O_3 structures, for nuclear applications, process for obtaining, P (10) 305*a*.
$2Al_2O_3 \cdot 5WO_3$, linear thermal expansion, (5) 154*j*.
$AlPO_4$, low-quartz modification, structure, refinement of, (8) 256*d*.
Al–Si and Al–Si–Mg alloys, electrical conductivity, (1) 16*e*.
antimonide, metallic, superconductivity, (4) 117*f*.
n-type, weak-field magnetoresistance in, (8) 258*c*.
n- and *p*-type, piezoresistance and piezo-Hall effects in, (11) 355*b*.
aqueous, hydroxide, fluoride, and sulfate complexes, graphical methods for studies of, (6) 180*d*.
borides, crystalline, preparation by vapor deposition process, (2) 45*i*.
borides, preparation and properties, (2) 45*d*.
carbide, hydrolysis in D_2O, (4) 111*a*.
carbides, formation by explosive shock, (2) 44*i*.
diboride and α-aluminum dodecaboride, heats of formation, (4) 111*c*.
enameled, offers color and versatility, (10) 296*e*.
enameling of, for building construction, (1) 4*i*.
films, vacuum-deposited, electron microscopic observation on thermal oxidation, (11) 352*j*.
fluoride, anhydrous, vapor phase reaction with boron oxide, (6) 190*e*.
fluoride, manufacture with moving aluminum fluoride bed, P (8) 250*d*.
high, ceramic, effect of surface grinding on physical properties, (7) 211*d*.
in high strength porcelain bodies, (11) 341*d*.
hydroxide, calcining by cross-flowing heating gas, P (8) 251*f*.
complexes, form and stability in dilute solution, (4) 110*c*.
kneading pretreatment for production of, P (3) 68*k*.
-montmorillonite complexes, nature, (2) 50*h*.
zeta potential in relation to water treatment coagulation, (1) 34*a*.
hydroxides, production and investigations of X-ray and catalytic properties of oxide, (5) 157*g*.
molten, corrosion of Al_2O_3 system crucible by, (11) 350*j*.
nitrate nonahydrate, decomposition, P (5) 135*b*.
nitride, analysis, (10) 313*a*.
films, by chemical transport, (11) 350*g*.
method of making, P (11) 340*b*.
preparation, optical properties, and electrical behavior, (2) 50*c*.
purified, production process, P (11) 340*h*.
orthophosphate, infrared absorption, dependence on disordering and temperature, (8) 252*j*.
oxide. See also *Boehmite; Corundum; Refractories*.
α-Al_2O_3 content of, determination, (10) 313*f*.
α-, enthalpy, (7) 218*b*.
α-, infrared lattice spectra, (6) 186*b*.
α-, low-energy electron diffraction observations, (4) 112*c*.
α-, powders, explosively shocked, X-ray line broadening study of, (8) 258 .
α-, substrate, single crystal growth on, (10) 325*g*.
Aluminum oxide (*continued*)
from anorthosite, by lime-soda sinter process, (6) 182*i*.
Bayer, customed-processed for ceramic applications, (6) 182*e*.
bayerite, preparation, P (5) 149*a*.
bicrystals, fabrication, (5) 152*i*.
boehmite, products, P (7) 214*i*.
carbon-coated, and process for making, P (4) 104*k*.
ceramic, dense abrasion-resistant 99.8%, (8) 241*j*.
ceramic, in design of deep-ocean pressure case, (1) 15*c*.
ceramic, dry ball mill grinding of, (4) 101*k*.
ceramics, compatibility with potassium vapor, (6) 166*c*.
-chromia, optical reflection spectra, (5) 156*e*.
containing small concentrations of MgO, sintering, (5) 133*i*.
and copper oxides, mixtures, phase conversions in, (9) 283*k*.
in cords, determination by electron microphobe, (8) 231*d*.
crystals, grown by vapor deposition, morphological development, (5) 155*c*.
in cutting tools, (6) 163*f*.
deposition from vapor phase, (6) 172*g*.
determination in chrome-bearing materials, (6) 179*i*.
dislocation movement in brittle fracture of, (10) 319*f*.
disperse inclusions, effect on sintered nickel, (8) 237*e*.
dispersion strengthened, with tungsten or molybdenum, as cutting tools, P (5) 123*i*.
distribution in Pujada laterite of Mati, Davao Province, Mindanao Island, Philippines, (2) 50*h*.
dry grinding of, P (4) 105*a*.
effect on chemical stability and structure of high-alkali potassium silicate glasses, (2) 38*j*.
effect on whiteware bodies, (2) 48*f*.
evaluation in electronic tubes, symposium, B (4) 122*d*.
evaporation coefficient, systematics, (7) 222*b*.
evaporation rate, discontinuity in, (5) 151*c*.
extraction, from Pennsylvania aluminous clays, (5) 147*j*.
film, anodized, of high dielectric strength, properties, (3) 86*f*.
films, anodic, recrystallization, (4) 115*d*.
films, preparation, (4) 98*i*.
fission fragment damage in, direct observation, (9) 281*b*.
fused, production, P (11) 340*j*.
γ-, model for surface of, (11) 354*f*.
γ-, surface hydration, infrared and gravimetric study, (11) 353*d*.
γ-induced electrical conductivity in, (3) 81*g*.
-glass composite, hot-pressed, chemical reaction, (1) 26*j*.
in glass-free body, P (7) 206*g*.
high-, fused cast products, crystallization, (7) 201*a*.
high-temperature electrical conductivity, (3) 81*b*.
hot-pressing, new treatment of final densification, (1) 29*c*.
hydrated, effect of pH on ion-exchange properties of: I, capacity and selectivity; II, kinetics of exchange, (3) 80*f,k*.
inert-gas bombarded, low-temperature diffusion in, (8) 254*g*.
lapping characteristics, with ordinary abrasives, (5) 123*i*.
lattice parameters, effect of high pressure on, (6) 185*g*.
low-frequency grain-boundary relaxation in, (7) 219*e*.
-M system, cermets of, impact strength, (7) 202*b*.
melting point, effect of environment, (4) 108*j*.
microcrystalline corundum, sols, and processes for preparing, P (5) 135*d*.
microcrystals, grown by chemical vapor deposition, growth patterns on, (10) 321*e*.
microspheres, porous bodies from, (10) 303*f*.
molten, in arc-image furnace, (1) 32*i*.
monohydrate, process for producing colloida-size particles, P (3) 78*c*.
with narrow pore size distribution, process for producing, P (4) 105*d*.
neutron irradiated, gas release, (4) 110*e*.
-niobium graded, hot-pressed composites, (7) 202*a*.
particles, attrition resistant, production, P (7) 215*f*.
particles, and method of preparation, P (3) 77*i*.
particulate, replication, for examination by electron microscope, (8) 248*f*.
plasma-sprayed, structural changes on reheating, (8) 239*j*.
polycrystalline, chemical strengthening of, (6) 175*e*.
polycrystalline, leaching, machining, and refiring, (9) 272*d*.
porous, products, and method of manufacture, P (8) 251*b*.
powder, spheroidization in high-frequency plasma discharge, (7) 211*h*.
powder, surface and bulk states of additives in, (6) 189*e*.
preparation with pretreatment of sodium aluminate liquor with alcohol vapors, P (8) 251*b*.
pressure shift of Cr levels in, (8) 256*g*.
Aluminum oxide (*continued*)
process of making, P (10) 318*a*.
production, P (1) 14*e*.
pure, in electrical engineering and electronics, (5) 139*b*.
pure, homodispersed particles, effect of rate of temperature rise on sintering, (1) 28*a*.
reactive grade, P (5) 136*b*.
recovery from clay with organic polymeric materials, P (5) 149*a*.
recovery from Pacific Northwest bauxites by Pedersen process, (6) 182*g*.
rods, thermally conditioned 96%, residual stress and flexural strength, (5) 157*j*.
selective recovery from ores, P (9) 279*e*.
silica-, preparation, P (9) 279*e*.
in silicate rocks and minerals, determination by atomic absorption spectroscopy, (9) 276*b*.
sintered, as wear- and heat-resisting material, (8) 239*a*.
sintered products, applications as wear- and corrosion-resistant material and properties, (6) 172*h*.
sintering, criteria for selection of additives for theoretical density, (1) 27*i*.
sintering to theoretical density in vacuum, effects of residual gas on, (1) 28*d*.
solid state reactions with SiO_2, MgO, CaO, Fe_2O_3, and ZrO_2, (7) 221*b*.
by spectrographic methods, B (7) 224*g*.
spectroscopic determination, in raw materials and slimes of alumina manufacture, (10) 315*g*.
spheres, small, coordination number, (11) 350*j*.
strengthening by glazing and quenching, (10) 306*d*.
substrates, VO_2 coatings applied to, (4) 99*a*.
surface grain growth, effect of metal oxides on, (10) 319*h*.
in vacuum, melting point, (1) 30*f*.
$:V^{3+}$, $^3T_2$ excited term, dynamic Jahn-Teller effect in, (11) 351*j*.
vapor-deposited, transitions, from 300° to 1200°C, (1) 33*b*.
-water, differential heats of adsorption as function of particle size for, (11) 353*i*.
water hydrolysis reactor for making, P (8) 252*a*.
whiskers, sizing and mechanical testing, (5) 158*f*.
whiskers, structure and properties, (11) 339*j*.
oxidized, for passive thin-film circuits, (10) 307*f*.
phosphate, as bonding material for refractory specialties, (8) 239*j*.
phosphates, bond properties, (1) 11*c*.
in quartz, geochemistry, (7) 217*b*.
silica fiber reinforcement of, (8) 229*j*.
in silicate and other rock material, rapid complexometric determination, (5) 146*e*.
in silicates with ferron, spectrophotometric determination, (10) 315*f*.
silicates, thermodynamic properties, (5) 159*c*.
-silicon spinel, infrared spectra, (3) 82*b*.
sintered, powder, alumina phases in, after irradiation, (6) 185*g*.
spectrochemical determination in fluorite, (3) 76*f*.
sulfates, crystallized neutral, with low water content, preparation, P (11) 349*h*.
systems. See *Systems*.
Alunite, thermal and chemical behavior, and use as ceramic raw material, (8) 250*b*.
Amethyst, paramegnetic resonance and optical properties, (3) 84*c*.
Ammonia, adsorption on dry γ-alumina, infrared study, (11) 353*f*.
removal from ammonium zeolite, P (1) 13*j*.
Ammonium, alkyl-, phosphatoaluminate and alkali metal complexes, and preparation of crystalline aluminosilicates, P (9) 279*b*.
bromide and chloride, single crystals, V_k center in, (8) 258*a*.
silicates, P (1) 25*h*.
Amphiboles, Moessbauer study, (5) 155*i*.
natural and synthetic, fibers, effect of heat treatment on mechanical properties, (2) 44*a*.
Amplifier, lithium niobate parametric, direct measurement of gain, (1) 16*d*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays*.
absorption spectrochemical, apparatus for, P (9) 275*i*.
activation, for determination of phosphorus in rocks and minerals, (3) 77*f*.
activation, for silicates, (6) 181*a*.
of aluminum nitride, (10) 313*a*.
beta-ray-back-scattering, for determination of resin-to-glass ratio of glass-epoxy structures, (9) 276*a*.
chemical, of cements, new standard for methods, (3) 62*c*.
of fluoride, (4) 103*c*.
of lead in glass, (11) 333*g*.
of major constituents in rocks and minerals, (2) 53*j*.
quantitative, of minerals in thin section with X-ray macroprobe, (5) 146*c*.
of chrome-bearing materials: II, determination of alumina, (6) 179*i*.
of clinkers, determination of mineral content by rational chemical analysis, (3) 62*c*.
complexometric, of cement and clinker, accuracy of, (10) 294*a*.
of DTA curve using transfer function, (3) 78*k*.

Analysis (*continued*)
gamma-activation, (2) 54*e*.
gas effluent, B (8) 260*b*.
of gases released on cleaving muscovite mica in ultrahigh vacuum and of gases which remain adsorbed on freshly cleaved surface, (3) 78*i*.
gravimetric, differential, P (6) 181*g*.
of high-purity synthetic vitreous silicas, (3) 63*e*; reply, 63*e*.
of Pb, Ti, and Zr in precipitates for production of homogeneous lead zirconate-lead titanate solid solutions, (9) 271*i*.
micro- electron probe, (5) 145*h*.
electron probe, correction for continuous fluorescence in, (3) 75*e*.
electron probe, with specific X-ray spectrometer structure, P (5) 146*c*.
electron probe, of sphalerite, (6) 185*h*.
of inclusions in irradiated UO_2, (2) 45*a*.
microspectrochemical, of minerals with laser microprobe, (7) 212*j*.
neutron activation, for precision analyses of manganese in rocks, (5) 145*j*.
nondestructive, by weak radioactivation of sodium in solids in presence of K, Al, and Si, (6) 180*j*.
phase chemical, of MgO–Cr_2O_3–SiO_2 system, (8) 248*b*.
qualitative, laser microprobe sampling for, (9) 276*a*.
quantitative, with aid of calculated X-ray powder patterns, (11) 347*b*.
quantitative mineralogical, of carbonate sediments, comparison of X-ray diffraction and electron probe microanalyzer methods, (8) 248*d*.
quantitative phase, of electrical porcelain, (8) 242*f*.
rapid, of cement and clinker by thermometric method with direct percentage indication, (8) 228*i*.
separation and determination, of Fe, Al, Cr, Ca, and Mg, by ion exchangers and Komplexon III, (2) 55*b*.
of silicon and phosphorus with ammonium molybdate, and successive determination, (9) 286*a*.
of Na and K in silicates, effect of sulfate, oxalate, and perchlorate ions, (7) 212*j*.
spectral, application of lasers to, (7) 211*i*.
spectrochemical, apparatus, supplying same energy to gap for all waveforms, P (3) 76*g*.
spectrochemical, in determination of Al, Fe, and Si in fluorite, (3) 76*f*.
thermochemical, rapid, of chamotte, kaolin, and clay, (11) 347*b*.
thermometric studies of complex formation with iron, aluminum, and gallium (2) 55*i*.
titrimetric, of organic material in clay, (11) 347*c*.
of tobermorite by silicate-derivative technique, (3) 79*a*.
trace element, of geological materials, precision and accuracy using solid source spark mass spectrography, (1) 22*h*.
of unperturbed dimensions of linear polyphosphate chain, (3) 79*b*.
volumetric, of titanium, (2) 55*a*.
volumetric and gravimetric, for inorganic compounds, (8) 249*a*.

Analyzers. See also *Gases*.
electronic particle size, for measurement of roundness and sphericity parameters, (2) 54*c*.
micro-, AMX, (10) 313*a*.
micro-, electron probe, applications to ceramics: I, potentialities; II, analysis of defects in ware; III, research problems, (6) 179*j*, 180*a,b*.
particle, threshold level control, P (10) 316*d*.
proton-excited soft X-ray, P (5) 147*b*.
radiation sensitive evaporative, P (11) 348*a*.

Anatase, -rutile transformation, enthalpy, (1) 29*a*.

Andalusite, mining, processing, uses and specifications, B (11) 358*h*.

Anelasticity, of uranium oxides, at room temperature: II, hyperstoichiometric oxides, (5) 132*c*.

Anions. See *Ions*.

Anisotropy, crystal, of density of surface states at Si–SiO_2 interface, (4) 107*e*.
of 3*c*, of hexagonal ferrite Zn_2Y, (4) 106*a*.
elastic, of crystals, (2) 58*c*.
of extruded graphite tubes, (5) 131*e*.
field, effective in-plane, in α-Fe_2O_3, (10) 320*b*.
in-plane, in α-Fe_2O_3, (4) 108*j*.
magnetic, induced by electron diffusion in $Co_{1+2x}Fe_{3-2x}$ and $Fe_{1-2x}Ni_{2x}Co_2O_4$, (4) 112*g*.
magnetic, in NiO: I, theory; II, experiment, (4) 112*h*.
magnetocrystalline, of single crystal CrO_2, (4) 112*i*.
medium, elastic field of inclusion in, (9) 281*g*.
in oxidation of graphite, (10) 319*a*.
perpendicular, of magnetic thin films originating from nonmagnetic grain boundaries, estimation, (3) 80*j*.

Ankerite, thermal decomposition, (9) 287*j*.

Annealing, conditions, effects on magnetic properties of Mg-Mn ferrite and zinc and cadmium substituted Mn-Mg ferrite, (9) 271*i*.
effect on Young's modulus of reactor graphite, (8) 253*i*.
of glass. See *Glass*.
of irradiation damage in graphite, (4) 106*a*.
of radiation damage in ZnSe, (11) 350*i*.

Anodes. See also *Electrodes*.
anodizing, by applying positive potential to body immersed in plasma, P (0) 310*c*.
graphite, process for producing, P (1) 14*d*.
graphite electrolytic, (2) 49*d*.
magnesium, and the porcelain-lined tank, (9) 263*a*.

Anomalies, vibrational, in inorganic glass formers, (5) 129*j*.

Antennas, rods, ferrite, made from iron ore, properties and effect on receiver performance, (8) 243*a*.

Antiferromagnetism. See *Ferromagnetism*.

Antimony, SbSI, current saturation and photoferroelectric effect in, (3) 71*b*.
compounds, crystallization in glasses and enamels, (1) 3*j*.
systems. See *Systems*.

Apatite, calcium-deficient, structure and composition, (5) 158*a*; (6) 189*g*.
crystallites, effects of carbonate on morphology, (4) 106*d*.
flux-grown, for Sb^{3+} and Mn^{2+} activated calcium halophosphate phosphors, (7) 208*a*.
hydroxyl-, alkaline earth metal, processes for preparing and compositions containing, P (7) 204*d*.

Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.

Aquasols. See *Colloids*.

Archeology, ancient ceramics, dating by thermoluminescence, (1) 1*j*.
of ancient Egypt, in Royal Ontario Museum, (5) 124*e*.
ancient pottery, exploratory trace elements in, (8) 227*j*.
porcelain bowls, K'ang-hse, in Florida, (5) 124*c*.
porcelain from the Longol San Miguel burial site, Guimbal, Iloilo, (8) 227*j*.
prehistoric ceramics, documentation and evaluation, (1) 2*b*.
of Roman ceramics and glassware, found in homes at Xanten (Germany), (5) 124*c*.

Arfvedsonite, from Seal Lake, Labrador, (1) 26*h*.

Argon, adsorption, on anatase at low relative pressures, (1) 26*e*.
$ATiNbO_5$, $ATiTaO_5$, and $ATiSbO_5$, crystal structure and fluorescence, (1) 27*c*.
thermal desorption, ionically pumped into glass, (8) 258*a*.

Art and artware. See also *Archeology; Decoration; Design; Majolica; Pottery; Tile*.
ceramic, in Yugoslavia, (8) 228*a*.
ceramics, modern European, hypotheses and events, (10) 293*j*.
ceramics, molding and forming, (3) 61*i*.
ceramics and glass, in Cerralbo Museum, Madrid, (10) 293*i*.
collection, of His Majesty King Gustav VI Adolph of Sweden, (4) 91*g*.
decorative, in U. S., (7) 194*c*.
Delftware, made at Glasgow pottery at Delftfield, (5) 124*b*.
drinking pottes, tygs, and possets, (3) 61*j*.
earthenware china, new MQ2, in England, (5) 124*c*.
enamel ornaments for German town council chains of office, (7) 194*a*.
flowerpots, P (8) 228*b*.
glass, diamond engraving by Dutch artists, (2) 35*j*.
diatreium, first reproduction by Roman grinding technique, (7) 194*a*.
lantern at Liverpool (2) 35*i*.
Murano terminology in book by Neri, (1) 6*j*.
old recipes for copper-red, PbO-frit and alabaster, (7) 194*a*.
pedestal bowl, origin and purpose, (5) 124*b*.
Western, 16th to 18th century, found in Turkey, (5) 124*d*.
Gultrol® flasks, forming and manufacture, (8) 227*j*.
Persian, immanent features, (4) 91*f*.
porcelain, in collection of Earl Spencer at Althorp, Northamptonshire: I, English porcelain, (4) 91*g*.
European, from Tuck bequest at Petit Palais, (4) 91*h*.
Hoechst, (10) 293*h*.
Meissen collection of Ernst Schneider, (4) 91*g*.
Royal Rockingham, (2) 36*a*.
refinement without lowering aesthetic qualities, (7) 193*j*.
stoneware, old Bunzlau, (1) 2*a*.
stoneware, Rhineland, exhibition, (10) 293*j*.
stoves, cast-iron and 20th century gas-fired, (10) 293*i*.
Swiss handicraft ceramics, (4) 91*h*.
Wedgwood Etruria 1766–1966, (4) 91*i*.

Artists, Balzar-Kopp, Elfriede, (4) 91*f*.
Breckwoldt, Antje, (1) 1*j*.
Colberg-Tjadens, Dorothee, (1) 1*j*.
Erdoes-Meisinger, Ida, (3) 61*i*.
Galle, Emile, (5) 124*c*.
Gebauer, Walter, (1) 1*i*.
Giles, James, decorator of glass, (4) 91*f*.
Griemert, Hubert, (1) 1*i*.
Heckmann, Hans and Renate, (10) 293*i*.
Hohlt, George, (10) 293*i*.
Kerstan, Horst, of Kandern in Black Forest, (4) 91*i*.
Kippenberg, Heide, fine stoneware of, (10) 293*j*.
Klauer-Simonis, Albrecht, design + designer, (4) 91*h*.
Koerting, Hans Heiner, and Lisa, (7) 193*j*.
Kuch, Wilhelm and Elly, (3) 61*i*.
Kuhn, Beate, (4) 91*f*.
Leach, Bernard, B (10) 328*e*.
Leach, Janet Darnell, (3) 61*j*.
Lenz-Gerharz, Franziska, sculpture and ceramics in stoneware, (10) 293*j*.
Mascarin, Mario, (5) 124*b*.
Naske, Sabine, (10) 293*h*.
Popp, Walter, (7) 194*a*.
Portainers, Gilbert, ceramic sculptures, (4) 91*f*.
Rie, Lucie, pottery, (2) 35*j*.

Artists (*continued*)
Schnidt-Reuther, Gisela, (10) 293*h*.
Stehr, Barbara, (1) 1*j*.
Walford, Andrew, (1) 1*i*.
White, Felix, engraver on glass, (2) 35*j*.
Wilson, Scottie, (2) 36*a*.

Asbestos, amosite, occurrence in formations of Babubudan, Chikmagalur district, Mysore, (1) 25*d*.
aqueous suspensions, effect of surfactants on coagulative structure formation in, (8) 237*h*.
and cement articles, method of curing, P (3) 69*a*.
-cement, flat sheets, specification, (3) 62*e*.
new method of preparation, (7) 202*c*.
pipe, method and apparatus for introducing flocculating agent to slurry to control thickness of sheet used in winding to form, P (5) 135*h*.
pipe, method and apparatus for manufacturing, P (5) 135*i*.
products, and improvement in manufacture, P (3) 68*j*.
sheets, containing cellulosic fiber, production, P (1) 13*g*.
sheets, machine for manufacture, P (5) 144*c*.
chrysotile, modification with organosiloxanes in acoustic field, (7) 202*a*.
dilute- and -cement suspensions, structure formation in, (10) 295*i*.
heat resistant bodies, P (9) 270*b*.
imported, substitution in asbestos cement products, (9) 262*d*.
ore particles, method of rendering differentially fluorescent, P (1) 25*f*.
ore, separation of iron from, P (6) 183*b*.
sheets, preparing from aqueous slurries containing silicon resin emulsions, P (11) 340*c*.
silica-gel, compositions, P (7) 215*d*.
and vermiculite mixtures and their cement mortars, thermal conductivity, (8) 240*d*.

Ash, basic, hydration, effect of hydrochloric acid treatment on, (6) 164*b*.
fly, and Egyptian portland cement mixtures, heats of hydration, (5) 125*a*.
pellets, for lightweight aggregate, P (6) 172*b*.
with pulp waste liquor, for process development of synthetic lightweight aggregate, (6) 165*j*.
separation of constituents, (6) 165*c*.
use in cement mortar and concrete, (6) 165*h*.
fuel, pulverized, composition and pozzolanic properties: I, composition of fly ashes from British power stations and properties of component particles; II, pozzolanic properties of fly ashes as determined by crushing strength tests on lime mortars, (10) 294*d,f*.
soda, active, compaction, P (7) 214*h*.
soda, preparation, P (7) 215*a*.

Atomic heat. See *Heat, capacity*.

Atmospheres, furnace, controlled, effects on mechanical strength of fired ceramic body, (1) 15*h*.
influence on thermal decomposition of ferrous oxalate dihydrate, (5) 153*b*.
reducing, effect on thermocouples based on platinum: I, unprotected thermocouples, (5) 145*g*.

Atomic energy. See *Nuclear energy*.

Atomization, atomizer, ultrasonic, applied to atomic absorption spectrophotometry, (5) 146*h*.
centrifugal, and spray drying, (5) 144*a*.
centrifugal, study, (6) 179*e*.

Atoms, atomic displacements, effect on color center production in MgO, (8) 253*d*.
constitution, theoretical ideas, (3) 81*h*.
oxygen, recombination on oxide surfaces: III, catalytic activities of doped oxides, (7) 221*b*.
substitutional hydrogen, in CaF_2, paramagnetic resonance and electron nuclear double resonance of, (1) 30*j*.
uranium, ejection from sintered UO_2 by fission fragments in different gases and at different gas pressures, (4) 108*j*.
valency states, in monosilicides of certain 3*d* transition metals at low temperatures, (9) 288*c*.

Attrition. See *Crushing; Grinding*.

Augers. See *Extrusion*.

Autoclaves, hardened bodies, use of Shirasu in, (8) 250*j*.

Balances (scales). See also *Weighing*.
for magnetic measurements, (3) 75*d*.

Ball mills. See *Mills*.

Barite, replacement for quartz in white earthenware manufacture, (9) 271*e*.

Barium, $BaAl_2O_4$, atomic parameters, (7) 215*j*.
$BaAl_2O_4$, single crystals, (6) 188*c*.
$BaFeSi_4O_{10}$, electronic spectra, vibronic polarization in, (6) 190*f*.
$BaPbO_3$, in electroconductive composition, P (6) 177*e*.
$BaMg(CO_3)_2$, norsethite, synthesis at approx 20° and 1 atm, model of dolomitization, (7) 222*j*.
$Ba_2NaNb_5O_{15}$, nonlinear optical properties, (11) 355*a*.
$Ba_{1-x}Sr_xTiO_3$, manufacture and ferroelectric properties, (6) 176*f*.
$BaTa_2O_6$, dielectric and structural studies, (11) 341*g*.
$BaTa_2O_6$, polymorphism, (1) 31*e*.
$Ba_2Zn_2Fe_{12}O_{22}$ single crystals, method of growing, P (8) 245*h*.
and calcium, and strontium, dibasic compounds, and solid solutions, (6) 164*i*.
carbide, reaction with 0 to 16M nitric acid, (5) 157*e*.

Barium (*continued*)
carbonate, kinetics of reaction with TiO_2, (9) 283*d*.
reaction with GeO_2, (9) 286*c*.
reactivity in combating scumming in structural clay products, correction, (1) 10*e*.
ferrates, oxygen stoichiometry in, and effect on magnetization and resistivity, (5) 139*e*.
ferrite, of the *W*-structure type with varying ferrous content, (10) 324*a*.
fluoride, single crystals, sublimation, Langmuir studies, (11) 354*d*.
hydroxide, production, P (5) 149*b*.
iron oxide, $BaFe_{12}O_{19}$, formation, (9) 272*b*.
iron oxide, thin crystals, thickness dependence of domain width in, (3) 88*f*.
metatitanate, enthalpy of formation, (9) 282*c*.
metatitanates, heat of formation, (1) 29*a*.
nitrides, ternary, with rhenium and osmium, preparation and properties, (6) 187*i*.
oxide, microwave spectrum, (5) 154*i*.
rotational magnetic moment, (5) 139*h*.
solid, reaction with water vapor, mass spectrometry, (5) 154*d*.
permitride, preparation and properties, (6) 187*h*.
Ru and Ir oxides, changes with substitutions of Sr for Ba, (5) 155*d*.
silicates and aluminates, preparation and properties, (9) 278*j*.
systems. See *Systems*.
titanate. See also *Dielectrics*.
(5) 137*h*.
antiparallel 180° domains in, observation by X-ray anomalous dispersion method, (5) 151*b*.
-$BaSnO_3$ and $BaTiO_3$–$Ba(Fe_{1/2}Ta_{1/2})O_3$, dielectric properties in, (11) 351*a*.
ceramics, high purity, relations between grain size and properties in, (9) 272*h*.
ceramics, with different grain size, electrical properties, (7) 207*d*.
crystallites, switching resonance in, (10) 325*h*.
crystals, birefringence, (3) 79*b*.
crystals, decoration techniques for revealing antiparallel 180° domains in, (8) 255*h*.
crystals, Gd^{3+} doped, grown in molten KF, resistivity of, (10) 325*c*.
ferroelectric domains in, scanning electron microscopy of, (1) 16*g*.
ferroelectric field, as measured by electron diffraction, (5) 138*j*.
ferroelectric structure revealed by electron-beam technique, (5) 138*j*.
fine-grained, diffraction line shifts in, (6) 185*e*.
hysteresis loss and dielectric constant, (5) 138*f*.
interband Faraday rotation in, (6) 186*c*.
ionic or electronic conduction in, (5) 137*j*.
microstructure determines usage, (1) 16*j*.
optical dielectric constant, contribution of grain boundary to, (11) 341*j*.
perovskite, lattice, hydroxyl as defect of, (10) 322*a*.
powder, discoloration, effect of grain size on, (10) 319*g*.
reduced, electron spin resonance, (4) 109*e*.
reduction, and effect on electrical properties, (6) 176*h*.
semiconducting, electrical resistivity, effects of additives and ambient atmosphere during heating on, (8) 253*i*.
semiconducting, with Al_2O_3, SiO_2, and TiO_2, (4) 99*a*.
semiconductive, as capacitor, (5) 140*a*.
shell model of interionic interactions for, (3) 72*c*.
shock-wave compression, (9) 286*b*.
silver-, rectifying junctions, (5) 137*i*.
single crystal, effect of hydrostatic pressure on permittivity and Curie point of, (4) 117*g*.
single crystal, elastic properties above Curie point, (5) 151*b*.
single crystal, ESR of Mn^{2+} in, (10) 320*g*.
single crystal films on LiF, {111} twin in, (10) 326*j*.
single crystal, forbidden transition in electron spin resonance of Mn^{2+} in, (3) 81*d*.
single crystals, growth by modified Remeika technique, (1) 29*f*.
single crystals, 120° phase transition, effect of Fe_2O_3, (5) 137*i*.
single crystals, PTCR effect, (5) 157*j*.
temperature dependence of transverse and longitudinal optic mode frequencies and charges in, (10) 326*f*.
thermal diffuse streak in electron diffraction and low frequency transverse lattice waves of, (4) 117*j*.
Basalt, melted, monomineral crystallization, (11) 338*a*.
Batch, formulas, calculation using linear programming, (1) 19*g*.
Batteries, containing sintered aluminosilicate separator, P (7) 204*g*.
high-temperature solid state, (6) 176*a*.
plate, method of making, P (2) 41*d*.
Bauxite, abrasive particles, microcrystalline sintered, P (9) 261*g*.
-clay mixtures, thermal behavior, (11) 339*f*.
decomposition, chemical technology: I, system Na_2O–Al_2O_3–H_2O, (2) 57*d*.
deposits of Bagru plateau (Lohardaga) and origin, (10) 317*g*.
in India, assessment of reserves, (3) 77*d*.
Pacific Northwest, recovery of alumina and iron from, by Pedersen process, (6) 182*g*.
Bearings, flame-sprayed, wear resistant, P (5) 134*d*.
multilayer, method for producing, P (5) 126*a*.
Belite, local encrustation of, in rotary cement kilns, (9) 262*c*.
Bending. See *Deformation*.
Beneficiation. See also *Classification; Classifiers; Crushing; Grinding; Filters; Flotation; Screens and sieves; Separation; Separators*.
of beach sand materials, role of high tension separation in, (1) 19*f*.
of clay by removal of titanium impurities, P (6) 183*b*.
of diatomaceous earth ores, P (7) 215*b*.
of lepidolite ores, (1) 19*f*.
Bentonites, activated, for bleaching, (5) 143*e*.
dispersions, aqueous, gelation by organic ammonium ions, (10) 321*d*.
glycol, effect of gamma-ray irradiation upon, (6) 185*f*.
quality, effect of heating temperature, (11) 339*a*.
solutions, light-scattering study when subjected to electric fields, (3) 83*d*.
Upper Cambrian K-, from Missouri, mineralogy, (4) 113*e*.
Beryl, alkaline, effect of annealing on structure, (4) 108*g*.
and beryl melts, high-temperature behavior at high pressure, (1) 29*b*.
melts and glasses, high temperature behavior, (1) 6*g*; correction, (3) 63*j*.
Beryllia. See *Beryllium, oxide*.
Beryllium, articles, oxidation-resistant, and process of making, P (1) 13*e*.
^9Be, magnetic resonance spectrum, quadrupole splitting in chrysoberyl, (3) 85*e*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
complexes, extraction using primary amines, P (4) 105*b*.
compounds, thermodynamic and physical properties: VII, enthalpy and entropy of sublimation of beryllium fluoride, (11) 357*e*.
diffusion in MgO, (10) 319*e*.
fluoride complexes, in chloride-fluoride melt, (10) 321*e*.
vapor, effusion studies, mass spectra and thermodynamics, (3) 80*j*.
vibrational spectra, (11) 358*a*.
halides, producing from beryllium ore in high intensity arc, P (10) 318*f*.
oxide, β-crystal structure, (3) 67*a*.
and BeO binaries, electrical conductivity, (7) 201*f*.
ceramic grade preparation and characterization, (3) 67*e*.
ceramics, compatibility with potassium vapor, (6) 166*c*.
cold-pressing and sintering, studies, (4) 96*h*.
dislocations, observation by transmission electron microscopy, (2) 45*e*.
electrical conductivity, (3) 67*e*.
electron irradiation, (2) 44*f*.
extruded and sintered, modulus of rupture, effect of machining, (5) 131*j*.
fast neutron-irradiated, cation self-diffusion in, (8) 252*e*.
field gradient in, (3) 67*f*.
fine particle size, preparation through crystallization and calcination, P (1) 25*g*.
fission fragment damage in, direct observation, (9) 281*b*.
fueled, fabrication by extrusion and sintering, (4) 96*d*.
Hertzian stress cracks in, (1) 29*b*.
high temperature (β) phase, X-ray diffraction intensities, (4) 119*c*.
high temperature reaction with water vapor, (4) 96*c*.
hot-pressing, (2) 44*c*.
hot-pressed, effect of adsorbed sulfate and fluoride on density, (1) 28*g*.
hydrous, adsorption behavior in media of varying pH, (7) 215*h*.
irradiated, X-ray diffraction effects, (2) 44*h*.
irradiated, X-ray diffraction studies, (2) 46*c*.
irradiation effects in, (4) 112*d*.
kinetics of sintering and grain growth in, (3) 67*h*.
lattice vibrations, (8) 254*f*.
localized corrosion rates, techniques for measuring, (2) 46*g*.
mechanical testing, study of variables, (4) 96*i*.
mechanisms of irradiation-induced growth and cracking in, (2) 45*a*.
neutron-irradiated, direct observations of damage, (2) 43*h*.
neutron-irradiated, removal of anisotropic growth strains in, (3) 86*a*.
neutron-irradiated, thermal conductivity at low temperature, (3) 68*f*.
neutron-irradiated, transmission electron-microscope studies of, (8) 258*g*.
polycrystalline, fracture energy, (11) 353*b*.
powders, crystallite grown, and inhibition by adsorbed phosphate, (10) 319*c*.
powders, molecular size pores in, (7) 219*h*.
powders, sinterability studies, (3) 68*b*.
powders, sintering and densification studies, (3) 68*e*.
preparation, P (7) 215*e*.
radiation effect on, (7) 201*a*.
residual strain and fracture-stress temperature relation in, (3) 67*j*.
self-diffusion in, (3) 68*a*.
single crystals, growth and properties, (3) 67*g*.
single crystals, irradiated, comparison of microscopic and X-ray growth, (2) 43*h*.
single crystals, nuclear magnetic resonance of ^9Be in, (3) 67*c*.
Beryllium oxide (*continued*)
sinterable powder, research to obtain sinters of given characteristics, (3) 67*j*.
sintered, experiments under thermal stress, (6) 173*c*.
sintered, irradiation damage as function of fast-neutron dose and flux at 110°, 650°, and 1100°C, (4) 112*a*.
sintering, (6) 173*i*.
sintering: III, hot-pressing of beryllia derived from hydroxide, (5) 134*b*.
specimens, finite neutron irradiated, primary damage state in, (8) 256*h*.
thermal shock tests in, (4) 96*i*.
thermal vibrations in, (3) 68*g*.
tubes, extruded polycrystalline, residual stress and grain deformation in, (7) 221*f*.
-UO_2-B fuel pellets, fabrication, (2) 44*i*.
use in advanced reactor concepts, (2) 46*b*.
use in reactors, (2) 46*c*.
valence excited states, (11) 358*c*.
valence levels, (10) 327*e*.
X-ray diffraction study of variation parameters and ratio at temperatures up to 2000°C, (4) 119*d*.
precipitation, from ores, P (11) 349*d*.
product, comprised of Be particles coated with metal beryllide, P (8) 240*b*.
self-diffusion, in unirradiated BeO, (3) 67*j*.
solubilized, and hydrogen fluoride, producing, P (7) 214*i*.
systems. See *Systems*.
values, process for separating from aqueous solutions, P (4) 105*f*.
Bibliographies, ceramic-metal systems and enamel, B (7) 224*i*.
Binders, aluminophosphate, hardening products, composition in refractory corundum mixes, (7) 200*i*.
aluminophosphate, thermal changes in, (2) 46*j*.
cellulose ethers, in ceramics, (10) 305*d*.
clays as, (1) 10*g*.
clays, Illinois, as, for iron ore pellets, (1) 10*h*.
composition, effect on durability of silicate concrete, (5) 124*f*.
composition, glass or vitreous fibers, P (8) 235*e*.
for core sand, P (5) 136*a*.
hydrothermally hardening, phosphorus slags for production of, (6) 165*h*.
for machinable ceramics, (2) 56*g*.
of molding sand: I, effect of heating temperature on quality of bentonites, (11) 339*a*.
quality, evaluation in hydrothermal hardening, (6) 164*f*.
structure, in hydrothermally bonded sand-lime bodies, (10) 295*h*.
Binding, properties, of reaction products of TiO_2 and H_3PO_4, (1) 11*a*.
Biotite. See *Mica*.
Birefringence. See *Refraction*.
Bismuth, $BiFeO_3$ solid solutions with $Pb(TiZr)O_3$, dielectric properties at high temperature and high frequency, (9) 280*f*.
$Bi_4Si_2O_{12}$, neutron diffraction study, (6) 187*h*.
$Bi_4Ti_3O_{12}$ single crystals, crystal symmetry, optical properties, and ferroelectric polarization, (3) 79*f*.
diselenide, and method for preparation, P (2) 50*g*.
systems. See *Systems*.
Bleaching, activated bentonite for, (5) 143*e*.
optical, simultaneous with gamma radiation, effect on room-temperature colorability of KCl, (11) 352*b*.
Blending. See *Mixing*.
Blending apparatus. See *Mixers*.
Bodies, ceramic. See also *Dielectrics*.
alumina, P (7) 206*g*.
apparatus for producing, P (8) 247*h*.
lightweight fired, process for making, P (9) 266*f*.
method for making, P (2) 47*i*.
mixed, in system Al_2O_3–$MoSi_2$, aluminothermic production and study, (6) 172*e*.
nonuniform metal coating on, utilizing abrasive erosion step, P (10) 310*f*.
and preparation, P (5) 131*a*.
replacement of imported ball clay by Mianwali plastic clay in, (9) 271*b*.
shear, investigation, (11) 346*d*.
surfaces, processes for metallization, P (1) 19*a*.
Boehmite, alumina products, P (7) 214*i*.
formation, during dehydration of gibbsite, (2) 57*j*.
infrared spectrum, interpretation, (3) 82*j*.
pellets, pressed, anisotropic diffusivities in, (9) 279*g*.
Bonding. See also *Seals and sealing*.
agents, new, (11) 349*a*.
aluminum to borides, P (6) 174*f*.
anodic, P (11) 343*e*.
apparatus, with microscope sighting means, for semiconductor devices, P (8) 243*i*.
boron nitride body to refractory metal, method, P (1) 13*b*.
chemical, for strengthening in brittle matrix composites, (11) 332*f*.
chemically, dental porcelain to synthetic resin base materials, P (5) 137*c*.
copper foil to foil containing superconductive layer, P (2) 52*c*.
devitrified surfaces, process, P (1) 10*a*.
diamond and metal, P (9) 261*f*.
diamond to molybdenum, P (7) 193*g*.
electrode bodies of dissimilar expansion, (7) 205*c*.
of glass to thermoplastic with vacuum evacuation, P (2) 42*e*.
heat and pressure glass, of spaced magnetic head portions by forming and using glass overflow channels, P (7) 209*a*.

Bonding (*continued*)
of iron, in fine-ceramic kaolins, (1) 15*b*.
mechanism, between metals and ceramics: I, ceramic-to-metal seals; II, ceramic-to-metal seals of heavy metals type to beryllia ceramics, (2) 37*j*.
in mixed cyanide-halide complexes of platinum, (4) 119*b*.
organic resins or rubbers to inorganic substances, P (11) 335*g*.
organic resins to siliceous materials, P (11) 335*h*.
phosphate, in refractories and other ceramic products, (5) 133*a*.
properties, of sulfur in bornite, (4) 117*a*.
of refractories with monoaluminum phosphate solution, (7) 200*g*.
refractory bodies, P (7) 205*c*.
of refractory specialties with aluminum phosphate, (8) 239*j*.
in SAP type alloys, (8) 238*g*.
semiconductor chips on substrate, machine for, P (11) 343*g*.
in Ag_2PbO_2 and $Ag_3Pb_2O_6$, (4) 106*j*.
thermocompression, of metals to semiconductor, metallic, or nonmetallic surfaces, P (8) 246*e*.
Bonds, adhesive, ultrasonic testing using Fokker Bond Tester, (7) 213*b*.
chemical, in semiconductors and thermodynamics, B (8) 259*e*.
chemical, theoretical reviews, (5) 155*c*.
covalent, in diamond, (9) 280*f*.
defective, detection using ultrasonic phase analysis, (7) 213*d*.
low resistance, to germanium-silicon bodies, and method of making, P (1) 18*g*.
to telluride thermoelectric bodies, method and materials for obtaining, P (10) 310*f*.
to thermoelectric bodies, method and materials for obtaining, P (6) 178*i*.
properties, of aluminum phosphates, (1) 11*c*.
of refractory concretes in zinc scrap melts, testing, (9) 269*d*.
Bone china, plasticity, effect of flocculants, (2) 48*j*.
Boracites, monocrystalline, production, P (8) 251*i*.
Boranes, polyhedral, B (5) 161*d*.
Borates, alkali, binary, subliquidus immiscibility in, (8) 257*j*.
hydrated, ^{11}B quadrupole coupling tensors in: I, tunnellite polyanion, (5) 137*g*.
infrared spectroscopy on; I, sodium (1:1:4) borate hydrate, (5) 153*d*.
lanthanide gallium, crystal structure and fluorescence, (5) 150*b*.
poly-, ions, cryoscopy in dilute solution in alkali halides, (3) 79*d*.
terbium-activated alkaline earth alkali, fluorescent properties, (4) 110*b*.
vitreous, structure, (5) 128*i*.
Borax, noncaking, production, P (8) 251*e*.
Boric oxide, crystallization, densification, and crystallization anomaly, effect of high pressure, (1) 28*g*.
infrared spectrum and molecular structure, (3) 82*f*.
–PbO–SiO_2, dielectric properties, (7) 196*a*.
vapor phase reaction with anhydrous aluminum fluoride, (6) 190*e*.
vaporization, thermodynamics of, (5) 159*e*.
viscosity, entropy interpretation, (4) 93*e*.
viscous relaxation and non-Arrhenius behavior in, (4) 93*j*.
vitreous, kinetics of volume relaxation: I, introduction and preparation, (11) 357*h*.
temperature dependence of high frequency moduli of, (5) 129*d*.
two-state model for free volume of, (4) 93*j*.
Borides, addition, effect on creep strength of niobium alloys, (11) 352*a*.
crystalline, method for producing, P (2) 47*j*.
di-, transition metal, alloying behavior of HfB_2 with, (9) 279*h*.
forming and firing, P (7) 205*d*.
industrial production, (2) 44*f*.
metal, production, P (7) 204*j*.
metallic, contact reaction with graphite at high temperature in vacuum, (2) 46*e*.
preparation, properties, and crystal chemistry, B (4) 119*i*.
Boron, alkoxy-, difluorides and dichlorides, preparation, structure, and spectroscopic properties, (5) 149*j*.
B_2O, periodic compound, synthesis at high pressures and temperatures, (4) 113*i*.
BaP, synthesis and crystal growth, (4) 117*j*.
carbide, armor, bulletproof, (4) 104*g*.
article, and method of making, P (5) 134*e*.
elastic properties, effect of low porosity, (4) 108*c*.
heat of formation, (9) 282*j*.
production, P (5) 136*e*.
coated, containing material dispersed in metal matrix, P (3) 68*j*.
ESR, in single-crystal BeO, (5) 152*a*.
4-coordination structures formation in glass, (8) 232*d*.
in glass, determination by thermal neutron capture gamma ray analysis, (5) 127*a*.
and inorganic compounds, determination, B (7) 225*h*.
nitride, body, method of bonding to refractory metal, P (1) 13*b*.
cubic, crystal growth, factors affecting, (7) 217*d*.
determination of nitrogen undecomposable by acids, (1) 11*e*.
effect on properties of aluminosilicate refractories, (9) 267*e*.
Boron nitride (*continued*)
hexagonal, direct transformation to denser forms, (5) 151*c*.
hexagonal, lattice parameters, effect of high pressure, (7) 217*c*.
hexagonal, normal modes in, (11) 355*b*.
hexagonal, stacking faults in, (10) 325*c*.
for joints of carbon or refractory oxides bodies, P (5) 135*i*.
powders, sintering during hot-pressing, (7) 203*g*.
and pyrolytic graphite bodies, heat treating with simultaneous application of multiaxial tension, P (2) 47*a*.
synthesis for preparation, (5) 155*i*.
noncrystalline, radial distribution function, (4) 114*e*.
in oxidizing media, potentiometric determination, (10) 315*b*.
as paleosalinity indicator, and application to offshore prospects, (9) 282*f*.
phosphide, method of producing or recrystallizing, P (3) 78*e*.
phosphide, production, P (11) 340*i*.
phosphides, in Ni–B–P system, phase stability regions, (4) 114*c*.
preparation by fused-salt electrolysis, statistical evaluation of factors in, (3) 77*f*.
systems. See *Systems*.
Boundary layer, between refractory and glass or slag, processes in, (7) 202*g*.
Brazing. See *Soldering*.
Brick. See also *Masonry; Refractories; Structural materials*.
and block, self-leveling self-aligning, P (11) 337*d*.
and building blocks, improvements in, P (5) 131*a*.
calcium silicate, (3) 62*b*.
calcium silicate, development, P (2) 37*d*.
clay, efflorescence in, (11) 337*d*.
clays, weathering, (10) 302*a*.
colored, by blending red beds shale and white clay, (7) 199*g*.
dehumidification, enabling, P (1) 10*b*.
face, semidry pressed, discussion, (10) 301*f*.
frost resistance. See *Frost resistance*.
handmolded, results of tests on ultimate strength for piers, (2) 43*a*.
hot processing, (2) 42*i*.
lightweight, from clay and expanded plastic, (1) 10*i*.
-making, clay based mechanized, in India, science, technology, and engineering, (9) 266*d*.
efficiency in machinery use, drying, use of manpower, service to customer, and utilization of resources, (5) 130*i*.
technology, up-to-date, (1) 10*g*.
methods and devices for production, P (7) 199*h*.
model tests on, (10) 301*g*.
packaging, method and apparatus, P (3) 66*g*.
plastic, materials, optimal preparation equipment for, (10) 301*d*.
production, automatic molded, (2) 42*g*.
raw materials resources in South Carolina, (3) 77*d*.
setting, method and apparatus, P (9) 266*e*.
surface coloring, (10) 302*a*.
thin-walled hollow, production and use in lightweight walls and facings in Italy, (10) 301*i*.
and tile research in India, (9) 266*d*.
for use in German building industry, (10) 301*f*.
and wall construction, P (10) 302*b*.
in Western European countries, future changes, (10) 301*i*.
-work, efflorescence and staining, (10) 301*g*.
-work, high rise load bearing, aspects of design in, (9) 266*c*.
Brick industry. See also *Structural clay products industry*.
Bulgarian, (2) 42*h*.
expanded markets and increased profits, (2) 42*h*.
incentive program for salesmen, (10) 301*e*.
in Iran, (10) 301*e*.
large inventory problems solved, (2) 42*j*.
line production by stabilizing technological conditions, (1) 10*j*.
one-high plant produces profits, (10) 301*h*.
palletizing equipment for, (5) 130*j*.
raw materials prospecting in Schleswig-Holstein, (10) 301*i*.
Swiss, Test-site "Melchtal" of Testing and Research Station of, (10) 302*b*.
and tile, quality control policy, (3) 66*h*.
Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses*.
laying machine, P (8) 236*g*.
setting system, automatic, (3) 66*f*.
stacker, P (10) 302*b*.
Brittle materials, apparatus for mechanical testing at 20° to 1200°C, (10) 313*g*.
nonmetallic, methods and apparatus for splitting, P (7) 211*f*.
severing methods along prescribed lines, P (8) 247*f*.
uniaxial and biaxial testing method, (9) 276*i*.
Brittleness, index, of ladle brick, relation with erosion rate, (7) 202*j*.
Bromine, chloride, formation and detection of low-lying excited electronic states of, (9) 282*j*.
Bronze, indium tungsten, (7) 218*i*.
molybdenum and tungsten, synthesis at high pressure, (6) 189*h*.
rare earth tungsten, (5) 157*c*.
tungsten, electronic properties, (5) 138*f*.
Bubbles, formation, in glazes, gas analysis study of mechanism of, (7) 206*c*.
gas, migration in irradiated UO_2, (5) 132*i*.
inert gas, binding to precipitates, (2) 43*g*.
Bubbles (*continued*)
in soda-lime-silica glasses, tendency of refractories to produce, (5) 129*d*.
sweeping, by grain boundaries in irradiated UC, (10) 325*g*.
Building materials. See also *Aggregates; Brick; Enamels; Insulation, thermal; Structural clay products; Structural materials*.
block, and brick, improvements in, P (5) 131*a*.
ceramic blocks, fused, process for producing, P (4) 95*i*.
ceramic panels, single-thickness, thermal characteristics, (10) 302*b*.
composite structures, development, (10) 327*i*.
for domestic water piping systems, (5) 130*j*.
panels, prefabricated composite masonry, formed of prelaid individual masonry modules bonded together, P (7) 199*i*.
roofing granules, intumescent coated, and asphalt composition felt-base roofing containing, P (5) 131*b*.
tile panels, P (4) 98*g*.
wall, economic development, (1) 10*h*.
wall tile and face brick, production, B (10) 329*h*.
Bulbs. See *Glass*.
Bulk modulus, temperature dependence and Anderson-Grueneisen parameter δ of oxide compounds, (6) 189*j*.
Burgers vector, of dislocation loops in graphite, (1) 26*f*.
Burners. See also *Flames*.
air distributors of, for solid, liquid, or gaseous fuel, P (4) 104*e*.
air preheating, with furnace preheating passage cleaner means, P (4) 104*f*.
combined, for oil and water mixtures, (8) 249*d*.
that creates uniform flame size by using progressively smaller holes, P (4) 104*a*.
dual fuel, system for purging nozzles in, P (8) 249*i*.
excess air, measurement and control, P (5) 147*f*.
fiber attenuating, P (6) 170*j*.
and furnace for testing temperature probes, P (11) 347*i*.
gas, P (4) 104*c*; P (10) 317*a*.
with proportional mixer, P (6) 182*c*.
radiating, apparatus, P (10) 317*d*.
unit, P (5) 147*e*.
high temperature generating high intensity, P (3) 77*b*.
industrial blue flame, (5) 147*d*.
for liquid, gaseous, and pulverulent fuels, P (5) 147*h*.
mineral working, apparatus, P (8) 251*a*.
multitube, P (3) 77*b*.
for producing metal oxides, P (6) 182*c*.
system, for test furnaces, (2) 55*j*.
for tempered flame operation, P (5) 147*g*.
Burning. See also *Calcination; Combustion; Firing; Lime*.
degree, effect on quicklime structure, (10) 294*j*.
Burnishing. See *Polishing*.

Cadmium, Cd^+, trapped in metaphosphate glass at room temperature, (5) 127*f*.
$Cd_{1-x}Ca_xF_2:In^{3+}$ single crystals, semiconductivity in, (1) 16*h*.
$CdTlS_2$, semiconducting compound, (1) 30*d*.
$Cd_2V_2O_7$, crystal structure, (5) 150*j*.
chalcogenide crystals, highly pure hexagonal, production by sublimation, P (4) 101*b*.
fluoride-CaF_2, doped, crystals, electrical and optical studies, (5) 151*d*.
rare-earth-doped, as far infrared photoconductor, (1) 16*d*.
single crystals, rare earth doped, electrical and optical properties, (4) 109*b*.
hydroxide, thermal decomposition, (11) 357*e*.
iodide, reaction with InAs, (10) 324*g*.
selenide, infrared absorption due to free electrons in, (5) 153*c*.
selenide, semiconducting, electron affinity, (11) 352*j*.
sulfide, colloidal particles, stepwise adsorption on glass, (10) 298*g*.
conductivity change in, by microwave phonons, (11) 350*i*.
crystals, photoconductivity, (5) 156*j*.
crystals, plastically bent, luminescence from, (5) 154*j*.
crystals, production, P (1) 26*b*.
crystals, semiconducting, high-field Hall effect, (4) 111*f*.
free-to-bound and bound-to-bound transitions in, (8) 253*j*.
insulating, transient polarization in, (9) 288*e*.
layered system on germanium, elastic surface waves in, (11) 352*f*.
magnetic susceptibility of Mn^{2+} in, and effects of antiferromagnetic exchange, (9) 284*i*.
:Mn, zero-phonon lines and phonon coupling, (11) 358*b*.
n-type, high field domains, (4) 111*f*.
optical absorption of photoelectrons in, (11) 355*d*.
photoconducting, of acoustic waves, in generated high electric fields, (2) 49*j*.
photoconducting, spatial variation of electric field strength in, (11) 356*j*.
photoconductivity and impact ionization, (1) 16*c*.
Raman effect in, (9) 286*a*.
room temperature lasing under pulsed electron bombardment, (4) 115*i*.
and selenide, films, vacuum deposited, preparation and properties, (5) 139*a*.

Cadmium sulfide (*continued*)
semiconducting, damping of sustained oscillations in, at high fields, (4) 107*j*.
semiconductive, carrier and potential distribution at high electric field in, (8) 252*e*.
single crystals, conductive, Hall effect and contact properties with metals in, (5) 153*h*.
single crystals, copper-doped, kinetics of optical charge exchange in, (8) 254*d*.
single crystals, resistivity homogeneity, effect of sulfur annealing pressure on, (11) 352*e*.
single crystals, surface states on, (5) 158*j*.
solar cells, formation of barrier layers in, P (6) 177*a*.
telluride, or selenide, thin films, P (4) 101*c*.
thin films, surface properties, ultrahigh vacuum system for preparation and study, (5) 140*i*.
sulfides, preparation, P (1) 25*h*.
sulfite, abnormal green edge emission in, (11) 350*c*.
systems. See *Systems*.
telluride, *n*-, current runaway and avalanche effects in, (2) 49*f*.
n-type, piezoresistance in, (9) 285*d*.
semi-insulating, transport properties using nuclear particles, (3) 72*h*.
X-ray diffraction studies at high pressure, (8) 258*c*.
tungstate, crystals, ESR of Cu^{2+} in, (7) 217*g*.
Calcia. See *Calcium, oxide*.
Calcination. See also *Firing*.
of cement. See *Cement, burning*.
of clay, P (8) 250*f*.
of magnesite, (5) 131*i*.
Calcining, aluminum hydroxide by cross-flowing heating gas, P (8) 251*f*.
gypsum, method and apparatus, P (2) 37*f*.
kettle discharge apparatus, P (7) 194*i*.
of limestone, method and means, P (1) 3*b*.
Calcite, cleavages of scalenohedral habit, etching of, (6) 185*c*.
crystals, growth from molten flux by slow cooling, P (1) 25*c*.
crystals, study of cross bands and twinning dislocations in, (7) 222*f*.
electrochemical crystallization, (2) 58*d*.
phase-matched four-frequency interactions in, (11) 355*h*.
synthetic, single crystals, growth, (5) 153*d*.
thermoluminescence, from high gamma radiation doses, (3) 88*c*.
Calcium, acid phosphate dihydrate, conversion to calcium acid phosphate, P (11) 349*d*.
aluminate, hydration in presence of $CaSO_4$ and $CaCl_2$, (3) 62*i*.
aluminate sulfate hydrate, alkali-containing, (3) 62*a*.
aluminates, crystallization of MgO in, (6) 164*d*.
aluminoferrite, phase and glass, hydration in portland cement clinkers, (8) 228*c*.
atomic absorption spectrophotometry, interferences in, (9) 286*c*.
and barium, and strontium, dibasic compounds, and solid solutions, (6) 164*i*.
β-$CaSO_4 \cdot {}^1/_2H_2O$, hydration rate, effect of storage, (2) 36*j*.
$CaAl_2SiO_6$, synthetic pyroxene, stability and properties, (5) 158*i*.
$3CaO \cdot Al_2O_3$, hydration character, influence of $CaSO_4 \cdot 2H_2O$, discussion, (8) 228*g*.
$3CaO \cdot Al_2O_3$, reaction with water in presence of $CaSO_4 \cdot 2H_2O$, (10) 295*j*.
$12CaO \cdot 7Al_2O_3$, crystal structure of fluoride derivative of, (10) 319*a*.
$3CaO \cdot SiO_3$, hydration mechanism, (9) 262*d*.
Ca_2SiO_4, optical relations between modifications of, (1) 30*g*.
$CaNaBO_3$, energy transfer in, activated with Tb and Gd, (6) 185*b*.
carbide, reaction with 0 to 16M nitric acid, (5) 157*e*.
carbide, studies of equilibrium metal vapor pressures over, (6) 189*j*.
carbonate, method of preparing, P (1) 25*d*.
phase transformations and decomposition, effect of impurities, (4) 108*b*.
reactivity in system $CaO–SiO_2–CaCO_3–H_2O$, (6) 165*f*.
chlorospodiosite, synthesis, P (7) 210*b*.
chromates, production from chromium ore, (9) 278*h*.
dicalcium silicate, β-, paste, DTA in vacuo, (8) 228*e*.
crystal chemistry, (2) 57*f*.
modifications, stability fields of, (7) 221*f*.
phases in portland cement clinker, high-temperature microscopic investigation, (1) 2*g*.
polymorphism, (2) 59*d*.
diferrite, Moessbauer study, (10) 323*d*.
ferrites, ferrimagnetic, containing tri- or tetravalent metal ions, magnetic and crystallographic studies, (11) 354*h*.
ferrites, properties, in $CaO–FeO–Fe_2O_3$ ternary system, (9) 287*g*.
fluoride, (Ce,Mn) sensitized fluorescence, saturation effects in, (8) 256*h*.
doped with GdF_3, dielectric spectrum, surface-layer relaxation in, (4) 117*h*.
elastic constants, pressure derivatives of, (8) 256*f*.
finely divided, with controlled particle size, process for producing, P (3) 74*b*.
natural and synthetic, from different sources, comparative studies on dislocations, (8) 184*i*.
orthorhombic ESR spectra of Yb^{3+} ions in, (11) 355*c*.
paramagnetic acoustic resonance and relaxation of rare earths in, (11) 355*f*.

Calcium fluoride (*continued*)
paramagnetic resonance of divalent praseodymium in, (10) 324*g*.
paramagnetic resonance and electron nuclear double resonance of substitutional hydrogen atoms in, (1) 30*j*.
preparation, P (5) 149*b*.
reflectivity, angle-of-incidence dependence of, (8) 252*b*.
hydrosilicates, crystallization in presence of gypsum and aluminum oxide, (2) 36*j*.
hydroxide, additions in clay fixing, mechanism, (5) 125*e*.
hydroxide, deformation during dehydroxylation of, (4) 107*a*.
in impure calcium carbonate and limestone, complexometric determination, (10) 313*c*.
metatitanates, heats of formation, (1) 29*a*.
molybdate, niobium compensated, laser characteristics, (3) 83*d*.
molybdate, single crystal, elastic constants, (7) 217*f*.
naphthenic acid extraction of, for determination by atomic absorption spectrophotometry, (10) 315*c*.
in ores and slags after separation of R_2O_3 and P_2O_5 with aqueous suspension of ZnO, (10) 313*h*.
orthovanadate, single crystal, growth, (11) 342*h*.
oxide. See also *Lime*.
^{45}, irradiated, and other alkaline earth oxides, electron spin resonance of F centers in, (4) 109*b*.
method for introducing into manganese-zinc ferrite magnetic materials, P (7) 209*f*.
sintering, effects of water vapor, (2) 58*c*.
solid state reactions with SiO_2, Al_2O_3, MgO, Fe_2O_3, and ZrO_2, (7) 221*b*.
structure, electron microscope study, (1) 28*i*.
phosphate, pure molten, application of rigid sphere model, (2) 57*d*.
polyphosphate, preparation by reacting calcium carbonate and wet process phosphoric acid, P (11) 350*a*.
pyroniobate, electrooptic effect in, (5) 138*g*.
self-diffusion, in glassy and crystalline in $Na_2O \cdot\cdot 2CaO \cdot 3SiO_2$, (8) 230*c*.
silicate, autoclaved lightweight building material, development, considering chemical reaction and mechanical strength, (1) 2*d*.
hydrates, in calcite-quartz interface region in hardened nonhydraulic lime mortars, (7) 194*d*.
insulating products, manufacture, P (2) 47*e*.
silicates, cast, physicotechnical properties, effect of composition on, (6) 164*a*.
silicates, colloid hydrated; I, solubility products; II, solubility relations in calcium oxide-silica-water system at 25°, (11) 350*h*.
silicide, high pressure phase, crystal structure and superconductivity, (8) 252*d*.
sulfate, alpha form, (2) 36*d*.
hemihydrate, centrifuging, P (7) 194*j*.
hemihydrate, change by heating, (2) 36*g*.
hemihydrate, formation from dehydrate, effect of hydrothermal treatment temperature and time on, (7) 194*g*.
precipitate formation, colloidal phenomena in, (10) 294*b*.
$\cdot 2H_2O$, influence on hydration character of $3CaO \cdot Al_2O_3$, discussion (8) 228*g*.
sulfoaluminate hydrates, expansion characteristics, discussion, (1) 2*g*.
systems. See *Systems*.
tricalcium silicate, hydration, (3) 62*e*; (11) 353*c*.
hydration in presence of potash at different temperatures, (6) 164*i*.
phases in portland cement clinker, high-temperature microscopic investigation, (1) 2*g*.
solid solutions, chemical and structural studies on formation, (2) 36*g*.
and its solid solutions, polymorphism, (1) 31*g*.
tungstate, crystal-field term symbols for Nd^{3+} in, (10) 319*a*.
crystals, iron-59 doped, Czochralski growth, and determination of iron retention by radiochemical analysis, (4) 107*j*.
ESR of niobium in, (11) 352*f*.
uranates, preparation and properties, (5) 157*c*.
vanadate, precipitation and processing, (5) 147*i*.
Calorimeter, apparatus, and method of directly determining enthalpy, P (6) 181*d*.
for DTA of samples, P (10) 316*a*.
high-temperature adiabatic drop, and enthalpy of α-alumina, (7) 218*b*.
for measurement of heats of solution, (7) 211*j*.
Calorimetry, fluorine bomb: X, enthalpies of formation of niobium and tantalum pentafluorides; XI, enthalpy of formation of YF_3; XII, enthalpy of formation of RuF_5, (11) 352*j*, 353*a*.
high-temperature in liquid oxide systems: II, enthalpies of solution of type MO oxides in vanadium(V) oxide; III, enthalpy of formation of magnesium-aluminum spinel, (6) 186*c*,*d*.
techniques, for studying saline liquid at high temperatures, (7) 216*h*.
Capacitors, with barbed terminals, and method of making, P (10) 309*h*.
barrier-layer, MnO dielectric coating for, P (9) 273*j*.
boron nitride film, P (4) 99*e*.
boundary layer ceramic, studies, (5) 140*a*.
ceramic, P (8) 245*j*.
ceramic radio frequency transmitter, (10) 306*h*.
coated ceramic, P (2) 50*i*.
with dysprosium oxide dielectric, P (9) 272*j*.
electrical, P (5) 141*a*.
electrolytic, comprising film-forming metal sheet carrying dielectric oxide film and metal dioxide electrolyte layer, P (7) 208*e*.

Capacitors (*continued*)
electronic, using dielectric glasses, P (7) 198*i*.
metal-oxide-plasma, dielectric relaxation effects in, (3) 80*a*.
mica, P (4) 100*h*.
mica disk, P (11) 344*g*.
for miniature electronic circuits, P (2) 50*g*.
MIS, transient voltage breakdown due to avalanche in, (2) 50*b*.
module, P (10) 311*b*.
multilayer ceramic, P (10) 311*g*.
multilayer electrical, P (7) 209*h*.
nickel oxide, P (2) 51*j*.
rare earth fluoride, P (7) 210*c*.
solid type electrolytic, of titanium, method for manufacture, P (4) 100*f*.
tantalum solid electrolytic, equivalent series resistance of, (10) 307*f*.
thin film, P (2) 51*b*; P (7) 210*f*; P (10) 311*f*; P (11) 344*c*.
using semiconductive oxide electrolytes, P (11) 345*b*.
yttrium oxide, (10) 308*j*.
vacuum sealed silvered mica, for capacitance substandard, (5) 140*a*.
Carbides. See also specific types.
addition, effect on creep strength of niobium alloys, (11) 352*a*.
alkaline earth, studies of equilibrium metal vapor pressures over: II, CaC_2, (6) 189*j*.
alloys, complex, containing ScC, conditions of preparation, (3) 66*i*.
carbiding, selectively, Ti, Fe, and V values, (9) 270*c*.
cemented, magnetic saturation, (9) 284*g*.
crystalline, method for producing, P (2) 47*j*.
flame spray material, P (11) 340*b*.
forming and firing, P (7) 205*d*.
industrial production, (2) 44*f*.
metal, production, P (7) 204*j*.
mixed, of UC–ZrC and UC–NbC, for use in nuclear reactors, preparation, P (7) 205*h*.
of molybdenum, high superconducting transitions, (4) 98*i*.
mono-, polycrystalline transition-metal, elastic properties, (10) 320*d*.
particles, coated, P (6) 174*a*.
refractory, Vol. 2, B (7) 225*i*.
refractory, reaction with noble and transition metals, (10) 324*i*.
refractory metal, field ion microscopy of, (8) 237*j*.
transition-metal, action of alkali on, (5) 149*g*.
ultrafine, preparation and characterization, (4) 114*j*.
Carbon. See also *Graphite*.
articles, process for preparing, P (1) 14*c*.
articles, thermally stable, P (10) 305*b*.
black-kaolin materials, sintered composite, electrical resistivity: IV, relation between temperature dependence of resistivity and carbon bulk density; V, effects of firing temperature on resistivity temperature dependence, (5) 151*d*,*e*; VI, pressure dependence of resistivity of carbon black under loose contact; VII, resistivity-bulk density relations of carbon black under loose contact; VIII, effects of carbon materials on resistivity, (7) 207*f*,*h*.
bodies, crystalline, apparatus for shaping, P (6) 163*h*.
content, effect on properties of WC-10%Fe and WC-10%(Fe–Co) cemented carbides, (9) 281*c*.
crystals, synthesis, P (8) 251*j*.
dioxide, adsorbed on evaporated alkali halides, infrared spectra, (3) 82*b*.
adsorption at high pressures by Al_2O_3, determined from measurement of dielectric constant, (3) 78*i*.
$^{14}CO_2$, desorption from micas, (3) 79*i*.
gaseous equilibrium between Li (Na, K, Mg) carbonate melt, MgO, and, (7) 217*a*.
effect of glass melts on, (7) 197*d*.
effect on mechanical properties of WC-Co hard alloys, (1) 11*f*.
effect on uranium-based ceramics, (10) 324*d*.
fibers, metal carbide formation on, P (3) 68*j*.
glassy, electric conduction in, (8) 253*b*.
graphitized, diamagnetic susceptibility and linear thermal expansion, (2) 43*j*.
impregnation, metallic, method and apparatus, P (11) 340*h*.
materials, protecting from oxidation, P (2) 48*b*.
materials, for seals, bearings, and brushes, (2) 49*d*.
metallurgical, preparation, P (5) 135*h*.
monoxide, breakdown, and catalytic poisoning, (9) 267*e*.
reduction of wustite, promoters for, (3) 77*j*.
use in low-temperature sintering of high density UO_2 pellets, (10) 304*i*.
neutron-irradiated pyrolytic, mechanical properties, (10) 323*f*.
preferential vaporization, from hafnium carbide, (3) 85*e*.
pyrolytic, mechanisms of high-temperature plastic deformation in, (4) 113*b*.
reactions with diborides of Ti, Zr, and Hf, (3) 85*j*.
substrates, coating with refractory metal carbides, P (10) 304*c*.
Carbonaceous materials, articles, treat solution for rendering oxidation resistant, P (2) 48*d*.
behavior in tar-bonded dolomite brick for LD converter, (9) 266*i*.
bodies, apparatus for forming, P (6) 174*i*.
bodies, containing carbides, production, P (1) 14*f*.

Carbonaceous materials *(continued)*
composite members, for furnace rolls and high temperature members, P (2) 46*h*.
products, method of making, P (5) 135*a*.
Carbonates, alkali metal, equilibrium between gaseous CO_2, MgO, and, (7) 217*a*.
coprecipitated triple, for receiving tube cathode, (2) 49*d*.
triple, for electron tubes, X-ray fluorescent analysis, (2) 50*d*.
Carburization, de-, of levitated iron droplet in oxygen, (6) 184*i*.
Casting. See also *Molding; Molds; Refractories; Slip casting.*
of conventional semiporcelain body, optimum conditions for, (9) 271*a*.
investment, techniques and binders, (2) 46*g*.
precision, fused silica radomes, (4) 96*h*.
reactive metal, P (8) 241*g*.
of refractories, (6) 172*i*.
refractory articles, P (8) 241*h*.
refractory materials, P (2) 47*f*.
slips and cast bodies, orientation phenomena as causes of inhomogeneities in, (7) 206*b*.
sound ingots, of thermoelectric materials, (7) 207*e*.
Castings, die, large precision, made from cavityless casting molds, P (10) 304*h*.
magnesium die, corrosion-resistant coating for, P (7) 195*a*.
Cast iron. See *Enameling metals; Iron.*
Catalysts, alumina-based, and method of preparing, P (4) 104*h*.
alumina-supported nickel, molybdenum and alkali metal, for dehydrogenation process, P (1) 25*a*.
aluminosilicate zeolite, physically stable, P (10) 318*h*.
antimony oxide-tin oxide, activation using water, P (1) 25*h*.
bonded molecular sieve, and preparation, P (8) 250*e*.
catalysis reviews, Vol. I, B (8) 258*j*.
chemical reaction, and preparation, P (7) 214*j*.
chromia-alumina, method for adjusting initial activity, P (1) 25*d*.
chromium oxide, supported, method of treating and polymerization, P (4) 105*h*.
clay-supported cracking, P (8) 250*h*.
composition, of bismuth molybdate or phosphomolybdate, P (6) 183*c*.
compositions, and process for preparation, P (1) 25*i*.
containing iron oxide, chromium oxide, and potassium compound, P (8) 250*g*.
containing silica-alumina and finely divided CaF_2, MgF_2, SrF_2, AlF_3, or InF_3, P (4) 104*i*.
conversion of hydrocarbons with steam treated Y type of crystalline aluminosilicate, P (10) 318*a*.
copper chromite-alkali metal oxide high surface area hydrogenation, P (6) 183*a*.
copper oxide-alumina, P (6) 183*b*.
cracking, preparation, P (8) 251*a*.
dehydrogenation, P (4) 104*j*.
for diamond synthesis, (5) 155*d*.
effect, in transformation of graphite to diamond, (5) 149*j*.
extruded, and catalyst supports containing polyacrylamide, preparation, P (1) 25*h*.
hydrocarbon conversion, P (5) 148*c*.
comprising acid treated crystalline aluminosilicate, production and use, P (5) 149*d*.
process, P (7) 214*d*.
hydrofining, and process for using, P (10) 318*a*.
with improved thermal stability, and preparation, P (10) 317*j*.
manufacture, P (8) 250*h*.
mixed-oxide, chemisorption sites on, (11) 333*e*.
mordenite, alumina, and platinum, for hydroforming process, P (7) 214*e*.
nickel and nickel oxide, on nickel spinel base, P (5) 148*f*.
oxidation, compositions and processes, P (1) 13*d*.
preparation, P (1) 25*d*; P (5) 148*j*.
preparation, and polymerization process using, P (1) 25*i*.
process, for preparation of nitriles, P (5) 148*a*.
promoted, used for town gas production, P (11) 350*a*.
silica-alumina, coprecipitated, process and composition, P (1) 25*i*.
silica-magnesia-magnesium fluoride cracking, P (11) 349*g*.
solid, P (5) 149*a*.
for stream reforming of naphtha and related hydrocarbons, P (10) 317*i*.
support, alpha alumina, preparation, P (10) 318*d*.
supported by magnesia or by materials containing it, process for stabilizing, P (1) 14*d*.
titania/chromium oxide, and polymerization process, P (5) 149*c*.
for treatment of combustible waste products, P (5) 149*c*.
Cathode-ray tubes. See *Tubes.*
Cathodes, dispenser, P (6) 177*d*.
field emission, with tungsten Miller indices 100 plane coated with Zr, Hf, or Mg on oxygen binder, P (6) 177*j*.
multialkali, method of making, P (6) 178*e*.
photo-, comprising channeled matrix with conductive inserts in channels tipped with photoconductive material, P (9) 274*b*.
photo-, for electron tubes, P (9) 274*c*.
pores, filled with barium scandate, P (3) 73*d*.
sandwiches, thin metal-oxide-metal, correlation between electroluminescence and electron emission of, (6) 176*c*.
Cathodes *(continued)*
thermionic, forming process using electrostatic charge attraction, P (1) 19*b*.
impaction process of forming, P (1) 18*e*.
emissive, P (5) 143*d*.
Cathodoluminescence. See *Luminescence.*
Cations. See *Ions, cations.*
Cells, cadmium sulfide solar, formation of barrier layers in, P (6) 177*a*.
electroluminescent, P (4) 99*i*.
electroluminescent ceramic: II, reflection layer, (1) 4*a*.
fuel. See *Fuel, cells*
PbO solid electrolyte voltaic, (5) 139*g*.
pn and *np*, photovoltaic series array comprising, P (6) 178*c*.
sizes, relationship with magnetic Curie points of solid solutions with ordered perovskite structure, (7) 221*d*.
solar, and process for making, P (4) 101*b*.
thermal, in present use, (8) 243*e*.
vertical double-pass multiple reflection, for internal reflection spectroscopy, P (10) 316*g*.
Cement industry, application of X-ray diffraction for determination of phases to, (6) 164*g*.
Cements. See also *Concrete; Mortars; Plasters; Pozzolans; Refractories.*
additives, containing polyvinylpyrrolidone and condensate of sodium naphthalene sulfonate with formaldehyde, P (4) 92*b*.
alumina, manufacture by burning in rotary kiln, and physicochemical properties, (8) 238*b*.
alumina, for refractory purposes, process for production, P (5) 135*j*.
analysis, rapid and accurate, (2) 36*e*.
asbestos, articles, method of curing, P (3) 69*a*.
for domestic water piping systems, (5) 130*j*.
pipe, method and apparatus for introducing flocculating agent to slurry to control thickness of sheet used in winding to form, P (5) 135*h*.
pipe, method and apparatus for manufacturing, P (5) 135*i*.
products, and improvement in manufacture, P (3) 68*j*.
products, substitution of imported asbestos in, (9) 262*d*.
sheets, machine for manufacture, P (5) 144*b*.
autoclave expansion, small specimens for measuring, (8) 229*c*.
barium silicate, properties as function of clinker minerals, (8) 228*h*.
burning, importance of separate grinding of limy clay and sand for clinker mineral formation during, (10) 294*i*.
burning, rings developed during process, (6) 165*h*.
cementation, low-temperature effects in nickelous nitrate–water–magnesium oxide system, (1) 29*i*.
clinker, crystalline structure, effect of temperature in rotary kilns, (5) 124*h*.
crystalline structure, influence on grindability, fraction distribution of minerals, and properties of cement, (6) 165*a*.
determination of content of certain minerals in, by rational chemical analysis, (3) 62*c*.
firing, as function of granulometric composition of raw material, (5) 124*g*.
hardening products, mixed with potash solutions, infrared spectra, (9) 262*b*.
materials, hydration, effect of chlorides, (8) 228*h*.
minerals, effect of preliminary curing on structure development of steamed specimens from, (6) 164*d*.
and clinker, accuracy of complexometric analysis of, (10) 294*a*.
and clinker, rapid analysis by thermometric method with direct percentage indication, (8) 228*i*.
clinker-based, hydration and hardening, (1) 2*g*.
composition, for high temperature wells, P (7) 194*d*.
low density, P (7) 194*g*.
for maximum thermal insulation, P (4) 92*b*.
and process for preparation, P (7) 194*c*.
resin bonded magnesium oxychloride, P (1) 3*c*.
significance for CO_2 treatment of cellular concrete, (10) 295*h*.
and concrete research, (2) 36*e*.
deformation during freezing, (5) 124*h*.
elements, including silicon, aluminum, and titanium, in, determination by atomic-absorption spectroscopy, (2) 36*i*.
false set, influenced by hydroxylated carboxylic acid type admixture, (11) 331*i*.
measures for combating, (2) 36*d*.
prevention, (5) 125*g*.
Ferrari, sulfate resistance of, (10) 296*b*.
fineness, Alpine Air Jet sieve, for determining, (3) 62*b*.
firing, K_2O sublimation during, (3) 62*j*.
granulometric composition of material fired in Lepol kiln, (6) 164*h*.
hardened, with chemical additives, complex salts in, (2) 36*h*.
reinforced with mineral fiber, (2) 37*b*.
steamed under accelerated conditions, physicomechanical properties, influence of water/cement ratio on, (6) 165*d*.
hardening, of sand-lime mixtures, (6) 164*f*.
hardening, structure and properties, influence of water/cement ratio at reduced temperatures, (6) 165*c*.
high alumina, composition and possible structure of quaternary phase in, and relation to other phases in system $CaO–MgO–Al_2O_3$, (7) 216*h*.
high temperature studies on individual constituents of, (9) 262*b*.
Cements high alumina *(continued)*
paste hydration, studies of early stages: I, hydration of individual aluminates; II, hydration of iron and silica components: III, hydration of commercial high alumina cements, (1) 3*a-c*.
in structural clay industry, (9) 266*f*.
hydration, control by ultrasonic method, (10) 294*g*.
hydration, effect on concrete form pressure, (5) 124*g*.
hydraulic, compositions and methods, P (4) 92*d*.
hydration-limited polymer-modified, (4) 92*d*.
methods of sampling, (3) 62*b*.
optical microscopy, (7) 194*h*.
of increased expansivity, (2) 36*f*.
in India, production, kilns used, and beneficiation procedures, (5) 124*f*.
Indian, for cement concrete mixes, design based on compressive strength of concrete, (10) 294*h*.
iron oxide, phase calculation and mix equations for, on equivalent basis, (10) 295*j*.
kilns. See *Kilns.*
mills. See *Mills.*
mortars. See *Mortars.*
nomenclature, B (7) 223*h*.
paste, failure, mathematical model, (8) 228*g*.
fresh, apparatus for measuring dimensional changes in, (8) 228*c*.
hardened high-alumina, microstructure of, (10) 295*h*.
hardened, NMR studies of water in, (6) 165*f*.
leaching in concrete, petrographic study, (1) 2*i*.
model, aggregate, temperature stresses in, (3) 63*a*.
plugging, expanding for gas boreholes, (3) 62*g*.
portland, and clinker minerals, hydration, effects of sucrose, *d*-glucose, and dextrin on, (11) 331*j*.
composition and products, P (11) 332*c*.
Egyptian, and fly ash mixtures, heats of hydration, (5) 125*a*.
hardening accelerated, P (6) 165*j*.
high strength inorganic compositions, (5) 125*c*.
hydration, effect of chlorides, (8) 228*h*.
paste, DTA, in vacuo, (8) 228*e*.
paste, of high water-cement ratio, apparatus for preparing, (11) 331*h*.
slag, alkali activity, (5) 124*f*.
structure, changes during grinding, (3) 62*f*.
technology, B (2) 60*g*; B (3) 90*c*.
portland clinker, etching, (9) 262*a*.
formation, factors that control rate of, (5) 125*j*.
fused at about 3000°C, (6) 165*d*.
high-temperature microscopic investigation of tricalcium silicate and dicalcium silicate phases in, (1) 2*g*.
liquid phase, effect of impurities of raw materials and alloying additives on viscosity of, (3) 62*e*.
potential compound composition of, (9) 262*e*.
production, quality, and development, (2) 36*e*.
properties, interrelations with concrete: III, compressive strengths of portland cement test mortars and steam-cured mortars, (10) 295*a*.
raw materials. See *Materials, raw.*
raw meal, homogenization, (3) 62*j*.
raw meal, preheating apparatus for, P (4) 92*f*.
raw mix, porphyroids as siliceous component in, (3) 62*d*.
raw mix, use of complex thermography to study burning process, (2) 37*f*.
for seismic-stable construction, (5) 124*g*.
setting and hardening, influence of sulfates, (10) 294*j*.
slag, method of operating blast furnace to produce, P (7) 194*h*.
sorel, analogs, hardening of, (2) 36*j*.
sorel: II, tile, (5) 125*a*.
specific surface, determination by adsorption of colorants, (3) 62*d*.
structural, bonded by silanes and siloxanes, (8) 240*d*.
sulfate expansion, further tests, (8) 228*d*.
in system $ZnO–P_2O_5–H_2O$, study of hardening, (2) 37*d*.
treatment of sludge in manufacture, P (2) 37*f*.
vibrogranulation of raw materials for, (2) 37*b*.
Centrifuges, high temperature, for phase equilibrium studies in molten salts, (2) 54*h*.
Ceramic engineering. See *Engineering.*
Ceramic industry, credit as sales tool, (2) 60*e*.
economic balance, (4) 119*g*.
incentive systems, (2) 60*e*.
labor's share, (4) 119*f*.
pneumatic controls in, (3) 76*d*.
preventing labor trouble, (2) 60*d*.
standardization in, (1) 34*d*.
Ceramic materials. See also *Bodies, ceramic; Materials, raw;* and specific types.
engineering properties, B (3) 89*j*.
toughness, determination, (6) 180*h*.
Ceramic-metal systems. See also *Enamels.*
and enamel bibliography and abstracts, 1967, B (7) 224*i*.
Li, Na, Ca || F, Cl, tetrahedral section, (7) 195*h*.
spraying by plasma gun, (6) 166*c*.
weld arresting composition, P (8) 230*a*.
Ceramics, article, low shrinkage, P (4) 97*d*.
articles, P (7) 206*h*.
compositions, P (2) 50*e*.
engineering, and cermets, (1) 11*h*.
environment, effect on creep properties of chromium alloys, (8) 253*f*.
Indian, outlook for, (1) 34*c*.

Ceramics (*continued*)
Institute of, textbook series: 4, effect of heat on, B (1) 34*i*.
Japanese, tools, materials, and processes, B (10) 329*h*.
laminar, residual stress development in, (1) 15*g*.
laminated, (3) 71*f*.
manufacturing techniques, (1) 20*a*.
nature and properties, in materials, B (11) 358*d*.
objects, and method of manufacturing, P (1) 20*e*.
past and present trends, (10) 327*j*.
periodic table, (2) 39*i*.
piezoelectric and Seignette, production by spray drying of solutions, (8) 243*j*.
-plastics composite material, method of making, P (4) 93*a*.
problems, use of Latin square in solving, (2) 54*a*.
processes, high-temperature, water vapor in, B (7) 226*g*.
properties, of clay mineral mixtures, (3) 81*c*.
science, Vol. 3, B (7) 226*d*.
shapes and bodies, manufacture, P (3) 70*f*.
technical, and optical microscope, (10) 315*h*.
technical, promise and problems, (2) 60*f*.
Training Board Annual Report, (2) 60*d*.
underwater structures, design parameters for, (3) 63*e*.

Cerium, $Ce^{3+}/CaWO_4$, electronic Raman spectrum at 77° and 2.2°K, (7) 217*h*.
dioxide, nonstoichiometric, defect structure model, (1) 28*a*.
high-temperature chemistry in systems cerium oxide-Al_2O_3, Cr_2O_3, Ga_2O_3, (6) 186*e*.
magnesium nitrate, powdered, thermal equilibrium with liquid ^3He at low temperatures, (10) 326*j*.
magnetostriction, in YIG, (4) 98*j*.
oxide, ceramic, sintered, change in electrical conductivity and rate of creep during reduction, (6) 184*e*.
electrical conduction by oxygen ions in, (5) 138*a*.
-lanthana, as solid electrolyte for fuel cells, (7) 207*g*.
microspheres, hollow, preparation, (9) 275*f*.
reaction with sodium borate melts, (6) 188*b*.
single crystals, growth and properties, (8) 254*d*.
single crystals, paramagnetic resonance of Gd^{3+} in, (8) 255*f*.
pairs in lanthanum chloride, electric quadrupole-quadrupole interaction between, (11) 352*g*.
sulfide, stabilization studies, (2) 59*h*.

Cermets, P (2) 46*g*.
Al_2O_3–Mo and ZrO_2–Mo, preparation and microstructure, (2) 45*b*.
of Al_2O_3–M system, impact strength, (7) 202*b*.
Cr–Si–O, resistance temperatures, (2) 50*f*.
electrical resistance material, and method of using, P (1) 12*j*.
and engineering ceramics, (1) 11*h*.
high-temperature: I, compatability; II, wetting and fabrication, (9) 267*c*.
irradiation behavior of UO_2 particles in, (11) 338*g*.
materials, two-component, relations in pressing of, (11) 339*b*.
Ni/Al_2O_3, deformation resistance and stability of strain distortions, (3) 67*a*.
resistance element, and terminal connections for, P (9) 273*h*.
resistors, by concurrent rf and dc sputtering, (8) 242*i*.
TiN–Mo, preparation and investigation, (2) 45*j*.
tungsten carbide base, P (6) 175*d*.
tungsten carbide based, effect of temperature on solid solutions in, (11) 337*h*.
UO_2–Mo and UO_2–W, dependence on microstructure of high temperature properties: II, heat transfer properties, (1) 11*c*.

Cesium, aluminosilicates, hydrothermal synthesis, and properties, (6) 182*h*.
bromide, U center in, (10) 327*b*.
$CsH_3(SeO_3)_2$, phase transition in, (3) 85*b*.
$CsLiF_2$, crystal structure, (4) 107*i*.
$CsMnF_3$, antiferromagnetic, direct observation of ^{55}Mn NMR in, (9) 281*c*.
chloride, single crystals, self-diffusion and ionic conductivity in, (8) 256*i*.
-GaAs Schottky barrier height, (11) 350*e*.
hexafluoroaluminate, complex formation with sodium cryolite, (9) 280*e*.
iodide, rare gas diffusion in, measurement by fission recoil doping techniques, (11) 355*h*.
systems. See *Systems*.
trivanadate, crystal structure, (6) 184*h*.

Chalcogenides, di-, ternary copper, zinc, cadmium, and manganese, with pyrite-type crystal structure, P (6) 178*h*.
rare earth, large single crystalline bodies, preparing, P (8) 246*a*.
making crystals of, P (6) 178*c*.
method for producing, P (3) 78*d*.
spinels, Cu^{2+} or Cu^{1+} in, (4) 107*i*.
zinc and cadmium, purifying, P (8) 245*f*.

Chalcogens, S, Se, Te, amorphous and crystalline, screw and ring molecules in, (7) 221*h*.

Chamotte. See *Refractories*.

Checker-brick. See *Refractories*.

Chemical analysis. See *Analysis*.

Chemical Engineering. See *Engineering*.

Chemical properties, of lithium and sodium ferrites and aluminates, (6) 183*b*.
of magnesites, (5) 147*j*.

Chemical properties (*continued*)
surface, of metal oxides, Lewis acid-base and ion-exchange reactions, (10) 325*f*.

Chemisorption, oxygen, on doped NiO and related conductivity changes, (3) 84*c*.

Chemistry. See also *Analysis; Electrochemistry; Geochemistry; Thermodynamics*.
and biochemistry, separation techniques, B (2) 60*h*.
crystal, of dicalcium silicate, (2) 57*f*.
of $M_{2-x}{}^{2+}Li_xM^{4+}O_{4-x}F_x$ crystals, (5) 150*i*.
of rare-earth oxides, (6) 184*c*.
of crystalline aluminosilicates: I, factors affecting formation of zeolite A; II, III: synthesis and properties of zeolite ZK-4 and ZK-5, (10) 319*h,i,j*.
descriptive, of phosphorus trioxide, (5) 150*h*.
high-temperature, of cerium in systems cerium oxide-Al_2O_3, Cr_2O_3, Ga_2O_3, (6) 186*e*.
high-temperature, current and future problems, B (7) 225*j*.
of polynuclear metal halides: I, preparation of polynuclear tantalum halides Ta_6X_{14}, (4) 106*d*.
of silicon difluoride, (4) 106*f*.
of silicon-sulfur compounds, (5) 150*b*.
solid-state: I, solid-state mechanism for polymorphic transformation of orthorhombic to tetragonal PbO, (6) 189*a*.
solid-state, whence, where, and whither, B (4) 121*f*.
spectroscopic techniques in, (1) 23*c*.
study, of minerals from Moine schists of Ardnamurchan area, Argyllshire, Scotland, (3) 79*d*.
surface, of rutile, electron spin resonance studies, (2) 58*e*.
technetium, oxidation states and species, (5) 159*d*.
of uranium (IV), (4) 106*f*.
of water used in porcelain enamel industry, (9) 262*h*.

China, bodies, vitreous, in literature and practice, (5) 137*a*.

Chinaware. See *Art and artware; Dinnerware; Porcelain*.

Chlorides, crystals, clear cuprous, gel growth, (2) 58*j*.
effect on hydration of portland cement and clinker materials, (8) 228*h*.
methylammonium, high-temperature reaction with certain metal oxides, (6) 186*c*.
molten group II, self-diffusion and structure in, (11) 356*a*.

Chlorination, for iron removal from spodumene concentrates, (11) 349*c*.
of metal sulfides, kinetics of, (3) 77*i*.
of niobium pentoxide with Cl in presence of excess graphite powder, kinetics, (7) 219*b*.

Chlorine, ion, diffusion in potassium chloride, (8) 253*a*.
in silica films, X-ray spectral determination, (10) 327*c*.

Chloritoid, in metamorphic rocks of Barrow's zones, (3) 79*f*.

Chromaticity. See *Color*.

Chromatography, adsorption, principles, separation of nonionic organic compounds, B (9) 290*c*.
cation-exchange, for separation of alkaline earth elements in ammonium malonate media, (4) 103*f*.
centrifugal, and electrophoresis device, P (11) 347*e*.
gas, for analysis of bubbles in glass, (3) 64*d*; (11) 334*a*.
fragmentation inlet for, and method of loading sample into, P (1) 23*h*.
in glass furnace atmospheres analysis, (11) 334*a*.
preparation of support for use in, P (10) 305*a*.
ion exchange, (10) 314*c*.
paper, of metal ions with aqueous-organic wash liquids, (5) 145*c*.
for separation of uranium from other elements, (2) 55*c*.
paper, and electrophoresis for separation of iron (II)–iron(III) mixtures, (11) 347*g*.
review, (10) 313*j*.
sample injection apparatus, P (3) 76*d*.
tracer-pulse, for measurement of phase equilibria at high pressures, (9) 276*c*.

Chrome. See *Chromium; Refractories*.

Chrome-magnesite brick. See *Refractories*.

Chromesil, jointing material used in recuperators in soaking pits, P (5) 135*g*.

Chromia. See *Chromium, oxide*.

Chromite. See also *Refractories*. analysis, rapid, (10) 315*c*.
formation of new minerals in, by firing in weakly reducing and oxidizing atmospheres, (5) 132*g*.

Chromium, alloys, creep properties, effect of ceramic environment, (8) 253*f*.
alloys, tensile creep properties, environmental effects on, (10) 302*i*.
boride, reaction with carbon, (5) 133*b*.
carbide, alloy, investigation of hard-facing rods of, (2) 44*h*.
carbide, free energy of formation, (11) 353*b*.
chrome-bearing materials, analysis: II, determination of alumina, (6) 179*i*.
Cr^{3+}, coexisting with Ti^{3+} in Al_2O_3, spin-lattice relaxation, (3) 86*g*.
Cr^{3+}, in phosphate glass, ESR and optical absorption studies of, (5) 127*i*.
Cr^{6+}, ultraviolet absorption in binary alkali borate glasses, (1) 8*e*.
Cr(VI), ultraviolet absorption in binary and ternary alkali and alkaline earth oxide glasses, (7) 197*f*.
CrOOH, polymorph, crystal structure, (6) 184*e*.

Chromium (*continued*)
CrO_2, ferromagnetic, electrical properties, (11) 352*i*.
Cr_2O_3, crystal fields and optical spectra, comparison, (5) 150*e*.
infrared lattice spectra, (6) 186*b*.
lattice parameters, effect of high pressure on, (10) 319*h*.
Cr_2WO_6, linear thermal expansion, (5) 154*j*.
Cr_2WO_6, magnetic structure, (11) 354*j*.
$CrVO_4$, determination of metal ion positions by X-ray absorption spectroscopy, (6) 185*d*.
dissolution in iron due to corrosion of QC refractories with added Cr_2O_3, (9) 269*c*.
dioxide, crystal growth, (1) 27*a*.
ferromagnetic modified, two stage process for making, P (6) 178*i*.
single crystal, electrical resistivity, (10) 320*b*.
single crystal, magnetocrystalline anisotropy, (4) 112*i*.
stability at high pressures and temperatures in "belt" apparatus, (4) 116*e*.
fluorides, reactivity, (6) 188*g*.
ground manifold, paramagnetic relaxation and crystal-field theory for, in rutile, (10) 324*f*.
ions, reciprocal effect in glass, (1) 7*d*.
ions, in ruby, measurement of fractional metastable-state population under *Q*-switching operation, (8) 255*d*.
levels, in Al_2O_3, pressure shift of, (8) 256*g*.
-nickel alloy, oxidation in CO_2 and CO_2–CO mixtures, (4) 113*g*.
ore, rapid analysis, (10) 315*c*.
oxide, alumina, antiferromagnetism, ESR study, (5) 138*f*.
alumina, optical reflection spectra, (5) 156*e*.
films, reactively evaporated, optical properties, (3) 84*g*.
-SiO cermet films, resistivity and structure, (5) 139*e*.
photo-induced paramagnetic resonance, in zinc sulfide crystals, (9) 285*c*.
reaction between nitrogen and spinel in, (10) 296*e*.
reaction with oxides of rare earth elements, (10) 324*h*.
refractory compounds, electron structure, (9) 282*a*.
in steel, spectrographic determination using laser as excitation source, (10) 315*e*.
systems. See *Systems*.
thiometallates and oxides, diffuse reflectance spectra, (3) 80*c*.
trivalent, with tetragonal symmetry in MgO, spin states, (6) 189*b*.

Circuits, assembly, multichip integrated, with interconnection structure, P (9) 274*b*.
breaker, electric, with ceramic capacitor elements connected in parallel with contacts, P (8) 244*a*.
components, relations between firing temperatures and structural properties in ceramics for, (5) 139*c*.
cryogenic, improved, process for preparing, P (10) 311*g*.
electrical, device, P (4) 99*h*.
electroformed welded, (9) 271*j*.
ferroelectric, element material, and transducer utilizing, P (1) 17*h*.
grinding, process dynamics and use of automatic control, (1) 19*i*.
high critical field superconducting, method for producing, P (2) 51*c*.
hybrid, integrated, ceramics in, (3) 71*a*.
hybrid, in thick and thin film techniques, (10) 307*c*.
idler, encapsulated in parametric or tunnel diode semiconductor device, P (10) 309*i*.
integrated, P (8) 244*f*.
with active and passive components in same semiconductor region, P (4) 100*e*.
and laser beams, (3) 71*g*.
method for fabricating, P (3) 73*h*.
micro-, with buried conductive layers, P (8) 245*h*.
temperature controlled, P (11) 345*b*.
thick-film hybrid, (6) 176*j*.
modules, integrated, P (5) 141*b*.
multilayer film, manufacturing, P (5) 142*e*.
package, ceramic, manufacture, P (4) 100*h*.
printed, base construction for evacuated envelope housing, and components, P (4) 99*d*.
semiconducting components, electrically isolating, P (8) 245*c*.
semiconductor, P (11) 344*a*.
integrated, P (11) 345*f*.
integrated, including fast switching transistor, method of forming, P (8) 245*h*.
integrated, structures for and methods of forming, P (1) 19*c*.
structure, transistor-capacitor integrated, P (8) 246*g*.
thin film, economic substrate size for, (3) 71*d*.
passive, oxidized aluminum for, (10) 307*f*.
RC, on single substrate, P (8) 246*f*.

Circulators, broadband microwave ferrite, (6) 176*b*.
ferrite, latched, P (2) 51*f*.

Classification. See also *Separation; Separators*.
continuous, of solid particles dispersed in fluid carrier, method and apparatus, P (2) 53*c*.
of dry process enamels for cast iron bathtubs by drip test, (5) 125*i*.
of sandstone, modification, (9) 284*f*.
of sandstone, numerical method, (1) 30*f*.
system, P (8) 247*a*.

Classifiers. See also *Beneficiation*.
Bahco type, for measurement of particle size distribution, (1) 21*e*.
centrifugal air, P (6) 179*f*.

Classifiers (*continued*)
hydrocyclone, eccentric head, P (8) 247*c*.
-separator, particle, P (5) 144*d*.
simple continuous solid particle shape, (6) 179*e*.
Clays. See also *Ball clay; Fireclay; Kaolin*.
axial ratio, (4) 106*e*.
Bansi, mineralogy, (4) 113*d*.
Bansi, mineralogy by intercalation technique, (6) 182*e*.
bauxite-, mixtures, thermal behavior, (11) 339*f*.
beneficiation, by removal of titanium impurities, P (6) 183*b*.
as binding materials, (1) 10*g*.
blue ball, deflocculation: sodium hydroxide and sodium carbonate, (7) 216*d*.
bodies, design for controlled microstructure: I, concepts and body design, (6) 172*a*; II, clay-aggregate bodies, (7) 199*h*; III, reactive aggregates and quantity of mixmatch, (9) 299*e*.
bodies, fired, relations between mineralogical and chemical composition and moisture expansion of, (10) 306*b*.
bonding and application in foundry industry, (6) 172*h*.
brick, constitution and behavior, (5) 150*g*.
brick, weathering, (10) 302*a*.
brickmaking, reserves in Britain, (1) 25*e*.
brightness, method for improving, P (3) 78*b*.
building, typical Polish, mineral compositions and properties in unfired condition, (6) 172*c*.
calcination, P (8) 250*f*.
for cast whiteware bodies, evaluation and selection, (1) 15*j*.
ceramic, of Ontario, processing problems, (11) 349*b*.
china. See *Kaolin*.
and clay-graphite mixtures, extrusion and microstructures, (9) 267*a*.
and clay minerals, B (5) 160*i*; B (6) 191*c*; B (7) 224*j*; B (8) 259*g*; B (9) 289*b*.
creamy, from Sriperumbudur, Madras State, (8) 250*e*.
dispersion, for particle size determination, (1) 21*d*.
Dorset ball, physicochemical properties for characterization and control, (1) 31*c*.
dry-bending strength, (1) 15*c*.
drying sensitivity, infrared spectrography, (7) 218*b*.
drying, water diffusion phenomena, (6) 172*a*.
engineering material, (2) 56*j*.
expandable, in St. Marys formation of southern Maryland, (7) 214*d*.
expanded, economic production, (4) 95*g*.
expansive, determination of swelling pressure, (1) 24*i*.
extruded, products, loss of quality, (2) 42*i*.
extruded, structure and behavior: I, surveying microstructure and flow patterns; II, piston and auger extrusion; III, effects of extrusion, (2) 43*c*.
extruder, flow process in, (7) 199*h*.
fabric, and relation to structural properties in midcontinent Pennsylvanian sediments, (1) 26*j*.
fat, shortening, (11) 337*b*.
fat, shortening with calcined clay or sand, influence on firing behavior and properties of unfired and fired products, (11) 337*c*.
flocculated, behavior in thickening, (5) 143*j*.
fractions and colors of some Devonian red beds in Catskill Mts., (1) 27*b*.
fractured, P (1) 25*b*.
for glass pot making, (11) 338*c*.
-grog mixtures, investigation for use in auger, (10) 301*h*.
Illinois, as binders for iron ore pellets, (1) 10*h*.
Indian, clay mineral composition, (1) 27*c*.
to replace Rajamahal china clays, (7) 214*e*.
particle size determination, and properties, (6) 182*f*.
London, in Suffolk, surface, (10) 317*i*.
kaolinite-halloysite, mineralogical studies: III, fibrous kaolin mineral from Piedade, Sao Paulo, Brazil; IV, platy mineral with structural swelling and shrinking characteristics, (5) 154*j*, 155*a*.
kaolinitic, dilatometric properties as measure of mineralogical composition, (6) 180*j*.
kaolinitic, illitic, and montmorillonitic, effects of soap, detergent, and water softener on plasticity, (1) 24*j*.
Kharga, constitution and suitability, (3) 79*j*.
materials, probability sizing, (10) 301*i*.
mechanism of structure formation with quicklime additions, (5) 125*e*.
Mianwali plastic, replaced by imported ball clay in ceramic bodies, (9) 271*b*.
microstructure and drying shrinkage, effect of graphite, (6) 172*j*.
milling, (9) 278*i*.
mineralogy studies, importance and application in civil engineering problems, (1) 24*j*.
minerals. See also specific types.
in bore core samples from Tsugaru Strait tunnel, (8) 250*i*.
cation exchange equilibria in Na–K–Ca–Mg systems of, (6) 184*d*.
dehydration, (7) 212*a*.
electrochemical and viscometric study, (5) 151*g*.
formation of water and dehydration of lattice in, (7) 215*h*.
forming processes, (2) 57*e*.
identifications from IL and dye absorption, (5) 145*b*.
interstratified, calculation of total one-dimensional diffraction function, (7) 218*f*.
interstratified, suggested terminology, (2) 59*j*.
Clays (*continued*)
mixtures, high-temperature reactions and ceramic properties: IV, dimensional and weight changes on refiring and pore-size distribution of fired kaolinite-muscovite-quartz mixtures with 25%(wt) quartz, (3) 81*c*.
mounting techniques for X-ray diffraction analysis, discussion, (8) 247*j*.
optical determination of preferred orientation in, and application to study of microstructure in consolidated kaolin, (9) 285*b*.
origin, (3) 84*i*.
plasticity, (1) 22*g*.
in southeastern U. S., transport and deposition, (5) 148*i*.
structure, (5) 158*e*.
structures, electron-diffraction analysis, B (10) 328*i*.
synthesis: II, randomly interstratified aluminian montmorillonoid, (5) 150*c*.
modified, process for manufacture, P (2) 57*a*.
organic matter in, (10) 315*d*.
particle size, reducing, P (2) 57*c*.
particle-size separation, (7) 212*i*.
preparation equipment, in structural clay products industry, (11) 348*j*.
preparation plant, (5) 147*i*.
products, of clay and charcoal, P (7) 214*j*.
properties, (3) 85*e*.
effect of surfactants, (2) 58*b*.
of lower Cabaniss underclays in western Missouri, (1) 10*e*.
-quartz mixtures, anomalous differential drying shrinkage of, (4) 106*d*.
quick, microstructure, (7) 220*f*.
quick, properties, Norwegian research into, (7) 220*d*.
raw material parameters determining extrudability, (10) 301*j*.
as raw material for structural clay industry, (2) 42*i*.
red stoneware, sand in, (8) 242*g*.
refractory, program for testing prospect samples, (2) 45*g*.
and related materials, Eastern counties of Virginia, analyses, (7) 214*c*.
resources, of Clark, Crawford, Cumberland, Edgar, Effingham, Jasper, and Vermillion Counties, Ill., (1) 10*f*.
of Saurashtra, Gujarat, India, silica to sesquioxide ratios for, (1) 32*b*.
sedimentation: III, treatment of acid waste liquor in industry and recovery of usable by-product, (8) 250*a*.
semiacid, of Kuznets Basin (USSR), using, (9) 269*i*.
and soils, research, recent developments, (3) 86*a*.
soils, stabilized with cementitious agents, structures, (8) 229*a*.
spray dried, product, and production, P (6) 183*f*.
in and around Srinagar in Andhra Pradesh, India, economic aspects of processing and activation, (3) 77*g*.
tertiary, in Birbhum District, West Bengal, (8) 250*i*.
thermal expansion, effect of lime, (9) 266*f*.
thermochemical analysis, rapid, (11) 347*b*.
titrimetric analysis of organic material in, (11) 347*c*.
ware, production in Tunisia, (6) 190*j*.
-water systems, foamed, for lightweight aggregate production, (4) 95*i*.
-water systems, rheology control, P (2) 57*c*.
works, drying and handling in, (5) 143*j*.
Cleaning, porcelain enamel, (9) 262*h*.
porcelain surfaces, P (8) 229*j*.
of semiconductor devices, P (8) 244*e*.
spinnerette, during preparation of inorganic oxide monofilaments, P (8) 247*e*.
Clinker. See *Cement; Dolomite; Forsterite; Magnesite*.
Coagulation. See *Agglomeration*.
Coal. See also *Coke; Fuels*.
ash. See *Ash*.
Coatings. See also *Enamels; Glazes; Resins*.
alumina-zircon ceramics, P (8) 240*a*.
Al, Ga, As, and P binary, formation, P (10) 309*f*.
aluminum nitride, on graphite, (5) 131*f*.
application. See *Electrostatic processes; Spraying*.
for boron, to prevent reaction with matrix metal, P (3) 68*j*.
for carbide particles, P (6) 174*a*.
carbon article, shaped, with polycarbon fluoride, P (11) 340*i*.
on carbon and graphite filaments, P (5) 136*c*.
carbon substrates with refractory metal carbides, P (10) 304*c*.
cathode-ray tubes, P (7) 209*d*.
ceramic, for drill rod assembly, P (3) 93*c*.
ceramic substrates colored, process, P (5) 144*e*.
chrome oxide, P (2) 38*a*.
clear, for exposed architectural concrete, (10) 294*b*.
color, clear glass permanently, (3) 63*f*.
corrosion-resistant, for magnesium die castings, P (7) 195*a*.
crystalline heat-resistant, substances for producing, P (8) 236*d*.
crystallized glass ceramic, P (9) 263*a*.
diamond, with adherent metal coating using cathode sputtering, P (2) 52*d*.
"elastic" ceramic as electronic material, (5) 137*j*.
electroless, on nonconducting surfaces, P (5) 141*d*.
electrostatic. See *Electrostatic processes*.
Coatings (*continued*)
evaporative, apparatus and method, P (4) 92*j*.
of feed and breed particles in fluidized bed under reduced pressure, (7) 200*e*.
films. See *Films*.
foamed pattern with refractory filler and silicon-containing binder, P (2) 47*d*.
formation, on pristine surface of glass rod, (2) 39*h*.
glass, composition, conductors and coils insulated with, and method of making, P (11) 332*h*.
dual protective, P (2) 40*j*.
for protection and lubrication of metals at high temperatures, P (3) 66*a*.
semicrystalline, and method of applying to metallic bases, P (5) 126*d*.
on glass articles, measuring thickness, P (11) 336*h*.
glassy plasma-sprayed, theoretical and technical viewpoints, (5) 126*d*.
ground, semicrystallized, and enameled articles from, P (11) 333*a*.
of hafnium oxide and zirconium boride, P (7) 195*c*.
heat and corrosion resistant, composition, P (9) 263*b*.
heat-resistant ceramic, of refractory oxides, produced by gas-flame spraying, thermal conductivity and total emissivity of, (5) 132*g*.
high-temperature, of aluminum silicate based glass, P (9) 270*d*.
reflective and thermally protective, P (4) 93*a*.
technology advancements, (2) 37*j*.
of high-temperature materials, B (7) 225*e*.
indium oxide, electroconductive transparent, method for deposition, P (3) 73*e*.
inorganic, apparatus for applying to glassware, P (3) 64*i*.
internal glass, of steel pipes, stress distribution in, due to difference in coefficients of expansion of glass and metal, (10) 298*j*.
light absorbing design, on screen structure of image reproducer, P (5) 141*f*.
lubricant, for glassware molds and equipment, P (1) 9*f*.
lubricous, for glass, P (9) 265*i*.
lubricous, for glass containing polyvinyl alcohol, emulsified polyethylene, and inorganic acid, P (3) 65*a*.
MnO dielectric, for barrier-layer capacitors, P (9) 273*j*.
metal, for ceramic bodies, method, P (1) 18*f*.
to diamond, evaporative application, P (7) 193*j*.
hard-solderable, adherence to ceramic surfaces, (1) 3*f*.
with high melting point, applying to ceramic article, P (5) 142*h*.
vapor lamp, P (6) 171*b*.
metallized, interaction with solders on ceramic materials, microspectral method for investigating, (10) 307*e*.
metallizing, of alumina ceramics with Mo, MoO_3 and Mo–Mn, (2) 37*j*.
automatic, (2) 37*g*.
flame spray, P (1) 20*b*.
manganese glass-molybdenum, (6) 166*c*.
paint, low dielectric loss, with reduced sintering temperature, P (2) 51*f*.
paint, low temperature, and method of making, P (2) 38*c*.
surfaces of ceramic bodies, P (1) 19*a*.
vacuum, (5) 144*b*.
method, for glass fabric and product, P (3) 65*e*.
mold, permanent: V, properties of metal mold coating for cast iron, (9) 268*c*.
$MoSi_2$/SnAl, protective, for molybdenum, (10) 296*h*.
niobates and tantalates of alkali metals and alkaline earth metals, P (5) 142*d*.
nonuniform metal, forming on ceramic body utilizing abrasive erosion step, P (10) 310*f*.
from organometallic solutions, (3) 63*b*.
oxide ceramic protective, properties and plasma spraying of, (1) 15*e*.
oxide, forming on semiconductor bodies, P (8) 245*g*.
photoelastic, for nondestructive testing, (7) 212*h*.
plasma, adhesion to base, (8) 237*a*.
plasma and diffusion, on graphite, (5) 133*a*.
plaster, on metal, to improve fire resistance, P (5) 125*g*.
platinum and palladium, electrodeposition on refractory metals from aqueous electrolytes, (2) 37*j*.
polytetrafluoroethylene, to surfaces of glass cooking vessels, P (6) 170*g*.
protective, (1) 3*j*.
ceramic, for metal, P (11) 332*j*.
high temperature, P (3) 63*c*.
metal oxide, on inner wall of quartz envelope in high pressure lamp, P (7) 209*b*.
refractory, for metal ingot mold, P (11) 332*i*.
of refractory material, to prolong life of furnace linings, P (2) 47*c*.
for refractory metals, method for providing and resulting article, P (4) 93*b*.
by surface nitridation of boron filaments, (10) 303*g*.
temporary high temperature agents, for metals, P (11) 333*a*.
for thin film devices, P (5) 140*j*.
transparent, for fluorescent lamp envelope, P (7) 208*h*.
pyrolytic-carbon, low-density, for nuclear fuel particles, (2) 44*i*.
pyrolytic graphite, on tungsten, P (7) 195*f*.

Coatings (*continued*)
refractory, forming on silicon-iron stock, P (9) 263*b*.
refractory, for graphite, and product obtained, P (5) 135*j*.
refractory metal carbides, on carbon substrates, P (10) 304*c*.
on refractory metals, B (7) 225*e*.
semiconductor devices surface, for improving noise characteristics, P (10) 310*j*.
semiconductor devices with silicon oxide, P (11) 344*e*.
silicide, modified, analysis for oxidation protection of columbium and tantalum, (1) 3*g*.
silicon, uniform, on graphite by chemical vapor deposition, (2) 38*e*.
silicon carbide, beta, for carbon crucible, P (8) 240*c*.
deposited by vapor phase reaction at high temperature, (11) 353*d*.
on graphite bores of heat exchanger, P (10) 305*a*.
silicon-containing diffusion, for ferrous metals P (11) 333*b*.
solid lubricant, applied by plasma spray, (10) 296*e*.
stabilized redpigment filter, in fluorescent lamp, P (5) 143*c*.
surface, effect on friction between glass containers, measurement, (5) 127*j*.
thermal control, on aluminum, P (11) 333*a*.
thermal-control, effects of interplanetary space environment on, (9) 263*c*.
thermal retardation, in rocket nozzles and skirts, (2) 46*a*.
thin conductive, method and apparatus for controlled deposition of, P (6) 177*h*.
thin films. See *Films, thin*.
titania, light-diffusing, method for producing on glass, P (2) 41*i*.
VO_2, applied to alumina substrates, (4) 99*a*.
vapor, nuclear fuel with BeO and C, P (11) 340*i*.
vapor, substrates, apparatus for, P (11) 343*f*.
weight, nuclear fluorescence for measuring, (9) 276*f*.
welding electrode, apparatus for drying and hardening, P (3) 63*c*.
zirconia, for protection of high-temperature metal-working extrusion dies, (2) 37*h*.
Cobalt, (II), environment, in nitrate glass, (10) 297*d*.
(II), semiquantitative estimation and separation on ultramicroscale, (3) 76*e*.
chloride, crystal-field effects in, (9) 280*b*.
paramagnetic and antiferromagnetic, pulsed-NMR study of protonic relaxation in, (8) 256*i*.
spin-cluster resonance in, (11) 357*b*.
thiourea-coordinated, magnetic transition in, (10) 323*e*.
$CoCr_2S_4$, NiAs-type polymorphs, magnetic properties, (8) 255*c*.
Co_3O_4, paramagnetic, NMR: I, experimental study; II, theory of NMR shift, (4) 113*c*.
$CoPt_3$, magnetic moments and unpaired-electron densities in, (9) 284*c*.
disulfide, preparation and magnetic properties, (8) 256*c*.
ferrite, pulverized, magnetic properties, (5) 154*b*.
fluoride, crystalline, Zeeman splitting of narrow lines in, evidence for spin-wave excitations, (10) 327*g*.
metallic, determination in reduced ores and oxides, (8) 248*b*.
monoxide, electrical properties, (5) 138*b*.
oxidation, short time, high temperature, (4) 115*d*.
oxide, crystals, electron distribution of ions in, (3) 80*d*.
at high pressure, Moessbauer study of ^{57}Co-(^{57}Fe) in, (10) 323*f*.
lattice parameter, as function of pressure, (7) 219*c*.
single crystals, antiferromagnetic magnetostriction in, (4) 111*h*.
single crystals, neutron-diffraction investigation, (8) 255*g*.
X-ray diffraction study, (7) 223*c*.
relation to basicity of borate glasses, (7) 196*j*.
systems. See *Systems*.
Coke. See *Coal; Fuels*.
Coke ovens. See *Refractories*.
Colloids. See also *Silicon, dioxide, gels*.
aerogel, organosilica, process of preparing, P (1) 25*i*.
aerosol, apparatus for determining particle size, P (2) 55*c*.
aerosols, monodisperse, of sodium chloride, preparation, (1) 31*j*.
aquasols, silica, preparing, P (6) 183*a*.
gels, alumina, process for producing, P (2) 47*j*.
-asbestos, silica, compositions, P (7) 215*d*.
growth of clear cuprous chloride crystals, (2) 58*j*.
metal phosphate, and methods for producing, P (8) 251*f*.
thoria, crystallite size measurements, (1) 27*h*.
thoria, equivalence of X-ray and electron microscopy crystallite sizes in, (5) 152*g*.
zirconium phosphate, of different crystallinity, effect of water content on sorption, (7) 218*e*.
sols, hydro-, apparatus for converting into solid microspheres, P (8) 250*d*.
microcrystalline corundum, and method of preparing, P (5) 135*d*.
nonaqueous silica, and method of preparing, P (2) 56*j*.
silica, method of stabilizing, P (1) 25*g*.
Colloids sols (*continued*)
stable alkaline colloidal silica, of low viscosity and processes for preparing, P (1) 26*a*.
thoria, preparation by heating aqueous solution of thorium salt in autoclave, P (3) 69*f*.
uranium oxide, P (7) 205*h*.
uranium oxide, forming method in presence of formic acid and palladium-on-thoria catalyst, P (4) 97*j*.
Color. See also *Pigments; Stains*.
and application in glazes and/or ceramic bodies, (9) 270*j*.
blues and greens over 50% of color spectrum, for enamels, (11) 332*e*.
center production, in MgO, effect of atomic displacements, (8) 253*d*.
centers, in alkali borate glasses containing Co, Ni, or Cu, (9) 263*f*.
in glasses of M_2O–Al_2O_3–SiO_2 system, (1) 8*c*.
radiation induced, in vitreous systems, (11) 334*g*.
in TlCl, (8) 252*h*.
ceramic, granulated zinc oxide for, (6) 206*g*.
ceramic, selection, (3) 88*j*.
coloration in glass, (8) 230*i*.
coloration, photo-, of metal oxides: I, light sensitivity of MoO_3 or WO_3 coprecipitated with TiO_2, (4) 114*d*.
control, in glass enamels, (2) 38*j*.
decolorizers, optimum quantity, in tableware glass, (8) 233*a*.
differences, MacAdam, optimized equations for, (6) 187*a*.
discoloration of barium titanate powder, effect of grain size on, (10) 319*g*.
induction, quantitative evaluation, (6) 188*a*.
luster, for glass and porcelain, (5) 136*g*.
matching, proper standard for, (10) 312*j*.
matching, spectrophotometric, with least squares technique, (6) 189*b*.
measurement. See *Colorimetry*.
ornamentation, of glass articles, P (1) 8*g*.
standardization and control: I, dependent on management determination; II, visual color comparisons, (2) 60*d*; III, setting up color control program, (3) 89*a*.
surface, for brick and structural clay products, (10) 302*a*.
and what affects them, (4) 91*f*.
Colorimetry, CIE recommendations, (6) 188*b*.
determination of sulfur in glasses, (6) 166*i*.
dynamic differential, quantitative application: I, theoretical and experimental evaluation, (5) 146*b*.
of ferric iron in high concentration range, simple method for, (1) 23*c*.
industrial, (10) 314*d*.
industrial, in glazes, practical problems, (10) 306*c*.
tests in ceramics, (10) 313*b*.
Coloring materials. See *Decoration; Pigments; Stains*.
Columbium. See also *Niobium*.
oxidation, observation of markers during, (6) 187*j*.
oxidation protection, analysis of modified silicide coatings for, (1) 3*g*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heat; Kilns*.
equipment and controls, for glass industry, recent developments, (9) 264*f*.
precision control, (8) 249*h*
process and apparatus to increase flame temperature, P (11) 348*h*.
time, effect on appearance of vibrating diffusion flames, (8) 249*e*.
Comminution. See *Crushing*.
Compaction. See also *Pressing*.
explosively shocked, MgO and α-Al_2O_3, X-ray line broadening study of, (8) 258*e*.
and means, for dense metallic articles, P (8) 247*b*.
of molybdenum disilicide, (11) 338*e*.
Compacts, method of producing by reacting particulate ingredients, P (3) 69*d*.
mixed ceramic, method of fabricating, P (1) 13*c*.
porous, grain growth in, comments on theory, (9) 282*e*.
UO_2–ThO_2–BeO, release of xenon-133 on post-irradiation heating of, (2) 45*j*.
Composites, Al_2O_3-glass, hot-pressed, chemical reaction, (1) 26*j*.
Al-10% Si, containing nickel-coated sapphire whiskers, role of nickel in, (10) 304*b*.
body, niobium and alumina, and method of making, P (7) 208*h*.
boron-epoxy and glass-epoxy, engineering constants of, (10) 290*f*.
brittle matrix, strengthening by chemical bonding in, (11) 332*f*.
casting, method of preventing segregation during, P (5) 135*b*.
ceramic fiber with carbon or graphite, (11) 332*f*.
elastic moduli, prediction, (9) 285*g*.
fiber. See also *Glass, reinforced*.
-reinforced, (6) 181*e*.
tensile strength and failure mechanics of, (8) 257*g*.
filament-reinforced, facture mechanisms, (10) 303*a*.
glass-indium-glass bimetallic, stress in, (8) 229*f*.
graphite metal body, P (8) 240*f*.
high temperature dielectric reinforced, P (9) 270*c*.
hot-pressed alumina-niobium graded, (7) 202*a*.
LaF_3-Nd^{3+} laser, continuous induced radiation from, at room temperature, (10) 306*i*.
MgO matrix, elastic behavior, (1) 28*f*.
material, of ceramic silver-gold alloy and nickel alloy, P (1) 17*d*.
material, and method for making, P (3) 72*c*.
Composites (*continued*)
metal-oxide-metal, thin, electroluminescence and electron emission, correlation between, (10) 306*j*.
materials, whisker-reinforced, (11) 338*e*.
nature and properties, in materials, B (11) 358*d*.
polybenzothiazole, glass fiber reinforced, strength properties, (10) 298*h*.
silicide-coated, and method of making, P (8) 230*a*.
structural plastic, incorporating new high modulus fibers, (9) 269*j*.
Compressibility, of crystals with NaCl or CsCl structure, effect of high pressures, (7) 217*c*.
isothermal, behavior near ferroelectric transitions, (10) 319*d*.
of powders, (1) 27*e*.
of pyrolytic graphite, (5) 150*f*.
Compression, shock-wave, of barium titanate and 95/5 lead zirconate titanate, (9) 286*b*.
shock-wave, of TiO_2, (4) 115*c*.
Computers, aid in bottle-glass production, (7) 195*i*.
analog, solves clay blending problem, (2) 48*g*.
control, for batching process, (2) 38*g*.
electronic, application for computing tables of indices of multicomponent systems, (1) 26*g*.
in float-glass production, (10) 297*e*.
for liquidus data of binary and ternary salt systems, (5) 154*b*.
processing of data in production of glass containers, (7) 195*j*.
for whiteware control tests, (4) 98*e*.
Concentration, of beryllium and aluminum minerals, P (7) 205*e*.
excess donor, in GaP grown from vapor phase in silica tubes, effect of water pressure, (4) 108*h*.
OH^-, influence on low-temperature dielectric loss in silica glass, (2) 58*b*.
relative, of elements, errors in determination, (9) 277*b*.
Concretes. See also *Cement; Masonry; Mortars; Pozzolans*.
acid resistance, increased with ocrate treatment, (1) 2*h*.
aggregate, blast furnace slag, and steel in, with blast furnace slag aggregate, discussion, (5) 124*j*.
architectural, exposed, clear coatings for, (10) 294*b*.
autoclave-hardened lime-sand, deformation, (1) 2*c*.
beams, rectangular reinforced and prestressed, shear strength, (8) 228*j*.
block, properties, influence on shrinkage cracking of masonry walls, (6) 165*c*.
calcium silicate lightweight, autoclaved, development, considering chemical reaction and mechanical strength, (1) 2*d*.
cellular, significance of cement composition for CO_2 treatment of, (10) 295*h*.
compressive strength, factors affecting, (8) 228*j*.
confined by rectangular transverse reinforcement, flexural stress-strain relationship of, (8) 228*c*.
creep, under uniaxial and biaxial stresses at elevated temperatures, (8) 228*d*.
densifier and waterproofing agents for, and method of making, P (5) 125*c*.
deterioration, from sand-gravel, reactivity, (6) 164*g*.
effect of mix proportions and method of testing on Poisson's ratio, discussion, (5) 124*j*.
electrical resistivity, (10) 294*f*.
foam, from chemical industry wastes, (5) 124*j*.
form pressure, effect of cement hydration, (5) 124*g*.
gap-graded shrinkage-compensating, proposed synthesis, (2) 36*f*.
gas, cellular structure, and granulometric composition of filler, (6) 164*a*.
heat-cured high-strength, strength, effect of pressure, (8) 228*j*.
of improved strength, production, P (9) 262*e*.
keramzit, effect of densification on deformation of, (1) 2*c*.
lightweight aerated cellular, (5) 125*d*.
mix, with set retarding admixture, P (2) 37*e*.
prestressed, for domestic water piping systems, (5) 130*j*.
elements, single cylinder hydraulic machine for tensile testing of, (10) 294*i*.
shrinkage and creep in, (9) 262*f*.
properties, interrelations with cement: III, compressive strengths of portland cement test mortars and steam-cured mortars, (10) 295*a*.
refractory, gas permeability determination, (10) 303*e*.
testing bond in zinc scrap melts, (9) 269*d*.
two-component failure mechanism in flue-gas duct, (6) 173*f*.
resistance to aggressive solutions, effect of open porosity, (8) 228*i*.
of retarded setting, experiments on hydration, (1) 2*d*.
ring structures, prestressed, influence of creep and shrinkage, (8) 228*b*.
sand, deformation during freezing, (5) 124*k*.
silicate, durability, effect of binder composition, (5) 124*f*.
slabs, fire endurance, influenced by thickness, aggregate type, and moisture, (10) 294*k*.
strength, estimate by ultrasonic pulse velocity and damping constant, (2) 36*j*.
tensile strength determination, (6) 164*i*.
Condensation, of high-melting oxide vapors, to stable and metastable condensed liquids, (7) 218*e*.
Condensers. See *Capacitors*.

Conductivity, electrical, and(or) Conduction, electric, of alkali germanate melts at 1300°C, (3) 80*a*.
of alkali metal nitrate melts, (11) 352*h*.
of alkali silicate glasses, (8) 231*b*.
of Al–Si and Al–Si–Mg alloys, (1) 16*e*.
in BaO–P_2O_5 glasses, and dependence on water content, (8) 231*j*.
of BeO, (3) 67*e*.
of BeO and BeO binaries, (7) 201*f*.
in cerium oxide, by oxygen ions, (5) 138*a*.
compositions, compound $Ag_2In_8Se_{13}$, P (1) 17*g*.
of concentrated aqueous solutions and molten salts, correlation through free volume transport model, (11) 352*g*.
in dust-laden [BaO] gases, photoelectric enhancement, (9) 285*a*.
of fused KNO_3, (3) 80*b*.
of GaAs, vapor deposited, changing by introduction of water into vapor deposition atmosphere, P (11) 344*d*.
gamma-induced, in alumina, (3) 81*g*.
of glass, method of changing, P (10) 300*j*.
in glassy carbons, (8) 253*b*.
of graphitic materials hot-worked with dispersed liquid carbide, (8) 254*d*.
high-temperature, of alumina, (3) 81*b*.
of lead silicate glass surface layer, change during heat treatment in hydrogen, (2) 38*i*.
impurity density, logarithmic dependence on, (10) 322*d*.
in Li-doped NiO, mechanism, (9) 284*b*.
of lithium hydride, molten and solid, (5) 138*b*.
low-temperature, in calcium-doped lithium fluoride, (10) 322*e*.
of MgO at low temperatures, (11) 352*h*.
of mixed alkali silicate glasses, (3) 64*h*.
of molten alkali silicates: I, experiments and results; II, theoretical discussion, corrections, (2) 39*a*.
of molten $PbCl_2$–PbS mixtures: II, systems PbS–$PbCl_2$–Pb–PbS–$PbCl_2$, (10) 320*h,i*.
of molten nitrates, effect of pressure, (5) 127*h*.
of NiO-doped with lithium, (7) 222*i*.
permanent photoinduced, in silver halide crystals (10) 324*h*.
semi-, in $Cd_{1-x}Ca_xF_2$:In^{3+} single crystals, (1) 16*h*.
semi-, in nonstoichiometric rare earth oxides, (5) 139*h*.
of SiO very thin films, (5) 150*i*.
of sintered CeO_2 ceramic, change during reduction, (6) 184*e*.
of soda-lime-silica melts, (8) 231*d*.
in Na_2O–Al_2O_3–SiO_2 and Na_2O–CaO–Al_2O_3–SiO_2 glasses, (1) 7*i*.
in solids, B (10) 328*e*.
of solids, (3) 71*f*.
space charge, in solids, B (9) 290*h*.
studies of tetragonal zirconia, (10) 320*i*.
super-, of high pressure phase of $CaSi_2$, (8) 252*d*.
of InSb high-pressure phases, (10) 325*d*.
of metallic aluminum antimonide, (4) 117*f*.
of technetium and technetium carbide, (4) 117*g*.
in thoria and thoria-yttria as function of oxygen pressure, (5) 138*b*.
time dependent, in titanium oxide, (6) 190*a*.
of UO_2, (1) 11*h*.
of zinc oxide, effect of variations in concentration of atmospheric constituents, (3) 71*e*.
Conductivity, electronic and(or) ionic, in alkali and thallium silicate glasses, (7) 196*b*.
in $BaTiO_3$, (5) 137*j*.
of CsCl single crystals, (8) 256*i*.
mechanisms in glasses, (10) 297*b*.
of sodium bromide containing barium bromide, (2) 50*i*.
Conductivity, thermal. See also *Heat*.
artificial use in, numerical procedure for shock problem, (10) 324*b*.
of basic brick for steel converter, (7) 203*i*.
of brazed expanded pyrolytic graphite to 700°C, (9) 269*f*.
of castable refractories, in relation to bulk density, (3) 68*f*.
coefficient, of solid materials at 200° to 1000°C, determination, (5) 145*a*.
in fibrous insulators, physical basis, (6) 173*j*.
of graphite parallel to basal planes, (4) 117*h*.
of graphitic materials hot-worked with dispersed liquid carbide, (8) 254*d*.
of heat-resistant ceramic coatings of refractory oxides produced by gas-flame spraying, (5) 132*g*.
high-temperature apparatus to obtain for refractories, (5) 134*h*.
of manganese ferrite single crystals at low-temperatures, (5) 159*b*.
measurement by cylinder method, (6) 180*h*.
measurements on basic brick, (7) 204*a*.
of molten alkali nitrates, (7) 197*b*.
of molybdenum thick films on BeO, (10) 308*j*.
of neutron irradiated BeO, at low temperature, (3) 68*f*.
of nometallic crystals, (2) 58*a*.
of plutonium monophosphide and monosulfide, (8) 258*a*.
of KH_2PO_4-type single crystals, (7) 222*d*.
radiant-molecular, of molten glass, (10) 299*h*.
of refractories, apparatus for measuring, (9) 276*g*.
of refractories, measurement at high temperatures, (8) 238*f*.
of refractory materials and insulating brick, hot-wire method of measuring, (6) 173*g*.
of selected materials, B (9) 290*d*.
of solids, measurement, especially of ceramic nuclear fuels at highest temperatures, (1) 11*f*.
of UO_2, effect of electrical conduction, (4) 108*g*.

Conductivity (*continued*)
of UO_2 at high temperature gradients, (10) 326*h*.
of UO_{2-x}, UO_2, and UO_{2+x}, effect of irradiation on thermal conductivity, (9) 281*h*.
of vermiculite and asbestos mixtures, and their cement mortars, (8) 240*d*.
Conductors, electrical. See also *Semiconductors*.
gold-palladium composition, P (1) 17*j*.
insulating composition for, and method of making, P (1) 4*g*.
photo-, far infrared, rare-earth-doped CdF_2 as, (1) 16*d*.
sheet, stable, method of making and product, P (1) 18*e*.
suitable for sealing in wall of electric discharge tube, P (7) 208*b*.
super-, with variable transition temperature, P (4) 101*d*.
vitreous materials, P (1) 9*d*.
welded, to carbon and graphite cloth, P (3) 74*f*.
Conferences, ceramic, transactions of 10th international, B (9) 290*e*.
ceramic chemists, October 1963, B (7) 223*i*.
ceramic chemists, on silicate analysis, September 1965, B (7) 223*i*.
Solid State, interaction of radiation with solids, B (10) 328*e*.
Congresses. See *Conferences*.
Consistency, measurement, of plaster slips, (4) 91*j*.
Contacts, alloy, containing Al and Sn, P (3) 72*i*.
angles, dynamic: I, effect of impressed motion, (9) 276*c*.
measurement of fibers, (9) 276*f*.
of small drops, microscopical methods of determining, (9) 277*b*.
body, sintered, P (1) 19*d*.
electrical, to GaAs wafer, P (9) 274*i*.
electrical, to solid nonmetallic conductors, (4) 99*a*.
high-duty electrical, sintered composition material for, P (8) 246*a*.
metal rectifying, forming to semiconductor material by displacement plating, P (11) 344*i*.
metallic, formation, P (9) 273*a*.
nickel-gold for semiconductors, P (4) 100*i*.
ohmic, forming in semiconductor devices, P (11) 344*f*.
low resistance, to *p*-type lead telluride, method of making, P (4) 100*d*.
preparation for *n*-type GaAs, (4) 99*e*.
properties, with metals in conductive CdS single crystals, (5) 153*h*.
Containers. See *Glass*.
Controls. See also *Instrumentation; Temperature*.
automatic, for closed circuit wet grinding, (1) 19*i*.
of molten glass levels, problems, (10) 298*j*.
for periodic kilns from 100° to 2000°F, (1) 10*e*.
structure, for particle study apparatus, P (9) 277*e*.
system, for X-ray diffraction apparatus, P (2) 55*c*.
direct digital, (9) 275*f*.
direct digital, of glass furnace, (3) 63*g*.
electrode rapping, for electrostatic precipitator, P (4) 102*a*.
furnace, time-temperature programing, (4) 103*d*.
kiln cooler, method and apparatus for optimization of, P (8) 229*a*.
mixing, during metal and metalloid oxide production, P (4) 105*a*.
pneumatic, in ceramic plant, (3) 76*d*.
process, electronic equipment for, (2) 52*j*.
Conveyors. See also *Materials handling*.
arrangements, for unfired brick, P (6) 179*g*.
and blender for solids, P (8) 247*d*.
jet, for semiconductor components, P (8) 244*h*.
and orienting apparatus, for transistor, P (7) 208*a*.
pneumatic, for dry portland cement, P (6) 166*a*.
pneumatic, for supplying granular material, P (5) 144*e*.
vibratory, and feeder systems, (10) 312*a*.
Coolers, for finely divided materials, and method, P (3) 77*a*.
gaseous, for pulverulent material, P (4) 92*c*.
Cooling, glass furnace electrodes, air stream device for, P (11) 335*c*.
system, rapid, for glass annealing lehrs, P (6) 171*f*.
in unloading area, (10) 312*c*.
Concentrators. See *Separators*.
Copper, and alumina oxides, mixtures, phase conversions in, (9) 283*h*.
compounds, with antimony, (4) 106*j*.
Cu^{2+}, ESR in $CdWO_4$, $ZnWO_4$, and $MgWO_4$ crystals, (7) 217*g*.
Cu(II) in octahedral sites in sphalerite, (1) 28*a*.
$CuFeO_2$, investigation by Moessbauer effect, (3) 71*f*.
CuF_2, sublimation, mass spectrometry of, (5) 154*d*.
$CuNb_2O_6$ and $CuTa_2O_6$, preparation, (5) 157*b*.
Cu_2O, and CuO, thermodynamic data, (4) 118*f*.
contour of absorption lines $n = 2$ of yellow and green series in, (4) 107*d*.
effect on polarization of (Zn,Cd)S, (11) 352*a*.
plastic deformation, (3) 85*a*.
Cu_2Se and Cu_2Te, physicochemical properties, (4) 114*g*.
crystals, deformed, recovery and recrystallization, effect of dispersed silica particles on, (10) 319*g*.
enameled, firing, (8) 229*g*.
enamels, transparency in, (8) 229*g*.
epitaxy, on sapphire, (10) 307*e*.
ferrite, magnetic properties, effect of oxygen deficiency on, (10) 310*j*.
iodide, thermochemical transformations, (9) 287*h*.
oxide, far-infrared properties, (8) 253*h*.

Copper (*continued*)
oxide, single crystal, production by melt, (11) 355*e*.
oxides, phase fields and thermal expansion, (4) 114*b*.
paramagnetic resonance, in amorphous and polycrystalline GeO_2, (10) 324*g*.
semiquantitative estimation and separation on ultramicroscale, (3) 76*e*.
-silica crystals, recrystallization in, (10) 325*b*.
sulfide, cubic high temperature, defect equilibria in, (6) 184*i*.
formed on single crystal CdS, orientation, (2) 50*a*.
systems. See *Systems*.
Cordierite, as basis of thermal shock resistant refractories, (8) 237*j*.
crystallization, primary, equilibrium reactions and dielectric characteristics of compositions near field of, (6) 176*f*.
electronic and vibrational absorption spectra in, (6) 185*j*.
polymorphism: I, crystal structure of low, (2) 59*a*.
synthesis, (10) 304*e*.
synthetic, structural conversions in, (6) 189*d*.
vitrified, compositions and uses for porcelain, (3) 69*i*.
Cores, ceramic ferromagnetic, for inductors or transformers, P (7) 208*h*.
ferrite, fired, continuous process of preparing, P (7) 208*j*.
fluid-cooled, P (7) 208*h*.
process controls in manufacturing, (3) 72*b*.
processing and control in manufacture, (7) 207*j*.
foundry, rapid curing, P (8) 241*b*.
magnetic, lithium nickel ferrite, P (7) 209*b*.
magnetic, problems solved by soft ferrites, (8) 243*d*.
from refractory compositions, P (5) 134*g*.
unconsolidated sediment, preservation in plastic, (5) 146*a*.
Corrosion, of Al_2O_3-SiO_2 system crucible by molten aluminum, (11) 350*j*.
of aluminosilicate refractories under service conditions, (8) 239*a*.
of graphite, inhibiting in CO_2-cooled nuclear reactor, P (6) 174*g*.
of magnesium aluminate spinel in sodium silicate melts, (10) 302*e*.
protection process, for edges of enameled products, (3) 63*c*.
rates, localized, of BeO, techniques for measuring, (2) 46*g*.
of refractories, by blast furnace slags, (8) 237*b*.
of refractory brick, by steelmaking slags, (10) 302*f*.
resistance, of enameled articles, (2) 37*i*.
resistance, of glass to various solutions, (2) 38*i*.
-resistant coating, for magnesium die castings, P (7) 195*a*.
of steel in HCl, inhibiting effect of ferrous chloride on rate of, (11) 332*f*.
tests, crucible method, experimental conditions for, including temperature distribution and cooling velocity of furnace, (10) 302*j*.
crucible method, and observations on heating conditions, (10) 302*g*.
crucible method, with reference to slag quantity and effect of heating rate, (10) 302*g*.
for refractory brick, (10) 303*i*.
standardization by adopting crucible method, (10) 304*d*.
Corundum. See also *Aluminum, oxide; Refractories*.
crystallization, from cryolite molten solutions, (5) 150*f*.
crystals, vanadium-doped, high-temperature magnetic susceptibilities and trigonal field splitting, (5) 138*e*.
single crystal, elastic constants below room temperature, (8) 253*a*.
single crystals, preparation by electron-beam zone melting, (9) 272*g*.
sintered, for synthetic fiber guides, (10) 299*e*.
sintering, under pressure, kinetics, (6) 186*h*.
transparent polycrystalline, ceramic shapes, (9) 271*b*.
trichites, preparation, (6) 172*f*.
Costs, by cube for whiteware, (2) 48*i*.
Cracking, shrinkage, of masonry walls, influence of mortar and block properties on, (6) 165*c*.
tendency, of solids, evaluating methods, (10) 314*h*.
Cracks, cleavage, in perfectly brittle solid, nature of stress at tip, (1) 6*a*.
criteria, of Griffith and Barenblatt, comparison, (1) 5*e*.
Hertzian stress, in BeO and glass, (1) 29*b*.
micro-, determination of relative increase in number of, in ceramic materials from changes in thermal conductivity, (10) 314*a*.
penny-shaped, shear and combined loading for, (4) 115*b*.
propagation, quasi-static, (9) 285*i*.
propagation, in viscoelastic media, (1) 5*i*.
Crazing. See *Glazes*.
Creep, of aluminosilicate brick under load at high temperatures, (10) 302*h*.
behavior, relation with texture of fireclay brick, (9) 268*j*.
of ceramic materials in MgO-$MgAl_2O_4$ system, (9) 280*h*.
characteristics, of selected high-alumina brick, (6) 172*e*.
compressive, of uranium carbide, (9) 266*i*.
in concrete, prestressed, (9) 262*f*.
of concrete under unaxial and biaxial stresses at elevated temperatures, (8) 228*d*.
curve, compression, of MgO, shape of, (4) 115*b*.

Creep (*continued*)
effect, on prestressed concrete ring structures, (8) 228*b*.
high temperature, of polycrystalline magnesia: I, effect of simultaneous grain growth; II, effects of additives, (7) 218*d*.
high-temperature steady-state, in lead sulfide, activation energies for, (6) 183*g*.
in MgO, grain shape change during, (1) 29*f*.
of MgO, stress, temperature, and strain rate in, (11) 357*d*.
mechanisms, diffusional, (3) 80*d*.
of polycrystalline silicon carbide, (3) 79*d*.
properties, of chromium alloys, effect of ceramic environment, (8) 253*f*.
rate, of sintered CeO_2 ceramic during reduction, (6) 184*e*.
rate, stress dependence, of two commercial graphites, (4) 116*h*.
steady-state diffusional, (8) 257*d*.
strength, of niobium alloys, effect of carbide and boride additions on, (11) 352*a*.
tensile, properties, of chromium alloys, environmental effects on, (10) 302*i*.
testing, micro, P (10) 316*b*.
tests on refractories, (10) 303*h*.

Cristobalite. See also *Silicon, oxide*.
β-, stability, lattice parameters, and thermal expansion, (3) 87*a*; dissussion and reply, (6) 185*f*.
as component in structure of porcelain, (3) 69*j*.
formation on vitreous silica boats and relation to GaAs crystal growing, (7) 207*c*.
quantitative determination by X-ray diffraction analysis, (10) 315*j*.
quantitative estimation, (10) 315*a*.
surface states, comparison with quartz and silicic acid, (10) 319*j*.

Crucibles. See *Refractories*.

Crushing. See also *Crushing apparatus; Mills*.
efficiency in relation to operational variables and material constants, (7) 211*e*.
resistant, alumina particles, produ tion, P (7) 215*f*.
size reduction, literature review, (8) 247*c*.

Crushing apparatus. See also *Mills*.
bowl adjustment for, P (11) 349*f*.
and drying, P (1) 25*j*.
feeders for, P (8) 251*b*.
gyratory, fluid pressure operated adjustment and release for, P (11) 349*h*.
hydraulic release for, P (11) 349*i*.
liner, P (3) 78*b*.
spiderless, with frictionless bearings, P (8) 251*i*.
spiderless with relief valve system, P (6) 183*e*.
suspended-spindle, with means to adjust spindle, P (1) 26*b*.
jaw, P (4) 105*h*; P (8) 251*a*.
jaw, high frequency hydraulic actuated, P (9) 279*d*.
pulverizer, P (1) 26*c*.
for stone, coal, ore and other solid materials, P (5) 148*b*.

Cryolite, melting point, (3) 83*a*.

Crystalline materials, poly-, ceramics, method of treating for polarizing, P (5) 142*h*.
production, P (7) 215*f*.
relation of lattice energy and grinding properties of, (7) 211*f*.
vitreous, based on slags, effect of heat treatment on phase composition and microstructure of, (11) 333*e*.

Crystallization, anomaly, of B_2O_3, effect of high pressure, (1) 28*g*.
of Sb compounds in glasses and enamels, (1) 3*j*.
of B_2O_3, effect of high pressure, (1) 28*g*.
of calcium hydrosilicates in presence of gypsum and aluminum oxide, (2) 36*j*.
continuous isothermal, of semiconductor glasses by measurement of electrical conductivity, (9) 264*e*.
of corundum, from cryolite molten solutions, (5) 150*f*.
effect on properties of acid resistant vitreous crystalline enamel, (11) 332*g*.
electrochemical, of calcite, (2) 58*d*.
of glass, initial stages, study by Moessbauer effect, (8) 234*i*.
of glasses, containing BaO and TiO_2, (8) 230*e*.
high-lead, (6) 169*d*.
Li_2SiO_3, kinetics, (8) 232*e*.
in MgO-Al_2O_3-SiO_2 system, forming and recrystallization of quartz-like phases during, (6) 185*j*.
multicomponent ferruginous, study by infrared spectroscopy, (10) 299*b*.
in Se-Ge system, (3) 63*i*.
in Na_2O-TiO_2-SiO_2 system, (6) 168*h*.
SnO-SiO_2, (1) 5*j*.
ZnS-doped Na_2O-CaO-MgO-Al_2O_3-SiO_2, (1) 7*f*.
of graphite and diamond, (11) 351*f*.
of high-alumina fused-cast products, (7) 201*a*.
of highly refractory glass-ceramic fiber, acceleration by salt treatment, (8) 230*c*.
isomorphous, of strontium and lead sulfates from solutions, for removal of lead from TiO_2, (7) 203*a*.
kinetics, of internally nucleated vitreous silica, (9) 280*b*.
kinetics, of sodium disilicate, (1) 27*i*.
literature review, (8) 246*j*.
of lithium disilicate from Li_2O-SiO_2 glasses, (5) 126*j*.
of MgO, in fused calcium aluminates, conditions for, (6) 164*d*.
of magnetic oxides in rutile structure, (11) 354*j*.
micro-, of glass in system MgO-Al_2O_3-SiO_2, effect of TiO_2, (6) 160*f*.

Crystallization (*continued*)
monomineral, of melted basalts, (11) 338*a*.
products, of lithium aluminosilicate glasses, (8) 230*j*.
of anodic alumina films, (4) 115*d*.
re-, influence of finely dispersed second phase on, (10) 322*c*.
review, (10) 319*d*.
of TiO_2 films, amorphous, prepared by vacuum evaporation, (7) 216*b*.
in vitreous crystalline enamels, infrared spectroscopy, (8) 229*h*.
of zirconium silicate, in glazes during firing, (3) 70*b*.
of composition $Fe_xGa_{1-x}O_3$ with polarized neutrons, (8) 252*g*.

Crystallography, computer program, for determining optical parameters and optical and crystallographic directions, (5) 144*j*.
of composition $Fe_2Ga_{2-x}O_3$ with polarized neutrons, (8) 252*g*.
of ferrimagnetic calcium ferrites containing tri- or tetravalent metal ions, (11) 354*h*.
of ferrimagnetic garnets containing F_2 (8) 255*a*.
low temperature, of $LaCoO_3$, (2) 49*g*.
of mixed manganite spinels, (8) 252*e*.
properties, of MnBi studied by neutron diffraction, (5) 138*h*.
X-ray, for determination of surface area of zeolites, (11) 357*g*.
of inorganic materials, (8) 248*f*.
and optical, data for Na_2ZrO_3, (11) 358*b*.

Crystals. See also specific kinds.
alkali halide, magneto-optical properties of defect centers in, (9) 284*j*.
alkali halide, pressure dependence of dislocation mobility in, (4) 114*c*.
AlAs-GaAs mixed, preparation and properties, (7) 207*i*.
Al_2O_3, grown by vapor deposition, morphological development, (5) 155*c*.
azide, mechanism of uptake of impurities by, (7) 219*a*.
$BaFe_{12}O_{19}$ and $SrFe_{12}O_{19}$, thin, thickness dependence of domain width in, (3) 88*f*.
$BaTiO_3$, decoration techniques for revealing antiparallel 180° domains in, (8) 255*h*.
Gd^{3+} doped, grown in molten KF, resistivity of, (10) 325*c*.
and WO_3, birefringence, (3) 79*b*.
behavior, in far infrared (40 to 1500 μ) absorption at liquid helium temperature, (5) 127*d*.
CdF_2-CaF_2, doped, electrical and optical studies, (5) 151*d*.
cadmium sulfide, plastically bent, luminescence from, (5) 154*j*.
photoconductivity, (5) 156*j*.
production, P (1) 26*b*.
$CdWO_4$, $ZnWO_4$, and $MgWO_4$, ESR of Cu^{2+} ion in, (7) 217*g*.
of cadmium and zinc chalcogenides, highly pure hexagonal, production by sublimation, P (4) 101*b*.
calcite, growth from molten flux by slow cooling, P (1) 25*c*.
calcite, study of cross bands and twinning dislocations in, (7) 222*f*.
$CaSO_4 \cdot 1/2H_2O$, α-, in water, microscopic study of dissolution, (1) 30*g*.
calcium tungstate, iron-59 doped, Czochralski growth, (4) 107*j*.
carbon, synthesis, P (8) 251*j*.
cholesteric liquid, and application to thermal nondestructive testing, (7) 211*j*.
copper, deformed, recovery and recrystallization, effect of dispersed silica particles on, (10) 319*g*.
copper-silica, recrystallization in, (10) 325*b*.
corundum, vanadium-doped, high-temperature magnetic susceptibilities and trigonal-field splitting, (5) 138*c*.
corundum, vanadium-doped, trigonal-field splitting, (5) 138*e*.
crystalline field studies, by perturbed angular correlation, apparatus for, (5) 144*h*.
crystalline fields in corundum-type lattices, (6) 184*h*.
crystalline swelling, in sodium and potassium montmorillonite, hysteresis in, (6) 186*j*.
crystallite growth of BeO powders and inhibition by adsorbed phosphate, (10) 319*c*.
crystallite size distribution, determination by X-ray diffraction and electron microscopy, (3) 75*f*.
cubic, tracer diffusion by divacancy and impurity-vacancy pairs in, (9) 286*b*.
data, for $Na_2Ca_2Si_2O_7$, (2) 57*g*.
defect clusters, small, in irradiated MgO, (11) 357*j*.
dendritic, continuous, method of angularly pulling, P (6) 190*h*.
dielectric, temperature and frequency dependence of sound velocity in, (8) 257*c*.
diethyl phthalate, heat capacities and related thermal data to 360°K, (4) 110*j*.
dislocations. See *Dislocations*.
divalent rare earth laser, method of making in electric field, P (10) 310*i*.
ductile and brittle, (1) 28*c*.
elastic anisotropy, (2) 58*c*.
epitaxial, device for manufacturing, P (8) 244*h*.
epitaxial dielectric MgO, P (9) 272*i*.
ferroelectric, Curie temperature, influence of impurities on, (9) 283*b*.
-field, effects in $CoCl_2 \cdot 6H_2O$, (9) 280*b*.
splitting, of trivalent thulium and erbium J levels in yttrium oxide, (7) 216*j*.
studies, of excited states of trivalent neodymium in YGaG and YAG, (7) 216*a*.
term symbols for Nd^{3+} in $CaWO_4$, (10) 319*a*.
theory, for ground manifold of chromium in rutile, (10) 324*f*.

Crystals (*continued*)
field, for Yb^{3+} in garnets, (5) 150*i*.
fields, of Cr_2O_3 and ruby, comparison with optical spectra, (5) 150*e*.
formation. See *Crystallization*.
forming from $A^{III}B^{V}$ compounds, (11) 344*e*.
growth, arc melting, for high temperature verneuil process, (3) 81*d*.
of BaP, (4) 117*j*.
contamination-nucleated, at bubble surfaces in glass, (1) 5*g*.
of CrO_2, (1) 27*a*.
of cubic boron nitride, factors affecting, (7) 217*d*.
of GaAs, (7) 207*d*.
in GaAs-Sn system, (3) 81*a*.
high temperature-moderate pressure, simple apparatus for, (1) 23*b*.
kinetics, (5) 154*e*.
of Mn-Zn ferrite, (8) 252*c*.
from melt, determination of temperature field around, (6) 181*h*.
patterns on surface of alumina grown by chemical vapor deposition, (10) 321*c*.
of SiC by vapor phase reaction at high temperature, (11) 353*e*.
by traveling solvent method, removal of dislocations in, (11) 356*f*.
twinning, kinetic considerations in genesis of, (5) 154*d*.
vapor-liquid-solid, technique, P (1) 19*d*.
by verneuil method, above 2200°C: II, (1) 27*c*.
verneuil, high temperature, by arc melting, (3) 81*d*.
verneuil, plasma heat transfer in, (2) 59*a*.
of YIG, P (9) 273*c*.
high perfection, process for growing, P (5) 150*j*.
Ho-doped, infrared quantum counter action in, (11) 353*e*.
homogeneities, correlation with laser performance, of ruby laser rods, (8) 252*i*.
homogeneous mixed, of zinc cadmium sulfide, growth, (1) 29*g*.
homogeneously doped, of semiconductor material, processes for manufacture, P (2) 52*h*.
hydrogen and potassium chloride, doped with nitrite and nitrate, reaction between, (3) 85*i*.
In_2O_3, grown from PbO-B_2O_3 melts, habit changes and growth mechanisms, (10) 321*f*.
ionic, displacements and polarization caused by point defects in, (1) 28*b*.
electric resonance of rotating dipoles in, (10) 320*h*.
entropy of vacancies in, (9) 282*e*.
intrinsic surface states on, theory and observation, (9) 287*i*.
LiF and MgO, temperature dependence of infrared dispersion in, (11) 357*b*.
particularly LiF, plastic deformation, electric charge during, (7) 222*g*.
slab including retardation, optical modes of vibration in: I, nonradiative region, (9) 285*f*.
surface phenomena and diffusion mechanism of defects movement in, (6) 189*e*.
thermodynamics of Soret effect in, (3) 88*a*.
thermoelectric power, (2) 50*i*.
with zinc blende and wurtzite structures, spin-orbit coupling in, (3) 86*i*.
lathanide oxide, spectrum of Nd^{3+} in, (11) 357*a*.
laser-induced damage in, (4) 112*j*.
lattice, of clay minerals, formation of water in, and dehydration, (7) 215*h*.
contractions associated with neutron irradiation of self-bonded SiC, (8) 254*e*.
dynamics of thallous bromide, (9) 283*g*.
fcc, point-defect calculations for, (10) 324*j*.
on level with atomic dimension, electron microscopic observation, (5) 152*a*.
perovskite $BaTiO_3$, hydroxyl as defect of, (10) 322*a*.
spinel B-site, magnetic stuctures in, (10) 323*a*.
super-, interstitial, of Ti_6O and transformation, (10) 322*g*.
vacancies, in molybdenite, detection, (11) 351*j*.
vibrations of BeO, (8) 254*f*.
waves, low frequency transverse optic, of barium titanate, (4) 117*j*.
lattice parameters, detection of changes around interface in transformation, (2) 54*c*.
of Al_2O_3, effect of high pressure on, (6) 185*g*.
of Cr_2O_3 and α-Fe_2O_3, effect of high pressure on, (10) 319*k*.
of β-cristobalite, (3) 87*a*; discussion and reply, (6) 185*f*.
of diamond, graphite, and hexagonal boron nitride, effect of high pressure, (7) 217*c*.
of oxides and sulfides as function of pressure, (7) 219*c*.
lithium fluoride, proton bombarded, negative electrolytic breakdown in, (10) 323*h*.
lithium metasilicate, effects of colloidal gold and K_2O on formation in photo-sensitive opal glass, (1) 5*h*.
lithium niobate, growth, P (1) 18*a*.
$M_{1-x}^{2+}Li_xM^{4+}O_{3-x}F_x$, crystal chemistry, (5) 150*k*.
Mg-Al spinel, Czochralski growth, (7) 216*d*.
MgO, bulk versus surface conductivity of, (5) 149*i*.
MgO, toughness, effect of water, (7) 217*f*.
MnO, cohesive energy, (3) 79*k*.
-melt interface, temperature, (2) 58*e*.
modifications, of binary systems containing zirconia molten and sprayed by arc-plasma, (11) 351*b*.
mono-. See *Crystals, single*.
monoclinic centro-symmetrical, structure, refinement by least squares method for NE 8033 computer, (11) 342*d*.

Crystals (*continued*)
NiO, MnO, and CoO, electron distribution of ions, in, (3) 80*d*.
NiO-type, antiferromagnetic domain walls, spin configuration in, (4) 116*d*.
nonmetallic, heat conduction in, (2) 58*a*.
nuclei, breeding, (3) 79*c*.
one-dimensional, mixed layer minerals as, (7) 219*a*.
optical, wire-saw cutting technique, (1) 23*g*.
optics, varioscopic microscopy in, (7) 212*f*.
orientation, dependence of X-ray production in bulk specimens, (8) 248*a*.
grain, determination by comparing sputtered patterns, P (11) 348*b*.
indicatrix, and 2V, determination with spindle stage, (1) 21*b*.
orienting, by alternate application of angularly spaced magnetic fields, P (7) 213*a*.
parameter, relation with anion-cation distances in compounds with perovskite structure, (6) 188*h*.
plates, rotated Y-cut rectangular piezoelectric quartz, P (7) 210*e*.
poly-, in materials characterization, B (8) 259*a*.
potassium bromide, V centers in, (8) 258*b*.
potassium chloride, polarization in, (6) 187*h*.
potassium tantalate-niobate, characterization by electrooptic measurements, (1) 26*k*.
of rare earth chalcogenides, P (6) 178*c*.
rare earth orthosilicates and orthogermanates, preparation, (7) 219*a*.
rare-earth vanadate, RVO_4, flux growth of, (10) 321*h*.
refractory, growth processes in high frequency plasma torches, (5) 146*a*.
ruby, grown by Czochralski technique, (11) 350*g*.
ruby laser, optical properties and laser thresholds, (5) 139*d*.
semiconductor, P (5) 142*f*.
apparatus for pulling, P (1) 17*i*.
bulk, voltage induced by electron beam in, (8) 258*b*.
pulling nozzle for oriented pulling of, P (10) 311*k*.
silicon, vapor growth, apparatus for producing, P (6) 177*a*.
silicon and Ge, method of growing, P (4) 100*j*.
SiC, α-, growth from various chromium alloys by traveling solvent method, (4) 110*i*.
silicon carbide, β-, method of seed-pulling from melt containing Ag, and product, P (3) 73*e*.
silver halide, permanent photoinduced conductivity in, (10) 324*h*.
single, α-Al_2O_3 substrate, growth on, (10) 325*g*.
$BaAl_2O_4$, (6) 188*c*.
barium titanate, elastic properties above Curie point, (5) 151*b*.
barium titanate, growth by modified Remeika technique, (1) 29*f*.
$BaTiO_3$, PTCR effect in, (5) 157*j*.
$Ba_2Zn_2Fe_{12}O_{22}$, growing, P (8) 245*h*.
BeO, growth and properties, (3) 67*g*.
BeO, irradiated comparison of microscopic and X-ray growth, (2) 43*k*.
$Bi_4Ti_3O_{12}$, crystal symmetry, optical properties, and ferroelectric polarization, (3) 70*f*.
$Cd_{1-x}Ca_xF_2$:In^{3+}, semiconductivity in, (1) 16*h*.
CdS, copper-doped, kinetics of optical charge exchange in, (8) 254*d*.
CdS, resistivity homogeneity, effect of sulfur annealing pressure on, (11) 352*e*.
CdS, surface states on, (5) 158*j*.
calcite, synthetic, growth, (5) 153*d*.
$CaMoO_4$, elastic constants, (7) 217*f*.
calcium orthovanadate, growth, (11) 342*h*.
CeO_2 and ThO_2, growth and properties, (8) 254*d*.
CsCl, self-diffusion and ionic conductivity in, (8) 256*i*.
containing rare earth elements, spectral properties, (6) 188*j*.
CoO, neutron-diffraction investigation, (8) 255*g*.
$CuCl_2 \cdot 2H_2O$, paramagnetic, calculation of electric-field-gradient tensor for, (11) 350*d*.
corundum, preparation by electron-beam zone melting, (9) 272*g*.
cuprous oxide, production by melt, (11) 355*e*.
depositing on amorphous film, P (6) 177*j*.
dimolybdenum carbide, dislocation etch pits and phase relations in, (9) 281*d*.
ferromagnetic, transparent, method of preparing, P (7) 209*b*.
high melting, preparation by flux method, (1) 31*i*.
homogeneous, vapor growing, P (10) 310*j*.
impurity distributions in: I, impurity striations in nonrotated InSb crystals, (10) 322*b*.
$Fe_{1.75}Ge$, neutron diffraction study, (5) 155*c*.
α-Fe_2O_3, epitaxially grown, vacancy ordering in, (10) 327*c*.
lanthanum fluoride, exposing dislocations in, (10) 321*d*.
$(Pb_xSr_{1-x})TiO_3$, grown by traveling heater method, (8) 243*c*.
magnesiowustite, oxidation, dependence on temperature, oxygen pressure and crystal composition, (1) 30*h*.
magnesium aluminate, pink, growth, (11) 353*i*.
manganese ferrite, thermal conductivity at low temperatures, (5) 159*b*.
metal oxide, epitaxially growing, P (5) 147*a*.
method for growing, P (2) 51*j*.
NH_4Br and NH_4Cl, V_K center in, (8) 258*a*.
orientation, binocular microscope for, (1) 23*a*.
oriented, preparation, P (9) 274*e*.
oxides MO_3, preparation, (7) 220*e*.
KH_2PO_4-type, thermal conductivity, (7) 222*d*.

Crystals (*continued*)
KTN, constant temperature method for growth, (1) 27*f*.
production, purification of materials in, P (9) 274*g*.
sapphire, growth, (8) 257*a*.
semiconductor, method of producing epitaxial layers on, P (1) 18*h*.
silicon, dislocation-free, P (11) 345*d*.
silicon, pulled by eccentric seeding method, (5) 139*j*.
silicon, for semiconductor, apparatus and method for producing, P (6) 177*a*.
single phase, UO_2, in O/U range 2 to 2.25, preparation, (5) 133*g*.
of slightly soluble substances, method and apparatus for growing, P (6) 190*h*.
NaCl, Schottky disorder and lattice relaxation due to X irradiation at room temperature, (11) 356*j*.
strontium fluoride and barium fluoride, sublimation, Langmuir studies, (11) 354*d*.
thoria, grown by vapor deposition in solar furnace, (8) 258*e*.
SnTe and GeTe, growth, (10) 325*h*.
TiC, microstructure, (8) 255*e*.
Ti_2O_3, growth from melt, (1) 29*j*.
uranium carbide, high carbon hyperstoichiometric, structure, (4) 116*c*.
δ-U_3O_8, (4) 107*d*.
uranium monocarbide, oriented growth of oxidation products on, (10) 324*c*.
vanadium dioxide, method of growing, P (7) 214*g*.
vanadium oxide, grown by oxychloride decomposition, growth and electrical properties, (7) 217*h*.
Y_2O_3 and LaF_3, rare earth doped, optical absorption and fluorescence intensities in, (10) 324*b*.
ZnO, optical and electrical properties of, (3) 84*f*.
ZnO, vapor reaction growth, (5) 159*h*.
$ZnRh_2O_4$, growth, (6) 186*b*.
$ZnWO_4$, spin-lattice relaxation of Rh(II) in, (10) 325*a*.
small, identification by X-ray diffraction analysis, (1) 23*a*.
small, interferometric method for measuring principal indices of, (3) 75*e*.
with NaCl or CsCl structure, compressibilities, effect of high pressures, (7) 217*c*.
NaCl, potential differences produced by plastic deformation at 4.2°K, (4) 114*i*.
NaCl, use as standard measure of microhardness, (10) 216*d*.
structure, of $ATiNbO_6$, $ATiTaO_6$, and $ATiSbO_6$, (1) 27*c*.
of β-BeO, (3) 67*a*.
of $Cd_2V_2O_7$, (5) 150*j*.
CrOOH, new polymorph of, (6) 184*e*.
of clinker, influence on grindability, fraction distribution of minerals, and properties of cement, (6) 165*a*.
of cordierite, low, (2) 59*a*.
of dawsonite $NaAl(CO_3)(OH)_2$, (4) 107*e*.
of disodium dimolybdate, refinement, (5) 157*i*.
of $DyMn_2O_5$ paramagnetic, at 298°K, (11) 251*e*.
of fluoride derivative of $12CaO \cdot 7Al_2O_3$, (10) 319*a*.
of high pressure phase of $CaSi_2$, (8) 252*d*.
of lanthanide gallium borates, (5) 150*b*.
of lanthanum telluride and tellurium-deficient neodymium telluride, (5) 150*b*.
of α-$LiAlO_2$, (7) 218*a*.
of lithium and sodium ferrites and aluminates, (6) 183*h*.
of $LiUO_3$, (5) 150*c*.
of $MO_3 \cdot 3R_2O_3$ compounds rhombohedral, and relation to ordered R_7O_{12} phases, (5) 150*d*.
of α-$MnMoO_4$, paramagnetic, (11) 351*e*.
and melting, (5) 154*f*.
and method of fabricating, P (11) 343*j*.
of neodymium tritelluride, (6) 184*c*.
of Ni_3B, *o*-Ni_4B_3, and *m*-Ni_4B_3, refinements (7), 216*a*.
of Ni_2TeO_4, (1) 27*d*.
and orientation, in deposits of metals on mica, (10) 308*h*.
of oxysulfides of rare earths, $Ln_2O_2S_2$, (1) 27*e*.
of piezoelectric ferromagnetic gallium iron oxide, (5) 137*g*.
of potassium and cesium trivanadates, (6) 184*h*.
of rare earth and yttrium oxybromides, (4) 107*e*.
of $RbCoCl_3$ and Rb_3CoCl_5, (5) 150*e*.
of $RbLiF_2$ and $CsLiF_2$, (4) 107*i*.
of tetragonal ruthenium dioxide, (5) 150*j*.
of Sm_3Ge_4, (2) 57*g*.
of scandium oxide, refinement, (11) 356*b*.
of scandium sesquioxide, refinement, (8) 256*d*.
of scandium sesquitelluride, (4) 107*g*.
of $Sc_2(WO_4)_3$, diamagnetic, (11) 351*e*.
of SiC film on silicon substrate, (11) 352*d*.
of SiC 14H, (10) 319*a*.
spherulite growth, kinetics, in silicate glass, (8) 232*i*.
spherulites formation, in silicate glasses, (8) 231*i*.
of technetium(IV) chloride, new AB_4 structure, (6) 184*e*.
of orthorhombic TeO_2, refinement, (8) 256*c*.
of Y_2BeO_4, (6) 184*f*.
of $Y(OH)_3$, (7) 218*g*.
of α-$ZnMoO_4$, diamagnetic, (11) 351*e*.

Crystals (*continued*)
ZnO, hydrothermal growth with ammonium ion additives, P (3) 72*i*.
ZnO, low carrier concentration, hydrothermal growth at high water and hydrogen pressures, (4) 111*a*.
zinc silicate, α-, manganese-doped, ESR study, (11) 352*g*.
zinc sulfide, cubic, growing in molten salt solvent, P (6) 183*c*.
ZnTe, photoconductivity, (5) 156*j*.
(Zn,Hg)Te and Ga(P,As), solution growth, (10) 308*j*.
Curing, cement and asbestos articles, P (3) 69*a*.
preliminary, effect on structure development of steamed specimens from clinker minerals, (6) 164*d*.
Currents, eddy, instrument, phase sensitive, applications, (7) 211*i*.
electric, use in glass melting, (1) 8*g*.
nonohmic, transport phenomena, in high-resistivity GaAs, (3) 83*j*.
space-charge-limited, in heteroepitaxial films of silicon grown on sapphire, (5) 158*g*.
space-charge-limited ionic, in silicon dioxide films, (1) 17*a*.
thermally stimulated, in semi-insulating GaAs, effect of illumination time on, (3) 80*e*.
Cutting, wire-saw, for optical crystals, (1) 23*g*.
Cutting tools. See *Tools*
Cyclones. See *Classifiers; Separators.*

Data storage, electronic processing of prehistoric ceramics, (1) 2*b*.
magnetic devices, method of making, P (10) 310*e*.
memories, laminated ferrite, (11) 342*j*.
memory, laminated-ferrite, MOS-transistor-driven, (11) 342*a*.
memory core, magnetic, manufacture, P (6) 178*h*.
lithium-nickel-manganese ferrite magnetic, manufacture, P (6) 178*g*.
material, lithium magnesium ferrite, P (5) 141*c*.
of vanadium-containing lithium ferrites, P (6) 179*a*.
memory element, adaptive, P (11) 343*c*.
memory elements, thin-ferromagnetic-film, method of making, P (10) 310*c*.
Debye-Waller factor, of ^{129}I in alkali iodides, (9) 280*c*.
Decals. See *Decoration.*
Decomposition, of aluminum nitrate nonahydrate, P (5) 135*h*.
of $CaCO_3$, effect of impurities, (4) 108*b*.
of $CaCO_3$, measurement of kinetics with recording thermobalance, (2) 58*g*.
high-pressure, of synthetic garnets, (10) 321*h*.
spinodal, in multicomponent system, thermodynamic conditions for, (6) 190*f*.
spinodal, in system TiO_2-SnO_2, (6) 189*b*.
thermal, of alkali metal sulfates, mass spectrometric studies at high temperatures, (11) 354*c*.
of cadmium hydroxide, (11) 357*e*.
of complex oxalates of iron(II), study using Moessbauer effect, (5) 158*g*.
of dolomite and ankerite, (9) 287*j*.
of ferrous oxalate dihydrate, (4) 117*j*; (5) 159*b*.
of ferrous oxalate dihydrate, influence of atmosphere, (5) 153*b*.
kinetics and mechanism: I, of kaolinite, temperature and vapor dependence, (5) 154*f*.
of metal salts, for preparation of mixed metal oxides, P (7) 214*j*.
of methylchlorosilane vapor, for production of silicon carbide, (1) 12*a*.
of neodymium oxalate, and changes in surface areas of products, (4) 117*j*.
of SnO-SiO_2 glasses, (1) 5*j*.
of titanium-bearing ores, P (11) 349*g*.
of tricalcium silicate with boric oxide, (7) 194*e*.
of zircon sand, P (9) 279*a*.
Decoration. See also *Art and artware; Color; Engobes; Glazes.*
of bathroom suites at Fourth Spanish Fair, (10) 327*j*.
of glass, customer standards and quality of plain ware, (10) 297*f*.
by James Giles, (4) 91*f*.
material handling pointers, (10) 298*c*.
materials, application, and firing, (10) 299*h*.
and glazing of ceramic tile, P (5) 137*c*.
gold, compositions and method, P (10) 312*c*.
metallic lusters, (9) 270*j*.
photographic process, P (5) 137*b*.
on porcelain surfaces, measurement of damage, (9) 276*b*.
of pottery, with silk screen, P (9) 271*h*.
special, application with spray gun, (8) 247*a*.
transfers, ceramic, P (2) 49*b*.
De-enameling. See *Enameling.*
Defects. See also *Crystals; Enameling; Enamels; Glass; Structure.*
distribution, on glass surface, theoretical and experimental investigation, (1) 8*a*.
equilibria, in cubic high temperature copper sulfide, (6) 184*i*.
internal, in chalcogenide glasses, examination by infrared defectoscopy methods, (6) 167*e*.
in materials characterization, B (8) 259*a*.
movement, in ionic crystals, surface phenomena and diffusion mechanism, (6) 189*e*.
point, in special positions held by trapping center of noncubic symmetry, jump rates for, (11) 353*j*.

Defects (*continued*)
in pottery and building materials, analysis by electron probe microanalyzer, (6) 180*a*.
in sodium bromate, nuclear-spin pumping study of, (9) 284*j*.
weakening, in glass, (1) 8*h*.
Deflocculants. See also *Electrolytes*.
uses in slips and spray drying, (10) 305*e*.
Deflocculation. See *Dispersion*.
Deformation, of autoclave hardened lime-sand concrete, (1) 2*c*.
of cement stone and sand concrete during freezing, (5) 124*h*.
characteristics, of nuclear grade graphite, (7) 201*c*.
during dehydroxylation of $Ca(OH)_2$ and $Mg(OH)_2$ (4) 107*a*.
of flexible sandstone, quantitative microstructural study, (8) 257*g*.
grain, in extruded polycrystalline BeO ceramics, (7) 221*f*.
plastic, of cuprous oxide, (3) 85*a*.
of diamond, birefringence, X-ray topography, and electron microscope examination, (1) 26*j*.
effect on anodic dissolution of iron in acids, (7) 195*b*.
effect on physicomechanical properties of WC-Co hard alloys, (5) 132*a*.
of galena (lead sulfide), (10) 324*j*.
of glass-ceramic, (8) 233*c*.
high-temperature, in pyrolytic carbons, mechanisms of, (4) 113*b*.
of ionic crystals, electric charge during, (7) 222*g*.
potential difference produced by, in NaCl, (4) 114*i*.
of quartz at atmospheric pressure, (4) 114*g*.
of Yule marble, mechanism for, (4) 113*a*.
Dehumidifiers. See *Dryers*.
Dehydration, clay-mineral, (7) 212*a*.
of crystal hydrates of double substituted magnesium phosphate, (4) 107*c*.
of gibbsite, and formation of boehmite, (2) 57*j*.
of gypsum, (6) 164*f*.
of magnesium chloride, P (1) 25*j*.
of magnesium chloride using gaseous ammonia, P (1) 25*a*.
of $MgSO_4 \cdot 7H_2O$, determination of thermal effects in, (4) 107*i*.
Dehydroxylation. See *Decomposition, thermal*.
Delay line, with thermoelectric generator responsive to rate of heat transfer, P (11) 343*b*.
Dendrites, apparatus for producing, P (1) 17*i*.
thickness, varying by addition of impurity to control growth in (111) direction, P (11) 344*f*.
Densification, of B_2O_3, effect of high pressure, (1) 28*g*.
during sintering of ZnO, (10) 325*i*.
effect on keramzit concrete deformation, (1) 2*c*.
of glass, under cutting wheel, (6) 166*j*.
of ionic solids by cold-pressing at ultrahigh pressures, (11) 351*h*.
of MgO in presence of liquid phase, (4) 107*f*.
permanent, of B_2O_3 glass by hydrostatic and nonhydrostatic pressures up to 55 kbars and 140°C, (1) 6*e*.
of pressure-sintered GaSb-GaAs alloys, (4) 99*g*.
of refractory compound powders, study by electrical conductivity method, (8) 240*a*.
of refractory compounds, P (1) 12*a*.
role in deformation of glasses under point loading, (11) 335*c*.
studies, on BeO powders, (3) 68*c*.
of tantalum mononitride-titanium diboride, (8) 237*c*.
Density, of alkali metal nitrate melts, (11) 352*h*.
apparatus and method for determining, P (4) 103*f*.
apparent, of granular ceramic raw and finished materials, determination, (1) 21*a*.
apparent, of solid bodies, rapid determination, (10) 315*d*.
bulk, of ceramic materials, (10) 313*g*.
of ceramic and cementitious materials, Eliott instrument for measuring, (5) 145*d*.
decrease during final stage of sintering of ZnO, (10) 325*i*.
determination, high precision, by hydrostatic weighing, (2) 54*g*.
fluidic measurement, (8) 248*g*.
of glasses, relation with refractive index, resulting from annealing compared with corresponding relation resulting from compression, (9) 264*f*.
of hot-pressed beryllium oxide, effect of adsorbed sulfate and fluoride, (1) 28*g*.
impurity, of electrical conductivity, logarithmic dependence on, (10) 322*d*.
of iron oxide-silica melts, (4) 107*g*.
of lithium aluminosilicate glasses, (8) 240*j*.
of material, apparatus with means to measure, P (3) 76*c*.
of microsize spherical particles, method for determining, (4) 103*b*.
of minerals, determination by micropycnometer, (1) 22*b*.
of mixed alkali silicate glasses, (3) 64*h*.
of powdered solids, apparatus for increasing, P (7) 214*h*.
of pyrolytic-carbon coatings, determination by microradiographic technique, (1) 22*c*.
silica, statistical method for checking, (9) 277*f*.
of states in metal-semiconductor tunneling, (2) 49*f*.
surface charge, of silicon-silicon dioxide interface, effect of metal-semiconductor work function difference on calculation, (5) 151*j*.
of thin Ta_2O_5 films, (3) 70*j*.
unpaired-electron, in $CoPt_3$, (9) 284*e*.
Dental ceramics, alumina tube post crown, (9) 270*h*.
high-alumina, for bridge pontic construction, (9) 270*j*.
porcelain, chemically bonding to synthetic resin base materials and resulting prosthetic appliance, P (5) 137*c*.
porcelain teeth, with new holding structure, P (5) 137*d*.
prophylactic paste compositions, with $ZrSiO_4$ and SnO_2, (7) 193*i*.
Deposition, of alumina from vapor phase, (6) 172*g*.
apparatus, spiral vacuum, and method, P (9) 275*c*.
calcium carbonate scale, on heat-transfer surfaces, (5) 147*e*.
chamber, for manufacture of refractory coated filaments, P (5) 134*h*.
chemical, of metals in production of metal film resistors, (10) 306*i*.
chemical vapor, of epitaxial YIG on YAG and epitaxial GdIG on YAG, (5) 150*a*.
for formation of silicon and titanium carbides, (3) 81*f*; correction, (7) 217*g*.
of hafnium carbide, (10) 306*j*.
I, SiC coatings by vapor phase reaction at high temperature; II, crystal growth of SiC by vapor phase reaction at high temperature, (11) 353*d*.
for uniform silicon coatings on graphite, (2) 38*c*.
controlled, of polycrystalline films in vacuum, means for, P (6) 177*h*.
controlled, of thin conductive layer, method and apparatus, P (6) 177*h*.
of electroconductive transparent indium oxide coating, P (3) 73*e*.
electro-, of iridium from fused sodium cyanide and aqueous electrolytes, (2) 44*f*.
for porcelain enamel, (10) 296*d*.
of thick platinum and palladium coatings on refractory metals from aqueous electrolytes, (2) 37*j*.
epitaxial, for forming semiconductor device, P (1) 18*a*.
of semiconductor materials, P (1) 17*h*.
of silicon on alpha-alumina, P (10) 309*d*.
gas-phase, of insulating films, B (8) 260*e*.
gaseous, method of making thermocouple probe, P (1) 23*i*.
of material on filament from ionized coating material, apparatus for, P (9) 275*e*.
of nickel by displacement reactions, (9) 262*i*.
oxide, in silicon epitaxial systems, (4) 99*b*.
of semiconducting material from gas phase, P (2) 50*j*.
of silica films on germanium by carbon dioxide process, (7) 207*d*.
of silicon on sapphire in ultrahigh vacuum, (10) 306*j*.
thin film, by cathode sputtering, B (8) 260*e*.
factors influencing accuracy of quartz-crystal oscillator as thickness monitor for, (10) 307*h*.
method and apparatus of controlling in vacuum, P (8) 245*c*.
vacuum, survey of techniques, (2) 50*b*.
of thin layer of very pure brittle material in form, P (2) 52*d*.
vacuum, of single-crystalline silicon on sapphire, (10) 309*e*.
vapor, apparatus including centrifugal force substrate-holding means, P (8) 247*h*.
of GaAs on germanium, (8) 242*j*.
method and apparatus for employing electron beam, P (1) 18*j*.
for preparing crystalline Al borides, (2) 45*i*.
of pyrolytic graphite on tungsten, P (7) 195*f*.
of vapor-deposited silicon carbide, (9) 267*c*.
Desiccants, silica gel, process for producing, P (4) 105*e*.
Design. See also *Art and artware; Decoration*.
of Alberecht Klauer-Simonis, (4) 91*h*.
of enameled cast-iron bath, (2) 35*i*.
in high rise load bearing brickwork, (9) 266*c*.
of plumbing fixtures, (1) 2*b*.
Desorption, of He and $^{14}CO_2$ from micas, (3) 79*i*.
thermal, of argon ionically pumped into glass, (8) 258*a*.
Detectors. See also *Tubes, electron*.
activated tungsten oxide gas, (11) 350*e*.
charged particle, with lithium compensated intrinsic silicon as intermediate region, P (11) 343*g*.
far infrared, preparation of doped germanium for, (7) 207*g*.
ferromagnetic, (10) 307*a*.
high-resolution semiconductor, application in X-ray emission spectrography, (5) 144*i*.
high speed ultraviolet, for thin spots, P (1) 9*e*.
housings, infrared, glass technology applied to, (3) 63*j*.
InSb MOS infrared, (4) 111*g*.
infrared radiation, black pigment for blackening, P (4) 93*a*.
lead salt, B (8) 260*f*.
photo-, PbO, physical interpretation, (11) 355*a*.
pn junction semiconductor, by diffusion of phosphorus in silicon, (7) 216*f*.
scintillators, europium activated strontium iodide, P (6) 177*g*.
semiconductor, method and apparatus, P (8) 246*e*.
Devitrification, of iron-containing glass, characterization by electrical and magnetic properties, (6) 166*g*.
for making glass-ceramics in single stage, P (2) 41*h*.
of tin oxide films, doped and undoped, prepared by reactive sputtering, (4) 107*i*.
Dewatering. See *Water, removal*.
Dewetting. See *Wetting*.
Diamonds, abasion hardness and cleavage, effect of neutron irradiation, (2) 35*g*.
abrasive article, containing hexagonal crystalline boron nitride particles, P (8) 227*h*.
abrasive body, metal-bonded, P (3) 61*g*.
abrasive matrix, P (6) 163*i*.
in abrasive wheels. See *Grinding apparatus*.
bonding to molybdenum, P (7) 193*g*.
capsules, for temperature measurement, (8) 248*d*.
clean, polishes ruby laser rods, (6) 163*i*.
crystallization, (11) 351*f*.
cleavage, effect of neutron irradiation, (2) 35*g*.
cohesive energy, (4) 106*h*.
Compton profiles, (4) 107*a*.
covalent bond in, (9) 280*f*.
disks, synthetic, for cutting optically active material, (10) 293*f*.
etch pits and trigons on, (8) 253*g*.
growth process, P (6) 163*i*.
hardness at high temperature, measurement, (10) 323*e*.
heat-treated synthetic, electron spin resonance properties, (1) 32*f*.
hexagonal, new form of carbon, (11) 353*j*.
lapping powders, difference between synthetic and natural, (8) 227*f*.
lattice parameters, effect of high pressure, (7) 217*b*.
metal-clad, for steel grinding, (6) 163*i*.
metal coatings to, evaporative application, P (7) 193*j*.
natural, of dodecahedral form, (8) 257*g*.
natural and synthetic, and North American outlook, (7) 220*a*.
phonon interactions, piezooptical properties, and interrelation of N3 and N9 absorption-emission systems in, (8) 255*j*.
plastic deformation, birefringence, X-ray topography, and electron microscope examination, (1) 26*j*.
plates, type IIA, effect of neutron irradiation on plastic behavior of, (1) 28*i*.
preparation, graphite-catalyst charge element for, P (1) 1*h*.
purification, P (2) 35*h*.
reshaping, apparatus, P (6) 163*h*.
slip and screw dislocations in, (6) 188*c*.
synthesis, catalysts for, (5) 155*d*.
tooling, in glassworks increases production six times, (6) 167*g*.
as tools for machining ceramic parts, (2) 35*f*.
tools, manufacture by rolling powders, (6) 163*j*.
type I, irradiation damage in, (3) 82*e*.
wetting, temperature influence on adhesion of metals inert to carbon in, (7) 195*f*.
wheels, in carbide grinding, variables affecting, (8) 227*f*; (9) 261*h*.
wheels, for cutting structural glass, (8) 230*g*.
Diaspore, spontaneous formation in partially dehydrated single crystals of gibbsite, (3) 86*j*.
Dicalcium silicate. See *Calcium*.
Dielectrics. See also *Ferrites; Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials; Glass; Porcelain, electrical; Steatite; Titanates; Whiteware*.
anodic tantalum oxide, prepared from body-centered-cubic tantalum and beta-tantalum films, (3) 70*i*.
base, with glaze containing metal particles, P (6) 177*d*.
bodies, with conducting portions, P (9) 273*i*.
ceramic, P (1) 17*b*; P (2) 50*h*; P (4) 99*f*.
ceramics, electroding, composition and method, P (1) 17*d*.
characteristics, of compositions near field of primary crystallization of cordierite, (6) 176*f*.
composite dual, for isolation in integrated circuits, and method of making, P (8) 244*f*.
composition, bismuth-free barium titanate, P (5) 140*d*.
constant, in barium titanate, (5) 138*f*.
of GaAs, resonance behavior at microwave frequencies, (1) 16*e*.
optical, of barium titanate, contribution of grain boundary to, (11) 341*j*.
of SiO very thin films, (5) 150*i*.
of thin Ta_2O_5 films, (3) 79*j*.
of zirconia, (2) 58*a*.
crossover, thick-film, performance data, (7) 207*e*.
crystalline, with improved shear strength, method and apparatus for fabricating, P (11) 344*c*.
crystals, temperature and frequency dependence of sound velocity in, (8) 257*c*.
ferroelectrics relaxation, (9) 272*b*.
isolation process, P (10) 309*a*.
lamellated of mixed bismuth oxides, P (4) 100*e*.
layer technology, thin, using vacuum deposition with piezoelectric crystal rate control, (5) 140*f*.
loss, low temperature, in silica glass, influence of OH^- concentration and irradiation, (2) 58*b*.
members, thickness, apparatus for measuring, P (10) 316*h*.
new, solve 10 insulation problems, (3) 72*a*.
panels, method of making, P (10) 310*h*.
properties, in $BaTiO_3$-$BaSnO_3$ and $BaTiO_3$-$Ba(Fe_{1/2}Ta_{1/2})O_3$ systems, (11) 351*a*.
of B_2O_3-PbO-SiO_2, (7) 196*a*.
of compositions in MgO-SiO_2-Al_2O_3 system, (3) 86*h*.
of evaporated indium sulfide films, (10) 308*a*.
in glasses of BaO-P_2O_5 system, anomalies of, (8) 230*e*.
of glasses at 40 Gc/sec, (5) 127*b*.
of glasses within range 20° to 600°C, (9) 263*h*.
of insulation materials, measurement and control, (5) 138*j*.
of lead magnesium niobate, (4) 107*j*.

Dielectrics, properties (*continued*)
of RO-R_2O-PbO-SiO_2 glasses, (6) 168*e*.
of semiconducting iron phosphate glasses, (8) 231*g*.
of sodium-strontium-cadmium niobates, (5) 137*i*.
of solid solutions of $BiFeO_3$ with $Pb(Ti,Zr)O_3$ at high temperature and high frequency, (9) 280*f*.
of solids, (6) 176*e*.
of spinel-corundum highly refractory ceramics, influence of heat treatment conditions, (8) 238*b*.
semiconductor-ferroelectric, P (5) 142*i*.
studies, on solid solution systems based on Na-NbO_3. (5) 150*j*
study of $BaTa_2O_6$, (11) 341*g*.
study, of thermal aftereffect in glasses, (10) 297*h*.
transparent, destruction by laser beams, polarization-optical studies of, (10) 308*b*.
Dies. See also *Extrusion*.
coating, P (10) 300*d*.
design, and material control, (2) 52*j*.
extrusion for drain tile cluster, (8) 236*e*.
high-temperature metal-working extrusion, ceramic protective coating for, (2) 37*h*.
Differential thermal analysis. See *Thermal analysis*.
Diffraction. See also *Electron diffraction; Neutrons; X rays*.
apparatus combined with microscope for electron-optical inspection of surfaces, P (4) 103*f*.
gratings, grazing incidence, P (9) 277*e*.
of light by elastic waves in YIG, (4) 108*a*.
line shifts, in fine-grained barium titanate, (6) 185*e*.
of neutrons and X-rays by vibrating quartz crystal, (5) 150*j*.
optical, for detection of acoustic nonlinear frequency mixing, (11) 350*c*.
Diffractometers. See *Electron diffraction; X rays*.
Diffusion, of aluminous cords in sheet glass, 231*i*.
anisotropic, in hydrated vermiculite, (6) 183*g*.
of Be in MgO, (10) 319*e*.
in ceramic products, electron microprobe in study of, (10) 314*j*.
chemical, in vanadium-carbon system above 1900°C, (5) 150*a*.
of chlorine ion in potassium chloride, (8) 253*a*.
coefficients, silicon, in silicon and in silicon compounds, determination, (11) 354*e*.
constant, of Fe ion in magnesia (9) 267*d*,
of contoured junction, P (11) 345*c*.
controlled electrical, in electromagnetic field, P (3) 72*d*.
for decreasing minority carrier lifetime, P (3) 73*e*.
electric field, of oxygen at 900° to 1000°C in UO_2, (9) 281*i*.
of glass constituents in refractories, (3) 63*f*.
grain boundary, in sintering, (11) 356*b*.
hydrogen, in doped fused silica, determination from fluorescence, (7) 195*j*.
for impregnation of graphite powders, (2) 43*g*.
of impurity from doped oxide of pyrolytic origin on semiconductor device, P (3) 73*f*.
inter-, in system α-Al_2O_3-Cr_2O_3, (2) 58*c*.
intermetallic, in uranium-aluminum system, (6) 186*e*.
invariant of, in binary systems, (10) 322*a*.
of iron into sodium disilicate glass, magnetic studies, (3) 64*d*.
isothermal, in systems with glasslike transitions, (5) 127*h*.
lattice and grain boundary, of U ions in UO_2, (4) 112*i*.
low-temperature, in inert-gas bombarded Al_2O_3, (8) 254*g*.
mechanism, of defects movement in ionic crystals, (6) 189*e*.
of metal into refractory or ceramic oxide with nitrate promoter, P (7) 205*f*.
of phosphorus in silicon and making of *pn* junction semiconductor detectors, (7) 216*f*.
of phosphorus and sodium in Na_2O-P_2O_5-SiO_2 liquids, (5) 151*a*.
of point defects in strontium titanate, (3) 71*c*.
processes, in surface layer of glass, (1) 5*e*.
quantum mass effects in, (4) 114*e*.
rare gas, in cesium iodide, measured by fission recoil doping techniques, (11) 355*h*.
rare gas, in nonstoichiometric ZrC, (10) 324*d*.
rates, in inorganic nuclear materials, (9) 280*k*.
self-, of beryllium in unirradiated BeO, (3) 67*j*.
in BeO, (3) 68*a*.
of calcium, in glassy and crystalline Na_2O-$2CaO$-$3SiO_2$, (8) 230*e*.
cation, in fast neutron-irradiated BeO, (8) 252*e*.
in CsCl single crystals, (8) 256*i*.
in ionic melts, (3) 80*b*.
in molten group II chlorides, (11) 356*a*.
of oxygen in uranium oxide, (7) 220*g*.
of various cations in natural mordenite, (3) 86*d*.
of silver and potassium ions in glass, (7) 196*d*.
sodium, in Na_2O-Al_2O_3-SiO_2 and Na_2O-CaO-Al_2O_3-SiO_2 glasses, (1) 7*i*.
sodium, in SiO_2 glass, (10) 298*d*.
solid state, anharmonicity in statistical dynamical theory of, (6) 183*i*.
in sphere with fast irreversible reaction in bounded systems, (7) 216*g*.
in system K_2O-SrO-SiO_2: I, effective binary diffusion coefficients, (3) 63*f*.
thermal, in porcelain materials, (5) 136*i*.
in solids, isotope effect in, (4) 112*g*.
in system UO_2-CeO_2, (9) 287*j*.
tracer, by divacancy and impurity-vacancy pairs in cubic crystals, (9) 286*b*.
of transition metal ions into rutile, (10) 319*e*.
Diffusion (*continued*)
volume and grain boundary, of ^{22}Na and ^{45}Ca in polycrystalline Na_2O·$2CaO$·$3SiO_2$, (2) 60*a*.
of water and vapor, into ceramic materials, (8) 241*j*.
of Zn^{2+} in single-crystal MgO, (3) 80*c*.
Diffusivity, anisotropic, in pressed boehmite pellets, (9) 279*g*.
thermal, of refractory materials over wide temperature range, method and apparatus for rapid determination, (11) 346*h*.
Dilatometers. See also *Expansion*.
differential, for use above 2000°C, (6) 179*j*.
dilatometric analysis, as control tool, (3) 75*h*.
high temperature, for measuring shrinkage during sintering, (2) 54*h*.
high-temperature interferometric, development using laser light source, (10) 314*f*.
vertical, for use up to 1600°C, (5) 145*f*.
Dilatometry, acoustic-, studies of borosilicate glasses structural parameters, (10) 296*i*.
properties, of kaolinitic clays as measure of mineralogical composition, (6) 180*j*.
of structural clay products, (9) 276*b*.
techniques, for studying saline liquid at high temperatures, (7) 216*h*.
Dinnerware. See also *Art and artware; Pottery; Whiteware*.
cup topping machine, P (3) 70*f*.
machine for attaching handle to cup, (4) 98*c*.
majolica glazes for, (9) 270*j*.
mechanical strength, (2) 48*g*.
new design and display needs for today, (4) 91*i*.
plates, list of, (3) 61*i*.
plates, porcelain, automatic production line, (6) 175*h*.
Diodes. See also *Tubes, electron; Rectifiers*.
Al-Al_2O_3, tunnel emission from, (11) 357*h*.
array, and process for making, P (8) 244*i*.
CdTe, electroluminescence in, (8) 253*c*.
CdTe, luminescent properties, (11) 354*f*.
with circuit element and wire leads sealed in glass sleeve, method and apparatus for making, P (5) 141*f*.
device, semiconductor tunnel, P (7) 210*g*.
double heat sink semiconductor, with glass envelope, P (4) 100*b*; P (8) 244*a*.
GaAs, and $GaAs_{1-x}P_x$, vapor-grown, electroluminescence of, (8) 243*d*.
electroluminescent, high-energy emission in, (11) 353*j*.
laser, low threshold, (8) 243*g*.
laser, thermal resistance, (4) 118*d*.
Schottky barrier, transient phenomena in capacitance of, (5) 140*f*.
$GaAs_{1-x}P_x$ negative resistance light emitting, (5) 152*i*.
glass, sealing head for, P (10) 301*d*.
Au-KTaO$_3$ Schottky barrier, pressure sensitivity, (5) 157*f*.
high frequency, with small spreading resistance, P (9) 273*d*.
high frequency semiconductor, P (8) 244*e*.
high sensitivity, P (5) 141*a*.
indium antimonide tunnel, (5) 138*g*.
lithium-drift, method of making by diffusion, P (6) 178*d*.
and method of making, P (9) 274*d*.
planar diffused semiconductor voltage reference, method of making, P (7) 209*g*.
point-contact, with Au-Pt point, P (3) 74*a*.
restricted-area GaAs tunnel, preparation, (4) 99*f*.
semiconductor, and manufacture, P (5) 142*i*.
semiconductor contact, P (7) 210*e*.
silicon avalanche, stress effect on microwave emission from, (8) 257*e*.
silicon variable capacitance, producing by diffusion, P (10) 310*i*.
SiC, forming by growing separate *p* and *n* layers together, P (7) 210*c*.
SiC *pn* junction electroluminescing, growing using modified traveling solvent method, P (11) 345*d*.
surface-oriented high frequency, P (11) 345*a*.
surface-oriented semiconductor, P (6) 178*h*.
tunnel, method of making, P (7) 209*j*.
tunnel, sandwiched construction for, P (3) 74*e*.
zener, method of forming by using mask and diffusion, P (3) 73*b*.
Directories, of U. S. standardization activities, (1) 21*c*.
Disintegrators. See *Crushing apparatus*.
Dislocations, in BeO, observation by transmission electron microscopy, (2) 45*e*.
in crystals grown by traveling solvent method, removal of, (11) 356*f*.
in cultured quartz, (7) 216*i*.
edge, arrays, stability, (5) 158*h*.
edge, in sodium chloride crystal, measurement of charge on, (1) 30*b*.
etch pits, in dimolybdenum carbide single crystals, (9) 281*d*.
glide, activation parameters for, (4) 105*i*.
loops, in graphite, Burgers vector, (1) 26*f*.
interaction with straight dislocations in anisotropic graphite, (1) 29*f*.
interstitial, in irradiated sapphire, growth kinetics of, (1) 29*h*.
use of field-ion micrographs in study of, (8) 248*i*.
mass, effective, (8) 253*i*.
misfit, in GaAs-Ge heterojunctions, (1) 16*i*.
movement in brittle fracture of alumina, (10) 319*f*.
movement, in electric field in NaCl, (4) 113*g*.
in natural and synthetic calcium fluoride from different sources, comparative studies, (6) 184*i*.
Dislocation (*continued*)
non-basal edge and screw, in graphite, identification and physicochemical consequences, (1) 29*d*.
in semiconductors, (11) 351*f*.
in single crystals of lanthanum fluoride, exposing, (10) 321*d*.
slip and screw, in diamond, (6) 188*c*.
stress field, (8) 257*f*.
Dispersion, analysis, with automatic weighing sedimentometer, (2) 54*c*.
of blue ball clay: I, sodium hydroxide and sodium carbonate, (7) 216*d*.
of clay, for particle size determination, (1) 21*d*.
interface-state time constant, MOS study of, (4) 113*g*.
of kaolins, clays, and ceramic bodies and preparation of workable casting slips, (10) 305*e*.
of metal oxide microspheres, electrical potential method for, P (2) 53*a*.
ratios, partial, of new borate and phosphate glasses, (9) 264*b*.
refractory metal, P (2) 48*a*.
study of optical glass in visible and infrared regions of spectrum, proposed mean reference line in, (2) 40*a*.
Dissolution. See *Solutions*.
Dolomite. See also *Refractories*.
dead-burned, process for making, P (11) 340*f*.
of different petrographic nature, sintering behavior, (1) 23*d*.
dolomitization, de-, experimental, (5) 152*h*.
dolomitization, marine, of Mifflin member Platteville limestone in southwest Wisconsin, (1) 30*b*.
estimation by DTA analysis and X-ray methods, (3) 62*h*.
high temperature properties: I, dolomite refractories, study by high temperature X-ray diffraction, (10) 303*d*.
Illinois, thermal expansion, (4) 118*a*.
Moldavia and Dobrogea, technology of sintering, (9) 269*d*.
plaster. See *Plaster*.
sintered, for linings in metallurgical furnaces, process for production, P (1) 12*b*.
sintered, mineralogical constitution, texture, and use, (8) 240*c*.
synthetic, porosity in, (9) 285*e*.
thermal decomposition, (9) 287*j*.
thermodynamics of formation of, (11) 355*b*.
Domains. See *Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials*.
Doping. See *Additives*.
Doppler effect, shift, second-order, of ^{129}I in alkali iodides, (9) 280*c*.
Dosimeter, glass, for measuring laser output, (7) 199*a*.
manganese arsenic borate glass, (1) 6*i*.
quartz thermoluminescence, properties, (2) 59*d*.
radioactive radiation, of silver phosphate glass type, P (8) 246*d*.
Dosimetry, gamma-ray, application of irradiation effect to, (6) 185*f*.
system, thermoluminescent, P (7) 213*e*.
Drilling, counterbore in ceramic whiteware, (6) 175*i*.
micro-, mechanical outperforms laser, (5) 143*g*.
Drills, rod assembly, magnesium alloy, with ceramic coated coupling member, P (3) 93*c*.
Dry pressing. See *Pressing*.
Dryers. See also *Drying*.
for ceramic ware, P (8) 249*j*.
for finely divided particles, P (3) 75*c*.
industrial, common, survey, (11) 348*g*.
for modifying fluid content of particulate material, P (10) 317*e*.
nozzle, in ceramic industry, (10) 317*b*.
for solids, P (4) 101*j*.
Drying. See also *Dryers*.
agglomerative, P (10) 312*a*.
brick, with waste heat from tunnel kilns, (2) 42*h*.
ceramic materials, psychrometry, (6) 179*d*.
ceramic product, modern methods, (9) 275*f*.
ceramic products, physical aspects, (2) 43*b*.
clays and bodies, water diffusion phenomena, (6) 172*a*.
in clayworks, (5) 143*j*.
and crushing apparatus, P (1) 25*j*.
extruded rodlike UO_2 sections and maintaining straightness, P (10) 317*b*.
faster, with modern metallic battens, (10) 316*j*.
freeze-, for disaggregating silts and clays for dry particle size analysis, (2) 54*d*.
gypsum, method and apparatus, P (2) 37*f*.
and heating, of gravel and crushed stone, method and apparatus, P (4) 105*g*.
high frequency and very high frequency, tests on earthenware products, (6) 175*e*.
laboratory investigations with direct application to industrial practice, (1) 24*d*.
plaster molds, (4) 98*b*.
in porcelain industry, (7) 206*a*.
spray, and centrifugal atomization, (5) 144*a*.
economics, (8) 246*j*.
as granulating method, (5) 143*j*.
in manufacture of structural ceramics, new technical information, (4) 95*i*.
of solutions for production of piezoelectric and Seignette ceramics, (8) 243*j*.
reproducible, organopolysiloxanes, P (8) 236*a*.
study, (6) 179*e*.
test, empirical, for clays, (6) 180*b*.
Durability, of silicate concrete, effect of binder composition, (5) 124*f*.
Dusts. See also *Air, pollution; Particles; Powders*.
collector apparatus, P (1) 20*a*.
control, (2) 52*j*.
extraction, from boiler flue gases, (5) 143*i*.

Dusts (*continued*)
measurements, on cement kilns, (2) 36*h*.
problems, in ceramic industry, (5) 143*i*.
rotary kiln, for making dense magnesite powder, (9) 267*f*.
Dynamics, crystal, of lead sulfide, (9) 280*i*.
Dysprosium, alkoxides, P (3) 69*g*.
alkoxides, preparation and properties, (5) 157*e*.
$DyMn_2O_5$, paramagnetic, crystal structure at 298°K, (11) 351*e*.
sesquioxides, crystalline varieties, stable at high temperature, (5) 155*d*.

Earthenware, compositions, for ceramic wall tile, (9) 271*i*.
products, high frequency and very high frequency drying tests on, (6) 175*e*.
white, replacemen tof quartz by barite in manufacture, (9) 271*e*.
Eclogite, barroisite-bearing, from Naustdal, Sogn og Fjordane, Norway, (4) 106*f*.
Education, continuing, in ceramic engineering, (1) 34*c*.
pottery school, of Kandern in Black Forest, under Horst Kerstan, (4) 91*i*.
Wedgwood's training development, (10) 327*i*.
Efflorescence, brickwork, (10) 301*g*.
causes and cures, (4) 95*h*.
in clay brick, (11) 337*d*.
influence on decay and expansion of mortar, (11) 337*a*.
relation to soluble sulfates, (8) 236*e*.
Effusion, studies, of beryllium fluoride vapor, (3) 80*j*.
Elasticity, constants, of CaF_2, pressure derivatives, (8) 256*f*.
constants, nonlinear, of monocrystalline and polycrystalline solids of cubic symmetry, relations between, (11) 356*e*.
of reactor graphites, (3) 67*d*.
of single crystal $CaMoO_4$, (7) 217*f*.
of single crystal corundum below room temperature, (8) 253*a*.
third order, c_{111}, in lithium fluoride, (11) 357*h*.
field, of inclusion in anisotropic medium, (9) 281*g*.
of glass, bibliography, B (8) 258*i*.
of MgO matrix composites, (1) 28*f*.
and microindentation hardness and Poisson's ratio of glasses, (7) 196*f*.
modulus, of ceramics at elevated temperatures, apparatus for dynamic measurement of, (10) 313*d*.
of composites, prediction, (9) 285*g*.
of faience tile, determination by different methods, (10) 305*e*.
of graphite, effect of interstitial loops, (4) 111*i*.
at high temperatures, apparatus for measuring, (10) 313*f*.
interrelation with hardness and porosity in gypsum systems, (7) 194*h*.
measurements, high temperature dynamic by use of ultrasonics, (7) 212*h*.
-porosity relation, (10) 319*j*.
relation with mechanical strength of ceramic body, verification, (7) 223*a*.
shear, bounds, of macroscopically isotropic aggregates of cubic crystals, (4) 106*j*.
of β-silicon carbide whiskers, (3) 80*a*.
of titanium diboride, (8) 253*c*.
of $91Y_2O_3 + 9ThO_2$ from 25° to 1100°C, temperature dependence of, (5) 159*e*.
photo-, for stress analysis of high pressure anvil, (9) 277*h*.
properties, of barium titanate single crystal above Curie point, (5) 151*b*.
of boron carbide, effect of low porosity, (4) 108*c*.
of polycrystalline transition-metal monocarbides, (10) 320*d*.
of silicon carbide, (5) 151*c*.
shock wave decay, in quartzite, calculated for cylindrical and spherical flow, (9) 281*h*.
of uranium oxides, at room temperature: II, hyperstoichiometric oxides, (5) 132*c*.
viscoelastic bodies, rheological models of, (11) 351*d*.
of whiteware, effect of porosity and mullite content, (6) 175*j*.
of whiteware, relation with flexural strength, (1) 15*h*.
Young's modulus, of artificial graphite, effect of porosity and crystalline orientation, (4) 108*d*.
of reactor graphite, effect of stress and annealing, (8) 253*i*.
and shear, of polycrystalline Y_2O_3, (10) 324*b*.
Electric resistors. See *Resistors, electrical*.
Electrical ceramics. See also *Electronics*.
fabricated from coprecipitated lead-zirconium-titanium hydroxide, ceramic and electrical properties, (9) 272*h*.
low dielectric loss, wollastonite for, (7) 206*a*.
Electrical conductivity. See *Conductivity, electrical*.
Electrical properties, of barium titanate, effect of reduction, (6) 176*h*.
of barium-titanate ceramics, with different grain size, (7) 207*d*.
behavior, of group IV impurities in solution grown gallium phosphide, (4) 116*b*.
behavior, of zinc, sulfur, selenium, and tellurium in gallium phosphide, (3) 86*c*.
of bodies fabricated from coprecipitated lead-zirconium-titanium hydroxide, (9) 272*h*.
of cobalt monoxide, (5) 138*b*.
of doctor-bladed ferroelectric ceramics, (1) 16*d*.
of evaporated silicon oxide films, effect of structure, (10) 308*d*.
of ferroelectric ceramics, relations with sintering by hot-pressing, (11) 342*g*.
Electrical properties (*continued*)
of ferromagnetic CrO_2, (11) 352*i*.
of glasses in system $PbO-Al_2O_3-B_2O_3-SiO_2$, (2) 39*f*.
high temperature, of manganese monoxide, (5) 138*c*.
of insulators, examination by surface charge measurement, (2) 49*i*.
of Li_2O-SiO_2, effect of metastable precipitate, (9) 263*j*.
of niobium-doped ferroelectric $Pb(Zr,Sn,Ti)O_3$ ceramics, (5) 138*c*.
photo-, of microcrystalline ZnO powder layers with adsorbed monolayer of long chain fatty acid, (11) 355*i*.
of KNO_3, (5) 138*c*.
of rare earth doped cadmium fluoride single crystals, (4) 109*b*.
of refractory oxides, at high temperatures, (3) 71*a*.
of semiconducting oxide glasses, effect of network former, (3) 64*b*; correction, (7) 197*e*.
of semiconductor β-Ga_2O_3, (3) 72*d*.
of strontium ferrates, (5) 138*a*.
of ternary alloys in pseudobinary system Sb-SnTe, (11) 355*h*.
of vanadium bronzes, (1) 29*i*.
of VO, (10) 320*e*.
of vanadium oxide single crystals grown by oxychloride decomposition, (7) 217*h*.
of volcanic glasses, (8) 231*h*.
of zinc-lithium manganites, (5) 138*d*.
of ZnO single crystals, (3) 84*f*.
Electrical resistance. See *Resistance, electrical*.
Electricity, field effect on ESR of Gd^{3+} in $SrTiO_3$, (10) 320*e*.
field strength, in photoconducting CdS, spatial variation of, (11) 356*j*.
fields, effect on electroreflectance spectrum, (11) 352*e*.
pyro-, of ZnO, (11) 355*f*.
thermophysical and electrical parameters, in molten glass, (10) 299*f*.
Electroanalysis. See *Analysis*.
Electroceramics. See *Electric ceramics*.
Electrochemistry. See also *Corrosion*.
behavior, of sodium silicates at high temperatures, (1) 6*a*.
model, for oxidation of Zr, (4) 109*g*.
Electrochromatography. See *Chromatography*.
Electrodes. See also *Heating elements*.
arc, of graphite with ball tip, P (11) 347*e*.
for arc furnaces, P (10) 317*f*.
arc welding, providing welds having high yield and rupture value, P (1) 4*d*.
assembly, plate, for electrostatic precipitator, P (6) 179*f*.
bodies, of dissimilar thermal coefficients of expansion, method of joining, P (7) 205*c*.
cation-sensitive glass, for reaction rate measurements, between Ag(I)-EDTA and Ni(II), (5) 146*g*.
cationic glass, response in aqueous solutions of sodium chloride and potassium chloride, (4) 102*f*.
ceramic, electrical contact system for, P (10) 300*e*.
on ceramic body, preparing for bonding, P (6) 178*a*.
coated, for arc welding of cast iron, P (6) 166*c*.
device for electric furnaces, P (8) 235*h*.
for electrically heated glass furnaces, P (1) 24*b*.
electrochemical, P (7) 195*c*.
electroding, dielectric ceramics, composition and method, P (1) 17*d*.
fluoride-sensitive membrane: I, containing thorium, lanthanum, or calcium fluoride, (8) 243*b*.
fuel cell, comprised of borides, carbides, nitrides, and/or silicides of one or more transition metals, method of making, P (8) 241*b*.
furnace, liquid-cooled holder for, P (8) 249*h*.
glass, P (3) 65*g*; P (5) 129*j*.
composition, P (6) 170*c*.
composition and method of using for measuring sodium ion and potassium ion concentration, P (3) 65*f*.
furnace, P (9) 278*d*.
furnace, air stream device for cooling, P (11) 335*c*.
numerical calculations for alkaline error of, (5) 156*b*.
with temperature control means, P (3) 65*e*.
for glassmelting furnaces, P (7) 198*d*.
graphite, protecting from oxidation, P (2) 48*b*.
holder, for glass melting furnace, P (8) 249*f*.
in magneto-hydrodynamic devices, method of improving performance, P (2) 51*a*.
metal inserts for use in wall of glass envelopes for support of, P (4) 100*i*.
MHD, effect of porosity on electrolysis in, (10) 302*h*.
multiple section graphite, P (4) 97*d*.
polycrystalline dual layered aluminum oxide-magnesium oxide storage, method of making, P (7) 209*h*.
porous, for fuel cells, (10) 303*f*.
porous, method of making, P (11) 340*i*.
potentials, in fused systems: IX, liquid junction potentials in AgCl-AgBr system, (5) 151*h*.
sodium, alkali-glass membrane as, (5) 126*g*.
spark plug center, with split truncated head, P (1) 16*a*.
specific ion, for determination of trace fluoride, (10) 316*a*.
target, indium doped pickup tube, P (2) 51*e*.
Electroluminescence. See *Luminescence*.
Electroluminescent materials. See *Luminescent materials*.
Electrolysis, fused-salt, for preparation of boron, statistical evaluation of factors, (3) 77*f*.
Electrolysis (*continued*)
fused-salt, for preparation of UO_2 using UO_2 or UF_4 as starting material, (5) 133*h*.
fused salt, for production of uranium metal from uranium oxide, (2) 45*f*.
in MHD electrodes, effect of porosity, (10) 302*h*.
of synthetic quartz with nonstructural impurity, (1) 28*g*.
Electrolytes, solid, ceria-lanthana as, for fuel cells, (7) 207*g*.
Electrolytic, negative, breakdown, in proton bombarded LiF crystal, (10) 323*h*.
treatment, controlled, of materials, P (9) 272*e*.
Electromagnets. See *Magnets*.
Electromechanical properties. See *Mechanical properties*.
Electron diffraction, analysis, of clay mineral structures, B (10) 328*i*.
of barium titanate, thermal diffuse streak in, (4) 117*j*.
for determination of free molecules structure, (5) 158*b*.
low-energy, observations of α-alumina, (4) 112*c*.
ring patterns, intensity measurement by "Gegenfeld" filter technique, (4) 111*h*.
of single-crystalline UO_2 layers, for determination of interstitial distribution of oxygen atoms, (5) 150*h*.
study of kaolinite formation from albite altered by water at 200°C, (7) 217*e*.
of MgO 400 systematic interactions, (1) 28*h*.
of sillimanite and natural and artificial mullites, (1) 27*d*.
of structure of PF_5, (4) 109*h*.
of surface replica extractions, (1) 21*j*.
Electron probes, microanalysis, quantitative, examination of accuracy, (9) 276*f*.
microanalyzer, applications to ceramics, (6) 179*j*, 180*a,b*.
comparison with X-ray diffraction in quantitative mineralogical analysis of carbonate sediments, (8) 248*d*.
rotatable sample changer for, with means for maintaining vacuum in analysis chamber, P (3) 76*g*.
micro-, analysis, (10) 313*b*.
analysis, at British Ceramic Research Association, (10) 313*c*.
for investigation of spherical inclusions in flat glass, (8) 232*c*.
mineralogical applications of, (10) 315*a*.
MS 46 Cameca, improvements, (10) 315*e*.
in study of diffusion in ceramic products, (10) 314*j*.
for study of contact between glass and refractory, (10) 298*j*.
of surface replica extractions, (1) 21*j*.
Electron tubes. See *Tubes*.
Electronic equipment, amplifier, chopper, with high breakdown voltage, P (5) 140*h*.
assembly, hermetic electrical lead-in, P (6) 177*c*.
bushings, cast electrical, method of constructing, P (11) 344*e*.
ceramic reed relay, P (9) 272*b*.
ceramic reed relay, with flux carrying means associated with armature, P (9) 272*c*.
components, method of calibrating, P (10) 310*d*.
miniature, precision and magnification radiography of, (7) 212*j*.
thick film, reliable, (11) 341*g*.
thin [Ta] film, method of terminating, P (7) 209*g*.
ultrasonic time delay, (10) 309*d*.
connector, hermetically sealed, P (6) 177*d*.
devices, glass encapsulated, P (10) 309*h*.
discharge device, high pressure, with fill of mercury, halogen, and alkali metal and barrier refractory oxide layers, P (2) 51*d*.
discharge device, with storage target electrode, P (6) 177*f*.
electric discharge device, with polycrystalline alumina end caps, P (4) 99*h*.
electrical devices, combination of thin-filmed, P (5) 140*i*.
Faraday rotator, using terbium aluminum and dysprosium aluminum garnets, P (5) 141*g*.
klystron, with high frequency radiation means comprising half-wave short-circuited choke, P (10) 310*b*.
laser amplifier device, P (11) 343*j*.
magnetic control device, current and temperature responsive, P (9) 272*e*.
manipulators, thermal, for ultrahigh vacuum, (8) 243*a*.
optical frequency-changing devices, and materials for use in, P (11) 344*h*.
overvoltage protective device, P (10) 311*e*.
piezoelectric spark igniter, P (11) 345*a*.
for process control, (2) 52*j*.
silver-barium titanate rectifying junctions, P (5) 137*i*.
S-M-S device, with partial semiconducting layers, P (7) 210*a*.
thin film field sustained conductivity device, P (11) 344*d*.
varistor, silicon carbide, P (8) 246*i*.
Electronics. See also *Electrical ceramics; Electronic equipment*.
carrier generation and switching phenomena in *n*-GaAs devices, (6) 176*b*.
ceramics, importance of microstructure, (1) 16*e*.
ceramics, wet chemical method for preparation of oxide mixtures applicable to, (9) 272*h*.
compounds, III-V, preparation, P (4) 100*j*.
cordierite and steatite ceramics, processing, (10) 306*f*.
material, "elastic" ceramic, for coating and bonding, (5) 137*j*.
materials, electrically conductive vitreous, P (2) 50*j*.

Electronics (*continued*)
micro-, review, (5) 139*a*.
substrate surfaces for, (7) 208*d*.
thick film, ceramic glazes for, (7) 207*a*.
packaging, high temperature, tooling for, (3) 72*h*.
properties, of amorphous dielectric films, (11) 342*a*.
of materials, B (5) 161*c*.
of semiconductors, (6) 176*f*.
of tungsten bronzes, (5) 138*f*.
quantum, in solids, B (10) 328*e*.
radio ceramics, accelerating grinding of raw materials for, (8) 242*h*.
states, low-lying excited, of BrCl and other halogens, formation and detection, (9) 282*j*.
structure, of SrO, (5) 138*g*.
Electrons, affinity, of semiconducting CdSe, (11) 352*j*.
auger, to chemically identify presence of light-weight elements, (8) 248*c*.
-beam apparatus for vacuum vaporization of metallic and nonmetallic samples, (10) 314*i*.
beam, induces voltage in bulk semiconductor crystal, (8) 258*b*.
for resistance measurement, (11) 354*d*.
used for vapor deposition, P (1) 18*j*.
discharge device, with barium dispensing anode structure, P (1) 17*g*.
electrolysis-resistant, P (5) 141*c*.
and method, P (3) 72*e*.
distribution, of ions in NiO, MnO, and CoO crystals, (3) 80*d*.
donor, in semiconductors, infrared absorption due to, (10) 322*e*.
emissions. See *Emissions*.
photo-, in CdS, optical absorption, (11) 355*d*.
screening, in *n*-type GaSb, (10) 320*e*.
transfer, at alumina surfaces: I, electron-acceptor properties, (3) 80*f*.
Electrooptic, coefficients, of ferroelectric strontium barium niobate, (3) 71*g*.
effect, in calcium pyroniobate, (5) 138*g*.
effect, in $LiNbO_3$ and KTN, (4) 109*f*.
measurements, of characterization of potassium tantalate-niobate crystals, (1) 26*h*.
properties, of lead magnesium niobate, (4) 107*j*.
scanning means, for measuring dimension of object, P (8) 249*c*.
Electrophoresis, and centrifugal chromatography device, P (11) 347*f*.
electrophoretic coating method for porcelain enamel, (8) 229*d*.
electrophoretic indication of thixotropic properties of clay mineral suspension, (7) 217*i*.
in ionic melts, (3) 80*b*.
and paper chromatography for separation of iron(II)-iron(III), (11) 347*g*.
review, (10) 314*a*.
Electrophotography. See *Photography*.
Electrostatic processes, coating apparatus, for uniformly applying phosphor powders, P (4) 99*i*.
coating, basic principles, (9) 262*h*.
ceramics on metal, (2) 37*i*.
methods, and apparatus for conductive coating materials, P (8) 247*c*.
system, P (8) 247*d*.
enameling, improvement in quality, (1) 4*d*.
separation, and conditioning compositions for, P (9) 279*c*.
separation apparatus, P (8) 251*b*.
spray, air atomized, enamel characteristics for, (9) 262*g*.
spraying, (9) 263*b*.
spraying, effect of production variables on efficiency, (7) 195*c*.
Electrostriction, ceramic articles, of lead zirconate titanate containing Mn and W oxides, P (6) 178*c*.
Elements, conductive, composition, and method, P (9) 272*d*.
electrical circuit, miniature ceramic bases for, P (4) 100*g*.
heating. See *Heating elements*.
lead telluride thermoelectric generator, brazing, P (8) 243*j*.
light, in nonconductors, preparation of samples for analysis, (6) 179*i*.
load-bearing mounting, for attachment to glass surfaces, P (8) 235*c*.
photosensitive, method of making, P (6) 178*c*.
trace, in sulfide minerals, determination by atomic absorption spectrophotometry with absorption tubes, (5) 145*b*.
Embrittlement, of oxide films on Zr by neutron irradiation, (10) 320*i*.
Emeralds, absorption, fluorescence, and Zeeman effect in, (3) 78*g*.
synthetic, characteristics, (8) 250*a*.
Emission, abnormal green edge, in CdS, (11) 350*c*.
band, K, of graphite, (4) 112*h*.
electron, correlation with electroluminescence of thin metal-oxide-metal sandwiches, (6) 176*c*; (10) 305*j*.
electron, from metal-BaO systems, (2) 49*h*.
gas, in vacuum from MgO surfaces previously exposed to air, (4) 98*j*.
high-energy, in GaAs electroluminescent diodes, (11) 353*j*.
infrared, for classification of ores, P (11) 349*c*.
laser, of Er^{3+} at 1.69 and Tm^{3+} at 1.86 in mixed crystals of CaF_2:ErF_3:TmF_3, thermal switching of, (4) 118*d*.
laser, room temperature, from CdS under pulsed electron bombardment, (4) 115*i*.
light, coherent and noncoherent, in II–VI compounds, (4) 106*h*.
microwave, from indium antimonide, temperature dependence, (2) 50*h*.

Emission (*continued*)
microwave, from Si avalanche diodes, stress effect on, (8) 257*e*.
of phosphor YVO$_4$:Eu, empirical studies, (4) 109*g*.
photoelectric, of InP, (8) 256*a*.
photoelectric and enhanced thermionic, from strontium oxide, (11) 355*j*.
photo-, of electrons from silicon and gold into SiO_2, (9) 285*b*.
photo-, from GaAs thin films, (8) 243*i*.
properties, of oxides of alkali earth metals, (6) 185*a*.
thermionic, of alkali ions from impregnated metal matrices, (1) 17*d*.
tunnel, from Al-Al_2O_3-metal structures, (11) 357*h*.
uranium, from sintered uranium oxide pellets, experiments, (7) 201*g*.
X-ray. See *X-rays*.
Emissivity, measurement, at 0.65μ with solar furnace, (4) 117*f*.
total, of heat-resistant ceramic coatings of refractory oxides produced by gas-flame spraying, (5) 132*g*.
Emittance, hemispherical spectral, of selected rare earth oxides, (5) 153*i*.
measurements of solids above 2000°C, (4) 109*f*.
spectral, of solids at high temperatures, techniques for measuring using solar furnace, (5) 146*c*.
Emitters, semiconductor light, high efficiency, P (2) 51*c*.
thermionic, consisting of BaO-UO_2 dispersed in tungsten matrix, (4) 118*c*.
Emulsions, practical: Vol. I, materials and equipment Vol. II, applications, B (9) 290*b*.
Enameled ware, bath, cast-iron, design, (2) 35*i*.
boiling and frying, comparative testing of service behavior with plastic-coated ware, (7) 195*a*.
edge treatment to prevent corrosion, (3) 63*c*.
range parts, rehandling causes damage, (3) 63*d*.
panels. See *Building materials*.
potable water tanks, evaluation of coatings, P (7) 195*c*.
tanks, and magnesium anode, (9) 263*a*.
Enameling, de-, (4) 92*h*.
defects, (7) 195*d*.
direct-on, evaluation, (9) 262*h*.
direct-on, in Canada, (11) 332*g*.
electrostatic, improvement in quality, (1) 4*d*.
enamelist, B (3) 89*e*.
equipment. See *Spraying*.
furnaces. See *Furnaces*.
gas reactions and consequences in, (11) 332*j*.
magnesium trisilicate as additive in, (2) 38*e*.
vitreous, of signs, (4) 92*j*.
Enameling apparatus. See *Furnaces; Spraying*.
Enameling metals, of aluminum, for building construction, (1) 4*i*.
of cast iron, (11) 332*j*.
influence of gases evolved or formed during, (4) 92*j*.
in nonmuffled furnaces, (5) 125*j*.
direct-to-steel, follow-up survey, (9) 262*h*.
processing prior to, (9) 263*a*.
sheet, low temperature white coat porcelain enamel for, (9) 262*j*.
parts, design and fabrication for porcelain enameling, (9) 262*j*.
direct-on enameled, investigations at metal-enamel interface, (5) 126*b*.
pickling procedures, (9) 262*g*.
surfaces, treatment prior to enameling, P (5) 126*c*.
Enamels. See also *Coatings*.
acid-resistant for Al, P (8) 229*h*.
acid-resistant vitreous crystalline, properties, effect of crystallization on, (11) 332*g*.
aluminum, (10) 296*e*.
adherence to aluminum plate, effects of conditions of anodic oxidation on, (8) 229*e*.
new applications, (1) 3*j*.
of system PbO–SiO_2–V_2O_5, (11) 332*c*.
-cast iron system, stresses determination, (5) 125*j*.
challenge, (2) 37*i*.
characteristics, for air atomized electrostatic spray, (9) 262*g*.
chemical resistance, assessment, (1) 3*h*.
cleaning, (9) 262*h*.
for coating wire, P (5) 126*d*.
color, blues and greens over 50% of spectrum, (11) 332*e*.
composite devitrified-vitrified, P (4) 93*a*.
composite material, P (1) 4*j*.
copper, transparency in, (8) 229*g*.
crystalline, infrared spectroscopy of crystallization in, (8) 229*h*.
dry process, classification for cast iron bathtubs by drip test, (5) 125*i*.
durability, performance criteria for building components and systems, (9) 263*a*.
electrodeposition for, (10) 296*d*.
electrophoretic coating method for, (8) 229*d*.
frits. See *Frits*.
glass, alkali resistance: II, attack on low temperature glasses containing ZrO_2 by alkali solution, (1) 3*h*.
color control, (2) 38*j*.
composition, conductors and coils insulated with, and method of making, P (11) 332*h*.
containing ZrO_2, attack by alkali solution (1) 3*h*.
granulated zinc oxide for, (7) 206*g*.
ground coat, effect of dissolved materials on pickup behavior, (9) 262*j*.
hard and flexible stoving, P (2) 38*c*.
industry, water chemistry used in, (9) 262*h*.
low temperature white coat, for sheet iron, (9) 262*j*.

Enamels (*continued*)
mat surface vitreous, for glass, P (8) 229*i*.
melting in electric furnaces, (8) 229*f*.
melts, kinetics of solution of solid ferrous oxide in, (9) 286*b*.
ornaments for German town council chains of office, (7) 194*a*.
particle size, measurement, (10) 296*d*.
preparation, (11) 332*i*.
preparation for future, (9) 263*b*.
resistance, to boiling citric acid, method of testing, IEI proposed standard, (1) 4*e*.
to boiling water and steam, method of testing, (4) 92*j*.
to hot sodium hydroxide, method of test, (4) 92*i*.
to boiling hydrochloric acid, method of testing, IEI proposed standard, (1) 4*f*.
to citric acid at room temperature, method of testing, IEI proposed standard, (1) 4*f*.
running surface for snow ski, P (11) 333*c*.
sheet steel, problems and solution, (5) 126*d*.
shop, inspection and quality control in, (9) 263*c*.
silicate, properties, effect of powdered metal fillers, (5) 125*i*.
slips. See *Slips*.
systems, correlation between warpage and chippage in, (9) 262*i*.
technology, B (2) 60*i*.
TiO_2 for more white in, (11) 332*g*.
vitreous, direct firing of, (4) 92*h*.
Energy, activation, of conduction, in tantalum anodic films, (8) 242*i*.
activation, for high-temperature steady-state creep in lead sulfide, (6) 183*g*.
activation, for sublimation of gallium nitride, (3) 78*h*.
band, calculation in disordered systems, (5) 155*j*.
3ρ, in lithium chloride, (8) 258*g*.
of PbTe, PbSe, and PbS, (8) 253*f*.
bond, (4) 106*g*.
cohesive, of diamond, (4) 106*h*.
of MnO crystal, (3) 79*h*.
of TiO_2, (8) 252*f*.
-conducting devices, fiber, apparatus for making, P (11) 335*c*.
dissociation, of alkaline-earth oxides, flame-photometric determination, (6) 185*i*.
of NaO_2, (3) 80*d*.
of $TiO_{(g)}$, (11) 351*e*.
electric, converting to hydrostatic mechanical energy, process and apparatus, P (3) 74*d*.
fracture, of polycrystalline BeO, (11) 353*b*.
free, of formation of chromium carbide, (11) 353*b*.
of formation, of kaolinite from solubility measurements, (5) 152*h*.
of formation, standard molar, of uranium dicarbide and uranium sesquicarbide, (11) 357*c*.
of formation, of thorium sulfides from solid-state emf measurements, (5) 152*f*.
interfacial, of mica, direct measurement of influence of vapor, liquid, and oriented monolayers on, (9) 280*j*.
laser-emissive, high resolution filter for, P (6) 177*d*.
lattice, relation with grinding properties of crystalline materials, (7) 211*f*.
levels, of Eu^{3+} in Y_2O_3, (6) 188*j*.
low-lying, of MgO, (10) 322*e*.
of trivalent europium in yttrium gallium garnet, (3) 80*j*.
of Yb^{3+} in garnets, (5) 152*d*.
Madelung, of perovskite structures: II, tetragonal case, (6) 187*c*.
Madelung, superlattice, of idealized ordered cubic perovskites, (6) 189*d*.
of [001] tilt boundaries in NiO, (5) 152*d*.
transfer, in $CaNaBO_3$ activated with Tb and Gd, (6) 185*b*.
transfer, in Eu^{3+}-activated tungstates and molybdates of type Ln_2WO_6 and Ln_2MoO_6, (10) 321*b*.
ultrasonic, effect on fluid flow in porous media, (1) 21*k*.
Engineering, ceramic, physical values in, conversion to International System, (10) 327*j*.
ceramic, plan for continuing education, (1) 34*c*.
ceramics, of future, (9) 275*c*; (10) 312*a*.
chemical, computation techniques in, (10) 327*i*.
projects, evaluating, (3) 89*b*.
properties of selected ceramic materials, B (3) 89*j*.
Engineers, ceramic, salary survey, (7) 223*d*.
seek materials for hostile environments, (7) 223*e*.
shortage, ceramic technicians to help solve, (4) 119*f*.
Epitaxy. See *Crystallization*.
Enthalpy. See *Heat, content*.
Entropy, change, at Morin point of hematite crystal, (4) 109*i*.
of dehydrated analcite, kaliophilite, and leucite, (6) 186*h*.
excess, at glass transformation, (5) 127*a*.
interpretation of viscosity of B_2O_3, (4) 93*e*.
of sodium bromide and sodium iodide, (4) 111*j*.
of sublimation of beryllium fluoride, (11) 357*e*.
of UP and U_3P_4, (7) 222*e*.
of vacancies in ionic crystals, (9) 282*e*.
Equations, and application to form of meniscus and production problems in continuous drawing of glass from molten or viscous bath, (7) 195*j*.
for calculating thermodynamic functions of two-component system from empirical equation of state, including liquid-vapor equilibria data, (6) 185*c*.
Clausius-Clapeyron, and V_2O_4, V_3O_5 phase transitions, (4) 106*g*.
for compressible cake filtration, (1) 19*h*.

Equations *(continued)*
optimized, for MacAdam color differences, (6) 187*a*.
rate, for sintering by surface diffusion, (10) 324*e*.
of state, of polymer liquids and glasses at elevated pressures, (5) 127*j*.
Equilibrium studies. See also *Systems*.
between (Li,Na,K,Mg) carbonate melt, gaseous CO_2, and MgO, (7) 217*a*.
chemical, at high temperatures, small furnace for, (6) 181*g*.
diagram, Yb_2O_3-TiO_2, existence of new composition Yb_4TiO_{11} in, (7) 217*c*.
equilibria, gypsum-anhydrite, at one atmosphere pressure, (5) 153*e*.
equilibria, solid-vapor, comparison of thermochemical measurements and calculations as opposed to direct experimental determination of, (8) 252*h*.
phase diagram, Ca_3SiO_4 and CaC_2, (7) 216*e*.
indium telluride-indium antimonide quasi-binary, (4) 117*a*.
of lithium and solidium ferrites and aluminates, (6) 183*h*.
for Li_2O-, Na_2O-, and K_2O-SiO_2, calculation for activities in, (1) 5*a*.
of silicon and germanium to 200 kbars, 1000°C, (6) 187*d*.
of sodium sulfate and sodium chromate to 45 kbars, (6) 187*d*.
of sodium tungstate and sodium molybdate to 45 kbars, (7) 220*j*.
ternary, and LnB_2C_2 in high temperature rare earth-boron-carbon studies, (6) 186*i*.
uranium-uranium dioxide, at high temperatures, (11) 358*a*.
phase equilibria, measurement, at high pressures by tracer-pulse chromatography, (9) 276*c*.
reactions, of compositions near field of primary crystallization of cordierite, (6) 176*f*.
Equipment. See *Machinery and equipment* and specific types.
Erbium, chloride, reaction with NaCl, (10) 324*f*.
Er^{3+} spectrum in single crystals of Y_2O_3, (5) 158*h*.
systems. See *Systems*.
Erosion, gaseous, of ZrO_2 refractories: II, changes at surface: III, effect of K additive on erosion resistance in stream of products of combustion, (5) 132*c*, *d*.
in LD converter, different zones of, (8) 237*d*.
mechanical, of charring ablators in ground-test and reentry environments, (9) 267*i*.
rate, of ladle brick, relation with brittleness index, (7) 202*j*.
of tar-dolomite and tar-magnesite bricks in oxygen process steel converters, mineralogy, (7) 202*i*.
Etch, pits and trigons, on diamond, (8) 253*g*.
Etchants, HF and HNO_3, for PuO_2, (1) 20*j*.
Etching, of calcite cleavages of scalenohedral habit, (6) 185*e*.
chemical, of hardened glasses, peculiarities, (6) 168*g*.
contacts on transistor to improve power output, P (9) 273*i*.
for forming semiconductor device, P (1) 18*a*.
in GaAs-Sn system, (3) 81*a*.
imperfections, fast, in silicon dioxide films, (7) 207*b*.
for making cermet resistors, P (11) 344*j*.
of matched fracture faces of quartz, (4) 110*e*.
of portland cement clinker, (9) 262*a*.
process, for producing nonreflective surface on float glass, P (6) 170*i*.
selective, of alkali glass, P (6) 171*a*.
silicon carbide, P (11) 344*h*.
solution, and process for producing nonreflective surface on transparent glass, P (6) 170*i*.
for strengthening of glass, (5) 128*i*.
thermal, of NaCl cleavage faces in vacuum, (5) 159*b*.
vapor, of sapphire by H_2-$SiHCl_3$ gas mixtures, (4) 118*j*.
Europium, Eu^{2+}, ESR, in $KTaO_3$, (10) 320*e*.
Eu^{2+} and Eu^{3+} interconversion, in silicate glasses, (8) 234*c*.
(III) chloride, reaction with NaCl, (10) 324*f*.
$EuLiO_2$, transformation under very high pressure and at very high temperature, (1) 33*a*.
fluorescence in mixed metal oxides: III, energy transfer in Eu^{3+}-activated tungstates and molybdates of type Ln_2WO_6 and Ln_2MoO_6; IV, photoluminescent efficiency of Eu^{3+}-activated oxides, (10) 321*b*,*c*.
metal and monoxide, magnetic and structural properties at high pressure, (9) 284*i*.
oxide, Curie-point increases in, (11) 357*f*.
emission and excitation spectra, compared with Y_2O_3:Eu phosphor, (8) 253*e*.
reaction with chromium, (10) 324*h*.
systems. See *Systems*.
trivalent, energy levels, in YGaG, (3) 80*j*.
trivalent, Raman transitions, in YGaG, (11) 352*c*.
Eutectics, between compounds, microstructures, preferred orientation in, (9) 285*g*.
Evaporation, behavior, of neptunium dioxide, (4) 110*h*.
coefficient, of Al_2O_3, Ga_2O_3, In_2O_3, systematics, (7) 222*b*.
evaporator, for studying thermodynamic properties of refractory materials, (11) 346*j*.
of lanthanum hexaboride, (5) 138*i*.
rate, of aluminum oxide, discontinuity in, (5) 151*c*.
Excitation, plasma, in LiF, (11) 355*c*.
volume, of ultrathin continuous-wave CdSe laser at 6900 A output, (1) 17*g*.
Expansion. See also *Dilatometers*.
autoclave, of cements, small specimens for measuring, (8) 229*c*.
characteristics, of Indian sands, (6) 173*a*.
fission fragment induced, in refractory materials, (5) 132*e*.
of glass. See *Glass*.
measurements, in silica-titanium oxide-potassium oxide system, (11) 335*c*.
moisture, of fired clay bodies, relations with mineralogical and chemical composition, (10) 305*b*.
sulfate, of cements, further tests, (8) 228*d*.
thermal, of albite, low and high, (6) 190*b*.
anomalous, of α-ferric oxide, (6) 183*h*.
behavior, near ferroelectric transitions, (10) 319*d*.
clay, effect of lime, (9) 266*f*.
coefficient of vitreous silica, (3) 87*e*.
of copper oxides, (4) 114*b*.
of β-cristobalite, (3) 87*a*; discussion and reply, (6) 185*f*.
of glass fibers, (8) 234*e*.
of glasses in system Al_2O_3-TiO_2-P_2O_5, (10) 299*f*.
of Illinois limestones and dolomites, (4) 118*a*.
irreversible, (2) 54*b*.
linear, of graphitized carbons, (2) 43*j*.
linear, of ZrW_2O_8, Cr_3WO_6, and $2Al_2O_3 \cdot 5WO_3$, (5) 154*j*.
of lithia ceramics with β-eucryptite composition, effect of heat treatment, (8) 241*j*.
of niobium carbides, (5) 134*f*.
of PuC and UC-PuC solid solution, (5) 134*e*.
of refractories, apparatus for measuring, (9) 276*g*.
of rutile from 100° to 700°K, (4) 118*b*.
of rutile-type GeO_2 by X-ray method, (9) 288*a*.
of silica brick, (7) 202*d*.
of tantalum monocarbide to 3020°C, (6) 190*e*.
of thorium monocarbide, (10) 320*j*.
of uranium monocarbide-zirconium monocarbide solid solution, (6) 190*e*.
of vanadium carbides, (5) 134*g*.
of vitreous selenium from −190° to +30°C, (10) 326*j*.
Extraction, of alumina and removal of iron from Pennsylvania aluminous clays, (5) 147*j*.
behavior, of cerium-group lanthanides in primary amine-chelating agent system, (6) 182*g*.
high-temperature two-phase, technique for tungsten minerals, (9) 278*h*.
liquid, of molybdophosphoric and molybdoarsenic acids, (2) 54*b*.
liquid-liquid, in Na_2O-B_2O_3-NaCl system, (4) 112*j*.
method, for preparing UO_2 microspheres, P (5) 134*j*.
of selenious oxide from gas mixtures, P (10) 318*c*.
of sulfuric acid complexes of beryllium using primary amines, P (4) 105*b*.
Extrusion. See also *Dies*.
augers, measurements on, (10) 301*g*.
auger machines, (10) 311*i*.
of clay, effects, (2) 43*d*.
of clay and clay-graphite mixtures, (9) 267*a*.
clay-grog mixtures, investigation for use in, (10) 301*h*.
of future, (9) 275*e*.
high-energy-rate, of powder material, for consolidation and forming, P (10) 312*b*.
hot, of metallic articles, P (9) 265*c*.
hydrostatic, processes, P (8) 247*d*.
piston and auger, of clay, (2) 43*d*.
pug mill-, operation, (10) 301*h*.
raw material parameters determining, (10) 301*j*.
of refractories, (6) 172*i*.
shaping, vacuum, of ceramic materials, P (9) 275*h*.

Faraday, effect, at low temperatures in terbium alumina silicate glass, (6) 176*g*.
rotation, in InSb, (11) 353*f*.
interband, in perovskite oxides and rutile, (6) 186*c*.
in $KTaO_3$, (11) 352*i*.
Fatigue, tests, for materials, (10) 314*e*.
Faujasite, synthetic, containing exchangeable magnesium cations, preparation, P (5) 148*j*.
synthetic, with high silica to alumina ratio, process for producing, P (1) 25*j*.
synthetic, method of cation exchanging, P (7) 214*e*.
Feeding apparatus, for cone crushers, P (4) 105*b*.
for crushers, P (8) 251*b*.
dry chemical, P (4) 101*j*.
gyratory fluidized solids, P (3) 75*b*.
for solid materials into rotary kiln, P (3) 76*j*.
tile, for depositing tiles on tile boards, P (7) 206*j*.
vibratory, and conveyor systems, (10) 312*a*.
Feldspars, alkali, solvus, in system Na_2O-K_2O-Al_2O_3-SiO_2-H_2O, (5) 149*b*.
alkali Na-K exchange equilibrium, at 600°C under pressure of 1000 bars, (7) 218*i*.
authigenic, and cherts, resulting from illitic limestones dolomitization, (9) 279*i*.
etched plagioclase, electron microscopy, (1) 28*j*.
Finnish flotation, (4) 104*k*.
flotation: I, proposals for classification according to response; II, adsorption of ions on, in relation to response, (5) 143*j*,*f*.
kaolinization, (5) 148*g*.
Rajdhwari, fusion study, (10) 305*i*.
and silica liquid mixtures, structural characteristics, (6) 189*d*.
Ferric, Ferrous, etc. See *Iron*.
Ferric oxide. See *Iron, oxide, ferric*.
Ferric sulfate. See *Iron, sulfate, ferric*.

Ferrites. See also specific types.
$2CaO \cdot (Al_2O_3)_x \cdot (Fe_2O_3)_{1-x}$, Moessbauer effect, (9) 284*a*.
and ceramic magnetic components, precision finishing, (2) 50*b*.
cores, fired, continuous process of preparing, P (7) 208*j*.
fluid-cooled, P (7) 208*k*.
manganese-ferrous, P (7) 208*f*.
process controls in manufacturing, (3) 72*b*.
processing and control in manufacture, (7) 207*j*.
crystallized from glass, (10) 307*j*.
cubic lithium, with high upper frequency limit, P (10) 309*j*.
dense nickel-zinc, and use in magnetic heads, (4) 98*k*.
development and production in India, (6) 176*i*.
device, nonreciprocal, with thin dielectric layer encircling ferrite element, P (2) 52*a*.
formation, by hydrothermal method: I, nickel ferrite, (9) 286*i*.
hard, future, (11) 342*g*.
hexagonal, Zn_2Y, anisotropy of dc and high frequency resistivity of, (4) 106*a*.
iron-cobalt, relaxation theory of uniaxial anisotropy induced by ionic migration in, (10) 326*h*.
lead, Ferriroll process for forming into permanent magnets, (3) 71*i*.
lithium, vanadium-containing, P (6) 179*a*.
lithium nickel for magnetic core, P (7) 209*b*.
$M_{1-x}Li_xFe_2O_{4-x}F_x$, magnetic properties, (7) 219*e*.
Mg-Mn and zinc and cadmium substituted Mn-Mg, effects of annealing conditions on magnetic properties of, (9) 271*i*.
manganese ferrous, low frequency magnetic relaxations at low temperatures in, (3) 71*h*.
Mn-Zn, crystals growth, (8) 252*c*.
magnetic properties, effect of Cd-for-Zn substitution, (10) 307*b*.
metallographic study, (9) 272*d*.
method for introducing calcium oxide into, P (7) 209*f*.
study by Moessbauer effect of intermediate phases in formation of, (1) 32*e*.
metallic, treatment, P (9) 275*c*.
Ni and Ni-Zn, containing excess iron and small amounts of Co, temperature variation of initial permeability in, (8) 257*f*.
nickel-zinc, tantalum doped, P (1) 19*a*.
phase shifter with longitudinal and circular magnetic fields applied to ferrite, P (8) 244*c*.
plate, manufacture, P (7) 209*d*.
precision machining for computer components, (6) 176*h*.
relations among porosity, grain size, and chipping resistance, (9) 286*f*.
scandium-containing, magnetic properties, causes of transformation of, (1) 16*b*.
sintered, pores in, (9) 272*e*.
soft, kiln for sintering, (5) 138*b*.
manufacture from mineral iron ore, (8) 243*c*.
solve magnetic core problems, (8) 243*d*.
spinel, hexagonal, and garnet, structures, properties, and compositions, (9) 272*a*.
of spinel type, X-ray diffraction study of formation mechanism of, (10) 327*c*.
Ferroelectric materials. See also *Barium, titanate; Ferroelectricity*.
barrier-free contacting, P (2) 50*f*.
body, with antiferroelectric substances, P (5) 141*a*.
ceramics, doctor-bladed, processing parameters and electric properties, (1) 16*d*.
in electron microscope, (11) 342*e*.
sintering by hot-pressing, and electrical properties, (11) 342*g*.
in system PbO-Nb_2O_5, (11) 342*f*.
crystallized from glass, (10) 307*j*.
electron-mirror microscope analysis of surface potentials on, (9) 281*j*.
perovskite-type, single-oscillator model of "sift-mode" lattice vibration in, (4) 115*g*.
piezoelectrically activating, P (4) 100*f*.
possible species of, (11) 355*d*.
$KNbO_3$-$AgNbO_3$, electrical, X-ray, and thermal expansion studies, (1) 16*e*.
process for optionizing electrical and physical characteristics of, P (1) 18*j*.
Ferroelectricity. See also *Barium, titanate; Ferroelectric materials*.
-to-antiferroelectric phase transitions, thermodynamics relations with composition, (11) 343*b*.
domain width, in thin crystals $BaFe_{12}O_{19}$ and $SrFe_{12}O_{19}$, thickness dependence of, (3) 88*j*.
domains, in barium titanate, scanning electron microscopy of, (1) 16*g*.
domains, high field, in n-type CdS, (4) 111*f*.
ferroelectric, photo-, effect in SbSI, (3) 71*b*.
field, of $BaTiO_3$ as measured by electron diffraction, (5) 138*j*.
perovskite, chemical shifts of ^{207}Pb in, (5) 137*i*.
properties, of ceramics of type $Ba_{1-x}Sr_xTiO_3$, (6) 176*f*.
of lead titanate, (11) 352*i*.
of $KSr_2Nb_5O_{15}$, (6) 176*i*.
random dilute, dipole correlations in, (8) 253*a*.
sensors, solid state PTC, production, P (2) 52*b*.
statistical theory, based on concept of ferroelectric modes of lattice vibration, (10) 325*d*.
structure, of $BaTiO_3$, revealed by electron-beam technique, (5) 138*j*.
Ferromagnetic materials. See also *Ferromagnetism*.
P (6) 177*i*.
anti-, $CsMnF_3$, direct observation of ^{55}Mn NMR in, (9) 281*c*.
crystals, transparent single, method of preparing, P (7) 209*b*.

Ferromagnetic materials (*continued*)
$(La_{1-x}Sr_x)MnO_3$, ^{139}La and ^{55}Mn NMR signals from, (10) 322*a*.
metal oxyfluorides, P (5) 141*h*.
$NiMnO_3$, preparation, P (8) 245*j*.
rare earth compound consisting of Gd_2Bi, Gd_2Sb, or Dy_2Sb, P (1) 17*i*.
rings or cylinders of, apparatus for manufacturing, P (5) 140*b*.
$YFeO_3$, parasitic, motion of single domain wall in, (3) 83*b*.

Ferromagnetism. See also *Ferromagnetic materials; Magnetic materials*.
anti-, band, and perovskite, $CaCrO_3$, (11) 341*k*.
domain walls, of NiO-type crystals, spin configuration in, (4) 116*d*.
in face-centered cubic lattice: I, random-phase Green's function approximation; II, magnetic properties of MnO; III, α-MnS, (8) 252*c*.
linear, in $ZnMn_2O_4$, (10) 323*a*.
in $LiFePO_4$, (9) 279*h*.
of V_2O_3 observed by Moessbauer effect, (4) 106*d*.
domain structure, in hematite, (1) 29*d*.
ferromagnetic cores, ceramic, for inductors and transformers, P (7) 208*k*.
ferromagnetic storage devices with uniaxial anistropy, P (10) 309*e*.
Green's-function theory of, with application to magnetite, (10) 321*d*.
induced parasitic, in $(La_{0.9}Bi_{0.1})CrO_3$, (3) 81*i*.
phases in products of thermal decomposition of nickel ferricyanide, (10) 321*d*.
trace, in zeolites, (3) 88*h*.
in zircon, source, (1) 16*j*.

Fibers, aluminum and chromium sesquioxide, preparation, P (10) 304*i*.
Al_2O_3-B, composite material, P (8) 240*j*.
carbon, metal carbide formation on, P (3) 68*j*.
carbon, and method, P (2) 46*f*.
carbon/graphite, high modulus, new in fiber-reinforced plastics race, (8) 237*e*.
ceramic, composites, (11) 332*f*.
contact angles on, measuring method, (9) 276*f*.
continuous and discontinuous, applications, chemical composition, design aspects, and testing as composites, (2) 56*e*.
dielectric, electrostatically applied, as spacer pads and gaskets on insulator, P (10) 310*a*.
energy-conducting devices, apparatus for making, P (11) 335*e*.
faceplates, sealing porosity by yttrium resinate, P (7) 199*a*.
glass. See also *Mineral wool*.
apparatus for forming, P (6) 170*b*.
bushing, silicon carbide, and method of making, P (2) 42*c*.
ceramic, highly refractory, acceleration of crystallization by salt treatment, (8) 230*d*.
coated, P (7) 198*e*.
colored, compositions and production methods, P (9) 264*j*.
composition, P (4) 94*a*.
continuous drawing, (10) 297*a*.
of different composition, properties, (6) 168*i*.
drawing and coating for battery plates, P (2) 41*d*.
E-, effect of environment and temperature on strength: I, high vacuum and low temperature, (7) 196*k*.
-elastomer systems, structures formed of, P (9) 266*a*.
-elastomeric systems, treated with mercaptan-containing organo silane anchoring agents, P (4) 94*b*.
elements, for energy-conducting components, P (2) 41*e*.
filter fabrics, endurance, (6) 167*d*.
formation processes, (10) 298*a*.
heat treatment method, P (2) 41*c*.
high temperature fibrous board, P (2) 41*b*.
internal friction, comparison with glass rods, (10) 297*e*.
ion exchange, P (8) 235*c*.
manufacture in blast nozzles, (8) 234*c*.
material, radiation process of deforming, P (5) 130*d*.
material, sized, P (5) 130*f*.
mats, P (3) 65*h*.
method to impede transmission of radiant energy to and from, in forehearth, P (10) 301*b*.
notched composite columns, carrying capacity and fracture of, (10) 297*d*.
oriented sodium metaphosphate, structure, (5) 128*h*.
package, resin coated wound, impregnation and partial polymerization of, P (8) 235*b*.
problem of strength, (10) 298*i*.
production, P (1) 9*g*.
products, manufacture, (5) 127*d*.
resin bonded, apparatus for forming continuous helical coils of, P (7) 198*a*.
-resin composite model, discontinuous, matrix and interface stresses in, (10) 298*a*.
-resin coupling compositions for, P (5) 130 *h*.
silicate, EPR in, (2) 39*f*.
spun, influence of drawing-off force on flow rate and diameter, (5) 127*e*.
surfaces, examination with scanning electron microscope, (8) 231*j*.
testing strength, (11) 335*j*.
thermal expansion and structure, (8) 234*e*.
and like thermoplastic material, method for production, P (1) 9*f*.
treated for combination with elastomeric materials, and method, P (10) 300*a*.
treatment, P (7) 199*b*.

Fibers, glass (*continued*)
yarn, apparatus and process, P (9) 264*k*.
yarn, high strength-high temperature, P (5) 130*b*.
yarn, method for processing, P (2) 41*k*.
graphite, silicon carbide, and beryllium, for use in structural plastic composites, (9) 269*j*.
high-emissivity, radiant heat transfer in, (5) 133*a*.
length distribution, methods for measuring, (3) 75*i*.
$MgAl_2O_4$, growth, (2) 59*b*.
$MgAl_2O_4$, and platelets, (2) 59*b*.
magnesium oxide, method of making, P (6) 174*i*.
mat, method for producing, P (8) 235*i*.
metal oxide-metal sulfide plural coated siliceous, method of preparing, P (6) 175*a*.
mineral, apparatus for manufacturing, P (10) 300*a*.
comparative survey with whiskers, (11) 338*d*.
forming process, waste wash water and waste binder reuse system and apparatus for, P (3) 66*e*.
method and apparatus for producing, P (6) 171*c*.
preparing from by-product slag of phosphate furnace, P (4) 97*i*.
production, P (6) 171*a*.
for reinforcing hardened cement, (2) 37*b*.
of natural and synthetic amphibols, effect of heat treatment on mechanical properties, (2) 44*a*.
optic device, quantum counters, P (7) 199*f*.
optic member, for light transfer, P (1) 8*i*.
optic readout device, and method of making, P (7) 208*g*.
optic strip, single layer, method of fusing, P (1) 9*c*.
optics, properties and uses, (10) 297*e*.
optics scan system, P (9) 265*c*.
optical, devices, making fine adjustment in numerical aperture of, P (11) 336*g*.
electroluminescent-photoconductive image intensifier, P (5) 142*j*.
frequency harmonic generating structure, P (11) 336*d*.
image transfer devices, apparatus for making, P (6) 170*d*.
image-transfer devices, method for making bubble free, P (3) 65*h*.
for optical purposes, (6) 167*f*.
orientation, effect on tensile strength of fiber-reinforced metals, (1) 4*b*.
parallel light, with longitudinal axes making oblique angle with display surface of cathode-ray tubes, P (4) 100*i*.
refractory, composition, P (2) 42*a*.
refractory metal nitride, flakes, and foil, method of making, P (6) 174*j*.
-scopes, method of making, P (8) 235*h*.
sheets, phosphoric acid bonded asbestos, and manufacture, P (8) 241*e*.
silica, method for preparation, P (3) 65*j*.
silica, reinforcement of aluminum, (8) 229*j*.
siliceous, treatment with aqueous mixtures of unsaturated polyimidazoline anchoring agents, and article, P (7) 199*d*.
silicon carbide, macroscopic, method of making with silica sheath, P (6) 174*h*.
silicon carbon, article containing, P (9) 270*a*.
single and multi-, interactions in discontinuously reinforced composites, (6) 181*e*.
from solidified phosphorus-furnace slag, P (4) 97*j*.
for strong, light composites, (3) 63*d*.
synthetic, guides, made of sintered corundum, (10) 299*e*.
from viscous melt, method of preparing, P (3) 66*a*.
zirconium carbide, preparation and product, P (8) 241*c*.

Filaments. See also *Fibers, glass*.
boron, protective coating by surface nitridation of, (10) 303*g*.
boron-tungsten boride, mechanical properties, (4) 96*f*.
carbon and graphite, producing coatings on, P (5) 136*c*.
fine short, tensile properties, testing apparatus, P (7) 213*b*.
glass, spinning, P (1) 10*a*.
glass, tape, P (10) 300*a*.
high-strength, reinforced composites, fracture mechanisms applicable to, (10) 303*a*.
mono-, inorganic oxide, method of spinnerette cleaning during preparation of, P (8) 247*e*.
multi-, strands, integrated body of, P (10) 300*d*.
refractory coated, deposition chamber for manufacture, P (5) 134*h*.

Films, aluminum, vacuum-deposited, thermal oxidation, electron microscopic observation on, (11) 352*j*.
aluminum nitride, by chemical transport, (11) 350*g*.
Al_2O_3, large-area planar and non planar, (4) 98*i*.
amorphous alloy, characterization, (7) 216*b*.
amorphous boron, (6) 176*a*.
amorphous dielectric, electronic properties, (11) 342*a*.
anodic alumina, recrystallization, (4) 115*d*.
anodic oxide, heat treatment on tantalum: IV, anodization in phosphoric acid solutions, (7) 207*b*.
anodized aluminum oxide, of high dielectric strength, properties, (3) 86*f*.
$BaTiO_3$ single crystals, on LiF, {111} twin in, (10) 326*j*.
of boron carbide, preparation, P (11) 345*a*.
CdS and CdSe, vacuum deposited, preparation and properties, (5) 139*a*.
chromium oxide, reactively evaporated, optical properties, (3) 84*g*.
Cr-SiO cermet, resistivity and structure, (5) 139*e*.

Films (*continued*)
dielectric layer, vacuum deposition, (5) 140*f*.
epitaxial, of UO_2, fission fragment damage in, (4) 110*b*.
gas, between plasma jet and cooled surface, characteristics, (7) 221*h*.
germania, method for growing, P (1) 18*a*.
germanium, vacuum-deposited, on polycrystalline Al_2O_3 substrates, (5) 140*j*.
glass, apparatus for forming, P (5) 129*i*.
glass, inorganic, preparation, properties, and uses, (11) 334*f*.
high brightness luminescent evaporated, P (1) 18*b*.
indium sulfide, evaporated, dielectric properties, (10) 308*a*.
insulating, gas-phase deposition, B (8) 260*e*.
insulating, on silicon, polarization effects in, (10) 307*j*.
iron oxide, on glass, mechanical properties, (10) 298*d*.
PbS, monocrystalline, photosensitivity in, (10) 307*i*.
p-type single-crystal, photoconductivity in, (4) 114*f*.
polycrystalline, interpretation of Hall effect data in, (6) 176*b*.
metal oxides, epitaxial growth, (9) 271*j*.
metal and semiconductor oxide, thermal growth, transport processes in, (10) 309*c*.
nickel, chemisorption and incorporation of oxygen by, (3) 79*f*.
nickel, improved in rock salt substrates due to electron bombardment, (11) 342*i*.
oxide, embrittlement on Zr by neutron irradiation, (10) 320*i*.
formed on copper-nickel alloys, (11) 356*h*.
on silicon, (1) 16*b*.
structure and morphology during initial stages of titanium oxidation, (10) 325*d*.
passivating vitreous, for semiconductor devices, P (1) 19*c*.
phosphosilicate glass, on silicon, polarization phenomena and other properties, (7) 207*f*.
phosphosilicate glass, on silicon dioxide, (10) 307*a*.
polycrystalline, means for controlled deposition and growth in vacuum, P (6) 177*h*.
refractory oxide, labeled, preparation, (10) 315*i*.
semiconducting, on eucryptite glass-ceramics, (8) 234*b*.
silicon carbide, epitaxial growth on silicon substrate and crystal structure, (11) 352*d*.
silicon heteroepitaxial, grown on sapphire, space-charge-limited currents in, (5) 158*g*.
SiO_2, chlorine content determination by X-ray spectral, (10) 327*e*.
deposited from SiH_4 and O_2, preparation and properties, (10) 308*c*.
deposition on germanium by carbon dioxide process, (7) 207*d*.
doped with phosphorus, (7) 208*b*.
fast etching imperfections in, (7) 207*b*.
formation by oxygen-ion bombardment, (9) 282*a*.
grown under bias, improved properties, (7) 207*d*.
growth, (8) 254*f*.
by oxidation of silane, (10) 308*f*.
on silicon, reflectivity thickness corrections for, (11) 356*d*.
space-charge-limited ionic currents in, (1) 17*a*.
tritium-labeled field-induced proton transport in, (11) 357*h*.
silicon nitride, reactively sputtered, evidence of excess silicon in, (11) 352*g*.
silicon oxide, evaporated, structure and effect on electrical and optical properties, (10) 308*d*.
structural evaluation, (4) 116*a*.
and nitride, deposited by rf glow discharge, (10) 308*h*.
Si and SiO_2, deposited through rf and dc sputtering, re-emission coefficients, (5) 139*b*.
silicon-on-sapphire, donor surface states and bulk acceptor traps in, (5) 151*d*.
Si-Ta_2O_5, prepared by reactive sputtering, (9) 283*i*.
single-crystal, of cubic silicon carbide, growth on silicon, (5) 153*c*.
gold, tensile behavior, (5) 159*e*.
high-purity gold and silver, epitaxial growth on MgO cleaved in ultrahigh vacuum, (5) 152*e*.
method of making and product, P (10) 310*c*.
orienting on polycrystalline substrates, P (6) 178*i*.
single-crystalline of silicon, vacuum deposited on sapphire, (10) 309*e*.
sputtered, of controlled specific resistivity and temperature coefficient of resistance, P (11) 344*f*.
tantalum anodic, activation energies of conduction in, (8) 242*i*.
tantalum oxide, sputtered, photoconduction and trapping in, (3) 72*a*.
thermal and anodic SiO_2, mutual transformation, (11) 354*h*.
thick-, automatic production, (6) 176*a*.
capability, Beckman Instruments', (11) 341*j*.
on crossover dielectrics, (7) 207*e*.
measurement, (4) 103*e*.
molybdenum, on beryllium oxide, thermal conductivity, (10) 308*j*.
-thickness and deposition-rate monitoring devices and techniques for producing films of uniform thickness, B (8) 260*d*.
thin, alumina, reactively sputtered, phase changes in, (11) 355*f*.
of cadmium sulfide, cadmium telluride, or cadmium selenide, P (4) 101*c*.
cadmium sulfide, surface properties, ultrahigh vacuum system for preparation and study, (5) 140*i*.

Films (*continued*)
Cr-SiO, sheet resistance control, (11) 342*d*.
of II-VI compounds, methods of activating and recrystallizing, B (8) 260*f*.
condensed, mechanical properties, B (8) 260*f*.
depositing, by cathode sputtering using controlled grid, P (4) 100*j*.
deposition by cathode sputtering, B (8) 260*e*.
deposits, nucleation and initial-growth behavior, (8) 255*j*.
dielectric, single carrier transport in, (11) 342*f*.
formation, P (5) 141*h*.
GaAs, photoemission from, (8) 243*i*.
of glass, P (7) 209*i*.
InSb, growing on InSb substrate from saturated In-InSb melt, (7) 208*c*.
magnetic, originating from nonmagnetic grain boundaries, estimation of perpendicular anisotropy, (3) 80*j*.
manufacture, (3) 72*g*.
measuring thickness of, (10) 307*d*.
metallic, capable of sorbing residual gases, production within electron tubes, P (9) 274*g*.
method for mounting without substrates, (1) 22*a*.
monocrystalline, manufacturing, P (8) 244*j*.
physics, advances, in research and development: Vol. 3, B (8) 260*d*.
removing from vitreous surfaces, P (6) 171*d*.
silica, refractive index, determination by simple immersion method, (11) 347*i*.
SiO_2, thickness measurements, (11) 356*c*.
silicon, deposition on sapphire in ultrahigh vacuum, (10) 306*j*.
SiO, dielectric constant and conductivity, (5) 150*i*.
single crystal, method and apparatus for preparing, P (2) 51*g*.
structure, biaxially anisotropic magnetic, with magnetic discontinuities, P (11) 343*g*.
of sulfospinels, preparation, (4) 114*b*.
Ta_2O_5, density and dielectric constant, (3) 79*j*.
theoretical study of sensitivities of normal incidence methods for measuring optical constants and thicknesses, (6) 190*a*.
and thick, techniques, hybrid circuits in, (10) 307*c*.
ultra-, Al_2O_3 support, for electron microscopy, (1) 23*j*.
vanadium dioxide, reactively sputtered, (4) 115*b*.
of $Zn_xCd_{(1-x)}S$, structural and optical properties, (7) 208*c*.
ZnO, spectral sensitization with organic dyes, (3) 72*e*.
of zinc sulfide, dc electroluminescence in, (8) 252*h*.
zirconia, obtained by oxidation of Zr, electron microscopic observations, (4) 109*i*.
tin oxide, doped and undoped, prepared by reactive sputtering, devitrification of, (4) 107*i*.
tin oxide, with minimum absorption, optimum temperature conditions for obtaining, (8) 243*h*.
TiO_2, amorphous, prepared by vacuum evaporation, crystallization, (7) 210*b*.
uniform thick metal, activation of glass for electroless metal deposition of, P (6) 170*a*.
VO_2, for infrared imaging, P (5) 141*b*.

Filters, apparatus, P (4) 102*a*.
automatic chamber pressure, P (1) 20*c*.
cathode-ray tube, method for making, P (4) 95*b*.
drum, element attaching means, P (3) 78*b*.
fabrics, fiber glass, endurance of, (6) 167*d*.
glass, and method for production, P (1) 8*j*.
high resolution, for laser-emissive energy, P (6) 177*d*.
horizontal rotary vacuum, method of increasing capacity, P (7) 211*d*.
light, vitreous off-axis, method of making, P (8) 235*i*.
press, P (4) 102*b*.
rotary drum, P (1) 20*f*; P (4) 102*b*.
sharp cutoff, fluorescence spectra, (5) 145*b*.
supported metal, process for making, P (3) 69*g*.
traveling belt type drum, P (3) 75*c*.

Filtration, P (7) 211*b*.
compressible cake, equation for, (1) 10*k*.
dynamic, of slurries, method and apparatus, P (7) 211*c*.

Fine ceramics. See *Whiteware*.

Firebrick. See *Refractories*.

Fireclay. See *Refractories*.

Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering*.
bisque, basic requirements, and control of bisque losses, (1) 15*a*.
in brickmaking, (10) 301*k*.
ceramic blanks containing organic plasticizers in combustible adsorbents, (3) 76*j*.
ceramic, process: I, formation of water in lattice of clay minerals; II, dehydration of lattice of clay minerals, (7) 215*k*.
ceramic ware, natural gas fulfills requirements for, (8) 249*g*.
damage, during cooling, origin, (6) 175*f*.
direct, of vitreous enamel, (4) 92*k*.
enameled copper, (8) 229*g*.
gas, of ceramic kilns, impulse, (10) 316*j*.
gas, natural, in cross-fired glass melting furnace, (5) 128*b*.
of glass powder, (1) 7*f*.
jet, high velocity, P (11) 348*e*.
laboratory investigations with direct application to industrial practice, (1) 24*d*.
oil, advances, (6) 181*j*.
equipment, developments for ceramic industry, (5) 147*f*.
of glass melting furnaces, (11) 348*f*.
of white wall tile, (7) 213*g*.

Firing (*continued*)
in porcelain industry, (7) 206*a*.
problem, investigating, (9) 277*c*.
of quartz-glass shapes, processes, (6) 168*h*.
radiation vs. convection, (2) 55*j*.
rapid, to suit operation and materials, (5) 136*g*.
re-, of alumina ceramic bodies, (9) 272*d*.
rotary kiln, method to avoid firing rings, P (8) 240*h*.
of salt-glazed Alsatian stoneware with propane, (3) 70*h*.
of sanitary ware, (5) 136*j*.
simulated town-gas, (7) 213*j*.
single and double, of whiteware, (9) 271*f*.
structural ceramic mass, with electric current, P (11) 337*b*.
tunnel and ring kiln, techniques, (10) 317*d*.

Flaws. See *Defects*.

Fission fragments, damage, in BeO, ThO_2, Al_2O_3, direct observation, (9) 281*b*.

Fission products, solid, in irradiated UO_2, (11) 339*f*.

Flame photometry. See *Photometry*.

Flames. See also *Burners; Firing*.
precision control, (8) 249*h*.
research, and glass melting, (8) 232*c*.
vibrating diffusion, effect of combustion time on appearance of, (8) 249*e*.

Flint, hot-worked and annealed, X-ray fabric analysis, (2) 60*a*.

Flotation. See also *Beneficiation*.
continuous, of fluorspar from calcareous Illinois ore, (1) 19*g*.
correlation with surface phenomena in silicates, (7) 214*c*.
of fly ash constituents, (6) 165*c*.
and non-, of quartz with ascorbic acid, (5) 143*g*.
selective, of beach sands—sillimanite, zircon, and rutile, (1) 25*f*.
for separating catalyst particles into fractions of differing surface area, P (4) 105*h*.
of silicates: I, proposals for classification according to response; II, adsorption of ions on feldspar in relation to response, (5) 143*j,f*.

Flow, control, in vertical shaft kiln, P (10) 296*c*.
fluid, in porous media, effects of ultrasonic energy, (1) 21*h*.
of glass, modern concepts: IV, theory, (2) 39*h*.
hydromagnetic, due to torsional oscillations of porous infinite plate, (10) 321*j*.
isothermal laminar, of non-Newtonian fluids in pipes, (9) 275*j*.
Newtonian, of simple silicate melts at high temperature, (5) 128*d*.
parameters, of gases and liquids in porous sintered materials, (1) 22*e*.
patterns, of extruded clay, (2) 43*c*.
patterns, in glass tank, determination by tracers, (11) 333*d*.
in porous bodies, determination, (10) 317*g*.
process in extruder, (7) 190*h*.
rates, small to large, measured by new meter, (2) 55*c*.
slow viscous, past cavity, (10) 325*i*.
Stokes, motion of deformed drop in, (10) 323*f*.
viscoelastic capillary, pressure loss due to elastic energy for, (11) 355*d*.

Flue gases. See *Gases*.

Fluids. See also *Liquids*.
non-Newtonian, designing, for: I, II, rheology III, instruments for viscometry; IV, isothermal laminar flow in pipes, (9) 275*j*.
simple dense, B (9) 290*g*.
van der Waals, in two-phase region, thermodynamic properties, (3) 87*j*.

Fluorescence, of $ATiNbO_6$, $ATiTaO_6$, and $ATiSbO_6$, (1) 27*c*.
brightness and color, measuring method, (7) 212*f*.
of doped fused silica, for determination of hydrogen diffusion, (7) 195*j*.
in emerald, (3) 78*g*.
Eu^{2+}, efficiency in oxygen-dominated host lattices, (3) 80*f*.
Eu^{2+}, in mixed metal oxides: III, energy transfer in Eu^{2+}-activated tungstates and molybdates of type Ln_2WO_6 and Ln_2MoO_6; IV, photoluminescent efficiency of Eu^{2+}-activated oxides, (10) 321*b,c*.
glass standard for, (3) 63*i*.
intensities, in rare earth doped Y_2O_3 and LaF_3 single crystals, (10) 324*b*.
of lanthanide gallium borates, (5) 150*b*.
nondispersive X-ray, for determination of zirconium in zirconium-bearing sand and zirconium concentrates, (4) 102*i*.
nuclear, for measuring coating weight, (9) 276*f*.
properties, of terbium-activated alkaline earth alkali borates, (4) 110*b*.
sensitized, of CaF_2 (Ce,Mn), saturation effects in, (8) 256*h*.
sensitized, in $Ca(PO_3)_2$:Sn:Mn glass phosphors, (11) 356*c*.
X-ray, in chemical analysis, B (7) 224*c*.

Fluorides. See also *Glass*.
active, in acid solution, analytical determination, P (10) 316*g*.
adsorption, by thorium oxide in aqueous thorium nitrate solutions, P (11) 340*c*.
conversion, into chlorides, bromides, or iodides, (5) 150*i*.
divalent metal doped, as optical maser material, P (8) 244*j*.
hydrogen, and solubilized beryllium, producing, P (7) 214*i*.
perovskite, cubic, electronic absorption spectrum of Ni(II) in, and concentration and exchange effects, (7) 217*k*
trace, determination with specific ion electrode, (10) 316*a*.

Fluorination, fluorinating agents, spheroidal, containing calcium fluoride suitable for fluid beds, and product, P (6) 183*a*.

Fluorine, balance and emission from cement kilns, (8) 228*c*.
determination in minerals and rocks, (8) 248*g*.
fluidized bed disposal, (1) 11*j*.
in silicate and phosphate rocks, micas, and stony meteorites, (10) 313*j*.
small amounts, determination in rocks and minerals, (5) 145*a*.
substitution in YIG, (3) 87*g*.

Fluorite, deposit at Hingoria, Broach, Gujarat State, (10) 317*j*.
spectrochemical determination of Al, Fe, and Si in, (3) 76*f*.
structures, anharmonic vibration in, (9) 279*i*.
synthetic, thermoluminescence, (5) 140*d*.
thermoluminescence, (9) 288*d*.

Fluorspar, continuous flotation from calcareous Illinois ore, (1) 19*g*.
in eastern United States, (3) 77*h*.
in Rajastan, (9) 278*h*.

Fluxes, arc welding, P (10) 296*f*.
fluxing pipe, P (7) 195*c*.
low-melting, for Al and its alloys, (7) 195*h*.
stannous chloride, for fusing GaAs, and method of making and using, P (9) 273*a*.

Fly ash. See *Ash*.

Foam, and foil, boron-pyrographalloy, preparation, (5) 133*e*.
high-strength carbon, P (9) 270*b*.
inorganic, preparation from alkali metal silicates and aluminum, P (11) 340*g*.
sodium silicate, compete with plastics, (4) 96*g*.

Forming, apparatus, for large carbonaceous bodies, (6) 174*i*.
apparatus, magnetic device, and method of making deep grooves on parts made of conducting materials, P (2) 47*e*.
of glass bonded transducer heads, P (5) 141*h*.
hydro-, process with mordenite, alumina, and platinum catalyst, P (7) 214*e*.
of plastic bodies, relation to rheological properties, (5) 146*h*.

Forsterite. See also *Refractories*.
lapping characteristics, using diamond abrasives, (5) 123*g*.
lapping characteristics, using ordinary abrasives, (5) 123*i*.
from Spanish serpentines: III, action of mineralizes on serpentines of Barranco de San Juan (Granada), (10) 317*g*.
synthetic, (1) 25*g*.

Fractionation. See *Separation*.

Fracture, of brittle materials, thermal shock in, statistical analysis, (11) 357*c*.
of carbide-cobalt hard metals, under impact loads, (5) 131*g*.
in ceramics, (2) 55*g*.
crack-branching, in sapphire and glass, (5) 126*h*.
energy, of polycrystalline BeO, (11) 353*b*.
fractography, to predict metal failures, (3) 76*h*.
in glass blocks produced by impact, (1) 7*h*.
of glass, modern concepts: IV, theory of flow, (2) 39*h*.
initiation, at sharp notch, (9) 282*c*.
laser-induced, in glass, (6) 167*g*.
mechanisms in alumina and beryllia, revealed by DCB test, (11) 346*c*.
mechanisms, applicable to advanced filament reinforced composites, (10) 303*a*.
of notched glass fiber composite columns, (10) 297*d*.
patterns, geological gulf coast, experimental analysis, (9) 282*i*.
in photo glasses, growth and branching of cracks, (5) 127*b*.
in polycrystalline graphite, (7) 201*i*.
propagation rate, in porcelain, (1) 15*f*.
of quartz, at atmospheric pressure, (4) 114*g*.
of tempered glass, (3) 63*i*.
in tempered glasses, secondary processes, (7) 197*g*.
toughness, of EGCR-type graphite, (2) 43*i*.

Freeze-drying. See *Drying*.

Freezing, on of zirconium boride thermocouple sheaths, (2) 44*j*.
points, of lanthanide oxides measured with solar furnace, (4) 110*c*.
points, of water in glass capillaries, (11) 353*c*.

Freezing and thawing, tests. See *Frost resistance*.

Frequency, high, treatment, of materials, method and apparatus, P (9) 278*a*.

Friction, between glass containers, measurement of effect of surface coatings on, (5) 127*j*.
dynamic, measured fast, accurately, (3) 75*i*.
internal, of cold-worked niobium and tantalum containing oxygen and nitrogen, (10) 322*f*.
comparison between fiber glass and glass rods, (10) 297*e*.
of glasses in system Na_2O-BaO-SiO_2, (1) 6*f*.
of ion-exchanged glasses, (6) 167*b*.
of sodium silicate glass after ion exchange, (11) 334*g*.
studies, empirical determination of background in, (3) 80*i*.
and structure of glass, (10) 297*k*.
of synthetic quartz crystal, method of testing by two different frequencies of infrared, P (2) 51*h*.
in vibrating granular reeds and application to vitreous silica, (9) 283*g*.

Frits, composition, effect on set stability, (9) 262*j*.
method of applying uniform thickness of, on semiconductor wafers, P (6) 177*i*.
porcelain enamel, selection, (9) 263*c*.
porcelain enamel, viscosity, (9) 263*d*.

Frost, damage, on earthenware wall tile, (7) 206*a*.

Frost resistance, of brick effects of manufacturing processes on, (10) 301*g*.
Fuel elements, with activated carbon, P (3) 68*c*.
ceramic, for gas-cooled nuclear reactor including metallic fuel container provided with oxidation resistant coating, P (4) 97*c*.
coolant channels, devices to measure, (9) 277*a*.
of fissionable oxide and burnable poison, method of preparing, P (4) 97*a*.
moderator-, P (1) 13*b*.
nuclear, annular pellet, refractory cores for, (4) 96*c*.
ceramic, P (1) 13*j*.
of cermet and ceramic, P (7) 204*h*.
clad ceramic, with axial void, P (7) 204*i*.
components, inspection by phase sensitive eddy current instrument, (7) 211*i*.
of dispersed-in-graphite type, process for preparing, P (1) 14*c*.
high temperature, P (1) 12*i*.
matrix-type, including fission product retentive materials, P (2) 47*f*.
reactor, P (1) 12*f*; P (2) 47*e*; P (3) 68*d*; P (7) 204*c*; 205*f*.
reactor, for rocket motor, P (7) 205*b*.
selective decladding, P (1) 14*c*.
sintered uranium dioxide, containing boride, method of producing, P (2) 47*a*.
spherical, apparatus for forming hollows in, P (7) 204*e*.
urania, high density, P (1) 12*h*.
UO_2 and UC, behavior of inert gases in, (11) 337*g*.
Fuels. See also *Ash, fly; Coal; Combustion; Gases; Oil.*
BeO-based, development of coated fuel particles for, (4) 96*b* based dispersion, behavior, (2) 57*h*.
-based, effects of irradiation on, (3) 67*c*.
dispersion, effects of fission product damage in, (4) 96*b*.
-UO_2, dispersion-type, for EBOR, irradiation effects on, (4) 96*f*.
carbide, modified, P (1) 13*b*.
cells, cerium oxide-lanthana as solid electrolyte, (7) 207*g*.
high temperature, ternary metallic oxide agglomerate for preparation of, P (6) 175*c*.
molten carbonate electrolyte, (4) 116*g*.
with packed catalytic substance, P (4) 100*a*.
with platinum-rhodium containing catalyst, P (4) 105*c*.
with solid stabilized ZrO_2 electrolyte, (2) 51*b*.
ceramic nuclear, measurement of thermal conductivity at highest temperatures, (1) 11*f*.
changing pattern in, (3) 76*i*.
efficient utilization, application of measurement and control techniques for, (1) 24*b*.
gas, and tophats, for use in British pottery industry, (6) 181*j*.
materials, molten $(U,Pu)O_2$, plutonium distribution in, (7) 202*e*.
natural gas, use in silicate industry, (6) 182*a*.
nuclear, aspects of void migration in, (7) 203*f*.
bodies, forming, P (1) 13*j*.
ceramic product, method of fabricating, P (3) 69*b*.
coating procedure, (7) 200*e*.
doped hypostoichiometric dioxide, composition and method of preparation, P (6) 174*b*.
high density beryllia-, containing additive for retention of fission products, P (5) 135*e*.
irradiated, recovery, P (4) 97*f*.
oxide, containing boride, method of making, P (6) 174*j*.
particles, coated, consolidated in graphite matrix, dispersion and breakage by hot-pressing, (11) 337*j*.
particles, coated with pyrolytic graphite, P (4) 97*f*.
particles, for high-temperature gas reactors, preparation and properties, (6) 173*j*.
particles, low-density pyrolytic-carbon coatings for, (2) 44*i*.
particles, small spherical, and processes for making, P (3) 69*f*.
pellets, method of preparing, P (6) 175*b*.
reactor, P (3) 69*e*.
reactor, nitrides, sulfides and phosphides, of U and Pu, chemical aspects, (7) 200*c*.
thermal properties, (1) 12*g*.
thoria-based, properties and prospects, (11) 338*j*.
UO_2, irradiation test to measure expansion rate, (6) 173*h*.
uranium mononitride, P (1) 14*a*.
vapor coating with BeO and C, P (11) 340*i*.
oil, advances, (6) 181*j*.
-oxygen-scrap process, (9) 278*a*.
particles, irradiated and unirradiated coated, study by electron microprobe, (4) 117*b*.
particles, tungsten-rhenium coated ceramic reactor, P (11) 341*b*.
pellet, for nuclear reactor, P (3) 68*d*.
porous ceramic materials as electrodes in, (10) 303*f*.
reactor, uranium carbide-plutonium phosphide, P (4) 97*j*.
reactor, UO_2 as, (6) 174*h*.
reprocessing, single cylce irradiated, P (3) 69*f*.
rods, oxide, columnar grain growth and central void formation in, (2) 46*h*.
UO_2-Nb and UO_2-Ta cermet, preparation by vapor deposition of metal in fluidized bed, (6) 173*a*.
usage, changing pattern in heavy clay and refractory industries, (3) 76*i*.
Fuller's earth, from Pompeii, (7) 194*b*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories.*
arc, electrode for, P (10) 317*f*.
atmospheres. See *Atmospheres.*
basic oxygen, construction, P (5) 134*c*; P (6) 174*j*; P (4) 97*a*.
blast, with air-cooled hearth bottom, temperature distribution in hearth of, (6) 174*f*.
blast, method of operating to produce pig iron and cement slag, P (7) 194*k*.
burner fired shaft, apparatus for operating, P (6) 182*b*.
and burner for testing temperature probes, P (11) 347*i*.
carbon arc image, stability and reproducibility, (5) 147*g*.
centrifugal, P (7) 213*g*.
control apparatus, P (10) 300*i*.
controls for, (1) 10*e*.
crucible melting, P (3) 68*b*.
design, (5) 147*d*.
diffusion, with transport means, P (11) 348*i*.
electric, for ceramic industry, (7) 213*h*.
for ceramics, P (3) 77*a*.
for crucible erosion tests, (10) 304*d*.
heating rods for, (7) 213*i*.
and oil-burning, temperature distribution and atmosphere in, (10) 304*f*.
electric resistance, P (11) 348*f*.
electric resistance, graphite heating element for, P (11) 348*f*.
electrical, high temperature, P (8) 249*f*.
electrical, high-temperature, for studying thermophysical and electrical properties of molten glass, (10) 299*h*.
electrode, liquid-cooled holder for, P (8) 249*h*.
electron beam vacuum, for manufacturing UC_2 bars, P (9) 278*c*.
fireplaces, artificial logs for, P (7) 204*f*.
gas-fired, simple, P (9) 278*b*.
glass, analysis of atmosphere by gas chromatography in, (11) 334*a*.
control for internal furnace pressures, P (6) 171*e*.
direct digital control, (3) 63*g*.
electric, P (7) 198*j,a*.
electric, electrode device for, P (8) 235*h*.
electrically heated, electrodes for, P (1) 24*h*.
floating refractory drawbar, P (11) 336*a*.
oxygen for heating, (7) 197*a*.
protective devices for thermocouples used in, (8) 233*g*.
recuperative-fired, control, (3) 63*h*.
small regenerative, use of booster electric heating in, (8) 234*h*.
glass feeding, P (8) 235*j*.
glass melting, P (4) 94*b*.
all-electric, in Europe, economics, (1) 5*g*.
bubbler apparatus for, P (11) 335*i*.
calculated efficiency in relation to melting load, (11) 333*e*.
cross-fired, natural gas firing in, (5) 128*b*.
electrode holder for, P (8) 249*f*; P (10) 300*g*.
engineering and economic considerations in evaluation, (1) 6*b*.
heat exchange in combustion area, (6) 167*i*.
hot repairs in, (4) 93*g*.
internationally based statistical study, (1) 6*h*.
magnesite brick construction from port to regenerator, (8) 233*d*.
method for damping stack, P (4) 94*j*.
oil firing of, (11) 348*f*.
use of basic brick in, (8) 240*b*.
glass melting tanks, dynamic study, (6) 167*a*.
regenerative chambers, rider arches in, (11) 335*a*.
with simultaneous gas and electric heating, (6) 167*j*.
glass tank, blocks for, B (1) 34*e*.
flow patterns in, determination by tracers, (11) 333*d*.
and furnace walls, P (4) 95*e*.
refractories for, (1) 12*c*.
superstructure, application of zircon and Zirmul refractories in, (11) 337*g*.
wall structure, P (1) 9*d*.
walls, P (4) 95*e*.
heat treatment refractory, (10) 303*c*.
heating, calculation of output, (1) 24*c*.
high temperature, P (1) 24*c*.
conveyor for, P (9) 278*e*.
electric, with molybdenum silicide heater elements, P (6) 182*d*.
for single crystal X-ray diffractometer, (2) 54*i*.
induction, construction, P (1) 12*j*.
industrial, repairs for Dinas and chamotte structures, (9) 268*j*.
iron and steel, gunned maintenance, (2) 44*b*.
large induction, refractory requirements in ferrous foundry, (6) 173*f*.
lime, heat exchange system, P (11) 332*a*.
linings. See also *Refractories.*
for making silicon carbide crystals, P (1) 24*h*.
open hearth, use of basic brick, (7) 200*b,c*.
polyphase arc, with control system to raise one electrode prior to all electrodes striking an arc, P (7) 214*a*.
porcelain, high temperature vacuum firing, P (8) 249*g*.
for producing aggregate, P (1) 3*e*.
for producing graphite electrodes, P (5) 147*e*.
recuperators, method for setting up, P (7) 213*j*.
refractories for. See *Refractories.*
regenerator, refractory tiles for use in, P (7) 205*d*.
roofs. See *Refractories.*
Furnaces (*continued*)
with rotatable tubular heat exchanger, P (8) 229*c*.
rotating-wall dc-arc plasma, (2) 54*j*.
rotary, heating and discharge apparatus for fused materials in, P (3) 68*g*.
shaft, for continuous drawing of quartz tube, P (1) 24*g*.
shaker hearth, P (8) 249*h*.
small graphite resistance, for studies on chemical equilibria at high temperatures, (6) 181*g*.
solar, large, construction, (4) 104*a*.
solar, theoretical concentration and attainable temperature in, (4) 104*d*.
tunnel, P (3) 77*b*; P (7) 214*b*.
for treatment of wax-bonded sinterable preforms, P (4) 104*b*.
walking beam, for effecting different feed speeds of charge, P (6) 182*c*.
wall, of blocks with embedded fastening elements, P (7) 204*c*.
wall structure with metal shell and lining blocks secured by support bars and retainer pins, P (7) 205*h*.
Fusion, of metal oxides, P (9) 270*b*.

Gadolinium, Gd^{3+}, in CeO_2 single crystals, paramagnetic resonance, (8) 255*f*.
Gd^{3+} ESR, in $KTaO_3$, (10) 320*e*.
ESR, in $SrTiO_3$, electric field effect on, (10) 320*e*.
ESR, in reduced $BaTiO_3$, (4) 109*c*.
$GdLiO_2$, transformation under very high pressure and at very high temperature, (1) 33*a*.
Gd_2O_3, vapor pressure from 2350° to 2590°K, (1) 33*e*.
and yttrium compounds, europium-activated, photoluminescent properties, (5) 139*g*.
Gages, Bourdon, determination of equilibrium in $ZnSe(s)$-$I_2(g)$ system, (10) 319*d*.
hot filament vs. cold cathode, (1) 21*b*.
strain, temperature compensated semiconductor, P (5) 143*d*.
Gallium, antimonide, lithium-diffused tellurium-doped *n*-type, Shubnikov-de Haas effect in, (9) 286*c*.
arsenide, bulk and epitaxial, evaluation by X-ray topography, (8) 243*e*.
controlled vapor growth on germanium, (8) 242*i*.
crystals, growth in silica boats, (7) 207*c*.
crystals, tin as dopant in, P (10) 311*g*.
defects, observation by photoluminescence at 20°K, (4) 113*c*.
depth of mechanical damage in, (3) 79*i*.
dielectric constant, resonance behavior at microwave frequencies, (1) 16*e*.
doped and pure, epitaxial growth in open flow system, (4) 109*i*.
epitaxial, for high-efficiency Gunn oscillators, (10) 307*c*.
epitaxial semi-insulating, preparation by iron doping, (7) 207*h*.
epitaxial, shallow donor levels and high mobility in, (11) 356*a*.
epitaxial synthesis using flow system, (7) 207*a*.
heavily doped *n*-type, Hall mobilities in, (3) 81*i*.
of high mobility obtained by liquid phase epitaxy, (5) 152*j*.
high-resistivity chromium doped, and process of making, P (1) 18*c*.
high-resistivity, nonohmic current transport phenomena in, (3) 83*j*.
junction lasers, Hermite-Gaussian mode patterns in, (4) 111*d*.
junctions, iron-sulfur diffused, electroluminescence, (4) 109*h*.
measurement of velocity-field characteristic, (4) 112*j*.
n-, current saturation in, (8) 243*a*.
n-, devices, carrier generation and switching phenomena in, (6) 176*b*.
n-type, field distribution under high electric field, (5) 138*a*.
n-type, preparation of ohmic contacts for, (4) 99*e*.
oxygen-grown, donor and carrier distributions, (4) 108*f*.
purifying, P (4) 101*a*.
semiconductor, with germanium connecting layer, P (5) 142*j*.
semi-insulating, effect of illumination time on thermally stimulated currents in, (3) 80*e*.
single crystals, polishing by reaction with gaseous atmosphere incompletely saturated with Ga, P (10) 310*f*.
solubilities in metallic solvents, (7) 208*b*.
systems. See *Systems.*
tellurium-doped, annular facets and impurity striations in, (11) 350*i*.
three-point probe calibration, (3) 88*h*.
vapor-deposited, changing conductivity by introduction of water into vapor deposition atmosphere, (11) 344*d*.
wafer, electrical contacts to, P (9) 274*i*.
zinc doped solution grown, luminescence, (8) 255*a*.
chloride, reaction with $FeCl_3$, (10) 325*a*.
dodecaboride, reported synthesis, (6) 188*i*.
GaSb, *n*-type, electron screening and longitudinal velocity of sound in, (10) 320*e*.
GaSb-GaAs, alloys, pressure-sintered, densification and thermoelectric properties, (4) 99*g*.
$GaAs_{1-x}P_x$, epitaxial, structural defects in, (6) 189*f*.
$Ga_xIn_{1-x}As$, epitaxial, reflectivity studies, (11) 356*d*.

Gallium (*continued*)
Ga_2O_3, evaporation coefficient, systematics, (7) 222*b*.
α-, bond lengths in, and high-pressure phase of $Ga_{2-x}Fe_xO_3$, (11) 350*c*.
α-, powder, ^{71}Ga quadrupole interaction in, (5) 152*i*.
β-, semiconductor, electrical properties, (3) 72*d*.
GaP_xAs_{1-x} crystals, grown from solution, (10) 308*j*.
iron oxide, piezoelectric ferromagnetic, crystal structure, (5) 137*g*.
monoxide, emission spectrum and thermodynamic properties, (5) 152*b*.
nitride, activation energy for sublimation of, (3) 78*h*.
phosphide, crystal, electroluminescent, with three dopants, P (5) 141*e*.
grown from the vapor phase in silica tubes, effect of water pressure on excess donor concentration in, (4) 108*h*.
pn junctions in, with external electroluminescence efficiency approx 2% at 25°C, (1) 16*c*.
solubility and electrical behavior of zinc, sulfur, selenium, and tellurium in, (3) 86*c*.
solution grown, solubility and electrical behavior of group IV impurities in, (4) 116*b*.
systems. See *Systems*.
vapor-grown, EPR study of effect of substrate orientation on, (11) 352*e*.
zinc-doped, producing, P (10) 311*a*.
in quartz, geochemistry, (7) 217*h*.
Garnets, almandine-pyrope, pyrope, and spessartine, optical absorption spectra, (5) 156*d*.
calcium, series from pyroxine scapolite rocks of Goldongiri, Gujarat States, (1) 24*i*.
chemical vapor deposition of epitaxial YIG on YAG and epitaxial GdIG on YAG, (5) 150*a*.
europium iron, absorption spectrum between 1900 and 5400 cm^{-1}, (3) 78*g*.
ferrimagnetic, containing fluorine, magnetic and crystallographic studies, (8) 255*a*.
minor elements in, (8) 250*i*.
miscibility of pyralspite and grandite molecules in, (8) 255*g*.
occurrence, in granulite facies terrane of Adirondack Highlands and elsewhere, (3) 84*b*.
of sillimanite zone in Darjeeling hills, (3) 87*f*.
synthetic, high-pressure decomposition, (10) 321*h*.
yttrium gallium, Raman transitions of trivalent Yb, Eu, and Nd in, (11) 352*c*.
and yttrium aluminum, crystal-field studies of excited states of trivalent neodymium in, (7) 216*a*.
and yttrium aluminum, spectra of praseodymium in, (10) 325*a*.
yttrium-iron, adiabatic time domain conversion of hybrid magnetoelastic waves in, (4) 105*j*.
diffraction of light by elastic waves in, (4) 108*a*.
growth, P (9) 273*c*.
induced magnetoelectric effect in, (8) 254*j*.
magnetoelastic two-port configuration in, (3) 71*j*.
magnetoelastic waves, high efficiency polarization reversal by optical-contact bonding of YAG disks, (3) 71*b*.
silicon-doped, high temperature resonance losses in, (3) 71*d*.
spin-wave interaction with laser beam in, (1) 17*b*.
substitution of fluorine in, (3) 87*g*.
$Y_4Mg_2Si_3O_{12}$, with rare earth and nickel analogs, (4) 113*a*.
Gases, bubbles, inert, in neutron-irradiated MgO, (4) 111*e*.
dust-laden [BaO], photoelectric enhancement of electrical conductivity in, (9) 285*a*.
effluent analysis, B (8) 260*b*.
evolved or formed during enameling and influence on enameling of cast iron, (4) 92*j*.
fission, in UO_2, (6) 173*f*.
flows, measurement and recording with capillary flow elements, (2) 54*c*.
flue, of natural gas, and use in dryers, (2) 55*j*.
fuel, recirculation in tunnel kilns, (10) 301*j*.
He and Ne, formation, by transmutation of MgO and Al_2O_3, (4) 110*e*.
industrial, analysis, (5) 147*e*.
inert, behavior in ceramic fuels, (11) 337*g*.
inhomogeneous hot, spectroscopic temperature profile measurements in, (9) 277*d*.
leakage, method and compositions for inspecting with gas pressure testing, P (9) 277*f*.
mixture, method and apparatus for determining dewpoint, P (9) 277*e*.
natural, in brick works of Wienerberger Ziegelfabriks- und Baugesellschaft, Austria, (10) 317*b*.
flames, refractories behavior in contact with, (7) 200*g*.
fulfills requirements for firing ceramic ware, (8) 249*g*.
for laboratory burners and furnaces, (7) 213*i*.
use in glass industry, (7) 197*h*.
use in southwestern France tile and brickworks, (10) 317*d*.
permeation, through dense mullite ceramics at high temperature, (3) 67*f*.
reactions, and consequences in enameling, (11) 332*j*.
released on cleaving muscovite mica in ultrahigh vacuum and gases which remain adsorbed on freshly cleaved surface, analysis, (3) 78*i*.
residual, effects on sintering of alumina to theoretical density in vacuum, (1) 28*d*.
waste, of cement kiln, heat transfer from, to pulverulent raw material, P (8) 229*a*.
Gels. See *Colloids; Silicon, dioxide*.
Generators, Hall, magnetic structure, P (6) 177*b*.
infrared ray, gas fired, P (4) 104*c*.
thermoelectric, including silicon germanium alloy thermoelements, P (1) 19*b*.
Geochemistry, of gallium and aluminum in quartz, (7) 217*h*.
Geology, Stony Mountain (Ordovician) and Interlake (Silurian) facies analogs of recent low-energy marine and subaerial carbonates, Bahamas, (4) 116*g*.
Geometry, of alkaline-earth dihalides, (5) 153*b*.
Germania. See *Germanium, dioxide*.
Germanates, ortho-, isomorphous, of rare earths, (7) 219*a*.
Germanides, metallic, low-temperature synthesis by amalgam method, (8) 254*i*.
Germanium, amorphous, (5) 149*j*.
amorphous, optical properties and electronic structure, (5) 156*e*.
deposition of SiO_2 films on, (7) 207*d*.
dioxide, amorphous and polycrystalline, paramagnetic resonance of copper in, (10) 324*g*.
electron spin resonance and optical absorption in, (3) 80*c*.
heats of formation, (3) 81*j*.
reaction with $BaCO_3$, (9) 286*c*.
rutile-type, thermal expansion by X-ray method, (9) 288*a*.
systems. See *Systems*.
tetragonal, and equilibria in Ge-O-H system, (3) 87*b*.
vibrational spectra, (11) 358*a*.
viscosity, and binary germanates containing Li_2O, Na_2O, K_2O, and Rb_2O, (5) 128*d*.
doped, preparation for far infrared detectors, (7) 207*g*.
elastic surface waves in layered system of CdS on, (11) 352*f*.
films, vacuum-deposited, on polycrystalline Al_2O_3 substrates, (5) 140*j*.
phase diagram, to 200 kbars, 1000°C, (6) 187*d*.
selenides, and production, P (7) 208*i*.
-silicon, homogeneous bodies, manufacturing, P (5) 142*e*.
-silicon bodies, low resistance bonds to, P (1) 18*g*.
systems. See *Systems*.
telluride, single crystal growth, (10) 325*h*.
tetrachloride, gaseous, X-ray absorption spectra in *L* shell of Ge in, (9) 286*d*.
tetrafluoride, heats of formation, (3) 81*j*.
Getters, electron vacuum tube, and method of using, P (9) 272*h*.
with getter metal and gas releasing material, P (9) 273*b*.
Gibbsite, dehydration, and formation of boehmite, (2) 57*j*.
Glass. See also *Art and artware; Furnaces; Glass industry; Glassmaking apparatus and equipment*.
P (5) 129*g*; P (7) 198*d,e*.
activation, for electroless metal deposition of uniform thick metal films, P (6) 170*a*.
adherence to metal, temperature, (8) 234*a*.
adsorption of colloidal CdS particles on, (10) 298*g*.
alkali, and alkaline earth oxide, binary and ternary, ultraviolet absorption of chromium(VI) in, (7) 197*f*.
-alkaline earth-silica, dielectric relaxation in, (7) 196*c*.
membrane, as sodium electrode, (5) 126*g*.
mixed, effect in, (3) 64*h*.
mixed, measurement of ionic transport in, (8) 233*f*.
and thallium silicate, ionic conduction in, (7) 196*b*.
treating, P (1) 9*h*.
alkali aluminosilicate, ion-exchanged, effect of stress on durability, (1) 5*h*.
alkali borate, binary, ultraviolet absorption of chromium(VI) in, (1) 8*e*.
binary, optical absorption of divalent Co in, and relation to basicity of, (7) 196*j*.
containing Co, Ni, or Cu, color centers in, (9) 263*g*.
coordination equilibria nickel(II) in, (5) 126*i*.
alkali silicate, electrical conductivity, (8) 231*b*.
influence of nature of cations on properties, (2) 39*a*.
structure transition, (4) 93*h*.
X-irradiated, study of trapped hole centers in, (5) 128*j*.
aluminoborate, color centers in, (4) 93*d*.
Al_2O_3-, composite, hot-pressed, chemical reaction, (1) 26*j*.
ampoule, vented enclosed, and method of making, P (7) 199*e*.
annealed and compressed, relations to density and RI, (9) 264*f*.
annealing lehrs, rapid cooling system for, P (6) 171*f*.
application, to semiconductor devices, P (3) 72*j*.
As-S, infrared absorption spectra, (8) 232*j*.
articles, color ornamentation, P (1) 8*g*.
electrically heated, P (7) 198*c*.
hot hollow, inspecting method and apparatus, P (3) 65*j*.
manufacture by crystallizing glass materials, P (1) 9*e*.
molding composition and method for making, P (7) 198*g*.
molding and releasing method, P (4) 95*e*.
strengthening by ion exchange, P (3) 66*e*.
toughening methods, P (2) 42*a*.
toughening, and article produced, P (4) 95*e*.
treating methods, P (2) 42*a*.
Glass (*continued*)
barium crown, phosphorescence of trivalent terbium ion in, (1) 6*g*.
$BaO-P_2O_5$, electrical conduction and dielectric relaxation in, and dependence on water content, (8) 231*j*.
of $BaO-P_2O_5$ system, anomalies of dielectric properties in, (8) 230*e*.
$BaO-SiO_2-TiO_2$, properties and structure, (9) 264*c*.
batch, calculation of charge, (10) 297*b*.
batch melting process, P (11) 336*b*.
batching, computer controlled, (2) 38*g*.
beads, forming in molten metal bath, P (3) 65*f*.
bearing, gas lubricated, method of making, P (4) 95*d*.
behavior, in far infrared (40 to 1500 μ) absorption at liquid helium temperature, (5) 127*d*.
bent, laminated assemblies, preliminary pressing, P (2) 42*c*.
beryl, high temperature behavior, (1) 6*e*.
bismuth phosphate, viscous behavior and constitution, (6) 169*g*.
blocks, fractures produced by impact, (1) 7*h*.
bodies, smooth precision dimensional, method and apparatus for producing, P (5) 130*f*.
borate, ESR of manganese in, (5) 127*i*.
fraction of four-coordinated boron atoms in, (5) 127*g*.
and phosphate, partial dispersion ratios, (9) 264*b*.
ternary, orthophosphate adsorption on, radiochemical study, (8) 233*j*.
boric anhydride and soda-borate, specific heat at low temperatures, (7) 197*j*.
boron in, determination by thermal neutron capture gamma ray analysis, (5) 127*a*.
B_2O_3, permanent densification by hydrostatic and nonhydrostatic pressures up to 55 kbars and 140°C, (1) 6*e*.
B_2O_3 and potassium borate, ^{11}B NMR measurements on high pressure modifications of, (6) 166*f*.
in $B_2O_3-Na_2O$ system, study of structure by viscometry, (1) 7*h*.
borosilicate, chemical heterogeneity, determination by dielectric losses, (8) 231*e*.
and construction of modern glass apparatus, (7) 195*i*.
dependence of properties on added elements, (6) 166*j*.
highly siliceous, defects during melting, (8) 230*i*.
relation between heat treatment and acid leaching of, (1) 7*a*.
structural parameters, acoustic-dilatometric studies of, (10) 296*i*.
synthesis and physicochemical properties, (6) 169*d*.
bottles. See also *Glass, containers*.
aerosol, and method for making, P (4) 94*i*.
apparatus for inspecting rim which uses polarized light at Brewster's angle, P (3) 64*j*.
computer-aided production, (7) 195*i*.
or like containers, P (1) 8*e*.
nonreturnable, growth and importance, (10) 297*j*.
nonreturnable, in-plant printing, drying, and direct filling of, (10) 297*g*.
breaking stresses determined from fracture surfaces, (2) 38*g*.
breaks. See *Glass, fractures*.
bubbles, analysis, gas chromatography in, (3) 64*d*; (11) 334*a*.
formation, and homogenization in glass melts, (4) 93*i*.
prepared by reheating solid glass particles, P (5) 129*i*.
speed, and diagram of fining process, (11) 335*e*.
surfaces, contamination-nucleated crystal growth at, (1) 5*g*.
calcium aluminoferrite phase, hydration in portland cement clinkers, (8) 228*e*.
calcium and magnesium silicate, alkali-free and Na_2O-containing, study of infrared absorption spectra of, (8) 230*j*.
$CaO-Al_2O_3-SiO_2$, coordination state of aluminum ions in, (1) 27*h*.
capillaries, freezing and melting points of water in, (11) 353*c*.
capillary passage, and method of making, P (7) 198*c*.
carbon-containing, method of making, and product, P (7) 199*c*.
cellular, manufacture on molten metal bath, P (4) 94*e*.
cellular nodules, and method of making, P (3) 65*d*.
cellular phosphate, method of making, P (1) 9*d*.
cements, P (6) 170*a*.
-ceramics, P (1) 9*b*; P (7) 198*e*.
articles, semicrystalline, method of glazing and resultant intermediate layer containing composite, P (8) 235*h*.
in chemical engineering, (10) 297*f*.
devitrified, and production, P (1) 8*i*.
eucryptite, semiconducting metal oxide layers on, (8) 234*b*.
evaluation for guided missile radomes, (3) 63*h*.
fine grained crystalline, studies, (1) 7*f*.
metal bonded, P (5) 140*e*.
method of making by devitrification in single stage, P (2) 41*h*.
method of making and product, P (2) 41*f*.
nucleation and growth of crystalline phases in glass, (8) 232*d*.

Glass, ceramics (*continued*)
- plastic deformation, (8) 233*c*.
- and production, P (1) 9*c*; P (7) 198*f*.
- quantitative phase analysis, (9) 285*f*.
- strengthening with compressive glazes, (3) 64*e*.
- for telescope-mirror, (11) 334*b*.

cerium containing, color-center kinetics in, (5) 126*h*.
chalcogenide, internal defects, examination by infrared defectoscopy methods, (6) 167*e*.
chalcogenide, nonoxide, as infrared optical materials, (9) 263*j*.
clear, color coating permanently, (3) 63*f*.
coating for, abrasion-resistant, P (5) 129*h*.
coating, scratch resistant, by decomposition of titanium ester chelate, P (9) 265*j*.
coatings, silanol groups, reactions of trimethyl chlorosilane and trimethylsilanol, (9) 264*i*.
cobalt, fading, (1) 6*b*.
color, review, (1) 5*d*.
coloration, (8) 230*i*.
colored, with molten additions of colorants in furnace forehearth, P (1) 9*j*.
colored signal, history, development, and speculation, (6) 166*i*.
complexometric determination of total amount of lead in Pb_3O_4, PbO_2, and PbF_2 used in, (11) 333*g*.
composition, changes in, DTA in study of, (11) 333*e*.
- comprising radioactive waste oxide material contained within steel vessel, P (5) 129*j*.
- Li_2O–MgO–Al_2O_3–SiO_2 system, P (8) 235*j*.
- method for controlling reduction of metallic ions in, P (1) 9*j*.
- mixed-cation phosphate, P (4) 95*g*.
- radioactive fluophosphate, P (6) 171*e*.
- resistant to discoloration, method of making and articles produced, P (2) 40*h*.
- selection and specifications, (4) 93*f*.
- soda-lime, green, P (4) 94*i*.
- surface and bulk, comparison with spark source mass spectrometer, (6) 166*i*.

conductive article, oxide-coated, P (7) 198*g*.
conductivity, electrical, method of changing, P (10) 300*j*.
constituents, diffusion in refractories, (3) 63*f*.
constitution, B (4) 120*b*.
containers, apparatus for inspecting for wall thickness distribution, P (7) 198*a*.
- automatic inspection apparatus, P (7) 198*b*.
- design and development, (2) 38*h*.
- hollow, radiation sensitive apparatus for inspecting bottom wall of, P (3) 66*b*.
- hollow, treatment, P (5) 130*h*.
- measurement of effect of surface coatings on friction between, (5) 127*j*.
- with metal oxide and resin coatings, P (7) 198*f*.
- method of treating surfaces, P (2) 41*i*.
- production, computer process of data in, (7) 195*j*.
- sorting, P (2) 40*i*.

containing BaO and TiO_2, crystallization, (8) 230*e*.
containing rare earth elements, spectral properties, (6) 188*j*.
containing Na_2O–CaO–MgO–Al_2O_3–SiO_2, corrosion effect on tank blocks of Corhart ZAC and sillimanite, (5) 125*j*.
controlling heat application, to repair scored regions, method, P (2) 41*a*.
coordination in, (6) 166*j*.
copper ruby, measurement of viscosity by fiber elongation method, (2) 39*g*.
copper ruby, viscosity in and below striking range of temperature, (7) 197*i*.
cords, aluminous diffusion in sheet glass, (8) 231*i*.
- determination of alumina in, by electron microprobe, (8) 231*d*.
- identification, (2) 39*a*.

corrosion resistance to various solutions, (2) 38*i*.
crack-branching in, (5) 126*h*.
crack propagation in viscoelastic media, (1) 5*i*.
cracks in, growth and branching, (5) 127*b*.
crystalline. See *Glass-ceramics*.
crystalline inclusions, attempt to trace origin, (1) 5*a*.
crystallization. See also *Crystallization*.
crystallization, initial stages, study by Moessbauer effect, (8) 234*i*.
decoration. See *Decoration*.
defects, (8) 230*h*.
defects, Tokyo symposium, (2) 40*e*.
deformation under point loading, role of densification in, (11) 335*c*.
densification, under cutting wheel, (6) 166*j*.
desorption, thermal, of argon, (8) 258*a*.
devitrified. See also *Glass-ceramics*.
devitrified, powder compacts, electron microscopy of, (11) 333*j*.
dielectric, and capacitors using, P (7) 198*i*.
dielectric properties, at 40 Gc/sec, (5) 127*b*.
dielectric properties within range 20° to 600°C, (9) 263*h*.
diffusion, in K_2O–SrO–SiO_2 system, (3) 63*f*.
- of silver and potassium ions in, (7) 196*d*.
- treatment to reduce helium permeation, P (11) 336*a*.

diethyl phthalate, heat capacities and related thermal data to 360°K, (4) 110*j*.
dihalide ions trapped in, (5) 127*d*.
diodes, sealing head for, P (10) 301*d*.
with dissolved carbon, methods of making and using, and obtaining graphite, P (2) 40*j*.

Glass (*continued*)
drawing, continuous, from molten or viscous bath: I; II, equations of problem; III, application of equations to form of meniscus and production problems, (7) 195*j*; IV, control of geometry and stability of meniscus; V, secondary thermal effects; VI, variations in technique, (11) 333*h,i*.
with dual protective coatings, and method of forming coatings, P (2) 40*j*.
durability, for disposal of highly radioactive waste, method and effect of leaching conditions, (7) 196*f*.
electrical and mechanical aftereffects in, (8) 231*e*.
electrodes. See *Electrodes*.
electronic conduction mechanisms in, (10) 297*b*.
elements, thin film, method for making, P (7) 209*i*.
-epoxy, corona and microwave methods for detection of voids in, (7) 212*b*.
equation of state, at elevated pressures, (5) 127*j*.
etching, process for producing nonreflective surface on, P (6) 170*i*.
fabric, coating method for, and product, P (3) 65*e*.
fabric, pigmented, process for post-finishing, P (11) 336*g*.
Faraday rotation in, (5) 127*a*.
ferruginous, crystallization, study by infrared spectroscopy, (10) 299*b*.
fibers. See *Fibers, glass*.
filaments, continuous, method for forming and processing, P (3) 65*c*.
filters. See *Filters*.
fining, diagram for, (11) 335*e*.
fire-polishing, P (1) 9*j*.
fittings, unground and clear, (5) 144*i*.
flat. See also *Glass: plate, sheet, window*.
- edging, mitering, and drilling by diamond tooling increases production, (6) 167*g*.
- made to order, (5) 127*a*.
- manufacture, P (2) 41*d*; P (7) 198*j*.
- manufacture on improved molten metal bath, P (1) 9*h*.
- manufacture in ribbon form, P (7) 199*a*.
- measurement of temperature distribution along debiteuse by Fourcault method during manufacture of, (3) 64*f*.
- spherical inclusions in, investigation by electron microprobe, (8) 232*c*.

flint soda-lime, reduced sulfur compounds as melting and refining aids for, (2) 40*b*
float, computerized production, (10) 297*e*.
- etching process for producing nonreflective surface on, P (6) 170*i*.
- method of controlling thickness, P (3) 65*e*.
- method of inhibiting flow of molten bath impurities to, P (11) 336*d*.
- tinting within production line, (11) 335*a*.

flow, calculation, (6) 168*c*.
fluoberyllate, with cobalt and nickel, paramagnetic resonance of, (3) 64*a*.
foam, method of making, P (2) 41*e*.
foam, production, P (4) 95*c*.
foam quartz, properties, (10) 298*d*.
formation, in alkali silicate-zirconium systems, (6) 169*i*.
formation, new approach to prediction, (6) 168*b*.
formation range and cooling rate, (8) 232*e*.
formers, inorganic, vibrational anomalies in, (5) 129*g*.
forming, precision, P (4) 95*d*.
- punching holes, by heating with high frequency pulse current, P (5) 130*a*.
- parameters for rods and tubes, (10) 298*g*.

-forming liquids, comparison of expression for cooperative properties in, (5) 126*h*.
-forming liquids, temperature dependence of cooperative relaxation properties in, (5) 129*c*.
-forming system, direct measurements of homogeneous nucleation rates in, (5) 127*e*.
-forming systems, inorganic, B (5) 161*d*.
forming tools, with iron casting of varying graphite structure, P (2) 42*e*.
fracture criteria of Griffith and Barenblatt, comparison, (1) 5*e*.
fracture, ring cracking by spherical indenters, (11) 335*a*.
germanium, luminescence and adsorption with Nd_2O_3 additions, (6) 169*a*.
- P, and S compositions, and use in infrared detection system, P (6) 170*e*.

Ge_2, As_2, Se_3 Te_3 composition, P (6) 170*g*.
GeO_2–SiO_2, binary, nonideal mixing in, (8) 233*j*.
Ge-Sb-Se, compositions, P (4) 94*h*.
Ge-Se-Te, and infrared detection system, P (1) 9*b*.
Ge-S-Te compositions, and infrared detection system, P (6) 170*j*.
Ge-Te-As, and method of preparation, P (1) 9*b*.
grinding. See *Grinding*.
handling operations, use of programable robots, (2) 40*e*.
hardened, peculiarities of chemical etching, (6) 168*g*.
hardening, in polyethylsiloxane liquids and in melts of heavy metals, (6) 167*g*.
hardness, micro, dependence on applied load, (10) 297*g*.
hardness and elasticity and Poisson's ratio of, (7) 196*f*.
heat treating and gas pressure supporting, in sheet form, methods, P (4) 95*f*.
heating, method and apparatus, P (7) 199*b*.
Hertzian stress cracks in, (1) 29*b*.
high-lead, crystallization, (6) 169*d*.
hollow, articles, method and apparatus for detecting light-deflecting flaws in, P (9) 265*j*.

Glass (*continued*)
hollow body, centrifugally cast, P (7) 198*d*.
homogeneity, effect of melting method as shown by light scattering, (11) 333*h*.
homogeneity and structure, (10) 297*f*.
hulls, for deep submergence capsules, (3) 64*a*.
and indium bimetallic composites, stress in, (8) 229*f*.
ink epoxy resin, for printing on, P (9) 265*b*.
inorganic, and supercooled liquids, heat capacity, (8) 232*h*.
inorganic, structure and mechanical properties, B (4) 121*i*.
internal friction and structure, (10) 297*h*.
ion-exchanged, internal friction, (6) 167*b*.
iron-containing, devitrification, characterization by electrical and magnetic properties, (6) 166*g*.
with iron oxide films, mechanical properties, (10) 298*d*.
irradiated, alkali borate, with high alkali oxide content, ESR studies, (5) 127*j*.
- containing boron, ESR studies, (5) 127*j*.
- inorganic radicals trapped in, at room temperature: I, iodine atoms and I_2^- in boric acid glass; II, Cd^+ and Ni^+ in metaphosphate glass; III, IBr^- in boric acid glass; IV, silver radicals in metaphosphate glass, (5) 127*f,g*.
- two-component, EPR spectra of, (10) 299*c*.

knives, P (6) 170*c*.
laminate with plastic, flexible, P (10) 300*h*.
laminated safety, P (9) 265*h*; P (11) 336*b*.
laminated structure, P (2) 41*c*; P (8) 235*d*.
laminated window panels, P (3) 65*j*.
laminates, polypropylene, (1) 7*a*.
- transparent, and method of making, P (9) 266*b*.
- treatment of coverplates for, P (9) 266*b*.

laminating process, P (1) 9*f*.
lamination, with amorphous fluorocarbon polymer, and method of making, P (6) 170*i*.
laser-induced breakdown and fracture in, (6) 167*g*.
laser, Nd^{3+}, polarization of stimulated radiation from, (10) 298*h*.
lasers, (9) 263*f*.
leaching, by soda, effect of surface condition on, (6) 167*b*.
lead silicate, surface layer, change in electrical conductivity during heat treatment in hydrogen, (2) 38*i*.
lead silicate, volatilization at high temperatures, (8) 234*j*.
lens blanks, supporting for grinding and polishing, P (3) 66*e*.
lenses. See *Glass, optical*.
light protective, (5) 127*j*.
-lined metal conduits, process for joining, P (4) 95*b*.
lithium aluminosilicate, density, and crystallization products, (8) 230*j*.
- homogeneity problem, (8) 233*e*.
- sitallization, kinetics of phase transformation and change in microstructure and mechanical properties during, (8) 232*g*.

lithium borate system, paramagnetic resonance of Mn^{2+} in, (5) 128*e*.
lithium-silicate, diffusion-controlled growth of second phase particles in, (1) 5*c*.
Li_2O–SiO_2, crystallization of lithium disilicate from, (5) 126*j*.
- electrical properties, effect of metastable precipitate, (9) 263*j*.
- kinetics of crystallization in, (8) 232*e*.

low melting point, P (7) 198*j*.
with low thermal conductivities, P (7) 198*h*.
lubricant, for extruding metal, P (9) 265*c*.
in M_2O–Al_2O_3–SiO_2 system, thermoluminescence and color centers, (1) 8*c*.
-making, application of activable tracer method, (11) 333*d*.
-making, sampling programs for raw materials, (7) 197*g*.
-making in Weald of Sussex and Surrey, history, B (4) 120*g*.
manganese arsenic borate, for dosimetry, (1) 6*i*.
manufacture, P (2) 4 *f,j*; P (7) 198*g*.
melting, P (1) 9*i*; P (3) 65*i*; P (4) 94*c*; P (7) 198*g*.
- all-electric, economic evaluation, (2) 38*j*.
- contact with refractory, study by electron microprobe, (10) 298*j*.
- control, instrumentation for, (2) 39*d*.
- electric, (11) 333*i*.
- electric, progress, (2) 40*a*.
- and flame research, (8) 232*c*.
- with increased content of rare-earth elements, (6) 168*c*.
- influence of crucibles on formation and properties, of heavy glasses, (7) 196*a*.
- process control variables in, (2) 39*j*.
- and refining, P (5) 130*f*.
- treatment with SO_2, P (7) 199*c*.
- use of electric "boosting," (1) 8*g*.

and melt, structural similarities between, (4) 93*d*.
melts, metal-line, corrosion and upward drilling by gas bubbles, caused by permanent peri-wetting, (8) 232*j*.
- soda-lime-silica, electrical conductivity, (8) 231*d*.
- soda-lime-silica, laboratory investigation of foaming and reboil in, (8) 233*a*.
- sodium silicate, dissolution kinetics of quartz spheres in, correction, (7) 196*f*.
- and vitreous carbon, reactivity, (7) 197*d*.

member, method for fluidtightly securing metal part to, P (4) 95*a*.
metal compositions, process for producing, P (5) 130*d*.

Glass (*continued*)
-metal melts, interface, determination of surface tension at, (11) 334*j*.
-to-metal sealing. See *Seals and sealing*.
microporous, thermal shrinkage, (1) 8*c*.
microscope cover, (7) 196*e*.
mirrors. See *Mirrors*.
molds. See *Molds*.
molten, electrical properties, high-temperature furnace and ceramic flask for studying, (10) 299*f*.
electrical resistivity between electrodes, (10) 297*i*.
eliminating foam blanket on surface of, P (2) 41*b*.
forming charges, method, P (2) 41*b*.
homogenization in chamber connecting refining furnace to working compartment, process and apparatus, P (2) 42*c*.
homogenization with flow separator, P (4) 94*d*.
homogenizing, apparatus for, P (5) 129*a*.
levels, automatic control problems, (10) 298*j*.
study of thermophysical and electrical parameters of transfer of heat and electricity in, (10) 299*f*.
multicomponent, calculation of charge composition of, by approximate calculation method, (10) 297*b*.
multiple glazing units, method for fabricating, P (4) 95*a*.
Murano terminology in book by Neri, (1) 6*j*.
nature and properties, in materials, B (11) 358*d*.
neodymium-doped, measurement of cross section for stimulated emission in, from output of free-running laser oscillator, (9) 263*g*.
network formers, infrared spectra, and interpretations, (6) 167*a*.
nitrate, environment of cobalt(II) in, (10) 297*d*.
nonoxide chalcogenide infrared transmitting, (2) 39*i*.
nucleated. See *Glass-ceramics*.
objects, manufacture, P (7) 199*d*.
opacification, by phosphate, (6) 169*c*.
optical, element, magnesium fluoride, P (5) 130*e*.
elements, calcium fluoride, and method of making, P (4) 94*e*.
elements, shaping by using ultrasonic vibration, P (11) 336*h*.
fiber, image-encoding-decoding device, P (4) 94*h*.
heterogeneity measurement, autocollimation method of, (5) 126*h*.
homogeneity measurement, with help of autocollimation method, (5) 128*i*.
image-transfer devices, method of forming embodying light-conducting fibers and light-absorbing filaments, P (9) 265*b*.
lens, forming on metal ring, P (1) 9*a*.
lenses, charging device for machines for working, P (3) 65*e*.
lenses, method for making, P (2) 41*h*.
light-scattering study of structural changes leading to devitrification, (7) 196*c*.
materials, measurement of homogeneity in visible and near infrared, (9) 263*h*.
method for specifying sensitivity to acids, (1) 6*b*.
in mine environment, transmission losses, (6) 168*f*.
properties. See *Optical properties*.
proposed mean reference line in dispersion study, (2) 40*a*.
reflex marker, P (1) 10*a*.
spectra of thallium in, as related to crystals and solutions, (4) 93*h*.
oxide, optical constants, in strong absorption region, (9) 263*j*.
oxide, in light of "ideal glass" concept: I, ideal and nonideal transitions and departures from ideality; II, interpretations by reference to simple ionic glass behavior, (4) 93*i*.
panels, electrically heated, and protective circuit for, P (7) 198*c*.
laminated, incorporating heating wires, P (7) 198*i*.
structural, and method for making, P (1) 10*b*.
structural, reinforced, P (1) 10*b*.
partitions, in rolls, (4) 93*f*.
periodic table, (2) 39*i*.
phase composition and microstructure, based on slag, effect of heat treatment on, (11) 333*e*.
phase separation in: II, structure of sodium silicate, (7) 197*b*.
phosphate, ESR and optical absorption studies of Cr^{3+} in, (5) 127*i*.
phosphate, slowly soluble, sequestering metal ions with, P (6) 171*e*.
photochromic, in laser as Q-spoiling medium, P (5) 130*c*.
optical properties and applications, (9) 264*a*.
properties and applications, (11) 334*b*.
silver halide, (11) 334*c*.
photoluminescent multicolor, P (6) 178*b*.
photosensitive, technology of obtaining pictures in, (3) 64*h*.
photosensitive opal, effects of colloidal gold and K_2O on formation of lithium metasilicate crystallites in, (1) 5*h*.
physical properties, bibliography, B (8) 258*i*.
pipe. See *Pipe*.
plate. See also *Glass: flat, sheet, window*.
manufacture, P (5) 130*c*.
packaged, P (2) 42*a*.
polishing. See *Polishing*.
porous, effect of micromechanical stress concentrations on strength of, (1) 28*i*.
porous silica, chemisorption sites on, (11) 333*e*.
potassium silicate, high-alkali, effect of Al_2O_3 on chemical stability and structure, (2) 38*j*.

Glass (*continued*)
pots. See *Glassmaking apparatus and equipment; Refractories*.
in powder metallurgy, (5) 129*f*.
powders, method for suppression of harmful recrystallization on heating, P (2) 41*i*.
slip casting and firing, (1) 7*f*.
specific surface, and relation to parameters determined statistically by grain size analysis, (6) 166*j*.
prepolishing, method and apparatus, P (2) 41*a*.
pressed, factors in formation of "flow marks" in, (8) 232*b*.
pressing, of flanged articles, P (9) 265*j*.
pressing, laboratory investigation, (8) 233*c*.
products, heat resistance, (3) 63*j*.
properties, B (4) 120*b*.
properties, dependence on physical and crystallochemical constants of added elements, (6) 166*j*.
Pyrex and sodium tetraborate, radiation-induced atomic silver in, (5) 128*g*.
quartz, crystallization and nature, correlations in, (1) 5*g*.
electron-microscope study, (10) 297*j*.
firing, (6) 168*h*.
production, use of high temperature thermocouples in, (8) 234*h*.
strengthening, (8) 233*i*.
radiation action on, (10) 328*b*.
radiation indicating, P (4) 95*d*.
reaction with water, (3) 64*f*.
reboil, method for reducing, P (9) 265*i*.
reciprocal effect of Cr and Mn ions in, (1) 7*d*.
refining, studied by light scattering, (11) 334*e*.
refractor, for use in uniformly illuminating polygonal area, P (1) 10*b*.
ribbon, manufacture, protective salts bath for use in, P (7) 199*f*.
method of attenuating on molten metal bath, P (2) 41*j*.
method of forming on gas support bed, P (3) 65*f*.
rigid organic, thermoluminescence of γ-irradiated solutions of aromatic compounds in, (2) 40*e*.
RO–R_2O–PbO–SiO_2, preparation and dielectric properties, (6) 168*c*.
rods, chemical strengthening, (7) 195*i*.
internal friction, comparison with fiber glass, (10) 297*e*.
pristine surface, formation of coatings on, (2) 39*h*.
and tubes, drawn by Danner method, parameters of preliminary forming of, (10) 298*g*.
safety. See also *Glass, laminated*.
P (1) 10*d,e*.
for automobiles, (6) 168*j*.
laminated, P (6) 171*a*.
sag temperature determination, (2) 39*j*.
sand. See *Sands*.
scoring means, control means for sequencing plurality of, P (1) 8*h*.
sealing. See *Seals and sealing*.
seam finishing, P (2) 42*b*.
seeds and stones in, photometric counting of, (10) 298*g*.
selenium on, impurity effects on heterogeneous nucleation from vapor, (5) 127*d*.
semiconducting, radiation effects in, (8) 233*h*.
iron phosphate, dielectric properties, (8) 231*g*.
oxide, role of network former on electrical properties, (3) 64*b*; correction, (7) 197*e*.
oxide, Seebeck coefficient, (5) 139*h*.
semiconductor, continuous isothermal crystallization study by measurement of electrical conductivity, (9) 264*e*.
semicrystalline. See *Glass-ceramics*.
sheet. See also *Glass: flat, plate, window*.
bending and annealing with supplemental cooling of hotter areas, P (9) 265*a*.
bending to complex curvature, method, P (2) 41*j*.
bending method, P (3) 65*d*.
bending stress equalization method, P (5) 129*h*.
bending and tempering by differential heating, (11) 336*c*.
cause of ream lines, (7) 196*j*.
chemical inhomogeneity in, (1) 5*c*.
diffusion of aluminous cords in, (8) 231*i*.
drawing, with portion of surface being untouched, P (1) 9*j*.
float bath, molten metal, method for removing dross from surface of, P (9) 265*a*.
float bath, removing contaminates from protective atmosphere of, P (3) 66*c*.
float operation, protecting molten bath surface in, P (3) 66*b*.
glazing units, multiple, method of producing, P (9) 265*h*.
heat treating on gaseous support bed, P (1) 9*c*.
high strength after etching in hydrofluoric acid, (1) 6*c*.
manufacture, P (1) 9*i*.
manufacture by drawing, P (2) 42*f*.
press bending between cold opposed shaping molds, P (6) 171*f*.
quality, determination from optical distortions, (11) 334*e*.
strength, measurement on flexible plate, (10) 298*c*.
support frame, P (1) 9*c*.
supported on bending mold, method for equalizing cooling, P (6) 171*b*.
tempering and conveying, P (6) 171*b*.
toughened, P (4) 95*f*.
trimming, P (1) 10*b*.

Glass sheet (*continued*)
undersurface, apparatus for marking by abrasive blasting, P (7) 197*j*.
varying thickness while on molten metal bath, P (1) 9*i*.
vertically suspended, press bending, P (1) 9*f*.
shifting, on molten metal bath, P (3) 66*d*.
silica, high, production and application: I, relation between heat treatment and acid leaching of borosilicate glasses, (1) 7*a*.
low-temperature dielectric loss, influence of OH^- concentration and irradiation, (2) 58*b*.
sodium diffusion in, (10) 298*d*.
silicate, based laser, P (8) 236*b*.
and borate, simple, structure, (6) 169*a*.
electron-microscopy study of spherulites formation in, (8) 231*i*.
kinetics of spherulite growth in, (8) 232*i*.
paramagnetism of Dy^{3+} and Gd^{3+} in, (8) 233*b*.
spectral study of interconversion of Eu^{3+} and Eu^{2+} in, (8) 234*c*.
substructures, (4) 93*i*.
silver-activated borate, polarization of photo- and radiophotoluminescence, (1) 6*j*.
silvering, production: II, methods, (2) 39*j*.
sintering kinetics, effect of particle shape, (11) 333*i*.
sitalls, preparation based on Tyranauz tailings, (6) 168*e*.
slag, kinetics of combustion of sulfides in, (2) 39*e*.
soda-boric oxide, structure of nickel in, (5) 129*b*.
soda-boric oxide, structure of vanadium in, (5) 129*c*.
soda-lime, with TiO_2, GeO_2, ZrO_2, and $AlPO_4$ partially substituted for SiO_2, chemical durability, (9) 263*f*.
soda-lime-silica, chemical composition of phase-separated droplets in, (4) 93*d*.
measurement of ionic transport in, (8) 233*g*.
strengthening by low temperature ion exchange, (8) 234*f*.
sulfate in, determination by combustion in oxygen, (8) 231*f*.
tendency of refractories to produce bubble in, (5) 129*d*.
soda-silica, solubility of ruthenium in, (4) 93*j*.
sodium borate, doped, "sensitized" stress buildup by ultraviolet irradiation, (9) 264*h*.
sodium borosilicate, internal structure, (6) 168*j*.
ordinary and porous, relation between structures of, (11) 334*i*.
ternary, volatilization loss, (8) 235*b*.
sodium disilicate, kinetics of dissolution and diffusion of iron oxides in, (10) 297*j*.
sodium ions in, stress-induced migration and partial volume of, (5) 128*a*.
Na_2O–Al_2O_3–SiO_2 and Na_2O–CaO–Al_2O_3–SiO_2, sodium diffusion and electrical conductivity, (1) 7*i*.
Na_2O–CaO–MgO–Al_2O_3–SiO_2, ZnS-doped, crystallization, (1) 7*f*.
Na_2O·$2SiO_2$, reaction with sintered mullite particle containing α-Al_2O_3, (11) 334*h*.
sodium phosphate, investigations, (6) 167*f*.
sodium silicate, devitrification products, study by X-ray diffraction and infrared spectrometry, (4) 93*h*.
electrochemical behavior at high temperature, (1) 6*a*.
internal friction after ion exchange, (11) 334*g*.
structure, (7) 197*b*.
structure, and far-infrared absorption spectra, (8) 234*i*.
solder, alkali-free, for covering interior surfaces of glass semiconductor housing, P (5) 141*j*.
solder, electrically conductive, P (10) 300*f*.
solubility, in system Cs_2O–Na_2O–SiO_2, (6) 169*c*.
specimens, of variable composition, methods of obtaining, (10) 298*e*.
spheres, high strength, method of making, P (9) 265*e*.
standard, for fluorescence, (3) 63*i*.
strain and homogeneity in, measurement of, (5) 127*h*.
strength, effect of surface and bulk defects on, statistical examination, (8) 234*d*.
increased, and ion exchange, (10) 297*i*.
and resistance, to thermal shock and chemical attack of vapors, liquids, and solids, improvements in, P (5) 130*b*.
and strengthening, (5) 128*a*.
window, statistical evaluation, (11) 335*g*.
strengthening, by etching, (5) 128*i*.
by ion exchange, P (11) 336*i*.
by treating in molten salt, P (11) 336*j*.
stress, caused by ultraviolet radiation, (8) 234*g*.
stresses, determination in containers, (6) 166*i*.
striae in, possible interpretation, (11) 334*d*.
structural, cutting with diamond wheels, (8) 230*g*.
structural changes in devitrification, (7) 196*c*.
structural changes after γ-radiation, thermographic studies, (8) 234*g*.
structural similarities with melt, (4) 93*d*.
structure, (4) 93*e*; B (4) 120*b*.
in borate glasses, (5) 127*g*.
formation of 4-coordination structures of intermediate ions and boron in, (8) 232*d*.
general concepts applied to, (7) 196*i*.
heating, method of terminating, P (8) 235*j*.
permitted and forbidden units in, (11) 334*a*.
review, (1) 5*d*.
of sodium borosilicate glasses, (6) 168*j*.
in system K_2O–B_2O_3–Al_2O_3, (7) 197*a*.
in system Na_2O–B_2O_3–P_2O_5, NMR studies, (7) 196*h*.
in system Na_2O-GeO_2-B_2O_3, (1) 7*e*.
vitroids, (6) 169*h*.

Glass (*continued*)
sulfide and selenide, new, preparation, structure, and properties, (10) 298*g*.
surface layer, diffusion processes, (1) 5*e*.
surfaces, chemisorption sites on, (11) 333*e*.
diffusion-controlled attack by molten hydroxides, (1) 5*b*.
flaw distribution on, theoretical and experimental investigation, (1) 8*a*.
kinetics of leached layers formation on, (8) 232*e*.
load-bearing mounting elements for attachment to, P (8) 235*e*.
massive, physical adsorption on, (1) 6*i*.
polished, observation of quality, (6) 168*a*.
reactions with trimethyl chlorosilane and trimethylsilanol, (9) 264*i*.
sterilizing, P (8) 236*b*.
in system Al_2O_3–TiO_2–P_2O_5, softening point, (10) 299*f*.
in system BaO–B_2O_3, nuclear magnetic resonance investigations, (3) 64*i*.
in system BaO–Li_2O–SiO_2, metastable immiscibility, (3) 64*f*.
in systems BaO–TiO_2–B_2O_3, BaO–TiO_2–P_2O_5, and BaO–TiO_2–SiO_2, properties, (2) 38*h*.
in system B_2O_3–SiO_2, physicochemical investigations, (6) 168*a*.
system iron-sodium disilicate, kinetics of interfacial reaction and diffusion processes in, (3) 64*b*.
in system PbO–Al_2O_3–B_2O_3–SiO_2, electrical properties, (2) 39*f*.
in systems Li_2O–SiO_2–ZrO_2 and K_2O–SiO_2–ZrO_2, formation, (6) 169*i*.
in system, MgO–Al_2O_3–SiO_2, crystallization, forming and recrystallization of quartz-like phases during, (6) 185*j*.
in system MgO–Al_2O_3–SiO_2, effect of TiO_2 on sitallization of, (6) 169*f*.
in system Se–Ge, crystallization, (3) 63*i*.
of system SiO_2–Al_2O_3–BaO–TiO_2, structural changes during initial crystallization stage, (2) 40*c*.
system silica-titanium oxide-potassium oxide, role of titanium oxide: I, viscosity measurements, (7) 197*e*.
system silica-titanium oxide-potassium oxide, role of titanium oxide in: II, expansion measurements, (11) 335*c*.
in system Na_2O–BaO–SiO_2, internal friction, (1) 6*f*.
in system Na_2O–B_2O_3–ZrO_2–SiO_2, crystalline phases, (3) 63*h*.
in system Na_2O–La_2O_3–SiO_2, properties, (8) 230*h*.
in system Na_2SiO_3–H_2O, (6) 167*d*.
in system Na_2O–TiO_2–SiO_2, phase separation and crystallization, (6) 168*h*.
tableware, optimum quantity of decolorizers in, (8) 233*a*.
technology, applied to infrared detector housings, (3) 63*j*.
technology and research, application of DTA to, (11) 333*d*.
television tubes. See *Tubes*.
temperature measurement with radiation pyrometers, (3) 63*e*.
temperature and temperature measurement in, (8) 230*e*.
tempered, fracture, (3) 63*i*.
tempered, fracture, secondary processes, (7) 197*g*.
tempering, between cold plates, method and apparatus, P (5) 130*g*.
terbium alumina silicate, Faraday effect at low temperatures in, (6) 176*g*.
thermal aftereffect in, dielectric study, (10) 297*h*.
thermal expansion and softening point in system Al_2O_3–TiO_2–P_2O_5, (10) 299*f*.
thermal properties, in anomalous interval, study by DTA, (10) 299*e*.
thermal properties, at low temperatures, (7) 197*d*.
thermoluminescent, P (11) 336*h*.
thin, samples, transmission electron microscopy, discussion and reply, (1) 5*g*.
thin, sections, for transmission electron microscopy, technique for obtaining, (9) 277*b*.
SnO–SiO_2, crystallization and decomposition, (1) 5*j*.
transformation, excess entropy at, (5) 127*a*.
transformation, kinetics by thermal analysis; I, glycerol, (5) 127*i*.
transition, experimental equivalence of Gibbs-DiMarzio and free-volume theories of, (5) 128*e*.
Gibbs-DiMarzio theory, (5) 128*i*.
thermodynamic aspects, free volume, entropy, and enthalpy theories, (5) 128*i*.
in *o*-terphenyl, (5) 127*b*.
-transition temperature, of molten nitrates, effect of pressure, (5) 127*h*.
-transition temperature, of simple liquids, measurement, (5) 128*b*.
tubes. See also *Tubes*.
tubes, forming miniature nozzle from, P (10) 301*a*.
tubing, continuously drawn, color indicia for, and method of applying, P (7) 198*f*.
tungsten oxide phosphate, X-ray studies, (6) 169*i*.
ultraviolet absorption, (5) 129*f*.
ultraviolet absorbing emerald green, color characteristics, (4) 93*e*.
underwater structures, design parameters for, (3) 63*e*.
up-drawing method, P (7) 199*e*.
use in buildings, (6) 168*c*.

Glass (*continued*)
vacuum apparatus, decomposable joint with indium seal for, (11) 333*j*.
valve, for scientific purposes, P (5) 130*b*.
vanadate, structural characterization of, and phase separation in, (9) 264*c*.
vs. plastics, (11) 334*f*.
vitreous states, (6) 169*h*.
vitreous systems, radiation induced color centers in, (11) 334*g*.
volcanic, electrical properties and hydrothermal reactions, (8) 231*h*.
-ware molds and equipment, lubricant coating for, P (1) 9*f*.
weakening defects, (1) 8*h*.
wetting and sticking to different refractories, (10) 299*c*.
window. See also *Glass: flat, sheet, plate*.
gas laser, vacuum sealing of, P (9) 266*a*.
proper thickness for, (11) 334*f*.
radiation, P (3) 66*c*.
silver and copper coated, protected by treatment with aminoazole compounds, P (8) 236*c*.
vacuum coated, P (11) 336*h*.
windshields, strengthened, P (11) 336*a*.
wired, manufacture, P (2) 41*e*.
wool. See *Fibers, glass*.
workability, (2) 39*j*.
for X-ray cryostat, P (9) 266*b*.
yarns. See *Fibers, glass*.
Glass industry, Canadian, history, (9) 263*g*.
developments in combustion equipment and controls for, (9) 264*f*.
flat, technological progress, (2) 40*d*.
in England, new factory and new glass, (9) 263*i*.
in 1967: I, flat glass applications; II, technical glasses; III, container glass and fiber glass; IV, fiber glass in aerospace and defense applications, (11) 334*c*.
inspection packing costs reduced, (3) 64*a*.
Japanese, (5) 127*i*.
Nailsea, in England, (5) 128*k*.
productivity and technical change, (5) 128*f*.
propane use in, (11) 335*i*.
refractories in, present trends and forecast, (11) 334*i*.
sheet, modern principles based on old idea, (6) 168*g*.
(9) 264*g*.
use of natural gas in, (7) 197*k*.
Glassmaking apparatus and equipment. See also *Burners*.
P (2) 41*f*.
annealing lehr, for sheets, with reradiating side wall plates, P (9) 264*f*.
for assembling sheets during manufacture of double glazed windows, P (10) 299*i*.
for attaching member to sheet, P (6) 170*j*.
automatic molten glass level control, P (2) 40*c*.
for automatically weighing containers, P (10) 300*f*.
for beads, P (4) 94*i*.
bending chamber, for making sheet glass by drawing, P (3) 65*b*.
for bending, P (7) 199*b*.
horizontally conveyed sheets between opposed shaping molds, P (4) 94*g*.
sheets, P (4) 94*a*.
and tempering sheets by differential heating, P (11) 336*c*.
blast head, for tempering sheets with means to attach and seal nozzles to blast head, P (9) 264*j*.
blasthead structure, for tempering sheet, P (3) 65*c*.
blast nozzle, for forming silicate fibers, P (2) 40*e*.
for blending, P (2) 40*h*.
body gaging, for containers, P (1) 8*d*.
for bottle inspection, P (11) 335*h*.
for breaking sheet, P (6) 170*j*.
for bulky yarn, P (9) 264*h*.
for carrying sheets, P (11) 336*b*.
for clamping, P (1) 8*e*.
for coating, with tracking means, P (1) 8*f*.
contacting roll, internally cooled hot glass, P (8) 235*c*.
containers, randomly spaced, coder for marker, P (11) 335*i*.
for continuous examination of train of articles, P (8) 235*g*.
for continuous manufacture of continuous profiled glass members, P (1) 8*k*.
for continuous production of bar of predetermined profile, P (2) 41*e*.
conveyor, dead plate, P (7) 198*h*.
conveyor, for sheets, P (1) 8*h*.
for cooling plungers and molds, P (4) 94*g*.
coupling, mechanical, for glass and ceramic articles, P (1) 9*i*.
cutter for pipe, P (11) 335*j*.
for cutting, P (2) 40*b*; P (6) 170*b*.
cutting control, P (9) 265*f*.
cutting tool, combination swiveling and stationary, P (10) 300*e*.
for decorating, P (10) 299*j*.
for decorating container, with means for holding and indexing, P (4) 94*f*.
decorating lehr, heating section of, P (9) 265*f*.
for delivering molten sheet over lip, P (1) 8*a*.
for detecting faults in or on flat surface, P (4) 94*a*.
for detecting flaws in transparent bodies, P (4) 94*k*.
for distributing melt and forming fibers from, P (9) 264*g*.

Glassmaking (*continued*)
for drawing, in cylindrical form, P (4) 94*b,c*.
manufacture of rolls for, P (5) 130*h*.
vertically, from molten metal bath, P (2) 41*i*.
for eliminating arcing in gas-electric sealing of TV bulbs, P (4) 94*k*.
for equalizing cooling sheet supported on bending mold, P (6) 171*b*.
for etching, single surface, of plates, P (6) 170*e*.
feeders, hinged orifice ring holder for, P (10) 300*c*.
fiber attenuating, P (2) 40*f*.
fiber cooling, P (10) 300*j*.
for fibrous material, P (1) 8*j*.
for fire-polishing edge of glass object, P (1) 9*j*.
for flakes, P (1) 8*b*.
flask gages, P (1) 8*j*.
for flat, on molten metal bath, P (2) 40*a*; 41*g*.
forced stream feeding through orifice, P (2) 40*g*.
for forming, P (3) 65*h*.
articles from overlapping sheets, P (1) 8*i*.
blow molding apparatus for, P (11) 335*g*.
drive for, P (9) 265*a*.
mold cooling control apparatus for, P (3) 66*a*.
open end portion of small containers, P (1) 8*i*.
and processing continuous filaments, P (3) 65*c*.
ribbon with lateral force means, P (2) 40*j*.
ribbon on molten metal with gas seal means, P (2) 40*i*.
settle blowhead and baffle attachment for, P (3) 66*d*.
take-out tong mechanism for, P (4) 95*e*.
furnaces. See *Furnaces*.
for grinding. See *Grinding apparatus*.
gripping tongs, P (10) 300*a*.
with ballast, P (10) 300*b*.
for conveying sheets, P (4) 94*g*.
and treatment, P (10) 300*b*.
for handling article, P (4) 94*d*.
for heating draw pot of window glass machine by electrical energy, P (11) 336*g*.
for heat-treating and conveying sheets vertically oriented, P (1) 8*j*.
to identify smooth or patterned surfaces, P (4) 94*e*.
for inhibiting flow of molten bath impurities to sheet, P (11) 336*d*.
for inspection for defects by fluorescent radiation, P (10) 300*f*.
inspection, for containers, P (10) 300*h*.
for joining parts, P (5) 129*b*.
for knives, P (6) 170*c*.
for laminated glass panel, P (5) 129*c*.
for laminating, P (1) 9*f*.
lehr, with transverse temperature control, P (7) 198*i*.
loading, P (10) 300*e*.
mandrel, for precision-shaping internal surfaces on vessels, P (6) 171*d*.
mandrel supporting, P (4) 94*d*.
for melting, or other oxidic substances, P (1) 9*i*.
for melting and feeding, P (3) 65*a*.
for molding, P (6) 170*d*.
for molding hollow articles, P (8) 235*a*.
molds. See *Molds, glass*.
opposed blasthead, for toughening sheets with spaced vertical deflecting shields, P (4) 95*a*.
optical inspection, for surface coatings on articles in liquid with same index of refraction as glass, P (11) 336*d*.
for optical lenses, P (2) 41*h*.
for packaging strand material, P (4) 94*i*.
polishing head with detachable felt pad, P (1) 9*c*.
for polishing. See *Polishing apparatus*.
for positioning, P (5) 130*b*.
for prepolishing, P (2) 41*a*.
press, variable index mechanism for, P (4) 95*f*.
press bending, with modified recesses for glass sheet engaging means, P (9) 265*j*.
sheet, with conveying roller recesses, P (6) 170*d*.
and toughening, glass sheet, P (5) 129*b*.
press shaping, with means to adjust pressing surface curvature, for sheet, P (5) 130*a*.
pressure rollers, for ribbon polishing machine, P (6) 171*e*.
for preventing bubbles in float glass apparatus, P (10) 300*k*.
for processing fibers, P (11) 336*e*.
for producing fibers from high temperature fusible material, P (9) 264*i*.
for producing multiple sheet glazing unit, P (8) 235*d*.
for production of coating layer of glass material, P (10) 300*b*.
for protecting sheet during thermal treatment, P (10) 300*i*.
protecting slipper for edge roller in support bath for sheet, P (6) 171*e*.
for purging, P (3) 66*b*.
for removing tipped-over bottles from conveyor, P (5) 129*d*.
for reshaping neck portion of small glass bottles with lubricating means, P (1) 9*g*.
for shaping open end of tubes between cooperating rollers, P (4) 94*d*.
for sheet, P (11) 335*f*.
by drawing, P (2) 42*f*.
glazing unit, spacers for, P (2) 42*e*.
on molten bath, P (3) 64*j*.
sheet press bending, with indexed cover over shaping surface, P (9) 265*e*.
for skimming dross from molten metal bath, P(1) 8*c*; P (9) 265*a*.
for spinning, continuous, P (8) 235*c*.

Glassmaking apparatus (*continued*)
spout, for discharge of molten glass, P (2) 42*e*.
spray mist proportioning system for, P (2) 42*e*.
for spreading chopped fibers, P (4) 94*j*.
strand delivery, P (10) 301*a*.
for supporting, and gaging cathode ray tube faceplate, P (5) 130*f*.
and heating sheets on gas bed, P (6) 170*e*.
ribbon on molten metal bath with glass ribbon heel flow means, P (2) 40*b*.
sheet in upright position for heat treating, P (3) 65*b*.
for surface treatment, P (3) 66*d*.
temperature control, for glass molding process, P (6) 170*f*.
for tempering between cold plates, P (5) 130*g*.
for testing automobile windows, P (8) 236*a*.
thermal homogenization, for drawing in sheet form, P (3) 65*a*.
for toughening sheets with reserve zone, P (11) 336*b*.
for toughening windshields, P (10) 300*b*.
for up-drawing, P (7) 199*e*.
for working of pasty fusion products, P (8) 235*g*.
for yarn processing, P (2) 41*h*.

Glazes. See also *Decoration*.
bubble formation in, gas analysis study of mechanism of, (7) 206*c*.
celadon, (4) 98*d*.
ceramic, optical properties, (10) 306*a*.
ceramic, for thick film microelectronics, (7) 207*a*
for ceramic articles, P (2) 49*c*.
fast fire, ceramic stains in, (9) 270*i*.
frits. See *Frits*.
granulated zinc oxides for, (7) 206*g*.
for high alumina substrates for Ta thin film circuitry, (6) 176*j*.
industrial color measurement, practical problems in, (10) 306*c*.
interaction with porcelain body, determination of degree, (5) 136*j*.
iron, relation with content of ferrous oxide and shade of, (9) 271*d*.
for lithia ceramics, (8) 242*a*.
majolica, for dinnerware, (9) 270*j*.
opaque, making with zircon, (5) 136*g*.
pottery, cracking in: I, dolomite earthenware glazes, (9) 271*g*.
for sewer pipe, (10) 301*j*.
strontium, B (10) 329*b*.
strontium leadless colored, for earthenware, new compositions for, (8) 242*e*.
substantially anhydrous ceramic, in propellant-type cans, P (8) 242*f*.
thallium oxide, with ruthenium oxide additive, P (2) 52*g*.
zircon opacified, for sanitary porcelain, fired at cone 9, (6) 175*f*.

Glazing, and decorating ceramic tile, P (5) 137*c*.
glass articles, apparatus, P (11) 335*d*.
of ignimbrite building stone, (1) 15*a*.
and sanding automatic machine, for electrical insulators, P (8) 242*d*.
semicrystalline glass-ceramic articles and resultant intermediate layer containing composite, P (8) 235*h*.
silicon nitride shaped body, and article, P (10) 304*g*.
unit, multiple sheet, P (11) 336*c*.

Glossaries. See *Nomenclature*.

Gold, colloidal, effect on formation of lithium metasilicate crystallites in photosensitive opal glass, (1) 5*h*.
decorating compositions and method, P (10) 312*c*.
deposits, structure on rocksalt substrates, (10) 308*f*.
films, single crystal, tensile behavior, (5) 159*e*.
liquid, factors affecting quality, (8) 242*a*.
and silver, single crystal high-purity films, epitaxial growth on MgO cleaved in ultrahigh vacuum, (5) 152*e*.

Goniometers, supports for crystal during analysis and cutting, P (8) 249*b*.
X-ray diffraction, with specific drive mechanism for specimen holder and detector, P (4) 103*j*.

Grain boundaries, of barium titanate, contribution to optical dielectric constant, (11) 341*j*.
degeneration, in materials which contain inert gas, theory, discussion, reply, (1) 326*g*.
energies, in NaCl rigid lattice approximation, (6) 180*a*.
geometry, (8) 253*j*.
grooving in uranium dioxide, (11) 353*g*.
in irradiated UC, sweeping of bubbles by, (10) 325*g*.
mobility, technique for measuring, and application to KCl, (6) 189*j*.
segregation, in final-stage sintering of Y_2O_3, (1) 29*e*.

Grain growth, columnar, of sintered UO_2, effect of organic additions, (9) 281*i*.
data, log-log plots in analyzing, (9) 275*j*.
during hot-pressing of tantalum carbide, (5) 153*b*.
during sintering of ZnO, (10) 325*i*.
kinetics, in BeO, (3) 67*h*.
in porous compacts, comments on theory, (9) 282*e*.
simultaneous, effect on high-temperature creep of polycrystalline magnesia, (7) 218*d*.
surface, of alumina, effect of metal oxides, (10) 319*h*.
in two phase (one solid + one liquid) and in three-phase (two solid + one liquid) systems, factors controlling, (5) 152*a*.
of UO_2, effect of vanadium oxide additions, (7) 201*c*.
in UO_2–Al_2O_3 in presense of liquid phase, (8) 254*c*.
in zirconium diboride during sintering, (8) 237*c*.

Grains. See *Particles*.

Granular materials. See also *Powders*.
conditioning apparatus, P (6) 174*b*.
homogenization chamber for, P (10) 312*d*.
method and apparatus for measuring and adjusting moisture content, and formability of, P (6) 174*e*.
roofing, intumescent coated, and asphalt composition felt-base roofing containing, P (5) 131*b*.
testing appartus, P (3) 76*f*.

Granulation. See also *Crushing; Grinding*.
of substances from melt, P (2) 56*j*.
vibro-, of raw materials for cement, (2) 37*b*.

Granulometric analysis. See *Analysis*.

Granulometry. See *Particle size*.

Graphite. See also *Carbon*.
aluminum nitride coating for, (5) 131*f*.
anisotropic, interaction between dislocation loops and straight dislocations, (1) 29*f*.
annealing of irradiation damage in, (4) 106*a*.
arc electrode with ball tip, P (11) 347*e*.
artificial, Young's modulus, effect of porosity and crystalline orientation, (4) 108*d*.
bodies, method for impregnating, and article produced, P (1) 13*d*.
borated, radiation-damage effects in, (4) 114*f*.
brazed expanded pyrolytic, thermal conductivity to 700°C, (9) 269*f*.
brick structures, for nuclear reactor, P (1) 12*g*.
bromination and irradiation growth, comparison, (5) 131*g*.
columns, influence of cross-sectional shape on irradiation-induced stresses in, (3) 81*j*.
commercial, stress dependence of creep rate of, (4) 116*h*.
compounds, optical transmission, (6) 187*a*.
Compton profiles, (4) 107*a*.
compressive strength, effect of oxidation, (8) 253*h*.
contact reaction with metallic borides at high temperature in vacuum, (2) 46*e*.
containing segmented thermoelement, and method of molding, P (10) 304*e*.
corrosion, inhibiting in CO_2-cooled nuclear reactor, P (6) 174*g*.
crystallization, (11) 351*f*.
dislocation loops in, Bergers vector, (1) 26*f*.
effect on microstructure and drying shrinkage of clay, (6) 172*j*.
EGCR-type, fracture toughness determination, (2) 43*i*.
epitaxial growth of UO_2 on, (9) 282*e*.
filament, pyrolytic coatings for, P (5) 136*c*.
graphitic materials, hot-worked with dispersed liquid carbide, thermal and electrical conductivity, (8) 254*d*.
-hydrogen reaction, reaction products formed at 1300° to 1400°C, (4) 113*h*.
impregnation, metallic, method and apparatus, P (11) 340*h*.
interstitial loops, their motion and effect on elastic modulus, (4) 111*i*.
irradiated, relation between irradiation temperature, flux intensity and start temperature for stored energy release in, (4) 115*f*.
K emission band, (4) 112*h*.
lattice parameters, effect of high pressure, (7) 217*b*.
lead-in rods, contact resistance of, (10) 306*h*.
materials, for seals, bearings, and brushes, (2) 49*d*.
metal body composite, P (8) 240*f*.
neutron-bombarded, electron spin resonance, (4) 109*c*.
non-basal edge and screw dislocations in, identification and physicochemical consequences, (1) 29*d*.
nuclear grade, deformation characteristics, (7) 201*c*.
oriented, P (1) 13*h*.
oxidation, anisotropy in, (10) 319*a*.
physical properties, effects of irradiation at 77°K, (8) 239*g*.
plasma and diffusion coatings on, (5) 133*a*.
polycrystalline, fracture in, (7) 201*i*.
powders, diffusional metallization, (2) 43*g*.
powders, sintering during thermochemical treatment with carbide-forming elements, (8) 239*a*.
process for making, P (8) 241*a*.
pulse propagation of thermal neutrons in, (9) 268*d*.
pyrolytic, and boron nitride bodies, heat treating with simultaneous application of multiaxial tension, P (2) 47*a*.
compressibility, (5) 150*f*.
foam and foil preparation, (5) 133*e*.
and isotropic, studies of attack by atomic and molecular oxygen at high temperatures, (7) 200*f*.
method of producing, P (6) 175*e*.
and nuclear fuel particles coated with, P (4) 97*f*.
vapor deposition on tungsten, P (7) 195*f*.
whisker production, P (7) 205*j*.
reaction with sodium at 400°, (6) 188*d*.
reactions, under exploding wire conditions, (2) 45*i*.
reactor, elastic constants, (3) 67*d*.
reactor, Young's modulus, effect of stress and annealing, (8) 253*i*.
refractory, and method of producing, P (6) 175*d*.
refractory coating for, P (5) 135*j*.
relation of accommodation factors in, (10) 325*b*.
single crystals, multilayer vacancy loops in, (1) 30*b*.
strength, under biaxial stresses, (6) 189*d*.

Graphite (*continued*)
structures, compressed vermicular, production, P (9) 270*d*.
low density, preparation, P (9) 270*c*.
in nuclear reactors, P (7) 204*d*.
vermicular, P (9) 270*c*.
thermal assembly jigs, (1) 11*j*.
thermal conductivity, parallel to basal planes, and velocity of phonons in "out-of-plane" acoustic mode, (4) 117*h*.
transformation, to diamond, catalytic effects, (5) 149*j*.
transport properties in, (4) 117*g*.
wetting, temperature influence on adhesion of metals inert to carbon in, (7) 195*f*.

Gravimetric analysis. See *Analysis*.

Grinding (*Comminution*). See also *Crushing apparatus; Mills*.
accelerated, composition for, P (1) 1*g*.
amorphous hydrophilic silica aerogel, P (5) 148*a*.
dry, of alumina, P (4) 105*a*.
dry, size distribution shift in, (5) 148*h*.
dry ball mill, of ceramic aluminas, (4) 101*h*.
method and apparatus, P (2) 56*i*.
of mineral pigments or fillers, white or pastel, P (11) 349*h*.
operations, P (3) 75*a*.
for product sizing control in closed circuit, P (11) 346*a*.
properties, relation with lattice energy of crystalline materials, (7) 211*f*.
of quartz, mechanical and thermal activation, surface layer, (5) 148*b*.
and calcite, effect of surface active reagents, (1) 21*g*.
calcite, barite, and halite, to lower micron size range, (4) 101*j*.
of raw materials for radio ceramics, accelerating with silicone liquids, (8) 242*h*.
separate, of limy clay and sand, importance for clinker mineral formation during cement burning, (10) 294*i*.
surface, effect on physical properties of high alumina ceramic, (7) 211*d*.

Grinding (*Material removal*). See also *Abrasives; Diamonds; Polishing*.
carbide, variables affecting diamond wheels in, (9) 261*h*.
central systems approach, (5) 123*g*.
deburring tumbling media, P (7) 193*i*.
diamond machining, ultrasonics for better accuracy and cutting rates, (3) 61*f*.
electrolytic, coated abrasives for, P (7) 193*h*.
flat lapping, (3) 61*e*,*f*.
steel, with metal-clad diamonds, (6) 163*i*.
theory, (2) 35*h*.

Grinding apparatus. See also *Abrasives*.
disk, abrasive, P (9) 261*i*.
in fluidized layer, P (8) 251*c*.
pad, for glass, P (3) 65*i*.
with rolls with stepwise-increasing speeds, P (6) 179*e*.
rotating, P (8) 251*h*.
for solids, P (4) 101*j*.
wheels, abrasive, apparatus for testing, (10) 293*g*.
abrasive, dressable heat conductive backing for, P (9) 261*i*.
abrasive, with microcrystalline sintered bauxite abrasive grain, P (9) 261*g*.
annular cutting, method and apparatus for making, P (3) 61*h*.
apparatus for molding resin bearing surface on, P (3) 61*f*.
diamond, "D" dropped from designation, (5) 123*g*.
diamond, in carbide grinding, variables affecting, (8) 227*f*.
diamond, in carbide grinding, variables affecting, (9) 261*h*.
diamond, dressing apparatus for, P (11) 331*f*.
diamond, peripheral, P (5) 123*j*.
diamond abrasive (2) 35*h*.
with diamond abrasive article containing hexagonal crystalline boron nitride particles, P (8) 227*h*.
glazing, (6) 163*g*.
for lenses, P (7) 193*f*.
method of making, P (7) 193*h*.
performance test: III, grinding of stainless steels, (1) 1*g*.
resin-bonded, apparatus for making, P (10) 293*g*.
structure, (10) 293*g*.

Gunning, materials, hot, for basic oxygen furnace maintenance, (4) 96*e*.
mix, castable, P (4) 97*b*.

Gypsum. See also *Plaster*.
alpha, process and apparatus for continuous production, P (6) 166*a*.
-anhydride equilibrium at one atmosphere pressure, (5) 153*e*.
articles, with improved strength to density ratio, method of producing, P (4) 92*f*.
composition, with dehydration resistant characteristics, P (10) 296*b*.
continuous production from waste sulfuric acid pickle liquor and calcium compound, P (7) 194*i*.
dehydration, (6) 164*f*.
drying or calcining, method and apparatus, P (2) 37*f*.
phospho-, treatment to form building plaster, (10) 296*b*.
product, and method of making, P (5) 125*d*.
solubility, at 100° to 140°C, (11) 331*j*.
systems, interrelation of hardness, modulus of elasticity, and porosity in, (7) 194*h*.
transformation to hemihydrate in water, (2) 36*d*.

Hafnium, boride, alloying behavior with uranium and transition metal diborides, (9) 279*h*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
carbide, chemical vapor deposition, (10) 306*j*.
carbide, high-temperature heat content, (5) 153*j*.
diboride, reaction with carbon, (3) 85*j*.
sulfides, lower, at high temperature, (4) 112*e*.
systems. See *Systems*.
Halides, alkali, corresponding-states melting curve at high pressure for, (7) 216*j*.
alkali, crystals, magneto-optical properties of defect centers in, (9) 284*j*.
crystals, pressure dependence of dislocation mobility in, (4) 114*c*.
external modes of vibration of small polyatomic ions isolated in, (11) 352*i*.
impurity-induced near-infrared spectra as source of information about frequency distributions of, (10) 322*c*.
intrinsic photoconductivity in, (8) 254*d*.
linear relationship for heavy-ion pulse heights in, (9) 283*j*.
parameters of *F* center in, (11) 356*h*.
room-temperature deformation luminescence in, (8) 256*g*.
two-photon absorption in, with pulsed N_2 laser, (11) 357*j*.
wave functions for F′ centers in, (9) 288*e*.
zero-phonon transition at *M′* and *R′* centers in, (11) 358*c*.
di-, alkaline-earth, geometry, (5) 153*b*.
hydrogen, use in insulating oxide and nitride deposits, P (6) 178*j*.
metal, polynuclear, chemistry, (4) 106*d*.
metal, vapor phase oxidation, to form metal oxides of pigmentary size, and apparatus, P (8) 251*j*.
tetra-, zirconium and silicon, production, P (2) 57*b*.
Hall effect, data, in PbS polycrystalline films, interpretation, (6) 176*b*.
high-field, of semiconducting CdS, (4) 111*f*.
with metals in conductive CdS single crystals, 153*h*.
piezo-, in *n*- and *p*-type aluminum antimonide, (11) 355*b*.
of VO_2 powder, (10) 321*f*.
Halloysite, suspensions, model for rheology, (6) 187*g*.
Halogens, use in insulating oxide and nitride deposits, P (6) 178*j*.
Hardening, of cements in system $ZnO–P_2O_5–H_2O$, (2) 37*d*.
of glasses, in polyethylsiloxane liquids and in melts of heavy metals, (6) 167*g*.
of nonhydraulic lime mortars as crystallization process, (3) 62*i*.
of portland cement, accelerated, P (6) 165*j*.
and sorel cement analogs, (2) 36*j*.
Hardness, abrasion, of diamond, effect of neutron irradiation, (2) 35*g*.
of diamond at high temperatures, measurement, (10) 323*e*.
of glass, in bibliography, B (8) 258*i*.
interrelation with modulus of elasticity and porosity in various gypsum systems, (7) 194*h*.
measurement apparatus, for bonded abrasive, P (1) 1*f*.
micro-, of crystallized glass materials, dependence on morphology of crystalline phases in spinel-silica system, (9) 280*c*.
determination by scratch tests, (10) 315*a*.
of glass, dependence on applied load, (10) 297*g*.
high-temperature, of semiconductors, measurement, (11) 346*e*.
tests on refractory raw materials and products, (6) 180*i*.
use of NaCl crystals as standard measure of, (10) 316*d*.
microindentation, and elasticity and Poisson's ratio of glasses, (7) 196*f*.
of plasters, determination by drilling strength, (10) 294*j*.
of silicides of rare-earth metals, (9) 282*h*.
testing, at elevated temperatures, (2) 54*f*.
testing, penetration-body, P (5) 147*b*.
Health. See also *Air, pollution; Dusts; Safety; Silicosis*.
effect of powdered alumina on china bisque placers in Stoke-on-Trent, (6) 191*b*.
Heat. See also *Conductivity, thermal; Temperature*.
calculated, of dilute solid solution among alkali halides other than cesium salts, (10) 319*e*.
capacity, low-temperature, of three uranium nitrides, (3) 87*h*.
low-temperature, of V_3Si with stress, pronounced change in, (9) 285*h*.
of plutonium monophosphide and monosulfide, (8) 258*a*.
and related thermal data for diethyl phthalate crystal, glass, and liquid to 360°K, (4) 110*j*.
of solids within wide rage of temperature, apparatus for measuring, (11) 346*c*.
of three inorganic glasses and supercooled liquids, (8) 232*h*.
of uranium mononitride from 5° to 350°K, (10) 327*b*.
of UP and U_3P_4, (7) 222*e*.
characteristics, of single-thickness ceramic panels, (10) 302*b*.
content, of α-alumina, and high-temperature adiabatic drop calimeter for measuring, (7) 218*b*.
of anatase-rutile transformation, (1) 29*a*.
determination, and calorimeter apparatus, P (6) 181*d*.
Heat content (*continued*)
of fusion of $PbO·2B_2O_3$, (8) 253*f*.
of fusion of UO_2, determination, (2) 58*a*.
high-temperature, of dehydrated analcite, kaliophilite, and leucite, (6) 186*h*.
high-temperature, of niobium carbide and tantalum carbide, (5) 153*j*.
high-temperature, of sodium bromide and sodium iodide, (4) 111*j*.
high-temperature, of TiC and ZrC, (3) 81*c*.
high-temperature, of tungsten carbide and hafnium carbide, (5) 153*j*.
high-temperature of UO_2, (6) 186*g*.
of hydration of UO_3, calorimetric determination, (4) 106*j*.
of $KAlSi_2O_6$ and $NaAlSi_2O_6$ fusion, (2) 58*g*.
of reaction of gamma UO_3 with fluoric acid, (9) 282*d*.
of solution to dissolve NaF and VF_3 in CaF_2, Born model calculation, (1) 26*f*.
of solution of type MO oxides in vanadium(V) oxide, (6) 186*c*.
of sublimation of beryllium fluoride, (11) 357*e*.
of uranium dicarbide from 1484° to 2581°K, (5) 153*h*.
of uranium nitrides, (3) 87*h*.
content of formation, of gamma UO_3, (9) 282*d*.
of kyanite, (5) 152*d*.
of lanthanum and praseodymium fluorides, (9) 282*c*.
of lithium metahafnate, (10) 321*a*.
of magnesium-aluminum spinel, (6) 186*d*.
of M_3VCl_6 and $M_3V_2Cl_9$, (10) 321*b*.
of niobium and tantalum pentafluorides, (11) 352*j*.
of $K_2Cl_2·BaCl_2$, (10) 321*a*.
of RuF_5, (11) 353*a*.
of sodium, potassium, and barium metatitanates, (9) 282*c*.
of titanates of zinc, (3) 80*j*.
of YF_3, (11) 353*a*.
conversion, to electricity by electrochemical means using UO_2 melt, P (5) 134*k*.
cycling, effects on uranium-carbon alloys, (6) 172*j*.
of dissociation, of gaseous alkali earth dihydroxides, (3) 81*j*.
effect on ceramics, institute of ceramics textbook series B, (1) 34*i*.
exchange, in combustion area of glass melting furnace, (6) 167*i*.
rings, extruded, apparatus for producing from plastic mass, P (10) 304*a*.
system, for calciner, P (11) 332*a*.
exchangers, graphite, for high pressures, (10) 316*j*.
rotary, with chain drive, P (9) 278*c*.
rotary, and hot-gas engines, seal for, P (6) 175*b*.
with rotatable tubular structure, P (8) 229*c*.
flow meters, (2) 54*g*.
of formation, of aluminum diboride and α-aluminum dodecarboride, (4) 111*c*.
of boron carbide, (9) 282*j*.
of germanium tetrafluoride and germanium dioxides, (3) 81*j*.
of metatitanates of calcium, strontium, and barium, (1) 29*a*.
of metatitanates of lithium and magnesium, (1) 29*a*.
of phosphorus pentafluoride, (3) 81*i*.
of fusion, of UO_2, (6) 186*g*.
of fusion, from $UO_2–PuO_2$ phase diagram, (10) 322*a*.
of hydration, of Egyptian portland cement and fly ash mixtures, (5) 125*a*.
of immersion: VIII, differential heats of adsorption as function of particle size for alumina–water system, (11) 353*i*.
losses, in refractory walls and structures, calculation, (10) 302*f*.
measurement, P (2) 55*f*.
resistance, of GaAs laser diodes, (4) 118*d*.
of glass products, (3) 63*j*.
of refractories: II, high-temperature apparatus to obtain thermal conductivity and thermal shock resistance, (5) 134*h*.
resistant materials, containing molybdenum disilicide, P (1) 12*h*.
of solution, measurement by calorimeter, (7) 211*j*.
specific, behavior near ferroelectric transitions, (10) 319*d*.
of boric anhydride and soda-borate glass at low temperatures, (7) 197*j*.
of NaCl, (8) 256*c*.
storage capacity, of refractories for furnace and kiln construction, (8) 237*g*.
transfer, characteristics, for dilute gas-solid mixture in externally heated tube, numerical method for determining, (1) 24*e*.
coefficients, for continuously recirculated gas-solid suspensions, (5) 148*a*.
coefficients, measurement in turbulent boundary layers with forced convection, (6) 167*h*.
phenomena, simulation in rotary kiln, (1) 24*g*.
plasma, in verneuil crystal growth, (2) 59*a*.
radiant, in fibrous thermal insulation, (5) 133*a*.
of refractories, in high temperature tunnel kiln, computation of effect, (9) 267*a*.
thermophysical and electrical parameters, in molten glass, (10) 299*f*.
from waste gas of cement kiln to pulverulent raw material, P (8) 229*a*.
of transition, in $NaBO_3$, (9) 283*a*.
transport, from metals to insulators at low temperatures, (8) 258*a*.
Heat (*continued*)
treating, of metal in molten bath of borate glass, P (9) 265*i*.
of powdered particle material, P (8) 251*d*.
pyrolytic graphite and boron nitride bodies with simultaneous application of multiaxia tension, P (2) 47*a*.
treatment, of anodic oxide films on tantalum: IV, anodization in phosphoric acid solutions, (7) 207*b*.
conditions, influence on mechanical and dielectric properties of spinel-corundum highly refractory ceramics, (8) 238*b*.
effect on mechanical properties of fibers of natural and synthetic amphiboles, (2) 44*a*.
effect on phase composition and microstructure of vitreous crystalline materials based on slags, (11) 333*e*.
effect on thermal expansion of lithia ceramics with β-eucryptite composition, (8) 241*j*.
effect on thermally oxidized silicon, (5) 151*j*.
of high-melting solids in fine particle form, P (2) 47*b*.
of oxygen-doped silicon single crystal, (5) 158*e*.
of vitreous fibers, P (2) 41*c*.
true specific, of refractory materials, measurement during cooling, (5) 146*f*.
waste, from tunnel kilns, for drying brick, (2) 42*h*.
Heat conductivity. See *Conductivity, thermal*.
Heaters. See also *Thermoelectricity*.
electric resistance, P (10) 309*b*.
high frequency dielectric, P (1) 24*c*.
high temperature electrical, P (7) 213*i*.
high-temperature of niobium and zirconium carbides, (5) 132*e*.
Heating. See also *Thermoelectricity*.
curves, of solids obtained by solar furnace, (4) 111*b*.
and drying, method and apparatus, of gravel and crushed stone, P (4) 105*g*.
electric, booster, use in small regenerative glass furnaces, (8) 234*k*.
flash, of $KMnO_4$, (10) 321*e*.
glass, method and apparatus, P (7) 199*b*.
metal, P (1) 4*k*.
panels, radiant, and resistive compositions for, P (11) 332*j*.
pre-, apparatus, for cement raw meal, P (4) 92*f*.
rods, for electric furnaces, (7) 213*i*.
tank furnaces, use of mazout for, (2) 56*a*.
unit, stacked dish infrared surface, P (3) 77*b*.
Heating elements. See also *Electrodes; Thermoelectricity*.
$Al_2O_3–MoSi_2$ composition, (6) 172*e*.
electric, P (4) 104*b*.
electrical, method of making, P (3) 73*b*.
graphite, for electric resistance furnace, P (11) 348*f*.
method of making, P (3) 73*c*.
sheathed electric, P (8) 230*a*.
Heavy clay industry. See *Structural clay products industry*.
Helium, in beryl, aquamarine, quartz, and related glasses, composite diffusion mechanisms and diffusional anisotropy of, (3) 79*j*.
desorption, from micas, (3) 79*i*.
dissolution in UO_2: I, interatomic forces in UO_2; II, helium solubility, (6) 190*b*.
^{3}He, liquid, thermal equilibrium with powdered cerium magnesium nitrate at low temperatures, (10) 326*j*.
Hematite. See also *Iron, oxide, ferric*.
crystal, entropy change at Morin point of, (4) 109*i*.
ferromagnetic domain structure in, (1) 29*d*.
Heterogeneity, chemical, of borosilicate glasses, determination by dielectric losses, (8) 231*e*.
measurement, optical glass, autocollimation method of, (5) 126*k*.
Holmium, chloride, reaction with NaCl, (10) 324*f*.
Homogeneity, in glass, instrument for measuring, (5) 127*k*.
in-, chemical, in glass sheets, (1) 5*c*.
in-, in slip casting and ceramic bodies, formation and causes, (10) 305*f*.
measurement, of optical materials in visible and near infrared, (9) 263*h*.
of microscopic particles, (3) 75*d*.
optical glass, measurement with help of autocollimation method, (5) 128*i*.
problem, of lithium aluminosilicate glasses, (8) 233*e*.
and structure of glass, (10) 297*f*.
Hot tops. See *Refractories*.
Humidity. See also *Moisture; Water*.
sensing device, process for making, P (5) 130*c*.
Hydrates, hydroniuum, $H_9O_4^+$ and $H_{13}O_7$ in minerals, (6) 185*h*.
Hydration, of ashes, basic, effect of hydrochloric acid treatment on, (6) 164*b*.
of calcium aluminoferrite phase and glass in portland cement clinkers, (8) 228*e*.
of $3CaO·SiO_2$ and $β$-$2CaO·SiO_2$ with quartz or slag at ordinary temperature, (1) 32*a*.
cement, control by ultrasonic method, (10) 294*g*.
cement, effect on concrete form pressure, (5) 124*g*.
of ceramic materials under high steam pressure, (8) 240*i*.
heat of. See *Heat*.
kinetics, of cement constituting minerals, (2) 36*c*.
kinetics, of tricalcium aluminate in presence of $CaSO_4$ and $CaCl_2$, (3) 62*i*.
mechanism, of $3CaO·SiO_2$, (9) 262*d*.
paste, of high alumina cements, studies of early stages, (1) 3*a*.

Hydration (*continued*)
of plaster slurry, ionic concentration in suspending liquid during, (10) 295*g*.
of portland cement and clinker materials, effect of chlorides, (8) 228*h*.
of portland cement and clinker minerals, effects of sucrose, *d*-glucose, and dextrin on, (11) 331*j*.
of praseodymium sesquioxide, (3) 85*a*.
products, of portland cement, adsorption of admixtures on, (2) 36*c*.
rate of β-$CaSO_4 \cdot {}^1/_2H_2O$, effect of storage, (2) 36*j*.
re-, of plaster, (6) 164*f*.
studies, by time-lapse photomicrography, (10) 294*h*.
surface, of γ-alumina, infrared and gravimetric study, (11) 353*d*.
of tricalcium silicate, (11) 353*c*.
in presence of potash at different temperatures, (6) 164*i*.
stoichiometry, (3) 62*e*.
vapor phase, of MgO, kinetics: II, dependence on temperature and water vapor pressure; III, effect of iron oxides in solid solution, (3) 82*j*, 83*b*.
Hydrides, alkaline earth metals and lithium, production, P (5) 149*b*.
properties, comparative predictions of, (9) 280*c*.
Hydrocarbons, catalytic conversion, with steam treated Y type of crystalline aluminosilicate, P (10) 318*a*.
conversion, by novel cyclic catalytic process, P (4) 105*a*.
process and catalyst, P (7) 214*d*.
process, and catalyst comprising Y-type crystalline aluminosilicate promoted with polyvalent metal, P (4) 105*c*.
Hydrochloric acid, treatment, effect on hydration of basic ashes, (6) 164*b*.
Hydrocracking, nitrogen-contaminated hydrocarbon charge stocks, P (4) 105*d*.
Hydrogen, atomic, spin relaxation, in fused silica, temperature dependence, (10) 325*b*.
crystals, reaction with potassium chloride crystals doped with nitrite and nitrate, (3) 85*i*.
cyanide, adsorbed on evaporated alkali halides, infrared spectrum and spectral shifts, (3) 82*g*.
graphite-, reaction, reaction products formed at 1300° to 1400°C, (4) 113*h*.
sulfide, dissociation by iron films, kinetics, (3) 82*e*.
Hydrogen ion concentration, effect on adsorption of 13 *s*-triazine compounds on montmorillonite clay, (5) 155*a*.
measurements, industrial, (11) 346*c*.
Hydrolysis, of aluminum alkoxides, P (11) 349*f*.
of dicarbides of rare earth metals [Y, La, Ce, Pr, and Gd], (10) 321*j*.
of uranium, thorium, and aluminum carbides in D_2O, (4) 111*a*.
Hydrophone, deep submergence, P (5) 140*j*.
Hydrothermal process, reactions, of volcanic glasses, (8) 231*k*.
Hydrothermal synthesis. See *Synthesis*.
Hydroxides, molten, diffusion-controlled attack of glass surfaces by, (1) 5*b*.
Hydroxyl, as defect of perovskite $BaTiO_3$ lattice, (10) 322*a*.
Hysteresis, loss, in barium titanate, (5) 138*f*.
Hygrometers, and method of making, P (1) 18*d*.

Ignition, of uranium mononitride and uranium monocarbide in oxygen, (2) 44*e*.
Illite. See also *Clays*.
chemical composition, (1) 26*i*.
method for determining post-depositional alteration, (4) 103*c*.
and mixed-layer illite/montmorillonites, mineralogy, (2) 59*b*.
nature, B (7) 224*a*.
Immiscibility, in granitic melts, indicated by fluid inclusions in ejected granitic blocks from Ascension Island, (4) 111*c*.
high-temperature, of uranium mono- and dicarbides, (11) 353*a*.
metastable, in BaO–Li_2O–SiO_2 system, (3) 64*f*.
metastable, in B_2O_3–SiO_2 system, (2) 59*a*.
subliquidus, in binary alkali borates, (8) 257*j*.
Impregnation, metallic, of carbon and graphite, method and apparatus, P (11) 340*h*.
of resin coated wound glass fiber package, P (8) 235*b*.
vacuum, of porous specimens prior to microscope examination, (2) 55*a*.
Impurities, Cr^{3+}-ion, Mn^{4+}-ion and OH-ion, reactions with vacancies in magnesium oxide, (11) 355*i*.
distribution in MgO, addenda, (1) 26*c*.
distributions in single crystals: I, impurity striations in nonrotated InSb crystals, (10) 322*b*.
effect on formation of red and yellow PbO, (5) 151*g*.
effects, on heterogeneous nucleation from vapor, selenium on glass, (5) 127*d*.
group IV, in solution grown gallium phosphide, solubility and electrical behavior, (4) 116*b*.
influence on Curie temperature of ferroelectric crystals, (9) 283*b*.
isomorphic, behavior in process of cocrystallization in open systems, (1) 26*i*.
removing from precipitation system of Bayer process, P (6) 183*c*.
uptake, by azide crystals, (7) 219*a*.
-vacancy complex, effect on degree of compensation in compound semiconductors, (10) 320*d*.
Index of refraction. See *Refractive index*.

Indium, antimonide, acoustoelectric oscillations with field-dependent period in, (5) 149*e*.
antimonide, alloys, with InTe, In_2Te_3, and tellurium, (7) 207*a*.
and arsenide, thin layers, method of producing, P (2) 51*g*.
compound, solid phases, thermodynamic properties, (6) 190*g*.
crystals, nonrotated, impurity striations in, (10) 322*b*.
high-pressure phases, structure and superconductivity, (10) 325*d*.
interband magnetoabsorption and Faraday rotation in, (11) 353*f*.
laser structures, planar, solution regrowth, (7) 208*c*.
millimeter wave radiation, (5) 154*j*.
monocrystalline layers, process of producing, P (3) 74*c*.
-NiSb, quasi-binary section in ternary system In–Sb–Ni, (1) 31*e*.
n-type, nonlinear galvanomagnetic effect in quantum limit, (9) 284*i*.
sound wave interactions in, (11) 342*j*.
structure at high pressures, (6) 189*h*.
arsenide, cross substitution in, (4) 107*d*.
optical second-harmonic generation produced by interaction of laser beams and drifting carriers in, (11) 355*d*.
reaction with cadmium iodide, (10) 324*g*.
and glass bimetallic composites, stress in, (8) 229*f*.
InBi, ultrasonic attenuation and magnetic susceptibility, quantum oscillations in, (9) 285*h*.
InOF, preparation and properties, (1) 31*a*.
In_2O_3, evaporation coefficient, systematics, (7) 222*b*.
In_2O_3 bands, passivating internal, forming in silver-indium alloys, P (7) 210*b*.
In_2O_3 crystals, grown from PbO–B_2O_3 melts, habit changes and growth mechanisms, (10) 321*f*.
InP, photoelectric emission and work function, (8) 256*a*.
oxide, coating, electroconductive transparent, method for deposition, P (3) 73*e*.
sulfide, films, evaporated, dielectric properties, (10) 308*a*.
systems. See *Systems*.
telluride-indium antimonide quasi-binary phase diagram, (4) 117*a*.
Inesite, X-ray and infrared absorption studies show $[(Si_2O_5)_2]_\infty$ type chains in, (2) 58*g*.
Infiltration, of metals. See *Impregnation*.
Infrared, optical materials, nonoxide chalcogenide glasses, (9) 263*j*.
radiation. See *Radiation*.
studies, of B_2O_3–BF_3 system, (5) 153*e*.
of rutile surface, (3) 82*k*.
of variation of H-bonded OH in synthetic α-quartz, (5) 153*f*.
techniques, for studying adsorption of volatile vapors by clays, (6) 180*g*.
Infrared absorption. See *Absorption*.
Infrared emission. See *Emission*.
Infrared spectra. See *Spectra*.
Inspection. See *Quality control*.
Instrumentation. See also *Controls*.
basic concepts, (6) 180*f*.
process, new, (4) 101*i*.
Instruments. See also specific types.
conductivity meter, self-contained, with tubular glass electrode assembly, P (1) 24*a*.
Coulter Counter, for determination of grain-size distribution, (6) 180*f*.
electronic particle study apparatus, P (11) 347*g*.
Elliott, for measuring densities of ceramic and cementitious materials, (5) 145*d*.
for glass melting control, (2) 39*d*.
heat flow meters, (2) 54*g*.
for measuring planes and vectors in space, (5) 145*c*.
for measuring strain and homogeneity in glass, (5) 127*k*.
for mixing and dividing test sample of material, P (1) 23*i*.
porosimeter, P (6) 181*f*; P (9) 277*h*.
porosimeter, electrical, P (6) 181*e*.
potentiometer, for electrical measurements, (11) 346*b*.
potentiometers, new, gives 5-digit accuracy, (3) 75*j*.
recorder, for analyzing particle distributions of powders, P (7) 213*b*.
stylometer, FES-1 photoelectric, for analysis of agglomerates, (11) 346*b*.
surface meter, for measuring specific surface of mineral powders, (11) 346*d*.
Insulating material, dielectric properties, measurement and control, (5) 138*j*.
electrical, operation at high temperatures, (5) 136*i*.
halogens and hydrogen halides, in oxide and nitride deposits, P (6) 178*j*.
of vermiculite, heat and/or sound, or refractory, P (5) 135*f*.
Insulation, acoustical, and absorption, (7) 214*c*.
ceramic, method of making, P (6) 174*g*.
panel, with openings and ceramic surfacing material bonded to, P (2) 40*g*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain*.
ceramic bodies, manufacture, P (5) 137*a*.
compositions, with heat tempered montmorillonite-free kaolin, P (5) 137*f*.
of conductors and coils with glass composition, P (11) 332*h*.
for electrical conductor, and method of making, P (1) 4*g*.

Insulation, thermal. See also *Fibers, glass; Mineral wool; Refractories, insulating*.
fibrous, radiant heat transfer in, (5) 133*a*.
high temperature, P (1) 12*i*.
low density, bonded with colloidal inorganic materials, P (3) 68*h*.
sodium silicate foams, (4) 96*g*.
Insulators, electrical, P (7) 206*h*.
automatic glazing and sanding machine for, P (8) 242*d*.
bodies, long shaft, study of porosity by measuring velocity of ultrasonic waves by direct reading device, (2) 49*a*.
body, with electrically conductive surface, P (11) 343*i*.
broadband microwave ferrite, (6) 176*b*.
coated, P (9) 271*f*.
corundum microlite, preparation and properties, for use in corrosive media at high temperatures and pressures, (5) 139*j*.
ferromagnetic, nuclear spin-lattice relaxation in, at low temperatures, (8) 255*j*.
high frequency, reduced pressure sintering of MgO as, (11) 355*j*.
high voltage, P (1) 15*j*.
electrical bushing, and manufacture, P (5) 137*e*.
shaping, (10) 306*f*.
with improved surface electrical stress distribution, P (5) 137*d*.
and method for making using electrostatically applied dielectric fibers as spacer pads and gaskets, P (10) 310*a*.
porcelain, for overhead power lines, specifications, (8) 242*h*.
post, with composite fillers, P (8) 242*e*.
properties, examination by surface charge measurement, (2) 49*i*.
self-washing, P (3) 70*g*.
steatite, 43-year-old, study, (10) 306*d*.
thin film metal-, $[Al_2O_3]$-metal structures, method of improving electrical characteristics, P (4) 100*b*.
Insulators, thermal, calcium silicate, manufacture, P (2) 47*e*.
fibrous, physical basis of thermal conductivity in, (6) 173*j*.
Interferometers, multiple color, multiple beam, P (4) 103*k*.
stage, for microinterferometry, P (2) 55*h*.
two-color multiple beam, for measuring small separations, P (4) 103*i*.
Interferometry, for measuring principal indices of small crystals, (3) 75*e*.
for measuring thickness of thick films, new method, (4) 103*e*.
strain analysis, P (3) 76*f*.
Iodides, alkali, Debye-Waller factor and second order Doppler shift of ^{129}I in, (9) 280*c*.
Iodine, atoms and I_3^-, trapped in boric acid glass at room temperature, (5) 127*f*.
IBr^-, trapped in boric acid glass at room temperature, (5) 127*g*.
Ionization, impact, in CdS, (1) 16*c*.
Ions, alkali, distribution in surface layer of glass attacked by water, (1) 5*e*.
alkali, thermionic emission from impregnated metal matrices, (1) 17*d*.
aluminum, in CaO–Al_2O_3–SiO_2 glasses, coordination state, (1) 27*h*.
anion-cation distances, relation with crystal parameter in compounds with perovskite structure, (6) 188*k*.
anion, poly-, tunellite, in hydrated borates, (5) 137*g*.
anions, Fe(II) and inorganic, complex formation between: I, effect of simple and complex halide ions on Fe(II) + H_2O_2 reaction, (7) 216*f*.
bombardment, for making semiconductor, P (9) 274*c*.
cationic field strengths, effect on liquidus of oxide systems, (9) 281*f*.
cation-vacancy centers, doubly associated, in magnesium oxide, (8) 253*d*.
cations, alkali metal, exchange on natural stilbite, (1) 29*b*.
distribution in chemically precipitated Zn-Fe_2O_4, (11) 350*d*.
distribution in $FeAl_2O_4$, Moessbauer and X-ray diffraction study, (11) 354*g*.
distribution in nickel ferrite, (11) 350*d*.
distributions in nonstoichiometric magnesium ferrite, (5) 140*f*.
exchange capacity, determination by continuous titration, (7) 212*d*.
exchanging, synthetic faujasite, P (7) 214*e*.
metallic, stability in zeolites, (11) 357*b*.
nature, influence on properties of alkali silicate glasses, (2) 39*a*.
ordering, in $Na_{0.5}Bi_{4.5}Ti_4O_{15}$, (4) 106*b*.
substitution for modification of structures of ternary oxides: I, strontium for barium in barium ruthenium oxide and in barium iridium oxide; II, cations for ruthenium in barium ruthenium oxide, (5) 155*d*,*f*.
Cr and Mn, reciprocal effect in glass, (1) 7*d*.
chromous, in MgO, (11) 350*g*.
dihalide, trapped in glasses, (5) 127*d*.
electron distribution, in NiO, MnO, and CoO crystals, (3) 80*d*.
exchange, (10) 314*e*.
equilibrium of Na-K ions in alkali feldspars at 600°C under pressure of 1000 bars, (7) 218*i*.
equilibrium, of synthetic zeolite type X, (1) 29*g*.
of glass fibers, P (8) 235*c*.
on hydrogen and aluminum forms of kaolinite, (11) 353*h*.

Ions, exchange (*continued*)
and increased strength of glass, (10) 297*i*.
on mineral clinoptilolite, (11) 353*h*.
in mordenite, kinetics, (3) 82*f*.
processes between immiscible molten phases, (11) 353*h*.
properties of hydrated alumina, effect of pH: I, capacity and selectivity; II, kinetics of exchange, (3) 80*f*,*h*.
properties of synthetic zeolites, (4) 119*c*.
exchangers, borate glass, for fused salts, (1) 5*b*.
inorganic: V, effect of water content on sorption of zirconium phosphate gels of different crystallinity, (7) 218*e*.
for separation and determination of Fe, Al, Cr, Ca, and Mg, (2) 55*b*.
exchanging, crystalline aluminosilicates, P (8) 251*g*.
exchanging, crystalline zeolites with nitrogenous bases, P (6) 183*e*.
H^- and D^-, in CaF_2, effects of uniaxial stress and electric fields on localized vibrational modes of, (1) 28*f*.
halide, simple and complex, effect on Fe(II) + H_2O_2 reaction, (7) 216*f*.
heavy-, pulse heights, in alkali halides, linear relationship for, (9) 283*j*.
hydrogen, exchanged form of crystalline zeolite, production, P (7) 215*a*.
intermediate, 4-coordination structures, in glass, (8) 232*d*.
ionic conductivity, high, of KAg_4I_5, (3) 85*b*.
ionic equilibria, in liquid silicates, (4) 93*h*.
metal, detection with substituted 8-hydroxyquinolines as colorimetric reagents, (1) 23*b*.
metal, sequestering with slowly soluble phosphate glasses, P (6) 171*e*.
metallic, method for controlling reduction in glass compositions, P (1) 9*j*.
Ni and Co, reduction in sapphire, spectroscopy, (7) 221*f*.
OH, in muscovite, vibrations of, (5) 159*i*.
orthoborate, infrared absorption, (3) 82*a*.
polyatomic, small, external modes of vibration, isolated in alkali halides, (11) 352*i*.
polyborate, cryoscopy in dilute solution in alkali halides, (3) 79*d*.
radii, and method of undetermined parameter, (3) 82*d*.
rare earth, in zinc borate as host, luminescent properties, (4) 112*f*.
S-state, in strontium oxide single crystals, paramagnetic resonance, (5) 156*a*.
silver and potassium, diffusion in glass, (7) 196*d*.
sodium, in glass, stress-induced migration and partial molar volume, (5) 128*a*.
sulfate, nephelometric determination of small amounts of, (2) 54*e*.
trivalent terbium, phosphorescence in barium crown glass, (1) 6*g*.

Iridium, electrodeposition, from fused sodium cyanide and aqueous electrolytes, (2) 44*f*.

Iron. See also *Enameling metals; Steel.*
alloy, for glass molding equipment, P (6) 170*h*.
-aluminum and -silicon alloys, Curie temperature, (5) 137*g*.
bonding, in fine-ceramic kaolins, (1) 15*b*.
cast, composition and process for making, P (10) 300*d*.
enamel-, system, stresses determination, (5) 125*j*.
enameling, (11) 332*j*.
enameling in nonmuffled furnaces, (5) 125*j*.
centers, in quartz, optical and paramagnetic properties, (7) 220*f*.
in clay minerals, Moessbauer analysis, (2) 59*g*.
compounds, with antimony, (4) 106*j*.
distribution in Pujada laterite of Mati, Davao Province, Mindanao Island, Philippines, (2) 56*h*.
droplet, levitated, in oxygen, decarburization, (6) 184*i*.
ferric, in high concentration range, simple method for colorimetric and spectrophotometric determination, (1) 23*c*.
ferric chloride, reaction with $GaCl_3$, (10) 325*a*.
ferric oxide, α-, anomalous thermal expansion, (6) 183*h*.
α-, effective in-plane anisotropy field in, (10) 320*b*.
α-, effective in-plane anisotropy and trigonal magnetostriction in, (4) 108*j*.
α-, fine particles, magnetic properties, (3) 83*i*.
α-, lattice parameters, effect of high pressure on, (10) 319*h*.
α-, magnetic memory, explanation based on negative pressure effect on Morin transition point, (11) 354*j*.
α-, single crystals, epitaxially grown, vacancy ordering in, (10) 326*c*.
α-, supported small particles, properties determined with Moessbauer effect, (8) 257*c*.
β-, monohydrate containing excess water, (4) 116*j*.
δ-, new (hydrate), (2) 59*h*.
δ-, (hydrate), as proposed by Okamoto, structure, (8) 257*f*.
effect on 120° phase transition in $BaTiO_3$ single crystals, (5) 137*i*.
effect on spalling characteristics of fireclay refractories, (5) 131*h*.
γ-, process for making, P (2) 52*f*.
preparation, P (11) 349*g*.
in raw materials and slimes of alumina manufacture, spectroscopic determination, (10) 315*g*.
reactions with lanthanum and yttrium oxides, (9) 286*e*.

Iron, ferric oxide (*continued*)
solid state reactions with SiO_2, Al_2O_3, MgO, CaO, and ZrO_2, (7) 221*b*.
variations of magnetic properties with pressure, (2) 50*b*.
ferrous chloride, inhibiting effect on corrosion rate of steel in HCl, (11) 332*f*.
ferrous fluoride, crystalline, Zeeman splitting of narrow lines in, evidence for spin-wave excitations, (10) 327*g*.
ferrous oxalate dihydrate, low-temperature magnetic susceptibility, (8) 254*i*.
thermal decomposition, (4) 117*j*; (5) 159*b*.
thermal decomposition, influence of atmosphere on, (5) 153*b*.
ferrous oxide, activity in silica-saturated slags, (2) 43*e*.
content, relation with shade of iron glazes, (9) 271*d*.
continuous production from waste sulfuric acid pickle liquor and calcium compound, P (7) 194*i*.
high-temperature defect structure, (4) 111*h*.
lattice parameter, as function of pressure, (7) 219*c*.
reduction from silicate and aluminate slags by carbon-saturated iron, rate and mechanism, (2) 45*g*.
glass-doped, model for doped tungsten, (9) 262*h*.
ion in magnesia, diffusion constant, (9) 267*d*.
ions, behavior in iron-titanium spinels, (3) 70*j*.
Fe^{3+} ion, in calcite, paramagnetic resonance spectrum, (5) 156*a*.
polycrystalline EPR spectrum in MgO, (3) 85*b*.
in SnO_2, electron spin resonance, (4) 109*c*.
$FeAl_2O_4$, cation distribution in, Moessbauer and X-ray diffraction study, (11) 354*g*.
$FeAl_2O_4$ (hercynite), formation and reduction, (3) 81*e*; II, reduction of synthesized hercynite with hydrogen, (10) 321*i*.
$FeCr_2S_4$, NiAs-type polymorphs, magnetic properties, (8) 255*c*.
$Fe_xGa_{3-x}O_3$, with polarized neutrons, crystallographic study, (8) 252*g*.
$Fe_{1.75}Ge$ single crystal, neutron diffraction study, (5) 155*c*.
Fe_3O_4 and α-Fe_2O_3, exchange coupling between, (4) 110*h*.
δ-FeOOH, structure, (11) 357*e*.
γ-FeOOH, preparation, P (8) 251*c*.
Fe_2Si alloy, ordering temperature determination, (3) 79*j*.
(II)-iron(III) mixtures, separation by paper chromatography and electrophoresis, (11) 347*g*.
(II) oxalates, complex, thermal decomposition, study using Moessbauer effect, (5) 158*g*.
(III) oxide-hydrate particles, ultrafine, prepared from iron(III) oxide-hydrate gels, magnetic properties, (8) 255*d*.
low carbon enameling, treatment, P (8) 230*b*.
metallic, determination in reduced ores and oxides, (8) 248*b*.
optical absorption spectra, in rock-forming silicates, discussion and reply, (6) 185*e*.
optical absorption spectra, in six-coordinate sites in chlorite, biotite, phlogopite, and vivianite, aspects of pleochroism in sheet silicates, (9) 284*j*.
ores, calcium and magnesium in, after separation of R_2O_3 and P_2O_5 with aqueous suspension of ZnO, (10) 313*h*.
oxides, dissolution and diffusion kinetics, in sodium disilicate glass, (10) 297*j*.
in perovskites $La_{1-x}Sr_xFeO_3$, Moessbauer studies, (9) 284*g*.
recovery from Pacific Northwest bauxites by Pedersen process, (6) 182*g*.
removal, from glassmaking sand, (10) 317*h*.
from Pennsylvania aluminous clays, (5) 147*j*.
from spodumene concentrates by chlorination, (11) 349*c*.
in rock-forming silicates, optical absorption spectra of, (3) 84*c*.
-series complexes, gyromagnetic factors and covalency in, (9) 282*h*.
in silicates with ferron, spectrophotometric determination, (10) 315*f*.
solubility, in TiO_2, (1) 32*f*.
spectrochemical determination in fluorite, (3) 76*f*.
sulfide, concentrates, catalyzed by nitric acid, wet oxidation of, (3) 77*g*.
sulfide, lattice parameter, as function of pressure, (7) 219*c*.
systems. See *Systems.*
total, in silicate and other rock material, rapid complexometric determination, (5) 146*e*.
values, selectively carbiding, P (9) 270*e*.

Irradiation. See also *Radiation;* specific types.
behavior of UO_2 particles in cermets, (11) 338*g*.
damage, to sintered BeO as function of fast-neutron dose and flux at 110°, 650°, and 1100°C, (4) 112*a*.
damage, in type I diamond, (3) 82*e*.
effects, on beryllia-based fuels, (3) 67*c*.
in BeO and ZnO, (4) 112*d*.
at 77°K, on physical properties of graphite, (8) 239*g*.
on thermal conductivity of UO_{2-x}, UO_2, and UO_{2+x} at 60°C, (9) 281*h*.
electron, of BeO, (2) 44*f*.
gamma-ray, effect upon glycol-bentonite and application to gamma-ray dosimetry, (6) 185*f*.
of graphite, relation between temperature and flux intensity, (4) 115*f*.
influence on low-temperature dielectric loss in silica glass, (2) 58*b*.

Irradiation (*continued*)
microstructural modifications produced in UO_2 particles by, (6) 173*h*.
neutron, of BeO, primary damage state, (8) 256*h*.
of BeO specimens, (8) 256*h*.
effect on abrasion hardness and cleavage of diamond, (2) 35*g*.
effect on plastic behavior of type IIA diamond plates, (1) 28*i*.
influence on ionic mobility in cubic zirconia, (10) 322*d*.
of quartz, light scattering and absorption, (8) 256*i*.
of self-bonded SiC, lattice contractions associated with, (8) 254*e*.
neutron-irradiated pyrolytic carbons, mechanical properties, (10) 323*f*.
ultraviolet, for production of *F* centers in pure potassium bromide, (11) 355*f*.
of uranium, effects on crystal structure of UO_2, (6) 173*f*.

Isomorphism, of Li_3PO_4, Li_3AsO_4, and Li_3VO_4, (5) 154*b*.

Isotopes. See also *Radioactive tracers.*
analyses, of uranium samples by alpha spectrometry, (1) 21*c*.
effect, in thermal diffusion in solids, (4) 112*g*.
radio-, for use in mineral prospecting, (1) 25*g*.

Jahn-Teller effect, dynamic, in $^3T_2$ excited term of $Al_2O_3:V^{3+}$, (11) 351*j*.
on Moessbauer spectra of ^{57}Fe in $FeCr_2O_4$, (4) 112*h*.

Jet propulsion, ceramics for. See *Aircraft ceramics.*

Jewelry. See *Art and artware.*

Joints. See also *Seals and sealing.*
construction, for glass pipe, P (6) 170*i*.
decomposable, with indium seal for glass vacuum apparatus, (11) 333*j*.
jointing material, chromesil, for use in recuperators in soaking pits, P (5) 135*g*.
pipe, bell and spigot, and sealing and locking, P (11) 337*f*.
prefabricated, for stoneware pipes, (4) 95*j*.

Junctions, assembly, thermoelectric, with insulating irregular grains bonding insulating layer to metallic thermojunction member, P (7) 210*d*.
contoured, diffusion, P (11) 345*c*.
GaAs, iron-sulfur diffused, electroluminescence, (4) 109*h*.
guard, for *pn* junction semiconductor devices, P (10) 309*i*.
hetero-, GaAs–Ge, misfit dislocations, (1) 16*i*.
interface-alloy epitaxial, method of producing, P (2) 51*e*.
method of producing between compound semiconductors by alloying and substitution reaction, (8) 255*c*.
planar, and devices, means for forming, P (4) 100*i*.
planar, treating, P (9) 274*j*.
pn, device with interstitial impurity means to increase reverse breakdown voltage, P (5) 142*b*.
device, selenotelluride, utilizing deep trapping states, P (9) 274*i*.
devices, method of making by diffusion, P (10) 310*a*.
forming by ionic beam, P (9) 273*c*.
forming in polycrystalline material, P (9) 273*c*.
forming by vaporization, P (6) 178*a*.
$Ga_{1-x}Al_xAs$, grown by liquid-phase epitaxy, efficient visible electroluminescence at 300°K from, (6) 176*e*.
in GaP, with external electroluminescence efficiency approx 2% at 25°C, (1) 16*c*.
making by hydrothermally growing, P (7) 209*h*.
making under glass, P (11) 344*a*.
producing in monocrystalline semiconductor member by etching and diffusion, P (7) 209*f*.
profiles, method of shaping, P (3) 73*f*.
tunneling, method of forming for intermetallic semiconductor devices, P (3) 73*a*.
valence-exchange-type semiconductor glass, symmetrical negative resistance in, (3) 87*h*.

Kaolin, deposits, around Karanjia, Singhbhum, Bihar, nature of, (1) 15*d*.
dry-bending strength, (1) 15*c*.
feldspathic, raw material, new source in Ukraine, (8) 250*h*.
fine-ceramic, bonding of iron in, (1) 15*b*.
low viscosity, production by controlled blending of high viscosity kaolins, P (10) 318*d*.
raw, blunging, (10) 312*a*.
subjected to direct shear, microscopic structures in, (10) 323*i*.
systems. See *Systems.*
thermochemical analysis, rapid, (11) 347*b*.

Kaolinite, AhI, mineralogy, (9) 278*j*.
dehydroxylation, role of monovalent and divalent cations in, (5) 158*c*.
dehydroxylation, temperature and vapor pressure dependence, (5) 154*f*.
differential thermal curves, evaluation with high temperature cell, (5) 145*i*.
disordered, ionic composition, (6) 186*f*.
as evidence for phase equilibria at low temperatures, (7) 224*c*.
formation from ablite altered by water at 200°C, electron microscopy and electron diffraction study, (7) 217*e*.

Kaolinite (*continued*)
free energy of formation, from solubility measurements, (5) 152*h*.
-halloysite clays, mineralogical studies: III, fibrous kaolin mineral from Piedade, Sao Paulo, Brazil; IV, platy mineral with structural swelling and shrinking characteristics, (5) 154*j*, 155*a*.
hydrogen and aluminum forms, ionic exchange, (11) 353*k*.
infrared spectra, (3) 82*b*.
meta-, infrared spectra, (3) 82*b*.
-muscovite-quartz mixtures with 25%(wt) quartz, dimensional and weight changes on refiring and pore-size distribution, (3) 81*c*.
Kiln furniture, manufacture, P (1) 13*a*.
saggers and, characteristics and behavior, (8) 236*j*.
Kilns. See also *Burners; Furnaces; Ovens.*
and boilers, oil-fired, formation of acid smuts in, (8) 249*f*.
car, with top of refractory tile, P (7) 204*j*.
cement, dust measurements, (2) 36*k*.
cement, fluorine balance and fluorine emission from, (8) 228*c*.
conveyor, with walking hearth for fast drying of porcelain without saggers, (4) 104*b*.
designing advances using characteristics of insulating refractories, (1) 24*c*.
fluid bed, P (10) 317*a*.
gas-fired intermittent car, for salt-glazing, (9) 266*f*.
glost, furniture for, (3) 70*b*.
investigation with aid of models, (1) 24*c*.
linings. See *Refractories.*
modern, (1) 11*i*.
roller hearth, (5) 147*f*.
rotary, P (1) 24*f*.
assemblies, P (6) 182*b*.
cement, build-up in, (6) 165*h*.
cement linings, deterioration by alkali sulfides and sulfates, (8) 237*c*.
cement, local encrustation in, and of berlite, (9) 262*c*.
control of exit gas conditions, P (5) 125*c*.
device for installing lining, P (8) 249*e*.
installations, P (4) 104*e*.
multiple-chamber, P (4) 104*d*.
refractory structure for, P (1) 14*b*.
with screw, P (11) 348*g*.
simulation of heat-transfer phenomena in, (1) 24*g*.
temperature measurement, P (1) 24*f*; P (7) 213*f*.
thermocouple collector ring and brush assembly, P (11) 348*h*.
tire fastening for shell, P (8) 249*j*.
shaft, P (3) 77*c*.
discharge grate and hopper for, P (4) 104*b*.
and method of operation, P (6) 182*c*.
radial grate for, P (6) 182*a*.
shuttle, P (3) 77*a*.
shuttle, with moveable floor and tube support, P (4) 104*e*.
for sintering soft ferrites, (3) 76*i*; (5) 138*b*.
Tophat, firing with natural gas, (6) 181*j*.
tunnel, P (4) 104*d*; P (9) 278*d*.
cars, made of refractory concrete, (10) 317*d*.
gas-heated, measurement and control, (4) 104*c*.
heating and cooling of refractories in, (9) 267*a*.
for kilning ceramic ware, P (7) 213*i*.
longitudinal slot-fired, (10) 316*j*.
preheating section, P (7) 214*a*.
pusher for, and method of charging, P (10) 317*c*.
requirements for modern operations, (9) 278*a*.
roofs for, P (1) 24*e*.
semicontinuous hot-press, (11) 348*f*.
ways to increase capacity, (7) 213*j*.
vertical, operation using shrouded fuel, P (1) 3*d*.
vertical lime, P (3) 63*a*.
vertical shaft, controlling flow in, P (10) 296*c*.
vertical shaft, for firing materials such as limestone, P (10) 317*b*.
Kinetics, characteristics, of sintering of oxides, (7) 219*b*.
of chlorination of metal sulfides, (3) 77*i*.
of chlorination of niobium pentoxide with Cl in presence of excess graphite powder, (7) 219*b*.
color-center, in cerium containing glass, (5) 126*h*.
of combustion, of sulfides in slag glasses, (2) 39*e*.
considerations, in genesis of growth twinning, (5) 154*d*.
of crystal growth, (5) 154*e*.
crystallization, of internally nucleated vitreous silica, (9) 280*b*.
crystallization in Li_2O-SiO_2 glasses, (8) 232*e*.
crystallization and melting, of sodium disilicate, (1) 27*i*.
decomposition of $CaCO_3$, measurement with recording thermobalance, (2) 58*g*.
dissociation of hydrogen sulfide by iron films, (3) 82*e*.
dissolution, of quartz spheres in sodium silicate melt, correction, (7) 196*f*.
dissolution and diffusion of iron oxides in sodium disilicate glass, (10) 297*j*.
of fast high-temperature processes, study methods, (10) 314*j*.
of formation of ferrites of spinel type, X-ray diffraction study, (10) 327*c*.
of formation of leached layers on glass surfaces, (8) 232*e*.
of glass transformation by thermal analysis: I, glycerol, (5) 127*i*.
Kinetics (*continued*)
grooving, of [001] tilt boundaries in NiO, (5) 152*d*.
growth, of interstitial loops in irradiated sapphire, (1) 29*h*.
hydration, of cement constituting minerals, (2) 36*c*.
hydrofluorination, of doped uranium dioxide, (3) 81*h*.
of initial reduction stages of magnetite in hydrogen, (9) 283*b*.
of interfacial reaction and diffusion processes in system iron-sodium disilicate glass, (3) 64*b*.
of ion exchange in mordenite, (3) 82*f*.
logarithmic oxidation, of zinc, (4) 112*b*.
of metastable phase separation in PbO–B_2O_3 system by small-angle scattering of X rays, (1) 32*c*.
of optical charge exchange in copper-doped cadmium sulfide single crystals, (8) 254*d*.
oxidation, of tantalum by water vapor, (6) 186*g*.
of tellurium, (5) 154*i*.
of UO_2–Y_2O_3 solid solutions, (4) 113*e*.
parameters, determination in solid state reactions, (7) 220*b*.
of phase transformations during sitallization of lithium aluminosilicate glass, (8) 232*g*.
of reaction, between $BaCO_3$ and TiO_2, (9) 283*d*.
between MgO and Cr_2O_3, atomic absorption to study, (4) 96*i*.
of water vapor with crystalline lithium hydride, (3) 82*h*.
rearrangement, of liquid-liquid immiscible microphases in alkali borosilicate melts, (5) 128*g*.
of SiO_2 + SiC reaction at elevated temperatures, (3) 86*g*.
sintering, based on geometric models, (5) 158*d*.
of corundum under pressure, (6) 186*h*.
and grain growth in BeO, (3) 67*h*.
of solution of clinker minerals in liquid phase of portland cement clinker, (8) 228*f*.
of spherulite growth in silicate glasses, (8) 232*i*.
studies on reaction of praseodymium oxides in oxygen atmosphere, (11) 354*c*.
study, of nickel carbide, oxidation, (7) 219*b*.
of uranium + water reaction, (3) 88*i*.
of vapor phase hydration of MgO: II, dependence on temperature and water vapor pressure; III, effect of iron oxides in solid solution, (3) 82*j*, 83*b*.
vaporization, of ceramic oxides at temperatures around 2000°C, (1) 33*g*.
of volume relaxation of vitreous boron oxide, (11) 357*h*.
Kyanites, enthalpy of formation, (5) 152*d*.
mining, processing, uses and specifications, B (11) 358*h*.
nuclear quadrupole coupling tensors of ^{27}Al in, (7) 220*d*.

Laboratories. See also *Research and research laboratories.*
ceramic tile color, (2) 48*k*.
for precalcining procedures for structural clay materials, (3) 66*h*.
Regional Research, annual report, 1966–67, B (8) 258*h*.
Ladles. See *Refractories.*
Lamps. See also *Glass.*
alkali metal vapor, P (8) 243*h*.
arc discharge, with polycrystalline ceramic arc tube, P (4) 99*c*.
bulbs, electric, frosting, (9) 263*j*.
capless, P (5) 129*d*.
decorative pulsating flame incandescent, P (8) 235*f*.
electric, forming method, P (11) 336*f*.
electric discharge, P (7) 208*c*.
electric discharge, envelope with molten inner surface at operating temperature, P (9) 265*a*.
electric incandescent, P (1) 8*i*.
electric incandescent, with levitating incandescent body, P (8) 235*h*.
electroluminescent, with alternatively defined and undefined indicia, P (11) 343*d*.
electroluminescent, with high resistivity electrode, P (2) 50*j*.
fluorescent, envelope with transparent protective coatings, P (7) 208*h*.
improved, process for fabrication, P (2) 52*e*.
using indium-mercury amalgam band for pressure control, P (10) 309*f*.
with reflective coating containing TiO_2 and Sb or its oxide, P (7) 198*d*.
stabilized red pigment filter coating in, P (5) 143*c*.
high pressure, with protective metal oxide layer on inner wall of quartz envelope, P (7) 209*b*.
high pressure electric discharge, with fill including uranium halide, P (5) 141*j*.
incandescent, P (3) 72*j*; 73*a*.
high energy tubular, with heat dissipative sleeves, P (3) 72*i*.
self-contained battery-powdered electric, P (8) 236*b*.
single ended quartz type, P (2) 42*d*.
with tungsten filament with tantalum imbedded in surface as gettering agent, P (1) 18*e*.
luminaire with optical refracting members, P (11) 336*c*.
mercury metal halide discharge, with iodine present in stoichiometric proportions with respect to reactive metals, P (8) 235*f*.
with molybdenum phosphate phosphor, P (4) 100*f*.
projection, with multiple reflectors, P (8) 236*a*.
Lamps (*continued*)
quartz-halogen incandescent, with filament and support made of rhenium-tungsten alloy, P (10) 311*a*.
reflector discharge, with frosted envelope and arc tube, P (8) 236*b*.
sealing apparatus, with double revolving and orienting sealing heads, P (6) 170*j*.
sodium vapor, high pressure saturation, containing mercury, P (8) 235*b*.
sodium-vapor discharge, having envelope with porous wall, P (7) 199*a*.
superhigh-pressure mercury vapor discharge, P (8) 236*a*.
tubular incandescent, filament supports for, P (9) 265*c*.
variable intensity, P (7) 199*e*.
Lanthanides, cerium-group, extraction behavior in primary amine-chelating agent system, (6) 182*g*.
compounds, $LiLnSiO_4$ and $LiLnGeO_4$, (5) 155*f*.
gallium borates, crystal structure and fluorescence, (5) 150*b*.
oxide, crystals, spectrum of Nd^{3+} in, (11) 357*a*.
oxides, freezing points measured with solar furnace, (4) 110*c*.
Lanthanons. See *Rare earths.*
Lanthanum, chloride, electric quadrupole-quadrupole interaction between cerium pairs in, (11) 352*g*.
chloride and bromide, ESR of Nd^{3+} pairs in, (11) 352*b*.
fluoride, enthalpy of formation, (9) 282*c*.
single crystals, exposing dislocations in, (10) 321*d*.
transport properties, (9) 288*f*.
hexaboride, evaporation, (5) 138*i*.
$LaCoO_3$, low temperature crystallographic and magnetic study, (2) 49*g*.
$LaTaO_4$ and $PrTaO_4$, new structure type, (5) 150*g*.
La_2Te_3, Th_3P_4 structure, structure refinement of, (5) 158*d*.
La_2TiO_5, structure, (6) 189*i*.
oxide, reaction with iron oxide, (9) 286*e*.
systems. See *Systems.*
trifluoride, single crystals, rare earth doped, optical absorption and fluorescence intensities in, (10) 324*b*.
spin-spin relaxation in, (9) 286*e*.
sublimation pressure, measured by mass spectrometry, (7) 219*k*.
Lapping, characteristics, of lead zirconate-titanate ceramics, (6) 176*c*.
characteristics, of steatite, forsterite, and alumina, with ordinary abrasives, (5) 123*i*.
elusive art for ultrafine finishes, (1) 1*f*.
forsterite, characteristics using diamond abrasives, (5) 123*g*.
Lasers. See also *Masers.*
with adjusting mechanism for mirror, P (11) 344*j*.
apparatus, with layer of silver and layer of silicon monoxide, P (4) 100*g*.
application to spectral analysis, (7) 211*i*.
beams, continuous deflection, (4) 107*c*.
and integrated circuits, (3) 71*g*.
interaction with spin-waves in YIG, (1) 17*b*.
CdSe, ultrathin continuous-wave, volume excitations at 6900 A output, (1) 17*g*.
characteristics, of niobium compensated $CaMoO_4$ and $SrMoO_4$, (3) 83*d*.
configuration, P (11) 344*i*.
containing single-phase solid solution luminescent compositions, P (7) 210*i*.
crystal, with prismatic end surface, P (8) 244*i*.
crystal and glass, Nd^{3+}-activated, high-temperature spectroscopy of stimulated radiation from, (10) 321*k*.
crystals, divalent rare earth, method of making in electric field, P (10) 310*i*.
crystalline solid, (9) 271*j*.
damage induced by, in solids, (4) 112*j*.
device, crystalline injection, manufacture, P (1) 17*e*.
using Nd:$PrCl_3$, P (3) 73*b*.
optical fiber, P (3) 73*i*.
semiconductor junction, P (4) 101*a*.
divalent metal doped fluorides as material for, P (8) 244*j*.
emission lines and materials, (5) 138*g*.
filamentary, mechanism, (6) 185*h*.
GaAs junction, continuous operation on diamond heat sinks at 200°K, (11) 350*i*.
Hermite-Gaussian mode patterns, (4) 111*d*.
spikes in light output, (11) 357*a*.
gas, generation of combination tones by orthogonal oscillations, (5) 138*d*.
gas, windows, vacuum sealing of, P (9) 266*a*.
glass, (2) 39*i*; (9) 263*f*.
glass, history, (2) 39*j*.
host material, $Ba(B_{0.4}Ta_{0.6})O_3$ ordered perovskite-type compounds, (5) 137*g*.
industrial, applications, (2) 54*a*.
LaF_3–Nd^{3+}, continuous induced radiation from, at room temperature, (10) 306*i*.
PbS diode, (4) 113*i*.
magic ray, (5) 139*d*.
microprobe, for microspectrochemical analysis of minerals, (7) 212*j*.
microprobe sampling, for qualitative analysis, (9) 276*a*.
operation, in wedge shaped ruby, (4) 112*h*.
using photochromic glass as Q-spoiling medium, P (5) 130*c*.
properties, of Nd^{3+}- and Eu^{3+}-doped YVO_4, (4) 113*d*.
pulse widths, picosecond, measurement, (3) 83*j*.

Lasers (*continued*)
ruby, giant impulse, optical sum generation of two-frequency output of, (2) 49*j*.
optical distortion during pumping, (5) 139*d*.
rooftop, polarization effects, (5) 139*i*.
ruby rods, correlation between laser performance and crystal homogeneities of, (8) 252*i*.
polished with clean diamond, (6) 163*i*.
specially grown, evaluation, (5) 138*h*.
semiconductive junction, with temperature compensation, P (4) 101*e*.
semiconductor, (9) 272*g*.
semiconductor, measurement of photon absorption loss in active and passive regions of, (4) 112*i*.
single transverse mode pulsed ruby, (11) 356*d*.
standards and materials, research at NBS, (9) 286*h*.
structure, high power junction, P (4) 100*c*.
structures, end pumped, using immersion optics, P (8) 244*b*.
thresholds, of ruby laser crystals, (5) 139*d*.
Laterite, origin, review, (1) 25*d*.
Lattice constants. See *Crystals, structure*.
Lattice defects. See *Crystals*.
Lattice energy. See *Energy*.
Lattices. See *Crystals*.
Leaching, of alumina ceramic bodies, (9) 272*d*.
conditions, method and effect on durability of glass for disposal of highly radioactive waste, (7) 196*f*.
Lead. See also *Glass; Glazes*.
bisilicates, B (7) 224*g*.
chloride-PbS mixtures, molten, electrical conductivities and structural properties, (10) 320*h*.
chromate, pigment, silica-coated, P (6) 183*d*.
dioxide, fluorite-type, high pressure synthesis, (7) 218*a*.
ferrite, increase in preferred orientation by firing, (11) 342*j*.
isotopes, in rock sample of Deccan traps, (6) 183*g*.
$PbCrO_3$, high-pressure synthesis, (3) 81*b*; correction, (6) 186*b*.
$Pb(Mg_{1/3}Nb_{2/3})O_3$–$PbTiO_3$–$PbZrO_3$ ceramics with Ba or Sr substitutions, piezoelectric properties and phase relations, (4) 99*d*.
in Pb_3O_4, PbO_2, and PbF_2 used in glass industry, complexometric determination of total amount of, (11) 333*g*.
$Pb_{1-x}Sn_xTe$ alloys, phase studies, (4) 114*c*.
$(Pb_xSr_{1-x})TiO_3$, single crystals, grown by traveling heater method, (8) 243*c*.
$PbTi_3O_7$, and process for manufacture, P (4) 105*b*.
$Pb(Zr, Sn, Ti)O_3$ ceramics, niobium-doped ferroelectric, electrical properties, (5) 138*c*.
$PbZrO_3$, phase transitions, (4) 117*d*.
magnesium niobate, dielectric and electrooptic properties, (4) 107*j*.
oxide-$2B_2O_3$, enthalpy of fusion, (8) 253*f*.
-Nb_2O_5, ferroelectric ceramics in, (11) 342*f*.
photodetector, physical interpretation, (11) 355*a*.
polymorphic of orthorhombic to tetragonal, solid state mechanism for, (6) 189*a*.
quantum efficiency of photoconduction in, (11) 355*h*.
red and yellow, effect of impurities on formation, (5) 151*g*.
removal from TiO_2 by isomorphous crystallization of strontium and lead sulfates from solutions, (7) 203*a*.
retrograde solubility, in *n*-type PbS, (6) 188*a*.
sulfantimonides, from Madoc, Ontario, (4) 113*j*.
sulfide, activation energies for high-temperature steady-state creep in, (6) 183*g*.
crystal dynamics, (9) 280*i*.
films, *p*-type single-crystal, photoconductivity in, (4) 114*f*.
(galena), plastic deformation, (10) 324*j*.
systems. See *Systems*.
telluride, selenide, and sulfide, energy bands, (8) 253*f*.
titanate, catalytic properties, process for improving, P (4) 105*c*.
ferroelectric properties, (11) 352*i*.
formation mechanism, (5) 152*f*.
$PbTi_3O_7$, (11) 355*c*.
and zirconate, production for ceramic bodies, P (2) 52*i*.
zirconate-lead titanate materials, vaporization: II, hot-pressed compositions at near theoretical density, (8) 243*h*.
zirconate-titanate, optical study, (3) 84*g*.
zirconate titanate, 95/5, shock-wave compression, (9) 286*b*.
zirconate-titanate ceramics, lapping characteristics, (6) 176*c*.
low loss, (2) 49*e*.
made from spray-dried coprecipitated powders, effect of fabrication procedure on properties, (11) 341*i*.
Lehrs. See *Furnaces; Glassmaking apparatus and equipment*.
Lenses. See *Glass, optical*.
Leucophyllite, ceramic uses of, (6) 182*f*.
Lepidolite, ores, beneficiation, P (1) 19*f*.
Light, amplifier, including layer for converting X-rays to visible radiation, P (9) 273*f*.
circularly polarized, selective absorption in broad bands by Zeeman components of divalent thulium in calcium fluoride, (9) 286*j*.
diffraction, by elastic waves in YIG, (4) 108*a*.
diffusion material, method of making and using, P (2) 56*g*.
scattering and absorption, by neutron irradiated quartz, (8) 256*i*.

Light (*continued*)
scattering study, of bentonite solutions when subjected to electric fields, (3) 83*d*.
scattering study, of structural changes leading to devitrification of optical glasses, (7) 196*c*.
source, radiant white, P (5) 136*f*.
transmitted polarized, apparatus for study of minerals opaque, (4) 102*e*.
transmitting device, variable density, P (10) 301*b*.
Lime. See also *Calcium, oxide; Glass*.
additions, effect on cubic-monoclinic transformation in rare earth sesquioxides, (7) 217*a*.
artificial hydraulic, from press mud, (3) 66*f*.
effect on spalling characteristics of fireclay refractories, (5) 131*k*.
quick-, high calcium, process for slaking, P (5) 125*k*.
or slaked, for preparing fine-grained satin white, P (10) 318*c*.
structure, effect of degree of burning, (10) 294*j*.
reactivity: XIII, sulfating of hydrated lime; XIV, sulfating of carbonated lime; XV, crystalline forms of sulfated lime, (10) 295*b,d,e*.
sand-, bodies, hydrothermally bonded, structure of binder in, (10) 295*h*.
treatment of sludge in manufacture, (2) 37*f*.
Limestone, calcining, method and means, P (1) 3*b*.
deposits, in India, (3) 77*j*.
Illinois, thermal expansion, (4) 118*a*.
Indian: I, mineralogical investigation, (6) 189*b*.
Indian, studies: IIA, estimation of dolomites by DTA analysis; IIB, estimation by X-ray methods, (3) 62*h*.
Mifflin member Platteville, in southwest Wisconsin, marine dolomitization, (1) 30*b*.
siliceous dolomitic, thermodynamic appraisal of steps in progressive metamorphism of, (3) 77*f*.
Linings. See also *Refractories*.
corrosion-proof rubber, for metallurgical grinding mills, P (7) 214*c*.
exothermic, for ingot and foundry molds and hot tops, P (1) 13*g*.
Liquids. See also *Fluids*.
diethyl phthalate, heat capacities and related thermal data to 360°K, (4) 110*j*.
molecular and ionic, viscosity, (7) 223*b*.
organic heavy, process for washing and removing from mineral particles, P (1) 26*a*.
polymer, equation of state at elevated pressures, (5) 127*j*.
refractory, surface tension measurements using modified drop weight method, (8) 248*i*.
saline, dilatometric, calorimetric, and ultrasonic techniques for studying at high temperatures, (7) 216*h*.
temperature variation of viscosity and structure of, (3) 87*a*.
Lithia. See *Lithium, oxide*.
Lithium, aluminum hydride, process for producing, P (3) 78*e*.
-aluminum silicates, thermodynamic properties, (4) 118*h*.
chloride, 3*p* energy band in, (8) 258*g*.
content in quartz from mica schists, gneisses, and granitoids of various origin in Lower Silesia, (7) 219*d*.
disilicate, crystallization, from Li_2O–SiO_2 glasses, (5) 126*j*.
ferrite, X-ray topography, (3) 88*e*.
ferrites and aluminates, crystal structures, chemical properties, and phase diagrams, (6) 183*k*.
fluoride, attenuation of high frequency elastic waves in, (8) 252*c*.
calcium-doped, low-temperature electrical conductivity in, (10) 322*e*.
crystal, proton bombarded, negative electrolytic breakdown in, (10) 323*h*.
crystalline, electronic spectrum, (8) 253*e*.
ionic crystals, temperature dependence of infrared dispersion in, (11) 357*b*.
:(Mg,Ti), photo- and thermoluminescence, (4) 114*d*.
plasma excitations in, (11) 355*c*.
stability and production of *R'* centers in, (11) 357*b*.
thermoluminescence, stimulation by ruby laser light, (4) 116*f*.
third-order elastic constant c_{111} in, (11) 357*k*.
hydride, molten and solid, electrical conductivity, (5) 138*b*.
hydrides, production, P (5) 149*b*.
Li^+, minimum-energy configuration, in KCl, (10) 323*a*.
α-$LiAlO_2$, high-pressure synthesis and crystal structure, (7) 218*a*.
$LiAl_5O_8$, microscopic parameters, NMR determination, (5) 156*a*.
$LiBO_2$, high-pressure single-crystal synthesis, (7) 220*d*.
β- and γ-$LiBO_2$, direct preparation of, in high pressure-high temperature studies, (3) 81*a*.
$LiFePO_4$, antiferromagnetism in, (9) 279*h*.
$LiGaTiO_4$, structure, new ordering type in spinels, (7) 222*a*.
$LiLnSiO_4$ and $LiLnGeO_4$, new lanthanide compounds, (5) 155*f*.
$LiMO_2$ compounds, polymorphism, (7) 220*c*.
Li_3PO_4, Li_3AsO_4, and Li_3VO_4, isomorphism and polymorphism, (5) 154*b*.
$LiUO_3$, crystal structure, (5) 150*c*.
metahafnate, enthalpy of formation, (10) 321*a*.
-metaniobate, assessment for nonlinear optics, (5) 149*f*.
metatantalate, ferroelectric, Curie temperature and birefringence variation as function of melt stoichiometry, (1) 16*d*.

Lithium (*continued*)
metatitanates, heat of formation, (1) 29*a*.
niobate, crystals, growth, P (1) 18*a*.
electrooptic effect in, (4) 109*f*.
image conversion from 1.6 μ to visible in, (8) 243*f*.
and $LiTaO_3$, ferroelectric, NMR study, (5) 139*c*.
parametric oscillat in, (4) 118*d*.
parametric oscill. or threshold with single-mode optical masers and observation of amplification in, (11) 357*d*.
oxide, ceramics, with β-eucryptite composition, effect of heat treatment on thermal expansion of, (8) 241*j*.
oxide and metaborate, thermodynamics of vaporization, (5) 159*e*.
oxide-SiO_2 solutions, activities, calculation, (1) 5*a*.
phosphate, pure molten, application of rigid sphere model, (2) 57*d*.
recovery, from Great Salt Lake brine, process, P (1) 25*j*.
silicate, composition, P (10) 318*b*.
silicate, minerals, procedures for utilization, review, (1) 25*e*.
systems. See *Systems*.
trihydrogen selenite, gamma-irradiated single crystal ferroelectric, paramagnetic species in, (3) 84*f*.
water-soluble, compounds, P (1) 26*c*.
Lubricants, inorganic solid film, P (11) 349*j*.
self-, for bearings and sliding parts, process for making, P (1) 14*d*.
solid, chemical stability at high temperatures, (11) 338*e*.
Lubrication, fluid film, for extrusion of metal, P (1) 8*j*.
system, automatic high pressure, for rotary grinding mills, P (7) 211*a*.
Luminescence, from cadmium sulfide plastically bent crystals, (5) 154*j*.
centers, blue and green, of electroluminescent ZnS:Cu phosphors, (11) 350*j*.
composition, single-phase solid solution, preparation, and lasers containing, P (7) 210*i*.
electro-, bibliography, (5) 137*h*.
in CdTe diodes, (8) 253*e*.
correlation with electron emission of thin metal-oxide-metal sandwiches, (6) 176*c*; (10) 306*j*.
dc, of zinc sulfide thin films, (8) 252*h*.
device, comprising electroluminescent films emitting light of complementary colors, P (9) 272*g*.
device, and conductive media for, P (7) 208*i*.
device, core structure for, and method of formation, P (10) 309*j*.
device, with incorporates barium oxide films as breakdown protection, P (7) 208*d*.
devices, P (10) 309*c*.
devices with light emission generally perpendicular to ionic current flow, P (7) 208*e*.
display device, piezoelectric, containing nonlinear resistance layer, P (7) 209*i*.
display panel, with rodlike electrodes embedded in phosphor, P (8) 244*b*.
efficient visible, at 300°K from $Ga_{1-x}Al_xAs$ *pn* junctions grown by liquid-phase epitaxy, (6) 176*c*.
using GaAs MIS structures, (2) 49*g*.
dopants, P (5) 141*c*.
gated, display device with plurality of electroluminescent cells with one cell including photoconductor element, P (3) 72*h*.
hypermaintenance, (7) 207*c*.
improved in gallium phosphide with three of iron-sulfur diffused GaAs junctions, (4) 109*h*.
material, *n*-type zinc cadmium sulfide, process for making, P (6) 178*e*.
and photo-, of rare-earth-doped ZnS, (4) 109*e*.
process for producing using ionically conducting electrolyte, P (2) 51*a*.
translator using thin film transistors, P (7) 208*e*.
of vapor-grown GaAs and $GaAs_{1-x}P_x$ diodes, (8) 243*d*.
in ZnS:Cu,Al phosphors, (3) 88*e*.
green copper, polarization in hexagonal ZnS single crystal, (3) 85*a*.
green–copper, transition, in ZnS as elucidated by measurements of time-resolved spectrum, (10) 323*g*.
intrinsic, of RbI and KI at 10°K, (10) 322*a*.
in Mg_2SiO_4:Tb, Li phosphors, (7) 207*d*.
of neodymium, in germanium glasses, (6) 169*a*.
photo-, efficiency in Eu^{3+}-activated oxides, (10) 321*c*.
multicolor, glass systems, P (6) 178*b*.
properties, of europium-activated gadolinium and yttrium compounds, (5) 139*g*.
and radio-, of silver-activated borate glass, polarization of, (1) 6*j*.
of silicon carbide phosphors doped with group IIIA elements and/or nitrogen, (7) 207*h*.
from strontium oxide, (11) 355*j*.
synergized lanthanide chelate composition, P (7) 210*b*.
and thermo-, of LiF:(Mg,Ti), (4) 114*d*.
properties, of CdTe diode, (11) 354*f*.
of $NaGdO_2$:Eu, (11) 354*f*.
of some rare earth ions in zinc borate at host, (4) 112*f*.
of Ti-activated zirconia, (7) 207*k*.
room-temperature deformation, in alkali halides, (8) 256*g*.
thermo-, of calcite from high gamma radiation doses, (3) 88*c*.

Luminescence, thermo- (*continued*)
characterization of quartziferous materials, P (9) 277*i*.
of color centers in irradiated polycrystalline MgO, (8) 258*d*.
for dating ancient ceramics, (1) 1*j*.
of fluorite, (9) 288*d*.
in glasses of M_2O–Al_2O_3–SiO_2 system, (1) 8*c*.
of irradiated doped vitreous silica, (7) 197*e*.
of γ-irradiated solutions of aromatic compounds in rigid organic glasses, (2) 40*e*.
in LiF, stimulation by ruby laser light, (4) 116*f*.
in quartz, (3) 88*f*.
of synthetic fluorite, (5) 140*d*.
of unirradiated MgO and $Mg(OH)_2$, (7) 222*j*.
in vitreous sodium silicate, (4) 93*i*.
in ZnS:Cu,Al phosphors, (3) 88*e*.
of zinc doped solution grown GaAs, (8) 255*a*.

Machinery and equipment. See also *Materials handling* and specific types.
anvil apparatus, tetrahedral, compressive efficiency, (11) 345*h*.
for attaching handle to cup, (4) 98*c*.
blunger, high speed, for clay, (5) 143*h*.
chopper, rotary screen and waste, (5) 143*h*.
for clay preparation in structural clay products industry, (11) 348*j*.
for controlling coating depth in balling drum, P (2) 53*h*.
disk, applications in ceramic processing, (3) 74*h*.
dispenser, measured-quantity intermittent-action, for particulate material, P (2) 53*c*.
drive mechanism for contouring of rotatable objects, P (5) 137*c*.
drum roller, P (6) 179*c*.
for drying, calcining or cooling granular material, P (6) 179*e*.
fan, centrifugal, selection, (3) 74*h*.
hopper, for materials with poor flow characteristics, (1) 19*g*.
insulator turning, and automation in future, (10) 312*a*.

Machining, of alumina ceramic bodies, (9) 272*d*.

Magnesia. See *Magnesium, oxide*.

Magnesiowustite, single crystals, oxidation: II, dependence on temperature, oxygen pressure, and crystal structure, (1) 30*h*.

Magnesite. See also *Refractories*.
containing ZnO, calcined products, properties, (11) 338*g*.
metasomatic formation, (9) 282*h*.
powder, dense, making from rotary kiln dust, (9) 267*f*.
raw Brazilian, mineralogical and chemical study, (3) 67*c*,

Magnesium, aluminate, fibers and platelets, (2) 59*b*.
aluminate, hot-pressed, microstructure and room-temperature mechanical properties as described by quadratic multivariable analysis, (2) 59*b*.
pink, single crystals, growth, (11) 353*i*.
spinel, preparation and properties, (1) 15*f*.
atomic-fluorescence spectroscopy of, with high-intensity hollow-cathode lamp as line source, (10) 313*h*.
carbonate, basic, calcined products, properties, (11) 338*g*.
carbonate and oxide, production, P (3) 69*a*.
chloride, anhydrous, production, P (11) 349*e*.
dehydration, P (1) 25*j*.
dehydration using gaseous ammonia, P (1) 25*a*.
compounds, high density, and preparation, P (1) 17*c*.
ferrite, nonstoichiometric, cation distributions in, (5) 149*j*.
ferrite, precipitation and coarsening in dilute solutions of iron and MgO, (8) 256*b*.
fluoride, optical element, P (5) 130*e*.
fluoride, sintering, (1) 25*g*.
hydrate and oxide, high-dispersion fine-pored structures, increase in strength with additions of SiO_2, (5) 125*c*.
hydroxide, deformation during dehydroxylation of, (4) 107*a*.
direct conversion to high-density periclase, (10) 302*d*.
preparation by treating dolomite with magnesium nitrate solution, P (10) 3[illegible]8*h*.
production, P (5) 149*c*.
$MgCr_2O_4$–$MgFe_2O_4$ series, (10) 325*f*.
MgF_2:Co^{2+}, electron paramagnetic resonance, hyperfine structure of ^{19}F in, (9) 283*b*.
MgF_2:Co^{2+}, electronic structure, (11) 352*d*.
Mg_2Ge, infrared absorption, (8) 254*a*.
$Mg(OH)_2$, high purity, starting material for high density ceramics, (2) 56*j*.
α- and β-$Mg_2P_2O_7$, ESR study of Mn^{2+} in, (11) 352*g*.
$MgSO_4{\cdot}7H_2O$, dehydration, determination of thermal effects in, (4) 107*i*.
metatitanates, heat of formation, (1) 29*a*.
in ores and slags after separation of R_2O_3 and P_2O_5 with aqueous suspension of ZnO, (10) 313*h*.
oxide. See also *Refractories*.
aggregates, hot-pressing, (1) 29*c*.
bicrystals, intrinsic brittle strength, (2) 58*f*.
ceramics, foamed, (9) 267*b*.
chromous ions in, (11) 350*g*.
compression creep curve, shape of, (4) 115*b*.
creep, stress, temperature, and strain rate in, (11) 357*d*.
crystallites, derived from thermal decomposition of various Mg compounds, X-ray strain analysis, (3) 88*d*.

Magnesium oxide (*continued*)
crystallization in fused calcium aluminates, conditions for, (6) 164*d*.
crystals, bulk versus surface conductivity of, (5) 149*i*.
crystals, epitaxial dielectric, P (9) 272*i*.
crystals, toughness, effect of water, (7) 217*f*.
densification in presence of liquid phase, (4) 107*f*.
doubly associated cation-vacancy centers in, (8) 253*d*.
effect of atomic displacements on color center production in, (8) 253*d*.
electrical conductivity at low temperatures, (11) 352*h*.
equilibrium between alkali metal carbonates, gaseous CO_2, and, (7) 217*a*.
fully dense transparent polycrystalline, fabrication, (5) 152*j*.
gas emission from, in vacuum, (4) 98*j*.
grain shape change during creep in, (1) 29*f*.
growth of gold and silver on, (5) 152*e*.
^{100} systematic interactions, electron diffraction study, (1) 28*h*.
hot-pressing, (10) 303*f*.
impurity distribution in, addenda, (1) 26*e*.
ionic crystals, temperature dependence of infrared dispersion in, (11) 357*b*.
with 1% Fe, Curie temperature and saturation magnetization, (5) 140*b*.
irradiated, study of small defect clusters in, (11) 357*j*.
irradiated polycrystalline, thermoluminescent study of color centers in, (8) 257*d*.
isostatically hot-pressed, fabrication and characterization, (3) 81*d*.
low-lying energy levels, (10) 322*e*.
low-porosity burned, manufacturing process, P (7) 205*g*.
-$MgAl_2O_4$, creep of ceramic materials in, (9) 280*h*.
and $Mg(OH)_2$, unirradiated, thermoluminescence, (7) 222*j*.
matrix composites, elastic behavior, (1) 28*f*.
mechanical degradation by water vapor, (9) 284*b*.
neutron-irradiated, gas release, (4) 110*e*,
neutron-irradiated, inert gas bubbles in, (4) 111*e*.
polycrystalline, high-temperature creep: I, effect of simultaneous grain growth; II, effects of additives, (7) 2[illegible]8*d*.
polycrystalline, thinning for transmission electron microscopy, (3) 88*h*.
powders, explosively shocked, X-ray line broadening study of, (8) 258*c*.
pure and doped, transport phenomena in, (5) 159*f*.
reactions between vacancies and impurities in: I. Cr^{3+}-ion impurities; II, Mn^{4+}-ion and OH^--ion impurities, (11) 355*i*.
Rebinder effects in, (8) 256*a*.
recrystallized hot-pressed, indications of preferred orientation in, (1) 29*d*.
reduced pressure sintering, as high frequency insulator, (11) 355*j*.
refractive index, variation with pressure to 7 kbars, (11) 358*d*.
-SiO_2–Al_2O_3, sintering diagram, and dielectric properties, (3) 86*h*.
single-crystal, diffusion of Zn^{2+} in, (3) 80*c*.
sintering kinetics and powder properties, (8) 239*c*.
solid state reactions with SiO_2, Al_2O_3, CaO, Fe_2O_3, and ZrO_2, (7) 221*b*.
solubility in molten MgF_2, (4) 115*j*.
spin-lattice coupling of Kramers doublet—Co^{2+} in, (9) 286*c*.
and titanate, solubilities in Al_2O_3, (2) 59*g*.
ultraviolet-irradiated, EPR of oxygen on, (7) 217*g*.
vapor phase hydration, kinetics of: II, dependence on temperature and water vapor pressure; III, effect of iron oxides in solid solution, (3) 82*j*, 83*h*.
whiskers, ductile, (1) 28*c*.
phosphate, double substituted, crystal hydrates, dehydration of, (4) 107*c*.

silicate, strength under biaxial stresses, (6) 189*d*.
systems. See *Systems*.
trisilicate, as additive in vitreous enameling, (2) 38*c*.
tungstate, crystals, ESR of Cu^{2+} in, (7) 217*g*.

Magnetic materials. See also *Ferrites; Ferromagnetic materials; Ferromagnetism*.
ceramics, (3) 71*i*.
elements, sizing apparatus, P (11) 343*i*.
europium silicate, and preparation, P (6) 177*g*.
feebly, device for recovering in wet separators, P (1) 25*b*.
sintered nonmetallic, production, P (9) 274*h*.
toroidal, evaluation, (5) 138*h*.

Magnetic properties. See also *Anisotropy; Resonance*.
of $A^{2+}Cr_2S_4$ compounds with the NiAs structure, (8) 255*c*.
of ceramics, (6) 176*c*.
of cobalt disulfide, (8) 256*c*.
of copper ferrite, effect of oxygen deficiency on, (10) 319*j*.
of cubic [illegible]talum carbide, (9) 284*e*.
dia-, [illegible]ptibility, of graphitized carbons, (2) 43*j*.
of divalent nickel in $Sr_2(NiW)O_6$, (10) 322*g*.
electro-, structures, for high-temperature service, P (5) 141*f*.
of europium metal and monoxide, at high pressure, (9) 284*i*.

Magnetic properties (*continued*)
fields, pulsed, frequency conversion of spin waves in, (4) 110*d*.
galvano-, nonlinear effect, of *n*-type InSb in quantum limit, (9) 284*i*.
gyromagnetic factors and covalency in iron-series complexes, (9) 282*h*.
interactions, in ternary ruthenium oxides, (6) 187*c*.
of α-Fe_2O_3 fine particles, (3) 83*i*.
of γ-Fe_2O_3, variations with compression, (2) 50*b*.
low temperature, of $LaCoO_3$, (2) 49*g*.
low-temperature, of terbium oxides, (5) 139*i*.
of $M_{1-z}Li_zFe_2O_4$–$_zF_z$, (7) 219*e*.
of magnesioferrite, (5) 140*b*.
of magnesites, (5) 147*j*.
of Mg–Mn ferrite and zinc and cadmium substituted Mn–Mg ferrite, effects of annealing conditions on, (9) 27 *i*.
magnetic moments in $CoPt_3$, (9) 284*e*.
magnetoelastic, hybrid waves, in YIG, adiabatic time domain conversion of, (4) 105*j*.
magnetoelastic two-port configuration in YIG, (3) 71*j*.
magnetoelastic waves, in YIG, high efficiency reversal by optical-contact bonding of YAG disks, (3) 71*b*.
magnetoresistance, weak-field, in *n*-type aluminum antimonide, (8) 258*c*.
magnetostriction, antiferromagnetic, in CoO single crystals, (4) 111*h*.
and domain walls in NiO: I, theory; II, experiment, (4) 112*h*.
trigonal, in α-Fe_2O_3, (4) 108*j*.
of ytterbium and cerium in YIG, (4) 98*j*.
of MnBi, studied by neutron diffraction, (5) 138*h*.
of $MnGeO_3$ and $MnTiO_3$, (7) 219*g*.
of MnO, (8) 252*c*.
of α-MnS, (8) 252*c*.
of manganese zinc ferrites, effect of Cd-for-Zn substitution, (10) 307*b*.
of orthosilicates with olivine structure, (10) 322*i*.
para-, of iron centers in quartz, (7) 220*f*.
para-, species, in gamma-irradiated single crystal ferroelectric lithium trihydrogen selenite, (3) 84*f*.
of pulverized cobalt ferrite, (5) 154*b*.
of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (3) 87*f*.
of $KMnF_3$: III, nuclear and electron spin resonance, (9) 284*g*.
of $RbNiF_3$, transparent, (1) 16*g*.
saturation, of cemented carbides, (9) 284*g*.
of scandium-containing ferrites, causes of transformation, (1) 16*b*.
of strontium ferrates, (5) 138*a*.
susceptibility, aspects of instrumentation and applications to chemistry and solid state science, (8) 248*a*.
of cubic UO_{2+x} at high temperatures, (11) 354*a*.
high-temperature, of vanadium-doped corundum crystals, (5) 137*e*.
low-temperature, of ferrous oxalate dihydrate, (8) 254*i*.
of Mn^{2+} in CdS and effects of antiferromagnetic exchange, (9) 284*i*.
of praseodymium oxides, (5) 138*j*; (6) 187*d*.
of $SrLaFeO_4$ with K_2NiF_4 structure, (10) 323*b*.
study of $UO_3{\cdot}xH_2O$, (6) 187*h*.
of thorium monocarbide, (10) 320*j*.
of $(U_{1-\zeta}Th_\zeta)O_2$, (11) 354*b*.
of ultrafine iron(III) oxide-hydrate particles prepared from iron(III) oxide-hydrate gels, (8) 255*d*.
of vanadium bronzes, (1) 29*i*.
of VO, (10) 320*e*.

Magnetism, characteristics, of some lanthanide nitrides, (1) 16*g*.
electromagnetic induction in plasma, (10) 312*c*.
magnetic control device, current and temperature responsive, P (9) 272*e*.
magnetic domains, direct observation by scanning electron microscopy, (8) 248*f*.
magnetic moments, rotational, of alkali-halide molecules, (8) 256*h*.
magnetic order, in Ti_2O_3, (11) 356*g*.
magnetic storage devices, method of making, P (10) 310*e*.
memory, of α-Fe_2O_3, explanation based on negative pressure effect on Morin transition point, (11) 354*j*.
meta-, of $NaNiO_2$, (11) 354*d*.
order, long-range, in MnO, (8) 254*g*.
para-, of Dy^{3+} and Gd^{3+} in silicate glasses, (8) 233*b*.
studies, of ferrimagnetic calcium ferrites containing tri- or tetravalent metal ions, (11) 354*h*.
of ferrimagnetic garnets containing fluorine, (8) 255*a*.
of iron diffused into sodium disilicate glass, (3) 64*d*.
structure, of Cr_2WO_6, (11) 354*j*.
transition, in thiourea-coordinated cobalt chloride, (10) 323*e*.

Magnetite, application of Green's function theory of ferrimagnetism to, (10) 321*d*.
artificial, by wet method, (9) 287*c*.
black, and properties as polishing agent, (5) 123*j*.
initial reduction stages, in hydrogen, kinetics, (9) 283*b*.
nuclear magnetic relaxation in, (10) 323*i*.
plasticity, measured by hardness as function of temperature, (7) 220*b*.
reduced, structural promotion, (3) 87*d*.

Magnetoelectric, effect, induced, in YIG, (8) 254*j*.
Magnetoresistance. See *Resistivity, electrical.*
Magnets, ceramic permanent, (3) 70*j*.
ferrite, P (6) 177*h*.
material, permanent, and process for manufacturing, P (8) 245*i*.
Maintenance, program, updated with visual records, (3) 75*a*.
Management, liquidity problems, (7) 223*f*.
obsolescence, (3) 89*a*.
plant, efficient, (7) 223*d*.
relation with labor to avoid unionization, (7) 223*f*.
Manganese, bismuth, magnetic and crystallographic properties studied by neutron diffraction, (5) 138*h*.
in borate glasses, ESR, (5) 127*i*.
carbonate, NMR in canted spin state, (8) 255*j*.
dioxide, of manganese ore, reduction to MnO, (7) 215*d*.
dioxide, preparing, P (3) 78*c*.
ferrite, single crystals, thermal conductivity at low temperatures, (5) 159*b*.
ferrites, study by Moessbauer effect of intermediate phases in formation of, (1) 32*e*.
fluoride, antiferromagnetic, two-magnon absorption in, (10) 327*a*.
crystalline, Zeeman splitting of narrow lines in, evidence for spin-wave excitations, (10) 327*g*.
effect of uniaxial stress on magnon sidebands in, (11) 352*e*.
NMR studies of critical phenomena in: I, time-average properties, (11) 355*c*.
germanate and titanate, magnetic properties, (7) 219*g*.
glass-molybdenum metallizing ceramics, (6) 166*c*.
ions, reciprocal effect in glass, (1) 7*d*.
Mn^{2+}, ESR in $BaTiO_3$ single crystal, (10) 320*g*.
Mn^{2+}, located at B-sites in manganese ferrite, ^{55}Mn NMR of, (4) 113*f*.
Mn^{2+}, in α- and β-$Mg_2P_2O_7$, ESR study, (11) 352*g*.
Mn^{4+}, located at B-sites in ferrites, ^{55}Mn NMR of, (4) 113*f*.
$MnCr_2S_4$, NiAs-type polymorphs, magnetic properties, (8) 255*c*.
$MnFeO_3$, Moessbauer effect in, (10) 323*b*.
α-$MnMoO_4$, paramagnetic, crystal structure, (11) 351*e*.
Mn_2O–Al_2O_3, initial sintering, (9) 283*c*.
MnP–MnAs solid solution, magnetic and structural study, (6) 176*d*.
$MnSi_2$, phase transformation in, (10) 324*i*.
$Mn_3V_2O_7$, thortveitite-type structure of, (5) 159*f*.
$MnYb_2S_4$ spinel, magnetic and structural study, (1) 30*a*.
metallic perovskites, first order magnetic transitions in, (4) 98*i*.
monoxide, high temperature electrical properties, (5) 138*e*.
nitride, P (9) 270*e*.
oxidation, in CO_2–CO mixtures, (4) 113*f*.
oxide, crystal, cohesive energy, (3) 79*h*.
crystals, electron distribution of ions in (3) 80*d*.
and dioxide, lattice parameter, as function of pressure, (7) 219*c*.
long-range magnetic order in, (8) 254*g*.
reduction from silicate and aluminate slags by carbon-saturated iron, rate and mechanism, (2) 45*g*.
in rocks, precision analyses by neutron activation analysis, (5) 145*j*.
silicides, thermodynamic properties, (9) 288*b*.
sulfide, lattice parameter, as function of pressure, (7) 219*c*.
systems. See *Systems.*
and titanium, reactive sputtering of, (10) 308*e*.
zinc ferrite, metallographic study, (9) 272*d*.
Manpower, profitability and industrial training, (7) 223*g*.
training of technologists, (7) 223*f*.
Marble, synthetic, forming, P (10) 318*d*.
Yule, mechanism for plastic deformation of, (4) 113*a*.
Marketing, (3) 89*b*.
Asian export threats, (6) 190*j*.
brick using supermarket display techniques, (7) 223*e*.
role in setting product specifications, (7) 223*d*.
Masers. See also *Lasers.*
junction diode, P (4) 100*e*.
Masonry, brick, model, bond tensile strength, bond shear, and effect of precompression on shear strength of, (10) 301*e*.
dehumidification, enabling, P (1) 10*h*.
walls, shrinkage cracking, influence of mortar and block properties on, (6) 165*c*.
Materials. See also *Ceramic materials.*
amorphous characterization, by diffraction patterns, (6) 180*f*.
ceramic, use in medium of steam of high parameters, (8) 240*i*.
characterization, B (8) 258*i*.
for deep ocean pressures, (4) 104*i*.
high melting, increasing strength of, (8) 237*i*.
inorganic, investigation by X-ray crystallography, (8) 248*f*.
nature of, B (11) 358*d*.
new, in engineering, (1) 25*c*.
powdered, phase analysis, electromechanical principles of, (10) 314*g*.
powdered-metal, influence of machining conditions on physicomechanical condition, B (1) 34*g*.
Materials *(continued)*
raw, ceramic, properties, B (11) 358*j*.
characterization, B (9) 288*g*.
cost of hauling vs. cost of land, (4) 119*f*.
gravel and crushed stone plants, development of mechanization and technology, (3) 77*g*.
leucophyllite, ceramic uses, (6) 182*f*.
Portuguese resources for ceramic industry, (9) 278*j*.
prereacted, and article obtained, P (4) 97*d*.
refractory, microhardness tests, (6) 180*i*.
refractory, physical methods of analysis, (6) 180*j*.
for rock-melting industry, (5) 148*f*.
bulk, sampling, (6) 181*c*.
Shirasu, industrial application: I, autoclave-hardened bodies using Shirasu, (8) 250*j*.
Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment.*
bulk, (2) 52*j*.
bulk shipments, of dry flowables, (3) 75*b*.
in clayworks, (5) 143*i*.
conveying fine granular and pulverous material by gaseous means, P (11) 345*j*.
device for discharging material from screw conveyor, P (1) 20*f*.
equipment, obsolescence, (2) 53*c*.
filled-bag stacking, P (8) 251*c*.
forklift truck, (2) 53*f*.
economic life of, (3) 74*i*.
gas or electric, (2) 53*a*.
granular flow stimulating devices, P (5) 144*a*.
of granular and powdered material, apparatus for controlling flow, P (5) 144*d*.
hopper, mechanism of gravity flow of particles from, (11) 345*h*.
intermittent-action dispenser for particulate material, P (2) 53*c*.
kiln loader and unloader, P (4) 98*f*.
loading chamber in bulk transport systems, P (4) 105*d*.
pallet, device for pulling, (4) 103*f*.
pneumatic outlet for unloading particulate materials, P (2) 53*f*.
Measurement, apparatus for modulus of elasticity at high temperatures, (10) 313*f*.
apparatus, for X-ray emission from and density of material, P (3) 76*c*.
dynamic, of elastic modulus of ceramics at elevated temperatures, apparatus for, (10) 313*d*.
of fractional metastable-state population of Cr ions in ruby under *Q*-switching operation, (8) 255*d*.
of ground-state population in ruby under optical pumping, (3) 83*j*.
high speed, of two-photon absorption processes, (6) 180*e*.
magnetometric and dilatometric, automation in, (1) 20*j*.
of material buckling of U–H_2O assembly, (9) 267*i*.
noncontacting dynamic distance, (3) 76*a*.
of picosecond laser pulse widths, (3) 83*j*.
precise differential, of monolayer surface potentials, (1) 31*i*.
techniques, application for efficient utilization of fuels, (1) 24*b*.
time, as indication of temperature, P (1) 24*a*.
voltage/current, in Ghz range, Bolovac, (5) 144*i*.
Measurement devices, Blaine apparatus, new method of calibration, (4) 92*e*.
consistency, P (5) 147*a*.
for fuel element coolant channels, (9) 277*a*.
for glaze or porcelain enamel wet thickness, (4) 103*f*.
for liquid and gas flow, (8) 248*d*.
melting point, P (5) 147*c*.
photosensitive, for dimension of object, P (8) 249*c*.
for small to large flow rates, (2) 55*c*.
Mechanical properties, of abrasive grain, (11) 331*g*.
behavior of anisotropic structural materials, (4) 120*j*.
behavior, of X-cut quartz shock loaded at 79°K, (3) 85*h*.
of blended and ball-milled Al–Al_2O_3 alloys, (2) 45*e*.
of boron-tungsten boride filaments, (4) 98*f*.
of dispersions of thoria in beryllia, (1) 30*c*.
of glasses with iron oxide films, (10) 298*d*.
high-temperature, of ceramic materials: V, $(Zn_{0.45}Mg_{0.55})_2SiO_4$, (5) 153*a*.
of lithium aluminosilicate glass during sitallization, (8) 232*g*.
of MgO, degradation by water vapor, (9) 284*b*.
of metals, influence of ceramic environment, (1) 29*e*.
of neutron-irradiated pyrolytic carbons, (10) 323*f*.
room-temperature, of hot-pressed $MgAl_2O_4$, described by quadratic multivariable analysis, (2) 59*b*.
of SiC and Si_3N_4 materials, (11) 338*j*.
of spinel-corundum highly refractory ceramics, influence of heat treatment conditions, (8) 238*b*.
of thin condensed films, B (8) 260*f*.
of WC–Co hard alloys, effect of carbon, (1) 11*f*.
of uranium monocarbide, effect of dispersed metallic uranium or uranium dicarbide, (6) 172*i*.
Meetings. See *Conferences.*
Melting, of analcite solid solutions in system $NaAlSiO_4$–$NaAlSi_2O_6$–H_2O, (2) 58*i*.
and crystal structure, (5) 154*f*.
curve, corresponding-states, for alkali halides at high pressure, (7) 216*j*.
Melting *(continued)*
-curve maxima, model, at high pressure, (11) 354*f*.
curves, of rubidium halides at high pressures, (6) 187*g*.
electric, of enamels, (8) 229*f*.
electron-beam zone, for preparation of corundum monocrystals, (9) 272*g*.
of glasses with increased content of rare-earth elements, (6) 168*c*.
induction, of central core portion of cylindrical shaped refractory materials, P (2) 47*c*.
kinetics, of sodium disilicate, (1) 27*i*.
law, modified, at high pressures, (1) 30*j*.
mechanisms, (1) 30*e*.
method, effect on homogeneity of glass as shown by light scattering, (11) 333*h*.
point, of alumina, experimental determination, (1) 32*a*.
of alumina in vacuum, (1) 30*f*.
of cryolite, (3) 83*a*.
determination of uranium monophosphide, (3) 83*b*.
determinations, applying, (1) 20*j*.
of sodium halides, effects of pressure on, (10) 320*b*.
of thorium mononitride, (11) 351*g*.
of water in glass capillaries, (11) 353*c*.
properties, of $KAlSi_2O_6$, effect of pressures up to 40 kbars, (5) 154*h*.
reactive arc, for preparation of rare earth nitrides, (7) 214*f*.
relation in system TiO_2–WO_2, (6) 187*g*.
re-, of compounds and alloys, P (5) 142*f*.
semiconductor materials, processes, P (2) 52*h*.
uranium oxide and plutonium oxide, method, P (1) 13*f*.
zone, temperature gradient, and growing of semiconductor material, P (4) 101*e*.
Melts, alkali borosilicate, rearrangement kinetics of liquid-liquid immiscible microphases in, (5) 128*g*.
alkali germanate, electrical conductance at 1300°C, (3) 80*a*.
alkali metal nitrate, electrical conductance and density, (11) 352*h*.
aluminogermanate, with Na_2O/Al_2O_3 ratio greater than unity, structure, (5) 128*b*.
chloride-fluoride, fluoride complexes of Be in, (10) 321*e*.
crystallizing, interface temperature, (2) 58*e*.
granitic, immiscibility, indicated by fluid inclusions in ejected granitic blocks from Ascension Island, (4) 111*c*.
ionic, electromigration and self-diffusion, (3) 80*b*.
iron oxide-silica, density, (4) 107*g*.
lead chloride, resistance of refractories in, (9) 267*d*.
oxide-carbonate, of alkaline earth metals, activities in, (4) 105*j*.
penetration into materials of capillary porosity, procedure for determining, (1) 22*i*.
simple silicate, Newtonian flow at high temperature, (5) 128*d*.
sodium aluminogermanate, with Na_2O/Al_2O_3 ratio equal to unity, structure, (5) 128*h*.
sodium aluminosilicate, containing 50% (mole) SiO_2 at 1500°C, (4) 93*f*.
sodium borate, reaction with neodymium and cerium oxides, (6) 188*b*.
structure, in $Na_2O \cdot GeO_2 \cdot B_2O_3$ system, (1) 7*e*.
vitreous carbon and glass, reactivity, (7) 197*d*.
Membranes, inorganic permselective, P (10) 309*j*.
Memory, module, electrical, method for fabricating, P (1) 18*j*.
Memory cores. See *Data storage.*
Memory devices. See *Data storage.*
Metallizing. See *Coatings.*
Metalloceramic compositions. See *Cermets.*
Metallography, of manganese zinc ferrite, (9) 272*d*.
Metallurgy, powder, use of glass in, (5) 129*f*.
process, heat and mass transfer in, B (1) 34*f*.
Metals. See also *Enameling metals; Rare earths.*
alkali, and alkylammonium phosphatoaluminate complexes, and preparation of crystalline aluminosilicates, P (9) 279*b*.
alkali, oxyzincates of, (5) 156*h*.
alkaline earth, hydrides, production, P (5) 149*b*.
alkaline earth, oxides, reaction with Sc_2O_3, (10) 324*i*.
aluminides, preparation, P (10) 318*i*.
carbide, adherently depositing on metal substrate, P (5) 126*b*.
carbide-cobalt hard, breaking strength under impact loads, (5) 131*g*.
-ceramics. See *Cermets.*
chemical deposition of, in production of metal film resistors, (10) 306*i*.
diethyldithiocarbamates, determination of extraction constants, (4) 104*h*.
fatigue tests for, (10) 314*e*.
ferrous, silicon-containing diffusion coating for, P (11) 333*b*.
ferrous, treatment, P (8) 230*b*.
fiber-reinforced, effect of fiber orientation on tensile strength, (1) 4*b*.
fiber-reinforced, tensile properties, (1) 4*d*.
fillers, powdered, effect on properties of silicate enamels, (5) 125*i*.
group IVa, ultrapurification of, (8) 248*j*.
heat treating, in molten bath of borate glass, P (9) 265*i*.
mechanical properties, influence of ceramic environment, (1) 29*e*.
molded material, expansion scabbing, (1) 11*h*.
molten, oxygen activity, methods and apparatus for determining, P (4) 97*a*.
molten, sampling apparatus and method, P (5) 130*a*.

Metals (*continued*)
nature and properties, in materials, B (11) 358*d*.
noble, additions, effect on toughness of iron-carbon alloys, (6) 185*h*.
noble and transition, reaction with refractory carbides, (10) 324*i*.
oxides. See *Oxides*.
protection and lubrication at high temperatures with glass coating, P (3) 66*a*.
protective coating agents for aluminum, temporary high temperature, for, P (11) 333*a*.
rare-earth, silicides, hardness, (9) 282*h*.
rare-earth, vacuum-thermal production of silicides of, (9) 288*b*.
structure and strength, B (5) 161*c*.
surfaces, measurement of organic films on, (11) 332*e*.
systems. See *Systems*.
thermocompression bonding of, to semiconductor, metallic, or nonmetallic surfaces, P (8) 246*c*.
trace, determination using coordination chain reactions with masking agents and automated rate measurement, (5) 145*c*.
transition, carbides and borides, porous materials from, (5) 133*c*.
transition, sesquioxides, electric field gradient calculations in, (9) 281*j*.
ultrafine, preparation and characterization, (4) 114*j*.
Metaphosphates. See *Phosphates*.
Meteorites, stony, fluorine in, (10) 313*j*.
Mica. See also *Refractories; Vermiculite*.
alternation, chemical changes during, (6) 184*h*.
biotites, intracrystalline chemical variation in, (10) 322*i*.
natural, charge balance and cation distribution, (10) 319*g*.
spectrum, hydroxyl-stretching region, (8) 254*i*.
brittle, structures, B (7) 224*j*.
color stabilized, P (6) 182*j*.
flakes, subjected to hot aqua regia, for making paper, P (9) 274*a*.
fluor-, and fluoramphiboles, and methods of making, P (4) 105*b*.
fluorine in, (10) 313*j*.
interfacial energy, direct measurement of influence of vapor, liquid, and oriented monolayers on, (9) 280*j*.
paper, P (2) 51*j*.
residual lines, studies, (5) 158*e*.
Micrographs, field-ion, interpretation, contrast from perfect dislocation loops, (8) 248*i*.
Micrography, electron, prints, technique for improving information quality, (5) 146*d*.
Microhardness. See *Hardness*.
Microscopes, binocular, for orientation of single crystals, (1) 23*e*.
cover glasses, manufacture, (7) 196*c*.
electron, of CaO structure, (1) 28*i*.
combined with diffraction apparatus for electron-optical inspection of surfaces, P (4) 103*f*.
for determination of thickness of deposited thin layer of Ni, (11) 346*g*.
examination of particulate Al_2O_3, (8) 248*f*.
examination of plastic deformation of diamond, (1) 26*j*.
ferroelectric ceramics in, (11) 342*e*.
-mirror, analysis of surface potentials on ferroelectrics, (9) 281*j*.
observations of thin zirconia films obtained by oxidation of Zr, (4) 109*i*.
for studying electrotechnical porcelain, (2) 48*h*.
thickness measurements in, (4) 103*d*.
transmission, studies of neutron-irradiated BeO, (8) 258*g*.
microprobe-electron, (10) 313*b*.
microscopical fields, accessories for locating in polished sections, (1) 20*g*.
optical, and technical ceramics, (10) 315*h*.
scanning electron, for examining glass fiber surfaces, (8) 231*j*.
for obtaining Kikuchi-like reflection patterns, (8) 248*j*.
specimen cooling stage for, (2) 55*d*.
Microscopy, chemical and mineral, methods, B (4) 120*d*.
electron, (10) 314*j*.
of defect structure due to ordering in alloy Ni_4Mo, (4) 109*a*.
for determination of crystallite size distribution, (3) 78*f*.
of devitrified glass powder compacts, (11) 333*j*.
of etched plagioclase feldspar, (1) 28*j*.
preparation of highly dispersed materials for, (11) 347*a*.
of spherulites formation in silicate glasses, (8) 231*i*.
study of kaolinite formation from albite altered by water at 200°C, (7) 217*e*.
study of quartz glass, (10) 297*j*.
ultrathin Al_2O_3 support films for, (1) 23*j*.
examination, using replica technique, (1) 22*e*.
field-ion, of refractory metal carbides, (8) 237*j*.
field-ion, of titanium carbide, (8) 253*h*.
methods of determining contact angles of small drops, (9) 227*b*.
for more about processes and products, (4) 103*d*.
optical, of hydraulic cements, (7) 194*h*.
proton scattering, (1) 31*e*.
resin epoxy, for preparation of thin sections of fragmental materials, (1) 22*i*.
scanning electron, for direct observation of magnetic domains, (8) 248*f*.
scanning electron, of ferroelectric domains in barium titanate, (1) 16*g*.

Microscopy (*continued*)
techniques for determination of preferred orientation in clay minerals, (9) 285*b*.
transmission electron, for observation of dislocations in BeO, (2) 45*e*.
obtaining thin glass sections for, (9) 277*b*.
of twinned silver bromide crystals, (4) 118*b*.
varioscopic, in crystal optics, (7) 212*j*.
X-ray, point-projection, (1) 22*g*.
Microstructure. See *Structure*.
Microwaves, and corona methods for detection of voids in glass-epoxy structures, (7) 212*b*.
devices, utilizing Eu–Fe garnet containing Ga, P (3) 73*h*.
for heating nonmetallic solids, (2) 53*b*.
void detection in honeycombed ablative materials, (7) 212*d*.
Migration, differential, for purification, (6) 181*c*.
particle, in shear fields, (10) 324*h*.
void, in oxide fuel, (7) 203*f*.
Milling. See also *Crushing; Grinding*.
of clay, (9) 278*i*.
conventional versus vibratory, (3) 75*e*.
of enamels, (11) 332*i*.
multistage, P (8) 247*g*.
vibration, effect of charge condition, (1) 19*i*.
Mills. See also *Crushing apparatus; Grinding apparatus*.
fine grind hammer, with adjustable hammer rotor, P (7) 214*c*.
grinding, and fineness control system, P (5) 148*c*.
large diameter, structure for, P (11) 346*a*.
and method of operation, P (2) 50*f*.
plant, P (11) 345*i*.
hammer, hammer tip and clamp for, P (7) 214*d*.
-jar support, P (3) 65*b*.
metallurgical grinding, corrosion-proof rubber lining for, P (7) 214*c*.
multichamber, P (10) 312*e*.
rotary grinding, automatic high pressure lubrication system for, P (7) 211*a*.
vibrating grinding, P (10) 318*j*.
vibratory, P (2) 57*c*; P (10) 312*i*.
Mineral fibers. See *Mineral wool*.
Mineral wool. See also *Fibers, glass*.
board, binder distribution method for producing, P (1) 12*i*.
manufacture in blast nozzles, (8) 234*c*.
Mineralizers. See also *Fluxes*.
effect on polymorphic transformation of SiO_2, (7) 217*d*.
preparation, and effect on Dinas quality, (9) 268*i*.
Mineralogy, of Ahl kaolinite, (9) 278*j*.
clay, of Glenwood formation, southeastern Minn., and adjacent areas, (2) 56*g*.
clay, of lower Cabaniss underclays in western Missouri, (1) 10*c*.
of clays, Bansi, (4) 113*d*.
diagenesis, role of electrical currents and potentials in, (1) 31*i*.
of illites and mixed-layer illite/montmorillonites, (2) 59*b*.
of Indian limestones, (6) 189*b*.
of kaolinite-halloysite clays: III, fibrous kaolin mineral from Piedade, Sao Paulo, Brazil, (5) 154*j*; IV, platy mineral with structural swelling and shrinking characteristics, (5) 154*j*; 155*a*.
of lower Devonian bentonites from Gaspe, P. Q., (5) 148*e*.
of potassium-barium feldspar series: I, determination of optical properties of natural members; II, studies on hydrothermally synthesized members, (9) 284*d*.
of Upper Cambrian K-bentonite from Missouri, (4) 113*e*.
Minerals. See also *Raw Materials; Rocks;* and specific types.
beach sand, of Kerala, correction factor for volume differences in estimation of, (10) 313*d*.
beryllium and aluminum, process for concentration, P (7) 205*e*.
carbonate, far infrared spectra, (5) 152*e*.
clay. See *Clays*.
clinoptilolite, ion exchange on, (11) 353*h*.
constituting cement, hydration kinetics, (2) 36*c*.
existence of hydronium hydrates $H_5O_2^+$ and $H_9O_4^+$ in, (6) 185*h*.
granulite-facies metamorphism, Granite Falls, Montevideo Area, Minnesota, (4) 110*f*.
Hungarian silicate, study by infrared spectrophotometry, (7) 222*i*.
Indian, quantitative estimation of free silica content, (1) 34*d*.
industrial, review, (1) 24*j*.
industrial, review, 1967, (11) 348*j*.
industries, Pennsylvania's, historical statistics, (11) 348*j*.
infrared absorption spectra of, (6) 180*f*.
microspectrochemical analysis, with laser microprobe, (7) 212*j*.
mixed layer, as one-dimensional crystals, (7) 219*a*.
from Moine schists of Ardnamurchan area, Argyllshire, Scotland, chemical study, (3) 79*d*.
new, discredited, and changes in nomenclature, index, B (1) 34*f*.
new, formation in chromites by firing in weakly reducing and oxidizing atmospheres, (5) 132*g*.
opaque, apparatus for study by transmitted polarized light, (4) 102*e*.
prospecting, use of radioisotopes, (1) 25*g*.
with pyrite, marcasite, arsenopyrite, and loellingite structures, structural stability, (9) 278*j*.
quantitative chemical analysis, in thin section with X-ray macroprobe, (5) 146*c*.

Minerals (*continued*)
silicate layer, and products made therefrom, P (3) 78*e*.
structure, complex, calculation of unit-cell volume of, (6) 184*c*.
tetradymite, synthesis, (5) 149*h*.
of Utah, (7) 214*f*.
yearbook, 1966: Vols. I–II, metals, minerals, and fuels, B (8) 260*b*.
Mines and mining, Sinya meerschaum, northern Tanzania, (4) 104*g*.
Mirrors, blank, 158-inch fused quartz, (6) 168*f*.
glass, with tarnishing resistance, P (7) 198*g*.
production: II, silvering methods, (2) 39*f*.
silver and copper coated, protected by treatment with aminoazole compounds, P (8) 236*c*.
telescope-, glass-ceramics for, (11) 334*b*.
Miscibility. See also *Solubility*.
gap system, thermodynamics, and test of nucleation theory, (7) 222*g*.
of pyralspite and grandite molecules in garnet, (8) 255*g*.
Missiles. See *Spacecraft*.
Mixers, P (1) 20*d*; P (6) 179*f*.
clay, and extruder, P (2) 53*i*.
for conditioning particulate material, P (2) 53*g*.
and conveyor, for solids, P (8) 247*d*.
drum-tumbler holder, P (7) 211*b*.
for foundry sand and additives, P (6) 174*b*.
-grinder, for foundry sand, P (3) 69*e*.
and milling, washing, extracting apparatus, P (8) 247*e*.
paddle and drum, comparison for quality and productivity, (8) 238*j*.
for producing self-hardening molding sands, P (9) 270*a*.
rotary, P (6) 179*h*.
solids-liquids, P (4) 102*b*.
vertical, P (2) 53*g*.
Mixing, bulk materials, method of forming permeable structure for, P (4) 102*a*.
clay, analog computer solves problem of, (2) 48*g*.
dry, statistical procedure to determine quality, (9) 275*h*.
literature review, (8) 247*a*.
nonideal, in binary GeO_2–SiO_2 glasses, (8) 233*j*.
of raw kaolin, (10) 312*a*.
solids, (5) 143*i*.
Mobility, Hall, in heavily doped *n*-type gallium arsenide, (3) 81*i*.
Models, Born, calculation of enthalpies of solution to dissolve NaF and YF_3 in CaF_2, (1) 26*f*.
defect structure, for nonstoichiometric CeO_2, (1) 28*a*.
for electric double layer, comparison, (1) 27*e*.
electrochemical, for oxidation of Zr, (4) 109*g*.
mathematical, for failure of cement paste and mortars, (8) 228*g*.
rheology, of halloysite suspensions, (6) 187*g*.
shell, of interionic interactions for $BaTiO_3$, (3) 72*c*.
solvable, of hydrogenic system in strong electric field, application to optical absorption in semiconductors, (10) 325*a*.
statistical, system derivation, in study of silicate materials, (10) 313*e*.
Modulators, and acoustooptical deflection devices, (9) 277*c*.
microwave, using anisotropic effects of ferromagnetic resonance in single crystals, P (11) 344*g*.
Modulus of elasticity. See *Elasticity*.
Modulus of rupture. See *Rupture*.
Moessbauer, effect, for determination of properties of supported small α-Fe_2O_3 particles, (8) 257*c*.
effect, ^{57}Fe, in nickel oxide, (9) 282*j*.
in $MnFeO_3$, (10) 323*b*.
for measurements of compound $2CaO{\cdot}(Al_2O_3)_x{\cdot}(Fe_2O_3)_{1-x}$, (9) 284*a*.
for precipitation and oxidation studies in Cu–Fe system, (10) 324*b*.
in system $BaFeO_{3.5-2.0}$, (6) 187*h*.
in system $SrFeO_{3.0-2.0}$, (5) 155*h*.
for study of initial crystallization stages of glass, (8) 234*i*.
study of V_2O_3, (10) 323*b*.
spectra, of amphiboles, (5) 155*i*.
study, of calcium diferrite, (10) 323*d*.
on cation distribution in $FeAl_2O_4$, (11) 354*g*.
of ^{57}Co (^{57}Fe) in cobaltous oxide at high pressure, (10) 323*f*.
on iron in perovskites $La_{1-x}Sr_xFeO_3$, (9) 284*g*.
Moire effect, for determination of discontinuous surface displacements, (8) 248*a*.
Moisture. See also *Humidity; Steam; Water*.
content, of plaster molds, apparatus to determine, (1) 15*b*.
determining device, with pressure operated capacitor member, P (7) 213*a*.
measurement apparatus with neutron reflecting material to provide optimum counting range, P (2) 55*f*.
measuring device including capacitor electrodes differing in size, P (10) 316*c*.
method and apparatus for measuring and adjusting, and formability of granular material, P (6) 174*e*.
in porous materials, determination with nuclear measurement techniques, (11) 346*c*.
in sand, measurement, P (1) 23*j*.
measurement, infrared, (7) 212*i*.
removal, from material, method and apparatus, P (9) 278*b*.
sensitive materials, glove box and drying system for manipulation of, (4) 102*g*.
Molding, comminuted nonplastic inorganic material, method, P (1) 20*c*.

Molding (*continued*)
composition, of calcium sulfate anhydrite and ammonium alum with water, and method of use, P (4) 92*f*.
composition, comprising refractory material and reaction product of formaldehyde, furfuryl alcohol and urea as binder, P (4) 97*c*.
and forming, artistic ceramics, (3) 61*i*.
graphite containing segmented thermoelement, P (10) 304*e*.
injection, apparatus, for making ceramic cores, P (3) 68*h*.
machine, use of match plate plaster of Paris for, (8) 238*c*.
pressure, powdered material, method, P (1) 18*g*.
Molds. See also *Slip casting; Slips*.
casting, P (7) 211*f*.
cavityless, for large precision die castings, P (10) 304*h*.
for ceramic article, P (7) 211*f*.
hollow ceramic articles, P (10) 306*e*.
multiple billet continuous, P (1) 13*c*.
ceramic-mass-containing, revolving, apparatus for shaping pottery in, (9) 271*e*.
ceramic shell, P (2) 46*g*.
cooling control apparatus, for glassware forming machine, P (3) 66*a*.
cores for. See *Cores*.
covers, method and apparatus for removal of condensed deposits from, P (8) 240*i*.
dressing, of hydroxylapatites, P (7) 204*d*.
flexible, method of making, P (5) 144*d*.
glass, P (2) 41*a*; P (7) 198*h*; P (7) 199*i*.
bonded ceramic ware pressing, and method of making, P (9) 271*g*.
holder actuating mechanism, P (3) 66*a*.
iron alloy for, P (6) 170*h*.
method of protecting surfaces, P (7) 199*d*.
and plunger, alignment structure for, P (10) 299*i*.
liner, for metallic compacts, P (7) 205*a*.
for manufacturing rings or cylinders of ferromagnetic material, P (5) 140*b*.
marks, caused by parting lines of casting molds, (1) 15*c*.
materials, effect on microstructure, shrinkage and mold wall movement of aluminum-4.5% Cu alloy, (2) 44*c*.
metal-casting, P (2) 47*h*.
metal-casting, continuous, mandrel for, P (1) 12*j*.
metal ingot, with protective refractory coating, P (11) 332*i*.
paste, with evaporation grooves, P (11) 336*e*.
paste, for glass articles, P (2) 42*b*.
plaster, apparatus to determine moisture content, (1) 15*b*.
plaster, drying, (4) 98*b*.
porous, pressurized for mold release, P (7) 211*d*.
pressing, crystalline bonded ceramic ware, and method of making, P (8) 242*d*.
and process of coating foamed pattern with refractory filler and silicon-containing binder, P (2) 47*d*.
from refractory compositions, P (5) 134*g*.
resinous shell, method of making, P (9) 270*f*.
sand, and cores, additives to, P (7) 204*c*.
sand-marshalite, behavior during pouring of Bakor-33 melt, calculation analysis, (10) 302*e*.
shell, P (11) 340*a*.
thermally insulated, and method of making, P (5) 136*c*.
wash composition for, P (8) 241*d*.
silica sand, process for making improved, P (2) 47*h*.
wash, P (4) 97*c*.
Molecules, free, structure determination by electron diffraction, (5) 158*b*.
high-temperature, spectroscopy, future developments, B (7) 225*d*.
screw and ring, in amorphous and crystalline chalcogens, S, Se, Te, (7) 221*h*.
Molybdates, laser induced Raman spectra, (6) 186*j*.
of type Ln_2MoO_6, Eu^{3+}-activated, energy transfer in, (10) 321*b*.
Molybdenite, detection of vacancies in, (11) 351*j*.
Molybdenum, bonding diamond to, P (7) 193*g*.
boride, reaction with carbon, (5) 133*b*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
bronzes, synthesis at high pressure, (6) 189*h*.
di-, carbide, single crystals, dislocation etch pits and phase relations in, (9) 281*d*.
disilicide, compaction, (11) 338*c*.
in heat-resistant and oxidation-proof materials, P (1) 12*h*.
solubility of disilicides of transition metals in, (11) 339*h*.
and ZrB_2 alloys, preparation and determination of properties, (2) 45*g*.
ditelluride, high-temperature high-pressure synthesis, P (8) 241*e*.
fluoride, reactivity, (6) 188*g*.
molybdic oxide, producing from molybdate solutions, P (2) 57*b*.
oxidation protection through $MoSi_2$/SnAl protective layer, (10) 296*h*.
oxides, double, (10) 319*f*.
reaction with flowing steam at 1100° to 1700°C, (7) 220*g*.
silicide, heat-resistant and oxidation-proof bodies, P (5) 135*c*.
systems. See *Systems*.
trioxide, coprecipitated with TiO_2, light sensitivity, (4) 114*d*.
trioxide, purifying, P (10) 318*c*.
Montmorillonite, adsorption of *n*-propyl alcohol on, investigation by infrared spectroscopy, (11) 353*g*.
sodium and potassium, crystalline swelling, hysteresis in, (6) 186*j*.
variation in character revealed by optical electron microscope, X-ray diffraction, thermal and dilatometric studies, (1) 33*i*.
Mordenite, kinetics of ion exchange in, (3) 82*f*.
natural, self-diffusion of various cations in, (3) 86*d*.
Morphology, of crystalline phases in spinel-silica system, dependence of microhardness of crystallized glass materials on, (9) 280*c*.
development, of Al_2O_3 crystals grown by vapor deposition, (5) 155*c*.
of oxide films during initial stages of titanium oxidation, (10) 325*d*.
Mortars. acidproofing, preparation and characteristics, (9) 268*i*.
cement, effect of kneading with regard to steam curing, (1) 2*k*.
cement, modified, containing emulsion polymer of 2 methyl α olefin and mixed dialkyl fumerate, P (6) 166*a*.
decay and expansion, influence of efflorescence, (11) 337*a*.
densifier and waterproofing agents for, and method of making, P (5) 125*c*.
effect of mix proportions and method of testing on Poisson's ratio, discussion, (5) 124*j*.
failure, mathematical model, (8) 228*g*.
hardened nonhydraulic lime, calcium silicate hydrates in calcite-quartz interface in, (7) 194*d*.
nonhydraulic lime, hardening, as crystallization process, (3) 62*i*.
piston-type, and pestle, for pulverizing ceramics, (5) 145*h*.
portland cement test, and steam-cured, compressive strengths, (10) 295*a*.
properties, effect of mechanical activation, (4) 92*c*.
properties, influence on shrinkage cracking of masonry walls, (6) 165*c*.
refractory bonding, P (7) 205*b*.
resistance to aggressive solutions, effect of open porosity, (8) 228*i*.
Mosaics, laying, (5) 124*d*.
method and apparatus for making, P (2) 49*a*.
Mullite. See also *Refractories*.
ceramics, dense, gas permeation through, at high temperature, (3) 67*f*.
composition, in chamotte and chamotte brick as function of temperature, (8) 236*h*.
effect on strength and elasticity of whiteware, (6) 175*j*.
formation, reaction mechanism, in system kaolinite-AlF_3, (7) 220*i*.
natural and artificial, electron diffraction study, (1) 27*d*.
particle, sintered, containing α-Al_2O_3, reaction with glass Na_2O·$2SiO_2$, (11) 334*h*.
production, P (5) 135*e*.
stability, at high temperatures, (9) 286*e*.
Muscovite. See also *Mica*.
vibrations of OH ions in, (5) 159*i*.

Neodymium, luminescence and absorption, in germanium glasses, (6) 169*a*.
Nd^{3+}, crystal-field term symbols for, in $CaWO_4$, (10) 319*a*.
energy levels and crystal-field splitting in yttrium oxide, (7) 217*j*.
spectrum, in lanthanide oxide crystals, (11) 357*a*.
$Nd_2O_2S_2$, preparation and properties, (6) 188*a*.
oxalate, thermal decomposition and changes in surface areas of products, (4) 117*j*.
oxide, reaction with sodium borate melts, (6) 188*b*.
systems. See *Systems*.
tritelluride, crystal structure, (6) 184*c*.
trivalent, Raman transitions, in YGaG, (11) 352*c*.
Neptunate, formation, in molten lithium nitrate-sodium nitrate, (4) 115*a*.
Neptunium, dioxide, evaporation behavior, (4) 110*h*.
Neutrons, absorbers, ceramic, for control organisms, (10) 319*e*.
activation, for determination of phosphorus in rocks, (8), 248*c*.
diffraction, data, accurate, general structure factor formalism for interpreting, (9) 282*f*.
data on Ti_2O_3 and V_2O_3, (11) 354*i*.
investigation of CoO single crystals, (8) 255*g*.
study of $Bi_6Si_2O_{13}$, (6) 184*h*.
study of $Fe_{1.3}$ Ge single crystal, (5) 155*c*.
by vibrating quartz crystal, (5) 150*f*.
thermal, pulse propagation in graphite, (9) 268*d*.
Nickel, borides Ni_2B, *o*-Ni_4B_3, and *m*-Ni_4B_3, crystal structure refinements, (7) 216*a*.
carbide, oxidation, (7) 219*b*.
and Cr-Ni alloy, oxidation in CO_2 and CO_2-CO mixtures, (4) 113*g*.
deposition, by displacement reactions, (9) 262*i*.
divalent in $Sr_2(Ni,W)O_6$, magnetic properties and paramagnetic spectra, (10) 312*g*.
epitaxy improved on rock salt substrates due to electron bombardment, (11) 342*i*.
F centers and epitaxial growth, (10) 307*i*.
ferricyanide, thermal decomposition products, ferromagnetic phases in, (10) 321*d*.
ferrite, cation distribution in, (11) 350*d*.
ferrite, formation by hydrothermal method, (9) 286*i*.
films, chemisorption and incorporation of oxygen by, (3) 79*f*.
Nickel (*continued*)
liquid, effect of Zr on surface properties at melt-gas and melt-solid Al_2O_3 interfaces, (2) 44*c*.
metallic, determination in reduced ores and oxides, (8) 248*b*.
(II), coordination equilibria, in alkali borate glasses, (5) 126*i*.
(II), electronic absorption spectrum, in cubic perovskite fluorides, concentration and exchange effects, (7) 217*h*.
Ni^+, trapped in metaphosphate glass at room temperature, (5) 127*f*.
$NiAl_2O_4$, thermodynamic characteristics, (10) 326*a*.
$NiCr_2O_4$, cubic-tetragonal transition and X-ray diffuse scattering in, (3) 79*g*.
$Ni_{1/4}Fe_{2/3}$ coprecipitate, structure and magnetic properties, (3) 87*f*.
$NiMnO_3$, ferromagnetic, preparation, P (8) 245*j*.
Ni_4Mo, alloy, structure defect due to ordering in, electron microscopy of, (4) 109*a*.
Ni_3TeO_6, crystal structure, (1) 27*d*.
and Ni-Zn ferrites, containing excess iron and small amounts of Co_3, temperature variation of initial permeability in, (8) 257*f*.
orthosilicate, cubic, synthesis, (1) 33*b*.
oxide, crystals, electron distribution of ions in, (3) 80*d*.
doped with lithium, thermoelectric power and electrical conductivity, (7) 222*i*.
doped, oxygen chemisorption on, and related conductivity changes, (3) 84*c*.
energies and grooving kinetics of [001] tilt boundaries in, (5) 152*d*.
high purity dense, method for production and product, P (1) 25*c*.
hopping transition probability of polaron holes in, (8) 256*g*.
^{57}Fe Moessbauer effect in, (9) 282*j*.
lattice parameter, as function of pressure, (7) 219*c*.
Li-doped, mechanism of electrical conduction in, (9) 284*b*.
magnetic anisotropy, magnetostriction, and magnetic domain walls in: I, theory; II, experiment, (4) 112*h*.
and SiO_2 equimolar mixture, mineral phases at high pressure and high temperature, (3) 85*g*.
type crystals, antiferromagnetic domain walls, spin configuration in, (4) 116*d*.
role in Al-10% Si composites containing nickel-coated sapphire whiskers, (10) 303*b*.
sintered, effect of disperse alumina inclusions on, (8) 237*e*.
in steel, spectrographic determination using laser as excitation source, (10) 315*e*.
structure, in soda-boric oxide glasses, (5) 129*b*.
surface, chemisorption and incorporation of oxygen at, (9) 280*a*.
systems. See *Systems*.
vanadium selenide, structure and properties, (5) 158*d*.
Niobates, alkali metals and alkaline earth, manufacture, and coating objects with, P (5) 142*d*.
alkali metal and mixed alkali metal-alkaline earth, with filled tetragonal tungsten bronze-like structures, characteristics, (5) 158*e*.
$KNbO_3$-$AgNbO_3$, electrical, X-ray, and thermal expansion, (1) 16*e*.
sodium-strontium-cadmium, dielectric properties and phase transitions, (5) 137*i*.
strontium barium, ferroelectric, electrooptic coefficients of, (3) 71*g*.
Niobium, alloys, creep strength, effect of carbide and boride additions on, (11) 352*a*.
alumina-, graded hot-pressed composites, (7) 202*a*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
carbide, high-temperature heat content, (5) 153*j*.
for high-temperature heaters, (5) 132*e*.
and nitride, fibrous, P (4) 97*e*.
-TaC solid solution, diffuse X-ray scattering by, (9) 280*g*.
carbides, thermal expansion, (5) 134*f*.
carbonitrides, cubic, superconductivity, (8) 257*j*.
cold-worked, containing oxygen and nitrogen, internal friction, (10) 322*f*.
diboride, reaction with carbon, (5) 133*e*.
ESR, in $CaWO_4$, (11) 352*f*.
fluoride, reactivity, (6) 188*g*.
higher oxides, (3) 81*g*.
nitride, and ZrN, superconductive material of, P (10) 311*e*.
$NbLi_3O_4$, structure, refinement, (5) 157*j*.
oxides, lower, (4) 112*c*.
pentafluoride, enthalpies of formation (11) 352*j*.
pentoxide, kinetics of chlorination, (7) 219*b*.
new modification, (3) 83*f*.
α-, nonstoichiometric, thermoelectric power, (5) 140*c*.
systems. See *Systems*.
Nitrates, molten, electrical conductance and glass transition temperature, effect of pressure, (5) 127*h*.
molten, relaxation effects in, (7) 221*d*.
molten alkali, thermal conductivity, (7) 197*b*.
Nitrides, of B and Si, determination of nitrogen undecomposable by acids, (1) 11*e*.
industrial production, (2) 44*f*.
lanthanide, magnetic characteristics, (1) 16*g*.
oxy-, metallic, (1) 30*g*.
powders, of elements Al, B, Si, or Zr, process and apparatus for manufacture, P (2) 47*e*.
rare earth, preparation by reactive arc melting, (7) 214*f*.
reactivity and polymorphism, at high temperatures and pressures, (4) 115*c*.

Nitrides (*continued*)
ternary, of strontium and barium, with rhenium and osmium, preparation and properties, (6) 187*i*.
ultrafine, preparation and characterization, (4) 114*j*.
Nitriles, catalytic process for preparation of, P (5) 148*a*.
Nitrogen, compounds, in silicate minerals and importance in technological behavior of feldspars, (3) 83*g*.
determination in nitrides of B and Si undecomposable by acids, (1) 11*e*.
reaction with spinel in chromium, (10) 296*e*.
systems. See *Systems*.
Nomenclature, cement and concrete, B (7) 223*h*.
to describe structure of vitreous systems and related crystalline compounds, (8) 234*j*.
glass, German-English glossary, B (9) 290*a*.
of interstratified clay minerals, (2) 59*j*.
of minerals, new names, discredited minerals, and changes, B (1) 34*f*.
Murano in book by Neri on glass, (1) 6*j*.
Nose cones. See *Spacecraft*.
Nozzles. See *Refractories; Spacecraft*.
Nuclear materials, science and technology for ceramists, B (4) 120*g*.
Nucleation, crystal, and absorptive properties, observation by mass spectrometric techniques, (8) 255*c*.
heterogeneous, from vapor, impurity effects on, selenium on glass, (5) 127*d*.
rates, homogeneous, in glass-forming system, direct measurements, (5) 127*e*.
theory, test, (7) 222*g*.
of thin-film deposits, (8) 255*j*.

Olefins, dehydrogenating to diolefins in presence of yellow iron oxide catalyst, P (4) 104*j*.
polymerization, using group VIII metal and zinc fluoride or boria on activated alumina as catalyst, P (4) 105*b*.
Opacification. See *Enamels; Glass; Glazes*.
Optical devices, element, electrically conductive, P (7) 208*c*.
Optical materials, concave sections, technique for slicing, (2) 60*a*.
optically active, cutting with synthetic diamond disks, (10) 293*f*.
Optical properties, of amethyst, (3) 84*c*.
of amorphous Ge and Si, (5) 156*e*.
of $Bi_4Ti_3O_{12}$ single crystals, (3) 79*f*.
of ceramic glazes, (10) 306*a*.
constants, of oxide glasses in strong absorption region, (9) 263*j*.
of evaporated silicon oxide films, effect of structure, (10) 308*d*.
of glass, transmission losses of eyepieces used in mine environment, (6) 168*f*.
of iron centers in quartz, (7) 220*f*.
magneto-, of defect centers in alkali halide crystals, (9) 284*j*.
of natural members of potassium-barium feldspar series, (9) 284*d*.
of Nd^{3+}- and Eu^{3+}-doped YVO_4, (4) 113*d*.
nonlinear, of $Ba_2NaNb_5O_{15}$, (11) 355*a*.
observations, on crystalline solids up to 300 kbars, (3) 88*a*.
optic angle, determined conoscopically on spindle stage: I, micrometer ocular method; II, selected rotation method, (9) 276*g,i*.
of photochromic glass, (9) 264*a*.
of $KSr_2Nb_5O_{15}$, (6) 176*i*.
of rare earth doped cadmium fluoride single crystals, (4) 109*b*.
of reactively evaporated chromium oxide films, (3) 84*g*.
reflectance and transmittance, of translucent materials, measurement, (1) 21*f*.
of $RbNiF_3$, transparent, (1) 16*g*.
of ruby laser crystals, (5) 139*d*.
spectra, of chromia alumina, (5) 156*e*.
studies, of anisotropic color centers in germanium-doped quartz, (5) 156*f*.
vibration frequencies of silicates, (1) 33*i*.
of $Zn_xCd_{(1-x)}S$ thin films, (7) 208*c*.
of ZnO single crystals, (3) 84*f*.
Ores, diatomaceous earth, beneficiation, P (7) 215*b*.
rare earth fluocarbonate, pyrohydrolytic attack of, P (7) 215*b*.
sorting, based on differential infrared emission, P (11) 349*c*.
stratiform, composition, as evidence of depositional processes, (4) 104*g*.
Orientation, of Cu_2S formed on single crystal CdS, (2) 50*a*.
crystal grain, determination by comparing sputtered patterns, P (11) 348*b*.
effects, of applied dc field on NaCl films deposited on silica glass, (5) 156*f*.
effects, in mechanical behavior of anisotropic structural materials, B (4) 120*j*.
extreme preferred, of quartz, produced by annealing, (2) 59*f*.
grain, in columns of powder and sintered bodies under effect of intermediate layers, (8) 254*c*.
preferred, increase in lead ferrite by firing, (11) 342*j*.
preferred, in microstructures of eutectics between compounds, (9) 285*g*.
re-, temperature-induced spin, in rare earth orthoferrites, (6) 176*j*.
of single crystal films on polycrystalline substrates, P (6) 178*i*.
of single crystals, binocular microscope for, (1) 23*a*.
Orthosilicates. See *Silicates, ortho-*.

Oscillations, acoustoelectric, with field-dependent period in indium antimonide, (5) 149*e*.
quantum, in ultrasonic attenuation and magnetic susceptibility of InBi, (9) 285*h*.
sustained current, in semiconducting cadmium sulfate at high fields, damping of, (4) 107*j*.
Oscillators, high-efficiency Gunn, epitaxial gallium arsenide for, (10) 307*c*.
quartz-crystal, factors influencing accuracy as thickness monitor for thin film deposition, (10) 307*h*.
ruby-laser-pumped optical parametric, with electrooptic effect tuning, (1) 16*e*.
tunable $LiNbO_3$ optical, with external mirrors, (4) 118*d*.
Osmium, tetraoxide, Coriolis ζ constants and force field for, (6) 184*b*.
Ovens. See *Furnaces; Kilns*.
Oxidation, anodic, conditions, effects on adherence of aluminum enamel to aluminum plate, surface potential diagrams, (8) 229*e*.
anodic, of *n*-type silicon wafer, P (7) 208*f*.
behavior, of black zirconia, (7) 203*g*.
of columbium, observation of markers during, (6) 187*j*.
effect on compressive strength of graphite, (8) 253*h*.
of graphite, anisotropy in, (10) 319*a*.
kinetics, of UO_2-Y_2O_3 solid solutions, (4) 113*e*.
of magnesiowustite single crystals: II, dependence on temperature, oxygen pressure, and crystal composition, (1) 30*b*.
of Mn in CO_2-CO mixtures, (4) 113*f*.
mechanism, of pure uranium in carbon dioxide between 350° and 650°C, (3) 84*j*.
mechanisms, for nickel-aluminum alloys at temperatures between 900° and 1300°C, (6) 187*b*.
of Ni and Cr-Ni alloy, in CO_2 and CO_2-CO mixtures, (4) 113*g*.
nickel carbide, kinetic study, (7) 219*b*.
of praseodymium sesquioxide, (3) 85*a*.
pre-, of stainless steel, P (6) 178*j*.
products, oriented growth, on single crystals of uranium monocarbide, (10) 324*c*.
proof materials, containing molybdenum disilicide, P (1) 12*k*.
protection, of columbium and tantalum with modified silicide coatings, (1) 3*g*.
resistance, of ZrB_2 alloys with $MoSi_2$, (3) 67*c*.
short time, high temperature, of cobalt, (4) 115*d*.
studies, in Cu-Fe system using Moessbauer effect, (10) 324*b*.
of tantalum, at high temperatures, effect of nitrogen, (4) 108*d*.
of tantalum by water vapor, kinetics, (6) 186*g*.
of tellurium, kinetics, (5) 154*i*.
thermal, of vacuum-deposited aluminum films, electron microscopic observation, (11) 352*j*.
of $TiCl_4$ to produce TiO_2, P (2) 57*a*.
of titanium monoxide at high temperatures, (11) 355*e*.
of uranium-based ceramics, behavior of UC and UO_2 contaminated with carbon-containing phases, (10) 324*d*.
of uranium dioxides, (1) 30*i*.
by CO_2 in reactor flux, (3) 84*j*.
containing small additions of other oxides, (5) 156*h*.
particles prepared from U_3O_8 calcined under various conditions, thermogravimetric study, (4) 118*j*.
and structure of U_3O_{8-x} superstructure phase, electron diffraction investigation, (5) 151*h*.
of uranium tetrachloride, (4) 113*h*.
vapor phase, P (2) 57*a*.
vapor phase, of metal halides to form metal oxides of pigmentary size, and apparatus, P (8) 251*j*.
wet, of iron sulfide concentrates catalyzed by nitric acid, (3) 77*g*.
of zirconium, electrochemical model for, (4) 109*g*.
Oxides. See also *Rare earths* and specific types.
alkali, in glasses and silicate raw materials, determination by flame-photometric method, (10) 314*d*.
of alkali earth metals, emission properties, (6) 185*a*.
bodies, compact, manufacture, P (1) 18*h*.
ceramic, vaporization kinetics at temperatures around 2000°C, (1) 33*g*.
ceramic, vaporization under vacuum at high temperatures, (6) 190*e*.
ceramics, abrasion, under influence of surfactants, (7) 210*j*.
compounds, Anderson-Gruneisen parameter δ of, and temperature dependence of bulk modulus, (6) 189*j*.
doped, catalytic activities, (7) 221*b*.
finely divided, production by plasma process, P (4) 105*g*.
inorganic, alternosorption at high temperatures, (5) 183*h*.
layer, produced by vapor deposition in silicon epitaxial systems, (4) 99*b*.
magnetic, crystallizing in rutile structure, (11) 354*j*.
metal, burner for producing, P (6) 182*c*.
complex, of type $AMMo^{IV}{}_3O_8$, (4) 106*j*.
effect on surface grain growth of alumina, (10) 319*h*.
with enlarged pore volume, process for preparation, P (2) 47*j*.
epitaxial growth, (9) 271*j*.
finely divided, P (2) 56*f*.
fusion, P (9) 270*b*.
and metalloid, production, P (5) 148*e*.
mixed, Eu^{3+} fluorescence in, (10) 321*b*.

Oxides metal (*continued*)
mixed, preparation by thermal decomposition of metal salts, P (7) 214*j*.
oxygen activity, methods and apparatus for determining, P (4) 97*a*.
pigmentary, free from falling accretion material, process for production, P (3) 78*d*.
pigmentary, reduction in scale buildup in vapor phase production of, P (10) 318*g*.
preparation by reactive sputtering of carbides, P (11) 345*b*.
surface chemical properties, Lewis acid-base and ion-exchange reactions, (10) 325*f*.
tellurium-containing, of type B_2TeO_6, preparation and X-ray study, (8) 256*d*.
ultrafine, P (5) 136*d*.
metallic, production as homodispersed spherical particles, (6) 173*b*.
metallic, reduction, P (8) 251*h*.
mixes, manufacture, P (2) 56*h*.
mixtures, applicable to electronic ceramics, preparation by wet chemical method, (9) 272*h*.
molten, structure: I, viscosity of GeO_2 and binary germanates containing Li_2O, Na_2O, K_2O, and Rb_2O, (5) 128*d*.
molten, in system $0.25Na_2O \cdot (0.75 - x)GeO_2 \cdot xSiO_2$, structure, (5) 128*f*.
nonfuel, radiation effect on, (7) 201*a*.
periodic table, (2) 39*i*.
pressure precipitation of, (8) 247*b*.
pure, ceramic shapes, strength, (6) 189*c*.
rate of solution in liquid silicates, (9) 286*b*.
-silicon interface, residual stresses at, (5) 158*a*.
sintered, spectral reflectance, (6) 189*a*.
systems. See *Systems*.
thorium-uranium, production, P (7) 205*a*.
of Ti, Zr, Fe, Al, and Si, manufacture, P (4) 105*c*.
of type MO, enthalpies of solution in vanadium (V) oxide, (6) 186*c*.
Oxygen, activity, of molten metals, metal oxides, and slags, methods and apparatus for determining, P (4) 97*a*.
adsorption, on sintered plutonium dioxide, (5) 131*d*.
atomic and molecular, attack on pyrolytic and isotropic graphite at high temperatures, (7) 200*f*.
chemisorption and incorporation, by nickel films, (3) 79*f*.
chemisorption and incorporation, at nickel surface, (9) 280*a*.
deficiency, effect on magnetic properties of copper ferrite, (10) 319*j*.
electric field diffusion, at 900° to 1000°C in UO_2, (9) 281*i*.
EPR on ZnO and ultraviolet irradiated MgO, (7) 217*g*.
for heating glass furnaces, (7) 197*a*.
lance, refractory coated, P (3) 69*d*.
self-diffusion, in uranium oxide, (7) 220*g*.
solubility, in molten carbonates, (11) 356*c*.
systems. See *Systems*.

Packaging. See also *Shipping*.
brick, ways of rationalizing, (4) 95*h*.
Fair and Labeling Act, (10) 327*j*.
siliceous pigments, process, P (9) 279*c*.
system, P (5) 148*g*.
Palladium, oxide, phase relations with rare earth sesquioxides in air, (6) 187*e*.
oxide, process of producing, P (3) 78*c*.
$PdAs_{2-x}Sb_x$, $Pd_{1-m}Pt_mAs_2$, $Pd_{1-m}Pt_mSb_2$, $Pd_{1-m}Au_mSb_2$, solid solubility and structural properties, (7) 221*j*.
Pallets. See *Materials handling*.
Panels. See *Building materials; Glass*.
Paper, making from mica flakes subjected to hot aqua regia, P (9) 274*a*.
Paramagnetic materials. See *Magnetic materials*.
Particles. See also *Colloids*.
abrasive, coarse, evaluation of shape, (9) 261*f*.
analyzing apparatus, with means for observing scanning aperture, P (9) 277*g*.
counting device, with fluid conducting means breaking up particle clusters, P (9) 277*h*.
eliminator, wide-band, (11) 343*b*.
fine, atlas, B (4) 121*c*.
grit, apparatus for continuous recovery, separation, and cleaning, P (9) 263*e*.
high rate zeolitic molecular sieve, method of preparing, P (2) 56*i*.
measuring and counting system, P (9) 275*g*.
microcrystalline sintered bauxite abrasive, P (9) 261*g*.
second phase, diffusion-controlled growth in lithium-silicate glass, (1) 5*c*.
shape, effect on sintering kinetics of glass, (11) 333*i*.
change during creep in MgO, (1) 29*f*.
sensitivity, of initial sintering equations, (11) 356*b*.
silica-alumina catalyst, heat treating, P (8) 251*d*.
size, analyzer, on-line, (3) 76*b*.
analyzer, photometric, with moving light flux, (1) 22*e*.
below 45 microns of porcelain enamel slips, composite method for determination (10) 296*d*.
of clay, reducing, P (2) 57*c*.
colloidal, apparatus for measurement, P (2) 55*c*.
control by viscosity, P (4) 103*g*.
determination, centrifuge, (9) 275*j*.
determination, dispersion of clay for, (1) 21*d*.
determination, of Indian clays, (6) 182*f*.
determination, in Practical Emulsions, Vol. I, B (9) 290*b*.

Particles, size (*continued*)
effect on discoloration of barium titanate powder, (10) 319*g*.
of ferrites, relations with porosity and chipping resistance, (9) 286*f*.
in high purity barium titanate ceramics relations with properties, (9) 272*h*.
in Materials Characterization, B (8) 259*b*.
measurement, (5) 146*i*.
measurement, problems, (11) 346*j*.
measurement, reporting of results, (10) 315*e*.
of plaster, effect on strength of hardened suspensions, (10) 294*c*.
reduction, (9) 275*g*.
reduction, of UO_3, oxidation-reduction procedure for, P (1) 13*d*.
relation with strength of porcelain, (10) 306*d*.
and shape of UO_2, importance in sintering behavior, (7) 202*c*.
size analysis, freeze-drying of disaggregating silts and clays for, (2) 54*d*.
Leschonski modification of Sartorious sedimentation balance for, (1) 21*d*.
shape, and compositional mode, combined, of grains in altered sandstones, (5) 144*i*.
of zircon using Coulter counter, (10) 315*i*.
size distribution, determination by Coulter Counter, (6) 180*f*.
effect on bodies for glazed roofing tile, (1) 15*e*.
frequency, of beach and river sands, dynamic processes and statistical parameters compared for, (1) 28*e*.
measured by simple instrument, (4) 103*g*.
measurement with Bahco type classifier, (1) 21*e*.
measurement in 200 to 1200 A range, (1) 22*j*.
method of calculating from sedimentation balance data, (1) 21*j*.
by micromerograph analysis, (2) 54*f*.
of powders, recorder for analyzing, P (7) 213*b*.
of UO_2 prepared from variously calcined U_3O_8 investigated by sedimentation analysis, (1) 28*b*.
of yttrium vanadate phosphors as function of preparation parameters, (5) 139*e*.
sizing, of clay materials, (10) 301*i*.
sizing, by forward scattering lobe, (9) 276*j*.
solid, capillary adhesion forces between, with intermediate liquid layer at contact: II, effect of degree of wetting, (9) 279*j*.
solid, dispersed in fluid carrier, method and apparatus for continuous classification, P (2) 53*c*.
spherical, apparatus for production, P (5) 144*e*.
spherical, preparation from metallic oxides, (6) 173*b*.
study apparatus, automatic control structure for, P (9) 277*e*.
electronic, P (11) 347*g*.
with self-clearing scanner element, P (11) 348*c*.
surface area, gas permeability of powder bed, new method of calibration, (4) 92*e*.
Pellets, fuel, BeO-UO_2-B, fabrication, (2) 44*i*.
sintered metallic oxide catalyst, process for preparation, P (1) 25*i*.
Periclase, high-density, from $Mg(OH)_2$, (10) 302*d*.
Perlite, -chamotte insulating products, production, (9) 268*a*.
trans-Carpathian, physicochemical properties, (6) 165*i*.
Permeability. See also *Porosity*.
gas, of porous materials from refractory compounds, (5) 132*a*.
gas, of refractory concrete, (10) 303*e*.
initial, in Ni and Ni-Zn ferrites containing excess iron and small amounts of Co, temperature variation of, (8) 257*f*.
magnetic, of sulfur dioxide, (4) 112*h*.
techniques for characterizing fine powders, (1) 22*d*.
Permittivity. See *Dielectrics, constant*.
Perovskites, $CaCrO_3$, band antiferromagnetism and, (11) 341*h*.
ferroelectrics, chemical shifts of ^{207}Pb in, (5) 137*i*.
fields, in portions of systems BaO-$LuTaO_4$-B_2O_3, BaO-$YTaO_4$-B_2O_3, and BaO-$LaTaO_4$-B_2O_3, (1) 30*j*.
idealized ordered cubic, superlattice Madelung energy, (6) 189*d*.
magnetic, $BiMnO_3$ and $BiCrO_3$, (3) 83*d*.
oxides, interband Faraday rotation in, (6) 186*c*.
structure, compounds, relation between crystal parameter and anion-cation distances in, (6) 188*h*.
structures, Madelung energy: II, tetragonal case, (6) 187*c*.
-type compounds, $Ba(B_{0.5}Ta_{0.5})O_3$, possible new laser host materials, (5) 137*g*.
Petrography, of carbonate transgressive-regressive sequence, (1) 31*b*.
luminescence, for visibility of carbonate rock structures, (5) 146*b*.
in studying leaching of cement paste in concrete, (1) 2*i*.
Petrology, of lower Devonian bentonites from Gaspe P. Q., (5) 148*c*.
pH. See *Hydrogen ion concentration*.
Phase, analysis, of powdered materials, electromechanical principles of, (10) 314*g*.
boundaries, geometry, (8) 253*j*.
change, first-order magnetic, in UO_2, (8) 258*a*.
composition, of SiC products with silica bond as function of environment, (9) 268*f*.
conversions, in mixtures of alumina and copper oxides, (9) 283*h*.
crystalline, in glass systems Na_2O-B_2O_3-ZrO_2-SiO_2, (3) 63*h*.
high-pressure, of $Ga_{2-x}Fe_xO_3$, (11) 350*c*.
micro-, liquid-liquid immiscible, in alkali borosilicate melts, rearrangement kinetics of, (5) 128*g*.

Phase (*continued*)
quartz-like, formation and recrystallization during crystallization of glasses in SiO_2-Al_2O_3-MgO system, (6) 185*j*.
relations, in dimolybdenum carbide single crystals, (9) 281*d*.
of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics with Ba or Sr substitutions, (4) 99*d*.
between palladium oxide and rare earth sesquioxides in air, (6) 187*e*.
in rare earth sesquioxides at high pressure, (5) 156*c*.
separation, of glasses in system Na_2O-TiO_2-SiO_2, (6) 168*h*.
separation, in glasses: I, internal structure of sodium borosilicate glasses, (6) 168*j*; II, structure of sodium silicate glasses, (7) 197*b*.
studies, of $Pb_{1-x}Sn_xTe$ alloys, (4) 114*c*.
Th_2N_2O and ThO_2, equilibrated with different nitrogen (plus oxygen) atmospheres, ranges of composition, (3) 85*f*.
transformation, of praseodymium sesquioxide, (3) 85*a*.
transformations, of $CaCO_3$, effect of impurities, (4) 108*b*.
transition, 120°, in $BaTiO_3$ single crystals, effect of Fe_2O_3, (5) 137*i*.
in $C_3H_5(SeO_3)_2$, (3) 85*b*.
ferroelectric-to antiferroelectric, thermodynamic relations with compositions, (11) 343*b*.
high-pressure induced, in ZrO_2, (11) 353*j*.
in $PbZrO_3$, (4) 117*d*.
of sodium-strontium-cadmium niobates, (5) 137*i*.
of titanium dioxide under various pressures, (3) 85*e*.
under high pressure: VI, mineral phases of equimolar mixture of NiO and SiO_2 at high pressure and high temperature, (3) 85*g*.
V_2O_4, V_2O_3 and Clausius-Clapeyron equation, (4) 106*g*.
in ZrO_2 and rare-earth oxides, X-ray and spectrographic investigations, (1) 34*b*.
Phase diagrams. See *Equilibrium studies*.
Phase rule. See *Equilibrium studies*.
Phonons, zero-, lines, and coupling, of ZnSe:Mn and CdS:Mn, (11) 358*b*.
zero-, transition at M' and R' centers in alkali halides, (11) 358*c*.
Phosphates. See also *Glass* and specific types.
boro-, vitreous, structure, (5) 128*i*.
Ca, Li, Na, and Zn, pure molten, application of rigid sphere model to, (2) 57*d*.
in ceramics and related materials, method for rapid estimation, (5) 145*e*.
minerals, liberation and concentration by attrition grinding and sizing, (1) 25*a*.
monoaluminum, solution, for bonding refractories, (7) 200*g*.
ores, reactivity with acids, (2) 56*j*.
poly-, linear chain, analysis of unperturbed dimensions of, (3) 79*b*.
systems. See *Systems*.
Phosphides, alkali metal, preparation and methylation, (1) 12*a*.
boron, in Ni-B-P system, phase stability regions, (4) 114*c*.
Ga, Al, or In, single crystal production, P (7) 210*h*.
preparation, properties, and crystal chemistry, B (4) 119*i*.
uranium carbide-plutonium, as reactor fuel, P (4) 97*j*.
Phosphorescence, of trivalent terbium ion in barium crown glass, (1) 6*g*.
Phosphoric acid, concentration, effect on properties of finely milled refractory materials, (9) 267*g*.
reaction with forms of alumina, (9) 268*e*.
and titanium dioxide, reaction products, binding properties, (1) 11*a*.
wet process, reacting with calcium carbonate for calcium polyphosphate, P (11) 350*a*.
Phosphors, alkali compensated rare earth doped zinc or cadmium borate, P (7) 208*e*.
Sb^{3+} and Mn^{2+} activated calcium halophosphate, from flux-grown apatites, (7) 208*a*.
blue electroluminescent, and production, P (9) 272*i*.
blue-white europium activated aluminosilicate, P (4) 99*e*.
$Ca(PO_3)_2$:Sn:Mn glass, sensitized fluorescence in, (11) 356*e*.
coated, with radioisotope dispersed therein, and method of preparation, P (5) 140*h*.
europium and bismuth activated yttrium vanadate, P (4) 99*j*.
europium and calcium or manganese activated yttrium vanadate, P (4) 99*j*.
for flying-spot cathode-ray tubes for color TV—yellow-emitting $Y_3Al_5O_{12}$-Ce^{3+}, (2) 49*j*.
green electroluminescent zinc sulfide, P (6) 177*b*.
green luminescing, for color television, P (11) 343*f*.
green-yellow emitting europium aluminosilicate, P (4) 100*b*.
halophosphate, method of processing, P (2) 51*c*.
halophosphate, preparation, P (7) 210*a*.
synthesis, using calcium chlorspodiosite, P (7) 210*c*.
treatment process, P (8) 244*d*.
impurity activated (Zn,Cd) (S,Se,Te), emission spectra: I, copper activated, (7) 207*j*.
Mg_3SiO_4:Tb,Li luminescence in, (7) 207*d*.
rare earth activated, based on yttrium orthovanadate and related compounds, (3) 85*h*.
rare earth activated indium borate cathodoluminescent, P (10) 311*a*.
red emitting Al_2O_3, (7) 208*a*.

Phosphors (*continued*)
with rare earths, optical and EPR spectra, (8) 243*f*.
silicon carbide, doped with group IIIA elements and/or nitrogen, preparation and photoluminescence, (7) 207*h*.
slurry, method of salvaging in spin coating process for making phosphor screens for cathode-ray tubes, P (4) 100*h*.
strontium magnesium orthophosphate, P (11) 345*g*.
vacancy compensated calcium neodymium vanadate, P (6) 178*j*.
vanadate, method of preparing, P (3) 73*e*.
yttrium oxide, preparation, P (5) 142*d*.
yttrium-thallium oxide, europium activated, (5) 152*h*.
yttrium vanadate, europium-activated, method of preparing, P (8) 245*c*.
particle size distribution as function of preparation parameters, (5) 139*e*.
process for preparing, P (4) 101*a*.
YVO_4:Eu, empirical studies on absorption and emission, (4) 109*g*.
ZnS:Cu, electroluminescent, blue and green luminescence centers, (11) 350*j*.
ZnS:Cu,Al, thermoluminescence and electroluminescence, (3) 88*c*.
Phosphorus, compounds, effect on quality of plaster, (10) 295*b*.
determination, in rocks and minerals by activation analysis, (3) 77*f*.
diffusion in silicon, and making of *pn* junction semiconductor detectors, (7) 210*f*.
diffusion, in Na_2O-P_2O_5-SiO_2 liquids, (5) 151*a*.
inorganic bound, analytical determination in presence of alkylated phosphorus, (5) 149*e*.
pentafluoride, heat of formation, (3) 81*i*.
pentafluoride, structure, electron diffraction study, (4) 109*h*.
phosphotungstate heterpolyanion blues, quantitative electrochemical formation, (5) 157*a*.
in rocks, determination by neutron activation, (8) 248*c*.
separation, with ammonium molybdate, and successive determination, (9) 286*a*.
systems. See *Systems*.
tetra-, triselenide, synthesis, preliminary infrared, nuclear magnetic resonance, and Raman studies, (4) 117*a*.
trioxide, descriptive chemistry, (5) 150*h*.
Photoconductive effect, and (or) **Photoconductivity,** in CdS, (1) 16*c*.
of CdS crystals, (5) 156*j*.
intrinsic, in alkali halides, (8) 254*d*.
of irradiated doped vitreous silica, (7) 197*e*.
in lead oxide, quantum efficiency of, (11) 355*h*.
in PbS films, *p*-type single-crystal, (4) 114*f*.
material, improving photoconducting characteristics of layers of, P (10) 310*f*.
photoconductive layer, P (10) 311*e*.
photoconductive target, with arsenic-selenium layers of different densities on cryolite layer, P (10) 311*f*.
photosensitivity in monocrystalline PbS films, (10) 307*i*.
properties, of ZnO modified by hydrogen sulfide, (5) 150*i*.
in sputtered tantalum oxide films, (3) 72*a*.
of zinc oxide, study by electrodeposition method, (5) 158*f*.
of ZnTe crystals, (5) 156*j*.
Photoconductors. See *Conductors, electrical, photo-*.
Photoelectric cells. See *Cells*.
Photoelectric effect, enhancement of electrical conductivity in dust-laden [BaO] gases, (9) 285*a*.
Photography, camera, electron diffraction, design and operation for study of small crystalline regions, (1) 20*j*.
camera, X-ray diffraction, employing two curved crystal transmission type monochromators, P (7) 213*e*.
images or designs, applying to ceramic objects and improved photographic emulsion for production of multicolor images or designs on objects, P (5) 137*b*.
micro-, precision camera for, (5) 146*a*.
Photometers. See also *Spectrophotometers*.
flame-, for determination of alkali oxides in glasses and silicate raw materials, (10) 314*d*.
Photometry, counting of seeds and stones in glass, (10) 298*g*.
flame, for determination of dissociation energies of alkaline-earth oxides, (6) 185*i*.
Photomicrography, time-lapse, for hydration studies, (10) 294*h*.
Photovoltaic effect, series array, comprising *pn* and *np* cells, P (6) 178*c*.
Physical chemistry. See *Chemistry*.
Physical properties, of alloys WC-TaC-Co and WC-NbC-Co, (7) 203*d*.
of beryllium compounds, (11) 357*e*.
of blended and ball-milled Al-Al_2O_3 alloys, (2) 45*e*.
of glass, bibliography, B (8) 258*i*.
of solid and liquid vanadium pentoxide, (11) 357*e*.
thermo-, research literature retrieval guide, B (5) 161*f*.
Physicochemical properties, of alumina cement, (8) 238*b*.
of borosilicate glasses, (6) 169*d*.
for characterization and control of Dorset ball clays, (1) 31*c*.
of Cu_2Se and Cu_2Te, (4) 114*g*.
of crystal hydrates of sulfates of rare-earth elements in terbium subgroup, (9) 285*c*.
of glasses in system B_2O_3-SiO_2, (6) 168*a*.
of trans-Carpathian perlite, (6) 165*i*.

Physicomechanical properties, of hardened cement steamed under accelerated conditions, influence of water/cement ratio on, (6) 165*d*.
Piezobirefringence. See *Refraction, birefringence.*
Piezoelectricity, behavior, of X-cut quartz shock loaded at 79°K, (3) 85*h*.
building units, P (9) 274*d*.
ceramic articles, of lead zirconate titanate containing Mn and W oxides, P (6) 178*c*.
ceramic composition, P (2) 52*b*.
ceramic composition, iridium and chromium doped lead zirconate titanate, P (6) 177*f*.
ceramics, (9) 272*e*.
lead zirconate-titanate-stannate, containing thorium and iridium, P (1) 18*f*.
lead zirconate titanate, with chromium and thorium additives, P (7) 209*i*.
of lead zirconate-titanate systems, (5) 130*h*.
-electroluminescent display device containing nonlinear resistance layer, P (7) 209*i*.
layers, making by flame spraying, P (9) 274*b*.
piezoresistance, in *n*-type CdTe, (9) 285*d*.
piezoresistance, in *n*- and *p*-type aluminum antimonide, (11) 355*b*.
piezoresistive properties, of reduced strontium titanate, (8) 256*a*.
polarons, cyclotron resonance of, (8) 252*h*.
properties, of $Pb(Mg_{1/3}Nb_{1/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics with Ba or Sr substitutions, (4) 99*d*.
vibrators and systems, embodying same for converting mechanical vibration into electric energy, P (6) 178*d*.
Pigments. See also *Color; Stains.*
aluminosilicate, P (10) 317*g*.
black, for blackening of radiation detectors, P (4) 93*a*.
calcined hydrophilic talc, P (5) 148*j*.
composite, preparing, P (7) 214*h*.
high grade, produced from titanium hydroxide production, P (5) 148*e*.
material, ceramic, containing zinc oxide, manufacture, P (7) 214*e*.
pink, conditions for forming and structure, (8) 250*c*.
silica, apparatus for production, P (9) 279*b*.
silica, and production, P (6) 183*d*.
silica-coated lead chromate, P (6) 183*d*.
siliceous, packaging process, P (9) 279*c*.
siliceous, preparing slurries of, P (7) 214*i*.
titanium dioxide, corrosion-inhibiting, P (1) 25*j*.
nacreous, P (11) 349*b*.
and preparation, P (1) 26*b*.
process for production in controlled calcination of basic titanium sulfate, P (4) 105*g*.
-silica, P (8) 251*j*.
wet silica, mechanical modification, for reduction of free water retentivity of, P (9) 279*d*.
zinc oxide, molybdated, and method for preparation, P (3) 78*f*.
Pipe. See also *Tile.*
asbestos cement, apparatus for forming, P (9) 275*f*.
apparatus for joining, P (8) 241*f*.
method and apparatus for forming an end profile on, P (8) 240*i*.
method and apparatus for introducing flocculating agent to slurry to control thickness of sheet used in winding to form, P (5) 135*h*.
method and apparatus for manufacturing, P (5) 135*i*.
clay, P (5) 131*a*; P (7) 199*j*.
clay, vitrified, or conduit, P (7) 190*i*.
coupling, flexible, P (10) 300*i*.
drain-, glazed and unglazed ceramic, hydraulic resistance of, (8) 236*f*.
glass, joint construction for, P (6) 170*i*.
lined, joined, method of making, P (9) 265*f*.
reinforced plastic, for domestic water piping systems, (5) 130*j*.
hole cutting apparatus for, P (5) 131*c*.
joint, P (5) 131*b*.
joint, monolithic, (3) 74*h*.
sewer, characteristics and manufacturing for prefabricated building, (9) 270*h*.
couplings, P (6) 172*c*.
glazes for, (10) 301*j*.
Plasma, chemical reactions in, (10) 312*j*.
electromagnetic induction in, (10) 312*c*.
engineering, (10) 312*h*.
jet, in chemical processing, (8) 249*h*.
jet, and cooled surface, simultaneous transfer of heat and material between, (7) 221*h*.
low-temperature, chemical processes in, (10) 312*b*.
low-temperature, problems in investigation of elementary processes in, (10) 312*i*.
Plaster of Paris. See *Gypsum; Plasters.*
Plasters, for application on metal, P (5) 125*g*.
building, production in rotary drum dryers, (5) 125*h*.
building, treatment of phosphogypsum to form, and effect of phosphorus compounds on quality of, (10) 296*b*.
dry, preparing by calcination and compression, P (4) 92*e*.
effect of sonic boom on, (11) 331*i*.
fire-resistant cementitious composition, P (6) 165*j*.
gypsum, high strength, P (7) 194*f*.
gypsum, setting, effects of organic acids and salts on: II, tartrates, (10) 294*e*.
hardened, properties, effect of preparation methods, (9) 261*j*.
hardened suspensions, effect of granulometry on strength, (10) 294*c*.
hardness, determination by drilling strength, (10) 294*j*.
industrial, composition, (10) 294*c*.
molds. See *Molds.*
Plasters (*continued*)
of Paris, match plate, for machine molding, (8) 238*c*.
plastering wall surfaces, and joint sealing compound used, P (8) 229*b*.
rehydration, (6) 164*f*.
slurry, ionic concentration in suspending liquid during hydration of, (10) 295*g*.
Plasticity, of bone china, effect of flocculants, (2) 48*j*.
of ceramic materials, determination by penetration method, (1) 22*a*.
of clay minerals, (1) 22*g*.
of clays, enhancing process, P (5) 148*d*.
of earth materials, effects of soap, detergent and water softener, (1) 24*j*.
of magnetite measured by hardness as function of temperature, (7) 220*b*.
measurement, (9) 276*c*.
super-, of ZrO_2, (1) 32*j*.
Plastics. See also *Resins.*
ceramic-, composite material, method of making, P (4) 93*a*.
-coated boiling and frying utensils, comparative testing of service behavior with enameled ware, (7) 195*a*.
porous, for lightweight refractory materials, (7) 202*f*.
reinforced, quality mass markets open for, (10) 298*c*.
surfaces, sterilizing, P (1) 236*b*.
thermo-, forming, steatite body for, (2) 48*i*.
thermo-, with high viscosity at decomposition temperature, P (11) 341*a*.
vs. glass, (11) 334*f*.
Plating. See *Coatings.*
Platinum, mixed cyanide-halide complexes, vibrational spectra, force constants, and bonding in, (4) 119*b*.
oxide, process of producing, P (3) 78*c*.
$PtP_{2-x}As_x$, $PtP_{2-x}Sb_x$, $PtP_{2-x}Bi_x$, $PtAs_{2-x}Sb_x$, $PtAs_{2-x}Bi_x$, $PtSb_{2-x}Bi_x$, and $Pt_{1-m}Sb_2$, solid solubility and structural properties, (7) 221*j*.
Plutonium, carbonitride, P (5) 135*g*.
dioxide, adsorption of oxygen on, (5) 131*d*.
chemical etchant for, (1) 20*j*.
sintering behavior, (8) 257*i*.
distribution, in molten $(U,Pu)O_2$ fuel materials, (7) 202*e*.
monophosphide and monosulfide, thermal conductivity and heat capacity, (8) 258*a*.
nitride, phosphide, and sulfide, chemical aspects as nuclear reactor fuel, (7) 200*c*.
oxide, melting, P (1) 13*f*.
sulfides and phosphides, preparation, (4) 114*a*.
systems. See *Systems.*
uranium-, monocarbide ceramics, (11) 338*a*.
Poisson's ratio, and microindentation hardness and elasticity of glasses, (7) 196*f*.
Polarization, effects in insulating films on silicon, (10) 307*j*.
effects in rooftop ruby laser, (5) 139*i*.
ferroelectric, of $Bi_4Ti_3O_{12}$ single crystals, (3) 79*f*.
of green copper luminescence in hexagonal ZnS single crystal, (3) 85*a*.
-optical studies of destruction of transparent dielectrics by laser beams, (10) 308*b*.
phenomena, of phosphosilicate glass films on silicon, (7) 207*f*.
of photo- and radiophotoluminescence of silver-activated borate glass, (1) 6*j*.
in potassium chloride crystals, (6) 187*h*.
reversal, high efficiency, of magnetoelastic waves in YIG by optical-contact bonding of YAG disks, (3) 71*b*.
of stimulated radiation from neodymium ions in glass base, (10) 298*b*.
third order nonlinear, in quartz, optical mixing due to, (10) 324*c*.
transient, in insulating CdS, (9) 288*e*.
vibronic, in electronic spectra of gillespite, (6) 190*f*.
of (Zn,Cd)S, effect of Cu_2O on, (11) 352*a*.
Polarography, of complexes formed by Zn, Mn, Ni, and Co with 1,2 diaminocyclohexanetetraacetic acid, (5) 145*i*.
of zirconium, (5) 145*i*.
Polyelectrolytes. See *Electrolytes.*
Polishing. See also *Abrasives; Diamonds; Lapping.*
chemical, of semiconductor substrate, P (1) 17*c*.
chemical, for thinning of sintered UO_2 to electron transparency, (5) 134*i*.
GaAs single crystals, by reaction with gaseous atmosphere incompletely saturated with Ga, P (10) 310*f*.
glass, composition, P (9) 265*d*.
composition containing dissolved Zr and ZrO_2, (9) 265*c*.
composition containing inorganic barium salt, P (9) 265*d*.
with slurry, P (10) 301*c*.
jet, controlled, of specimens for transmission electron microscopy, (1) 20*h*.
ruby laser rods, with clean diamond, (6) 163*i*.
surface, of semiconductor, and reagent for, P (8) 245*g*.
Polishing apparatus. See also *Abrasives; Diamonds.*
conforming, for aspheric surfaces of revolution, P (1) 20*f*.
disks, apparatus for testing, (10) 293*g*.
pad, for glass, P (3) 65*i*.
Polymerization, olefin, using group VIII metal and zinc fluoride or boria on activated alumina as catalyst, P (4) 105*b*.
partial, of resin coated wound glass fiber package, P (8) 235*b*.
Polymers, amorphous fluorocarbon, for lamination of glass, and method of making, P (6) 170*i*.
Polymers (*continued*)
articles, tetrafluoroethylene, with readily cementable surface containing glass particles, P (5) 130*g*.
in materials characterization, B (8) 259*a*.
nature and properties, in materials, B (11) 358*d*.
vitreous inorganic, structural characterization by thermal studies, (1) 7*a*.
Polymorphism, of $BaTa_2O_6$, (1) 31*e*.
of cordierite: I, crystal structure of low cordierite, (2) 59*a*.
of dicalcium silicate, (2) 59*d*.
in IV-VI compounds induced by high pressure and thin-film epitaxial growth, (5) 156*j*.
of $LiMO_2$ compounds, (7) 220*c*.
of $LiPO_4$, $LiAsO_4$, and $LiVO_4$, (5) 154*b*.
of nitrides at high temperatures and pressures, (4) 115*c*.
of tantalum pentoxide, effect of oxide additions, (9) 281*a*.
of tricalcium silicate and its solid solutions, (1) 31*g*.
Polymorphs, NiAs-type, of $MnCr_2S_4$, $FeCr_2S_4$, and $CoCr_2S_4$, magnetic properties, (8) 255*c*.
SiC, low-temperature far infrared spectra, (8) 254*g*.
Porcelain, art. See *Art and artware.*
articles, bonded, and method of forming, P (5) 137*c*.
bath, perineal, P (7) 206*i*.
bodies, elasto-plastic-viscous properties, (5) 136*i*.
high strength, alumina in (11) 341*d*.
high strength, based on quartz or cristobalite, (3) 70*b*.
interaction with glaze, determination of degree, (5) 136*j*.
casing bead construction, P (3) 70*g*.
cone 11 dry process, (11) 341*e*.
cordierite, vitrified, compositions for, (3) 69*i*.
cristobalite in structure of, (3) 69*j*.
decorated, behavior under conditions of machine washing, (1) 15*a*.
dental. See *Dental ceramics.*
electrical. See also *Insulators, electrical.*
quantitative phase analysis, (8) 242*f*.
thermal diffusion, (5) 136*i*.
electrotechnical, use of electron microscope for studies of, (2) 48*b*.
fracture propagation rate, (1) 15*f*.
grain size and strength, relation between, (10) 306*d*.
industry, drying and firing in, (7) 206*a*.
invention, experimental notes by Johann Friedrich Boettger, (4) 98*c*.
-like articles, manufacturing from blast furnace slag, P (7) 206*h*.
porcelaneous dense ceramic material with high resistance to changes in temperature and high mechanical strength, and method of producing, P (7) 206*i*.
properties, effect of fine silica, (2) 48*i*.
semi-, body, conventional, optimum conditions for casting of, (9) 271*a*.
structure, during stages of production, (2) 48*j*.
surfaces, cleaning process, P (8) 229*j*.
triaxial, microstructure, (10) 306*a*.
Pores, growth, during final stage of sintering of ZnO, (10) 325*i*.
in materials characterization, B (8) 259*b*.
molecular size, in beryllium oxide powders, (7) 219*k*.
in sintered ferrite, (9) 272*e*.
size, fine, in refractories, apparatus for determining, (10) 313*d*.
Porosity. See also *Permeability; Pores.*
of ceramic materials, (10) 313*g*.
dependence of sound velocity and Poisson's ratio for polycrystalline MgO determined by resonant sphere method, (9) 285*d*.
dependence, of Young's and shear moduli of polycrystalline Y_2O_3, (10) 324*b*.
determination apparatus, specimen mounting device for, P (2) 55*g*.
effect on electrolysis in MHD electrodes, (10) 302*h*.
effect on strength and elasticity of whiteware, (6) 175*j*.
-elastic modulus relation, (10) 319*j*.
of ferrites, relations with grain size and chipping resistance, (9) 286*f*.
interrelation with hardness and modulus of elasticity in gypsum systems, (7) 194*h*.
of long shaft insulator bodies, study by measuring velocity of ultrasonic waves with direct reading device, (2) 49*a*.
open, effect on resistance of mortars and concretes to aggressive solutions, (8) 228*i*.
porosimetry, mercury, application to refractory materials, (1) 11*a*.
of refractories, nondestructive determination, (9) 267*j*.
sealing, of fiber faceplates by yttrium resinate, P (7) 199*a*.
in synthetic dolomites, (9) 285*c*.
ultra- and micro-, of quartz crystals, (4) 118*c*.
Portland cement. See *Cement, portland.*
Porous materials. See also *Cements; Concretes; Insulation, thermal.*
bodies, from alumina microspheres, (10) 303*f*.
bodies, texture and flow determination in, (10) 317*g*.
correlation between hydrodynamic and electrical coefficients of tortuosity for, (5) 148*f*.
Potash feldspar. See *Feldspar.*

Potassium. See also *Alkalis.*
-barium feldspar series, mineralogy: I, determination of optical properties of natural members; II, studies on hydrothermally synthesized members, (9) 284*d*.
bromide, crystals, V centers in, (8) 258*b*.
disks, unusual absorption bands of infrared spectra of α- and γ-FeOOH in, (9) 287*a*.
doped with NaBr, second-order quadrupole shifts of ^{81}Br in, (9) 286*i*.
pure, production of *F* centers in, by ultraviolet irradiation, (11) 355*f*.
sidebands of infrared U center in, (8) 257*a*.
vacancy-production efficiencies in, at low temperatures, (8) 258*b*.
chloride, additively colored, formation of aggregate centers in, (8) 253*i*.
additively colored, M_A centers in, (11) 354*g*.
aqueous, activity coefficients measured with potassium-sensitive glass electrode, (4) 105*i*.
crystals, polarization in, (6) 187*h*.
crystals, reaction with hydrogen crystals, doped with nitrite and nitrate, (3) 85*i*.
diffusion of chlorine ion in, (8) 253*a*.
measuring technique for grain boundary mobility, (6) 189*j*.
minimum-energy configuration of Li^+ in, (10) 323*a*.
modulated F-center absorption in, (10) 323*a*.
paraelectric resonance of OH^- dipoles in, (10) 324*f*.
room-temperature colorability, effect of simultaneous bleaching and gamma radiation, (11) 352*c*.
determination, in important materials in silicate technology, effect of sulfate, oxalate, and perchlorate ions on, (7) 212*j*.
determination, method and apparatus, P (11) 347*j*.
hexafluoroaluminates, complex formation with sodium cryolite, (9) 280*e*.
iodide, intrinsic luminescence at 10°K, (10) 322*a*.
lead pyrogermanate, structure, (5) 158*c*.
metatitanate, enthalpy of formation, (9) 282*c*.
nitrate, electrical properties, (5) 138*c*.
fused, electrical conductivity, (3) 80*b*.
melting properties under pressure, (5) 154*g*.
oxide, effect on formation of lithium metasilicate crystallites in photosensitive opal glass, (1) 5*h*.
-SiO_2 solutions, activities calculation, (1) 5*a*.
sublimation, study by mathematical design of experiment, (3) 62*j*.
permanganate, flash heating and kinetic spectroscopy, (10) 321*e*.
$KAlSiO_4$ and $KAlSi_2O_6$, dehydrated, high-temperature heat contents and entropies, (6) 186*h*.
$KAlSi_2O_6$, melting relations, effect of pressures up to 40 kbars, (5) 154*h*.
$K_2Cl_2 \cdot BaCl_2$, enthalpy of formation, (10) 321*a*.
$KMnF_3$, magnetic properties: III, nuclear and electron spin resonance, (9) 284*g*.
$K_4Nb_6O_{17}$, growth and properties, (10) 321*e*.
$KAgI_2$, high ionic conductivity, (3) 85*b*.
$KSr_2Nb_5O_{15}$, ferroelectric and optical properties, (6) 176*i*.
KTN, electrooptic effect in, (4) 109*f*.
recovery, from Great Salt Lake brine, process, P (1) 25*j*.
systems. See *Systems.*
tantalate, ESR of Gd^{3+} and Eu^{2+} in, (10) 320*e*.
Faraday rotation in, (11) 352*i*.
-niobate crystals, characterization by electro-optic measurements, (1) 26*g*.
and KTN, interband Faraday rotation in, (6) 186*c*.
trivanadate, crystal structure, (6) 184*h*.
Potters, and roof-tile makers in South Italy, Sicily, and Greece, B (4) 121*d*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Whiteware.*
bodies, structure, (9) 271*f*.
Canadian sports series, made in Scotland, (5) 124*a*.
decoration. See *Decoration.*
Delftware, made at Glasgow pottery of Delftfield, (5) 124*b*.
manufacture, P (2) 49*c*.
manufacture, method and machine, P (9) 271*h*.
school, Kandern in Black Forest, under Horst Kerstan, (4) 91*i*.
shaping apparatus, in revolving ceramic-mass-containing molds, P (9) 271*e*.
slab, (3) 61*j*.
Pottery industry, Indian, (1) 2*b*.
of opportunity, (2) 60*f*.
unit labor cost measurement in decorating department of, (3) 70*d*.
Potterymaking apparatus and equipment. See also *Dryers; Kiln furniture; Kilns; Materials handling; Molds.*
continuous forming, automatic greenware replacing device for, P (4) 98*f*.
Powder metallurgy, fundamentals, methods, and applications: Vol. I, new methods for consolidation of metal powders; Vol. II, vibratory compacting, principles and methods, B (3) 89*f,g*.
Powders. See also *Granular materials.*
apparatus for densifying, P (7) 214*h*.
apparatus for uniform feeding into plasma spray gun, P (9) 263*a*.
BeO, molecular size pores in, (7) 219*h*.
brittle inorganic polycrystalline, preparation by shock-wave technique, P (5) 148*h*.
ceramic, P (2) 56*f*.
ceramic, aggregating action of semimacromolecular surfactants on, (11) 350*e*.
Powders (*continued*)
columns, grain orientation in, under effect of intermediate layers, (8) 254*c*.
compacting method, P (1) 20*e*.
compressibility, (1) 27*e*.
fine, characterization by permeability techniques, (1) 22*d*.
fractionating, new technique, (1) 22*g*.
nitride, of elements Al, B, Si, or Zr, process and apparatus for manufacture, P (2) 47*e*.
oxide, mixed, detection of thermal reaction in by electrical resistance measurements, (11) 351*i*.
pressure molding, method, P (1) 18*g*.
silica, alumina, Cr_2O_3, highly dispersed, preparation for electron microscopy, (11) 347*a*.
spherical, of refractory compounds, preparation and properties, (5) 133*f*.
two-component systems, vibration compaction, (1) 23*e*.
vibration packing, (1) 23*c*.
spray-dried, for production of wall tile, (8) 242*c*.
surface areas, measurement by krypton gas adsorption method, construction and operation of apparatus, (1) 21*g*.
Power. See also *Energy.*
to circulate gas-solids suspensions, (2) 53*d*.
thermoelectric, of NiO doped with lithium, (7) 222*i*.
Pozzolans. See also *Cements; Mortars.*
artificial, specific surface, pozzolanic activity in relation to: I, measurement from water adsorption isotherms; II, relation between activity and surface, (5) 125*f*.
calcined shale as, at Bhakra, (1) 2*j*.
laboratory investigation for large scale use and manufacture of, (3) 62*d*.
pozzolanic properties of pulverized fuel ashes, specifically fly ashes as determined by crushing strength tests on lime mortars, (10) 294*d,f*.
Praseodymium, divalent, paramagnetic resonance in CaF_2, (10) 324*g*.
fluoride, enthalpy of formation, (9) 282*c*.
oxides, magnetic susceptibility, (5) 138*j*; (6) 187*d*.
oxides, reaction in oxygen atmosphere—kinetic studies, (11) 354*c*.
$PrTaO_4$ and $LaTaO_4$, new structure type, (5) 150*g*.
sesquioxide, phase transformation, oxidation, and hydration, (3) 85*a*.
systems. See *Systems.*
Precipitates, calcium sulfate, kinetics of formation, colloidal phenomena in, (10) 294*b*.
metastable, effect on electrical properties of Li_2O-SiO_2 glass, (9) 263*f*.
superparamagnetic magnesioferrite, from dilute solutions of iron in MgO, (5) 140*b*.
Precipitation, of beryllium from ores, P (11) 349*d*.
particle, by space charge in tubular flow, (3) 76*c*.
pressure, of oxides, (8) 247*b*.
studies, in Cu-Fe system using Moessbauer effect, (10) 324*b*.
Precipitators, electrostatic control circuit, P (7) 211*b*.
Presses, brick, attachment for, P (11) 337*f*.
brick, with density control, P (5) 134*f*.
for compacting electrically conductive compositions, P (8) 247*h*.
composite laminated resilient means for, P (10) 312*b*.
for drawing ceramic and other materials in plastic state, P (6) 179*g*.
filter, P (1) 20*a*; P (6) 179*d*.
arrangement for automatically displacing plates and frames in, P (3) 75*c*.
filter cloth fitting apparatus in, P (5) 144*g*.
filter plate coupling apparatus in, P (5) 144*a*.
German, (10) 312*f*.
mechanized heavy duty, P (10) 312*e*.
friction and screw, for manufacture of ceramic articles, P (4) 102*b*.
high pressure isostatic, P (7) 211*c*.
Pressing, apparatus, for testing at temperatures up to 1800°C, instrumental modifications for, (4) 102*i*.
cold-, of BeO, studies, (4) 96*h*.
die-, submicron size alumina powder, problems, (3) 74*j*.
Dinas bodies on hydraulic presses, (9) 267*j*.
flanged glass articles, P (9) 265*j*.
glass, laboratory investigation, (8) 233*c*.
hot-, of alumina, new treatment of final densification, (1) 29*c*.
of BeO derived from hydroxide, (5) 134*b*.
of BeO and ZrO_2, (2) 44*c*.
of BN, sintering behavior, (7) 203*i*.
ceramics for high strength, precision, (3) 74*j*.
of decomposable compounds to form oxide-containing products, P (7) 204*h*.
for dispersion and breakage of coated particle consolidated in graphite matrix, (11) 337*j*.
of magnesia, (10) 303*f*.
of magnesia aggregates, (1) 29*c*.
magnesia refractories, (10) 303*f*.
for nuclear applications of BeO—process, product, and properties, (4) 96*c*.
reactive, of clays and hydroxides, kinetics, (9) 270*i*.
semiautomatic, (2) 53*f*.
thermoelectric elements, (1) 16*f*.
of titanium diboride with binding metals, (8) 237*f*.
of UO_2, (2) 44*d*.
vacuum, of magnesium aluminate spinel, (7) 222*j*.
of zirconium diboride with binder metals, effects of chromium and nickel addition, (11) 338*d*.
Pressing (*continued*)
isostatic, for ceramics, (1) 19*f*.
equipment, selection, (10) 312*i*.
high-temperature, of articles, P (4) 102*c*.
of large refractory blocks, (8) 238*a*.
scientific and technological problems in, (10) 311*i*.
preliminary, of bent glass laminated assemblies, P (2) 42*c*.
quasi-isostatic, experiments, (10) 312*c*.
refinements, for critical compacting requirements, (3) 74*i*.
semidry, face brick, discussion, (10) 301*f*.
system for deep ceramic containers, P (7) 211*g*.
of two-component cermet materials, relations in, (11) 339*b*.
Pressure, case, deep-ocean, design using ceramic tube, (1) 15*c*.
compaction, dependence on ratio of compacting surface area and area of friction surface between powder and die walls, (2) 54*b*.
decomposition, of thorium mononitride, (11) 351*g*.
dependence, of resistance of VO_2, (5) 157*f*.
dissociation, in system ytterbium-ytterbium dihydride, comparison with calcium-calcium dihydride, (8) 253*b*.
distribution in simple press, measurement by quartz glass powder, (11) 346*f*.
effect, on electrical conductance and glass-transition temperature of molten nitrates, (5) 127*h*.
on formation of compounds in Y_2O_3-Al_2O_3 system, (7) 217*d*.
on melting points of sodium halides, (10) 320*b*.
on strength of heat-cured high-strength concrete, (8) 228*j*.
equilibrium nitrogen, of UN, (2) 58*g*.
high, effect on compressibilities of seven crystals having NaCl or CsCl structure, (7) 217*c*.
effect on crystallization, densification and crystallization anomaly of B_2O_3, (1) 28*g*.
effect on ion exchange in feldspars, (7) 218*i*.
effect on lattice parameters of Al_2O_3, (6) 185*g*.
effect on lattice parameters of Cr_2O_3 and α-Fe_2O_3, (10) 319*h*.
effect on lattice parameters of diamond, graphite, and boron nitride, (7) 217*b*.
effect on lattice parameters of oxides and sulfides, (7) 219*c*.
equation of state of polymer liquids and glasses, (5) 127*j*.
and high temperature apparatus, P (2) 55*d*; P (5) 144*b*; P (8) 247*d*.
-high temperature studies: II, direct preparation of β- and γ-$LiBO_2$, (3) 81*a*.
model for melting-curve maxima at, (11) 354*f*.
research, tetrahedral anvil apparatus for, (9) 277*i*.
structural properties of europium metal and monoxide at, (9) 284*i*.
very, modern research, (2) 59*f*.
X-ray diffraction studies of CdTe at, (8) 258*c*.
hydrostatic, effect on permittivity and Curie point of single crystal barium titanate, (4) 117*g*.
and nonhydrostatic up to 55 kbars and 140°C, for permanent densification of B_2O_3 glass, (1) 6*e*.
to 20 Kbars, effects on dielectric constant of rubidium chloride, (11) 352*f*.
loss, due to elastic energy for viscoelastic capillary flow, (11) 355*d*.
oxygen, equilibrium, over nonstoichiometric uranium oxides UO_{2+x} and U_3O_{8-z} at higher temperatures, (4) 109*j*.
pressurizing, liquid, apparatus, P (5) 144*d*.
sensitivity, of Au-$KTaO_3$ Schottky barrier diodes, (5) 157*f*.
swelling, determination, of expansive clays, (1) 24*i*.
300 kbars, effect on crystalline solids measured by X-ray diffraction and optical observations, (3) 88*d*.
of uranium, over uranium-uranium dioxide system, (3) 70*j*.
vapor. See *Vapor pressure.*
Probes, three-point, evaluation of point material for, (11) 346*j*.
Propane, for firing salt-glazed Alsatian stoneware, (3) 70*h*.
Proustite, synthetic, crystal for optical mixing, (4) 117*b*.
Pug mills. See *Mills.*
Pulpstones. See *Abrasives.*
Pulverizers. See *Crushing and grinding apparatus.*
Pulverizing. See *Crushing and grinding.*
Pulverulent materials. See *Powders.*
Pumps, for abrasive slurry handling, (2) 53*e*.
Purification, chemical, of Izumiyama pottery stone, and effects, (9) 278*f*.
diamond, P (2) 35*h*.
by differential migration, (6) 181*c*.
electromagnetic and electrostatic, of raw materials, (9) 275*g*.
of fluosilicic acid solution by distillation with phosphoric acid solution, P (9) 279*f*.
of GaAs, P (4) 101*a*.
of materials in single crystal production, P (9) 274*g*.
of molybdenum trioxide, P (10) 318*c*.
of TiO_2 pigment with organic sequestering agents, P (10) 318*e*.
of tungsten hexachloride, (4) 114*d*.
ultra-, of group IVa metals, (5) 248*j*.
of zinc and cadmium chalcogenides, P (8) 245*f*.
Pycnometer, micro-, for determination of specific gravity of minerals, (1) 22*b*.

Pyrochlor, Canadian, chemical composition and crystalline structure, (11) 350*f*.
Pyrometers; Pyrometry. See *Temperature measuring instruments*.
Pyrometric cones, high temperature, (9) 276*h*.
Pyroxenes, calcic, intracrystalline chemical variation in, (10) 322*i*.

Quality control, automatic logging, data storage for experimentation and, (2) 53*i*.
during production of electroceramic products, (2) 50*e*.
by electrical, radiographic, and ultrasonic techniques for glass industry, (3) 76*a*.
and inspection, in enamel shop, (9) 263*c*.
inspection, of rocket motor by infrared method, (9) 276*a*.
policy, in brick and tile industry, (3) 66*h*.
system design, and evaluation, process studies, (2) 54*j*.
ultrasonic inspection system, using television techniques, (7) 212*f*.
Quartz. See also *Glass; Refractories; Silicon, dioxide*.
alpha, observation of leaky elastic surface waves, (5) 151*c*.
alpha-, synthetic, infrared studies of variation H-bonded OH in, (5) 153*f*.
amethyst, postulated structures causing optical color-center bands in, (7) 220*d*.
and anomalies, surface structure in α-β inversion, (6) 189*g*.
comminution, influence of pH on, (4) 101*i*.
crystal, synthetic, internal friction, method of testing by two different frequencies of infrared, P (2) 51*h*.
crystals, ultra- and micro[illegible]ity, (4) 118*e*.
cultured, dislocations in, [illegible]*i*.
depression, with ascorbic acid, [illegible]5) 143*g*.
differential thermal curves, evaluation with high temperature cell, (5) 145*i*.
disks, method for joining to Kovar tubes under vacuum by inductive heating, (2) 53*j*.
elastic surface waves in, at 316 Mhz, (4) 109*a*.
fused, for porous refractory shapes, (1) 11*j*.
geochemistry of gallium and aluminum in, (7) 217*h*.
germanium-doped, EPR study of impurity-related color centers in, (5) 152*g*.
germanium-doped, optical studies of anisotropic color centers in, (5) 156*f*.
ground, surface layer, mechanical and thermal activation, (5) 148*b*.
irradiated,—atomic hydrogen, electron spin resonance, (3) 80*d*.
magmatic, as indicator of kaolinization of granite, (4) 104*j*.
matched fracture faces, etching of, (4) 110*e*.
natural, rhombohedral faces, gradient of growth pyramids and flow of mother liquor on, (8) 254*b*.
neutron irradiated, scattering and absorption of light by, (8) 256*i*.
optical mixing due to third order nonlinear polarization in, (10) 324*c*.
optical and paramagnetic properties of iron centers in, (7) 220*f*.
orientation, extreme preferred, produced by annealing, (2) 59*f*.
plastic deformation and fracture, at atmospheric pressure, (4) 114*g*.
pseudomorphous replacement of apophyllite by, (10) 324*c*.
quantitative estimation, (10) 315*a*.
quartziferous materials, thermoluminescent characterization of, P (9) 277*i*.
replaced by barite in manufacture of white earthenware, (9) 271*e*.
rf-sputtered, processing and evaluation, (10) 308*d*.
sands, of fine grain size, methods for determining specific surface of, (3) 75*g*.
sawed and grooved by diamond tools, (6) 176*d*.
spheres, dissolution kinetics in sodium silicate melt, correction, (7) 196*f*.
stimulated Brillouin scattering in, temperature dependence of, (11) 357*c*.
surface, activation for adsorption of anionic polyelectrolytes, (3) 78*h*.
surface states, comparison with cristobalite and silicic acid, (10) 319*j*.
synthetic, crystal growth using lithium ions in nutrient solution, P (10) 318*i*.
growth, P (3) 74*h*.
with nonstructural impurity, electrolysis, (1) 28*f*.
systems. See *Systems*.
thermodynamics of phase transformation between 848° and 1953°K, (7) 222*h*.
thermoluminescence in, (3) 88*f*.
thermoluminescence dosimeters, properties, (2) 59*d*.
trace elements in, as indicators of provenance, (4) 118*b*.
undulatory range and crystal size, (1) 33*c*.
in whiteware and porcelain bodies, (4) 98*f*.
X-cut, shock loaded at 79°K, piezoelectric and mechanical behavior, (3) 85*h*.
Quartzite, elastic precursor decay in, for cylindrical and spherical flow, (9) 281*h*.
replaced by silica sand briquets and pellets, (7) 203*h*.
two, transformation behavior, (1) 33*h*.
Quenching, radiation, of radioluminescence of ZnS phosphors, (3) 85*f*.
Quicklime. See *Lime*.
Quinoline, hydroxy-, substituted 8-, for use as colorimetric reagents in detection of metal ions, (1) 23*b*.

Radiation, action on inorganic glasses, (10) 328*b*.
blackbody, high temperature, evaluation as working standard of spectral radiance, (9) 276*e*.
coherent, apparatus for generating in semiconductor body, P (3) 72*f*.
continuous induced, from LaF_3–Nd^{3+} laser at room temperature, (10) 306*i*.
damage, in ZnSe, annealing of, (11) 350*i*.
-damage effects in borated graphite, (4) 114*f*.
effect, on BeO, nonfuel oxides, and UO_2, (7) 201*a*.
in non-crystalline solids, B (10) 328*e*.
in semiconducting glasses, (8) 233*h*.
fluorescent, for inspecting transparent articles for defects, P (10) 300*f*.
gamma, simultaneous with optical bleaching, effect on room-temperature colorability of KCl, (11) 352*b*.
infrared, transmission from flames by CO_2, (9) 278*b*.
millimeter wave, from InSb, (5) 154*j*.
radiative transfer in spectral lines, (10) 324*c*.
sensitive apparatus, for inspecting bottom wall of hollow transparent containers, P (3) 66*b*.
-sensitive means for detecting flaws in radiation transmissive materials, P (5) 147*c*.
stimulated, from Nd^{3+}-activated crystal and glass lasers, high-temperature spectroscopy, (10) 321*h*.
thermal, of metals, semiconductors, ceramics, partly transparent bodies, and films, B (4) 121*i*.
ultraviolet, cause of stress in glass, (8) 234*g*.
Radioactive materials. See also *Isotopes; Wastes*.
source, high silica matrix, and method of preparation, P (4) 100*c*.
Radioactive tracers. See also *Isotopes*.
and applications in glassmaking, (11) 333*d*.
for determination of flow patterns in glass tank, (11) 333*d*.
studies with samarium via instrumental neutron-activation analyses, (11) 335*b*.
Radioactivity. See *Isotopes*.
Radiochemistry, of orthophosphate adsorption on ternary borate glasses, (8) 233*j*.
Radiography, auto-, and radiometric methods for determining optimal homogenization time for refractory raw material mixture in Eirich mixer, (9) 268*d*.
at energies below 400 kvp, factors in, (7) 212*g*.
film and filmless, for nondestructive testing of thin materials and electronic assemblies, (7) 212*d*.
micro-, for determining densities of pyrolytic-carbon coatings, (1) 22*c*.
micro-, projection, and application to study of ceramics and refractories, (6) 173*c*.
precision and magnification, of miniature electronic components, (7) 212*j*.
Radioisotopes. See *Isotopes*.
Radiometer, direct reading wave length independent, using pyroelectric crystal detector, P (11) 343*b*.
radiometric and autoradiographic methods for determining optimal homogenization time for refractory raw material mixture in Eirich mixer, (9) 268*d*.
Radomes, construction, P (8) 245*d*.
fused silica, precision casting, (4) 96*h*.
research, to improve ceramic properties and reduce sintering temperatures, (3) 67*i*.
Raman effect, in cadmium sulfide, (9) 286*a*.
in zinc oxide, (8) 256*j*.
Rare earths (lanthanons). See also specific types.
activated phosphors, based on yttrium orthovanadate and related compounds, (3) 85*h*.
-alkaline earth oxide compounds, (5) 155*f*.
-boron-carbon, high temperature studies: III, LnB_2C_2 and ternary phase diagram, (6) 186*i*.
compounds, $K_{0.1}Ln_{0.1}Ta_2O_6$, with $PbNb_2O_6$ structure, (5) 150*g*.
compounds, low-lying crystal-field spectra, (11) 354*e*.
elements, oxides, reaction with chromium, (10) 324*h*.
oxychlorides, thermodynamic investigation, (10) 326*b*.
stability of complex compounds of, (10) 325*b*.
-fluorine materials, process for treating, P (3) 74*d*.
-group Vb compounds, simple low-contamination preparative technique, (2) 46*a*.
FeO_3 and CoO_3, preparation, (6) 181*d*.
isomorphous orthosilicates and orthogermanates, (7) 219*a*.
$Ln_2O_2S_2$, oxysulfides, crystal structure, (1) 27*e*.
metal oxalate hydrates, thermogravimetry, (4) 118*j*.
metals [Y, La, Ce, Pr, and Gd], dicarbides, hydrolysis of, (10) 321*j*.
orthoaluminates, antiferromagnetic, thermal properties, (11) 356*i*.
orthoferrites, hydrothermal growth, (11) 353*c*.
orthoferrites, temperature-induced spin reorientation in, hysteresis loop studies, (6) 176*j*.
oxides, crystal chemistry, (6) 184*c*.
hemispherical spectral emittance, (5) 153*i*.
reduction and volatilization, (1) 31*f*.
nonstoichiometric, semiconduction in, (5) 139*h*.
systems. See *Systems*.
X-ray and spectrographic investigations of phase transitions in, (1) 34*b*.
oxybromides, crystal structure, (4) 107*e*.
paramagnetic acoustic resonance and relaxation, in CaF_2, (11) 355*f*.
sesquioxides, crystalline transformations at high temperatures, (1) 27*g*.
effect of additions of lime on cubic-monoclinic transformation in, (7) 217*a*.

Rare earths, sequioxides (*continued*)
phase relations at high pressure, (5) 156*e*.
phase relations with palladium oxide in air, (6) 187*e*.
suboxides, P (8) 258*g*.
sulfates, basic, structural study, (4) 116*b*.
trivalent, in inorganic phosphor systems, (8) 243*f*.
trivalent 4*f*, separation from molten fluoride compositions with UF_3, P (7) 205*e*.
vanadate crystals, type RVO_4, flux growth, (10) 321*h*.
Raw materials. See *Materials; Sands; Rocks*.
Reactivity, alkali, of dolomitic limestone aggregate, (4) 91*j*.
of barium carbonate, in combating scumming in structural clay products, (1) 10*e*.
of $CaCO_3$, in system CaO–SiO_2–$CaCO_3$–H_2O under hydrothermal conditions, (6) 165*f*.
of nitrides at high temperatures and pressures, (4) 115*c*.
of sand-gravel aggregates, field and laboratory studies, (6) 164*g*.
of transition metal fluorides: I, higher fluorides of chromium, molybdenum, and tungsten; II, uranium hexafluoride; III, higher fluorides of vanadium, niobium, and tantalum, (6) 188*g*.
Reactors, concepts, advanced, use of BeO in, (2) 46*b*.
control rods, selection of materials for, (10) 319*e*.
high-temperature flame, (6) 182*a*.
nuclear, fuel elements for, P (1) 12*f*; P (3) 68*d*; P (7) 204*c*, 205*f*.
fuel pellet for, P (3) 68*e*.
graphite brick structures for, P (1) 12*g*.
graphite structures in, P (7) 204*d*.
preparation of mixed carbides for use in, P (7) 205*h*.
shielding with heavy aggregates, (7) 203*h*.
use of BeO in, (2) 46*c*.
water hydrolysis, for making alumina, P (8) 252*a*.
Reagents. See also specific types.
1-(o-carboxyphenyl)-3-hydroxy-3-phenyltriazene, for direct gravimetric determination of titanium(IV), (5) 145*g*.
controlled introduction in magnesite ore concentration process, P (8) 250*i*.
surface active, effect on comminution of quartz and calcite, (1) 21*g*.
Rebinder effects, in MgO, (8) 256*a*.
Recrystallization. See *Crystallization*.
Rectifiers, high voltage, with controlled current leakage, P (1) 18*d*.
high voltage semiconductor, with sloping surface across barrier edge, P (11) 343*h*.
selenium midget, method of producing, P (1) 18*h*.
selenium, with high blocking voltage, production, P (5) 142*f*.
semiconductor, mechanics and potential applications, (1) 16*h*.
semiconductor controlled, P (4) 100*a*.
Recuperators. See *Furnaces; Kilns; Refractories*.
Reduction, of barium titanate, and effect on electrical properties, (6) 176*h*.
carbon monoxide, of wustite, promoters for, (3) 77*j*.
galvanostatic cathodic, of fused sodium chloride on graphite, Ni, Fe, or liquid aluminum at 800° to 950°C, (7) 217*g*.
initial stages, of magnetite in hydrogen, kinetics, (9) 283*b*.
to MnO the MnO_2 of manganese ore, P (7) 215*d*.
of metallic oxides, P (8) 251*h*.
of Ni and Co ions in sapphire, spectroscopy, (7) 221*f*.
of synthesized hercynite with hydrogen, (10) 321*i*.
of ZnO, by carbon monoxide in presence of strontium oxide, (4) 115*e*.
Reflectance. See *Reflection*.
Reflection, calcium fluoride, angle-of-incidence dependence of, (8) 252*b*.
characteristics, reststrahlen, of amorphous silica, (7) 221*f*.
electroreflectance in III-V semiconductors, (10) 320*i*.
infrared, of SiO, dependence on layer thickness, (10) 319*d*.
patterns, Kikuchi-like, obtained with scanning electron microscope, (8) 248*j*.
spectral, of sintered oxides, (6) 189*a*.
studies, of epitaxial $Ga_xIn_{1-x}As$, (11) 356*d*.
thickness corrections for silicon dioxide films on silicon, (11) 356*d*.
ultrasonic, for material evaluation, (7) 212*b*.
ultraviolet, of α- and β-SiC, (11) 357*j*.
Reflectivity. See *Reflection*.
Reflectors, optically round mechanically ovate, with radially stepped sections, P (11) 336*e*.
Refraction, birefringence, of $BaTiO_3$ and WO_3 crystals, (3) 79*b*.
birefringence, examination of plastic deformation of diamond, (1) 26*j*.
birefringence and optical band gap of ZnS polytypes, (9) 285*a*.
light, in elastically stressed plate and shadow patterns of circular holes and linear cracks, (9) 283*i*.
Refractive index, of glasses, relation with density, resulting from annealing compared with corresponding relation resulting from compression, (9) 264*f*.
of liquids and glasses, variation in strong ruby laser fields, (10) 327*e*.
of MgO, variation with pressure to 7 kbars, (11) 358*d*.
of thin silica films, determination by simple immersion method, (11) 347*i*.
Refractivity. See *Refraction*.

Refractories. See also *Aircraft ceramics; Insulation, thermal: Kiln furniture; Silicon, carbide.*
acid- and wear-resistant, physicochemical conditions for production from blast furnace slags, (8) 239*e*.
alumina, P (3) 68*g*.
-based, P (10) 305*c*.
grade reactive, P (5) 136*b*.
high, P (5) 135*d*.
high, with Cr_2O_3 and TiO_2, P (7) 204*f*.
high, creep characteristics, (6) 172*e*.
high, fused-cast, (7) 201*a*.
high, high temperature strength, (7) 202*a*.
super, (9) 267*h*.
aluminosilicate, brick, creep and refractoriness under load at high temperatures, (10) 302*h*.
chemical determination of glassy phases in, (5) 131*j*.
microstructure, and corrosion under service conditions, (8) 238*j*, 239*a*.
properties, effect of boron nitride addition, (9) 267*e*.
articles, casting, P (8) 241*h*.
articles, ducted, method of making, P (1) 13*e*.
B-Al-N materials, preparation, (8) 237*a*.
basic. See also *Refractories, chrome-magnesite; specific kinds.*
P (4) 97*b*.
application in electric furnace roofs, (9) 266*h*.
behavior in roof of open-hearth furnaces, (7) 200*b,c*.
carbon-bearing, slag attack on, (1) 12*e*.
composition, P (10) 305*a*.
direct-bonded, manufacture and properties, (8) 238*b*.
direct-bonded, performance in open-hearth furnace, (9) 268*b*.
direct-bonded, so-called, chromite-containing, structure of, (7) 203*j*.
direct-bonded, use tests in open-hearth furnace roof, (9) 269*e*.
of dolomite, chemical and physical characteristics, (1) 11*e*.
fused, P (10) 304*b*.
in glass melting furnace, (8) 240*h*.
in glass tank regenerators, (1) 5*b*.
high-fired, behavior in steel furnaces, (7) 200*e*.
high hot strength in, (8) 237*e*.
hot bending strength, test conditions for measuring, (8) 239*j*.
investigation by torsional method, (8) 238*e*.
for LD oxygen converters, (10) 303*j*.
manufacture, P (8) 240*h*.
methods and machines for production, P (1) 12*h*.
or neutral, P (2) 48*c*; P (7) 204*g*.
or neutral brick for industrial furnaces, P (5) 136*a*.
with periclase-based stabilized solid solution, P (1) 14*a*.
in reverberatory furnace for refining of tin, (10) 304*g*.
Simultansinter, under different service conditions, (8) 239*i*.
for steel converter, thermal conductivity, (7) 203*i*.
tar-bonded dolomite and magnesite, American and German methods of testing for steel converters, (8) 236*h*.
thermal conductivity measurements on, (7) 204*a*.
torsional test as aid in determining quality, (9) 269*f*.
basic block, P (2) 46*f*.
basic brick, P (2) 47*i*.
changes in oxygen process steel converters, (7) 200*j*.
chemically bonded, dependence of hot and cold strength on temperature-time history, (7) 201*e*.
direct-bonded, use in open-hearth roofs, (6) 173*b*.
maturing during use, (4) 96*f*.
tar-bonded, tar-impregnated, (11) 339*d*.
basic fireclay and high aluminous, manufacture, P (3) 68*i*.
for basic oxygen process as related to types of wear, properties, (3) 67*e*.
behavior, in contact with natural gas flames, (7) 200*g*.
binder for $MoSi_2$, P (11) 339*j*.
blast-furnace, (9) 267*g*.
blast-furnace, linings. See *Refractories, linings.*
blocks, large, isostatic pressing of, (8) 238*a*.
blocks, support for, P (2) 48*c*.
bodies, for repairing Dinas and chamotte structures in industrial furnaces, (9) 268*f*.
bonding, with monoaluminum phosphate solution, (7) 200*g*.
bonding composition, P (3) 69*d*.
brick. See also *acid, basic* and specific types under *Refractories.*
P (1) 14*g*; P (7) 205*c*; P (11) 340*j*.
apparatus for handling and impregnating, P (4) 96*j*.
blocks, and masses of burned MgO, tar-bonded, P (2) 48*c*.
furnace lining, P (2) 48*d*.
hydration resistant, process for making, P (5) 135*j*.
and manufacture, P (5) 136*a*.
silica, study by DTA, (11) 339*e*.
briquets, vanadium carbide, P (1) 14*b*.
carbide, articles, induction sintering, P (2) 47*h*.
boride, or silicide, method for producing, P (2) 47*j*.
fatigue tests for, (10) 314*e*.
carbon, with hard carbide, boride, or silicide outer region, process of making, P (2) 47*g*.

Refractories, carbon (*continued*)
microscopical assessment, (3) 67*a*.
physical properties, technology, and production, (6) 173*i*.
shaped article, coating with polycarbon fluoride, P (11) 340*i*.
cased, blocks, P (10) 305*c*.
cast silicate, thermophysical processes of shaping, (2) 46*a*.
castable, based on spodumene, (4) 96*a*.
high alumina, P (11) 340*d*.
thermal conductivity in relation to bulk density, (3) 68*f*.
casting, continuous, apparatus with improved nozzle composition, P (3) 68*a*.
casting and extrusion, (6) 172*i*.
cellular material, and method of making, P (1) 12*i*.
cement. See also *Refractories, blast-furnace.*
cement, with siliceous filler, (8) 240*d*.
chamotte, composition of mullite in, as function of temperature, (8) 236*k*.
chamotte, thermochemical analysis, rapid, (11) 347*b*.
chrome-magnesite. See also *Refractories, magnesite-chromite.*
chrome-magnesite, development using Indian chrome ores, (5) 131*g*.
chromite, P (4) 97*c*.
clays. See *Clays.*
coatings. See *Coatings.*
composition, P (1) 14*i*.
batch consists of size-graded fused cast refractory particles, P (8) 241*d*.
high temperature, P (2) 47*b*.
resistant to slag erosion, P (8) 241*c*.
ZrO_2 based, and formation of cores and molds from, P (5) 134*g*.
compound powders, study of densification by electrical conductivity method, (8) 240*a*.
compounds, densification, P (1) 12*a*.
experience in producing under industrial conditions, (2) 44*f*.
and method of production, P (2) 48*e*.
study of rate of vaporization, vapor pressure, compositional discontinuity, and thermodynamic properties, up to 3000°C, (1) 32*g*.
concrete. See *Concrete.*
construction, P (11) 341*a*.
in continuous steel casting process, (9) 269*h*.
cores, for annular pellet nuclear fuel elements, (4) 96*c*.
corrosion, by blast furnace slags, (8) 237*b*.
in boundary layer between glass or slag, (7) 202*g*.
influence of formation and properties of heavy glasses, (7) 196*a*.
by steelmaking slags, (10) 302*g*.
corrosion tests, crucible method for, (10) 302*g*.
crucible method, experimental conditions for, including temperature distribution and cooling velocity of furnace, (10) 302*j*.
crucible method, with reference to slag quantity and effect of heating rate, (10) 302*g*.
crucible method for standardization of, (10) 304*d*.
methods for, (10) 303*i*.
temperature distribution and cooling rates in furnace, (10) 304*g*.
corundum mixes, composition of aluminophosphate binder hardening products in, (7) 200*i*.
creep tests on, (10) 303*h*.
crucible, Al_2O_3-SiO_2 system, corrosion by molten aluminum, (11) 350*j*.
carbon, coated with beta silicon carbide, P (8) 240*c*.
induction furnace, P (20) 304*f*.
for molten fused silica, P (2) 46*j*.
cupola, corrosion, with added Cr_2O_3 and dissolution of Cr in iron, (9) 269*d*.
corrosion by molten pig iron, (9) 269*d*.
review, (10) 302*j*.
deformation, determination in regard to temperature and load, and high temperature properties, (9) 276*g*.
delivery apparatus, method of making and apparatus produced, P (3) 69*c*.
dense, technology of making, (9) 269*d*.
diffusion treated with nitrate promoter, P (7) 205*f*.
Dinas, bodies, pressing on hydraulic presses, (9) 267*j*.
quality, effect of mineralizers, (9) 268*i*.
use in upper zone of checkers of blast furnace stoves, (9) 269*i*.
wear in Bessemer converters, (9) 269*j*.
discharge brick, for casting ladles and intermediate containers, P (7) 204*a*.
dolomite blocks, tar- and pitch-bonded, for oxygen blown converter linings, (9) 267*d*.
fired, use in rotary kiln lining for calcining dolomite ore, (10) 304*a*.
stabilized, use tests in uptake of open-hearth furnace, (9) 269*f*.
study by high temperature X-ray diffraction, (10) 303*d*.
tarred, for converters, B (10) 329*e*.
dolomite-magnesite, tarred, properties, effect of tar viscosity, (9) 267*i*.
dolomitic, use and performance in steel industry, (9) 268*j*.
drying, B (9) 290*e*.
effects of CO, (9) 267*e*.
electrocast. See *Refractories, fused cast.*
elements, P (7) 205*d*.
erosion tests, crucible, electric furnaces for, (10) 304*d*.
erosion zones, in LD converter, and choice of, (8) 237*d*.

Refractories (*continued*)
expansion, fission fragment induced, (5) 132*e*.
firebrick, lightweight, manufacture and use in industrial furnaces, (7) 202*g*.
fireclay, bodies, rheological properties and forming process, (6) 173*g*.
evaluation for rider arches and tile of preheated glass tank checkers, (11) 337*j*.
from Irao Province, Kumamoto Prefecture, properties, (9) 268*c*.
nozzles, nondestructive testing by sonic technique, (8) 239*d*.
products of improved quality, (1) 11*i*.
relation between creep behavior and texture of, (9) 268*j*.
spalling characteristics, effect of alkali, lime, TiO_2, Fe_2O_3, (5) 131*h*.
foamed, of magnesia, (9) 267*b*.
forsterite, made from various raw materials, behavior, (8) 236*i*.
furnace and, P (3) 68*e*.
fused, electrically, at high temperature, P (4) 97*a*.
fused cast, applications in refractory tunnel kilns, (4) 96*d*.
fused cast, with high ZrO_2 content, (8) 237*b*.
gap, shortening between development and furnace practice, (11) 339*e*.
in glass factories, trends and forecast, (11) 334*i*.
for glass melting tanks, (1) 12*c*.
glass plant, tendency to form bubbles in glass, (5) 129*d*.
glass pots, clays for making, (11) 338*c*.
grains, basic fettling, P (2) 46*e*.
gunning, in blast furnaces, (6) 173*e*.
gunning mix, P (3) 69*e*.
hearth, of blast furnace with air-cooled hearth bottom, temperature distribution, (6) 174*f*.
hearth, dam, P (7) 204*e*.
for hearth and bank of open-hearth furnace, (9) 269*k*.
heat shield, resin impregnated ceramic, P (11) 341*b*.
heat storage capacity of, for furnace and kiln construction, (8) 237*g*.
heating and cooling computation in high temperature tunnel kiln, (9) 266*a*.
hot top, apparatus for determining moisture, P (5) 135*e*.
bottom ring, and method of making, P (7) 204*i*.
with centering lugs, P (2) 47*c*.
and composition, P (6) 174*c*.
ingot, consumable product for, P (2) 46*i*.
liners, method for forming, P (8) 240*j*.
lining, P (10) 304*e*.
material, P (6) 174*d*.
insulating. See also *Refractories, firebrick.* (9) 268*a*.
aluminosilicate (5) 131*d*.
foamed, in Canada, (5) 132*f*.
foamed-in-place ceramic, P (8) 240*d*.
perlite-chamotte products, production, (9) 268*a*.
from polyethers and diisocyanates, (7) 202*f*.
product, laminated, P (11) 340*f*.
product, lightweight, manufacture, P (1) 13*a*.
riser sleeve composition, P (11) 340*e*.
vermiculite, (5) 134*a*.
vermiculite, heat and/or sound, P (5) 135*f*.
iron and steel plant, trends, (5) 134*j*.
keep pace with rising output rates in iron and steel plants, (2) 45*j*.
for kiln furniture. See *Kiln furniture.*
ladle, dolomite brick, results of service test, (7) 203*d*.
ladle brick, relation between erosion rate and brittleness index, (7) 202*j*.
60, 90, and 100% zircon, results of service tests, (7) 203*f*.
unfired, P (7) 205*c*.
ladle lining, 60-ton LD converter, extending service life, (7) 202*h*.
160-ton converter, measures for lengthening life, and test results, (7) 202*g*.
of roseki brick and zircon brick, comparison of test results in 60-ton basic electric furnace, (7) 200*h*.
of unburned brick with bloating tendency and burned test brick, comparison of test results, (7) 200*g*.
ladle starter shape, P (10) 304*f*.
lance, refractory-coated oxygen, P (2) 48*d*.
liner anchorage, P (1) 14*h*.
liners, shaped charge, P (7) 205*f*.
linings, aluminum induction, using zircon and calcium aluminate, P (3) 68*h*.
basic oxygen furnace, construction, P (11) 339*i*.
block for, P (11) 340*a*.
brick for, P (2) 48*d*.
cement rotary kiln, deterioration by alkali sulfides and sulfates, (8) 237*c*.
clay, deterioration in torpedo hot-metal transfer car, (8) 239*c*.
for conical portion of furnace, P (2) 48*c*.
design, for use in hot-blast stoves, (9) 268*d*.
in furnace of Kaldo, Linz-Donawitz, De May, or basic or acid converter types, method of prolonging life, P (2) 47*d*.
of furnaces, ovens, kilns, P (7) 204*j*.
in LD vessel, factors affecting rate of wear, (6) 173*d*.
materials, for 80-ton FOS furnace, (9) 268*i*.
metallurgical furnace, P (7) 205*a*.
monolith, in situ fabrication, P (3) 69*c*.
of oxygen converters, life at August-Thyssen-Huette works at Beeckerwerth, (1) 11*d*.

Refractories, linings (*continued*)
of rotary kilns, device for installing or replacing, P (8) 249*e*.
rotary kiln, method, P (4) 97*k*.
stockline, for blast furnace, P (4) 97*i*.
structure for rotary kiln, P (4) 97*k*.
two-component, of flue-gas duct, failure mechanism, (6) 173*f*.
magnesia, differential method load tests, (9) 269*b*.
in floor of open-hearth furnace idle for long period, changes in properties of, (9) 266*b*.
high, product, and process of making, P (7) 204*g*.
hot-pressed, (10) 303*f*.
reaction of slag on: II, properties after slag penetration, (10) 303*i*.
shovel mix, P (4) 97*g*.
magnesia clinker, differential load tests, (9) 269*a*.
magnesia-chrome, basic and chrome magnesia, P (5) 136*c*.
and magnesia brick, service in open-hearth furnace, (5) 132*c*.
ore, P (4) 97*g*.
magnesia-chromite, fused-cast, dependence on temperature of development of various phases in, (7) 201*h*.
magnesite. See also *Refractories, chrome-magnesite*.
P (9) 270*e*; P (11) 340*b*.
brick, construction in glass melting furnaces from port to generator, (8) 233*d*.
brick, and method of improving spalling resistance, P (2) 47*d*.
brick, torsional behavior under cyclic loading, (8) 240*e*.
calcination, and importance in, (5) 131*i*.
damage by carbon at CO decomposition temperatures, (9) 267*b*.
grains, sea-water, compressive strength at high temperature, (9) 266*j*.
with increased lime content, (5) 133*g*.
magnesite-chromite, unfired volume-stable, (9) 269*h*.
bricks, high-fired, results and problems in production, (7) 203*b*.
series, properties, (4) 96*i*.
mandrel, for continuous casting mold, P (1) 12*j*.
manufacture by high energy-rate impaction, P (1) 12*d*.
materials, altered pyroclastic rocks as source of, (7) 200*a*.
of alumina glass and MgO, containing predominantly cordierite, anorthite, spinel, and/or forsterite, P (5) 135*c*.
apparatus for applying to structures, P (2) 46*c*.
application of mercury porosimetry, (1) 11*a*.
bonded, P (7) 204*h*.
cylindrical shaped, induction melting process of central core portion of, P (2) 47*c*.
finely milled, properties, effect of phosphoric acid concentration, (9) 267*g*.
firing, B (9) 290*e*.
hard metal, process for production, P (2) 48*a*.
process and apparatus for continuously melting and solidifying, P (1) 13*h*.
for reheating furnaces, developments, (9) 267*c*.
standards, (10) 304*a*.
thermal diffusivity, method and apparatus for rapid determination over wide temperature range, (11) 346*h*.
thermodynamic properties, evaporator for studying, (11) 346*j*.
for today and tomorrow, (8) 239*j*.
true specific heat measurement during cooling, (5) 146*f*.
melt-cast, contact with glass, study by electron microprobe, (10) 298*j*.
metal article, surface hardened composite, P (5) 136*b*.
metal clad, P (4) 97*h*.
metal nitride, fibers, flakes, and foil, method of making, P (6) 174*j*.
metal oxides, dispersing in other metals, P (8) 241*h*.
metal oxides, particulate, forming spheroids of, P (11) 349*a*.
metals, coated, properties, B (7) 225*e*.
highly pure, sputtering in anodically biased chamber, P (10) 310*i*.
production of rigid shapes, P (6) 175*c*.
protective coatings for, and resulting article, P (4) 93*b*.
reaction with flowing steam, (7) 220*g*.
siliconizing under nonequilibrium conditions, (3) 68*a*.
and method, P (3) 69*e*.
microstructures, (2) 45*c*; (5) 132*i*.
moldable, (2) 45*d*.
molded material, adjustable keystone assembly for arches, walls, P (11) 339*g*.
molding methods, B (9) 290*e*.
molds. See *Molds*.
for molten iron tapping spout of blast furnace, (8) 238*d*.
modern, (1) 11*i*.
mortar, basic highly, with additions of open-hearth agglomerate, (9) 266*h*.
nozzles, blast, for forming silicate fibers, P (2) 40*e*.
for bottom pour ladle for molten metal, P (11) 340*d*.
in dual fuel burners, system for purging, P (8) 249*i*.
exothermically heated molten metal pouring, P (10) 304*c*.

Refractories, nozzles (*continued*)
with improved composition for continuous casting apparatus, P (3) 68*a*.
prestressed, P (1) 13*f*.
pulling, for oriented pulling of semiconductor crystals, P (10) 311*h*.
for steel plants and foundries, P (3) 68*g*.
steel teeming, (6) 174*f*.
zircon, service, handling converter steel in continuous casting plant, (9) 269*i*.
open hearth ladle, mechanism of wear, (10) 303*b*.
oxides, doped with silicon carbide and silicon nitride, P (1) 14*j*.
liquid phase sintering, (3) 67*k*.
solidification points measurement with solar furnace, (5) 154*e*.
for oxygen process steel converters, (4) 96*a*.
panel, heat insulating, for lining furnaces, P (5) 135*f*.
particle sizing, practical application, (3) 67*g*.
periclase-chrome spinel, petrochemical study after service in open-hearth roof, (9) 268*f*.
phosphate bonding in, (5) 133*a*.
plastic, use in slag pockets of open-hearth furnace, (9) 269*g*.
plug, porous, assembly for metallurgical receptacle, P (1) 13*f*.
porosity, nondestructive determination, (9) 267*j*.
porous, from carbides and borides of transition metals, (5) 133*c*.
compressive and bending strengths, (8) 239*h*.
gas permeability, (5) 132*a*.
pouring tube, for degassing vessels, P (3) 69*f*.
preparation, from SiC with nitride binder and from Si_3N_4-SiC materials, (2) 45*d*.
products, P (1) 13*f*; P (7) 205*d*.
development, review, (10) 302*c*.
improving resistance, P (2) 47*g*.
manufacture, properties, and use, B (9) 290*e*.
microhardness tests, (6) 180*i*.
of silica and alumina, physical methods of analysis, (6) 180*j*.
pyrophyllite-sodium silicate, low temperature burned, P (5) 135*g*.
raw material mixture, radiometric and autoradiographic methods for determining optimal homogenization time in Eirich mixter, (9) 268*d*.
raw materials, silicoaluminous, of Romania, technology, (9) 269*d*.
reaction with scale and oxidized steel, (9) 268*f*.
reactions with alkali in cement kilns, (10) 302*f*.
refractoriness under load, of aluminosilicate brick at high temperatures, (10) 302*h*.
differential method for determining on magnesia clinker and brick, (9) 269*a*.
differential tests on magnesia brick, (9) 269*b*.
regenerators, glass tank, basic refractories in, (1) 5*b*.
with granular or chimney-flue-like heart reservoirs, investigation of heat transfer and pressure drop in, (6) 167*b*.
radial flow, matrix formed from ceramic blocks, and method of making, P (5) 136*e*.
resistance to hot slags, measuring, (3) 67*i*.
resistance, in lead chloride melts, (9) 267*d*.
roofs, construction, electric furnace, P (5) 134*j*.
dome-shaped electric, construction, P (3) 68*c*.
electric furnace, basic brick application in, (9) 266*h*.
open-hearth furnace, P (11) 339*i*.
panelized, P (7) 213*j*.
silica, of 250-ton open-hearth furnace, study of erosion rate by tracer techniques, (1) 12*f*.
for tunnel kiln, P (1) 24*e*.
shaped, sampling, (11) 338*a*.
shapes, chemically bonded, P (2) 46*g*.
formed with bond of pitch and carbon black, P (6) 175*a*.
and method for lining rotary kiln, P (8) 241*e*.
porous, from fused quartz, (1) 11*j*.
sheaths, for immersion thermocouples, (9) 267*h*.
sleeve, P (2) 48*b*.
zirconium diboride thermocouple, production, (9) 268*b*.
silica, thermal expansion and stability, (7) 202*d*.
silica, used, from chamber walls of coke oven batteries, (10) 303*j*.
siliceous graphitic, P (7) 205*b*.
silicon carbide, clay-bonded: I, effects of grading of SiC on properties of refractories, (9) 269*a*.
silicon carbide, silicon bonded, (3) 68*a*.
sintering, chemical, P (4) 97*d*.
slag. See *Slags*.
spalling resistance, of zirconium dioxide, effect of phase composition, (9) 267*g*.
specialties, bonded by aluminum phosphate, (8) 239*j*.
spinel and corundum, reaction with compounds, (9) 268*h*.
spinel and spinel-corundum sintered, properties, (8) 239*f*.
stopper, for ladle, P (2) 48*b*.
stopper head tops, causes of damage, (9) 269*b*.
stopper rod sleeve, with insulating inner portion, P (7) 204*a*.
structure, for rotary kiln, P (1) 14*b*.
tank blocks, for glass furnaces, B (1) 34*e*.
taphole, for metallurgical vessel, P (1) 14*b*.
taphole, precast assembly, P (11) 340*e*.
tar-bonded dolomite brick, behavior of carbonaceous materials in, for LD converter, (9) 266*i*.
tar-dolomite, relations between tested properties and stability in oxygen process steel converters, (4) 96*d*.
tar-dolomite and tar-magnesite bricks, mineralogy of erosion in oxygen process steel converters, (7) 202*i*.
testing, need and validity, (10) 304*a*.
testing, survey, (10) 302*c*.

Refractories (*continued*)
thermal conductivity, hot-wire method of measuring, (6) 173*g*.
thermal conductivity, measurement at high temperatures, (8) 238*f*.
thermal resistance: II, high-temperature apparatus to obtain thermal conductivity and thermal shock resistance, (5) 134*h*.
thermal shock resistant, cordierite as basis for, (8) 237*j*.
tile, for furnace regenerator, P (7) 205*d*.
tile block for suspended construction, P (5) 135*c*.
vacuum vessel, design considerations, (6) 172*h*.
walls, division, for soaking pits, P (7) 204*b*.
walls and structures, calculation of heat losses, temperature gradients and junction temperatures in, (10) 302*f*.
wetting and sticking of glass to, (10) 299*c*.
zircon, P (1) 41*i*; P (4) 98*a*.
as ladle brick, (7) 202*g*; 203*f*.
and Zirmul, application in glass tank superstructure, (11) 337*g*.
zircon-dolomite, fired at 1500°C, mineral constitutions, (8) 239*b*.
zirconia, gaseous erosion: II, changes at surface; III, effect of K additive on erosion resistance in stream of products of combustion, (5) 132*c,d*.
granular, strength up to 2500°K, (5) 134*d*.
-magnesia composition, and method of making and using, P (5) 136*d*.
zirconium boride and carbide, P (5) 136*b*.
Refractories industry, changing pattern of fuel usage in, (3) 76*i*.
electrocast, control of quality in, (3) 67*a*.
Globe plant, features three automatic setters, (4) 96*h*.
history and development, (2) 44*b*.
impact of technical trends in steel industry, (2) 46*g*.
of India, (5) 134*c*.
legislation impact, (2) 44*g*.
Regenerators. See *Refractories*.
Relaxation, dielectric, in alkali-alkaline earth-silica glasses, (7) 196*c*.
dielectric, in BaO-P_2O_5 glasses, and dependence on water content, (8) 231*j*.
dielectric, in strontium titanate solid solutions containing mixed cations, (7) 216*e*.
effects, in molten nitrates, (7) 221*d*.
low-frequency grain-boundary, in alumina, (7) 219*e*.
magnetic, low frequency, in manganese ferrous ferrites at low temperatures, (3) 71*h*.
nuclear magnetic, in magnetite, (10) 323*i*.
nuclear spin-lattice, in ferromagnetic insulators at low temperatures, (8) 255*j*.
paramagnetic for ground manifold of chromium in rutile, (10) 324*f*.
protonic, in paramagnetic and antiferromagnetic $CoCl_2 \cdot 6H_2O$, pulsed-NMR study of, (8) 256*i*.
of rare earths in CaF_2, (11) 355*f*.
in sodium bromate, nuclear-spin pumping study of, (9) 284*j*.
spin, of atomic hydrogen in fused silica, temperature dependence, (10) 325*b*.
spin-lattice, of Cr^{3+} coexisting with Ti^{3+} in Al_2O_3, (3) 86*g*.
spin-lattice, of Rh(II) in $ZnWO_4$ single crystals, (10) 325*a*.
spin-spin, in LaF_3, (9) 286*e*.
surface-layer, in dielectric spectrum of CaF_2 doped with GdF_3, (4) 117*h*.
of uniaxial anisotropy induced by ionic migration in iron-cobalt ferrites, theory, (10) 326*h*.
volume, kinetics, of vitreous boron oxide, (11) 357*h*.
Replica method. See *Microscopy*.
Research, brick and tile, in India, (9) 266*d*.
cement and concrete, (2) 36*e*.
ceramic, current, (3) 89*b*.
ceramic, in England, (10) 327*i*.
of clays and soils, recent developments, (3) 86*a*.
in glass industry, (9) 264*g*.
high-temperature, localized-heating microchamber for, (10) 314*f*.
on laser standards and materials at NBS, (9) 286*h*.
on sinterable BeO Powder to obtain sinters of given characteristics, (3) 67*j*.
Resins, -to-glass ratio, of glass-epoxy structures, determination by beta-ray backscattering, (9) 276*a*.
ion-exchange, (6) 180*h*.
ultrafine ion exchange, (10) 317*g*.
Resistance, electrical. See also *Conductivity, electrical*.
of concrete, (10) 294*f*.
contact, of graphite lead-in rods, (10) 306*h*.
equivalent series, of tantalum solid electrolytic capacitors, (10) 307*f*.
measurement by electron beam, (11) 354*d*.
measurements, for detection of thermal reaction in mixed oxide powders, (11) 351*i*.
of molten glass between electrodes, (10) 297*i*.
specific, of silicon crystal, measurement by measuring breakdown voltage, P (5) 142*c*.
symmetrical negative, in valence-exchange-type semiconductor glass junctions, (3) 87*h*.
of uranium, during oxidation at 10^{-3} torr and 500° to 800°C, (4) 109*e*.
of VO_2, pressure dependence of, (5) 157*f*.
Resistivity, of Cr-SiO cermet films, (5) 139*e*.
electrical, in ceramics at high temperatures (1000° to 1700°C), measurement, (10) 314*g*.
of semiconducting $BaTiO_3$, effects of additives and ambient atmosphere during heating on, (8) 253*i*.
of single crystal CrO_2, (10) 320*b*.

Resistivity, electrical (*continued*)
of sintered composite carbon black-kaolin materials: IV, relation between temperature dependence of resistivity and carbon bulk density; V, effects of firing temperature on resistivity temperature dependence, (5) 151*d,e*; VI, pressure dependence of resistivity of carbon black under loose contact; VII, resistivity-bulk density relations of carbon black under loose contact; VIII, effects of carbon materials on resistivity, (7) 207*f,h*.
of thorium monocarbide, (10) 320*f*.
of titanium diboride, (8) 253*c*.
of Gd^{3+} doped $BaTiO_3$ crystals grown in molten KF, (10) 325*c*.
high frequency, of hexagonal ferrite Zn_2Y, (4) 106*a*.
in Ti_2O_3, (11) 356*g*.
volume, of molten glass, unit for complex study of effective coefficient of, (10) 299*f*.
Resistors, electrical, P (4) 100*c*; P (5) 141*b*; P (8) 245*j*; P (10) 310*j*.
adjustable damping, 67DR, (10) 306*g*.
cermet, by concurrent rf and dc sputtering, (8) 242*i*.
cermet, making by etching, P (11) 344*j*.
Cr-SiO cermet, phenomenon associated with abrasion of, (10) 307*h*.
composition, carbon film, P (1) 17*a*.
elements, and method of making, P (9) 272*f*.
glass bonded, containing refractory metal nitrides and refractory metal, P (10) 309*g*.
comprising spaced metal contings on resistive layer and traveling wave tube using, P (5) 142*g*.
diffused, for integrated circuit, P (9) 272*f*.
electroconductive composition containing $BaPbO_3$ for, P (6) 177*e*.
etched film, tolerance limitations of, (10) 309*b*.
evaporated cermet, (11) 342*c*.
film, P (6) 178*c*.
film, preparing by sputtering ternary alloy of tin, antimony, and indium in presence of oxygen, P (9) 274*e*.
heating, P (1) 12*c*.
for integrated circuits, P (4) 101*d*.
metal film, chemical deposition of metals in production of, (10) 306*i*.
for low range and linear temperature coefficient, P (3) 73*c*.
reversible temperature dependence of, (10) 308*f*.
molded, P (3) 73*h*.
rhenium thin film, P (8) 246*d*.
ruthenium oxide glaze, (2) 50*g*.
sandwich, P (10) 310*b*.
thallium oxide glaze with ruthenium oxide additive for, P (2) 52*g*.
thermistor, P (4) 100*c*; P (5) 142*b*; P (10) 310*d*.
positive temperature coefficient [La–Ba–Sr] titanate, P (7) 210*a*.
PTC, properties and applications, (3) 72*c*.
thin film, P (10) 310*c*.
and varistors, (3) 72*f*.
thin film, P 245*f*, 246*g*.
adjustment method, P (9) 274*d*.
composed of chromium and vanadium, P (4) 101*f*.
variable, and resistive element, P (2) 52*c*.
wound, with terminal means, P (9) 275*d*.
Resonance, antiferromagnetic, modes, in $RbMnF_3$, nonlinear coupling between, (1) 16*j*.
behavior, of GaAs dielectric constant at microwave frequencies, (1) 16*c*.
cyclotron, of piezoelectric polarons, (8) 252*h*.
electric, of rotating dipoles in ionic crystals, (10) 320*h*.
electron-nuclear double, of Ag nuclei in AgCl + Fe^{3+}, (9) 282*a*.
electron paramagnetic, (10) 314*a*.
application, (11) 346*i*.
of effect of substrate orientation on vapor-grown GaP, (11) 352*e*.
of MgF_2:Co^{2+}, hyperfine structure of ^{19}F in, (9) 283*b*.
of oxygen on ZnO and ultraviolet-irradiated MgO, (7) 217*g*.
of photosensitive donors in ZnO, (10) 320*e*.
in silicate glass fibers, (2) 39*f*.
spectra, of irradiated two-component glasses, (10) 299*c*.
study of impurity-related color centers in germanium-doped quartz, (5) 152*g*.
electron spin, of boron in single-crystal BeO, (5) 152*a*.
of center in fluorine-doped zinc sulfide, (5) 138*f*.
of Cr^{3+} in phosphate glass, (5) 127*i*.
of Cu^{2+} ion in $CdWO_4$, $ZnWO_4$, and $MgWO_4$ crystals, (7) 217*g*.
of F centers in irradiated ^{43}CaO and other alkaline earth oxides, (4) 109*b*.
of Gd^{3+} in reduced $BaTiO_3$, (4) 109*c*.
of Ga^{2+} in $SrTiO_3$, electric field effect on, (10) 320*e*.
of Gd^{3+} and Eu^{2+} in $KTaO_3$, (10) 320*f*.
in GeO_2, (3) 80*c*.
of Fe^{3+} in SnO_2, (4) 109*c*.
of irradiated quartz—atomic hydrogen, (3) 80*d*.
of manganese in borate glasses, (5) 127*i*.
of Mn^{2+} in $BaTiO_3$ single crystal, (10) 320*g*.
of Mn^{2+} in α- and β-$Mg_2P_2O_7$, (11) 352*g*.
of Nd^{3+} pairs in $LaCl_3$ and $LaBr_3$, (11) 352*b*.
in neutron-bombarded graphite, (4) 109*c*.
of niobium in $CaWO_4$, (11) 352*f*.
parameters, in 6H polytype of silicon carbide crystal doped with boron, (3) 80*e*.
in phosphorus doped silicon at low temperatures, (3) 80*f*.
in phosphorus doped silicon, effect of doping, (7) 217*b*.
Resonance, electron spin (*continued*)
of photosensitive gallium center in ZnS, (11) 352*b*.
properties of heat-treated synthetic diamond, (1) 32*f*.
in reduced $BaTiO_3$, (4) 109*c*.
of Rh_{II} in $ZnWO_4$, (6) 185*i*.
in SiO_2 grown on silicon, (5) 152*b*.
study of crystallographic phases in $Zn_2P_2O_7$:Mn and $Zn_2P_2O_7$:Cu, (5) 152*h*.
study of γ- and X-irradiated zeolites, (6) 185*j*.
study, of irradiated alkali borate glasses with high alkali oxide content, (5) 127*j*.
study of irradiated glasses containing boron, (5) 127*j*.
study of manganese-doped α-zinc silicate crystals, (11) 352*g*.
study of surface chemistry of rutile, (2) 58*c*.
ferromagnetic, measurement by simple cryostat for range −190° to +200°C, (11) 347*h*.
losses, high temperature, in silicon-doped YIG, (3) 71*d*.
magnetic, preliminary, study of $UO_2 \cdot xH_2O$, (6) 187*h*.
magnetic, in solids, B (10) 328*c*.
nuclear and electron spin, of $KMnF_3$, (9) 284*g*.
nuclear magnetic, of ^9Be in single crystals of BeO, (3) 67*c*.
^{11}B, measurements on high pressure modifications of B_2O_3 and potassium borate glasses, (6) 166*f*.
determination of microscopic parameters of $LiAl_5O_8$, (5) 156*a*.
investigations of system $BaO–B_2O_3$, (3) 64*f*.
^{139}La and ^{55}Mn signals, from ferromagnetic $(La_{1-x}Sr_x)MnO_3$, (10) 322*a*.
of $MnCO_3$ in canted spin state, (8) 255*j*.
^{55}Mn, in antiferromagnetic $CsMnF_3$, direct observation, (9) 281*c*.
^{55}Mn, of Mn^{2+} ions located at B-sites in manganese ferrite, (4) 113*f*.
^{55}Mn, of Mn^{4+} ions located at B-sites in ferrites, (4) 113*f*.
of paramagnetic $CoSO_4$: I, experimental study; II, theory of NMR shift, (4) 113*c*.
studies of critical phenomena in MnF_2: I, time-average properties, (11) 355*c*.
pulsed, study of protonic relaxation in paramagnetic and antiferromagnetic $CoCl_2 \cdot 6H_2O$, (8) 256*i*.
study of ferroelectric $LiNbO_3$ and $LiTaO_3$, (5) 139*c*.
study of glass structure in system $Na_2O–B_2O_3–P_2O_5$, (7) 196*h*.
study of hydrated sodium tetraborate minerals: I, boron-oxygen polyions in borax and tincalconite; II, ^{23}Na sites in borax and tincalconite, (5) 155*j*; 156*a*.
study of interlayer water in hydrated layer silicates, (5) 156*a*.
study of V_2O_5, (11) 355*c*.
study of water in hardened cement paste, (6) 165*f*.
optical double, experiments in ruby, (3) 84*e*.
paraelectric, of OH^- dipoles in KCl, (10) 324*f*.
paramagnetic acoustic, of rare earths in CaF_2, (11) 355*f*.
paramagnetic, of amethyst, (3) 84*e*.
of copper in amorphous and polycrystalline GeO_2, (10) 324*g*.
determination of nuclear quadrupole interaction by means of forbidden hyperfine transitions—Ca–WO_4:Mn^{2+}, (10) 324*g*.
of divalent praseodymium in CaF_2, (10) 324*g*.
and electron nuclear double, of substitutional hydrogen atoms in CaF_2, (1) 30*j*.
of fluoberyllate glasses with cobalt and nickel, (3) 64*e*.
of Gd^{3+} in CeO_2 single crystals, (8) 255*f*.
of Mn^{2+} in glasses and compounds of lithium borate system, (5) 128*e*.
photo-induced, of chromium in zinc sulfide crystals, (9) 285*c*.
of S-state ions in strontium oxide single crystals, (5) 156*a*.
study at millimeter wavelengths of axial Fe^{3+} spectrum in strontium titanate, (9) 285*f*.
piezoelectric and nuclear, spectroscope for, (3) 76*g*.
spin-cluster, in $CoCl_2 \cdot 2H_2O$, (11) 357*b*.
switching, in $BaTiO_3$ crystallites, (10) 325*h*.
Resonators, devices, piezoelectric ceramic, P (1) 18*j*.
piezoelectric, P (4) 100*j*; P (5) 142*a*; P (8) 245*j*.
quartz, P (7) 210*c*.
Rhenium, ditelluride, synthesis, (6) 180*j*.
(V)oxyhalide complexes, chemical and structural studies: I, complexes from rhenium(III) bromide, (4) 106*c*.
reaction with flowing steam at 850° to 1700°C, (7) 220*h*.
Rheology, control of clay-water systems, P (2) 57*c*.
evaluation of casting slips, (10) 305*h*.
of fireclay bodies, and forming process, (6) 173*g*.
in kaolinite and bentonite gels, thixotropy and dilatancy, (6) 190*h*.
models, of viscoelastic bodies with Kelvin elements, differential relations for, (11) 351*d*.
of non-Newtonian materials, (9) 275*j*.
properties, of nonmetallic materials, (11) 357*i*.
properties, of plastic ceramic materials and technical data of shaping process, relation between, (5) 146*h*.
zeta potential determination, (9) 277*a*.
Rhodium, (II) spin-lattice relaxation, in $ZnWO_4$ single crystals, (10) 325*a*.
Rhodizite, structure and composition, (5) 158*b*.
Rock wool. See *Mineral wool*.
Rockets. See *Spacecraft*
Rocks. See also *Phosphates; Silicates*.
altered pyroclastic, as source of refractory material, (7) 200*a*.
carbonate, control of quality by ultrasonics, (3) 77*e*.
of Deccan traps, lead isotopes in, and estimate of age from lead ratio, (6) 183*g*.
fused. See *Stone, cast*.
Indian, quantitative estimation of free silica content, (1) 34*d*.
mechanics, testing techniques, B (3) 90*g*.
metamorphic, of Barrow's zones, chloritoid and isochemical character of, (3) 79*f*.
metamorphic, high-grade, at Broken Hill, Australia, microstructures, (9) 284*b*.
Precambrian plutonic and volcanic, of lower Critical Zone, Farm Ruighoek, Western Bushveld, evolution, (3) 81*b*.
pyrophyllite and kaolinite pelitic, stability, effect of chemical reduction, (9) 281*g*.
silicate, determination of major elements in, by photoelectric spectrometry with the A.R.L. quantometer, (6) 180*h*.
and phosphate, fluorine in, (10) 313*j*.
X-ray fluorescence analysis using powdered samples dispersed in silica without fusion or pelletization, (10) 316*f*.
use in determination of depositional environments, Mesaverde Formation, William Fork Mountains, Colorado, (4) 118*g*.
Roughness. See *Surface*.
Rubidium, chloride, dielectric constant, effects of hydrostatic pressure to 20 kbars on, (11) 352*f*.
dizirconate, (4) 115*j*.
halides, melting curves at high pressures, (6) 187*g*.
hexafluoroaluminate, complex formation with sodium cryolite, (9) 280*e*.
iodide, intrinsic luminescence at 10°K, (10) 322*a*.
polyhafnates, (10) 324*a*.
Rb_3CoCl_5 and Rb_7CoCl_9, crystal structures, (5) 150*e*.
$RbLiF_2$, crystal structure, (4) 107*i*.
$RbNiF_3$, transparent, magnetic and optical properties, (1) 16*g*.
-strontium, geochronological study of Willyama Complex, Broken Hill, Australia, (3) 86*d*.
systems. See *Systems*.
trizirconate, (10) 325*e*.
Ruby. See also *Lasers; Masers*.
crystal fields and optical spectra, comparison, (5) 150*e*.
crystals, grown by Czochralski technique, (11) 356*g*.
Czochraiski, X-ray topography, (1) 34*a*.
ground-state splitting in, (3) 81*i*.
level splittings, effect of stress, (5) 137*i*.
measurement of ground-state population in, under optical pumping, (3) 83*j*.
optical double resonance experiments in, (3) 84*e*.
of optical quality, growth problems, (9) 272*c*.
optically pumped, absorption spectrum: I, experimental studies in excited states; II, theoretical analyses, (10) 318*j*.
spectrum, symmetry considerations, (5) 158*j*.
temperature dependence of Al nuclear quadrupole interaction in, (5) 159*e*.
ultraviolet absorption and excitation spectrum, (7) 222*j*.
wedge shaped, laser operation in, (4) 112*h*.
Rupture, modulus, of extruded and sintered BeO, effect of machining, (5) 131*j*.
moduli of silicon nitride bodies, effect of binder, grain size, sintering temperature, and atmosphere, (2) 43*i*.
Ruthenium, complex compounds, containing NO group, thermal stability, (10) 326*a*.
dioxide, tetragonal, crystal and molecular structure, (5) 150*j*.
$MO_3 \cdot 3R_2O_3$ compounds, rhombohedral, crystal structure and relation to ordered R_7O_{12} phases, (5) 150*d*.
oxides, ternary, magnetic interactions, (6) 187*c*.
pentafluoride, enthalpy of formation, (11) 353*a*.
solubility, in soda-silica glasses, (4) 93*j*.
spectrophotometric determination, (11) 347*i*.
Rutile. See also *Titanium, dioxide*.
interband Faraday rotation in, (6) 186*c*.
mixed, crystal formation, in Ti–Ni–Sb–O system, (7) 219*c*.
paramagnetic relaxation and crystal-field theory for ground manifold of chromium in, (10) 324*f*.
polycrystalline, intercrystalline thermal stresses in, (5) 153*j*.
reduced, conductivity increase with saturation of electron spin resonance, (4) 107*b*.
selective flotation, (1) 25*f*.
surface, characterization by nitrogen and water vapor adsorption, (7) 216*b*.
surface, infrared study, (3) 82*h*.
surface chemistry, electron spin resonance studies of, (2) 58*c*.
thermal expansion from 100° to 700°K, (4) 118*b*.

Safety. See also *Health*.
health and, (10) 328*a*.
production-quality control-cost problem, (2) 60*d*.
Saggers. See *Kiln furniture*.
Salts, aliphatic amine onium, high-temperature reaction with strontium and barium carbonates, (6) 186*b*.
bath, protective, for use in glass ribbon manufacture, P (7) 199*f*.
complex, in hardened cement with chemical additives, (2) 36*b*.
Er^{3+} doped, two-photon stepwise absorption in, (1) 17*g*.
hygroscopic, dynamic sorption by, (11) 351*j*.
of M_3VCl_6 and $M_3V_2Cl_9$ type, enthalpy of formation, (10) 321*b*.

Salts (*continued*)
molten, and concentrated aqueous solutions, electrical conductance of, correlation through free volume transport model, (11) 352*g*.
diffusion-conductance relations and free volume in, (11) 351*d*.
mixtures, new class involving hydrated dipositive ion as independent cation species, (4) 113*h*.
solution, reactions in: I, uranate and neptunate formation in molten lithium nitrate-sodium nitrate, (4) 115*a*.
organic, effects on setting of gypsum plaster, (10) 294*e*.
NaCl. See *Sodium, chloride*.
strontium, preparation from celestite, (9) 278*g*.
Samarium, oxide, reaction with chromium, (10) 324*h*.
Sm^{3+} in $BaTiO_3$ host lattice, luminescence spectra, (3) 83*e*.
Sm_5Ge_4, crystal structure, (2) 57*g*.
$SmLiO_2$, transformation under very high pressure and at very high temperature, (1) 33*a*.
$Sm_4(SiO_4)_3$, preparation, (5) 157*d*.
systems. See *Systems*.
Sampling, apparatus, for unground solids, P (8) 249*a*.
of bulk materials, (6) 181*c*.
of dust particles, through orifice in base of horizontal cylinder, effect of crosswind, (5) 145*f*.
laser microprobe, for qualitative analysis, (9) 276*a*.
of materials, process for reducing error in, P (10) 316*e*.
programs, for raw materials in glassmaking, (7) 197*g*.
shaped refractories on receipt, (11) 338*a*.
Sandblasting. See *Blasting*.
Sandpaper. See *Abrasives*.
Sands, beach, selective flotation, (1) 25*f*.
beach and river, size frequency distribution, dynamic processes and statistical parameters compared for, (1) 28*e*.
core, binding agent for, P (5) 136*a*.
fine-ground quartz, indirect methods of determining specific surface of, (2) 54*j*.
foundry, method and apparatus for accurately proportioning, P (3) 69*a*.
foundry, mixer-grinder for, P (3) 69*e*.
glassmaking, occurrence near Churulia, Burdwan district, West Bengal, (1) 6*e*.
glassmaking, removal of iron from, (10) 317*h*.
Indian, expansion characteristics, (6) 173*a*.
Indian foundry, angularity and mineralogical studies, (6) 172*g*.
Indian foundry, specific surface area and water absorption capacity, (6) 174*e*.
industrial, in Pike County, Kentucky, (7) 214*e*.
-lime bodies, hydrothermally bonded, structure of binder in, (10) 295*h*.
moisture, and properties, (3) 74*i*.
molding, apparatus for measurement of physical characteristics, P (1) 12*h*.
molding, binders: I, effect of heating temperature on quality of bentonites, (11) 339*a*.
in red stoneware clays, (8) 242*g*.
refining, P (6) 183*b*.
resources, of Texas gulf coast, (7) 214*g*.
zircon, decomposition process, P (9) 279*a*.
Sandstones, altered, combined analysis of size, shape and compositional mode of grains in, (5) 144*i*.
classification, modification, (9) 284*f*.
classification, numerical method, (1) 30*f*.
flexible, structure-property relation in, (8) 257*g*.
Sanidine. See *Feldspar*.
Sanitary ware, bathtubs, cast iron, classification of dry process enamels by drip test, (5) 125*i*.
characteristics and manufacturing methods for prefabricated building, (9) 270*h*.
continuous slip-casting line for, (4) 98*b*.
firing, (5) 136*j*.
lavoratory, self-rimming, P (4) 98*g*.
improvements, P (5) 137*e*.
quality, (9) 271*b*.
sink, fixture to prevent chipping and seal between sink and support, P (5) 137*c*.
water closet installations, P (10) 306*f*.
Sapphire, chemical-vapor-deposited silicon on, observation by transmission electron microscopy (5) 156*c*.
crack-branching in, (5) 126*i*.
epitaxy of copper on, (10) 307*e*.
irradiated, growth kinetics of interstitial loops in, (1) 29*h*.
Ni and Co in, spectroscopic study, (7) 221*f*.
of optical quality, growth problems, (9) 272*c*.
produced in filament form, (4) 96*e*.
single-crystal growth, (8) 257*a*.
ultraviolet absorption and excitation spectrum, (7) 222*j*.
vapor etching by H_2-$SiHCl_3$ gas mixtures, (4) 118*j*.
wetting by liquid aluminum, effect of nature of surfaces, (11) 352*b*.
Saws, diamond blades, P (6) 163*j*.
wire, for cutting optical crystals, (1) 23*g*.
Scaling, on pure nickel-chromium alloys at 800° to 1200°C, (7) 207*b*.
Scandium, oxide, crystal structure, refinement, (11) 356*b*.
oxide, reaction with oxides of alkaline earth metals, (10) 324*i*.
α-ScOOH and γ-ScOOH, hydrothermal preparation, and crystal structure of α-ScOOH, (5) 153*a*.
$Sc_2(WO_4)_3$, diamagnetic, crystal structure, (11) 351*e*.
Scandium (*continued*)
sesquioxide, structure, refinement of, (8) 256*d*.
sesquitelluride, crystal structure, (4) 107*g*.
trifluoride, sublimation pressures, measured by mass spectrometry, (7) 219*h*.
Scapolite, stoichiometry, (5) 158*i*.
Scattering, Brillouin, stimulated, in quartz, temperature dependence of, (11) 357*c*.
diffuse X-ray, by solid solution NbC–TaC, (9) 280*g*.
light, to show effect of melting method on homogeneity of glass, (11) 333*h*.
light, for study of glass refining, (11) 334*e*.
Raman, first- and second-order, of $SrTiO_3$, (11) 352*j*.
Raman, near-forward, in zinc oxide, (10) 323*g*.
resonant electron-phonon, in polar semiconductors, (2) 50*g*.
X-ray diffuse, in $NiCr_2O_4$, (3) 79*g*.
Schools. See *Education*.
Screen process printing. See *Decoration*.
Screening, silk-, elements, (8) 246*j*.
silk, satisfactory light-sensitive solutions for, (8) 247*c*.
wet, of particles, apparatus, P (3) 78*a*.
wet and dry, method and apparatus, P (1) 20*c*.
Screens and sieves, P (7) 211*g*.
Alpine Air Jet, to determine fineness of cement, (3) 62*b*.
cathode ray tube display, comprising woven mat of luminescent glass fibers, P (6) 177*b*.
circular, for fineness and speed, (3) 74*j*.
color, of cathode ray tube, P (9) 265*d*.
color phosphor, P (1) 18*b*.
color-phosphor mosaic, optical system for making, P (8) 245*b*.
fluorescent, for brightness amplifier tubes, P (3) 72*g*.
fluorescent, high contrast, with spaced phosphor layer, and method of manufacture, P (4) 100*c*.
mechanical, P (5) 144*c*.
molecular, crystalline zeolitic, preparation, P (10) 318*b*.
granules, production, P (3) 78*d*.
nodules and extrudates, high strength, process for making, P (7) 215*d*.
pretreatment, P (10) 318*a*.
molecular, wet attrition-resistant bodies, and manufacture, P (8) 252*b*.
oscillating, frame, P (10) 312*g*.
phosphor, method of manufacture, P (9) 265*g*.
phosphor, for cathode-ray tubes, method of salvaging phosphor slurry in spin coating process for making, P (4) 100*b*.
powder sifting machine, P (10) 312*h*.
projection viewing, coated with light transmitting composition, P (2) 56*g*.
rod, P (10) 312*i*.
silk, finishing, basic techniques and data on high production, (1) 15*g*.
vibrator, tensioning apparatus, P (1) 20*f*.
Sculpture. See *Art and artware*.
Seals and sealing. See also *Bonding; Soldering*.
alumina with Mo, MoO_3 and Mo–Mn, (2) 37*j*.
apparatus, lamp, with double revolving and orienting sealing heads, P (6) 170*j*.
ceramic-to-metal, P (2) 38*c*; P (5) 126*f*; P (5) 140*g*; P (8) 244*d*.
of heavy metals type to beryllia ceramics, (2) 37*j*.
manufacture, applications and future, (2) 37*h*.
oxidation resistant high temperature, compatible with cesium, (1) 4*g*.
compound, joint, in casting molds, P (11) 341*c*.
compound, joint, in plastering wall surfaces, P (8) 229*b*.
electrical discharge vessel, vacuum-tight connection between ceramic tube and disk-shaped metal part of, P (8) 230*a*.
electrolytically, layer of semiconductors, P (11) 344*g*.
gastight thermobalance-load, (2) 54*e*.
glass, noble metal coated ceramic substrate for, P (10) 311*d*.
glass, radiation-resistant, P (5) 130*e*.
glass-to-metal, P (3) 65*i*.
bonding mechanism in, (8) 242*j*.
formation by high-frequency induction heating, (2) 37*i*.
hermetic, P (6) 171*g*.
for high temperature electronic packaging, (3) 72*h*.
strength, (9) 264*j*.
high-temperature alumina-to-niobium, in vacuum-type devices, P (9) 273*e*.
integrated circuit, method and structure, P (2) 51*e*.
and locking bell and spigot pipe joints, P (11) 337*f*.
metal-to-ceramic, P (5) 141*d*.
for high voltage electron tubes, P (11) 344*b*.
spring tensioned, (1) 4*a*.
metal-to-glass, P (8) 245*b*.
metal-to-glass, hermetic, and application, P (6) 170*f*.
metal-to-glass-to-ceramic, P (3) 73*c*.
noble metal coated ceramic, for glass seals and electronic connector elements, P (10) 311*d*.
for pipe joints, P (3) 66*h*.
polyoptical, of vacuum tubes, (5) 139*i*.
refractory ceramic-to-metal, (4) 99*i*; P (5) 142*f*.
refractory metal-to-ceramic, method of forming, P (9) 273*d*.
rotary vacuum, large, for manual operation, (4) 102*j*.
solders, interaction with metallized coatings on ceramic materials, microspectral method for investigating, (10) 307*e*.
Seals, solders (*continued*)
spark plug, with lower coefficient of expansion than ceramic insulator core, P (1) 19*d*.
vacuum, of gas laser windows, P (9) 266*a*.
Sedimentation, of clay: III, treatment of acid waste liquor in clay industry and recovery of usable by-product, (8) 250*a*.
system, P (5) 144*f*.
Sediments, analysis, scientific method, B (6) 192*b*.
carbonate, ancient and recent impregnated, stained dry cellulose peels of, (8) 248*h*.
carbonate, quantitative mineralogical analysis, (8) 248*d*.
Selenide, metal, group IV di-transition, (4) 110*h*.
metallic, and process for making, P (9) 273*g*.
semiconductor, method of passivating supports for, P (3) 73*d*.
systems. See *Systems*.
Selenium, materials, highly pure semiconducting, process for continuous production, P (3) 74*b*.
materials survey, (3) 77*e*.
selenious oxide, extraction from gas mixtures, P (10) 318*c*.
single crystal hexagonal, growth from supercritical ammonia, (2) 58*j*.
systems. See *Systems*.
vitreous, thermal expansion from −190° to +30°C, (10) 326*j*.
Semiconductors, P (1) 19*c*.
alkali metal doping of, (1) 16*a*.
alloy composition, with thermoelectric properties, P (4) 101*e*.
arrangements, P (1) 19*b*.
assemblies, producing, P (10) 310*g*.
bodies, crystalline, drawing from melt, P (2) 52*d*.
with doped zone, P (2) 52*g*.
forming oxide coating on, P (8) 245*g*.
method and apparatus for making, P (2) 51*i*.
monocrystalline, method for producing, P (7) 209*d*.
producing pure polished surfaces on, P (10) 310*g*.
rod-shaped, apparatus for pyrolytic production, P (4) 99*c*.
of silicon carbide, methods of making, P (2) 51*i*.
treatment, P (5) 143*b*.
ceramic compositions, with positive temperature coefficient of resistance, P (6) 178*g*.
chemical bond in, B (8) 259*c*.
chips, bonding machine, P (11) 343*h*.
components, P (1) 19*c*.
ceramic housing for, P (9) 272*a*.
producing, P (1) 18*i*.
compound, effect of impurity-vacancy complex on degree of compensation in, (10) 320*d*.
single phase ternary, of silver or copper, thallium, and sulfur or selenium, P (11) 345*g*.
of two or more components, method and apparatus for producing, P (1) 18*i*.
crystals, P (5) 142*f*.
apparatus for pulling, P (1) 17*i*.
body, P (5) 142*a*.
high purity, preparation, P (3) 74*a*.
pulling nozzle for oriented pulling of, P (10) 311*h*.
dangling bonds and dislocations in, (11) 351*f*.
devices, P (2) 52*d*; P (3) 74*a*, *f*, *g*; P (4) 100*d*, 101*f*; P (5) 142*h*, *i*; P (6) 178*g*; P (7) 209*g*, *h*; P (8) 245*a*; P (9) 272*j*; 274*b*, *e*, *j*; P (10) 311*c*.
with anisotropic inclusions for producing electromagnetic radiation, P (7) 210*f*.
apparatus for die and wire bonding on, P (8) 243*i*.
application of glass to, P (3) 72*j*.
beam lead, P (9) 272*j*.
cleaning, P (8) 244*e*.
coating with silicon oxide, P (11) 344*e*.
contacting, strain relieving transition member for, P (9) 275*a*.
with depletion area, forming, P (7) 209*e*.
discontinuous resistance, P (3) 72*d*.
double diffused, making by double masking step, P (4) 100*b*.
electrically isolated, fabricating in integrated circuits, P (6) 178*a*.
essential ratings and characteristics, (8) 243*e*.
with exposed surfaces of hydrophilic oxide, method of stabilizing, P (2) 51*h*.
fast responding, using light as transporting medium, P (5) 141*g*.
formation, P (5) 141*i*.
forming by diffusion, P (11) 343*f*.
forming by diffusion and alloying, P (9) 273*f*.
forming by etching and epitaxial deposition, P (1) 18*a*.
forming ohmic contacts in, P (11) 344*f*.
forming metal contact on, P (9) 273*a*.
of four-layer type, P (10) 311*c*.
GaAs, and contact alloy for, P (6) 177*a*.
glass molded type, P (7) 208*j*.
hermetically sealed, P (8) 244*d*.
with improved p-n junction avalanche characteristics, method of making, P (1) 18*c*.
induced region, P (4) 100*d*.
integrated, with p-n junction running through wafer, P (6) 177*h*.
large area wafer, P (8) 244*h*.
light emitting, P (5) 141*c*.
with low leakage current across junction, P (4) 101*g*.
luminescent, including compensated zone with substantially balanced concentration of donors and acceptors, P (9) 273*f*.
mass producing, P (11) 344*e*.
making by diffusion and forming oxide, P (11) 344*b*.
making by double diffusion, P (1) 18*c*.
making by double masking, P (1) 18*d*.

Semiconductors, devices (*continued*)
making by masking and diffusion, P (10) 310*b*.
method for diffusion impurity from doped oxide of pyrolytic origin on, P (3) 73*f*.
multilayer contact system for, including gold and copper layers, P (5) 142*j*.
with novel isolated diffused region arrangement, P (8) 246*f*.
opto-electronic, P (5) 142*j*.
oxide protected, P (5) 141*j*.
package for, P (3) 73*j*.
passivated, P (5) 142*a*.
and passivation, P (1) 19*c*.
planar, P (2) 51*k*.
planar, isolated by encapsulating oxide filled channels, P (9) 274*f*.
power bulk breakdown, P (5) 142*b*.
providing electrical connections to, P (8) 245*e*.
reduction of unwanted thermoelectric effects in, P (5) 142*f*.
with regions of different conductivity types, P (11) 345*e*.
silicon, passivating with sputtered tungsten oxide at low temperatures, P (2) 52*b*.
small area, P (4) 101*b*.
small geometry diffused junction, P (9) 273*g*.
surface, treating for improving noise characteristics, P (10) 310*j*.
thin film negative resistance, P (5) 143*b*.
thyristors, producing by Au diffusion in semiconductor material, P (1) 18*i*.
using glass and oxides as insulator for hermetically sealing junctions, P (8) 246*g*.
and devices using, P (2) 52*e*; P (3) 74*b*.
of diamond and zinc blende structures, band structures and pseudopotential form factors for, (8) 252*d*.
electronic properties, (6) 176*f*.
element, and apparatus for generating coherent radiation, P (3) 72*f*.
with organic silicone base cement, P (8) 246*h*.
switching, with heat-responsive central current path, P (8) 246*i*.
variable capacitance, P (8) 246*i*.
forming, by diffusion using crystal masking technique, P (3) 73*i*.
by double diffusion, P (3) 73*j*.
by masking and diffusion, P (6) 178*b*.
GaAs, doped with chromium and shallow acceptor impurity, P (10) 309*g*.
GaAS, with germanium connecting layer, P (5) 142*j*.
β-Ga_2O_3, electrical properties, (3) 72*d*.
housing, glass, with interior surfaces covered with alkali-free solder glass, P (5) 141*j*.
impact, on ceramics, (3) 71*f*.
insulator-, wafer, composite, P (5) 140*j*.
junction, with depletion layer, P (3) 74*a*.
junction devices, with semiconductor wafers having beveled edges, P (4) 101*g*.
junction laser device, P (4) 101*a*.
latching switch, with light-coupled triggering means, P (5) 143*a*.
layer, electrolytically binding together, P (11) 344*g*.
layers, epitaxial growth on metal supports, P (8) 246*b*.
making by ionic bombardment, P (9) 274*c*.
material, P (9) 275*a*.
apparatus for pyrolytic production, P (1) 17*j*.
compound, P (10) 310*g*.
deposition from gas phase, P (2) 50*j*.
doped crystalline layers, method of growing upon crystalline semiconductor bodies, P (2) 51*j*.
enhancing efficiency of recovery in perturbable disproportionation systems, P (3) 73*g*.
epitaxial deposition, P (1) 17*h*.
epitaxially deposited, method and apparatus, P (5) 141*e*.
in form of thin layer, determining specific resistance, P (7) 209*d*.
forming metal rectifying contact to, by displacement plating, P (11) 344*i*.
galvanomagnetic, thin layers, method of producing, P (2) 51*g*.
[Ge], epitaxially grown, method of doping, P (4) 100*j*.
intrinsic-appearing GaAs compound, P (6) 177*e*.
manufacture, P (1) 18*h*.
manufacturing at least one electrically isolated region of, P (6) 178*g*.
monocrystalline, production, P (2) 52*b*; P (5) 142*e*.
processes involving melting, P (2) 52*h*.
producing, and elements made from, P (5) 142*i*.
slicing, (3) 72*d*.
use of anodizing to reduce channelling on, P (3) 74*f*.
members, monocrystalline, with layers of respectively different conductance, method of producing, P (4) 100*g*.
monocrystalline, method for indiffusion of foreign material into, P (7) 209*e*.
producing by alloying metal into semiconductor body, P (9) 274*f*.
metal-oxide, study of interface-state time constant dispersion, (4) 113*g*.
metal-, tunneling, density of states in, (2) 49*f*.
-metal-semiconductor structure, P (9) 275*b*.
microhardness, high-temperature, measurement, (11) 346*e*.
miniature chips, machine for automatically testing and orienting, P (8) 244*i*.
monocrystals, method of producing epitaxial layers on, P (1) 18*h*.

Semiconductors (*continued*)
piezoelectric, nonlinear theory of current saturation in, (10) 323*h*.
pin, producing, P (7) 209*e*.
plate, manufacturing using molten zone on powder support, P (8) 245*b*.
polar, mobility and temperature of electrons, (5) 139*a*.
polar, resonant electron-phonon scattering in, (2) 50*g*.
polishing process, and reagent for, P (8) 245*g*.
reflectivity enhancement, thermal effects in, (1) 17*d*.
research, chemical problems in, (3) 71*a*.
rods, apparatus and method of producing by pulling from melt, P (4) 99*b*.
rods, monocrystalline, method of producing, P (2) 51*e*.
separation of ring ohmic contact microelectronic component, method, P (1) 19*b*.
small area junction, forming, P (6) 178*b*.
spark gap, P (7) 209*a*.
substrate, making reliable low-ohmic nonrectifying connection to, P (10) 310*a*.
sulfides, selenides, and tellurides, method of passivating supports for, P (3) 73*d*.
surfaces, (1) 16*i*.
testing, P (7) 210*f*.
III-V, electroreflectance and spin-orbit splitting in, (10) 320*i*.
III-V, intervalley-scattering selection rules in, (10) 322*i*.
thyristor, of *pnpn* type, P (5) 143*a*.
tunneling devices, magnetic field responsive, P (5) 141*d*.
wafers, applying uniform thickness of frit on, P (6) 177*i*.
with epitaxial layer, P (7) 210*g*.
method and apparatus for breaking into elementary pieces, P (11) 344*c*.
n-type silicon, anodic oxidation, P (7) 208*f*.
scribing method for, P (10) 311*b*.
substantially monocrystalline, process for production, P (2) 52*h*.
vapor polishing, P (5) 143*c*.
Separation. See also *Beneficiation; Classification; Flotation.*
continuous, of mixtures of substances, by fractional crystallization, process and apparatus, P (2) 53*g*.
electrostatic, apparatus, P (8) 251*b*.
of fine particles, method and apparatus, P (11) 348*a*.
gravity, of heavy mineral grains, simple and effective device for, (8) 248*g*.
of heavy minerals, method and apparatus, P (9) 279*e*.
high tension, role in beneficiation of beach sand minerals, (1) 19*j*.
of iron(II)-iron(III) mixtures by simultaneous paper chromatography and electrophoresis, (11) 347*g*.
of mixtures of particulate solid materials, P (2) 53*d*.
multistage, processes: I, ideal and squared cascades; II, thermodynamic efficiency, (5) 143*k*.
of nondiamond carbonaceous material from synthetic diamantiferous products, P (9) 261*h*.
particle-size, of clays, (7) 212*i*.
of particles in liquid suspension in hydrocyclone, P (2) 53*d*.
of particulate materials, method and apparatus, P (10) 316*a*.
phase, in vanadate glasses, (9) 264*d*.
of powders, new technique, (1) 22*g*.
prevention, during casting of composites, P (5) 135*b*.
of silicon in gallium phosphide, (4) 115*b*.
of substances, P (10) 318*g*.
of TiO_2, P (1) 26*a*.
of trivalent 4*f* rare earths from molten fluoride compositions with UF_3, (7) 205*c*.
of uranium from other elements by ion exchange chromatography, (2) 55*c*.
of uranium and thorium, P (4) 97*e*.
of zirconium from hafnium, P (11) 349*j*.
Separators, abrasive, P (5) 123*h*.
classifier-, particle, P (5) 144*d*.
cyclone apparatus, P (5) 144*e,g*.
dry, centrifugal, P (6) 179*d*.
electromagnetic iron, for ceramic slips and glazes, (6) 175*i*.
for granular materials, P (10) 317*h*; P (11) 349*e*
hydrocyclones, for slip classifying, (7) 206*e*.
magnetic, P (7) 214*e*; P (11) 345*f*.
magnetic, with combination field, P (8) 251*e*.
for materials of different densities, P (1) 20*c*.
for mixtures of solid particles, P (3) 77*j*.
multicell centrifugal dust, P (2) 53*f*.
shaking-funnel device, for gravity concentration of solid particles, P (5) 144*f*.
specific gravity, for solid particles, P (3) 77*j*.
vibratory, self-cleaning screen structure for, P (5) 144*e*.
wet, with venturi-shaped gas channels, P (1) 20*f*.
Serpentine, forsterite from: III, action of mineralizers on, (10) 317*g*.
minerals, from Manitoba, (9) 278*i*.
Setting. See *Binders.*
Settling. See *Sedimentation.*
Sewer pipes. See *Pipe.*
Shakers. See *Screens and sieves.*
Shales, aggregate, lightweight, sources in New Mexico, (7) 214*g*.
calcined, use and manufacture as pozzolan at Bhakra, (1) 2*j*.
carbonaceous clay, chemical and mineral composition and properties after firing, (6) 171*h*.

Shales (*continued*)
for lightweight aggregate in Appalachian region, Kentucky and Tennessee, (10) 301*j*.
of Ontario, processing problems, (11) 349*b*.
resources of Clark, Crawford, Cumberland, Edgar, Effingham, Jasper, and Vermillion Counties, Ill., (1) 10*f*.
Shipment. See *Transportation.*
Shock, explosive for formation of W and Al carbides, (2) 44*i*.
pre-, treatment, effects on synthesis of titanium and tungsten carbides, (7) 201*e*.
thermal, in ceramics, (2) 55*g*.
in disks of brittle materials, statistical analysis, (11) 357*c*.
tests in BeO, (4) 96*i*.
Shock resistance, thermal, ceramics, of Li_2O–Al_2O_3–SiO_2 system: V, glazes for lithia ceramics, (8) 242*a*.
high-temperature apparatus to obtain for refractories, (5) 134*h*.
and mechanical, of ceramics, (6) 188*j*.
Shrinkage, anomalous differential drying, of clay-quartz mixtures, (4) 106*d*.
drying, of clay, effect of graphite, (6) 172*j*.
effect, on prestressed concrete ring structure, (8) 228*b*.
in prestressed concrete, (9) 262*f*.
thermal, of microporous glasses, (1) 8*c*.
of zirconium diboride during sintering, (8) 238*h*.
Sieves. See *Screens and sieves.*
Silex. See *Quartz.*
Silica. See *Silicon, dioxide.*
Silicates, activation analysis for, (6) 181*a*.
alumino-, crystalline, method of ion exchanging, P (8) 251*g*.
ammonium, P (1) 25*h*.
arc emission spectrography applications to (6) 180*e*.
correlation between surface phenomena and flotation in, (7) 214*c*.
dicalcium. See *Calcium, dicalcium silicate.*
flotation: I, proposals for classification according to response; II, adsorption of ions on feldspar in relation to response, (5) 143*j,f*.
fluo-, manufacture, P (5) 148*j*.
infrared spectra, B (7) 225*f*.
liquid, ionic equilibria in, (4) 93*h*.
lithium-aluminum, thermodynamic properties, (4) 118*h*.
manganese-bearing chain, pyroxmangite, rhodonite, bustamite, and serandite, absorption spectra, (9) 279*g*.
materials, derivation of system of statistical models in study of, (10) 313*e*.
materials, X-ray spectral analysis, (11) 346*i*.
minerals, chemical interpretation of surface phenomena in, (7) 216*e*.
molten alkali, electrical conductance: I, experiments and results; II, theoretical discussion, corrections, (2) 39*a*.
ortho-, isomorphous, of rare earths, (7) 219*a*.
ortho-, with olivine structure, magnetic properties, (10) 322*i*.
pure alkali metal, and finely divided amorphous silica solution, process, P (1) 26*a*.
rocks, partial analysis by atomic absorption, (1) 22*i*.
silica rich binary, melts and glasses, microstructures, (4) 108*c*.
systems, solid state reactions, (7) 221*b*.
tin-bearing, from skarn in Cassiar district, northern British Columbia, (9) 279*a*.
tricalcium, decomposition with boric oxide, (7) 194*e*.
vibrational spectra, (1) 33*i*.
Silicides, crystalline, producing, P (2) 47*j*.
metallic, low-temperature synthesis by amalgam method, (8) 254*i*.
mono-, of certain 3d transition metals at low temperatures, valency states of atoms in, (9) 288*c*.
preparation, properties, and crystal chemistry, B (4) 119*i*.
of rare-earth metals, vacuum-thermal production, (9) 288*b*.
Silicon, amorphous, (5) 149*j*.
amorphous, optical properties and electronic structure, (5) 156*c*.
carbide. See also *Refractories.*
α- and β-, ultraviolet reflectivity, (11) 357*j*.
α-, crystals, growth from various chromium alloys by traveling solvent method, (4) 110*i*.
applications, (9) 266*a*.
β-, crystals, method of seed-pulling from melt containing Ag, and product, P (3) 73*e*.
coatings by vapor phase reaction at high temperature, (11) 353*d*.
colloidal, fluidized bed process for preparation, P (5) 135*a*.
crystal, doped with boron, electron spin resonance parameters in 6H polytype of, (3) 80*e*.
crystal growth, by vapor phase reaction at high temperature, (11) 353*e*.
crystals, furnace for making, P (1) 24*h*.
cubic, single-crystal films, growth on silicon, (5) 153*c*.
elastic properties, (5) 151*c*.
epitaxial growth, (7) 207*j*.
epitaxially growing by pyrolytically decomposing SiH_4 and CH_4, P (8) 245*f*.
etching, P (11) 344*h*.
film, epitaxial growth on silicon substrate and crystal structure, (11) 352*d*.
finely divided, production, P (1) 14*f*.
formation by chemical vapor deposition, (3) 81*f*; correction, (7) 217*g*.
14H, crystal structure, (10) 319*a*.

Silicon, carbide (*continued*)
heat-resistant and oxidation-proof bodies, P (5) 135*c*.
igniter, P (6) 175*b*.
lattice contractions from irradiation, (8) 254*e*.
layer, epitaxially growing on seed by pyrolytic decomposition of hydrocarbons or mixtures of silanes and hydrocarbons, P (9) 273*h*.
layers, producing on silicon substrates, P (9) 274*g*.
luminescent materials, P (4) 101*a*.
and nitride materials, mechanical properties, (11) 338*j*.
polycrystalline, creep, (3) 79*d*.
production by thermal decomposition of methylchlorosilane vapor, (1) 12*a*.
products, with silica bond as function of environment, phase composition, (9) 268*f*.
self-bonded, lattice contractions associated with neutron irradiation of, (8) 254*e*.
systems. See *Systems*.
technical production, role of sodium chloride in, (1) 12*c*.
treatment, P (5) 136*d*.
ultrapure, production, P (1) 26*c*.
vapor-deposited, deposition and microstructure, (9) 267*c*.
with wurtzite structure, growth, luminescence, selection rules, and lattice sums, (9) 282*g*.
chemical-vapor-deposited, on sapphire, observation by transmission electron microscopy, (5) 156*c*.
chlorides, preparation, P (7) 215*a*.
content, free, of some Indian rocks and minerals, quantitative estimation, (1) 34*d*.
crystal, specific resistance, measurement by measuring breakdown voltage, P (5) 142*c*.
crystals, vapor growth, apparatus for producing, P (6) 177*a*.
determination by extractive-conductometric method, (10) 314*b*.
diffusion coefficients in silicon and silicon compounds, determination, (11) 354*e*.
difluoride, chemistry, (4) 106*f*.
dioxide. See also *Cristobalite; Glass; Quartz; Quartzite; Refractories; Sands*.
-alumina, preparation, P (9) 279*e*.
amorphous, reststrahlen reflection characteristics, (7) 221*f*.
aquasols, preparing, P (6) 183*a*.
cellulated, production, P (11) 349*i*.
copper-, crystals, recrystallization in, (10) 325*b*.
contamination during high-temperature degassing in Vycor tubes, (3) 79*b*.
density, statistical method for checking, (9) 277*f*.
dispersed particles, effect on recovery and recrystallization of deformed copper crystals, (10) 319*g*.
distribution in Pujada laterite of Mati, Davao Province, Mindanao Island, Philippines, (2) 56*h*.
and feldspar liquid mixtures, structural characteristics, (6) 189*d*.
films, doped with phosphorus, (7) 208*b*.
films, evaporated, structure and effect on electrical and optical properties, (10) 308*d*.
films, fast etching imperfections in, (7) 207*b*.
films, formation by oxygen-ion bombardment, (9) 282*a*.
films, growth, (8) 254*f*.
films, on silicon, reflectivity thickness corrections for, (11) 356*d*.
films, tritium-labeled field-induced proton transport in, (11) 357*h*.
fine, effect on porcelain properties, (2) 48*i*.
finely divided, process for changing properties, P (7) 215*d*.
finely divided amorphous, and pure alkali metal silicate solution, process, P (1) 26*a*.
free, reduction in vitreous body, (3) 70*e*.
fused, boats, cristobalite formation on, and relation to GaAs crystal growing, (7) 207*c*.
fused, crystallization resistant, formed by addition of silicon, P (6) 170*h*.
fused, doped, determination of hydrogen diffusion in, from fluorescence, (7) 195*j*.
fused, irradiated doped, thermoluminescence, photoconduction, and optical absorption, (7) 197*e*.
fused, physical limitations on performance in high-frequency ultrasonic and acoustooptical devices, (6) 176*g*.
fused, spin relaxation of atomic hydrogen in, temperature dependence, (10) 325*b*.
gel-asbestos compositions, P (7) 215*d*.
high-dispersion fine-pored, of magnesium hydrate and oxide, increase in strength with SiO_2 addition, (5) 125*c*.
high-purity synthetic vitreous, analysis, (3) 63*e*.
infrared absorption, dependence on disordering and temperature, (8) 252*j*.
internally nucleated vitreous, crystallization kinetics, (9) 280*b*.
layers, grown under bias, improved properties, (7) 207*d*.
and NiO equimolar mixture, mineral phases at high pressure and high temperature, (3) 85*g*.
photoemission of electrons from silicon and gold into, (9) 285*b*.
pigments, and production, P (6) 183*d*.
polymorphic transformation, effect of mineralizers, (7) 217*d*.
preventing activation in ore flotation, P (8) 251*i*.

Silicon, dioxide (*continued*)
production in form of hollow spheres, P (8) 251*f*.
pyrogenic, production, P (10) 318*f*.
"reduced" fused, absorption, luminescence, and excitation spectra, (5) 120*g*.
sand briquets and pellets, as replacement for quartzite, (7) 203*h*.
in seawater, control by silica minerals, (4) 115*f*.
in silicate rocks and minerals, determination by atomic absorption spectroscopy, (9) 270*b*.
+ SiC reaction at elevated temperatures: I, kinetics and mechanism, (3) 86*g*.
solid state reactions with Al_2O_3, MgO, CaO, Fe_2O_3, and ZrO_2, (7) 221*b*.
in sparingly soluble fluoride slags, (10) 314*b*.
sputtered, for multilayer interconnects, (10) 308*b*.
systems. See *Systems*.
thermal behavior and application to dental investments, (11) 341*e*.
thin films, thickness measurements, (11) 356*c*.
with tungsten inclusions, viscous behavior, (7) 204*c*.
vitreous, internal friction in vibrating granular reeds and application to, (9) 283*g*.
vitreous, vibrational spectra, (11) 358*a*.
-X, thermal behavior, and relation to natural silica minerals, (7) 222*c*.
and zirconium oxide mixture, process for production, P (1) 25*j*.
elementary, reactions, (5) 157*e*.
epitaxial deposition on alpha-alumina, P (10) 309*d*.
excess, in reactively sputtered silicon nitride, films, (11) 352*g*.
films, heteroepitaxial, grown on sapphire, space-charge-limited currents in, (5) 158*g*.
fluoride, force field for, (10) 321*h*.
hydride and deuteride, spectra, (7) 221*e*.
nitride, bodies, effect of binder, grain size, sintering temperature, and atmosphere on moduli of rupture, (2) 43*i*.
commercially available, dissolution in liquid iron, (11) 351*f*.
determination of nitrogen undecomposable by acids, (1) 11*e*.
effects of additives on sintering, (2) 44*d*.
reaction-bonded, technology and engineering applications, (11) 339*e*.
shaped body, glazing method, and article, P (10) 304*g*.
shapes, production, (7) 202*i*.
nitride, systems. See *Systems*.
whiskers, P (11) 340*g*.
oxide, films, structural evaluation, (4) 116*a*.
infrared reflectivity, dependence on layer thickness, (10) 319*d*.
systems. See *Systems*.
thin films, dielectric constant and conductivity, (5) 150*i*.
oxynitride, production, P (3) 69*c*.
phase diagram, to 200 kbars, 1000°C, (6) 187*d*.
phosphorus diffusion in, and making of *p-n* junction semiconductor detectors, (7) 216*f*.
phosphorus doped, effect of doping on ESR in, (7) 217*b*.
phosphorus doped, electron spin resonance at low temperatures, (3) 80*f*.
separation, with ammonium molybdate, and successive determination, (9) 286*a*.
separation, in gallium phosphide, (4) 115*b*.
and SiO_2 films, deposited through rf and dc sputtering, reemission coefficients, (5) 139*b*.
-SiO_2 interface, effect of metal-semiconductor work function difference on calculation of surface charge density of, (5) 151*j*.
grown by vapor deposition, surface states of, (8) 257*a*.
investigation using MOS structure, (3) 82*c*.
single-crystalline, vacuum deposited on sapphire, (10) 309*e*.
single crystal, oxygen-doped, heat treatment, (5) 158*c*.
pulled by eccentric seeding method, (5) 139*j*.
for semiconductor, apparatus and method for producing, P (6) 177*a*.
Na_8Si_{46} and Na_xSi_{136} ($x < 11$), clathrate structure, (4) 106*g*.
spectrochemical determination in fluorite, (3) 70*f*.
steam-oxidized, stacking faults in, (10) 325*c*.
-sulfur compounds, chemistry, (5) 150*b*.
surface, oxide films on, (1) 16*b*.
systems. See *Systems*.
tetrachloride, gaseous, X-ray absorption spectra in *K* shell of Si in, (9) 286*d*.
tetrahalides, production, P (2) 57*b*.
thermally oxidized, effects of heat treatment, (5) 151*j*.
thermal properties: I, effect of temperature on infrared reflection spectra of quartz cristobalite, and vitreous silica; II, thermal expansion coefficient of vitreous, (3) 87*d,e*.

Silicone, rubbers, room-temperature-cured, use in ceramic ware molds, (8) 242*c*.

Sillimanite. See also *Refractories*.
–andalusite, kyanite, sillimanite, mining, processing uses and specifications, B (1) 358*h*.
electron diffraction study, (1) 27*d*.
selective flotation, (1) 25*f*.

Siloxanes, organopoly-, methods of reproducibly spray drying, P (8) 236*a*.

Silver, -barium titanate rectifying junctions, (5) 137*i*.
bromide, crystals, twinned, transmission electron microscopy of, (4) 118*b*.
compositions, containing novel vitreous binders and vehicle, P (2) 42*c*.

Silver (*continued*)
and gold, single-crystal high-purity films, epitaxial growth on MgO in ultrahigh vacuum, (5) 152*e*.
halide, crystals, permanent photoinduced conductivity in, (10) 324*h*.
nuclei, electron-nuclear double resonance, in AgCl + Fe^{3+}, (9) 282*a*.
radiation-induced atomic, in Pyrex and sodium tetraborate glasses, (5) 128*g*.
radicals, trapped in metaphosphate glass at room temperature, (5) 127*g*.
Ag_3AsS_3, synthetic proustite, crystal for optical mixing, (4) 117*b*.
Ag_2PbO_2 and $Ag_3Pb_2O_4$, bondings in, (4) 106*j*.
systems. See *Systems*.

Silvering. See *Glass*.

Single crystals. See *Crystals*.

Sintering, of alumina containing small concentrations of MgO, (5) 133*i*.
of alumina, criteria for selection of additives for theoretical density, (1) 27*i*.
pure, homodispersed particles, effect of rate of temperature rise, (1) 28*a*.
to theoretical density in vacuum, effects of residual gas on, (1) 28*d*.
in As-S-Se system, (1) 32*d*.
behavior, of dolomites of different petrographic nature, (1) 23*d*.
of plutonium dioxide, (8) 257*i*.
of UO_2, importance of particle properties, (7) 202*c*.
of BeO, (6) 173*i*.
III, hot-pressing of beryllia derived from hydroxide, (5) 134*b*.
powders, studies, (3) 68*c*.
studies, (4) 96*h*.
of boron nitride powders, during hot-pressing, (7) 203*i*.
of corundum, under pressure, kinetics, (6) 186*h*.
of ferroelectric ceramics by hot-pressing, and electrical properties, (11) 342*g*.
final-stage, of Y_2O_3, grain-boundary segregation in, (1) 29*e*.
of glass, effect of particle shape, on kinetics, (11) 333*i*.
of graphite powders during thermochemical treatment with carbide-forming elements, (8) 239*a*.
induction, of refractory carbide articles, P (2) 47*h*.
initial, of calcia, effects of water vapor, (2) 58*c*.
equations, shape sensitivity, (11) 356*b*.
of Mn_xO-Al_2O_3, (9) 283*c*.
kinetics, based on geometric models, (5) 158*d*.
in BeO, (3) 67*h*.
of MgO and UO_2 powders, (8) 293*c*.
liquid phase, of refractory oxides, (3) 67*h*.
low-temperature of BeO powders, studied by crystallite growth, and inhibition by adsorbed phosphate, (10) 319*c*.
of magnesium fluoride, (1) 25*g*.
mechanisms, (1) 32*b*.
of Moldavia and Dobrogea dolomites, technology, (9) 269*d*.
of oxides, kinetic characteristics, (7) 219*b*.
of porous parts from high-melting-point compounds, relations in, (11) 339*c*.
pressure, apparatus, for ceramic material, P (8) 247*f*.
pressure, of NaCl and other ionic materials, (1) 31*b*; (5) 151*c*.
rate of UO_2 in hydrogen, qualitative relations with observed microstructures, (8) 256*j*.
reduced pressure, of MgO as high frequency insulator, (11) 355*j*.
of Si_3N_4, effects of additives, (2) 44*d*.
sinterability studies on various BeO powders, (3) 68*b*.
sintered articles, dense, apparatus for manufacture, P (1) 20*b*.
sintered bodies, grain orientation in, under effect of intermediate layers, (8) 254*c*.
soft ferrites, kiln for, (5) 138*b*.
of sulfate-derived BeO, effects of powder characteristics, additives, and atmosphere, (4) 96*c*.
by surface diffusion, rate equation for, (10) 324*e*.
of TiO_2, with rutile crystals, MnO, and Na_2O as additives, (6) 173*j*.
of UO_2, Dorn method in study of initial phase of, (5) 151*e*.
effect of TiO_2 additions, (4) 108*g*.
effect of vanadium oxide additions, (7) 201*c*.
of UO_2 ceramics: I, preparation by low temperature sintering; II, determination of specific surfaces of UO_2 and initial materials for preparation; III, dispersity and microagglomerate state of UO_2; IV, application of activators of sintering, (3) 68*c*.
of UO_2 pellets, high density, use of carbon monoxide in, (10) 304*i*.
ZrB_2, shrinkage during, (8) 238*h*.
of ZnO: I, densification and grain growth; II, density decrease and pore growth during final stage of, (10) 325*i*.

Size reduction. See *Crushing; Grinding*.

Slags, attack, on carbon-bearing basic refractories, (1) 12*e*.
blast furnace, as aggregate for concrete, (4) 91*b*; discussion, (5) 124*j*.
blast furnace, use in cement mortar and concrete, (6) 165*k*.
calcium and magnesium in, after separation of R_2O_3 and P_2O_5 with aqueous suspension of ZnO, (10) 313*h*.
as cement aggregate, effect on steel, (4) 92*g*.
oxygen activity, methods and apparatus for determining, P (4) 97*a*.
phosphorus, for hydrothermally hardening binders production, (6) 165*k*.

Slags (*continued*)
reaction, on magnesia brick: II, properties after slag penetration, (10) 303*i*.
Rourkela, test investigation, (8) 229*b*.
sitalls, influence of phase composition on physicochemical properties, (1) 11*c*.
sparingly soluble fluoride, silica in, (10) 314*b*.
synthetic, rich in manganese, surface tensions, (3) 87*h*.
titaniferous, in systems TiO_2–Al_2O_3–SiO_2–CaO–MgO and TiO_2–Al_2O_3–FeO–SiO_2–CaO–MgO, liquidus temperatures, (9) 284*a*,*b*.
titanium-containing blast-furnace, as component of cement charge, (3) 63*a*.
Slaking. See *Lime, hydration of*.
Slip casting, B (10) 329*j*.
application of products from reactions of cationic materials with agar to, (9) 271*b*.
articles, method, P (11) 341*e*.
characterization and evaluation, (10) 305*h*.
classifying by hydrocyclones, (7) 206*e*.
continuous, line, for sanitary ware, (4) 98*b*.
of glass powder, (1) 7*f*.
inhomogeneities in, formation and causes, (10) 305*f*.
mechanism of, (3) 70*g*.
theory and practice, (1) 15*h*.
of TiC components, (2) 46*b*.
use and effect of cellulose ether binders, (10) 305*d*.
workable, preparation, and deflocculation of kaolins, clays and ceramics bodies, (10) 305*e*.
of zirconium boride, (2) 46*d*.
Slips. See also *Suspensions*.
plaster, apparatus for measuring consistency, (4) 91*j*.
porcelain, control of thixotropy of, and effect of feldspars on slip properties, (6) 175*e*.
properties, practical control, (1) 15*e*.
Smelting. See *Metallurgy*.
Soapstone. See *Talc*.
Soda or Soda ash. See *Sodium, carbonate*.
Sodium. See also *Alkalis*.
aluminogermanate, melts, with Na_2O/Al_2O_3 ratio equal to unity, structure, (5) 128*h*.
aluminogermanate melts, with Na_2O/Al_2O_3 ratio greater than unity, structure, (5) 128*b*.
aluminum, systems. See *Systems*.
borohydride, reaction with sulfur, (3) 85*j*.
bromate, nuclear-spin pumping study of relaxation and defects in, (9) 284*j*.
bromide, containing barium bromide, thermoelectric power and ionic conductivity, (2) 50*j*.
bromide and iodide, high-temperature heat contents and entropies, (4) 111*j*.
bromide, systems. See *Systems*.
calcium metaborate, P (10) 318*h*.
carbonate, manufacture by use of CO_2, P (5) 149*a*.
production, P (7) 215*b*.
reactions with transition-metal carbides, (5) 149*g*.
systems. See *Systems*.
chloride, cleavage faces, thermal etching in vacuum, (5) 159*b*.
crystal, measurement of charge on edge dislocations, (1) 30*b*.
crystals, potential differences produced by plastic deformation at 4.2°K, (4) 114*i*.
crystals, use as standard measure of microhardness, (10) 316*d*.
electric field, dislocations movement in, (4) 113*g*.
evidence for L bands in, (10) 321*c*.
films, deposited on silica glass, orientation effects of applied dc field on, (5) 156*f*.
fused, galvanostatic cathodic reduction on graphite, Ni, Fe, or liquid aluminum at 800° to 950°C, (7) 217*g*.
grain boundary energies in rigid lattice approximation, (6) 186*a*.
monodisperse aerosols, preparation, (1) 31*j*.
and other ionic materials, pressure sintering, (5) 151*c*.
precise vibrational frequency distributions and second-order Raman spectrum and specific heat of, (8) 256*c*.
pressure sintering, (1) 31*b*.
reaction with chlorides of europium (III), holmium, and erbium, (10) 324*f*.
role in technical production of silicon carbide, (1) 12*c*.
single crystals, Schottky disorder and lattice relaxation due to X irradiation at room temperature, (11) 356*j*.
systems. See *Systems*.
transition in, searched to 25 kbars, (11) 356*j*.
cryolite, complex formation with hexafluoroaluminates of potassium, rubidium, and cesium, (9) 280*e*.
determination, in important materials in silicate technology, effect of sulfate, oxalate, and perchlorate ions on, (7) 212*j*.
determination, method and apparatus, P (11) 347*j*.
diffusion, in Na_2O–P_2O_5–SiO_2 liquids, (5) 151*a*.
disilicate, crystallization and melting kinetics, (1) 27*i*.
di-, dimolybdate, crystal structure, refinement, (5) 157*i*.
ferrites and aluminates, crystal structures, chemical properties, and phase diagrams, (6) 183*h*.
fluoride, porous pellets, process for making, P (6) 183*e*.
properties of F centers in, (8) 256*i*.
systems. See *Systems*.
halides, melting points, effects of pressure on, (10) 320*b*.
ions, in glass, stress-induced migration and partial molar volume, (5) 128*a*.

Sodium (*continued*)
metaniobate, stoichiometry, (7) 221*i*.
metasilicate, anhydrous, preparation, P (5) 148*g*.
pentahydrate product, and preparation, P (7) 215*e*; P (9) 279*f*.
structure, reinvestigation, (1) 31*h*.
metatitanate, enthalpy of formation, (9) 282*c*.
niobate, heats of transition in, (9) 283*a*.
nitrate, metamagnetism, (11) 354*d*.
oxide, activities in molten sodium sulfate and sodium silicates, (7) 197*i*.
oxide-SiO_2 solutions, activities calculation, (1) 5*a*.
phosphate, pure molten, application of rigid sphere model, (2) 57*d*.
polyuranates, anhydrous, (6) 183*j*.
reaction with graphite at 400°, (6) 188*d*.
silicate, binder in various compositions, (5) 125*a*.
electrochemical behavior at high temperature, (1) 6*a*.
speeding up production, (8) 250*f*.
systems. See *Systems*.
vitreous, thermoluminescence in, (4) 93*i*.
vitreous, ultraviolet absorption bands, development during melting, (9) 280*c*.
$NaAl(CO_3)(OH)_2$, dawsonite, crystal structure, (4) 107*e*.
$NaAlSi_2O_6$, dehydrated, high-temperature heat contents and entropies, (6) 186*h*.
$Na_{0.5}Bi_{4.5}Ti_4O_{15}$, cation ordering in, (4) 106*b*.
$Na_2CaSi_2O_6$, crystal data, (2) 57*g*.
$NaGdO_2$: Eu, luminescent properties, (11) 354*f*.
$Na_2O \cdot 2CaO \cdot 3SiO_2$, polycrystalline, volume and grain boundary diffusion of ^{22}Na and ^{45}Ca in, (2) 60*a*.
NaO_2, dissociation energy, (3) 80*d*.
Na_2ZrO_3, X-ray and optical crystallographic data, (11) 358*b*.
Na_2ZrSiO_5, solid state synthesis, (11) 356*e*.
sulfate and chromate, phase diagrams, to 45 kars, (6) 187*d*.
systems. See *Systems*.
tetraborate minerals, hydrated, NMR studies: I, boron-oxygen polyions in borax and tincalconite; II, ^{23}Na sites in borax and tincalconite, (5) 155*j*, 156*a*.
tripolyphosphate, with high content of phase I material, manufacture, P (9) 279*b*.
tripolyphosphate, preparation, P (8) 251*h*.
trisilicate, preparation, P (3) 78*a*.
tungstate and molybdate, phase diagrams, to 45 kbars, (7) 220*j*.
Soils, aluminous lateritic, of Lutawon Basin area, Nonoc Island, Surigao Province, Philippines, (2) 56*e*.
analysis by flame spectrophotometer, (6) 179*i*.
clayey sandy, electrochemical strengthening, (1) 24*i*.
and clays, research, recent developments, (3) 86*a*.
Solar batteries or **Solar cells.** See *Cells, photovoltaic*.
Solar furnaces. See *Furnaces*.
Solder, method, for providing standoff of device from substrate, P (10) 311*e*.
Soldering. See also *Seals and sealing*.
brazing, ceramic to metal, means for, P (8) 244*c*.
lead telluride thermoelectric generator elements, P (8) 243*j*.
preform, P (2) 40*f*.
to form ohmic contacts in semiconductor devices, P (11) 344*f*.
graphite to metals, method, (1) 22*b*.
Solidification, characteristics, in continual casting of uranium carbide, (6) 174*c*.
points, of refractory oxides, measurement with solar furnace, (5) 154*e*.
Solid solutions. See *Solutions, solid*.
Solid state, chemistry, whence, where, and whither, B (4) 121*f*.
reactions, determination of kinetic parameters in, (7) 220*b*.
process and apparatus for effecting, P (7) 205*d*.
of silicate systems, (7) 221*b*.
between SiO_2-Al_2O_3, MgO, CaO, Fe_2O_3, and ZrO_2, (7) 221*b*.
in system cadmium-magnesium-tin oxides, (3) 86*b*.
in system SiO_2-Al_2O_3-MgO, (6) 176*f*.
relay devices, making from tellurides, P (11) 344*c*.
studies, of tungsten trioxide and their significance to tungsten bronze theory, (5) 158*g*.
translating device, comprising irradiation implanted conductivity ions, P (8) 246*b*.
Solids, crystalline, empirical relation between shear strength, pressure, and temperature, (5) 152*c*.
crystalline, X-ray diffraction and optical observations, up to 300 kbars, (3) 88*a*.
dielectric properties, (6) 176*e*.
electrical conductivity, (3) 71*f*.
emittance measurements above 2000°C, (4) 109*f*.
-gas reactions, volumetric apparatus for studying, (3) 76*b*.
heating curves obtained by solar furnace, (4) 111*b*.
with high ionic conductivity in group I halide systems, (7) 221*c*.
high-melting, in fine particle form, heat treatment of, P (2) 47*b*.
ionic, densification by cold-pressing at ultrahigh pressures, (11) 351*h*.
interatomic forces in, (10) 322*f*.
/liquid interface, factors involved in adsorption at, (4) 110*i*.
monocrystalline and polycrystalline, of cubic symmetry, relations between nonlinear elastic constants of, (11) 356*c*.
non-metallic: Vol. 2, inorganic glass-forming systems, B (5) 161*d*.
nonmetallic, rheological properties, (11) 357*i*.

Solids (*continued*)
reactions in and on, B (3) 90*h*.
space charge conduction in, B (9) 290*h*.
structure, theoretical ideas, (3) 81*h*.
surface, functional groups on, (10) 321*a*.
Sols. See *Colloids*.
Solubility, of disilicides of transition metals in $MoSi_2$ and WSi_2, (11) 339*h*.
of GaAs in metallic solvents, (7) 208*b*.
of glasses in system silica-sodium oxide-cesium oxide, (6) 169*c*.
of group IV impurities in solution grown gallium phosphide, (4) 116*b*.
of gypsum, at 100° to 140°C, (11) 331*j*.
high-temperature, of uranium in uranium monocarbide, (3) 86*c*.
of iron in TiO_2, (1) 32*f*.
of MgO and UO_2 in MgF_2, (4) 115*j*.
mutual solid, of $PdAs_2$, $PdSb_2$, PtP_2, $PtAs_2$, $PtSb_2$, $PtBi_2$, and $AuSb_2$, (7) 221*j*.
of oxygen, in molten carbonates, (11) 356*c*.
products, of colloidal hydrated calcium silicates, (11) 350*h*.
retrograde, of lead in *n*-type PbS, (6) 188*a*.
of ruthenium, in soda-silica glasses, (4) 93*j*.
of transition metal oxides in zinc oxide, (4) 116*b*.
of zinc, sulfur, selenium and tellurium in gallium phosphide, (3) 86*c*.
of zirconium silicate, in glazes during firing, (3) 70*b*.
Solutions, concentrated aqueous, and molten salts, electrical conductance of, correlation through free volume transport model, (11) 352*g*.
dis-, of α-$CaSO_4 \cdot {}^1/_2H_2O$ crystals in water, microscopic study, (1) 30*g*.
anodic, of iron in acids, effect of plastic deformation, (7) 195*b*.
of Cr in iron due to corrosion of QC refractories with added Cr_2O_3, (9) 269*c*.
of silicon nitride, commercially available, in liquid iron, (11) 351*f*.
of Zr in HF-H_2SO_4, rotating disk study, (4) 115*j*.
light-sensitive, for silk-screening, (8) 247*c*.
molten salt, reactions in: I, uranate and neptunate formation in molten lithium nitrate-sodium nitrate, (4) 115*a*.
rate, of oxides in liquid silicates, (9) 286*b*.
Solutions, solid. See also *Equilibrium studies*.
alkali halide, lattice distortions and field gradients in, (10) 322*c*.
analcite, melting, in system $NaAlSiO_4$-$NaAlSi_2O_6$-H_2O, (2) 58*i*.
$BaFe_{2x}Al_{2-x}O_4$ and $BaGa_xAl_{2-x}O_4$, studies, (7) 215*j*.
of $BiFeO_3$ with $Pb(Ti,Zr)O_3$, dielectric properties at high temperature and high frequency, (9) 280*f*.
of calcium, barium, and strontium dibasic compounds, (6) 164*i*.
of calcium orthophosphate in dicalcium silicate, (6) 188*f*.
of CaO and Y_2O_3 in ZrO_2, volatilization, (9) 288*d*.
in $2CaO \cdot SiO_2$-$K_2O \cdot CaO \cdot SiO_2$ system, (2) 36*i*.
compounds, ferromagnetic lanthanide chalcogen, modifying Curie temperature of, P (6) 178*f*.
dilute, among alkali halides other than cesium salts, calculated heats of, (10) 319*e*.
effect on Curie temperature in Fe_3O_4-Mn_2O_3 and Fe_2O_3-Cr_2O_3 systems, (11) 352*c*.
of fine grain metallic carbides, and method, P (8) 241*e*.
in GeTe-InTe system, (3) 86*a*.
Fe_3O_4-γ-Fe_2O_3, magnetic aging effect, (3) 83*g*.
limited, of uranium and thorium dicarbides, (6) 187*a*.
MnP-MnAs, magnetic and structural study, (6) 176*d*.
with ordered perovskite structure, relationship between magnetic Curie points and cell sizes of, (7) 221*d*.
Orville's microcline-low albite, series, axial angle determinations in, (6) 183*j*.
PuC and UC-PuC, thermal expansion, (5) 134*e*.
relations, between wolframite and scheelite, (6) 188*d*.
rutile, and reaction diagram in Ti-Ni-Sb-O system, (7) 219*e*.
of scheelite with other $R^{III}WO_4$-type tungstates, (6) 188*g*.
strontium titanate, containing mixed cations, dielectric relaxation in, (7) 216*e*.
systems, based on $NaNbO_3$, dielectric and X-ray studies, (5) 150*j*.
in system $SrTiO_3$-(La_2O_3:$3TiO_2$), (1) 32*d*.
Ti-O, reaction rates with $TiCl_3$ in molten NaCl, (4) 114*j*.
of tricalcium silicate, chemical and structural studies on formation, (2) 36*g*.
of tricalcium silicate, polymorphism, (1) 31*g*.
uranium monocarbide-zirconium monocarbide, thermal expansion, (6) 190*e*.
of UO_2-Y_2O_3, oxidation kinetics, (4) 113*e*.
of UO_2-Y_2O_3 and UO_2-La_2O_3 equilibrium oxygen pressures, (1) 29*b*.
Sonics, for testing ceramic materials, (4) 103*c*.
ultra-, for control of carbonate rock quality, (3) 77*e*.
for high temperature dynamic modulus measurements, (7) 212*h*.
for nondestructive testing of electrial porcelain, (6) 181*a*.
speed diamond machining, (3) 61*f*.
techniques for studying saline liquid at high temperatures, (7) 216*h*.
testing of solid-propellant rocket motors, (9) 277*c*.
time delay, new electronic component, (10) 309*d*.

Sorel cement. See *Cement, magnesium oxychloride.*
Sorption. See also *Absorption; Adsorption.*
alterno-: II, inorganic oxides at high temperatures, (6) 183*h*.
cesium, properties, of Indian vermiculites, (7) 222*b*.
dynamic, by hygroscopic salts, (11) 351*j*.
on porous titania, (1) 33*a*.
Sound, isotropic, velocities, approximate method for computing using refractive index data, (2) 57*f*.
velocity, in dielectric crystals, temperature and frequency dependence of, (8) 257*c*.
velocity, longitudinal, in *n*-type GaSb, (10) 320*e*.
waves, 3 Ghz, attenuation in ZnO, (11) 350*j*.
wave interactions in InSb, (11) 342*j*.
Spacecraft, aircraft nose radome with ceramic cover mounted on metallic framework, P (11) 339*g*.
guided missile radomes, evaluation of glass-ceramics for, (3) 63*h*.
rocket motor, infrared method of inspection, (9) 276*a*.
nuclear, reactor fuel element for, P (7) 205*b*.
solid-propellant, ultrasonic testing, (9) 277*c*.
rocket nozzle, insert, thermal shock resistant, P (8) 241*g*.
multislot film cooled pyrolytic graphite, P (3) 69*e*.
and skirts, thermal retardation coatings in, (2) 46*a*.
Spalling. See *Refractories.*
Spark plugs, with conductive glass seal electrode of glass, copper, and zinc, P (2) 52*f*.
connector and insulating sleeve for, P (4) 99*g*.
creepage, with low voltage igniter seal, P (1) 17*e*.
with insulator tip coated with lead oxyhalide, P (1) 19*e*.
with insulator tip coated with spinels of Al and Co oxides, P (5) 143*b*.
and manufacture, P (6) 175*b*.
process for making, P (2) 52*e*.
seal, with lower coefficient of expansion than ceramic insulator core, P (1) 19*d*.
with sealing glass mixture with graphite and iron, nickel, or cobalt, P (4) 101*d*.
visual indicating, with integral gas lamp, P (1) 19*d*.
Specific gravity. See *Density.*
Specific heat. See *Heat, capacity.*
Specific surface. See *Surface.*
Specifications, for burned clay tile for use in lining irrigation and drainage works, (3) 66*h*.
writing principles, B (5) 161*d*.
Spectra, absorption, of europium iron garnet between 1900 and 5400 cm^{-1}, (3) 78*g*.
absorption, luminescence, and excitation, of "reduced" fused silica, (5) 126*g*.
of manganese-bearing chain silicates pyroxmangite, rhodonite, bustamite, and serandite, (9) 279*g*.
of optically pumped ruby: I, experimental studies in excited states; II, theoretical analyses, (10) 318*j*.
biotite mica, hydroxyl-stretching region, (8) 254*i*.
dielectric relaxation, in metal-oxide-plasma capacitor, (3) 80*a*.
diffuse reflectance, of thiometallates and oxides of chromium family, (3) 80*c*.
electron energy, of refractory Cr compounds, (9) 282*a*.
EPR, of irradiated two-component glasses, (10) 299*c*.
electronic, of crystalline lithium fluoride, (8) 253*c*.
electronic absorption, of Rh_{II} in Zn WO_4, (6) 185*i*.
electronic absorption, of Ni(II) in cubic perovskite fluorides, concentration and exchange effects, (7) 217*h*.
electronic Raman, of $Ce^{3+}/CuWO_4$ at 77° and 2.2°K, (7) 217*h*.
electronic Raman: I, Raman transitions of trivalent Yb, Eu, and Nd in YGaG, (11) 352*c*.
electronic and vibrational absorption, in cordierite, (6) 185*j*.
electroreflectance, effect of strong electric fields on, (11) 352*e*.
emission, of impurity activated (ZnCd)(S,Se,Te) phosphors: I, copper activated phosphors, (7) 207*j*.
emission and excitation, of Eu_2O_3 compared with Y_2O_3:Eu phosphor, (8) 253*e*.
Er^{3+}, in single crystals of Y_2O_3, (5) 158*b*.
excitation, of ruby and sapphire, (7) 222*j*.
exciton, of ZnO, (9) 282*h*.
far infrared, of carbonate minerals, (5) 152*e*.
far-infrared absorption, of sodium silicate glasses, (8) 234*i*.
fluorescence, of sharp cutoff filters, (5) 145*b*.
of gallium monoxide, (5) 152*b*.
impurity-induced near-infrared, as source of information about frequency distributions of alkali halides, (10) 322*c*.
infrared, of Aerosil silicas, investigation of 1800 to 1400 cm^{-1} region of, (3) 82*j*.
of α- and γ-FeOOH in potassium bromide disks, unusual absorption bands in, (9) 287*a*.
of boehmite, interpretation, (3) 82*j*.
of B_2O_3, (3) 82*f*.
of CO_2 adsorbed on evaporated alkali halides, (3) 82*b*.
of gaseous Al_2O, (5) 153*e*.
of glass network formers, and interpretations, (6) 167*a*.
of hardening products of cement clinker mixed with potash solutions, (9) 262*b*.
of kaolinite, metakaolinite, and aluminum-silicon spinel, (3) 82*b*.
Spectra, infrared (*continued*)
of silicates, B (7) 225*f*.
and spectral shifts of HCN adsorbed on evaporated alkali halides, (3) 82*f*.
of synthetic talcs, (7) 218*a*.
infrared absorption, of alkali-free and Na_2O-containing calcium and magnesium silicate glasses, (8) 230*j*.
of As-S glass, (8) 232*j*.
of minerals, (6) 180*f*.
infrared lattice, of α-Al_2O_3 and Cr_2O_3, (6) 186*b*.
infrared reflectance, of $BaTiO_3$, temperature dependence, (10) 326*d*.
infrared reflection, of quartz, cristobalite, and vitreous silica, effect of temperature on, (3) 87*d*.
laser induced Raman, of tungstates and molybdates, (6) 186*j*.
low-lying crystal-field, of rare earth compounds, (11) 354*e*.
low-temperature far infrared, of SiO_2 polymorphs, (8) 254*g*.
luminescence, of Sm^{3+} in $BaTiO_3$ host lattice, (3) 83*e*.
magnetic resonance, of ^9Be in chrysoberyl, quadrupole splitting, (3) 85*c*.
mass, of beryllium fluoride vapor, (3) 80*j*.
micowave, of BaO, (5) 154*i*.
Moessbauer, of ^{57}Fe in $FeCr_2O_4$, Jahn-Teller effects on, (4) 112*h*.
Moessbauer, study of intermediate phases in formation of Mn and Zn ferrites, (1) 32*e*.
of Nd^{3+} in lathanide oxide crystals, (11) 357*a*.
optical, of Cr_2O_3 and ruby, comparison with crystal fields, (5) 150*e*.
and paramagnetic, of divalent nickel in $Sr_2(NiW)O_6$, (10) 322*g*.
of thallium in glasses as related to crystals and solutions, (4) 93*h*.
optical absorption, of garnets almandine-pyrope, pyrope, and spessartine, and structural interpretations of mineralogical significance, (5) 156*d*.
optical absorption, of iron in rock-forming silicates, (3) 84*c*; discussion and reply, (6) 185*f*.
of iron in six-coordinate sites in chlorite, biotite, phlogopite, and vivianite, (9) 284*j*.
orthorhombic ESR, of Yb^{3+} ions in CaF_2, (11) 355*e*.
paramagnetic resonance, of Fe^{3+} in calcite, (5) 156*a*.
polycrystalline EPR, of Fe^{3+} ions in MgO, (3) 85*b*.
of praseodymium in yttrium gallium garnet and yttrius aluminum garnet, (10) 325*a*.
properties, of monocrystals and glasses containing rare earth elements, (6) 188*j*.
Raman, second-order, of NaCl, (8) 256*c*.
reflectance, of Mn^{2+} and Fe^{2+} in tetrahedral fields, (4) 116*b*.
of ruby, symmetry considerations, (5) 158*j*.
of silicon hydride and silicon deuteride, (7) 221*e*.
spectral lines, radiative transfer in, (10) 324*c*.
vibrational, in mixed cyanide-halide complexes of platinum, (4) 119*b*.
of silicates, (1) 33*i*.
of vitreous silica, germania, and beryllium fluoride, (11) 358*a*.
X-ray absorption, in *K* shell of Si in gaseous $SiCl_4$ and in *L* shell of Ge in gaseous $GeCl_4$, (9) 286*d*.
Spectrochemical analysis. See *Analysis.*
Spectrography, arc emission, applications to silicates, (6) 180*e*.
of beryllium in its minerals with gas-stabilized arc, (2) 55*d*.
infrared, of drying sensitivity of clays, (7) 218*b*.
determination of Cr and Ni in steel using laser as excitation source, (10) 315*e*.
mass, solid source spark, for precision and accuracy in trace element analysis of geological materials, (1) 22*h*.
Moessbauer adsorption, of iron in clay minerals, (2) 59*g*.
of phase transitions in ZrO_2 and rare-earth oxides, (1) 34*b*.
techniques, application of mineralogical principles and infrared spectra in development of, (1) 20*i*.
X-ray emission, high-resolution semiconductor detectors in, (5) 144*i*.
of zirconium in ceramic raw material and bodies, (2) 55*c*.
Spectrometer, controlling mechanism for, P (5) 146*b*.
interferometric, using three Fabry-Perot etalons in series, P (6) 181*c*.
mass, sample insertion devices, P (8) 249*c*.
mass, small 180° fast scanning, (4) 103*j*.
Moessbauer, (5) 146*h*.
monopole mass, with ceramic electrode, P (2) 55*g*.
spark source mass, for comparison of surface and bulk glass compositions, (6) 166*i*.
Spectrometry, acoustic, for measuring structure, composition, and bond strength, (3) 76*g*.
alpha, for isotope analyses of uranium samples, (1) 21*c*.
atomic fluorescence flame, using mercury line source, (5) 144*j*.
emission, (10) 314*b*.
infrared, (10) 314*e*.
infrared, applications to study of ceramic material, (6) 180*c*.
infrared absorption, principles, and methods of sample preparation, (6) 181*a*.
light absorption, (10) 314*f*.
mass, (10) 314*g*.
of BeO-BeF_2 system at high temperatures, (6) 187*e*.
Spectrometry, mass (*continued*)
high sensitivity, multichannel analyzer system for, (1) 22*f*.
at high temperatures: IX, sublimation pressure of copper(II) fluoride, (5) 154*c*; X, sublimation pressures of scandium(III), yttrium(III), and lanthanum(III) trifluorides, (7) 219*b*; XXIX, thermal decomposition and sublimation of alkali metal sulfates, (11), 354*c*.
for observation of adsorption and crystal nucleation, (8) 255*c*.
of reaction of water vapor with solid barium oxide, (5) 154*d*.
of systems boron-carbon and boron-carbon-silicon, (5) 154*d*.
Moessbauer, (10) 315*b*.
nuclear magnetic resonance, (10) 315*d*.
photoelectric, for determination of major elements in silicate rocks with A.R.L. quantometer, (6) 180*h*.
Raman, review, (10) 315*b*.
techniques, for identification of light-weight elements, (8) 248*c*.
time-of-flight mass, (11) 347*a*.
ultraviolet, (10) 316*c*.
Spectrophotometers. See also *Photometers.*
P (4) 103*i*.
evaluating laboratory performance of, (1) 21*b*.
fluorescence, recording corrected excitation spectra between 100°K and room temperature, (6) 180*c*.
infrared, (11) 347*a*.
micro-, design and construction, (4) 102*g*.
scattered light, P (1) 24*a*.
Spectrophotometry. See also *Photometry.*
atomic absorption, with absorption tubes, for determination of trace elements in sulfide minerals, (5) 145*b*.
of calcium, interferences in, (9) 286*c*.
ultrasonic atomizer applied to, (5) 146*h*.
color matching with least squares technique, (6) 189*b*.
determination of aluminum and iron in silicates with ferron, (10) 315*f*.
comparison, of iron determination methods, (5) 146*a*.
determination of iron using ethyl 4,6-dihydroxy-5-nitrosonicotinate, (5) 146*b*.
of ferric iron in high concentration range, simple method for, (1) 23*c*.
flame, for analysis of soils, (6) 179*i*.
of fluoride ion with cerium(III)-alizarin fluorine blue complex, (4) 103*b*.
infrared, of Hungarian silicate minerals, (7) 222*i*.
infrared, theory and practical applications, (1) 21*c*.
of phosphorus traces by extraction method, (4) 103*a*.
of ruthenium with 2,4,6-tri(2′-pyridyl)-*s*-triazine, (11) 347*i*.
Spectropolarimeter, P (4) 103*i*.
Spectroscopy, apparatus, for transmitting light longitudinally of spectral flame, P (8) 249*b*.
atomic-absorption, for determination of elements, including silicon, aluminum, and titanium, (2) 36*i*.
atomic absorption, for direct and rapid determination of alumina and silica in silicate rocks and minerals, (9) 276*b*.
atomic-fluorescence, of Mg with high-intensity hollow lamp as line source, (10) 313*h*.
in chemistry, (1) 23*e*.
emission, in chemical analysis, B (7) 224*c*.
flash photolysis, P (3) 76*e*.
high-temperature, of stimulated radiation from Nd^{3+}-activated crystal and glass lasers, (10) 321*h*.
of high-temperature molecules, future developments, B (7) 225*d*.
infrared, on borates: I, sodium (1:1:4) borate hydrate, (5) 153*d*.
of crystallization in vitreous crystalline enamels, (8) 229*h*.
of deuterium exchange properties of Aerosil silicas, (3) 82*a*.
of interaction of BCl_3 with Aerosil silica, (3) 82*d*.
for investigation of *n*-propyl alcohol adsorption on montmorillonite, (11) 353*g*.
for study of crystallization of multicomponent ferruginous glasses, (10) 299*b*.
internal reflection, vertical double-pass multiple reflection cell for, P (10) 316*g*.
kinetic, of $KMnO_4$, (10) 321*e*.
microspectroscopic method for investigating interaction between solders and metallized coatings on ceramic materials, (10) 307*e*.
for piezoelectric and nuclear resonance, (3) 76*g*.
Raman, study of molten salt system $ZnCl_2$-KCl, (10) 324*d*.
of reduction of Ni and Co ions in sapphire, (7) 221*f*.
of solids, B (10) 328*e*.
X-ray absorption, for determination of metal atom positions in $CrVO_4$, (6) 185*d*.
Sphalerite, Cu(II) in octahedral sites in, (1) 28*a*.
electron probe microanalysis of, (6) 185*h*.
optical absorption studies of mixed-ion (Cu and Al) doping of, (9) 285*a*.
Spheres, micro-, alumina, porous bodies from, (10) 303*f*.
micro-, CeO_2 hollow, preparation, (9) 275*f*.
metal oxide, electrical potential method for dispersion of, P (2) 53*a*.
sol-gel, forming process using dissolved ammonia in dehydrating solvent, P (1) 14*g*.
solid, apparatus for converting hydrosols into, P (8) 250*d*.

Spheres, micro- (*continued*)
UO_2, extraction method for preparing, P (5) 134*j*.
UO_2-Y_2O_3-ZrO_2, process for preparing, P (3) 69*h*.
spheroids, forming of particulate refractory metal oxides, P (11) 349*a*.
spherules, crystalline, P (2) 47*a*.
SiO_2, production, P (8) 251*f*.
small of Al_2O_3, coordination number, (11) 350*j*.
Spheroidization, of Al_2O_3 powder in high-frequency plasma discharge, (7) 211*h*.
Spinel. See also *Refractories*.
aluminum-silicon, infrared spectra, (3) 82*b*.
chalcogenide, Cu^{2+} or Cu^{1+} in, (4) 107*i*.
equilibrium order-disorder in, (1) 29*a*.
gallate, reinvestigation of order-disorder in, (6) 188*h*.
magnesium aluminate, dissolution in sodium silicate melts, (10) 320*e*.
magnesium aluminate, vacuum hot-pressing, (7) 222*j*.
Mg-Al, Czochralski growth, (7) 216*d*.
Mg-Al, enthalpy of formation, (6) 186*d*.
$MnYb_2S_4$, magnetic and structural study, (1) 30*a*.
mixed manganite, crystallographic studies, (8) 252*e*.
oxide, containing hexavalent tellurium, (8) 255*d*.
reaction with nitrogen in chromium, (10) 296*e*.
reactive magnesia, preparation and properties, (1) 15*f*.
in series $MgCr_2O_4$-$MgFe_2O_4$, (10) 325*f*.
-silica, system, morphology of crystalline phases, (9) 280*c*.
structures defects, evaluation on basis of chemical analysis data, (9) 282*g*.
sulfo-, thin films, preparation, (4) 114*b*.
Spodumene, castable refractories from, (4) 96*a*.
concentrates, iron removal from, by chlorination, (11) 349*c*.
treatment, P (11) 350*b*.
Spraying. See also *Atomization*.
airless, (3) 74*h*.
carbide flame spray material, P (11) 340*b*.
electrostatic. See *Electrostatic processes*.
flame, with high temperature refractory metal powder, P (7) 195*d*.
for making piezoelectric layers, P (9) 274*b*.
method, and powder, P (6) 166*c*.
pistols, high temperature, P (10) 296*f*.
refractory oxides, automatic gun for, (10) 296*g*.
gun, for applying special decorative finishes, (8) 247*a*.
plasma, growth processes in refractory crystals, (5) 146*a*.
of oxide ceramic protective coatings, and properties, (1) 15*e*.
of solid lubricant coatings, (10) 296*e*.
plasma arc, of hafnium oxide and zirconium boride mixtures, P (7) 195*e*.
by plasma gun, (6) 166*c*.
plasma gun, apparatus for uniform feeding of powder into, P (9) 263*a*.
radio frequency plasma flame, P (1) 4*j*.
Sputtering, apparatus, small scale radio frequency, (11) 342*i*.
cathode, apparatus with plasma confining means, P (10) 309*h*.
apparatus including precision temperature control of substrate, P (5) 140*f*.
apparatus, including shielded rf electrode, P (5) 140*a*.
apparatus including thermionic means for increasing sputtering efficiency, P (5) 140*g*.
for depositing films of controlled specific resistivity and temperature coefficient of resistance, P (11) 344*f*.
for depositing thin films, B (8) 260*e*.
for depositing thin films, using controlled grid, P (4) 100*j*.
highly pure refractory metals in anodically biased chamber, P (10) 310*i*.
patterns, for determination of crystal grain orientation, P (11) 348*b*.
reactive, of carbides, for preparation of metal oxides, P (11) 345*b*.
of manganese and titanium, (10) 308*c*.
for preparation of Si-Ti_3O_5 films, (9) 283*i*.
ternary alloy of tin, antimony, and indium in presence of oxygen, for preparing film resistor, P (9) 274*e*.
Stability, chemical, of solid lubricants at high temperatures, (11) 338*c*.
of β-cristobalite, (3) 87*a*; discussion and reply, (6) 185*f*.
of CrO_2 at high pressures and temperatures in the "belt" apparatus, (4) 116*e*.
of complex compounds of rare earth elements, (10) 325*b*.
of edge dislocation arrays, (5) 158*k*.
fields, of dicalcium silicate modifications, (7) 221*f*.
of metallic cations in zeolites, (11) 357*b*.
of mullite at high temperatures, (9) 286*e*.
of R' centers in lithium fluoride, (11) 357*b*.
of silica brick, (7) 202*d*.
of synthetic pyroxene $CaAl_2SiO_6$, (5) 158*i*.
thermal, of complex compounds of ruthenium containing NO group, (10) 326*a*.
thermal, of compound Ti_3O in titanium-oxygen system, (9) 288*b*.
Stabilization, cubic, in zirconia, limitations, (11) 356*g*.
of gamma phase cerium sulfide, (2) 59*k*.
method, influence on zirconium ceramics properties, (7) 202*c*.
of semiconductor devices with exposed surfaces of hydrophilic oxide, P (2) 51*h*.
of silica sols, P (1) 25*g*.
Staining, of brickwork, (10) 301*g*.
Stains. See also *Color; Pigments*.
ceramic, P (2) 56*f*.
in fast fire glazes, (9) 270*i*.
preparation, (9) 271*a*.
resistance, of glass body subjected to ion exchange strengthening setup, method of increasing, P (3) 65*g*.
Standards, ASTM Metric Practice Guide, B (4) 119*h*.
for ceramic materials, B (9) 288*g*.
IEI proposed, ITE/14, for testing resistance of vitreous enamel to boiling water and steam, (4) 92*j*.
ITE/15, for resistance of vitreous enamel to hot sodium hydroxide, (4) 92*i*.
for method of testing resistance of enamel to boiling citric acid, (1) 4*e*.
for method of testing resistance of enamel to boiling hydrochloric acid, (1) 4*f*.
for method of testing resistance of enamel to citric acid at room temperature, (1) 4*f*.
National Standard Reference Data System, (2) 54*e*.
new, for methods of chemical analysis of cements, (3) 62*c*.
Stannic oxide. See *Tin, oxide*.
Statistical analysis. See *Analysis*.
Steam. See also *Moisture; Water*.
flowing, reaction with refractory metals: I, molybdenum (1100° to 1700°); II, rhenium (850° to 1700°C); III, tungsten (1000° to 1700°C), (7) 220*g,h*.
injectors, star-shaped, for complete heat distribution, (10) 317*b*.
Steatite. See also *Talc*.
body, for thermoplastic forming, (2) 48*i*.
lapping characteristics, with ordinary abrasives, (5) 123*i*.
low-loss, physical properties vs. crystalline phases in, (2) 50*b*.
Steels. See also *Enameling metals; Iron*.
casting process, continuous, and refractories used, (9) 269*h*.
in concrete with blast furnace slag aggregate, (4) 92*g*.
corrosion rate in HCl, inhibiting effect of ferrous chloride on, (11) 332*f*.
industry, technical trends and impact on refractories industry, (2) 46*g*.
refractory carbide tool, heat-treatable nickel-containing, P (5) 135*d*.
stainless, grinding by wheels, (1) 1*g*.
stainless, preoxidation, P (6) 178*j*.
Stoichiometry, melt, as function for Curie temperature, and birefringence variation in ferroelectric lithium metatantalate, (1) 16*d*.
non-, of thorium dicarbide and monocarbide, (10) 326*c,e*.
non-, in uranium dioxide, (7) 220*c*.
oxygen, in barium ferrates, and effect on magnetization and resistivity, (5) 139*e*.
of scapolite, (5) 158*i*.
of sodium metaniobate, (7) 221*i*.
sub-, high temperature, causes in sintered UO_2, (5) 131*i*.
sub-, of tungsten trioxide, (5) 158*g*.
Stokers. See *Feeding apparatus*.
Stones. See also *Rocks*.
ignimbrite building, glazing, (1) 15*a*.
pottery, Izumiyama, chemical purification and effects, (9) 278*f*.
oneware, salt-glazed Alsatian, firing with propane, (3) 70*h*.
Storage, effect on hydration rate of β-$CaSO_4 \cdot 1/2H_2O$, (2) 36*j*.
silo plan, P (2) 53*g*.
Strains, anisotropic growth, in neutron-irradiated BeO, removal of, (3) 86*a*.
apparatus for measuring, P (5) 146*i*.
of ceramic tile installations, investigations, (1) 10*e*.
gages, temperature effects, fatigue life, drift, and creep behavior, (6) 181*h*.
in glass, instrument for measuring, (5) 127*k*.
in quartz particles of whiteware bodies, X-ray measurement, (9) 271*e*.
rate, in creep of MgO, (11) 357*d*.
residual, relation with fracture-stress temperature in BeO, (3) 67*j*.
torsional angular, for testing of basic brick, (8) 238*e*.
wire, gages, temperature coefficient, apparatus for adjusting, P (6) 181*a,c*.
Stratifiers. See *Concentrators; Separators*.
Strength, bond tensile, bond shear, and effect of precompression on shear strength of model brick masonry, (10) 301*e*.
of ceramic materials, B (9) 288*g*.
determination, (6) 180*h*.
methods of testing, (3) 75*j*.
of ceramic shapes made of pure oxides, (6) 189*c*.
compressive and bending, of porous refractory compounds, (8) 239*h*.
compressive, of concrete, design of cement concrete mixes with different Indian cements based on, (10) 294*k*.
of concrete, factors affecting, (8) 228*j*.
of graphite, effect of oxidation, (8) 253*h*.
of portland cement test mortars and steam-cured mortars, (10) 295*a*.
of sea-water magnesite refractory grains at high temperature, (9) 266*j*.
of concrete, estimate by ultrasonic pulse velocity and damping constant, (2) 36*j*.
dry-bending, of kaolins and clays, (1) 15*c*.
of E-glass fibers, effect of environment and temperature, (7) 196*h*.
flexural, of thermally conditioned 96% alumina rods, (5) 157*j*.
Strength (*continued*)
flexural, of whiteware, relation with elasticity, (1) 15*k*.
of glass, in bibliography, B (8) 258*i*.
of glass, at 20° to 1200°C, apparatus for mechanical testing, (10) 313*g*.
of glass fiber, problem of, (10) 298*i*.
of glass-metal joints, (9) 264*j*.
of glass-reinforced composites, (10) 298*h*.
of granular zirconia refractories up to 2500°K, (5) 134*d*.
of heat-cured high-strength concrete, effect of pressure, (8) 228*j*.
of high-dispersion fine-pored structures of magnesium hydrate and oxide, increase with addition of SiO_2, (5) 125*c*.
high hot, in basic brick, (8) 237*e*.
of high melting point compounds, increasing, (8) 237*i*.
high temperature, of high alumina refractories, (7) 202*a*.
hot bending, of basic brick, test conditions for measuring, (8) 239*j*.
hot and cold, of chemically bonded basic bricks, dependence on temperature-time history, (7) 201*e*.
impact, of cermets of Al_2O_3-M system, (7) 202*a*.
improvement in ceramic materials, (4) 119*g*.
intrinsic brittle, of MgO bicrystals, (2) 58*f*.
of iron-carbon alloys, effect of noble metal additions on, (6) 185*k*.
of magnesite-chromite refractories, (7) 203*b*.
of magnesium silicate and graphite under biaxial stresses, (6) 189*d*.
mechanical, of ceramic tableware, (2) 48*g*.
of fired ceramic body, effects of controlled furnace atmospheres, (1) 15*h*.
at high temperatures, (3) 75*g*.
of rapidly charred ablation materials, testing technique, (8) 229*i*.
relation with modulus of elasticity of ceramic body, verification, (7) 223*a*.
of metals, B (5) 161*e*.
of porcelain, relation with grain size, (10) 306*d*.
of porous glass, effect of micromechanical stress concentrations on, (1) 28*i*.
of raw material granules (cement), increasing, (3) 62*a*.
shear, of rectangular reinforced and prestressed concrete beams, (8) 228*j*.
of sheet glass, measurement on flexible plate, (10) 298*c*.
tensile, of ceramics, measurement, (3) 75*f*.
of concrete, determination, (6) 164*i*.
of fiber composites, (8) 257*g*.
test, difference between flint and alumina whiteware bodies, (2) 49*a*.
testing, of fine short filaments or whiskers, P (7) 213*b*.
of unfired ware, increasing by pressing from both sides, (10) 312*f*.
of whiteware, effect of porosity and mullite content, (6) 175*j*.
Strengthening, alumina by glazing and quenching, (10) 306*d*.
in brittle matrix composite by chemical bonding, (11) 332*f*.
chemical, of polycrystalline alumina, (6) 175*e*.
chemical, of untouched glass rods, (7) 195*i*.
electrochemical, of clayey sandy soils, (1) 24*i*.
glass article, by ion exchange, P (3) 66*e*.
of glass-ceramics, by application of compressive glazes, (3) 64*e*.
of glasses, by etching, (5) 128*i*.
mechanisms; metals and ceramics, B (4) 121*j*.
quartz glass, (8) 233*i*.
of sodium calcium silicate glass by low temperature ion exchange, (8) 234*f*.
Stresses, analysis, of high pressure anvil by photoelasticity, (9) 277*h*.
bonding and shearing, security measures for, when using prestressed ribbed floors of ceramic elements, (10) 295*g*.
breaking, of glass determined from fracture surfaces, (2) 38*g*.
in creep of MgO, (11) 357*d*.
distribution, in internal glass coating of steel pipes due to difference in coefficients of expansion of glass and metal, (10) 298*j*.
distribution, produced by screw dislocation pileups at rigid circular cylindrical inclusions, (4) 116*j*.
effect, on durability of ion-exchanged alkali alumino-silicate glasses, (1) 5*h*.
on level splittings of ruby, (5) 137*i*.
on microwave emission from Si avalanche diodes, (8) 257*e*.
on Young's modulus of reactor graphite, (8) 253*i*.
elastic, calculation of distribution around circular holes and liner cracks, (9) 283*i*.
in enamel-cast iron system, (5) 125*j*.
in fiber-reinforced materials, (3) 87*c*.
field, of dislocation, (8) 257*f*.
in glass caused by ultraviolet radiation: V, thermal release of stress caused by ultraviolet irradiation; VI, stress build-up in binary borate glasses by ultraviolet radiation, (8) 243*g,h*.
in glass-indium-glass bimetallic composites, (8) 229*f*.
irradiation-induced, in graphite columns, influence of cross-sectional shape on, (3) 81*j*.
matrix and interface, in discontinuous fiber composited model, (10) 298*a*.
micromechanical, concentrations, effect on strength of porous glass, (1) 28*i*.
nature, at tip of perfectly brittle crack, (1) 6*a*.

Stress (*continued*)
relief mechanisms, in magnesia- and yttria-stabilized zirconia, (2) 59*g*.
residual, development in laminar ceramics, (1) 15*g*.
in extruded polycrystalline BeO ceramics, (7) 221*f*.
at oxide-silicon interface, (5) 158*a*.
of thermally conditioned 96% alumina rods, (5) 157*j*.
"sensitized" buildup, in doped sodium borate glasses by ultraviolet irradiation, (9) 264*h*.
-strain relationship, flexural, of concrete confined by rectangular transverse reinforcement, (8) 228*c*.
thermal, intercrystalline, in polycrystalline rutile, (5) 153*j*.
unaxial, effect on magnon sidebands in MnF_2, (11) 352*e*.
Strontium, and calcium, and barium, dibasic compounds, and solid solutions, (6) 164*i*.
cations, substitution for barium in barium ruthenium oxide and in barium iridium oxide, (5) 155*d*.
ferrates, electric and magnetic properties, (5) 138*a*.
fluoride, single crystals, sublimation, Langmuir studies, (11) 354*d*.
magnesium carbonate, (4) 116*j*.
metatitanates, heat of formation, (1) 29*a*.
molybdate, niobium compensated, laser characteristics, (3) 83*d*.
nitride, ternary, with rhenium and osmium, preparation and properties, (6) 187*i*.
oxide, electronic structure, (5) 138*g*.
oxide, photoluminescence, photoelectric emission, and enhanced thermionic emission from, (11) 355*j*.
rubidium-, geochronological study of Willyama Complex, Broken Hill, Australia, (3) 86*d*.
salts, preparation from celestite, (9) 278*g*.
$SrFeO_{3-x}$, Moessbauer effect in, (5) 155*h*.
$SrFe_{12}O_{19}$, thin crystals, thickness dependence of domain width in, (3) 88*f*.
$Sr(Fe_{1/2}Ta_{1/2})O_3$, crystal distortion in, and solid solutions, (8) 252*j*.
$SrLaFeO_4$ with K_2NiF_4 structure, magnetic susceptibility, (10) 323*b*.
$Sr_2(NiMo)O_6$, structural and magnetic transitions in, (7) 221*j*.
α-$SrHPO_4$, highly crystalline, preparation, P (8) 251*d*.
systems. See *Systems*.
titanate, diffusion of point defects in, (3) 71*c*.
electric field effect on ESR of Gd^{3+} in, (10) 320*e*.
first- and second-order Raman scattering, (11) 352*j*.
formation of point defects in, (3) 71*i*.
interband Faraday rotation in, (6) 186*c*.
irradiated by fission fragments, X-ray examination, (7) 46*c*.
paramagentic resonance study at millimeter wavelengths of axial Fe^{3+} spectrum in, (9) 285*f*.
radiative and nonradiative transitions in fluorescence decay of Eu^{3+} in, (6) 188*b*.
reduced, free-carrier absorption in, (9) 282*e*.
reduced, piezoresistive properties, (8) 256*a*.
solid solutions containing mixed cations, (7) 216*e*.
temperature dependence of transverse and longitudinal optic mode frequencies and charges in, (10) 326*f*.
uranates, preparation and properties, (5) 157*c*.
Structural clay products. See also *Brick; Pipe; Tile*.
body design, (6) 172*a*.
composite decorative elements, P (8) 236*f*.
composition for vibratory forming, P (11) 337*b*.
dilatometry, (9) 276*b*.
forming and firing, P (11) 337*b*.
and gas flow problems, during drying and firing of brick, and ceramic products, (6) 172*b*.
laboratory, for precalcining procedures, (3) 66*h*.
paving block, P (1) 10*h*.
scumming in, reactivity of barium carbonate in combating, (1) 10*e*.
surface coloring, (10) 302*a*.
yearbook 1968, B (5) 161*e*.
Structural clay products industry, changing pattern of fuel usage in, (3) 76*i*.
in Germany, mastering future problems by rational methods and use of brick, (10) 301*f*.
high alumina cements in, (9) 266*f*.
proper scheduling makes money, (7) 199*i*.
Structural materials. See also *Aggregates; Brick; Building materials; Cement; Concrete; Enameled ware; Glass; Insulation, thermal; Masonry; Structural clay products*.
anisotropic, orientation effects in mechanical behavior, B (4) 120*j*.
ceramic floors, security measures for bonding, (10) 295*g*.
effect of sonic boom on, (11) 331*i*.
method and composition of matter for forming, P (3) 66*g*.
roofing granules, soot-resistant, P (11) 337*e*.
Structure, of alkaline beryls, effect of annealing on, (4) 108*g*.
of alloys WC-TaC-Co and WC-NbC-Co, (7) 203*d*.
of aluminogermanate melts, with Na_2O/Al_2O_3 ratio greater than unity, (5) 128*b*.
atomic arrangements in $Sr(FeTa)_{1/3}O_3$-$Sr(CrTa)_{1/2}O_3$ system, (10) 319*a*.
band, and pseudopotential form factors for semiconductors of diamond and zinc blende structures, (8) 252*d*.
of bismuth phosphate glasses, (6) 169*g*.
of calcium-deficient apatites, (5) 158*a*.

Stress (*continued*)
cellular, of gas concrete and granulometric composition of filler, (6) 164*a*.
changes, of zeolite X caused by ion exchange and temperature, (1) 32*f*.
of Cr-SiO cermet films, (5) 139*e*.
clay mineral, electron-diffraction analysis, B (10) 328*i*.
of clay minerals, (5) 158*c*.
of clay soils stabilized with cementitious agents, (8) 229*a*.
of crystals. See also *Crystals*.
crystal, of α-ScOOH, (5) 153*a*.
crystalline, of pyrochlore, of Oka, P.Q., (11) 350*f*.
defect, in alloy Ni_4Mo, due to ordering, electron microscopy of, (4) 109*a*.
and bonding of zirconium nitride containing excess nitrogen, (6) 184*j*.
in epitaxial $GaAs_{1-x}P_x$, (6) 189*f*.
high-temperature, of ferrous oxide, (4) 111*h*.
densest packing of ellipsoids, (8) 252*h*.
electronic, of amorphous Ge and Si, (5) 156*e*.
evaluation, of silicon oxide films, (4) 116*a*.
evolution, as function of temperature of tungsten bronzes low in inserted element, (1) 32*h*.
of free molecules, determination by electron diffraction, (5) 158*b*.
of gaseous Al_2O, (5) 153*e*.
of glass fibers, (8) 234*e*.
of high carbon hyperstoichiometric uranium carbide single crystals, (4) 116*c*.
of high-fired, so-called directly bonded, chromite-containing brick, (7) 203*j*.
of InSb high-pressure phases, (10) 325*d*.
interatomic forces in solids, (10) 322*f*.
of δ-FeOOH, (11) 357*e*.
of δ-Fe_2O_3, new, (hydrate), (2) 59*h*.
of δ-Fe_2O_3 (hydrate) as proposed by Okamoto, (8) 257*f*.
lattice distortions and field gradients in alkali halide solid solutions, (10) 322*c*.
layer stacking, survey, (8) 257*c*.
of liquids, (3) 87*a*.
of $LiGaTiO_4$, (7) 222*a*.
Madelung constants needed for calculation of lattice energies and enthalpies of formation of, (10) 322*f*.
magnetic, in spinel B-site lattices, (10) 323*a*.
magnetic, in $TCrO_3$ and $TMnO_3$ compounds, (6) 176*e*.
in materials characterization, B (8) 259*a*.
of metals, B (5) 161*e*.
method for calculating tracer diffusion, (9) 286*b*.
micrographic, of black zirconia, (7) 203*g*.
microscopic, in kaolin subjected to direct shear, (10) 323*i*.
micro-, of Al_2O_3-Mo and ZrO_2-Mo cermets, (2) 45*b*.
of barium titanate, determines usage, (1) 16*j*.
of ceramic materials: V, aluminosilicate refractories, (8) 238*j*.
of clay, effect of graphite, (6) 172*j*.
of clay bodies, relation with aggregate properties, (7) 199*k*; (9) 266*e*.
of clay and clay-graphite mixtures, (9) 267*a*.
of eutectics between compounds, preferred orientation in, (9) 285*g*.
of extruded clay, (2) 43*c*.
of hardened high-alumina cement pastes, (10) 295*k*.
of high-grade metamorphic rocks at Broken Hill, Australia, (9) 284*b*.
of hot-pressed $MgAl_2O_4$, described by quadratic multivariable analysis, (2) 59*b*.
modifications produced in UO_2 by irradiation, (6) 173*h*.
quick clay, (7) 220*f*.
of refractories, (2) 45*c*; (5) 132*i*.
of silica rich binary silicate melts and glasses, (4) 108*c*.
of single-crystal TiC, (8) 255*e*.
of sintered urania pellets, influence of origin of UO_2, (1) 11*a*.
of triaxial porcelain, (10) 306*a*.
in two phase (one solid + one liquid) and in three-phase (two solid + 1 liquid) systems, factors controlling, (5) 152*a*.
of vapor-deposited silicon carbide, (9) 267*c*.
variation due to fabrication, (5) 154*i*.
of modified U_3O_8 (ρ-U_3O_8), high temperature and sintering behavior, (4) 116*d*.
molecular, of B_2O_3, (3) 82*f*.
effect on adsorption of 13 *s*-triazine compounds on montmorillonite clays, (5) 155*a*.
of tetragonal ruthenium dioxide, (5) 150*j*.
in molten group II chlorides, (11) 356*a*.
of molten oxides: I, viscosity of GeO_2 and binary germanates containing Li_2O, Na_2O, K_2O, and Rb_2O, (5) 128*d*.
of molten oxides in system $0.25Na_2O\cdot(0.75-x)$-$GeO_2\cdot xSiO_2$, (5) 128*f*.
MOS, tunneling into interface states of, (1) 17*e*.
of $Ni_{1/3}Fe_{2/3}$ coprecipitate, (3) 87*f*.
of nickel in soda-boric oxide glasses, (5) 129*b*.
of nickel vanadium selenide, (5) 158*d*.
order-disorder, in synthetic cordierite, (6) 189*d*.
of oriented sodium metaphosphate glass fibers, (5) 128*h*.
of oxide films during initial stages of titanium oxidation, (10) 325*d*.
of porcelain, during stages of production, (2) 48*j*.
postulated, causing optical color-center bands in amethyst quartz, (7) 220*d*.
of potassium lead pyrogermanate, (5) 158*c*.
properties, of europium metal and monoxide at high pressure, (9) 284*i*.
of molten $PbCl_2$-PbS mixtures, (10) 320*h*.
of $PdAs_{2-x}Sb_x$, $PtP_{2-y}As_y$, $PtP_{2-x}Sb_x$, $PtP_{2-x}Bi_x$, $PtAs_{2-x}Sb_x$, $PtAs_{2-x}Bi_x$, $PtSb_{2-x}Bi_x$, $Pd_{1-m}Pt_mAs_2$, $Pd_{1-m}Pt_mSb_2$, $Pd_{1-m}Au_mSb_2$, and $Pt_{1-m}Sb_2$, (7) 221*j*.

Stress, properties (*continued*)
of $Ta_{1+x}Se_2$ phase, (5) 158*j*.
of $Zn_xCd_{(1-x)}S$, thin films, (7) 208*c*.
refinement of La_2Te_3, ThP_4 structure, (5) 158*d*.
of simple silicate and borate glasses, (6) 169*a*.
of sodium aluminogermanate melts with Na_2O/Al_2O_3 ratio equal to unity, (5) 128*h*.
of sodium metasilicate, reinvestigation, (1) 31*k*.
of solid and liquid vanadium pentoxide, (11) 357*c*.
stability, of minerals with pyrite, marcasite, arsenopyrite, and loellingite structures, (9) 278*j*.
of stranskiite, $Zn_2Cu(AsO_4)_2$, (9) 286*k*.
structural units, permitted and forbidden, in vitreous systems, (11) 334*a*.
study, of basic sulfates of rare earths and yttrium, (4) 116*b*.
super-, of tantalum pentoxide, high resolution electron microscopic observations of, (5) 153*i*.
surface, of quartz and anomalies in α-β inversion, (6) 189*g*.
of system $ZrCr_2$-$TaCr_2$, (4) 116*f*.
of ternary oxides, modification by cation substitution, (5) 155*d*.
thortveitite-type, of $Mn_2V_2O_7$, (5) 159*f*.
of vanadium, in soda-boric oxide glasses, (5) 129*c*.
of vitreous borates and borophosphates, (5) 128*i*.
Stylolites, nature and origin, (9) 287*i*.
Sublimation, of alkali metal sulfates, mass spectrometric studies at high temperatures, (11) 354*c*.
of strontium fluoride and barium fluoride single crystals, Langmuir studies, (11) 354*d*.
Substrates, apparatus for vapor coating, P (3) 343*f*.
high alumina, for Ta thin film circuitry, glazes for, (6) 176*j*.
multilayer thin-film coated, with metallic parting layer to permit selective sequential etching, P (9) 274*b*.
resistor, with integral metal terminations, P (4) 101*c*.
semiconductor, chemical polishing, P (1) 17*c*.
semiconductor, method of making reliable low-ohmic nonrectifying connection to, P (10) 310*a*.
size, economic, for thin film circuits, (3) 71*d*.
Sulfates, alkali metal, thermal decomposition and sublimation, mass spectrometric studies at high temperatures, (11) 354*c*.
basic, of rare earths and yttrium, structural study, (4) 116*b*.
influence on setting and hardening of cements, (10) 294*j*.
of rare-earth elements in terbium subgroup, physicochemical properties of crystal hydrates of, (9) 285*c*.
resistance, of Ferrari cements, (10) 296*b*.
in soda-lime-silica glasses, determination by combustion in oxygen, (8) 231*f*.
soluble, determination in fired ceramic products, (8) 236*e*.
systems. See *Systems*.
Sulfides, kinetics of combustion, in slag glasses, (2) 39*e*.
metal, group IV di-transition, (4) 110*h*.
metal, kinetics of chlorination of, (3) 77*i*.
semiconductor, method of passivating supports for, P (3) 73*d*.
Sulfur, annealing pressure, effect on resistivity homogeneity of CdS single crystals, (11) 352*e*.
in bornite, bonding properties, (4) 117*a*.
compounds, reduced, as melting and refining aids for flint soda-lime glass, (2) 40*b*.
dioxide, magnetic permeability, (4) 112*h*.
pilot plant study of alkalized alumina system for removal from hot flue gases, (1) 24*f*.
in treatment of molten glass, P (7) 199*d*.
in glasses, colorimetric determination, (6) 166*i*.
reaction with sodium borohydride, (3) 85*j*.
removal from fuels, (4) 101*k*.
silicon-, compounds, chemistry, (5) 150*b*.
systems. See *Systems*.
Superconductors, composite structures, P (8) 244*g*.
material, of NbN and ZrN, P (10) 311*e*.
at 20°K, of Nb_3Al and Nb_3Ge solid solution, (1) 17*c*.
superconductivity, of cubic niobium carbonitrides, (8) 257*j*.
Supersonics. See *Sonics*.
Surface, of γ-alumina, model, (11) 354*f*.
area measurements, problems, (11) 346*j*.
cooled, and plasma jet, simultaneous transfer of heat and material between, (7) 221*h*.
displacements, discontinuous, determination by moire effect, (8) 248*a*.
foreign ions on, (10) 321*a*.
layers, black metal-containing, method of producing, P (1) 18*g*.
phenomena, correlation with flotation in silicates, (7) 214*c*.
of defects movement in ionic crystals, (6) 189*e*.
in silicate minerals, chemical interpretation, (7) 216*e*.
potentials, monolayer, precise differential measurement, (1) 31*i*.
properties, of hydrolyzed titania: IV, rates of sorption, (1) 33*a*.
specific, of cement, determination by adsorption of colorants, (3) 62*d*.
of fine-ground quartz sands, indirect methods of determining, (2) 54*j*.
of fine mineral particles, measurement with surface meter and BET gas adsorption, (11) 346*d*.
of glass powders, and relation to parameters determined statistically by grain size analysis, (6) 166*j*.
of ground minerals, modified Blaine method for determining, (2) 54*d*.
of quartz sands of fine grain size, methods for determining, (3) 75*g*.

Surface *(continued)*
states, on CdS single crystals, (5) 158*j*.
contributions to MOS impendance, (5) 150*g*.
intrinsic, on ionic crystals, theory and observation, (9) 287*i*.
of silicon-silicon dioxide interface grown by vapor deposition, (8) 257*a*.
substrate, for microelectronics, (7) 208*d*.
tension, of glass. See *Glass*.
at interface of glass-metal melts, determination, (11) 334*j*.
of solids, (3) 76*a*.
textures, method and apparatus for removing, P (7) 211*c*.
Surface-active substances, effect on clay properties, (2) 58*b*.
effect on coagulative structure formation in aqueous suspensions of asbestos, (8) 237*h*.
semimacromolecular, aggregating action on ceramic powder, (11) 350*e*.
Surfactants. See *Surface-active substances*.
Suspensions. See also *Slips*.
aqueous, of clay minerals, characterization evaluation, (10) 305*h*.
aqueous, of colloidal, crystalline, hydrous oxides of zirconium and hafnium, P (4) 97*f*.
aqueous asbestos, effect of surfactants on coagulative structure formation in, (8) 237*h*.
clay. See *Clays*.
clay mineral, thixotropic properties, electrophoretic indication of, (7) 217*i*.
coagulation, effect of magnetic treatment of water on, (5) 136*h*.
dilute asbestos and asbestos-cement, structure formation in, (10) 295*i*.
gas-solid, continuously recirculated, heat transfer coefficients for, (5) 148*a*.
halloysite, model for rheology, (6) 187*g*.
Swelling. See *Expansion*.
Switches, four layer planar semiconductor, and method of making, P (9) 273*b*.
pnpn, with $10 < (N_B/N_E) < 100$, P (3) 73*j*.
pnpn, stabilized, with rough area shorted junction, P (5) 143*c*.
reed, P (5) 142*a*.
reed, assemblies, method of forming projections by selective heat softening, P (5) 141*i*.
semiconductor latching, with light-coupled triggering means, P (5) 143*a*.
unitary multiple solid stage, assembly, P (3) 74*f*.
voltage controlled, P(11) 345*e*.
Symmetry, of crystals. See *Crystals*.
Symposiums, on fluorescence, theory, instrumentation and practice, B (1) 34*e*.
on heat and mass transfer in process metallurgy, B (1) 34*f*.
on nuclear science and technology for ceramists, B (4) 120*g*.
Tokyo, on defects in glass, (2) 40*e*.
on valve (electronic tube) development, B (4) 122*d*.
on whiteware, B (3) 89*c*.
Synthesis, of alkaline earth zeolites, (3) 88*g*.
of aluminum borate whiskers, P (2) 48*c*.
for boron nitride preparation, (5) 155*i*.
of B_4P, (4) 117*f*.
of borosilicate glasses, (6) 169*d*.
of calcium chlorspordiosite, P (7) 210*b*.
of carbon crystals, P (8) 251*j*.
clay mineral: II, randomly interstratified aluminum montmorillonoid, (5) 150*c*.
of commercial Titan Yellow active component in determination of Mg, (5) 146*c*.
of cordierite, (10) 304*e*.
of cubic nickelorthosilicate. (1) 33*b*.
diamond, high temperature high pressure apparatus in, P (5) 144*b*.
epitaxial, of GaAs using flow system, (7) 207*a*.
of gap-graded shrinkage-compensating concrete, (2) 36*f*.
of halophosphate phosphors using calcium chlorspodiosite, P (7) 210*c*.
high pressure, of fluorite-type PbO_2, (7) 218*a*.
of $PbCrO_4$, (3) 81*b*; correction, (6) 186*b*.
of α-$LiAlO_2$, (7) 218*a*.
single-crystal, of $LiBO_2$, (7) 220*c*.
high-temperature high-pressure, of molybdenum ditelluride, P (8) 241*e*.
hydrothermal, of cesium aluminosilicates, and properties, (6) 182*h*.
low-temperature, of metallic silicides and germanides by amalgam method, (8) 254*i*.
of molybdenum and tungsten bronzes at high pressure, (6) 189*h*.
of norsethite, $BaMg(CO_3)_2$, at approx 20° and 1 atm, model of dolomitization, (7) 222*j*.
reported, of gallium dodecaboride, (6) 188*i*.
of rhenium ditelluride, (6) 189*j*.
solid state, of Na_2ZrSiO_5, (11) 356*e*.
of tetraphosphorus triselinite, preliminary infrared, nuclear magnetic resonance, and Raman studies, (4) 117*a*.
of titanium and tungsten carbides, effects of preshock treatment, (7) 201*e*.
Systems. See also *Equilibrium studies; Phase diagrams*.
Al-Al_2O_3, vapor pressures studied by effusion and pressure compensation methods, (1) 33*e*.
Al + Al_2O_3, thermodynamic functions by emf measurements on solid galvanic cells in nonstationary conditions—, (3) 87*f*.
Al-Mn-Fe-Si-O-H, phase relations, model for garnet equilibria, (9) 285*j*.
α-Al_2O_3-Cr_2O_3, interdiffusion studies, (2) 58*c*.
Al_2O_3-Cr_2O_3-SiO_2, (11) 357*b*.
Al_2O_3-Fe_2O_3-H_2O, phase relations, (3) 84*i*.
Sb-SnTe, pseudobinary, phase diagram, and electrical properties of ternary alloys, (11) 355*h*.
Systems *(continued)*
As-S-Se, partially vitreous, sintering study, (1) 32*d*.
$BaFeO_{2.8-3.0}$, Moessbauer effect, (6) 187*h*.
BaO-Al_2O_3-SiO_2-TiO_2, dependence of crystalline phase amount on heat-treating conditions of sitalls in, (6) 185*b*.
BaO-$LuTaO_4$-B_2O_3, BaO-$YTaO_4$-B_2O_3, and BaO-$LaTaO_4$-B_2O_3, perovskite fields in portions of, (1) 30*j*.
BaO-SiO_2, phase separation, (6) 187*g*.
BaO-ZrO_2-SiO_2, subsolidus structure and ternary compounds, (6) 189*d*.
BeO-Al_2O_3-SiO_2-H_2O, reconnaissance, (5) 157*g*.
BeO-BeF_2, mass spectrometry at high temperatures, (6) 187*e*.
BeO-MgO, (4) 96*a*.
binary, containing zirconia, molten and sprayed by arc-plasma, crystal modifications of, (11) 351*b*.
binary, invariant of diffusion in, (10) 322*a*.
Bi_2Te_3-Bi_2S_3, and synthesis of mineral tetradymite, (5) 149*h*.
bismuth-tellurium phase, evaluation, (4) 110*g*.
boron-carbon and boron-carbon-silicon, mass spectrometry, (5) 154*d*.
B_2O_3-BF_3, infrared studies, (5) 153*e*.
B_2O_3-SiO_2, metastable immiscibility, (2) 59*a*.
Cd-Sb-Cu, ternary, CdSb-Cu section of, (4) 106*b*.
Cd-In-As, (10) 325*j*.
cadmium-magnesium-tin oxides, solid-state reactions, (3) 86*b*.
CdS-MnS and CdSe-MnSe, phase diagrams, (10) 319*e*.
$CaCO_3$-$SrCO_3$ at high pressures and 500° to 700°C, (1) 33*b*.
$CaCO_3$-$SrCO_3$-$MgCO_3$, (4) 116*a*.
CaF_2-BaF_2, CaF_2-MgF_2, and BaF_2-MgF_2, binary and ternary diagrams, (2) 57*j*.
CaO-Al_2O_3-$CaCl_2$-H_2O, amorphous phase, (7) 215*h*.
CaO-Al_2O_3-iron oxide, phase relations, (5) 156*g*.
CaO + $CaCO_3$, temperature-pressure relations between melt and solid CaO, (4) 105*j*.
CaO-CaO·SiO-$CaSO_4$, (7) 222*d*.
CaO-Cr_2O_3-SiO_2, reaction in, (5) 157*c*.
CaO-Cr_2O_3-ZrO_2, reaction in: I, $CaZrO_3$-Cr_2O_3; II, $CaCrO_4$-ZrO_2, (7) 220*j*, 221*a*.
CaO-FeO-Fe_2O_3, properties of calcium ferrites in, (9) 287*g*.
CaO-MgO-Al_2O_3, composition and possible structure of quaternary phase in high-Al_2O_3 cement and relation to other phases in, (7) 216*h*.
CaO-MgO-Fe_2O_3 and CaO-MgO-Al_2O_3, factors controlling microstructure and grain growth in, (5) 152*a*.
calcium oxide-silica-water, solubility relations at 25°, (11) 350*h*.
CaO-ZrO_2, cubic field in, (11) 351*f*.
Ca_2SiO_4-Ba_2SiO_4, (1) 33*d*.
Ca_2SiO_4-$Y_2(SiO_4)_3$, phase diagram, (3) 84*f*.
$CaWO_4$-LiCl(NaCl,KCl), fusibility in, (10) 321*b*.
C-H-O-S, gaseous equilibria in portions of, (5 153*a*.
cerium oxide-Al_2O_3, Cr_2O_3, Ga_2O_3, high-temperature chemistry of cerium in, (6) 186*e*.
Ce_2O_3-ZrO_2, (9) 287*a*.
Cs,Cd,Pb||Cl, (4) 117*c*.
Cs,Sr||Cl,SO_4, (10) 325*j*.
CsF-KF and CsF-RbF, (4) 117*e*.
Cr-O, phase diagrams, (9) 285*g*.
CrO_3-Cr_2O_3, phase equilibrium in, (8) 255*j*.
clay–water. See *Clays*.
Cu-Fe, precipitation and oxidation studies using Moessbauer effect, (10) 324*b*.
Cu_2S-FeS-Na_2S, (1) 33*e*.
diopside-akermanite-nepheline, (5) 159*a*.
of fluorides of lithium, cesium and lanthanum, (9) 287*a*.
of fluorides of lithium, sodium, and cesium, (9) 287*b*.
of fluorides and chlorides of lithium and cesium, (9) 287*j*.
gallium-phosphorus-zinc, phase diagram, (11) 353*g*.
gallium-chlorine and gallium arsenide-chlorine, vapor phase equilibria, (4) 118*j*.
GaAs-Sn, etching and crystal growth in, (3) 81*a*.
Ge-GaAs, phase diagram, (10) 324*i*.
Ge-O-H, tetragonal germanium dioxide and equilibria in, (3) 87*b*.
Ge-Te, in region of compound GeTe, (4) 117*d*.
GeO_2-Al_2O_3 and GeO_2-Fe_2O_3, comparison with systems based on SiO_2, (10) 326*c*.
GeTe-InTe, solid solution in, (3) 86*a*.
$HfCl_4$-AlCl$_3$-NaCl and $HfCl_4$-AlCl$_3$-KCl, (1) 33*k*.
HfO_2-CaO, comparison with corresponding system based on ZrO_2, (9) 287*c*.
halide, group I, solids with high ionic conductivity in, (7) 221*c*.
In-Sb-Ni, ternary, quasi-binary section InSb-NiSb in, (1) 31*e*.
InSb-InSe, pseudobinary, phase diagram, (11) 355*g*.
Fe-Mn-O, involving "(Fe,Mn)O" and $(Fe,Mn)_3O_4$ solid solutions, equilibria in, (6) 185*d*.
Fe_2O_3-Mn_2O_3 and Fe_2O_3-Cr_2O_3, effect of solid solution on Curie temperature in, (11) 352*c*.
ferric oxide-water, correction, (1) 33*c*.
kaolinite-AlF_3, reaction mechanism of mullite formation in, (7) 220*i*.
La_2O_3-ZrO_2, (9) 287*a*.
Pb-PbO-Sb_2O_3, slag-metal equilibria in, (4) 115*g*.
$PbAl_{(12-x)}Fe_xO_{19}$, unit cell dimensions, (1) 33*d*.
PbO-B_2O_3, kinetics of metastable phase separation in, by small-angle scattering of X rays, (1) 32*c*.
PbO-B_2O_3-SiO_2, phase equilibria and liquid immiscibility, (5) 156*b*.
Systems *(continued)*
PbO-Fe_2O_3, resistivity technique to determine initial reaction temperature in, (11) 358*a*.
lead oxide-lead sulfate, (10) 322*c*.
PbO-Nb_2O_5-TiO_2, X-ray study, (7) 223*a*.
PbO-SiO_2-V_2O_5, phases in aluminum porcelain enamel, (11) 332*c*.
PbO-ZnO-B_2O_3 oxide, X-ray investigation, (3) 85*b*.
PbO-ZrO_2-TiO_2 at 1100°C, (9) 287*f*.
lead telluride, P-T-x phase diagram, (5) 157*i*.
Li, Na, K||F, P_2O_7, horizontal cross sections, (9) 283*a*.
Li_3AlF_6-CaF_2, phase diagram, (7) 220*i*.
lithium-carbon, compound formation in, (9) 280*c*.
LiF-ThF_4, molar volumes in, (5) 155*a*.
lithium hydride: II, solid-liquid equilibrium in sodium chloride-lithium hydride system; III, solid-liquid equilibrium in lithium bromide-lithium hydride and lithium iodide-lithium hydride systems, (7) 222*c*.
Li_2SO_4-Ag_2SO_4, solid and liquid mixtures, transport properties, (5) 159*g*.
$MgCr_2O_4$-$MgFe_2O_4$, (10) 325*f*.
MgO-Al_2O_3-Cr_2O_3, coherent precipitation in, (2) 57*e*.
MgO-Cr_2O_3-Fe_2O_3 at 1300°C in air, (7) 222*a*.
MgO-Cr_2O_3-SiO_2, phase chemical analysis of, (8) 248*b*.
MgO-FeO-Fe_2O_3, equilibrium relations up to 1750°C in air, (7) 218*h*.
MgO-$LiVO_3$, structure, (5) 154*a*.
MgO-$MgCr_2O_4$-$CaMgSiO_4$, factors controlling microstructure and grain growth in, (5) 152*a*.
Mg_2Si-Mg_2Pb, (10) 326*a*.
Mn-O-CO_2, thermodynamic study, (11) 357*f*.
metal-ceramic, solid-solid interfacial energy determinations in, (4) 115*i*.
Mo-C, investigations, (6) 184*j*.
Nd_2O_3-ZrO_2, (9) 287*a*.
nepheline-alkali feldspar-plagioclase, mineral equilibria in, and petrological significance, (9) 284*c*.
Ni-B-P, boron phosphides in, phase stability regions, (4) 114*c*.
nickelous nitrate-water-magnesium oxide, low-temperature cementation effects, (1) 29*i*.
Nb-Fe-C, phase equilibria, (9) 285*g*.
niobium-sulfur, new subsulfide in, (4) 113*a*.
oxide, binary and ternary, relation between liquidus and cationic field strengths in, (9) 281*f*.
oxide, binary and ternary, structural relations between liquid and glass states, (1) 7*c*.
palladium-phosphorus, X-ray diffraction and thermoanalytical investigation, (4) 119*a*.
of periodic compounds at high pressures and temperatures, (4) 113*i*.
plutonium-silicon, (8) 256*b*.
polycomponent, numerical determination of phase compounds in, (10) 324*a*.
K,Ca,Ba||Cl,SO_4, interactions in melts, (9) 283*c*.
K,Ca,Ba||SO_4, interactions, (9) 283*e*.
K^+,Cd^{2+},Cl^-,"Br^-", reciprocal, surface tension in, (11) 357*a*.
$KAlSiO_4$-$MgSiO_4$-SiO_2-H_2O: I, inferred phase relations and petrologic applications, (4) 116*b*.
KCl-NaCl, phase equilibrium diagram, (3) 84*b*.
KF-K_2BeF_4-K_2ZrF_7, (9) 287*e*.
KI-AgI, phase diagram, —high ionic conductivity of KAg_4I_5, (3) 85*b*.
K_2SO_4-$MgSO_4$-$CaSO_4$, ternary, (5) 159*f*.
K_2TiO_3-Na_2TiO_3, (9) 283*f*.
$K_xV_2O_5$, new families of vanadium bronzes, (1) 33*f*.
salt, binary and ternary, machine plotting of liquidus data, (5) 154*b*.
$SmCl_3$-NaCl-KCl, (9) 287*f*.
Sc_2O_3-Cr_2O_3, phase diagram, (6) 187*b*.
silicon-nitrogen-boron, dehydrohalogenation and cleavage reactions in, (6) 185*b*.
Si-O, phase diagrams, (9) 285*g*.
Si-SiO_2, interface states and interface disorder in, (8) 254*b*.
SiO_2-SiC, thermodynamics of reactions in, (9) 288*d*.
SiO_2-ThO_2 and SiO_2-ThO_2-UO_2, liquidus curves and thermodynamic properties, (4) 117*b*.
SiO_2-ZrO_2-V_2O_5, X-ray study of zircon formation in, (3) 88*d*.
Ag-Cl-AgBr, liquid junction potentials in, (5) 151*h*.
silver nitrate-sodium nitrate, molten, thermoelectric properties, (11) 357*g*.
Na,Cs,K||Br, (10) 326*a*.
Na-K-Ca-Mg, of clay minerals, cation exchange equilibria in, (6) 184*d*.
$NaAlSiO_4$-$NaAlSi_2O_6$-H_2O, melting of lanalcite solid solutions in, (2) 58*i*.
$NaAlSi_2O_6$-$KAlSi_2O_6$, enthalpies of fusion, (2) 58*g*.
NaF-AlF_3, calculated model, (6) 184*a*.
NaF-AlF_3, thermochemical study, (3) 87*f*.
Na_2O-B_2O_3-NaCl, liquid-liquid extraction in, (4) 112*j*.
Na_2O-K_2O-Al_2O_3-SiO_2-H_2O, alkali feldspar solvus in, (5) 149*h*.
Na_2O-TiO_2-H_2O, (2) 60*b*.
Na_2TiO_3-NaCl-TiO_2, (3) 87*i*.
$Sr(FeTa)_{1/2}O_3$-$Sr(CrTa)_{1/2}O_3$, atomic arrangements in, (10) 319*a*.
$SrFe_{12}O_{19-\gamma}$, Moessbauer effect in, (10) 323*d*.
$SrTi_{1-x}Fe_{2x}O_{3-x/2+\delta}$, preparation and properties, (11) 342*c*.
$SrTiO_3$-(La_2O_3:$3TiO_2$), solid solutions, (1) 32*d*.
structure, causality, (5) 149*j*.
sub-,' $CaAl_2O_4$-$CaAl_4O_7$-$Ca_2Al_2SiO_7$-$MgAl_2O_4$, liquidus relations, (2) 58*g*.
Ta-Mo-C, investigations, (6) 184*b*.

Systems (*continued*)
tantalum-tantalum bromide and tantalum-tantalum iodide, equilibrium phase diagrams, (4) 110*b*.
Ta_2O_5-TiO_2, effect of oxide additions on polymorphism of, (9) 281*a*.
TlBr-TlI, (3) 87*j*.
thorium-nitrogen, phase equilibria, (3) 86*d*.
ThC_2-UC_2, limited solid solutions, (6) 187*a*.
ThO_2-CeO_2-Ce_2O_3, X-ray study, (4) 119*a*.
Sn-MnSn$_2$-NiSn$_4$, (7) 222*b*.
$SnCl_2$-$ZnCl_2$, binary, vapor pressure of metal halides in, (4) 118*j*.
Ti-Ni-Sb-O, mixed rutile crystal formation in: I, rutile solid solution and reaction diagram; II, mechanism of rutile solid solution, (7) 219*e*.
titanium-oxygen, thermodynamics, discrepancies in, (11) 351*e*.
Ti-W-O, high-temperature condensed phase equilibria in, (8) 254*h*.
TiO_2-Al_2O_3-SiO_2-CaO-MgO and TiO_2-Al_2O_3-FeO-SiO_2-CaO-MgO, liquidus temperatures of titaniferous slags in, (9) 284*a*,*b*.
TiO_2-SnO_2, spinodal decomposition, (6) 189*b*.
TiO_2-WO_2, melting relation in, (6) 187*g*.
uranium-aluminum, intermetallic diffusion in, (6) 186*e*.
uranium-carbon-chromium, numerical determination of phase compounds in, (10) 324*a*.
uranium-carbon-oxygen, phase relations in uranium monocarbide region at 1700°C, (3) 84*i*.
U-C-Si, four solid phase equilibrium in, (9) 287*e*.
uranium-iridium, (6) 188*f*.
uranium-oxygen, in range $UO_{2.00}$ to $UO_{2.45}$, high-temperature X-ray study, (3) 81*e*.
uranium-oxygen, in range $UO_{2.30}$ to $UO_{2.67}$, study by high temperature X-ray phase analysis, (10) 325*e*.
uranium-oxygen-carbon, research, (1) 31*i*.
uranium-rhodium, (6) 188*f*.
uranium-ruthenium, (6) 188*f*.
UO_2-CeO_2, thermal diffusion in, (9) 287*j*.
UO_2-Eu_2O_3, at high temperatures, (10) 326*a*.
UO_2-PbO_2, (9) 288*f*.
UO_2-Nb-H and UO_2-Ta-H, compatibility studies, (6) 172*j*.
UO_2-PuO_2, phase diagram, ideal solution behavior and heats of fusion from, (10) 322*a*.
UO_2-PuO_2, solid-liquid phase diagram for, (10) 325*j*.
UO_2-V_2O_5, study, (6) 189*c*.
UO_2-ZrO_2, phase equilibrium studies, (5) 156*b*.
UO_2-ZrO_2-CaO, thermal properties of compositions in, (1) 12*g*.
vanadium-carbon, chemical diffusion and phase equilibria above 1900°C, (5) 150*a*.
vanadium-selenium, near composition VSe, (4) 117*e*.
V_2O_3-V_5O_9, phase diagram and phase transition, (8) 255*h*.
H_2O-KCl-$CaCl_2$, thermodynamics at 25°C, (10) 326*g*.
YCl_3-CsCl, phase diagram, (3) 84*g*.
YCl_3-NaCl-KCl, (9) 287*g*.
Y_2O_3-Al_2O_3, effect of pressure on formation of compounds in, (7) 217*d*.
Y_2O_3-H_2O-Na_2O, Y_2O_3-D_2O-Na_2O, Y_2O_3-H_2O, and Y_2O_3-H_2O-NH_3, hydrothermal investigation, (7) 218*g*.
zinc and lithium chloride with lead chromate, (1) 33*g*.
Zn-Mn-O, in air, phase equilibria, (4) 114*a*.
$Zn_xCd_{(1-x)}SnAs_2$ semiconducting alloy, (4) 119*d*.
$ZnCl_2$-KCl, Raman spectroscopic study, (10) 324*d*.
ZnSe(*s*)-I_2(*g*), Bourdon gage determination of equilibrium in, (10) 319*d*.
Zr-Co-C, phase equilibria, (9) 285*g*.
Zr-Ag, ternary hydrides in, (8) 257*i*.
$ZrCr_2$-$TaCr_2$, structure, (4) 116*f*.
ZrO_2-HfO_2, (2) 60*b*.
ZrO_2-TiO_2, phase changes in solids measured in solar furnace, (4) 113*j*.
ZrO_2-TiO_2, phase studies, (6) 187*g*.

Tableware, earthenware and porcelain, (3) 70*a*.
to staellites, (6) 191*b*.
Talc. See also *Steatite*.
synthetic, infrared spectra, (7) 218*a*.
and use in manufacture of steatite, forsterite, and cordierite bodies, (6) 176*i*.
Tanks. See also *Furnaces, glass*.
water storage, glass-lined, (9) 263*c*.
Tantalates, alkali metals and alkaline earth metals, manufacture, and coating objects with, P (5) 142*d*.
Tantalum, borides, carbides, and oxides, diffusion rates in, (9) 280*b*.
carbide, cubic, magnetic properties, (9) 284*e*.
ductile-brittle transition in, (11) 351*h*.
grain growth during hot pressing of, (5) 153*b*.
high-temperature heat content, (5) 153*j*.
NbC-, solid solution, diffuse X-ray scattering by, (9) 280*g*.
cold-worked, containing oxygen and nitrogen, internal friction, (10) 322*f*.
diboride, reaction with carbon, (5) 133*e*.
fluoride, reactivity, (6) 188*g*.
halides Ta_6X_{14}, polynuclear, preparation, (4) 106*d*.
heat treatment of anodic oxide films on: IV, anodization in phosphoric acid solutions, (7) 207*b*.
metal, reaction with UO_2, (4) 114*h*.
monocarbide, thermal expansion to 3020°C, (6) 190*e*.

Tantalum (*continued*)
mononitride-titanium diboride, densification and wear resistance, (8) 237*c*.
oxidation, at low temperatures, effect of nitrogen, (4) 108*d*.
protection, analysis of modified silicide coatings for, (1) 3*g*.
by water vapor, kinetics, (6) 186*g*.
oxide, films, sputtered, photoconduction and trapping in, (3) 72*a*.
pentoxide, superstructure, high resolution electron microscopic observations of, (5) 153*i*.
sputtered, structure, (11) 343*a*.
sysems. See *Systems*.
$Ta_{1+x}Se_2$ phase, structural properties, (5) 158*j*.
Technetium, (IV) chloride, crystal structure, new AB_4 structure, (6) 184*e*.
and technitium carbide, superconductivity, (4) 117*g*.
Television screens. See *Screens*.
Television tubes. See *Tubes*.
Tellurides, lanthanum, and tellurium-deficient neodymium, crystal structure, (5) 150*b*.
metallic, and process for making, P (9) 273*g*.
semiconductor, method of passivating supports for, P (3) 73*d*.
Tellurium, dioxide, orthorhombic, crystal structure, refinement, (8) 256*c*.
materials survey, (3) 77*e*.
oxidation, kinetics, (5) 154*i*.
systems. See *Systems*.
Temperature, clay, versus kiln loss, (2) 42*j*.
coefficient, of metal film resistors, (10) 308*f*.
constant, method for growth of KTN single crystals, (1) 27*f*.
control. See also *Controls*.
controls, electronic, TROWI and TROFE, (5) 145*d*.
in creep of MgO, (11) 357*d*.
Curie, in Fe_2O_3-Mn_2O_3 and Fe_2O_3-Cr_2O_3 system, effect of solid solution on, (11) 352*c*.
of ferroelectric crystals, influence of impurities on, (9) 283*b*.
of ferromagnetic lanthanide chalcogen solid solution compounds, modifying, P (6) 178*f*.
of iron-aluminum and iron-silicon alloys, (5) 137*g*.
magnetic, relationship with cell sizes of solid solutions with ordered perovskite structure, (7) 221*d*.
Curie-point increases in EuO, (11) 357*f*.
Debye, of titanium diboride, (8) 253*c*.
dependence, of Al nuclear quadrupole interaction in ruby, (5) 159*e*.
of $BaTiO_3$ infrared reflectance spectrum, (10) 326*d*.
of cooperative relaxation properties in glass-forming liquids, (5) 129*c*.
of development of various phases in fused-cast magnesia-chromite brick, (7) 201*h*.
of elastic moduli of $91Y_2O_3 + 9ThO_2$ from 25° to 1100°C, (5) 159*e*.
of high frequency moduli of vitreous B_2O_3, (5) 129*d*.
of infrared dispersion in ionic crystals LiF and MgO, (11) 357*b*.
of stimulated Brillouin scattering in quartz, (11) 357*c*.
of transverse and longitudinal optic mode frequencies and charges in $SrTiO_3$ and $BaTiO_3$, (10) 326*f*.
distribution, along debiteuse during manufacture of flat glass, measurement by Foucault method (3) 64*f*.
field, around crystal growing from melt, determination, (6) 181*h*.
fracture-stress, relation with residual strain in BeO, (3) 67*j*.
gradients and junction, in refractory walls and structures, calculation, (10) 302*f*.
high, high pressure apparatus, P (5) 144*b*; P (8) 247*d*.
and high pressure apparatus, P (2) 55*d*.
high pressure-, studies: II, direct preparation of β- and γ-$LiBO_2$, (3) 81*a*.
modifications of compounds of type $MeIXO_4$ (Me = Cs, Tl; X = Re, Tc, Cl), (4) 118*a*.
processes, methods for study of kinetics of, (10) 314*j*.
reactions of clay mineral mixtures, (3) 81*c*.
research, localized-heating microchamber for, (10) 314*f*.
research, tetrahedral anvil apparatus for, (9) 277*i*.
high superconducting transition, in molybdenum carbide family of compounds, (4) 98*i*.
hydrothermal treatment, effect on formation of calcium sulfate hemihydrate from dihydrate (7) 194*g*.
low, and high vacuum, effect on strength of E-glass fibers, (7) 196*h*.
measurement, at 0.65μ with solar furnace, (4) 117*f*.
bibliography, B (4) 119*j*.
by diamond capsules, (8) 248*d*.
in glasses, (8) 230*e*.
in rotary kiln, P (1) 24*f*.
of temperatures or small temperature changes, circuit arrangement for, P (1) 23*h*.
using time measurement, P (1) 24*a*.
system for making series of, P (10) 316*f*.
ordering, of Fe_3Si alloy, (3) 70*j*.
profile measurements, spectroscopic, in inhomogeneous hot gases, (9) 277*d*.
rapid changes, apparatus for producing during mechanical behavior tests, (1) 20*h*.
resistance, of Cr-Si-O cermets, (2) 50*f*.
rise, rate, effect on sintering of pure alumina homodispersed particles, (1) 28*a*

Temperature (*continued*)
in rotary kilns, effect on clinker crystalline structure, (5) 124*h*.
Scale, International Practical, secondary reference points, (1) 32*a*.
sensing probe, P (3) 76*h*.
in sintering grate of type used for drying and calcining shapes, process and apparatus for controlling, P (1) 24*d*.
stresses, in aggregate cement paste model, (3) 63*a*.
Temperature measuring instruments, of forty years, discussion, (8) 248*h*.
for molten metal, P (5) 134*c*.
pyrometer, automatic optical system, with automatic gain control, P (3) 76*d*.
radiation, applying to glass manufacture, (3) 63*e*.
on rotary kiln, P (7) 213*f*.
sheaths, selection and use, (2) 46*a*.
ultrasonic, P (2) 55*h*.
pyrometric probe, P (11) 348*d*.
pyrometry, radiation, (3) 76*c*.
sensor, instantaneous, (9) 283*c*.
sensors, electrical, with connected heat conductive means, P (11) 347*f*.
thermocouple, assembly with deformable ferrule housing, P (7) 213*c*.
with cast iron contacting junction, P (9) 277*i*.
collector ring and brush assembly in rotary kiln, P (11) 348*h*.
effect of reducing atmospheres based on platinum: I, unprotected, (5) 145*g*.
fixed point, calibration facility, (4) 102*e*.
furnace and burner for testing, P (11) 347*i*.
gage control, P (11) 348*b*.
in glass furnaces, protective devices for, (8) 233*g*.
grid type, P (4) 103*g*.
for high temperature, (8) 249*i*.
high temperature, and protective tubes, with SiC thermoelectrodes, (3) 67*e*.
high temperature, use in quartz glass production, (8) 234*i*.
immersion, manufacture of refractory sheaths for, (9) 267*h*.
immersion-type, with sheath composed of sintered ceramic refractory, P (7) 204*i*.
intrinsic, transient response, (11) 347*c*.
with junction bead compressively supported by plug, P (11) 348*c*.
junctions, P (7) 213*c*.
location, protection, and connection, (4) 102*j*.
and manufacturing, P (7) 213*d*.
noble metal, with base metal leads, P (6) 181*f*.
probe, gaseous deposition method of making, P (1) 23*i*.
probe with plural junctions, P (10) 316*g*.
sheaths, ZrB_2, freezing on of, (2) 44*j*.
sheaths, ZrB_2, production, (9) 268*b*.
single, differentiating method and system, P (4) 103*h*.
for studying thermophysical properties of insulating materials at high temperatures, (10) 299*b*.
surface contacting, P (11) 348*a*.
surface temperature, fixture, P (4) 103*i*.
temperature emf relation for, (4) 102*g*.
for temperatures up to 2500°K, (5) 146*g*.
tungsten-rhenium, for use at high temperatures, (1) 23*i*.
ultrahigh temperature, (8) 249*j*.
thermometer, manufacture, P (7) 199*b*.
Tempering, of glass. See *Glass*.
Tension, apparatus, for vibrator screens, P (1) 20*f*.
behavior, of single crystal gold films, (5) 159*e*.
surface, and contact angle, computation by sessile-drop method, (9) 275*j*.
measurements, of refractory liquids using modified drop weight method, (8) 248*i*.
in reciprocal system K^+,Cd^{2+}-Cl^-,Br^-, (11) 357*a*.
of synthetic slags rich in manganese, (3) 87*h*.
Terbium, oxides, preparation and low-temperature magnetic properties, (5) 139*i*.
sesquioxides, crystalline varieties stable at high temperature, (5) 155*d*.
$TbLiO_2$, transformation under very high pressure and at very high temperature, (1) 33*a*.
Terminology. See *Nomenclature*.
Testing. See also *Analysis* and specific types.
apparatus, for high speed tools, (10) 293*g*.
apparatus, for sequence of transistors with condition responsive marker, P (1) 19*b*.
of ceramic materials, B (9) 288*g*.
device, fluid-pressure, for tension or compression, (7) 212*g*.
Machine, Universal, evaluation, (3) 75*i*.
machines, compression, mechanical aspects, (8) 248*h*.
mechanical, of brittle materials at 20° to 1200°C, apparatus for, (10) 313*g*.
nondestructive, (7) 212*g*.
for adhesive bonds using Fokker Bond Tester, (7) 213*b*.
electrical, radiographic, and ultrasonic techniques for material control by, (3) 76*a*.
of electrical porcelain with ultrasonics, (6) 181*a*.
of fireclay nozzles by sonic technique, (8) 239*d*.
using photoelastic coating technique, (7) 212*h*.
of thin materials and electronic assemblies, film and filmless radiographic systems for, (7) 212*d*.
techniques, for rock mechanics, B (3) 90*g*.
tensile, of prestressed concrete elemens, single cylinder hydraulic machine for, (10) 294*i*.
thermal nondestructive, application of cholesteric liquid crystals to, (7) 211*j*.

Testing (*continued*)
ultrasonic phase, for unbound detection, (7) 213*d*.
uniaxial and biaxial, of brittle materials, (9) 276*i*.
Tests, drying, empirical, for clays, (6) 180*b*.
laboratory, for determining absorption of aggregates, (4) 102*d*.
torsion, as aid in determining quality of basic refractories, (9) 269*f*.
valid, designing, (1) 20*j*.
whiteware control, effectiveness, (9) 270*j*.
Texture, parameters, evaluation, (9) 287*h*.
in porous bodies, determination, (10) 317*g*.
Thallium, chloride, color centers in, (8) 252*h*.
optical spectra in glasses as related to crystals and solutions, (4) 93*h*.
oxide glaze, with ruthenium oxide additive, P (2) 52*g*.
systems. See *Systems*.
tetrachlorosulfide and selenide, (9) 287*h*.
thallous bromide, lattice dynamics, (9) 283*g*.
Thermal analysis, differential, application to glass technology and research, (11) 333*d*.
differential, curve, analysis using transfer function, (3) 78*h*.
curves, kaolinite and quartz, evaluation with high temperature cell, (5) 145*i*.
heating problems, (6) 181*b*.
of materials with very volatile components, (4) 102*d*.
of refractories, apparatus for measuring, (9) 276*g*.
sample holder for use to 1700°C, (4) 102*e*.
for study of silica brick, (11) 339*c*.
in study of changes in glass composition, (11) 333*e*.
in vacuo of portland cement and β-dicalcium silicate pastes, (8) 228*c*.
for study of thermal properties of glass in anomalous interval, (10) 299*e*.
of palladium-phosphorus system, (4) 119*a*.
permeability, (10) 315*f*.
review, (10) 316*a*.
Thermal conductivity. See *Conductivity*.
Thermal decomposition. See *Decomposition*.
Thermal expansion. See *Expansion*.
Thermal properties, of antiferromagnetic rare-earth orthoaluminates, (11) 356*i*.
of glasses, at low temperatures, (7) 197*d*.
of glass in anomalous interval, study by DTA, (10) 299*e*.
of silica: I, effect of temperature on infrared reflection spectra of quartz, cristobalite, and vitreous silica; II, thermal expansion coefficient of vitreous silica, (3) 87*d,e*.
Thermal shock resistance. See *Shock resistance, thermal*.
Thermistors. See *Resistors, electrical*.
Thermochemistry. See *Thermodynamics*.
Thermocouples. See *Temperature measuring instruments*.
Thermodynamics, of beryllium fluoride vapor, (3) 80*j*.
characteristics, of $NiAl_2O_4$, (10) 326*a*.
chemical bond in, B (8) 259*e*.
conditions, for spinodal decomposition in multicomponent system, (6) 190*f*.
data, for cuprous and cupric oxides, (4) 118*f*.
of formation of dolomite, (11) 355*b*.
functions, by emf measurements on solid galvanic cells in nonstationary conditions—system $Al + Al_2O_3$, (3) 87*f*.
from equilibrium constants, evaluation, (3) 81*a*.
of two-component system from an empirical equation of state, equations for calculating, (6) 185*c*.
introduction, B (5) 161*f*.
investigation, of oxychlorides of rare earth elements, (10) 326*b*.
measurements and calculations, comparison with direct experimental determination of solid-vapor equilibria, (8) 252*h*.
of miscibility gap system and test of nucleation theory, (7) 222*g*.
of phase transformations of quartz between 848° and 1953°K, (7) 222*h*.
properties, of aluminum silicates, (5) 159*c*.
of beryllium compounds, (11) 357*e*.
of gallium monoxide, (5) 152*b*.
of manganese silicides, (9) 288*b*.
of refractory compounds up to 3000°C, (1) 32*g*.
of refractory materials, evaporator for studying, (11) 346*j*.
of several solid phases of compound InSb, (6) 190*g*.
of thorium dicarbide and monocarbide, (10) 326*c,e*.
of three lithium-aluminum silicates, (4) 118*k*.
of titanium monosulfide, (3) 81*d*.
of uranium carbides, (10) 326*f*.
of uranium compounds: II, low-temperature heat capacity and entropy of three uranium nitrides, (3) 87*k*; III, low temperature heat capacity and entropy of UP and U_2P_3, (7) 222*e*.
of uranium mononitride from 5° to 350°K, (10) 327*b*.
of UN, (2) 58*g*.
of van der Waals fluid in two-phase region, (3) 87*j*.
of reactions in SiO_2-SiC system, (9) 288*d*.
relations between composition and ferroelectric-to-antiferroelectric phase transitions, (11) 343*b*.
of Soret effect in ionic crystals, (3) 88*a*.
study of Mn-O-CO_2 system, (11) 357*f*.
of system NaF-AlF_3, (3) 87*f*.
of ternary system water-potassium chloride-calcium chloride at 25°C, (10) 326*g*.
of titanium oxides, (11) 351*e*; (11) 353*b*.
Thermodynamics (*continued*)
of titanium-oxygen system, discrepancies in, (11) 351*e*.
of vaporization of lithium oxide, boric oxide, and lithium metaborate, (5) 159*e*.
Thermoelectric materials, mosaic interconnected by semiconductor leg protrusions and metal coating, P (10) 311*f*.
for sound ingots, method of casting, (7) 207*e*.
Thermoelectric properties, of molten silver nitrate-sodium nitrate system, (11) 357*g*.
of pressure-sintered GaSb-GaAs alloys, (4) 99*g*.
of yttrium-group V and yttrium-group VI binary and ternary compounds, (2) 50*j*.
Thermoelectricity, bodies, method of producing, P (4) 100*g*.
bodies, telluride, method and materials for obtaining low-resistance bonds to, P (10) 310*f*.
body, two-phase, comprising boron-carbon matrix, P (1) 19*c*.
device, chalcogenide, with braze comprising antimony compounds and method of forming, P (6) 177*c*.
device, comprising 100 $SnO_2 \cdot x Sb_2O_3$, P (5) 143*a*.
effects, unwanted, reduction in semiconductor devices, P (5) 142*f*.
elements, hot-pressing, (1) 16*f*.
modules, P (4) 101*e*.
power, of ionic crystals: I, general theory; II, of sodium bromide containing barium bromide, (2) 50*i*.
in nonstoichiometric α-Nb_2O_5, (5) 140*c*.
of uranium during oxidation at 10^{-3} torr and 500° to 800°C, (4) 109*e*.
of VO_2 whisker, (10) 326*h*.
Thermography, complex, in studying burning process of raw mix, (2) 37*f*.
of structural changes in glass after γ-irradiation, (8) 234*g*.
Thermogravimetry, of composition-oxygen partial pressure diagram of wustite ($Fe_{1-y}O$), (5) 159*e*.
isothermic, heater controller for, P (1) 23*i*.
of oxidation of UO_2 particles prepared from U_3O_8 calcined under various conditions, (4) 118*j*
of rare earth metal oxalate hydrates, (4) 118*j*.
Thermoluminescence. See *Luminescence*.
Thermometers. See *Temperature measuring instruments*.
Thermophysical properties. See *Physical properties*.
Thermoplastics. See *Plastics*.
Thickness, coating on glass articles, method of measuring, P (11) 336*h*.
of deposited thin layer of Ni, determination with electron microscope, (11) 346*g*.
of dielectric members, apparatus for measuring, P (10) 316*b*.
of thin films, methods for measuring, (10) 307*d*.
Thixotropy, of porcelain slips, control, (6) 175*e*.
properties, of clay mineral suspension, electrophoretic indication of, (7) 217*i*.
Thin sections. See *Microscopy*.
Thoria. See *Thorium, oxide*.
Thorite, growth and preferential doping, (10) 321*e*.
Thorium, systems. See *Systems*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
carbide, hydrolysis in D_2O, (4) 111*a*.
carbide, reaction with aqueous solutions of hydrochloric acid and sulfuric acid, (5) 157*f*.
dicarbide and monocarbide, thermodynamic properties and nonstoichiometry, (10) 326*c,e*.
dioxide, fission fragment damage in, direct observation, (9) 281*b*.
single crystals, growth and properties, (8) 254*d*.
xenon migration and trapping in, (10) 327*a*.
hydride, production, P (8) 241*a*.
monocarbide, electrical resistivity, magnetic susceptibility, and thermal expansion, (10) 320*j*.
mononitride, decomposition pressure and melting point, (11) 351*g*.
nitrate solutions, aqueous, fluoride adsorption by thorium oxide in, P (11) 340*c*.
oxide, dense, and sulfate containing, preparation from aqueous thorium nitrate solution, P (5) 135*g*.
dispersions, in beryllia, mechanical properties, (1) 30*c*.
gel, crystallite size measurements, (1) 27*k*.
gel, equivalence of X-ray and electron microscopy crystallite sizes in, (5) 152*g*.
single crystals, grown by vapor deposition in solar furnace, (8) 258*e*.
and thoria-yttria, electrical conduction in, as function of oxygen pressure, (5) 138*b*.
pyrophosphate, preparation, P (2) 52*b*.
sulfides, free energies of formation, from solid-state emf measurements, (5) 152*f*.
Th_2N_2O and ThO_2 phases, equilibrated with different nitrogen (plus oxygen) atmospheres, ranges of composition, (3) 85*f*.
and uranium dicarbides, limited solid solutions, (6) 187*a*.
-uranium oxides, production, P (7) 205*a*.
Tile. See also *Pipe*.
P (1) 16*a*.
acoustical, apparatus for producing, P (3) 63*a*.
bodies, method and apparatus for handling and placing in precise locations, P (2) 49*a*.
bodies, preblended, (3) 70*b*.
and brick research in India, (9) 266*d*.
burned clay, for use in lining irrigation and drainage works, specifications, (3) 66*h*.
ceramic, adhesive composition for fixing, P (1) 15*j*.
glazing and decorating, P (5) 137*c*.
improving quality, (9) 270*h*.
installations, strain investigations, (1) 10*e*.
Tile (*continued*)
drain, cluster, extrusion die for, (8) 236*e*.
drain, structure, P (5) 131*b*.
drainage, P (11) 337*a*.
facing, industry, evolution and problems of quality, (3) 66*g*.
faience, modulus of elasticity, determination by different methods, (10) 305*e*.
floor, double-layer stoneware, determination of producibility by laboratory methods, (2) 42*h*.
floor and wall, characteristics and manufacturing methods, for prefabricated building, (9) 270*h*.
floor and wall, future developments, (9) 266*e*.
flooring, mechanical device for laying, P (7) 206*h*.
history, B (6) 192*f*.
hot processing, (2) 42*i*.
industry, Bulgarian, (2) 42*h*.
industry, line production by stabilizing technological conditions, (1) 10*j*.
Kervite, (slip cast) manufacture, (7) 206*i*.
panels, P (4) 98*g*.
roof, makers, and potters, in South Italy, Sicily, Greece, B (4) 121*d*.
roofing, glazed, effect of particle size distribution on bodies for, (1) 15*e*.
setter, P (5) 137*d*.
stoneware, production, (3) 70*d*.
structural clay, containing sound absorbing pad, P (1) 10*h*.
unfired, increasing breaking strength by pressing from both sides, (10) 312*f*.
vitreous, and mounting structure for, P (2) 49*b*.
wall, ceramic, new earthenware compositions for, (9) 271*i*.
earthenware, frost damage on, (7) 206*a*.
and floor industry, rationalization and automation in, (4) 95*h*.
production with spray-dried powders, (8) 242*e*.
Time, effect on formation of calcium sulfate hemihydrate from dihydrate, (7) 194*g*.
Tin, as dopant in GaAs crystals, P (10) 311*g*.
oxide, lattice parameter, as function of pressure, (7) 219*c*.
sulfide and selenide, optical absorption in, (9) 282*e*.
systems. See *Systems*.
telluride, single crystal growth, (10) 325*h*.
Tintinaite, antimony analog of kobellite, (9) 288*e*.
Titanates. See also *Dielectrics* and specific types.
alkali metal, thermally stable fibrous, P (8) 246*d*.
lead zirconate, piezoelectric ceramic, with chromium and thorium additives, P (7) 209*i*.
piezoelectric lead zirconate, containing rhodium, P (7) 209*j*.
with positive temperature coefficients of resistance, P (7) 210*f*.
systems. See *Systems*.
Titania. See *Titanium, dioxide*.
Titanium, -bearing ores, digestion, P (11) 349*g*.
boride, preparation, properties, and uses, (6) 174*g*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
carbide. See also *Cermets*.
and boride, porous parts, relations in sintering of, (11) 339*c*.
components, slip casting, (2) 46*b*.
fibrous, (1) 24*j*.
field-ion microscopy, (8) 253*h*.
finely divided, production, P (1) 14*f*.
formation by chemical vapor deposition, (3) 81*f*; correction, (7) 217*g*.
high-temperature heat contents, (3) 81*c*.
single crystal, microstructure, (8) 255*e*.
synthesis, effects of preshock treatment, (7) 201*e*.
chlorides, reaction rates with titanium-oxygen alloy system in molten NaCl, (4) 114*j*.
determination, in titanium dioxide, (10) 314*d*.
determination, by X-ray fluorescence method using ^{55}Fe radioactive source, (11) 346*h*.
diboride, electrical resistivity, elastic modulus, and Debye temperature, (8) 253*c*.
hot-pressing, with binding metals, (8) 237*f*.
production, P (2) 48*b*.
reaction with carbon, (3) 85*j*.
tantalum mononitride-, densification and wear resistance, (8) 237*c*.
dioxide. See also *Rutile*.
amorphous, preparation as films, (7) 216*b*.
cohesive energy, (8) 252*f*.
effect on sitallization of glass in system $MgO-Al_2O_3SiO_2$, (6) 169*f*.
effect on spalling characteristics of fireclay refractories, (5) 131*k*.
fine particle size, means for producing, P (4) 105*f*.
hydrolyzed, surface properties: IV, rates of sorption, (1) 33*a*.
kinetics of reaction with $BaCO_3$, (9) 283*d*.
lattice parameter, as function of pressure, (7) 219*c*.
lead removal from, (7) 203*a*.
minor additions, effect on sintering behavior of UO_2, (1) 11*g*.
phase transition under various pressures, (3) 85*c*.
and phosphoric acid, reaction products, binding properties, (1) 11*a*.
pigment, process for production in controlled calcination of basic titanium sulfate, P (4) 105*g*.
pigment, purification with organic sequestering agents, P (10) 318*e*.
pigmentary, treatment, P (8) 251*g*.
preparation, P(3) 78*b*; P(8) 251*d*.
process and apparatus for continuously producing by oxidation of vaporized titanium tetrachloride, P (3) 78*a*.

Titanium, dioxide (*continued*)
produces better white in glass enamel, (11) 332*g*.
production, P (1) 26*c*; P (5) 149*d*.
separation, P (1) 26*a*.
shock-wave compression and X-ray studies, (4) 115*c*.
sintering, with rutile crystals, MnO, and Na_2O as additives, (6) 173*j*.
solubility in Al_2O_3, (2) 59*g*.
transition metal ions, diffusion into rutile, (10) 319*e*.
type determines results, (11) 349*d*.
hydride, production, P (8) 241*a*.
hydroxide, producing, and high grade pigments produced, P (5) 148*e*.
impurities, removal, for beneficiation of clay, P (6) 183*b*.
and manganese, reactive sputtering of, (10) 308*e*.
mononitride, electronic structure and ground-state properties, (11) 352*c*.
monosulfide, high-temperature vaporization and thermodynamic properties, (3) 81*d*.
monoxide, oxidation at high temperatures, (11) 355*e*.
nitride, reaction with Fe-group metals, Mo, and W, (3) 66*i*.
nitride, process and apparatus for manufacture, P (1) 13*j*.
oxide, removal of lead from, (7) 203*a*.
role in system silica-titanium oxide-potassium oxide: I, viscosity measurement, (7) 197*c*; II, expansion measurements, (11) 335*c*.
time dependent conductivity, (6) 190*a*.
high-temperature vaporization and thermodynamics: I, vaporization characteristics of crystalline phases, (11) 353*b*.
high-temperature vaporization and thermodynamics, and dissociation energy of TiO(*g*): II, tri-titanium pentoxide, (11) 351*e*.
systems. See *Systems*.
tetrachloride, oxidation to produce TiO_2, P (2) 57*a*.
tetrachloride, process for production, P (4) 105*f*.
(IV), gravimetric determination, with new reagent, (5) 145*g*.
Ti_2O compound, in titanium-oxygen system, thermal stability, (9) 288*b*.
Ti_6O, interstitial superlattice, and transformation, (10) 322*g*.
Ti_3O_5, neutron diffraction data, (11) 354*i*.
resistivity and magnetic order in, (11) 356*g*.
single crystals, growth from melt, (1) 29*j*.
values, selectively carbiding, P (9) 270*e*.
volumetric analysis, (2) 55*a*.
Titration. See also *Analysis*.
continuous, for determination of cation-exchange capacity, (7) 212*d*.
precipitation, for simultaneous determination of alkali and alkaline-earth metals in nonaqueous medium, (4) 103*h*.
Tobermorite, analysis by silicate-derivative technique, (3) 79*a*.
Tools. See also *Drills*.
bits, alumina based ceramic, B (5) 160*a*.
cutting. See also *Abrasives*.
abrasive, P (3) 61*h*.
alumina-based, (6) 163*f*.
WC, method of making and product, P (7) 193*g*.
diamond-carrying, method for making, P (1) 1*h*.
diamond, manufacture by rolling powders, (6) 163*j*.
for precision machining of ferrites, (6) 176*h*.
for sawing and grooving quartz (6) 176*d*.
grinding. See *Grinding apparatus*.
wire saw, for cutting and grinding, P (1) 1*g*.
Topography, X-ray, of Czochraliski ruby, (1) 34*a*.
X-ray, for evaluation of bulk and epitaxial GaAs, (8) 243*e*.
examination of plastic deformation of diamond, (1) 26*j*.
of lithium ferrite, (3) 88*e*.
Trace elements. See *Elements*.
Tracers. See *Radioactive tracers*.
Transducers, assembly, for producing ultrasonic vibrations, P (11) 345*c*.
crystal temperature and pressure, P (3) 76*e*.
electromechanical, P (11) 343*e*.
electromechanical, using piezomagnetic manganese ferrous ferrite, P (7) 208*f*.
using ferroelectric circuit element material, P (1) 17*h*.
field-effect pressure, P (7) 208*h*.
heat flux, (4) 102*h*.
isolated glass, P (8) 244*g*.
piezoelectric ceramic, (5) 139*h*.
piezoelectric pressure, P (2) 52*b*.
piezoelectric ultrasonic, method of forming, P (9) 273*b*.
production, P (8) 245*d*.
segmented ferrite sonar, with permanent magnet bias, P (8) 246*e*.
semiconductor, P (10) 311*d*.
sonic, P (5) 143*b*.
structure, with emitter region epitaxially grown over base region, P (11) 345*c*.
ultrasonic, P (5) 143*c*.
variable capacitance force measuring, P (8) 246*h*
zinc-oxide film microwave acoustic, (3) 88*h*.
Transfers. See *Decoration*.
Transformations, behavior, of two quartzites, (1) 33*h*.
crystalline, of rare earth sesquioxides at high temperatures, (1) 27*g*.
crystalline, of SAP transition aluminas to stable α-Al_2O_3 phase, (6) 185*g*.
cubic-monoclinic in rare earth sesquioxides, effect of lime additions, (7) 217*a*.

Transformation (*continued*)
direct, of hexagonal boron nitride to denser forms, (5) 151*c*.
of glass, kinetics by thermal analysis: I, glycerol, (5) 127*i*.
of graphite to diamond, catalytic effects, (5) 149*j*.
of gypsum to hemihydrate in water, (2) 36*d*.
of interstitial superlattice of Ti_6O, (10) 322*g*.
of magnetic properties of scandium-containing ferrites, causes, (1) 16*b*.
of $MnT'O_3$, hexagonal form, under high pressure to perovskite form, (1) 33*j*.
martensitic, in U_3Si, metallographic evidence for, (10) 323*h*.
mutual, of thermal and anodic SiO_2 films, (11) 354*h*.
phase, on dissociation of β and γ forms of uranium trioxide, (7) 220*a*.
of higher carbide of vanadium, (9) 285*i*.
kinetics, of lithium aluminosilicate glass during sitallization, (8) 232*g*.
in Mn_6Si_5, (10) 324*i*.
of quartz, between 848° and 1953°K, thermodynamics, (7) 222*h*.
polymorphic, of orthorhombic to tetragonal PbO, solid state mechanism for, (6) 189*a*.
polymorphic, of SiO_2, effect of mineralizers, (7) 217*d*.
of $SmLiO_2$, $EuLiO_2$, $GdLiO_2$, and $TbLiO_2$, under very high pressure and at very high temperature, (1) 33*a*.
thermochemical, of copper iodide, (9) 287*h*.
of TiO_2 prepared by gas phase reaction from $TiCl_4$, effect of additives, (5) 151*f*.
Transformers, with windings between two ferrite strips, P (2) 52*h*.
Transistors, P (1) 19*c*; P (9) 274*d*.
base, and method of making P (9) 275*b*.
chips, apparatus for handling and cleaning, P (7) 208*g*.
constant current gain composite, P (10) 309*i*.
with constant gain over broad temperature range, P (6) 178*i*.
conveying and orienting apparatus for, P (7) 208*a*.
device, silicon, P (4) 101*b*.
electroluminescent device, P (11) 343*d*.
etching contacts on, to improve power output, P (9) 273*i*.
field-effect, with gate-insulator variations, P (6) 177*j*.
with improved transmission admittance, P (3) 72*g*.
with induced p-type channel, P (8) 244*c*.
GaAs, method of forming by diffusion, P (2) 51*h*.
GaAs, and methods of making, P (1) 17*j*.
germanium, P (1) 17*j*.
germanium alloy, baked in oxygen, (5) 139*e*.
germanium alloy, baked in oxygen, life characteristics, (5) 138*h*.
high frequency power, with electrodes forming transmission lines, P (9) 273*d*.
high power multiemitter, P (8) 244*f*.
with layer of soft metal film for dividing, P (4) 99*d*.
insulated-gate field-effect, P (6) 177*c*; P (9) 273*i*,*j*.
metal base, and thin-film metal base, method for manufacturing, P (6) 177*j*.
metal-oxide-semiconductor field effect, P (1) 18*i*.
miniature, enclosed in glass disk-shaped housing, P (7) 209*h*.
narrow emitter, making by masking and diffusion, P (9) 274*a*.
optically coupled, P (5) 141*g*.
pressure-responsive, P (5) 142*c*.
remote cutoff field effect, P (3) 74*e*.
short-channel field-effect, with impurity gradient in channel increasing from midpoint to each end, P (11) 345*f*.
small junction area S-M-S, P (10) 311*d*.
structure, low capacity and resistance, using two-conductivity collector region, P (7) 209*c*.
structure, variable gain, employing base zones of various thicknesses and resistivities, P (7) 210*g*.
thin film, for electroluminescent translator, P (7) 208*e*.
ultrahigh-frequency, "power tower" for, (10) 305*j*.
unipolar, with narrow channel between source and drain, P (1) 19*d*.
and varistor, method of forming by reduction and diffusion, P (2) 51*h*.
wide band gap emitter, P (5) 141*i*.
Transitions, cubic-tetragonal, in $NiCr_2O_4$, (3) 79*g*.
ductile-brittle, in tantalum carbide, (11) 351*h*.
ferroelectric, behavior of specific heat, thermal expansion, and isothermal compressibility near, (10) 319*d*.
forbidden, in electron spin resonance of Mn^{2+} in $BaTiO_3$ single crystal, (3) 81*d*.
free-to-bound and bound-to-bound, in CdS, (8) 253*j*.
magnetic, first order, in metallic perovskites of manganese, (4) 98*i*.
member, strain relieving, for contacting semiconductor devices, P (9) 275*a*.
phase. See *Phase*.
radiative and nonradiative, in fluorescence decay of Eu^{3+} in $SrTiO_3$, (6) 188*b*.
in NaCl, searched to 25 kbars, (11) 356*j*.
structural and magnetic, in $Sr_3(NiMo)O_6$, (7) 221*j*.
superconducting, in molybdenum carbide compounds, (4) 98*i*.
in vapor-deposited alumina from 300° to 1200°C, (1) 33*b*.
zero-photon, at M' and R' centers in alkali halides, (11) 358*c*.

Transmission, device, for short electromagnetic waves, especially highest frequency tubes, P (8) 244*h*.
optical, of graphite compounds, (6) 187*a*.
Transport, ionic, measurement in mixed alkali and soda-lime-silica glasses, (8) 233*f*,*g*.
nonohmic current, phenomena in high resistivity GaAs, (3) 83*j*.
phenomena, in pure and doped MgO, (5) 159*f*.
processes, in thermal growth of metal and semiconductor oxide films, (10) 309*c*.
properties, in graphite, (4) 117*g*.
of LaF_3, (9) 288*f*.
of semi-insulating CdTe using nuclear particles, (3) 72*h*.
in solid and liquid mixtures of system Li_2SO_4-Ag_2SO_4, (5) 159*g*.
thermal and electronic, of p-type ZnSb, (8) 258*c*.
single carrier, in thin dielectric film, (11) 342*f*.
tritium-labeled field-induced proton, in SiO_2 films, (11) 357*h*.
Trapping, in sputtered tantalum oxide films, (3) 72*a*.
Tricalcium. See *Calcium*.
Tridymite, chemical, X-ray, and optical data, (6) 187*i*.
Triodes, device, high frequency field-effect, P (8) 244*e*.
insulated-gate field effect, with insulator having same atomic spacing as channel, (P) (3) 73*a*.
mesa multichannel field-effect, P (8) 245*a*.
planar multichannel field-effect, P (8) 245*j*.
solid state, with gate electrode therin subtending portion of source electrode, P (4) 101*d*.
stacked electrode field effect, P (8) 246*c*.
Tubes, brightness amplifier, fluorescent screen for, P (3) 72*g*.
cathode, cold, gas discharge, with optically opaque masking plate, P (5) 140*i*.
cathode ray, coating, P (7) 209*d*.
color screen, P (9) 265*d*.
envelopes, and methods for preparing parts and making envelopes, P (5) 129*e*.
faceplate, of energy-conducting fibers, P (5) 129*g*.
faceplate, method and apparatus for supporting and gaging, P (5) 130*f*.
fiber optic, assembly, P (4) 100*a*.
flying-spot, for color TV, new phosphor for, (2) 49*j*.
generating circular beam, P (8) 244*a*.
image orthicon, with copper screen target having chromium supported MgO film, P (4) 100*d*.
with improved fiber optic faceplate, P (1) 8*e*.
with integral light trapping filter, method of making, P (4) 95*c*.
manufacture, P (3) 72*a*; P (8) 235*e*.
metal/ceramic, P (8) 245*a*.
with mosaic type phosphor screen, P (3) 72*b*.
parallel light, with longitudinal axes making oblique angle with display surface of, P (4) 100*i*.
with perforated aluminum film graticule overlying illuminescent layer, P (3) 72*b*
reinforcing, P (8) 244*a*.
removing airlines in, P (1) 9*g*.
with screen having integrity against stress, P (5) 140*e*.
subtractive type color, with overlapping color phosphor areas, P (1) 10*a*.
color, picture, of line-screen sensing variety, P (5) 141*j*.
triad, with heat-absorptive material on aluminum screen backing for cooling shadow mask, P (10) 309*i*.
with triplet phosphor strips making 40° to 70° angle with horizontal, P (4) 99*g*.
TV picture, and mating support members for mounting color selection mask within tube, P (3) 72*c*.
color-producing, with screen containing plurality of birefringent materials, P (10) 309*i*.
electron, gettering system for, P (3) 72*h*.
method to introduce vaporizable materials, P (5) 140*b*.
photocathode for, P (9) 274*c*.
separating frit sealed parts of, P (9) 274*j*.
sockets, method and means for making, P (3) 65*i*.
thermal connector for, P (4) 97*i*.
X-ray fluorescent analysis of triple carbonates for, (2) 50*d*.
electron-beam, P (11) 343*k*.
glass, apparatus for and method of shaping open end, between cooperating rollers, P (4) 94*d*.
graphite, extuded, anisotropy, (5) 131*e*.
high power traveling wave, P (8) 244*h*.
parallel, ceramic lined return bend for, P (1) 15*j*.
protective, and high-temperature thermocouples with SiC thermoelectrodes, (3) 67*e*.
television camera, employing photosensitive target with transparent member for absorbing reflected light from target, P (7) 210*d*.
television camera, used in ultrasonic inspection system, (7) 212*f*.
ultrahigh frequency thermionic, dielectric shield for, P (4) 99*g*.
vacuum, polyoptical sealing, (5) 139*i*.
vacuum, provided with light conducting members and a screen of high photoelectric sensitivity, P (7) 210*g*.
Tungstates, laser induced Raman spectra, (6) 186*j*.
of type Ln_2SO_6, Eu^{3+}-activated, energy transfer in, (10) 321*b*.
vitreous alkali, (2) 40*f*.

Tungsten, boride, reaction with carbon, (5) 133*b*.
bronzes, electronic properties, (5) 138*f*.
low in inserted element, structural evolution as function of temperature, (1) 32*h*.
synthesis at high pressure, (6) 189*k*.
carbide, coated article of manufacture, P (9) 263*c*.
-cobalt hard alloys, effect of carbon content on mechanical properties, (1) 11*f*.
formation by explosive shock, (2) 44*i*.
high-temperature heat content, (5) 153*j*.
iron bonded, P (8) 240*g*.
-10% Fe and WC-10% (Fe-Co) cemented carbides, properties, effects of carbon content, (9) 281*c*.
porous parts, relations in sintering of, (11) 339*c*.
synthesis, effects of preshock treatment, (7) 201*e*.
-cobalt alloys, reaction with oxygen at 1000° and 1100°K, (2) 45*i*.
compatibility with molten UO_2, (4) 106*h*.
doped, model for, (9) 262*h*.
fluorides, reactivity, (6) 188*g*.
hexachloride, purification, (4) 114*d*.
-indium powder bodies infiltrated with copper, P (3) 74*d*.
minerals, high-temperature two-phase extraction technique, (9) 278*h*.
monocarbide, preparation, P (7) 205*i*.
powder bodies, infiltrated with copper-titanium alloys, P (3) 74*e*.
protection at high temperatures, (1) 4*i*.
reaction with flowing steam at 1000° to 1700°C, (7) 220*h*.
systems. See *Systems*.
trioxide, coprecipitated with TiO_2, light sensitivity, (4) 114*d*.
crystals, birefringence, (3) 79*b*.
properties modified by substitution of Mo and Cr, (1) 31*d*.
solid-state studies, and significance to tungsten bronze theory, (5) 158*g*.
substoichiometry, (5) 158*g*.
WO_2Br_2, $WOBr_4$, WBr_6, and WBr_5, reoentgenometric constants, (3) 86*d*.
WSi_2, solubility of disilicides of transition metals in, (11) 339*h*.

Tuyeres. See *Refractories*.

Ultrasonics. See *Sonics*.

Uranates, formation, in molten lithium nitrate-sodium nitrate, (4) 115*a*.

Urania. See *Uranium, oxide*.

Uranium, alloying behavior of HfB_2 with, (9) 279*h*.
atoms, ejection from sintered UO_2, (10) 320*d*.
atoms, ejection from sintered UO_2 by fission fragments in different gases and at different gas pressures, (4) 108*j*.
carbide, compressive creep, (9) 266*i*.
high quality, preparation, P (10) 304*j*.
hydrolysis in D_2O, (4) 111*a*.
irradiated, sweeping of bubbles by grain boundaries in, (10) 325*g*.
manufacture, P (5) 135*h*.
and oxide, contaminated with carbon-containing phases, behavior, (10) 324*d*.
particles, submicron, formation in metallic uranium, P (1) 12*e*.
-Pu phosphide, as reactor fuel, P (4) 97*j*.
preparation, (1) 12*e*.
pure dense hypostoichiometric, P (11) 340*e*.
reaction with aqueous solutions of hydrochloric acid and sulfuric acid, (5) 157*f*.
single crystals, high carbon hyperstoichiometric, structure, (4) 116*c*.
solidification characteristics in continual casting of, (6) 174*c*.
thermodynamic properties, (10) 326*f*.
wetting, (10) 326*g*.
ceramics, application of X-ray diffraction analysis to: II, quantitative analysis of uranium carbides, (8) 247*i*.
compounds, tetravalent, pentavalent, and hexavalent, of type $A_2BB'O_6$, (5) 159*j*.
compounds, thermodynamic properties: II, low-temperatures heat capacity and entropy of three uranium nitrides, (3) 87*h*; III, low temperature heat capacity and entropy of UP and UP_4, (7) 222*e*.
dicarbide, heat content, from 1484° to 2581°K, (5) 153*h*.
dicarbide and sesquicarbide, standard molar free energy of formation, (11) 357*c*.
dioxide-Al_2O_3, grain growth in, in presence of liquid phase, (8) 254*c*.
ceramics, sintering: I, preparation by sintering at low temperatures; II, determination of specific surfaces and initial materials for preparation; III, dispersity and microagglomerate state; IV, application of activators of sintering, (3) 68*c*.
containing small additions of other oxides, oxidation, (5) 156*h*.
δ-, high temperature modification: I, preparation and characterization; II, single crystal studies, (4) 107*d*,*f*.
doped, hydrofluorination kinetics, (3) 81*h*.
effect of electrical conduction on measurement of high temperature thermal conductivity as determined by radial flow techniques, (4) 108*i*.
effect of minor additions of TiO_2 on sintering behavior, (1) 11*g*.
electrical conductivity, (1) 11*h*.
epitaxial growth on graphite, (9) 282*e*.
epitaxial film, fission fragment damage in, (4) 110*b*.

Uranium dioxide-Al_2O_3 (*continued*)
first-order magnetic phase change in, (8) 258*a*.
as fuel in power reactors, (6) 174*h*.
grain boundary grooving in, (11) 353*g*.
helium dissolution theory in: I, interatomic forces in; II, helium solubility, (6) 190*b*.
high-temperature enthalpy and heat of fusion, (6) 186*g*.
high-temperature vapor-pressure studies by effusion method and thermodynamic interpretation, (7) 218*e*.
hot-pressing, (2) 44*d*.
interstitial distribution of O_2 atoms, (5) 150*h*.
-iridium composition, sintered, P (1) 14*f*.
irradiated, microanalysis of inclusions, (2) 45*a*.
irradiated, migration of gas bubbles in, (5) 132*i*.
irradiated, solid fission products in, (11) 339*f*.
molten, compatibility of W with, (4) 106*h*.
-Nb and UO_2-Ta, preparation as fuel elements by vapor deposition of metal in fluidized bed, (6) 173*a*.
nonstoichiometry in, (7) 220*c*.
origin, influence on microstructure of sintered urania pellets, (1) 11*a*.
oxidation, (1) 30*i*.
oxidation by CO_2 in reactor flux, (3) 84*j*.
oxidation and U_3O_{8-x} superstructure phase structure, electron diffraction investigation, (5) 151*h*.
particle properties and sintering behavior, (7) 202*c*.
particles in cermets, irradiation behavior, (11) 338*g*.
particles, microstructural modifications produced by irradiation, (6) 173*h*.
particles, prepared from variously calcined U_3O_8 distribution investigated by sedimentation analysis, (1) 28*b*.
pellets, high density, use of carbon dioxide in low-temperature sintering, (10) 304*i*.
pellets, sintered, influence of UO_2 origin on microstructure, (1) 11*a*.
photocurrent and thermal release time studies of, (9) 285*j*.
powdered, relation between surface area and oxidation temperature, (4) 115*h*.
preparation by fused salt electrolysis using UO_2 or UF_4 as starting material, (5) 133*h*.
radiation effect on, (7) 201*a*.
reaction with Ta, (4) 114*h*.
single crystals, single phase, in O/U range 2 to 2.25, preparation, (5) 133*g*.
sintered, causes of high temperature substoichiometry in, (5) 131*i*.
sintered, containing yttrium oxide, P (1) 14*e*.
sintered, effect of organic additions on columnar grain growth of, (9) 281*i*.
sintered, thining to electron transparency by chemical polishing, (5) 134*i*.
sintering, effect of TiO_2 additions, (4) 108*g*.
sintering and grain growth, effect of vanadium oxide additions, (7) 201*c*.
sintering, initial phase, Dorn method in study of, (5) 151*e*.
sintering kinetics and powder properties, (8) 239*d*.
sintering rate in hydrogen, qualitative relations with observed microstructures, (8) 256*j*.
solubility in molten MgF_2, (4) 115*j*.
thermal conductivity at high temperature gradients, (10) 326*h*.
or UO_2-PuO_2 mixtures, dense sintered bodies, method of producing, P (7) 205*c*.
·xH_2O, magnetic resonance and susceptibility study, (6) 187*h*.
-yttria, solid solutions, oxidation kinetics, (4) 113*e*.
dispersed metallic, or uranium dicarbide, effect on mechanical properties of uranium monocarbide, (6) 172*i*.
diuranate, preparation, P (11) 340*c*.
electrical resistance and thermoelectric power during oxidation at 10^{-3} torr and 500° to 800°C, (4) 109*e*.
emission, from sintered UO_2 pellets, (7) 201*g*.
hexafluoride, processing, P (8) 241*c*.
hexafluoride, reactivity, (6) 188*g*.
high-temperature solubility in UC, (3) 86*c*.
ions, in UO_2, lattice and grain boundary diffusion of, (4) 112*i*.
metal, production from uranium oxide by fused salt electrolysis, (2) 45*f*.
metaphosphate, preparation and properties, (5) 157*d*.
monocarbide, and dicarbide, high-temperature immiscibility, (11) 353*a*.
pellets, pilot plant for, (11) 337*i*.
single crystals, oriented growth of oxidation products on, (10) 324*c*.
stoichiometric, production from uranium fluoride, P (1) 14*f*.
mononitride, heat capacity and thermodynamic properties from 5° to 350°K, (10) 327*b*.
mononitride and monocarbide, ignition in oxygen, (2) 44*e*.
monophosphide, melting point determination, (3) 83*b*.
nitride, equilibrium nitrogen pressures and thermodynamic properties, (2) 58*g*.
formation and stability relations, (5) 132*j*.
sulfide, and phosphide, chemical aspects as nuclear reactor fuel, (7) 200*c*.
oxide, crystal structure, effects of irradiation and fission of U, (6) 173*f*.
double, (10) 319*f*.
double, investigation, (3) 82*c*.
elasticity and anelasticity, at room temperature, hyperstoichiometric oxides, (5) 132*c*.

Uranium dioxide-Al_2O_3 (*continued*)
electric field diffusion of oxygen at 900° to 1000°C in, (9) 281*i*.
hypostoichiometric, vapor pressure as function of composition, (6) 190*e*.
melting, P (1) 13*f*.
modified, structure, high temperature and sintering behavior, (4) 116*c*.
oxygen self-diffusion, (7) 220*f*.
particle-size reduction, P (1) 13*d*.
particles, oxidation, thermogravimetric study, (4) 118*j*.
reduction, to UO_2, (5) 157*h*.
sols, P (7) 205*h*.
-plutonium monocarbide ceramics, (11) 338*a*.
pressure, over U−UO_2 system, (3) 79*j*.
pure, oxidation mechanism in carbon dioxide between 350° and 650°C, (3) 84*j*.
reactions, with platinide elements, (6) 188*f*.
recovery, processes, P (1) 14*e*.
recovery, from uranium-containing nuclear fuels, P (3) 69*h*.
samples, isotope analyses by alpha spectrometry, (1) 21*c*.
systems. See *Systems*.
tetrachloride, oxidation, (4) 113*h*.
tetrafluoride, producing, P (8) 241*c*.
and thorium dicarbides, limited solid solutions, (6) 187*a*.
thorium-, oxides, production, P (7) 205*a*.
trioxide, β and γ forms, phase transformations on dissociation of, (7) 220*a*.
gamma, enthalpy of reaction with fluoric acid, and enthalpy of formation, (9) 282*d*.
gamma, unit cell of, (4) 118*g*.
hydration, calorimetric determination of enthalpy of, (4) 106*j*.
(IV): I, uranium-oxygen bonds in products derived from hydrolysis of UCl_4, (4) 106*f*.
$(U_{1-x}Th_x)O_2$, magnetic susceptibility, (11) 354*c*.
$UCrO_4$, atomic parameters and magnetic structure, (5) 149*g*.
UO_{2-x}, UO_2, and UO_{2+x}, thermal conductivity, effect of irradiation at 60°C, (9) 281*h*.
UO_{2+x}, cubic, magnetic susceptibilities at high temperature, (11) 354*a*.
UO_{2+x} and U_3O_{8-z}, nonstoichiometric, equilibrium oxygen pressures over, at higher pressures, (4) 109*j*.
U_4O_9, stacking faults and antiphase boundaries in, (9) 286*f*.
U_3Si, martensitic transformation in, metallographic evidence for, (10) 323*h*.
-water assembly, measurements of material buckling of, (9) 267*i*.
+ water reaction: I, kinetics, products, and mechanism, (3) 88*i*.

Vacuum, devices, handbook of materials and techniques, B (4) 120*h*.
high, and low temperature, effect on strength of E-glass fibers, (7) 196*h*.
system, differentially pumped ultrahigh-, bakeable to 900°C, (5) 145*c*.
system, ultrahigh, for preparation and study of surface properties of CdS thin films, (5) 140*i*.

Vacuum tubes. See *Tubes*.

Valves, glass, for scientific purposes, P (5) 130*b*.
porcelain, mechanical means for preventing blowouts of, P (8) 242*c*.
use of ceramics in, B (4) 122*d*.

Vanadium, bronzes, magnetic and electrical properties, (1) 29*i*.
carbide, process, P (8) 241*g*.
carbides, thermal expansion, (5) 134*g*.
diboride, reaction with carbon, (5) 133*c*.
dioxide, coatings, applied to Al_2O_3 substrates, (4) 99*a*.
powder, Hall effect, (10) 321*f*.
resistance, pressure dependence of, (5) 157*f*.
single crystals, method for growing, P (7) 214*g*.
thin films, reactivity sputtered, (4) 115*b*.
V_2O_3 phase transitions and Clausius-Clapeyron equation, (4) 106*g*.
whisker, thermoelectric power, (10) 326*h*.
whisker, growth, (7) 217*i*.
fluoride, reactivity, (6) 188*g*.
higher carbide, phase transformation, (9) 285*i*.
oxide, additions, effect on sintering and grain growth of UO_2, (7) 201*c*.
catalyzed oxidations, P (11) 350*a*.
electric and magnetic properties, (10) 320*e*.
single crystals, grown by oxychloride decomposition, growth and electrical properties, (7) 217*h*.
pentoxide, NMR study, (11) 355*c*.
effects on formation of zircon, (5) 151*a*.
solid and liquid, structure and physical properties, (11) 357*e*.
in silicate rocks and minerals, determination with *N*-benzoyl-*o*-tolylhydroxylamine, (5) 145*d*.
silicide, with stress, pronounced change in low-temperature heat capacity of, (9) 285*h*.
structure, in soda-boric oxide glasses, (5) 129*c*.
systems. See *Systems*.
trioxide, antiferromagnetism of, observed by Moessbauer effect, (4) 106*d*.
Moessbauer effect study of, (10) 323*b*.
neutron diffraction data, (11) 354*i*.
values, selectively carbiding, P (9) 270*e*.

Vapor pressure, of Gd_2O_3 from 2350° to 2590°K, (1) 33*e*.
high temperature, studies of UO_2 by effusion method and thermodynamic interpretation, (7) 218*e*.
of hypostoichiometric urania as function of composition, (6) 190*e*.

Vapor pressure (*continued*)
of metal halides, $SnCl_2$-$ZnCl_2$ binary system, (4) 118*j*.
rate, of refractory compounds up to 3000°C, (1) 32*g*.
in system Al-Al_2O_3, studied by effusion and pressure compensation methods, (1) 33*e*.
Vaporization, high-temperature, of titanium monosulfide, (3) 81*d*.
high-temperature, of titanium oxides, (11) 351*c*.
high-temperature, of titanium oxides: I, vaporization characteristics of crystalline phases, (11) 353*b*.
kinetics, of ceramic oxides at temperatures around 2000°C, (1) 33*g*.
of lead zirconate-lead titanate materials: II, hot-pressed composition at near theoretical density, (8) 243*h*.
preferential, of carbon from HfC (3) 85*e*.
rate, of refractory compounds up to 3000°C, (1) 32*g*.
under vacuum of ceramic oxides at high temperatures, (6) 190*e*.
vacuum, of metallic and nonmetallic samples, electron-beam apparatus for, (10) 314*i*.
Vapors, coating rate, determination by X rays emitted from vapor, P (6) 181*d*.
high melting oxide, homogeneous condensation in plasma jet close to cold surface, (7) 218*e*.
high-temperature, characterization, B (3) 89*c*.
phase, for producing metal oxides, P (2) 57*b*.
production of pigmentary metal oxides, reduction in scale buildup in, P (10) 318*g*.
reaction between anhydrous aluminum, aluminum fluoride and boron oxide, (6) 190*e*.
reaction, for SiC coatings and crystal growth at high temperatures, (11) 353*d*.
water, in high-temperature ceramic processes, B (7) 226*g*.
Velocity, interfacial, effect on dynamic contact angles, (9) 276*c*.
Vermiculite, and asbestos mixtures and their cement mortars, thermal conductivity, (8) 240*d*.
hydrated, anisotropic diffusion in, (6) 183*g*.
Indian, cesium sorption properties, (7) 222*b*.
Vibration, anharmonic, in fluorite structures, (9) 279*i*.
compaction, of two-component systems of spherical powders, (1) 23*e*.
external modes, of small polyatomic ions isolated in alkali halides, (11) 352*i*.
frequency distributions, of NaCl, (8) 256*c*.
of OH ions in muscovite, (5) 150*i*.
optical modes, in ionic crystal slab including retardation: I, nonradiative region, (9) 285*d*.
packing, of spherical powders, (1) 23*c*.
"sift-mode" lattice, in perovskite-type ferroelectrics, single-oscillator model of, (4) 115*g*.
thermal, in BeO, (3) 68*g*.
ultrasonic, for shaping optical elements, P (11) 336*h*.
ultrasonic, transducer assembly for producing, P (11) 345*c*.
Viscometers, P (6) 181*c*.
capillary tube, correction for nonuniformity of bore, (1) 20*h*.
discussion, in Practical Emulsions, (9) 290*b*.
for non-Newtonian fluids, (9) 275*j*.
stainless steel coiled-capillary, steady-state laminar flow boundary conditions for, (1) 23*f*.
wide range portable, (11) 347*d*.
Viscometry, for study of structure of glasses of B_2O_3-Na_2O system, (1) 7*h*.
Viscosity, behavior, of $BiPO_4$ glasses, (6) 160*g*.
of B_2O_3, entropy interpretation, (4) 93*e*.
for control of particle size, P (4) 103*g*.
of copper ruby glass in and below striking range of temperature, (7) 197*i*.
of GeO_2, and binary germanates containing Li_2O, Na_2O, K_2O, and Rb_2O, (5) 128*d*.
of glass, automatic measurement, (10) 313*j*.
of liquid phase of portland cement clinker, effect of impurities of raw materials and alloying additives, (3) 62*e*.
of liquids containing spherical molecules or ions, (7) 223*b*.
measurement, of copper ruby glass by fiber elongation method, (2) 39*g*.
measurements in system silica-titanium oxide-potassium oxide, (7) 197*e*.
measuring process and apparatus, for molten glass, P (8) 236*c*.
of porcelain enamel frits, (9) 263*d*.
of silica with tungsten inclusions, (7) 204*c*.
tar, effect on properties of tarred dolomite-magnesite refractories, (9) 267*i*.
temperature variation of, of liquids, (3) 87*a*.
Voids, defects, in glass-epoxy structures, corona and microwave methods for detection, (7) 212*b*.
detection, in honeycombed ablative materials, microwave technique, (7) 212*d*.
Volatilization, of components of glasses containing lead oxide at high temperature, (8) 234*j*.
of components from zirconia ceramics, (9) 288*d*.
loss, of Na borosilicate ternary glasses, (8) 235*b*.
of rare earth oxides, (1) 31*f*.
Volume, molar, in LiF-ThF_4 system, (5) 155*a*.
Volumeter, for studying solid-gas reactions, (3) 76*b*.

Wallboard, catalyzed gypsum, and method of production, P (6) 165*i*.
fire resistant, P (7) 194*e*.
Wastes, highly radioactive, durability of glass for disposal of, (7) 196*f*.
industrial, disposal, B (8) 260*b*.
products, combustible, treatment and catalyst for, P (5) 149*c*.
radioactive, disposal, (3) 67*g*; P (7) 223*g*; B (8) 260*b*.
Wastes (*continued*)
radioactive, high level, thermite process for fixation of, (4) 101*h*.
Water. See also *Humidity; Moisture; Steam.*
/cement ratio, influence on hardening, structure, and properties of cement at reduced temperatures, (6) 165*c*.
/cement ratio, influence on physicomechanical properties of hardened cement steamed under accelerated conditions, (6) 165*d*.
chemistry, used in porcelain enamel industry, (9) 262*k*.
content, in BaO-P_2O_5 glasses, effect on electrical conduction and dielectric relaxation, (8) 231*j*.
diffusion phenomena, in drying of clays and bodies, (6) 172*a*.
effect on toughness of MgO crystals, (7) 217*f*.
/interlayer, in hydrated layer silicates, NMR study, (5) 156*a*.
magnetic treatment of, effect on coagulation of suspensions, (5) 136*h*.
pollutants, control in finishing industries, (11) 345*j*.
reaction with $3CaO \cdot Al_2O_3$ in presence of $CaSO_4 \cdot 2H_2O$, (10) 295*j*.
reaction with glass: III, (3) 64*f*.
systems. See *Systems*.
uranium +, reaction: I, kinetics, products, and mechanism, (3) 88*i*.
vapor, adsorption on silica-alumina treated with potassium chloride, (3) 78*g*.
effect on initial sintering of calcia, (2) 58*c*.
reaction with crystalline lithium hydride, kinetics, (3) 82*h*.
reaction with solid barium oxide, mass spectrometry, (5) 154*d*.
and vapor, diffusion into ceramic materials, (8) 241*j*.
Water glass. See *Sodium, silicate.*
Waves, elastic surface, in layered system of CdS on germanium, (11) 352*f*.
elastic surface, in quartz at 316 Mhz, (4) 109*a*.
high frequency elastic, in LiF, attenuation of, (8) 252*c*.
short electromagnetic, device for transmission, P (8) 244*h*.
Wear, resistance, of tantalum mononitride-titanium diboride, (8) 237*c*.
Weathering. See *Frost resistance.*
Weighing. See also *Balances; Thermogravimetry.*
device, with electronic computer, P (2) 53*h*.
glass containers, automatically, P (10) 300*f*.
hydrostatic, for high precision density determinations, (2) 54*g*.
weigher, batch, with respective dials for successive loads and total weight, P (3) 75*a*.
Welding, arc, flux, P (10) 296*f*.
electrical, method and apparatus, P (5) 141*c*.
electrodes. See *Electrodes*.
electroslag, method, P (2) 38*d*.
metal to glass, P (4) 94*f*.
wire, for electric arc welding of steel in protective gas atmosphere, P (10) 296*g*.
Wettability, of solid particle compacts, evaluation of indirect measuring methods, (1) 21*h*.
Wetting, of diamond and graphite by molten metals alloys: IV, influence of temperature on adhesion of metals inert to carbon, (7) 195*f*.
peri-, permanent, cause of additional corrosion at metal line of glass melts and upward drilling by gas bubbles, (8) 232*j*.
of sapphire by liquid aluminum, effect of nature of surfaces, (11) 352*b*.
of uranium carbide, (10) 327*g*.
Whiskers. See also *Crystals.*
Al_2O_3, structure and properties, (11) 339*j*.
α-Al_2O_3, sizing and mechanical testing, (5) 158*d*.
aluminum borate, synthesis, P (2) 48*c*.
crystallogenesis and physical properties, preparation of corundum trichites, (6) 172*f*.
MgO, ductile, (1) 28*c*.
MgO, growth by vapor-liquid-solid mechanism, (1) 29*b*.
pyrolytic graphite, production, P (7) 205*j*.
SiC, (4) 96*e*.
β-SiC, elastic modulus, (3) 80*a*.
silicon nitride, P (11) 340*g*.
status and applications: I, comparative survey of whiskers and mineral fibers; II, whisker-reinforced composite materials, (11) 338*d*.
tensile properties, testing apparatus, P (7) 213*b*.
VO_2 growth, (7) 217*i*.
VO_2, thermoelectric power, (10) 326*h*.
Whiteware. See also *Art and artware; Bodies, ceramic; Bone china; Dielectrics; Dinnerware; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile.*
articles, towing or smoothing, P (5) 137*e*.
bodies, alumina effects, (2) 48*f*.
cast, evaluation and selection of clays, (1) 15*j*.
function of quartz in, (4) 98*f*.
structure, (9) 217*f*.
X-ray measurement of strain in quartz particles of, (9) 271*e*.
ceramic, curved section, drilling counterbore in, (6) 175*i*.
control tests, by computer, (4) 98*e*.
control tests, effectiveness, (9) 270*j*.
costs, by cube, (2) 48*i*.
firing, single and double, (9) 271*f*.
flatware dimensions, (3) 70*a*.
industry, British Pottery Promotion Service, (7) 206*h*.
industry, current developments, B (3) 89*c*.
plant, for body preparation, in Westerwald, Germany, (1) 15*i*.
strength and elasticity: I, relation between flexural strength and elasticity, (1) 15*h*; II, effect of porosity and mullite content, (6) 175*j*.
Windows. See also *Glass.*
bakeable quartz-metal sealed, (2) 53*j*.
Wire, glass or ceramic covered, P (4) 95*d*.
high temperature resistant insulated, process of producing and coils made therefrom, P (2) 38*e*.
pyrolyzable enamel coated, comprising manganese and cobalt chelates, P (5) 126*d*.
superconducting, P (10) 310*c*.
Wollastonite, for low dielectric loss ceramics, (7) 206*a*.
Wustite, FeO_x, vacancy concentrations near p to n transition, (6) 190*c*.
$Fe_{1-y}O$, composition-oxygen partial pressure diagram, thermogravimetric determination, (5) 159*e*.
manganese-bearing sintered, nature: I, observation of thermal disintegration by microscopic and X-ray analysis, (9) 284*g*.
promoters for CO reduction of, (3) 77*j*.

Xanthophyllite, from type locality, re-examination, (4) 115*e*.
Xenon, migration and tripping in doped ThO_2, (10) 327*a*.
-133, release on postirradiation heating of UO_2-ThO_2-BeO compacts, (2) 45*j*.
oxide tetrafluoride, complexes, (5) 150*f*.
tetroxide, preparation and properties, (4) 119*b*.
X-rays, absorption, review, (10) 316*e*.
absorption and emission, (10) 316*e*.
analysis, apparatus for preparing samples for, P (9) 277*d*.
apparatus, automatic, for crystal Z-axis orientation determination and sorting, P (5) 146*j*.
chamber, high-temperature, using image furnace, (3) 75*j*.
diffraction, apparatus, automatic control system for, P (2) 55*c*.
camera, employing two curved crystal transmission type monochromators, P (7) 213*e*.
chambers, low temperature, (4) 103*a*.
for characterization of amorphous materials, (6) 180*f*.
comparison with electron probe microanalyzer for quantitative mineralogical analysis of carbonate sediments, (8) 248*d*.
data, accurate, general structure factor formalism for interpreting, (9) 282*f*.
for determination of crystallite size distribution, (3) 75*f*.
for determination of phases, application to cement industry, (6) 164*g*.
effects in irradiated BeO, (2) 44*h*.
high temperature, for study of dolomite refractories, (10) 303*d*.
intensities of high temperature (β) phase of beryllium oxide, (4) 119*c*.
mechanism in which monochromator diffracts X-ray beam in planes transverse to axis of specimen rotation, P (10) 316*h*.
observations on crystalline solids up to 300 kbars, (3) 88*a*.
of palladium-phosphorus system, (4) 119*a*.
powder patterns, standard, (9) 277*d*.
review, (10) 316*e*.
sample changer for oriented clay aggregates in, (8) 248*f*.
by vibrating quartz crystal, (5) 150*j*.
diffraction analysis, application to uranium ceramics: II, quantitative analysis of uranium carbides, (8) 247*i*.
clay mineral mounting techniques for, (8) 247*j*.
of clays and clay minerals, B (9) 289*b*.
collimated, of sections in standard camera, (10) 313*a*.
for identification of small crystals, (1) 23*a*.
for quantitative determination of cristobalite, (10) 315*j*.
diffraction study, on CdTe at high pressure, (8) 258*c*.
on cation distribution in $FeAl_2O_4$, (11) 354*g*.
of CoO, (7) 223*c*.
of formation mechanism of ferrites of spinel type, (10) 327*c*.
of irradiated BeO, (2) 46*c*.
of tungsten oxide phosphate glasses, (6) 169*i*.
of variation of lattice parameters and ratio for BeO at temperatures up to 2000°C (4) 119*d*.
diffractometers, single crystal, high temperature furnace for, (2) 54*i*.
diffractometers, specimens, sample cups and technique for sideward packing, (1) 23*a*.
emission, apparatus with means to measure, P (3) 76*c*.
emission, review, (10) 316*e*.
of hot-worked and annealed flint, (2) 60*a*.
fluorescence, analysis, local quantitative, methods, (10) 314*i*.
analysis, of silicate rocks using powdered samples dispersed in silica without fusion or pelletization, (10) 316*f*.
analysis of triple carbonates for electron tubes, (2) 50*d*.
method using ^{55}Fe radioactive source for determination of Ti, (11) 346*h*.
intensity, diffracted from elastically vibrating single-crystal plate, (2) 54*a*.
interference patterns, obtaining, P (10) 316*b*.
investigation, in PbO-ZnO-B_2O_3 oxide system, (3) 88*b*.
investigations, of phase transitions in ZrO_2 and rare-earth oxides, (1) 34*b*.
line broadening study, of explosively shocked MgO and α-Al_2O_3 powders, (8) 258*e*.

X-rays, fabric analysis (*continued*)
measurement of strain in quartz particles of whiteware bodies, (9) 271*e*.
phase analysis, high temperature, for study of uranium-oxygen system in range $UO_{2.00}$ to $UO_{2.67}$, (10) 325*e*.
phase analysis, quantitative, possible use for crystallized glass materials, (9) 285*f*.
photography. See *Photography*.
production, in bulk specimens, dependence on crystal orientation, (8) 248*a*.
spectral analysis, of silicate materials, (11) 346*i*.
spectral determination of chlorine in silica films, (10) 327*e*.
spectrometer. See *Spectrometers*.
strain analysis, of MgO crystallites derived from thermal decomposition of various Mg compounds, (3) 88*d*.
study, high-temperature, of system uranium-oxygen in range $UO_{2.00}$ to $UO_{2.40}$, (3) 81*e*.
of PbO-Nb_2O_5-TiO_2 system, (7) 223*a*.
of Nb_2Br_8 and $NbBr_{2.64}$, (10) 327*g*.
on solid solution systems based on $NaNbO_3$, (5) 150*j*.
of system ThO_2-CeO_2-Ce_2O_3, (4) 119*a*.
of tellurium-containing metal oxides of stype B_2TeO_6, (8) 256*d*.
of TiO_2, (4) 115*c*.
of zircon formation in system SiO_2-ZrO_2-V_2O_5, (3) 88*d*.
three-dimensional, (7) 213*a*.

Young's modulus. See *Elasticity*.

Ytterbium, alkoxides, P (3) 69*g*.
alkoxides, preparation and properties, (5) 157*e*.
magnetostriction, in YIG, (4) 98*j*.
trivalent, Raman transitions, in YGaG, (11) 352*e*.
Yb^{3+} ions, in CaF_2, orthorhombic ESR spectra, (11) 355*e*.
in garnets, crystal field for, (5) 150*i*.
in garnets, energy levels, (5) 152*d*.
$YbSb_2$, $ZrSi_2$ isotope, structure, (6) 189*i*.
Yb_4TiO_{11}, new composition in Yb_2O_3-TiO_2 equilibrium diagram, (7) 217*c*.
-ytterbium dihydride, dissociation pressures in, comparison with Ca-CaH_2, (8) 253*b*.

Yttria. See *Yttrium, oxide*.

Yttrium, alkoxides, P (3) 69*g*.
alkoxides, preparation and properties, (5) 157*e*.
fluoride and carbonate, formation and thermal dissociation, (10) 321*a*.
and gadolinium compounds, europium-activated, photoluminescent properties, (5) 139*g*.
group V and VI binary and ternary compounds, thermoelectric properties, (2) 50*j*.
hydroxide, crystal structure, (7) 218*g*.
magnesium silicate, with apatite structure, preparation and properties, (7) 220*e*.
oxide, crystal-field splitting of trivalent thulium and erbium J levels in, (7) 216*j*.
elastic moduli of $91Y_2O_3$ + $9ThO_2$, temperature dependence, (5) 159*e*.
energy levels and crystal-field splitting of Nd^{3+}, (7) 217*j*.
grain-boundary segregation in final-stage sintering, (1) 29*e*.
polycrystalline, Young's and shear moduli, porosity dependence of (10) 324*b*.
reaction with iron oxide, (9) 286*e*.
single crystals, Er^{3+} spectrum in, (5) 158*h*.
single crystals, rare earth doped, optical absorption and fluorescence intensities in, (10) 324*b*.
spectra and energy levels of Eu^{3+} in, (6) 188*j*.
transparent, ceramics, (1) 33*b*.
oxybromides, crystal structure, (4) 107*e*.
sulfates, basic, structural study, (4) 116*b*.
systems. See *Systems*.
-thallium oxide phosphor, Eu activated, (5) 152*h*.
trifluoride, enthalpy of formation, (11) 353*a*.
trifluoride, sublimation pressure, measured by mass spectrometry, (7) 219*h*.
vanadate, Nd^{3+}- and Eu^{3+}-doped, optical and laser properties, (4) 113*d*.
Y_2BeO_4, crystal structure, (6) 184*f*.
$YFeO_3$, parasitic ferromagnet, motion of single domain wall in, (3) 83*b*.

Zeolites, A, bodies, and preparation, P (11) 350*a*.
A, factors affecting formation, (10) 319*h*.
adsorbents, production in nodular form, P (6) 183*c*.
caustic-treated, P (6) 182*j*.
compositions, pelleted, P (10) 318*g*.
pelleted, with improved crushing strength, P (3) 78*a*.
crystalline, aluminosilicate, preparation in siliceous matrix, P (1) 25*g*.
particles, preparation, P (4) 105*c*.
preparing, P (6) 183*f*; P (10) 318*b*.
production of hydrogen ion exchanged form of, P (7) 215*a*.
ZK-21, P (3) 77*a*.
decationated Y, perturbation of OH groups in, by physically adsorbed gases, (7) 220*g*.
faujasite, crystalline, ion exchanging with nitrogenous bases, P (6) 183*c*.
producing, P (10) 318*g*.
synthetic, increasing thermal stability, P (6) 183*d*.
γ- and X-irradiated, ESR studies, (6) 185*j*.
ion exchanging crystalline, process, P (5) 148*j*.
and method for making improved, P (5) 149*d*.
particles, molecular sieve, P (3) 78*d*.
silver, of improved exchange capacity, preparation and use, P (8) 251*b*.
spherically shaped crystalline particles, preparation, P (9) 279*e*.
stability of metallic cations in, (11) 357*b*.

Zeolites, compositions (*continued*)
stabilized, and use for hydrocarbon conversions, P (3) 78*f*.
studies: I, synthesis of alkaline earth zeolites, (3) 88*g*; II, ion-exchange properties of synthetic, (4) 119*c*.
surface area, determination by physical adsorption and X-ray crystallography, (11) 357*g*.
synthetic, P (7) 215*f*.
contact masses, P (5) 149*b*.
growth of larger single crystals, (4) 117*c*.
trace ferromagnetism in, (3) 88*h*.
X, structural changes caused by ion exchange and temperature, (1) 32*f*.
surface OH groups on, (11) 357*a*.
synthetic, effective pore radii of ion-exchanged forms of, (1) 28*b*.
synthetic, kinetics and ion-exchange equilibrium, (1) 29*g*.
ZK-4 and ZK-5, synthesis and properties, (10) 319*i*,*j*.

Zinc, α-, silicate crystals, manganese-doped, ESR study, (11) 352*g*.
ammonium phosphate, granular, continuous multistep process for preparing, P (8) 250*i*.
cadmium sulfide, homogeneous mixed crystals, growth, (1) 29*g*.
chalcogenide, crystals, highly pure hexagonal, production by sublimation, P (4) 101*b*.
ferrite, chemically precipitated, cation distribution in, (11) 350*d*.
ferrites, study by Moessbauer effect of intermediate phases in formation of, (1) 32*e*.
-lithium manganites, electrical properties, (5) 138*d*.
logarithmic oxidation kinetics of, (4) 112*b*.
α-molybdate, diamagnetic, crystal structure, (11) 351*e*.
oxide, attenuation of 3 Ghz sound waves in, (11) 350*j*.
compositions, P (1) 26*d*.
crystals, hydrothermal growth with ammonium ion additives, P (3) 72*i*.
crystals, low carrier concentration, hydrothermal growth at high water and hydrogen pressures, (4) 111*a*.
electrical conductivity, effect of variations in concentration of atmospheric constituents on, (3) 71*e*.
EPR of oxygen on, (7) 217*g*.
EPR of photosensitive donors in, (10) 320*e*.
exciton spectrum, (9) 282*h*.
free-flowing dust-free granular, for glazes, enamels, and ceramic colors, (7) 206*g*.
irradiation effects in, (4) 112*d*.
modified by hydrogen sulfide, photoconductive properties, (5) 156*i*.
near-forward Raman scattering in, (10) 323*g*.
photoconductivity, study by electro-disposition method, (5) 158*f*.
pigments, molybdated, P (3) 78*f*.
powder layers, with adsorbed monolayer of long chain fatty acid, photoelectric properties, (11) 355*i*.
pyroelectricity, (11) 355*f*.
Raman effect in, (8) 256*j*.
reduction by carbon monoxide in presence of strontium oxide, (4) 115*e*.
single crystals, optical and electrical properties, (3) 84*f*.
single crystal, vapor reaction growth, (5) 159*h*.
sintering: I, densification and grain growth; II, density decrease and pore size during final stage of sintering, (10) 325*i*.
solubility of transition metal oxides in, (4) 116*b*.
thin films, spectral sensitization with organic dyes, (3) 72*e*.
phosphate, pure molten, application of rigid sphere model, (2) 57*d*.
selenide, annealing of radiation damage in, (11) 350*i*.
selenide:Mn, zero-phenon lines and phonon coupling, (11) 358*b*.
sulfide, crystals, photo-induced paramagnetic resonance of chromium in, (9) 285*c*.
cubic crystals, growing in molten salt solvent, P (6) 183*c*.
ESR of photosensitive Ga center in, (11) 352*b*.
fluorine-doped, ESR of center in, (5) 138*f*.
green-copper luminescence transition in, as elucidated by measurements of time-resolved spectrum, (10) 323*g*.
hexagonal, single crystal, polarization of green copper luminescence in, (3) 85*a*.
phosphors, radiation quenching of radioluminescence of, (3) 85*f*.
polytypes, optical band gap and birefringence of, (9) 285*a*.
preparation, P (1) 25*b*.
rare-earth-doped, electro- and photoluminescence, (4) 109*e*.
thin films, dc electroluminescence in, (8) 252*k*.
two-photon absorption in, (1) 17*g*.
valence-band bending to Fermi level and radiative recombination in, with liquid electrodes, (11) 358*c*.
systems. See *Systems*.
telluride, crystals, photoconductivity, (5) 156*j*.
titanates, enthalpy of formation, (3) 80*j*.
tungstate, crystals, ESR of Cu^{2+} ion in, (7) 217*g*.
electron spin resonance and electronic absorption spectra of Rh_{II} in, (6) 185*i*.
single crystals, spin-lattice of Rh(II) in, (10) 325*a*.
ZnSb, *p*-type, thermal and electronic transport properties, (8) 258*c*.
$Zn_2Cu(AsO_4)_2$, stranskiite, structure of, (9) 280*h*.

Zinc (*continued*)
$(Zn_{0.65}Mg_{0.35})_2SiO_4$, high-temperature mechanical properties, (5) 153*a*.
$ZnMn_2O_4$, linear antiferromagnetism in, (10) 323*a*.
$Zn_xHg_{1-x}Te$ crystals, grown from solution, (10) 308*j*.
$Zn_3P_2O_7$: Mn and $Zn_2P_2O_7$: Cu, crystallographic phases, ESR study, (5) 152*h*.
$ZnRh_2O_4$, single crystals, growth, (6) 186*b*.

Zircon. See also *Refractories; zirconium silicate*.
effects of progressive metamorphism on, (4) 116*c*.
ferromagnetism in, source, (1) 16*j*.
formation, effects of V_2O_5, (5) 151*a*.
formation in system SiO_2-ZrO_2-V_2O_5, X-ray study, (3) 88*d*.
growth and preferential doping, (10) 321*e*.
particle size analysis using Coulter counter, (10) 315*i*.
from quartzites of Dodguni area, Tumkur District, (8) 250*c*.
selective flotation, (1) 25*f*.

Zirconia. See *Zirconium, oxide*.

Zirconium, boride, alloys, with $MoSi_2$, oxidation resistance, (3) 67*c*.
borides, carbides, and oxides, diffusion rates in, (9) 280*h*.
and $MoSi_2$ alloys, preparation and determination of properties, (2) 45*g*.
porous parts, relations in sintering of, (11) 339*c*.
preparation, properties, and uses, (6) 174*g*.
slip casting, (2) 46*d*.
carbide, high-temperature heat contents, (3) 81*c*.
for high-temperature heaters, (5) 132*e*.
manufacture, P (5) 135*h*.
nonstoichiometric, rare-gas diffusion in, (10) 324*d*.
ceramics, properties, influence of degree of purity of ZrO_2 and stabilization method, (7) 202*c*.
diboride, grain growth during sintering, (8) 237*c*.
hot-pressing, with binder metals, effects of chromium and nickel addition, (11) 338*d*.
mechanism of shrinkage during sintering, (8) 238*h*.
preparation, (5) 133*j*.
reaction with carbon, (3) 85*j*.
dioxide, cubic, effect of irradiation on ionic mobility, (10) 322*d*.
degree of purity, influence on zirconium ceramics properties, (7) 202*c*.
porous fired, and method, P (10) 304*h*.
spalling resistance, effect of phase composition, (9) 267*g*.
dissolution, in HF-H_2SO_4, rotating disk study, (4) 115*j*.
effect on surface properties of liquid Ni at melt-gas and melt-solid Al_2O_3 interfaces, (2) 44*c*.
hydride, production, P (8) 241*a*.
-molybdenum nitride, (8) 258*f*.
nitride, containing excess nitrogen, defect structure and bonding, (6) 184*j*.
nitride, and NbN, superconductive material of, P (10) 311*e*.
oxide, amorphous hydrated, nature and thermal evolution, (7) 220*b*.
black, obtained by fusion in electron beam furnace, micrographic structure and oxidation behavior, (7) 203*g*.
cubic, influence of neutron irradiation on ionic mobility in, (10) 322*d*.
dielectric constant, (2) 58*a*.
flame-sprayed coating, for high temperature metal-working extrusion dies, (2) 37*k*.
Franck-Condon factors and *r* centroids for band systems of, (2) 58*i*.
high-pressure induced phase transition in, (11) 353*j*.
hot-pressing, (2) 44*c*.
limitations of cubic stabilization in, (11) 356*g*.
magnesia- and yttria-stabilized, stress relief mechanisms, (2) 59*g*.
pure, or compounds, modifications in structure by passage of dc at elevated temperatures, (1) 30*i*.
pure dense oxidized, fabrication of specimens from, (7) 201*i*.
pure, superplasticity, (1) 32*j*.
and silica mixture, production, P (1) 25*j*.
solid state reactions with SiO_2, Al_2O_3, MgO CaO, and Fe_2O_3, (7) 221*b*.
tetragonal, electrical conductivity studies, (10) 320*i*.
thin films, obtained by oxidation of Zr, electron microscopic observations, (4) 109*i*.
Ti-activated, preparation and luminescent properties, (7) 207*b*.
vibrational transition probabilities and *r* centroids of $A \rightarrow X$ bad system of, (2) 60*c*.
volatilization of CaO and Y_2O_3 solid solutions in, (9) 288*d*.
X-ray and spectrographic investigations of phase transitions in, (1) 34*b*.
yttria stabilized, manufacture, (3) 70*h*.
phosphate gels, effect of water content on sorption, (7) 218*e*.
polarography, (5) 145*i*.
separation, from hafnium, P (11) 349*j*.
silicate, solubility and crystallization in glazes during firing, (3) 70*b*.
sponge, nuclear grade, pilot-plant production from Indian zircon, (1) 11*j*.
surface boronation, (1) 4*c*.
systems. See *Systems*.
tetrahalides, production, P (2) 57*b*.
in zirconium-bearing sand and zirconium concentrates, determination by nondispersive X-ray fluorescence method, (4) 102*i*.
ZrW_2O_8, linear thermal expansion, (5) 154*j*.